Initial lexical fallback: Methodology and Evidence

CS781 Capstone – Krishna K Karthikeya G N

12 November 2026

Status. Post-run methodology reconstruction grounded in archived source and reports. This document is not an executed historical notebook.

Research question

Establish a no-neural retrieval floor before spending T4 time on adaptation. This is a retrieval baseline and fallback, not a Phase 1 neural architecture.

Architecture and mechanism

TF-IDF document features rank candidates by lexical similarity and emit seven IDs per query. The initial submission predates the later self-match correction.

Measured result

Scored submission	1039286
Codabench micro-F1@7	0.3680
Archived local metric	not independently reported after correction

The initial Codabench micro-F1@7 was 0.3680. Its exact submitted ZIP is not present in the inspected local archive, so the package does not invent or regenerate it as historical evidence.

Limitations and next check

The historical ZIP is missing locally; this package includes source and run evidence but no exact-byte prediction artifact. Local, pilot, and hidden metrics are deliberately kept distinct. A single scored run does not establish a causal architecture effect or statistical significance.

Source and reproducibility

Original source modules: phase7_run.py. SHA-256 hashes, the original report, and the prediction ZIP receipt are in the companion provenance file. The explanatory notebook was written after the historical run; original execution output is never implied. Reproduction requires authorized course data, the Phase 1 parent weights/tokenizer, and the dependencies in the archived source.

Documentation disclosure

AI assistance was used to organize the archived evidence and draft this explanatory document. All numerical claims above come from saved run records or the provided finished-submission screenshot; missing evidence is labelled as such.