B1 full-data reference

Phase 4 Court Judgment Prediction | source-audited documentation

Problem statement and data

Phase 4 Court Judgment Prediction predicts binary outcome 0/1 from legal case text. The preserved official inputs are Train/train.json, Train/dev.json and Test/test.json. Test labels are private. Original run records report 994 official dev labels and 1,517 test IDs; macro-F1 is the central metric.

Architecture and mechanics

B1 6-encoder/6-decoder original Phase 1 backbone; 256 tokens per chunk, 8 ordered chunks per case, overlap 0, uniform sampling. Original evidence head: token evidence, ordered chunk BiGRU, attention/mean document mix. Token representation uses a learned mixture of mean, attention and last content token; position enters before document aggregation. The final learned attention pools document states for two-class logits. Data flow: Legal case -> B1 6+6 backbone -> 256×8 windows -> Token evidence mix -> Original evidence head: token evidence, ordered chunk BiGRU, attention/mean document mix -> Attention pool -> Binary ZIP.

Training design and checkpoint selection

Staged B1 fine-tuning; document head mode reference. Original B1 study notebook lineage code/v1.ipynb through code/v4.ipynb; latest source snapshot code/source/b1_study/. Saved configs and terminal/run evidence are in evidence/.. Original B1 study notebook lineage code/v1.ipynb through code/v4.ipynb; latest source snapshot code/source/b1_study/. Saved configs and terminal/run evidence are in evidence/.

Exact configuration, training progress and compute

Head mode reference; 6 encoder blocks, no FFN expansion in this scored configuration; window policy uniform, 256 tokens per window, 8 windows, overlap 0. Backbone learning rate 1e-05, head learning rate 0.0003, accumulation 8, warmup updates 100, target maximum epochs 4. Latest recorded segment 4 in this package; selected step 12500, optimizer updates 14500, completed full epochs 3, seen training cases 115988. Selected checkpoint SHA-256 5dadedc58ce5ecc89b8abe80b80c24a6165e2abb60108a81ea637bb3b3de1396; peak GPU bytes 2163620352. The preserved lineage JSON traces the resumed optimizer/checkpoint state across segments; the ZIP is produced from a selected checkpoint, not an invented continuation.

Measured results

Version 4 run state complete; 14500 optimizer updates and 3 complete epochs, selected step 12500. Calibrated official 994-case dev macro-F1 0.604727 at threshold 0.211745; default 0.5 dev macro-F1 0.634498. Selected checkpoint SHA-256 5dadedc58ce5ecc89b8abe80b80c24a6165e2abb60108a81ea637bb3b3de1396; verified 1,517-ID ZIP SHA-256 fecc6fd3abe831f9156cf474dd5980a6edfc2c038eae4a84368d87c1b646be30. User-provided Codabench screenshot: 0.6145 (finished submission).

Evaluation mechanics

Official labeled dev cases 994; balanced class supports [497, 497]; selected-threshold confusion matrix [[220, 277], [104, 393]]; calibrated threshold 0.211745 and macro-F1 0.604727; default 0.5 macro-F1 0.634498. These are two evaluations of the same selected weights, with different binary decision thresholds. The 1,517-ID test prediction ZIP is a separate label-free artifact.

Prediction contract and verification

The original prediction ZIP contains one root-level prediction.json with 1,517 unique official test IDs and integer labels restricted to 0 and 1. This package checks the ZIP CRC and SHA-256 against the archived run/verification record. Full model checkpoint tensors remain outside GitHub; their downloaded backup receipts and hashes live in the local Phase 4 study archives.

Reproducibility and limits

A budget-paused run is not converged; the target was four epochs with checkpoint selection and train-only calibration. The v7 source also defines gated depth expansion and an upper FFN option, but the recorded configs for these exports keep encoder_depth=6 and expand_ffn=false; those unlaunched options have no reported score. Original checkpoint bytes were downloaded and verified in the local archive, but are omitted from GitHub. Reports and companion notebook were created after training; original scores come from copied artifacts. Model weights and course data are preserved locally, not uploaded to GitHub.