

TDM API Migration Guide

Upgrading from TDM 9.5 to TDM 10

Focus: Task-Related APIs

1. Overview

This document describes the API changes required when invoking TDM APIs after upgrading from TDM 9.5 to TDM 10. It focuses primarily on task-related endpoints.

2. Breaking Changes

The following changes require immediate code updates — existing callers will break without modification.

2.1 POST /task/{taskId}/forced/{forced}/startTask

Starts an execution of a TDM task. The entire request body has been redesigned in TDM 10: the ten individual v9.5 override fields are replaced by a single overrideParameters object containing named keys.

Request Body Structure

Field	Type	Notes
overrideParameters	object	Optional. A map of override keys and their values. All keys are optional — omit the body entirely for a plain default execution. See the full key reference below.

Field	Type	Notes
draftExecutionId	number	Optional. When provided, promotes an AI draft record (created via POST /task/{taskId}/aiDraftOverride) to a real execution instead of allocating a new execution ID.

overrideParameters Key Reference

All keys are optional. When a key is omitted, the value stored in the task definition is used.

Key	Description
BE_ID	Business Entity ID of the task.
ENTITY_LIST	Comma-separated list of entity IDs to process. When the task uses an Entity Clone selection method, only a single entity ID is allowed.
SOURCE_ENVIRONMENT_NAME	Override the source environment name.
TARGET_ENVIRONMENT_NAME	Override the target environment name.
TASK_GLOBALS	Map of Fabric Global variable names to their override values. If a Global's value is a JSON string, escape internal quotes with a backslash.
NO_OF_ENTITIES	Override the number of entities processed by the task. Applicable only when ENTITY_LIST is not set and the task selection method is not Entity List.
SELECTED_VERSION_TASK_EXE_ID	Task execution ID of the selected data version. Applicable to Data Versioning load tasks only.
DATAFLUX_RETENTION_PARAMS	Retention period of the extracted data version. Object with two fields: units (Hours, Days, or Weeks) and value (integer).
RESERVE_IND	Boolean (true or false). Set to true to reserve the task entities on the target environment.
RESERVE_RETENTION_PARAMS	Reservation period for the task entities. Object with two fields: units (Hours, Days, or Weeks) and value (integer).
EXECUTION_NOTE	Free-text note attached to the execution.
SELECTION_METHOD	Override the task selection method. Supported values: 'L' (entity list — requires ENTITY_LIST), 'ALL' (predefined entity list), 'R' (random — requires NO_OF_ENTITIES), 'C' (custom logic — requires NO_OF_ENTITIES; CUSTOM_LOGIC_FLOW and CUSTOM_LOGIC_LU_NAME must be present in the override or in the task definition).
PARAMETERS	JSON string overriding the task's filter or input parameters. For Custom Logic ('C'): {"inputs":

Key	Description
	[{"name": "...", "value": "..."}]. For Business Parameters ('P'/'PR'): the full parameter group JSON.
BP_QUERY	SQL WHERE clause string overriding the business parameter filter. Applicable only for selection methods 'P' (Parameters) or 'PR' (Parameters with Random selection).
GENERATE_DATA_PARAMS	Map of synthetic data generation parameter overrides. Each key is a parameter name; each value is an object with a "value" field. Applicable only when the selection method is 'GENERATE'.
CUSTOM_LOGIC_FLOW	Override the flow name used for a Custom Logic selection method.
CUSTOM_LOGIC_LU_NAME	Override the LU name used for a Custom Logic selection method.
LOGICAL_UNITS	List of per-LU override objects. Each entry must include lu_id and lu_name, and may optionally include max_no_of_workers, source_affinity, and target_affinity.
TABLE_FILTERS	List of reference table filter overrides. Each entry must include ref_table_name and a fields array. Each fields item must include field and may include condition and value.
PRE_EXECUTION_PROCESSES_PARAMS	List of pre-execution process parameter overrides. Each entry must include process_id and a parameter_overrides array of {name, value} objects.
POST_EXECUTION_PROCESSES_PARAMS	Same structure as PRE_EXECUTION_PROCESSES_PARAMS, applied to post-execution processes.

Request Body Example

```
POST /task/15/forced/false/startTask
{
  "overrideParameters": {
    "BE_ID": "2",
    "ENTITY_LIST": "1,2,4,9,8,11",
    "SOURCE_ENVIRONMENT_NAME": "SRC",
    "TARGET_ENVIRONMENT_NAME": "TAR",
    "TASK_GLOBALS": {
      "CUST_TYPE": "BUS",
      "Customer.SUB_TYPE": "XX"
    }
  }
}
```

```
,
"NO_OF_ENTITIES": 14,
"SELECTED_VERSION_TASK_EXE_ID": 2,
"DATAFLUX_RETENTION_PARAMS": {
  "units": "Days",
  "value": "10"
},
"RESERVE_IND": true,
"RESERVE_RETENTION_PARAMS": {
  "units": "Days",
  "value": "5"
},
"EXECUTION_NOTE": "Example Task",
"LOGICAL_UNITS": [
  {
    "lu_id": 1,
    "lu_name": "Customer",
    "max_no_of_workers": 5,
    "source_affinity": "DC1",
    "target_affinity": "DC2"
  }
],
"TABLE_FILTERS": [
  {
    "ref_table_name": "RefT",
    "interface_name": "RefInterface",
    "schema_name": "RefSchema",
    "fields": [
      { "field": "coll", "condition": "=", "value": "vall" }
    ]
  }
],
"PRE_EXECUTION_PROCESSES_PARAMS": [
  {
    "process_id": 1,
    "parameter_overrides": [
      { "name": "param1", "value": "v1" }
    ]
  }
],
"POST_EXECUTION_PROCESSES_PARAMS": [
  {
    "process_id": 2,
    "parameter_overrides": [
      { "name": "param1", "value": "v1" }
```

```

    ]
  }
]
}
}

```

Migration action:

- Update the API's request body.

2.3 PUT /environment/{envId}/envname/{envName}/global

The request body field `luName` was renamed to `lu_name` and the `environment_id` field was removed (the environment is now identified solely via the path parameters).

v9.5 Field	v10 Field	Change
<code>luName</code>	<code>lu_name</code>	Renamed (camelCase to snake_case)
<code>environment_id</code>	(removed)	No longer accepted in request body
<code>global_name</code>	<code>global_name</code>	Unchanged
<code>global_value</code>	<code>global_value</code>	Unchanged

Migration action:

- Rename `luName` to `lu_name` and remove `environment_id` from the request body.

2.4 POST /extractrefstats

The `type` field has been removed from the request body. Only `taskExecutionId` is accepted.

Migration action:

- No need to take an action. The API ignores the `type` field.

2.5 POST /businessentity/{beld}/bename/{beName}/preexecutionprocess and postexecutionprocess

Both endpoints now require the `lu_name` field in the request body.

v9.5 Fields	v10 Fields	Change
<code>process_name</code> , <code>execution_order</code> , <code>process_description</code>	<code>process_name</code> , <code>lu_name</code> , <code>execution_order</code> , <code>process_description</code>	<code>lu_name</code> added (Required)

Migration action:

- Add `lu_name` (required) to the request body for both pre- and post-execution process calls.

2.6 GET /preexecutionprocesses and GET /postexecutionprocesses (Removed)

These two endpoints have been removed and replaced by business-entity-scoped equivalents.

Removed Endpoint	Replacement
GET /preexecutionprocesses	GET /businessentity/{beld}/preexecutionprocesses
GET /postexecutionprocesses	GET /businessentity/{beld}/postexecutionprocesses

3. Modified Endpoints — Optional Changes

The following endpoints have new optional fields. Existing calls continue to work without changes.

3.1 POST /task and PUT /task/{taskId} — Changes in TDM 10

TDM 10 adds 7 new optional fields to both POST /task (Create Task) and PUT /task/{taskId} (Update Task).

Optional New Fields

Field	Type	Description	Default values
taskGroupIds	array of number	IDs of the task groups this task belongs to. Every task must belong to at least one. Create task groups first via POST /taskgroup.	The task will be attached to the General task group
task_override_fields	string (JSON)	JSON-encoded string defining which fields testers may override at run time. Omitting it causes a runtime error in most validation paths. See structure details below.	All task attributes are locked and cannot be edited by the task runner at execution time.
env_name	string	Target environment name (complements the existing environment_id).	Retrieved automatically based on the environment_id field.

Field	Type	Description	Default values
enable_sequence_report	boolean	Enable sequence-level reporting for the task.	true
statistics_report_flag	string	Controls statistics report generation (e.g. "ALL", "FAILED").	ALL
permissions	array	Users or groups permitted to execute this task. See structure below.	The task can be executed by all TDM users who are assigned to TDM environments with permission sets that allow task execution.
notes	array	Free-text notes to attach at create or update time. See structure below.	Empty

task_override_fields — Structure

Pass as a JSON-encoded string (not a JSON object). Each top-level key maps to an object with `field_connector` (internal field name) and `is_editable` (boolean — true lets a tester override it at run time). The API automatically mirrors `source_environment.is_editable` to `target_environment.is_editable`.

```
{
  "business_entity": { "field_connector": "be_name",
    "is_editable": false },
  "source_environment": { "field_connector": "source_env_name",
    "is_editable": false },
  "target_environment": { "field_connector": "environment_name",
    "is_editable": false },
  "task_globals": { "field_connector": "task_globals",
    "is_editable": false },
  "reservation_period": { "field_connector":
    "reservation_period", "is_editable": false },
  "retention_period": { "field_connector": "retention_period",
    "is_editable": false },
  "data_version_name": { "field_connector": "data_version_name",
    "is_editable": false },
  "selection_method": {
    "field_connector": "selection_method",
    "is_editable": false,
    "max_entities": { "is_editable": false },
    "entity_list": { "is_editable": false },
    "random": { "is_editable": false },
    "business_parameters": { "is_editable": false },
```

```
    "custom_logic":          { "is_editable": false, "can_add_params": {
"is_editable": false } }
  }
}
```

logicalUnits — override_fields (new field on each LU item)

A JSON string on each LU item specifying which LU-level parameters testers may override at run time:

```
{
  "source_affinity":  true,
  "target_affinity":  true,
  "max_no_of_workers": true
}
```

globals — is_editable (new field on each global item)

When true, the tester may override this global's value at run time:

```
{
  "lu_name":      "ALL",
  "global_name":  "MASK_FLAG",
  "global_value": "false",
  "is_editable": true
}
```

preExecutionProcesses / postExecutionProcesses — is_editable (new fields)

is_editable is now supported at the process level and within the parameters object:

```
{
  "process_id":      1,
  "process_name":    "preProcessName",
  "lu_name":         "luName1",
  "execution_order": 1,
  "is_editable":     true,
  "parameters": {
    "inputs": [ { "name": "param1", "value": "value1" } ],
    "is_editable": true
  }
}
```

permissions — array structure

Field	Type	Description
type	string	"ID" — specific user login. "GROUP" — user group name.
value	string	The user login name or group name.


```

"permissions": [
  { "type": "ID",      "value": "tester1" },
  { "type": "GROUP",  "value": "qa-team" }
]

```

notes — array structure

Field	Type	Description
note_title	string	Short title.
note_description	string	Full text of the note.
note_date	string	Date/time: YYYY-MM-DD HH:MM:SS

```

"notes": [
  {
    "note_title":      "Note 1",
    "note_description": "Some note",
    "note_date":       "2025-01-01 00:00:00"
  }
]

```

3.2 GET /task/{taskId} (New endpoint)

TDM 10 adds a dedicated GET endpoint to retrieve a single task by ID. In v9.5, callers had to use list endpoints and filter client-side.

3.3 PUT /task/{taskId}/direct — New Fields

New Field	Type	Required	Description
env_name	string	No	Environment name
enable_sequence_report	boolean	No	Enable sequence-level reporting
statistics_report_flag	string	No	Statistics report mode
editable_params	string	No	Comma-separated list of parameters testers can edit at execution time

3.4 GET /task/refsTable/{task_id}

The mode query parameter changed from required to optional. No code change is needed if callers already supply it.

3.5 POST /wsAddPermissionGroupMapping and PUT /wsUpdatePermissionGroupMapping

Both endpoints now accept the optional `can_create_tasks` boolean, which controls whether users in the permission group are allowed to create tasks.

3.6 Other Query Parameter Additions

Endpoint	New Parameter	Required	Description
GET /getActiveBusinessentities	source_environment_id	No	Filter by source environment
GET /getActiveBusinessentities	target_environment_id	No	Filter by target environment
GET /userEnvironments	taskId	No	Filter environments relevant to a specific task
GET /getDMPopParams	taskExecutionId	No	Scope DM population params to a specific execution

4. New Task-Related Endpoints in TDM 10

These new endpoints do not affect existing integrations but unlock new TDM 10 capabilities.

4.1 Task Groups

TDM 10 introduces task groups — named collections for organizing tasks. Every task must belong to at least one group.

Method	Endpoint	Description
GET	/taskgroup	Get all task groups visible to the connected user
POST	/taskgroup	Create a new task group. Required: task_group_name, task_group_desc.
PUT	/taskgroup/{task_group_id}	Update an existing task group
DELETE	/taskgroup	Delete a task group (task_group_id in request body)
POST	/assignTaskToTaskGroups	Assign a task to one or more groups. Required: taskId, task_group_id[].
DELETE	/deleteTaskFromTaskGroup	Remove a task from a task group

Method	Endpoint	Description
GET	/getTasksPerTaskGroup	Return tasks grouped by task group, filtered by user permission
GET	/getTasksForAssign	Return tasks available for assignment to a group
GET	/taskAvailableGroups/{task_id}	Return task groups available for a given task
PUT	/moveTasksToGroups	Move tasks between task groups

4.2 Task Favorites

Users can mark tasks and task groups as favorites. Favorites are shown first in search results and task lists.

Method	Endpoint	Description
POST	/markTaskFavorite	Mark a task as a favorite for the current user
DELETE	/unMarkTaskFavorite	Remove a task from favorites
POST	/markFavorite	Mark a task group as a favorite
DELETE	/unMarkFavorite	Remove a task group from favorites

4.3 Task Notes

Method	Endpoint	Description
GET	/task/{taskId}/notes	Return all notes for a task
POST	/task/{taskId}/notes	Add new notes. Required: taskId, notes (array).
PUT	/task/{taskId}/notes	Replace all notes. Deletes existing, inserts provided list.

4.5 Task Execution History

Returns executions filtered by scope. Required: scope. fromDate and toDate are required for History and All scopes (ISO 8601).

Method	Endpoint	Description
GET	/tasks/executions	Scope values: All, In-process, Future, History.

4.6 Task Creation and Execution Permissions

Method	Endpoint	Description
GET	/taskCreationPermission/canCreateTasks	Check if the current user is allowed to create tasks
GET	/task/fnGetPermissionsForTask	Return what a tester can/cannot do for a specific task configuration
GET	/taskExecutionPermission/getTaskExecution	Get execution permissions for a task
POST	/taskExecutionPermission/insertTaskExecution	Insert execution permission entries
POST	/taskExecutionPermission/updateTaskExecution	Replace execution permissions (delete then insert)

4.7 Task Search and Filter Helpers

Method	Endpoint	Description
POST	/search	Full-text and faceted search. Filters: text, taskTypes, sourceEnvironmentIds, targetEnvironmentIds, belds, selectionMethods, creator, isScheduled, dataType. All optional.
GET	/selectionMethods	Return valid selection method values for use as search filter inputs

4.8 Report Indicators

Method	Endpoint	Description
GET	/reportsIndicators	Return defaults for enable_sequence_report and statistics_report_flag
