

Protecting Sensitive Values using HashiCorp

Technote

Overview

1. Protecting sensitive values via the use of Project Advanced Settings config.ini override
2. Using HashiCorp Sensitive Values in the Connection UI

This document contains copyrighted work and proprietary information belonging to K2view. All intellectual property rights (including, without limitation, copyrights, trade secrets, trademarks, etc.) evidenced by or embodied in and/or attached, connected, or related to this document, as well as any information contained herein, are and shall be owned solely by K2view. K2view does not convey to you an interest in or to this document, the information contained herein, or its intellectual property rights, but only a personal, limited, fully revocable right to use the document solely for review purposes. Unless explicitly set forth otherwise, you may not reproduce by any means any document and/or copyright contained herein.

Information in this document is subject to change without notice. Corporate and individual names and data used in the examples herein are fictitious unless otherwise noted.

Copyright © 2025 K2view Ltd. / K2VIEW LLC. All rights reserved.

The following are trademarks of K2view: K2view logo, K2view's platform.

K2view reserves the right to update this list document from time to time.

Protecting Sensitive Values with Project Advanced Settings (config.ini Override)

You can use the **Project Advanced Settings** UI to configure **HashiCorp** `auth_token` and `secret_id` secret manager settings. When saved, these overrides in `config.ini` are **automatically encrypted**. Upon reopening the UI, the encrypted values will be displayed.

Additionally, when `auth_token` and `secret_id` parameters are saved to the server via the **K2Cloud Orchestration Manager**, Fabric encrypts them before storing them in the server's `config.ini` file. Once applied, Fabric reads and encrypts these values before saving them to the server. As such, these values are not persisted in plain-text.

Important: After modifying config overrides for secret managers, you must **restart Fabric** to apply the changes, implying you need to Pause and then Resume the space that is configured with these values.

Using HashiCorp Sensitive Values in the Connection UI

You can specify **HashiCorp** keys in the **Username** and **Password** fields of the UI. Additionally, secret manager values can be substituted directly in the connection string, such as the **Security Token** for the Salesforce interface.

The connection string format is as follows:

```
jdbc:k2view:sforce://login...;SecurityToken=${secretmanager:Secretname.Secretkey}
```

Therefore, the security token's value shown in the connection UI can be `${secretmanager:Secretname.Secretkey}`.

Implementation > Shared Objects > Interfaces > JDBC > SF_SandBox



Salesforce

Active: ☒

Test Connection

SF_SandBox

Connection Details

Host
login.salesforce.com

Port

Database

User
xxxxxxxxxx

Password

Connection String (JDBC URL) *

`jdbc:k2view:sforce://login.salesforce.com;RefreshSchema=true;SecurityToken= ${secretmanager:Secretname.Secretkey}`

Connection Pool Settings

Post Connection Commands

Connection Properties