Арестов Никита ИС223

1. Создал сеть



2. Конфигурация роутера0

```
Router>en
Router#conf t
Enter configuration commands, one per line. End with CNTL/2.
Router(config)#int fa0/0
Router(config-if)#in ad 192.168.10.1 255.255.255.0
Router(config-if)#no sh
Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up
```

3. Конфигурация DHCP

```
Router(config-if) #exit
Router(config) #ip dhop pool VOICE
Router(dhop-config) #network 192.168.10.0 255.255.255.0
Router(dhop-config) #default-router 192.168.10.1
Router(dhop-config) #exit
Router(dhop-config) #exit
Router(config) #telephony-service
Router(config) #telephony) #max-dn 5
Router(config-telephony) #max-ephones 5
Router(config-telephony) #pource-address 192.168.10.1 port 2000
Router(config-telephony) #auto assign 1 to 5
Router(config-telephony) #exit
```

4. Конфигурация свитч

```
Switch>en
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#int range fa0/1-6
Switch(config-if-range)#switchport mode access
Switch(config-if-range)#switchport voice vlan 1
Switch(config-if-range)#
```

5. Задал номер телефона

```
Router>en
Router#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#ephone-dn 1
Router(config-ephone-dn)#%LINK-3-UPDOWN: Interface ephone_dsp DN 1.1, changed state to up
```

6. Попытался дозвониться с одного телефона на другой