



```

Router(config-ephone-dn)#number 101
Router(config-ephone-dn)#
%IPPHONE-6-REGISTER: ephone-1 IP:10.3.0.2 Socket:2 DeviceType:Phone has registered.

Router(config-ephone-dn)#ephone-dn 2
Router(config-ephone-dn)%LINK-3-UPDOWN: Interface ephone_dsp DN 2.1, changed state to up

Router(config-ephone-dn)#number 102
Router(config-ephone-dn)#ephone-dn 3
Router(config-ephone-dn)%LINK-3-UPDOWN: Interface ephone_dsp DN 3.1, changed state to up

Router(config-ephone-dn)#number 103
Router(config-ephone-dn)#ephone-dn 4
Router(config-ephone-dn)%LINK-3-UPDOWN: Interface ephone_dsp DN 4.1, changed state to up

Router(config-ephone-dn)#number 104
Router(config-ephone-dn)#ephone-dn 5
Router(config-ephone-dn)%LINK-3-UPDOWN: Interface ephone_dsp DN 5.1, changed state to up
ephone-dn 4
Router(config-ephone-dn)#ephone-dn 5
Router(config-ephone-dn)#
Router(config-ephone-dn)#number 105
Router(config-ephone-dn)#ephone-dn 6
Router(config-ephone-dn)%LINK-3-UPDOWN: Interface ephone_dsp DN 6.1, changed state to up

Router(config-ephone-dn)#number 106
Router(config-ephone-dn)#exit
Router(config)#ephone 1
Router(config-ephone)#mac-address 0009.7C34.3C01
ephone slot is already registered with 00D0.FFCB.0101
Cannot change MAC address.

Router(config-ephone)#type ata
Router(config-ephone)#button 1:1
Dn already assigned.
Router(config-ephone)#ephone 2
Router(config-ephone)#mac-address 0009.7C09.D862
Router(config-ephone)#type 7960
Router(config-ephone)#1:2
^
% Invalid input detected at '^' marker.

Router(config-ephone)#button 1:2
Router(config-ephone)#ephone 3
Router(config-ephone)#mac-address 0006.2A28.7710
Router(config-ephone)#type CIPC
Router(config-ephone)#button 1:3
Router(config-ephone)#ephone 4
Router(config-ephone)#mac-address 0006.2A28.7711
Router(config-ephone)#type CIPC
Router(config-ephone)#button 1:4
Router(config-ephone)#ephone 5
Router(config-ephone)#mac-address 0006.2A28.7712
Router(config-ephone)#type CIPC
Router(config-ephone)#button 1:5
Router(config-ephone)#ephone 6
Router(config-ephone)#mac-address 0006.2A28.7713
Router(config-ephone)#type CIPC
Router(config-ephone)#button 1:6
Router(config-ephone)#|

```