







典型应用电路图: Vout= 5V/2A

TX4130L:
VFB: min=369 typ=380 max=391 mV
VCS: min=145 typ=150 max=155 mV

R1 = R3
R2 = R4
Vout= VFB * (R2+R1)/R1
Iout=VCS/R7 (R7=0.06R -> I_o=2.6A)
Frequency: Fixed 140kHz
Inductance: 33uH-100uH

ON/OFF Voltage Filters



https://datasheet.lcsc.com/lcsc/1912231403_XDS-TX4130L_C448635.pdf
<https://www.pwchip.com/en/product/PW2902-174.html>

Jens Overby

Sheet: /driver/
File: driver.kicad_sch



Title: FOC KING

Size: A4 Date:
KiCad E.D.A. kicad 6.0.2+dfsg-1

Rev:
Id: 6/4

External booster drive:
https://www.infineon.com/dgdl/Infineon-External_booster_for_Driver_IC-ApplicationNotes-v01_06-EN.pdf?fileId=5546d46146d18cb40146ffb0461d3894

PNP turn-off circuit:
<https://www.youtube.com/watch?v=6pp1jj2oDvo>





Calculate cut-off freq of low pass filter, pg 3:
https://www.st.com/resource/en/application_note/an4304-how-to-filter-the-input-of-a-highside-current-sensing-stmicroelectronics.pdf


Current sensing:
https://www.ti.com/lit/eb/slyy154a/slyy154a.pdf?ts=1678787132262&ref_url=https%253A%252F%252Fwww.startpage.com%252Fpg%204%2Cpg%2015

Jens Overby	
Sheet: /power/	
File: power.kicad_sch	
Title: FOC KING	
Size: A4	Date:
KiCad E.D.A. kicad 6.0.2+dfsg-1	Rev:
	Id: 7/4

TIM3_CH4 is configured for pin PB1 pin 27
according to stm32f405 datasheet
<https://www.st.com/en/microcontrollers--microprocessors/stm32f405rg.html>



Changes:
Xtal caps from 18pF to 12pF
Separate the two LEDs from the single resistor
CAN spike protection
RC between GND and pb12 to stop false trips
PC12->PA15 to drive LED
Increased functionality of several header pins



Jens Overby	
Sheet: /mcu/	
File: mcu.kicad_sch	
Title: FOC KING	
Size: A4	Date:
KiCad E.D.A. kicad 6.0.2+dfsg-1	
Rev:	
Id: 9/4	