



Laptop0

Physical Config Desktop Programming Attributes

Command Prompt

```
Cisco Packet Tracer PC Command Line 1.0
C:\>ping 192.168.100.103

Pinging 192.168.100.103 with 32 bytes of data:

Reply from 192.168.100.103: bytes=32 time<1ms TTL=128
Reply from 192.168.100.103: bytes=32 time<1ms TTL=128
Reply from 192.168.100.103: bytes=32 time<1ms TTL=128
Reply from 192.168.100.103: bytes=32 time<1ms TTL=128

Ping statistics for 192.168.100.103:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>ping 192.168.200.100

Pinging 192.168.200.100 with 32 bytes of data:

Request timed out.
Reply from 192.168.200.100: bytes=32 time=1ms TTL=127
Reply from 192.168.200.100: bytes=32 time<1ms TTL=127
Reply from 192.168.200.100: bytes=32 time<1ms TTL=127

Ping statistics for 192.168.200.100:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 1ms, Average = 0ms

C:\>ping 192.168.200.100

Pinging 192.168.200.100 with 32 bytes of data:

Reply from 192.168.200.100: bytes=32 time<1ms TTL=127
Reply from 192.168.200.100: bytes=32 time<1ms TTL=127
Reply from 192.168.200.100: bytes=32 time<1ms TTL=127
Reply from 192.168.200.100: bytes=32 time<1ms TTL=127

Ping statistics for 192.168.200.100:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>
```

☐ Top

00:47:30

alttime Simulation

Edit Delete