

```
(root@kali)-[/home/kali]
# nmap -sT 192.168.32.101 -p 1-1024
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-04-17 11:34 EDT
Nmap scan report for 192.168.32.101
Host is up (0.0018s latency).
Not shown: 1012 closed tcp ports (conn-refused)
PORT      STATE SERVICE
21/tcp    open  ftp
22/tcp    open  ssh
23/tcp    open  telnet
25/tcp    open  smtp
53/tcp    open  domain
80/tcp    open  http
111/tcp   open  rpcbind
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
512/tcp   open  exec
513/tcp   open  login
514/tcp   open  shell
MAC Address: 08:00:27:EA:75:E7 (Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 13.44 seconds
```

```
(root@kali)-[/home/kali]
```

No.	Time	Source	Destination	Protocol	Length	Info
55	13.083841172	192.168.32.100	192.168.32.101	TCP	76	39008 → 21 [SYN] Seq=0 Win=32120 Len=0 MSS=146...
57	13.084319515	192.168.32.101	192.168.32.100	TCP	76	21 → 39008 [SYN, ACK] Seq=0 Ack=1 Win=5792 Len...
58	13.084372673	192.168.32.100	192.168.32.101	TCP	68	39008 → 21 [ACK] Seq=1 Ack=1 Win=32128 Len=0 T...
90	13.090172592	192.168.32.100	192.168.32.101	TCP	68	39008 → 21 [RST, ACK] Seq=1 Ack=1 Win=32128 Le...

```
↳ Frame 58: 68 bytes on wire (544 bits), 68 bytes captured (544 bits) on interface any, id 0
↳ Linux cooked capture v1
↳ Internet Protocol Version 4, Src: 192.168.32.100, Dst: 192.168.32.101
↳ Transmission Control Protocol, Src Port: 39008, Dst Port: 21, Seq: 1, Ack: 1, Len: 0
  Source Port: 39008
  Destination Port: 21
  [Stream index: 15]
  ↳ [Conversation completeness: Complete, NO_DATA (39)]
    ...1. .... = RST: Present
    ...0 .... = FIN: Absent
    .... 0... = Data: Absent
    .... .1.. = ACK: Present
    .... ..1. = SYN-ACK: Present
    .... ...1 = SYN: Present
  [Completeness Flags: R..ASS]
  [TCP Segment Len: 0]
  Sequence Number: 1 (relative sequence number)
  Sequence Number (raw): 1827403678
  [Next Sequence Number: 1 (relative sequence number)]
  Acknowledgment Number: 1 (relative ack number)
  Acknowledgment number (raw): 3077969821
  1000 .... = Header Length: 32 bytes (8)
  ↳ Flags: 0x010 (ACK)
    000. .... = Reserved: Not set
    ...0 .... = Accurate ECN: Not set
```