INT 最終レポート

科目名　INT

学生番号　12345678

所属　SS
AAA BBB 1年

氏名　k5-mot

提出日　2021/8/30

提出期限　2021/8/31

目次

図目次

表目次

コード目次

1 Intro

Intro

2 Samples

AAAAA AAAAA

2.1 Itemize

- Python
- Java
- Ruby

2.2 Enumerate

1. Python
2. Java
3. Ruby

2.3 Description

Python Python
Java Java
Ruby Ruby

2.4 Itembox

Myouji

スズキ
斎藤

2.5 Multicol1

Myouji

スズキ
斎藤

Namae

イチロー
ジロー

2.6 Multicol2

AAAAA BBBBB CCCCC DDDDD EEEEE FFFFF GGGGG
EEEEE FFFFF GGGGG AAAAA BBBBB CCCCC DDDDD
AAAAA BBBBB CCCCC DDDDD EEEEE FFFFF GGGGG

2.7 Figure

- 世阿弥 (図 1)

図 1　世阿弥

2.8 Table

- 九州 (表 1)

表 1　九州

都道府県	人口 (人)	面積 (km^2)	域内総生産 (円)
福岡	5,108,038	4847.32	18,084,000,000,000
佐賀	807,203	2439.67	2,093,500,000,000
長崎	1,305,650	4105.88	4,037,900,000,000
熊本	1,732,644	7267.93	5,070,800,000,000
大分	1,121,589	5099.65	4,047,300,000,000
宮崎	1,061,032	6794.78	3,056,000,000,000
鹿児島	1,586,435	9044.66	5,035,700,000,000

2.9　Equation

$$\frac{\partial u\left(x,y,t\right)}{\partial t} = D\left(\frac{\partial^2 u\left(x,y,t\right)}{\partial x^2} + \frac{\partial^2 u\left(x,y,t\right)}{\partial y^2}\right) \tag{2.9.1}$$

$$\begin{cases} 7x + 2y = -5 \\ 2x + 5y = 8 \end{cases} \tag{2.9.2}$$

2.10　Code

- C 言語 (コード 1)

コード 1　C 言語

```c
#include <stdio.h>
int main(int argc, char* argv[])
{
  // 日本語
  printf("Hello␣world!");
}
```

2.11　Input Code

- Python (コード 2)

コード 2　Python

```python
import sys


def is_int(s):
```

```
  try:
      int(s)
  except:
      return False
  return True


def main(argv=sys.argv):
  print("ARGC: " + str(len(argv)))
  print("ARGV: ", end="")
  # First loop
  itr = iter(argv)
  last = next(itr)
  # 2 ~ (n - 1) loop
  for arg in itr:
    print(last, end=", ")
    last = arg
  # Last loop
  print(last)
  if is_int(last):
    if int(last) == 1:
      return 1
  return 0


if __name__ == "__main__":
    sys.exit(main())
```

2.12 Bibliography

- VGG [1]
- ResNet [2]
- SSD [3]
- Image Captioning [4]
- U-Net [5]
- Mask R-CNN [6]
- Clique Net [7]

参考文献

[1] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

[2] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

[3] Wei Liu, Dragomir Anguelov, Dumitru Erhan, Christian Szegedy, Scott Reed, Cheng-Yang Fu, and Alexander C Berg. Ssd: Single shot multibox detector. In *European conference on computer vision*, pp. 21–37. Springer, 2016.

[4] Kelvin Xu, Jimmy Ba, Ryan Kiros, Kyunghyun Cho, Aaron Courville, Ruslan Salakhudinov, Rich Zemel, and Yoshua Bengio. Show, attend and tell: Neural image caption generation with visual attention. In *International conference on machine learning*, pp. 2048–2057. PMLR, 2015.

[5] Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pp. 234–241. Springer, 2015.

[6] Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask r-cnn. In *Proceedings of the IEEE international conference on computer vision*, pp. 2961–2969, 2017.

[7] Yibo Yang, Zhisheng Zhong, Tiancheng Shen, and Zhouchen Lin. Convolutional neural networks with alternately updated clique. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2413–2422, 2018.