

Staged Training Method to ternarize neural network weights

Kenji Ogura

1 Abstract

I propose the staged training method (STM) for ternary weights network. I show mAP performance of full ternarized weights network against full precision network. Ternarization method is referred to related work[2] and training algorithm is referred to related work[3]. Proposed STM expands the method in related work[1]. I use VOC dataset as estimation dataset. Full ternarized yolov2 with STM perform 73.82% mAP against full precision's 76.85% mAP 3.0% drops. Full ternarized yolov3 with STM perform 71.26% mAP against full precision's 75.54% mAP 4.3% drops. The result denotes that full ternary weights network is useful for small computing device.

2 Introduction

For small device or Embedded systems without GPU, realtime object detection task via neural networks should be worked. I was inspired below papers,

- Training a Binary Weight Object Detector by Knowledge Transfer for Autonomous Driving[1]
- Ternary weight networks[2]
- XNOR-Net: ImageNet Classification Using Binary Convolutional Neural Networks[3]

Generally the inference task using full ternary weights -1,0,+1 is considered as low accuracy than full precision weights. But for mobile device such as raspberryPI small weights will be efficient one of choices. Some quantization methods for model weights are proposed now such as FP16, bfloat, fixed point 16bits, 8bit, ternary 2bits and XNOR 1bit too. I consider that re-training after quantization

of weights is needed. In this paper I propose Staged Training Method (STM) for full ternary weights network and show the result as mAP.

3 Staged training method

In this paper I propose the staged training for yolov2-voc.cfg, yolov3-voc.cfg on Darknet website[4]. You can get full ternarized weights within 3 points accuracy drops for yolov2, within 4.5 points accuracy drops for yolov3 using this method. 2bits ternary weights representation may be x16 smaller than 32bit floating point.

STM generates Ternarized weights for yolov2-voc, yolov3-voc. This method splits a training step into 4 stages. Staging Plan is below,

- Stage-0 : few layers without around of detector are ternarized (M0)
- Stage-1 : 40% of all layers are ternarized (M1)
- Stage-2 : 90% of all layers are ternarized (M2)
- Stage-3 : full ternarized (M3)

Each stage imports weights from previous stage, such as stage-2 weights from stage-1. But stage-0 (M0) imports usual full precision weights. Figure.1 shows staging for yolov2-voc.cfg into 4 training stages, and Figure.2 for yolov3-voc.cfg. On each figures 'F' denote full precision weights and 'T' denotes ternarized weights. To estimate this staged training method I implement ternary keyword for each convolution layer in cfg file like 'ternary=1' and I also support ternarizing weights function and ternarized weights memory area in darknet framework. To avoid local minimum problem via training ternarized model I split training into some steps.

no	layer	filters	size	input -> output	M0	M1	M2	M3
0	conv	32	3x3/1	416x416x3->416x416x32	F	F	F	T
1	max	-	2x2/2	416x416x32->208x208x32				
2	conv	64	3x3/1	208x208x32->208x208x64	F	F	T	T
3	max	-	2x2/2	208x208x64->104x104x64				
4	conv	128	3x3/1	104x104x64->104x104x128	F	F	T	T
5	conv	64	1x1/1	104x104x128->104x104x64	F	F	T	T
6	conv	128	3x3/1	104x104x64->104x104x128	F	F	T	T
7	max	-	2x2/2	104x104x128->52x52x128				
8	conv	256	3x3/1	52x52x128->52x52x256	F	F	T	T
9	conv	128	1x1/1	52x52x256->52x52x128	F	F	T	T
10	conv	256	3x3/1	52x52x128->52x52x256	F	F	T	T
11	max	-	2x2/2	52x52x256->26x26x256				
12	conv	512	3x3/1	26x26x256->26x26x512	F	T	T	T
13	conv	256	1x1/1	26x26x512->26x26x256	F	T	T	T
14	conv	512	3x3/1	26x26x256->26x26x512	F	T	T	T
15	conv	256	1x1/1	26x26x512->26x26x256	F	T	T	T
16	conv	512	3x3/1	26x26x256->26x26x512	F	T	T	T
17	max	-	2x2/2	26x26x512->13x13x512				
18	conv	1024	3x3/1	13x13x512->13x13x1024	F	T	T	T
19	conv	512	1x1/1	13x13x1024->13x13x512	F	T	T	T
20	conv	1024	3x3/1	13x13x512->13x13x1024	F	T	T	T
21	conv	512	1x1/1	13x13x1024->13x13x512	F	T	T	T
22	conv	1024	3x3/1	13x13x512->13x13x1024	F	T	T	T
23	conv	1024	3x3/1	13x13x1024->13x13x1024	T	T	T	T
24	conv	1024	3x3/1	13x13x1024->13x13x1024	T	T	T	T
25	route	16	-	-				
26	conv	64	1x1/1	26x26x512->26x26x64	T	T	T	T
27	reorg/2			26x26x64->13x13x256				
28	route	27	24	-				
29	conv	1024	3x3/1	13x13x1280->13x13x1024	T	T	T	T
30	conv	125	1x1/1	13x13x1024->13x13x125	F	F	F	T
31	detection	-	-	-				

Figure 1: Staging for yolov2-voc.cfg

no	layer	filters	size	input->output	M0	M1	M2	M3
0	conv	32	3x3/1	416x416x3->416x416x32	T	T	T	T
-	-	-	-	-	T	T	T	T
79	conv	512	1x1/1	13x13x1024->13x13x512	T	T	T	T
80	conv	1024	3x3/1	13x13x512->13x13x1024	F	F	F	T
81	conv	75	1x1/1	13x13x1024->13x13x75	F	F	F	T
82	yolo	-	-	-				
83	route	79	-	-				
84	conv	256	1x1/1	13x13x512->13x13x256	F	T	T	T
85	upsample			2x13x13x256->26x26x256				
86	route	85	61	-	F	T	T	T
87	conv	256	1x1/1	26x26x768->26x26x256	F	T	T	T
88	conv	512	3x3/1	26x26x256->26x26x512	F	T	T	T
89	conv	256	1x1/1	26x26x512->26x26x256	F	T	T	T
90	conv	512	3x3/1	26x26x256->26x26x512	F	T	T	T
91	conv	256	1x1/1	26x26x512->26x26x256	F	T	T	T
92	conv	512	3x3/1	26x26x256->26x26x512	F	F	F	T
93	conv	75	1x1/1	26x26x512->26x26x75	F	F	F	T
94	yolo	-	-	-				
95	route	91	-	-				
96	conv	128	1x1/1	26x26x256->26x26x128	F	T	T	T
97	upsample	F		2x26x26x128->52x52x128				
98	route	97	36	-				
99	conv	128	1x1/1	52x52x384->52x52x128	F	F	T	T
100	conv	256	3x3/1	52x52x128->52x52x256	F	F	T	T
101	conv	128	1x1/1	52x52x256->52x52x128	F	F	T	T
102	conv	256	3x3/1	52x52x128->52x52x256	F	F	T	T
103	conv	128	1x1/1	52x52x256->52x52x128	F	F	T	T
104	conv	256	3x3/1	52x52x128->52x52x256	F	F	F	T
105	conv	75	1x1/1	52x52x256->52x52x75	F	F	F	T
106	yolo	-	-	-				

Figure 2: Staging for yolov3-voc.cfg

I trained yolov2-voc.cfg on 4 jobs, and checked each loss curves on Excell graph. And I use AlexeyAB[5] darknet to get mAP of experiments.

4 Result of Training

Tables denote the result of my staged training. VOC 2012, 2007 Dataset is used with training and VOC 2007 for estimation of mAP.

Stage	mAP	IOU	comments
-	76.85	54.67	official Weights
M0	77.09	57.04	-
M1	76.44	56.18	-
M2	75.06	57.71	-
M3	73.82	54.90	full ternary

Table 1: result regard to yolov2

In Table.1 Iteration 41000(2000/class), steps x0.1 80% 90%, lr=0.001 at all stages

Stage	mAP	IOU	comments
-	75.54	62.78	FT from darknet53.conv.75
M0	75.02	63.04	-
M1	73.69	63.75	-
M2	73.76	63.54	-
M3	71.26	61.61	full ternary

Table 2: result regard to yolov3

In Table.2 Iteration 100400(5000/class), steps x0.1 80% 90%, lr=0.001 at M0 and M1 Iteration 60400(3000/class), steps x0.1 80% 90%, lr=0.001 at M2 and M3.

5 Conclusion

If your applications using object detection task requires speed but not accuracy you can use full ternary weights network. To get efficient ternary weights you can use staged training method in this paper. Ternary weights is x16 smaller than fp32 representation. Full ternary weights network performs accuracy

within 4.5% mAP drops with yolov2 or yolov3 network on darknet framework.

References

- [1] Jiaolong Xu, Peng Wang, Heng Yang† and Antonio et.al. "Training a Binary Weight Object Detector by Knowledge Transfer for Autonomous Driving" <https://arxiv.org/pdf/1804.06332.pdf>
- [2] Fengfu Li and Bo Zhang, Bin Liu "Ternary weight networks" <https://arxiv.org/pdf/1605.04711.pdf>
- [3] ohammad Rastegari, Vicente Ordonez, Joseph Redmon, Ali Farhadi Allen Institute for AI, University of Washington "XNOR-Net: ImageNet Classification Using Binary Convolutional Neural Networks" <https://arxiv.org/pdf/1603.05279.pdf>
- [4] <https://github.com/pjreddie/darknet>
- [5] <https://github.com/AlexeyAB/darknet>