Lab 06

- **Implement SQL Operators: Demonstrate the use of different types of operators in SQL with examples Special Operators, and Set Operations(UNION)**

```
SELECT 'Special SQL Operators' AS Operations;
SELECT * FROM Product;

SELECT ProductName, Price
FROM Product
WHERE Price BETWEEN 1000 AND 30000;

SELECT ProductName, Price
FROM Product
WHERE ProductName IN ('Laptop', 'Mobile');

SELECT ProductName, Price
FROM Product
WHERE ProductName LIKE 'M%';

SELECT ProductName, Price, Discount
FROM Product
WHERE Discount IS NULL;
```

```
41  SELECT 'Special SQL Operators' AS Operations;
42  SELECT * FROM Product;
43
44  SELECT ProductName, Price
45  FROM Product
46  WHERE Price BETWEEN 1000 AND 30000;
47
48  SELECT ProductName, Price
49  FROM Product
50  WHERE ProductName IN ('Laptop', 'Mobile');
51
52  SELECT ProductName, Price
53  FROM Product
54  WHERE ProductName LIKE 'M%';
55
56  SELECT ProductName, Price, Discount
57  FROM Product
58  WHERE Discount IS NULL;
59
```

```
+----------------------+
| Operations           |
+----------------------+
| Special SQL Operators |
+----------------------+
+-----------+-------------+----------+----------+----------+
| ProductID | ProductName | Price    | Quantity | Discount |
+-----------+-------------+----------+----------+----------+
|         1 | Laptop      | 50000.00 |        2 |  5000.00 |
|         2 | Mobile      | 20000.00 |        3 |  2000.00 |
|         3 | Keyboard    |  1500.00 |        5 |   100.00 |
|         4 | Mouse       |   800.00 |        4 |    50.00 |
+-----------+-------------+----------+----------+----------+
+-------------+----------+
| ProductName | Price    |
+-------------+----------+
| Mobile      | 20000.00 |
| Keyboard    |  1500.00 |
+-------------+----------+
+-------------+----------+
| ProductName | Price    |
+-------------+----------+
| Laptop      | 50000.00 |
| Mobile      | 20000.00 |
+-------------+----------+
+-------------+----------+
| ProductName | Price    |
+-------------+----------+
| Mobile      | 20000.00 |
| Mouse       |   800.00 |
+-------------+----------+
```

```
CREATE TABLE BCA_Students (
    Student_ID INT,
    Name VARCHAR(50),
    Marks INT
);
INSERT INTO BCA_Students VALUES
(101, 'Rahul', 85),
(102, 'Anu', 72),
(103, 'Kiran', 90),
(104, 'Priya', 65);
CREATE TABLE BBA_Students (
    Student_ID INT,
    Name VARCHAR(50),
    Marks INT
);
INSERT INTO BBA_Students VALUES
(105, 'Arun', 78),
(106, 'Sneha', 88),
(107, 'Rahul', 85),
(108, 'Vikas', 70);
SELECT * FROM BCA_Students;
SELECT * FROM BBA_Students;
```

```sql
CREATE TABLE BCA_Students (
    Student_ID INT,
    Name VARCHAR(50),
    Marks INT
);

INSERT INTO BCA_Students VALUES
(101, 'Rahul', 85),
(102, 'Anu', 72),
(103, 'Kiran', 90),
(104, 'Priya', 65);


CREATE TABLE BBA_Students (
    Student_ID INT,
    Name VARCHAR(50),
    Marks INT
);

INSERT INTO BBA_Students VALUES
(105, 'Arun', 78),
(106, 'Sneha', 88),
(107, 'Rahul', 85),
(108, 'Vikas', 70);

SELECT * FROM BCA_Students;
SELECT * FROM BBA_Students;
```

Output:

Student_ID	Name	Marks
101	Rahul	85
102	Anu	72
103	Kiran	90
104	Priya	65

Student_ID	Name	Marks
105	Arun	78
106	Sneha	88
107	Rahul	85
108	Vikas	70

```sql
/* UNOIN */
SELECT Student_ID, Name, Marks
FROM BCA_Students
UNION
SELECT Student_ID, Name, Marks
FROM BBA_Students;


/* UNION ALL */
SELECT Student_ID, Name, Marks
FROM BCA_Students
UNION ALL
SELECT Student_ID, Name, Marks
FROM BBA_Students;
```

```sql
/* UNOIN */
SELECT Student_ID, Name, Marks
FROM BCA_Students

UNION

SELECT Student_ID, Name, Marks
FROM BBA_Students;


/* UNION ALL */
SELECT Student_ID, Name, Marks
FROM BCA_Students

UNION ALL

SELECT Student_ID, Name, Marks
FROM BBA_Students;

```

Output:

Student_ID	Name	Marks
101	Rahul	85
102	Anu	72
103	Kiran	90
104	Priya	65
105	Arun	78
106	Sneha	88
107	Rahul	85
108	Vikas	70

Student_ID	Name	Marks
101	Rahul	85
102	Anu	72
103	Kiran	90
104	Priya	65
105	Arun	78
106	Sneha	88
107	Rahul	85
108	Vikas	70