@eshaaldev

Day 6

CSS

Visibility, Overflow, Object-Fit

@eshaaldev

Comparison

Property	What It Does	Affects Layout?	Clickable?	Use Case Example
`display: none`	Hides element **completely** (no space)	❌ No space	❌ Not clickable	Temporarily remove from DOM
`visibility: hidden`	Hides element, but **keeps space**	✅ Keeps space	❌ Not clickable	Hide item but retain layout
`opacity: 0`	Makes element **invisible**, but present	✅ Keeps space	✅ Still clickable	Soft hiding (e.g., animation)

👉 Use `display: none` when layout shouldn't reserve space,

👉 `visibility: hidden` when preserving layout is important,

👉 `opacity: 0` when you still need interactivity (e.g., for transitions).

@eshaaldev

Overflow

It defines what happens when content overflows its container.

Value	Description	Use Case
`visible`	Default. Content spills out.	Rarely used deliberately
`hidden`	Cuts off extra content. No scrollbars.	Custom containers, tooltips
`scroll`	Always adds scrollbars.	For scrollable content areas
`auto`	Adds scrollbars **only if needed**	Recommended for responsive design

@eshaaldev

Object Fit

It controls how content (like images or videos) resizes to fit its container.

Value	Description	Use Case
`visible`	Default. Content spills out.	Rarely used deliberately
`hidden`	Cuts off extra content. No scrollbars.	Custom containers, tooltips
`scroll`	Always adds scrollbars.	For scrollable content areas
`auto`	Adds scrollbars **only if needed**	Recommended for responsive design

@eshaaldev

Tutor Info Cards

Our Tutors

John Doe

Math & Programming Expert

Teaches high school and university level math and algorithms. Loves simplifying complex topics.

Sarah Ali

Web Development Tutor

Specializes in HTML, CSS, and React. 5+ years of teaching experience in frontend development.

@eshaaldev

HTML

```html
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>Tutor Cards</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>

  <h1 class="heading">Our Tutors</h1>
  <div class="grid-container">
    <div class="card">
      <img src="tutor.jpg" alt="Tutor 1" class="card-img">
      <div class="card-body">
        <h2>John Doe</h2>
        <p class="visible-text">Math & Programming Expert</p>
        <div class="bio-box">
          <p>Teaches high school and
       university level math and algorithms.
       Loves simplifying complex topics.</p>
        </div>
      </div>
    </div>
    <div class="card">
      <img src="tutor.jpg" alt="Tutor 2" class="card-img">
      <div class="card-body">
        <h2>Sarah Ali</h2>
        <p class="visible-text">Web Development Tutor</p>
        <div class="bio-box">
          <p>Specializes in HTML, CSS, and React.
            5+ years of teaching experience in frontend development.</p>
        </div>
      </div>
    </div>

  </div>

</body>
</html>
```

@eshaaldev

CSS

```c
/* Reset + Base */
body {
  margin: 0;
  padding: 0;
  font-family: sans-serif;
  background: #f3f0fa;
}
.heading {
  text-align: center;
  margin: 20px 0;
  font-size: 32px;
}

/* Grid Layout */
.grid-container {
  display: grid;
  grid-template-columns: repeat(auto-fit, minmax(260px, 1fr));
  gap: 20px;
  padding: 20px;
  box-sizing: border-box;
}

/* Tutor Card */
.card {
  background: white;
  border: 2px solid #ddd;
  border-radius: 10px;
  overflow: hidden;
  display: flex;
  flex-direction: column;
  position: relative;
}
```

@eshaaldev

CSS

```
.card-img {
  width: 100%;
  height: 180px;
  object-fit: cover;
}

.card-body {
  padding: 15px;
  flex: 1;
  display: flex;
  flex-direction: column;
  justify-content: space-between;
}

.visible-text {
  font-weight: bold;
  margin-bottom: 10px;
}

/* Bio Box - Hidden but takes space */
.bio-box {
  background: #6e44d9;
  color: white;
  padding: 10px;
  font-size: 14px;
  max-height: 100px;
  overflow-y: auto;
  opacity: 0.8;
  visibility: visible;
  position: relative;
  box-sizing: border-box;
}
```