@eshaaldev

Day 8

CSS

Pseudo Element & Class

What Are Pseudo-classes?

A pseudo-class targets an element based on its state (like hover, focus, or its position in the DOM). It starts with a single colon :

@eshaaldev

Common Classes

Common Pseudo-classes:

Pseudo-class	Description
`:hover`	When mouse is over an element
`:focus`	When an element is focused (input field)
`:active`	While an element (like a button) is being clicked
`:visited`	A visited link
`:first-child`	Targets the first child of a parent
`:last-child`	Targets the last child of a parent
`:nth-child(n)`	Targets the nth child (1-based)
`:nth-of-type(n)`	Targets the nth element of its type
`:not(selector)`	Selects everything except the given selector
`:checked`	A checked input (radio/checkbox)
`:disabled`	Disabled form fields
`:empty`	Elements with no children (text or elements)
`:required`	Input fields with `required` attribute

What Are Pseudo-elements?

A pseudo-element lets you style part of an element (e.g. first letter or insert content). It uses two colons :: (modern syntax).

Common Pseudo-elements:

Pseudo-element	Description
`::before`	Inserts content **before** an element
`::after`	Inserts content **after** an element
`::first-line`	Styles the first line of text
`::first-letter`	Styles the first letter of text
`::selection`	Styles the highlighted text

Best Practices

Use ::before and ::after only with elements that can contain content.

:hover, :focus, and :active are great for interactivity.

Use :nth-child() for precise targeting without classes.

Avoid overly complex selectors—be specific and semantic.

@eshaaldev

HTML

```html
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>FAQ</title>
  <link rel="stylesheet" href="styles.css">
</head>
<body>

<div class="faq">
  <h2>Frequently Asked Questions</h2>

  <div class="faq-item">
    <input type="checkbox" id="q1" />
    <label for="q1">What is your refund policy?</label>
    <p class="answer">We offer a 30-day full refund on all purchases.</p>
  </div>

  <div class="faq-item">
    <input type="checkbox" id="q2" />
    <label for="q2">Do you offer support?</label>
    <p class="answer">Yes, 24/7 support is included in all plans.</p>
  </div>
</div>


</body>
</html>
```

@eshaaldev

CSS

```
/* Reset */
body {
  font-family: sans-serif;
  background: #f9f9f9;
  padding: 40px;
  color: #333;
}

.faq {
  max-width: 600px;
  margin: auto;
  background: white;
  border-radius: 10px;
  padding: 20px;
  box-shadow: 0 10px 25px rgba(0, 0, 0, 0.1);
}

.faq h2 {
  text-align: center;
  margin-bottom: 20px;
}

/* Hide checkboxes */
.faq-item input {
  display: none;
}

/* FAQ Labels */
.faq-item label {
  display: block;
  position: relative;
  font-weight: bold;
  cursor: pointer;
  padding: 15px 20px;
  background: #eee;
  margin-bottom: 5px;
  border-radius: 5px;
  transition: background 0.3s;
}
```

@eshaaldev

CSS

```
/* Hover & Focus Pseudo-classes */
.faq-item label:hover,
.faq-item label:focus {
  background: #dcd5f8;
}

/* Answer Initially Hidden */
.faq-item .answer {
  max-height: 0;
  overflow: hidden;
  transition: max-height 0.4s ease-in-out;
  padding: 0 20px;
  background: #f5f5f5;
  border-left: 3px solid #6e44d9;
}

/* Show Answer if Checked */
.faq-item input:checked ~ .answer {
  max-height: 200px;
  padding: 15px 20px;
}

/* ::before Arrow Icon */
.faq-item label::before {
  content: "▶";
  position: absolute;
  left: 10px;
  top: 50%;
  transform: translateY(-50%);
  font-size: 14px;
  transition: transform 0.3s;
}

/* Rotate Arrow on Open */
.faq-item input:checked + label::before {
  transform: translateY(-50%) rotate(90deg);

}

/* Optional: Highlight text selection */
.faq::selection,
.faq *::selection {
  background: #d3c1ff;
  color: #000;
}
```