

SQL (Structured Query Language)

➤ Operations on Table :-

➤ ALTER TABLE :-

ALTER TABLE


- ALTER TABLE statement is used to add, modify or delete columns in an existing table.
- It is also used to rename a table.



1) ALTER - Add Column

ALTER – Add Column

- Add columns in SQL table



ALTER TABLE table_name **ADD** column_name column-definition;

Eg. **alter table** student **add** name **varchar**(20);

2) ALTER – Modify Column

ALTER – Modify Column

- Modify an existing column in SQL table



ALTER TABLE table_name **MODIFY** column_name column_type;

Eg. **alter table** login **MODIFY** name int(10);

3) ALTER – Drop Column

ALTER – Drop Column

- Drop an existing column in SQL table

Syntax

ALTER TABLE table_name **DROP COLUMN** column_name;

Eg. **alter table** login1 **drop column** name;

4) ALTER – Rename Column

ALTER – Rename Column

- Rename an existing column in SQL table

Syntax

ALTER TABLE table_name **RENAME COLUMN** old_name **to** new_name;

OR

ALTER TABLE login1 **CHANGE** column_name datatype;

Eg. **alter table** login1 **RENAME COLUMN** pass **to** pass1;

OR

alter table login1 **change** roll_no id int(20);

➤ SELECT TABLE :-

Select

- It is used to query the database and retrieve selected data that follow the conditions we want.
- The SQL **SELECT** statement is used to fetch the data from a database table which returns this data in the form of a result table.

Clauses in SELECT Statement

WHERE

GROUP BY

HAVING

ORDER BY



SELECT * FROM table_name;

Eg. **SELECT * FROM** student;



SELECT column_name **FROM** table_name;

Eg. **SELECT** name **FROM** student;

1) SELECT UNIQUE OR SELECT DISTINCT



- **SELECT UNIQUE** is an old syntax which was used in oracle description but later ANSI standard defines **DISTINCT** as the official keyword.



SELECT UNIQUE column_name **FROM** table_name;

Eg. **SELECT UNIQUE** name **FROM** student;

OR



SELECT DISTINCT column_name **FROM** table_name;

Eg. **SELECT DISTINCT** name **FROM** student;

2) SELECT COUNT



- The **SQL COUNT()** function is used to return the number of rows in a query.
- it is very useful to count the number of rows in a table having enormous data.



I. SELECT COUNT(Column_name)

SELECT COUNT(column_name)

- It will return the total number of names of student_table.
- null fields will not be counted.

Syntax

SELECT COUNT (column_name) FROM table_name;

Eg. **SELECT COUNT (name) FROM student;**

II. SELECT COUNT(*)

SELECT COUNT(column_name)

- It will return the total number of names of student_table.
- null fields will not be counted.

Syntax

SELECT COUNT (column_name) FROM table_name;

Eg. **SELECT COUNT (name) FROM student;**

III. SELECT COUNT(DISTINCT column_name)

SELECT COUNT(DISTINCT column_name)

- It will return the total distinct names of student_table.

Syntax

SELECT COUNT (DISTINCT column_name) FROM table_name;

Eg. **SELECT COUNT (DISTINCT name) FROM student;**

3) SELECT TOP

SELECT TOP

- It is used to select top data from a table.
- The top clause specifies that how many rows are returned.

Syntax

SELECT COUNT (expression)

Eg. **SELECT TOP 2 * FROM** student;

OR

Syntax

SELECT * FROM table_name **LIMIT** count;

Eg. **select * from** student **limit** 2;