

CSS (Cascading Style Sheet)

Overlay in CSS :-



- it is used to set one thing on the top of another.
- Creating an overlay effect means to put two **div** together at the same place

```
<style>
img { width: 300px; height: 300px; }

.container { position: relative; width: 25%;
height: auto; }

.overlay {
position: absolute; transition: 0.5s ease;
height: 300px; width: 300px; top: 0;
background-color: blue; opacity: 0; }

.container:hover .overlay {
opacity: 0.9; }
</style>
```

```
<div class="container">
  <img src= "test.jpg">
  <div class="overlay"></div>
</div>
```



Implementation :-

HTML Code -

```
CSS > overlay.html > html
1 <!DOCTYPE html>
2 <html lang="en">
3 <head>
4   <meta charset="UTF-8">
5   <meta name="viewport" content="width=device-width, initial-scale=1.0">
6   <title>Document</title>
7   <link rel="stylesheet" href="./overlay.css">
8 </head>
9 <body>
10
11   <!--Overlay-->
12
13   <div class="container">
14     
15     <div class="overlay"></div>
16   </div>
17
18 </body>
19 </html>
```

CSS Code -

```
CSS > # overlay.css >  .container:hover .overlay
1  .container{
2      height:400px;
3      width:400px;
4      border-style: dashed;
5  }
6
7  img{
8      height: 300px;
9      width: 300px;
10 }
11
12 .overlay{
13     height: 300px;
14     width: 300px;
15     background-color:  chartreuse;
16     position: absolute;
17     top: 10px;
18     opacity: 0;
19 }
20
21 .container:hover .overlay{
22     opacity: 0.5;
23 }
```

Output –



CSS Position Property –

- CSS positioning is about controlling the placement of elements within a web page.
- With CSS positioning, you can override the normal document flow.
- The position property specifies the positioning type for an element.

This property can have one of the following values:

1. static - This is default
2. relative
3. fixed
4. absolute
5. sticky

➤ **static (default)**

- Elements are positioned in the normal document flow.
- Top, right, bottom, left have no effect.

```
div {  
  position: static;  
}
```

➤ **relative**

- Element is positioned relative to its normal position.
- You can use top, left, right, bottom to move it.

```
div {  
  
  position: relative;  
  top: 20px;  
  left: 10px;  
}
```

➤ **absolute**

- Element is positioned relative to the nearest positioned ancestor (not static).
- If no ancestor is positioned, it will be placed relative to the <html> (document body).

```
div {  
  position: absolute;  
  top: 50px;  
  right: 30px;  
}
```

➤ **fixed**

- Element is positioned relative to the viewport (browser window).
- It does not move when the page is scrolled.

```
div {  
  position: fixed;  
  bottom: 0;  
  right: 0;  
}
```

➤ **sticky**

- A hybrid of relative and fixed.
- Element acts like relative until you scroll to its defined threshold (top, left, etc.), then it “sticks” like fixed.

```
div {  
  position: sticky;  
  top: 0;  
}
```