





# The Field Concept and Dependency Graphs




Tim Weißker

# Last Week: Scenegraphs



# Last Week: Scenegraphs





Every node in the scenegraph is a *field container*!

# Fields and Field Containers

---

## Field

- ▶ more complex form of an attribute
- ▶ object state information
- ▶ single and multi fields
- ▶ easy serialization and distribution



# Fields and Field Containers

---

## Field Container

- ▶ collection of fields
- ▶ `evaluate()` method called when one field changes

Increment
Input : SFlnt Output : SFlnt
<code>evaluate()</code>

# Fields and Field Containers

---

## Field Container

- ▶ collection of fields
- ▶ `evaluate()` method called when one field changes

```
class Increment(avango.script.Script):  
  
    Input = avango.SFInt()  
    Output = avango.SFInt()  
  
    def evaluate(self):  
        self.Output.value = self.Input.value + 1
```

# Evaluation

---

```
def evaluate(self):  
    self.Output.value = self.Input.value + 1
```

- ▶ a field container's `evaluate()` method executes three steps in the following order

Increment
Input : SFlnt Output : SFlnt
evaluate()

# Evaluation

---

```
def evaluate(self):  
    self.Output.value = self.Input.value + 1
```

- ▶ a field container's `evaluate()` method executes three steps in the following order
  - ▶ read values from local input fields

Increment
Input : SFlnt Output : SFlnt
evaluate()



# Evaluation

```
def evaluate(self):  
    self.Output.value = self.Input.value + 1
```

- ▶ a field container's `evaluate()` method executes three steps in the following order
  - ▶ read values from local input fields
  - ▶ calculate new values derived from these values

Increment
Input : SFlnt Output : SFlnt
evaluate()

# Evaluation

```
def evaluate(self):  
    self.Output.value = self.Input.value + 1
```

- ▶ a field container's `evaluate()` method executes three steps in the following order
  - ▶ read values from local input fields
  - ▶ calculate new values derived from these values
  - ▶ write the results to output fields

Increment
Input : SFlnt Output : SFlnt
evaluate()

# Evaluation

```
def evaluate(self):  
    self.Output.value = self.Input.value + 1
```

- ▶ a field container's `evaluate()` method executes three steps in the following order

- ▶ read values from local input fields
- ▶ calculate new values derived from these values
- ▶ write the results to output fields

Increment
Input : SFlnt Output : SFlnt
evaluate()

- ▶ to increase reuse, no external data should be accessed

# Implementing a Field Container

---

```
class Container(avango.script.Script):
```

# Implementing a Field Container

---

```
class Container(avango.script.Script):
```

```
    #declaration of fields, e.g.
```

```
    sf_mat = avango.gua.SFMatrix4()
```

# Implementing a Field Container

---

```
class Container(avango.script.Script):
```

```
    #declaration of fields, e.g.
```

```
    sf_mat = avango.gua.SFMatrix4()
```

```
    def __init__(self):
```

```
        self.super(Container).__init__()
```

# Implementing a Field Container

---

```
class Container(avango.script.Script):  
  
    #declaration of fields, e.g.  
    sf_mat = avango.gua.SFMatrix4()  
  
    def __init__(self):  
        self.super(Container).__init__()  
  
    def my_constructor(self, PARAMETER1, PARAMETER2, ...):  
        #initialize variables, parameters, etc.
```

# Implementing a Field Container

---

```
class Container(avango.script.Script):  
  
    #declaration of fields, e.g.  
    sf_mat = avango.gua.SFMatrix4()  
  
    def __init__(self):  
        self.super(Container).__init__()  
  
    def my_constructor(self, PARAMETER1, PARAMETER2, ...):  
        #initialize variables, parameters, etc.  
  
    def evaluate(self):  
        #perform update when fields change
```



# Evaluation policies

---

```
class Container(avango.script.Script):  
  
    #declaration of fields, e.g.  
    sf_mat = avango.gua.SFMatrix4()  
  
    def __init__(self):  
        self.super(Container).__init__()  
  
    def my_constructor(self, PARAMETER1, PARAMETER2, ...):  
        #initialize variables, parameters, etc.  
  
    def evaluate(self):  
        #perform update when fields change
```

# Evaluation policies

---

- ▶ `evaluate()`
  - ▶ called when at least one of the field changes

# Evaluation policies

---

```
class Container(avango.script.Script):
```

```
    #declaration of fields, e.g.
```

```
    sf_mat = avango.gua.SFMatrix4()
```

```
    def __init__(self):
```

```
        self.super(Container).__init__()
```

```
        self.always_evaluate(True)
```

```
    def my_constructor(self, PARAMETER1, PARAMETER2, ...):
```

```
        #initialize variables, parameters, etc.
```

```
    def evaluate(self):
```

```
        #perform update when fields change
```

# Evaluation policies

---

- ▶ `evaluate()`
  - ▶ called when at least one of the field changes
- ▶ `self.always_evaluate(True)`
  - ▶ forces evaluation every frame regardless of field changes

# Evaluation policies

---

```
class Container(avango.script.Script):  
  
    #declaration of fields, e.g.  
    sf_mat = avango.gua.SFMatrix4()  
  
    def __init__(self):  
        self.super(Container).__init__()  
  
    def my_constructor(self, PARAMETER1, PARAMETER2, ...):  
        #initialize variables, parameters, etc.  
  
    @field_has_changed(sf_mat)  
    def sf_mat_changed(self):  
        #perform update when fields change
```

# Evaluation policies

---

- ▶ `evaluate()`
  - ▶ called when at least one of the field changes
- ▶ `self.always_evaluate(True)`
  - ▶ forces evaluation every frame regardless of field changes
- ▶ `@field_has_changed(SFFoo)`
  - ▶ only evaluated when `SFFoo` changes
  - ▶ function name can be arbitrary

# Dependencies

---

- ▶ sometimes it is the case that an output field of one field container forms the input of another one (e.g. sensors)


Container A
Input : type Output : type
evaluate()

Container B
Input : type Output : type
evaluate()

# Dependencies

---

- ▶ sometimes it is the case that an output field of one field container forms the input of another one (e.g. sensors)
- ▶ field connections: the value of a field is copied into another one after evaluation






# Dependencies

---

- ▶ sometimes it is the case that an output field of one field container forms the input of another one (e.g. sensors)
- ▶ field connections: the value of a field is copied into another one after evaluation




- ▶ `b.Input.connect_from(a.Output)`


(no .value needed)

# Cyclic dependencies

---




# Cyclic dependencies




► `a.Input.connect_weak_from(b.Output)`

# Orthogonality




# Orthogonality



# Orthogonality

---



# Summary

---

- ▶ every node of the Scenegraph and classes derived from `avango.script.Script` are called field containers

# Summary

---

- ▶ every node of the Scenegraph and classes derived from `avango.script.Script` are called field containers
- ▶ state of a field container is defined by state of its fields
  - ▶ easy serialization
  - ▶ easy network distribution



# Summary

---

- ▶ every node of the Scenegraph and classes derived from `avango.script.Script` are called field containers
- ▶ state of a field container is defined by state of its fields
  - ▶ easy serialization
  - ▶ easy network distribution
- ▶ within a field container, no external data should be accessed
  - ▶ realize dependencies with field connections
  - ▶ loose coupling between field container instances (easily reusable)


# Summary

---

- ▶ every node of the Scenegraph and classes derived from `avango.script.Script` are called field containers
- ▶ state of a field container is defined by state of its fields
  - ▶ easy serialization
  - ▶ easy network distribution
- ▶ within a field container, no external data should be accessed
  - ▶ realize dependencies with field connections
  - ▶ loose coupling between field container instances (easily reusable)
- ▶ the dependency graph is orthogonal to the scenegraph

# The Field Concept

## Questions?



```
class Container(avango.script.Script):
```

```
#declaration of fields, e.g.
```

```
sf_mat = avango.gua.SFMatrix4()
```

```
def __init__(self):
```

```
    self.super(Container).__init__()
```

```
def my_constructor(self, PARAMETER1, PARAMETER2, ...):
```

```
    #initialize variables, parameters, etc.
```

```
def evaluate(self):
```

```
    #perform update when fields change
```