# Assignment-3

Name-KAARTHIKA M

Class-24CS4B

Reg No-732924CSR064

**1. Display all records from the Employee table.**

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.

  CREATE TABLE Employees (EmpID INT PRIMARY KEY,Name VARCHAR(50),Department VARCHAR(50),Salary
INT,City VARCHAR(50));

INSERT INTO Employees VALUES
(101, 'kani', 'IT', 50000, 'Chennai'),
(102, 'karthi', 'HR', 45000, 'Bangalore'),
(103, 'KV', 'IT', 60000, NULL),
(104, 'nithya', 'Finance', 55000, 'Chennai'),
(105, 'paarkavi', 'HR', 40000, 'Coimbatore');

SELECT * FROM Employees;
```

Output

| EmpID | Name | Department | Salary | City |
|---|---|---|---|---|
| 101 | kani | IT | 50000 | Chennai |
| 102 | karthi | HR | 45000 | Bangalore |
| 103 | KV | IT | 60000 | |
| 104 | nithya | Finance | 55000 | Chennai |
| 105 | paarkavi | HR | 40000 | Coimbatore |

**2. Display only the Name and Salary of employees**

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT Name, Salary FROM Employees;
```

Output

| Name | Salary |
|---|---|
| kani | 50000 |
| karthi | 45000 |
| KV | 60000 |
| nithya | 55000 |
| paarkavi | 40000 |

**3. Display employees whose salary is greater than 50,000.**

Input

Run SQL

```
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT * FROM Employees WHERE Salary > 50000;
```

Output

| EmpID | Name | Department | Salary | City |
|---|---|---|---|---|
| 103 | KV | IT | 60000 | |
| 104 | nithya | Finance | 55000 | Chennai |

**4. Display employees who belong to the IT department.**

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT * FROM Employees
WHERE Department = 'IT';
```

Output

| EmpID | Name | Department | Salary | City |
|---|---|---|---|---|
| 101 | kani | IT | 50000 | Chennai |
| 103 | KV | IT | 60000 | |

**5. Display employees whose city is Chennai.**

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT * FROM Employees
WHERE City = 'Chennai';
```

Output

| EmpID | Name | Department | Salary | City |
|---|---|---|---|---|
| 101 | kani | IT | 50000 | Chennai |
| 104 | nithya | Finance | 55000 | Chennai |

**6. Display employees whose salary is between 40,000 and 60,000.**

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT * FROM Employees
WHERE Salary BETWEEN 40000 AND 60000;
```

Output

| EmpID | Name | Department | Salary | City |
|---|---|---|---|---|
| 101 | kani | IT | 50000 | Chennai |
| 102 | karthi | HR | 45000 | Bangalore |
| 103 | KV | IT | 60000 | |
| 104 | nithya | Finance | 55000 | Chennai |
| 105 | paarkavi | HR | 40000 | Coimbatore |

**7. Display distinct departments from the Employee table.**

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT DISTINCT Department FROM Employees;
```

Output

| Department |
| --- |
| IT |
| HR |
| Finance |

**8. Display employees whose City value is NULL**

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT * FROM Employees
WHERE City IS NULL;
```

Output

| EmpID | Name | Department | Salary | City |
|---|---|---|---|---|
| 103 | KV | IT | 60000 | |

**9. Find the total salary paid to all employees.**

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT SUM(Salary) FROM Employees;
```

Output

| SUM(Salary) |
| --- |
| 250000 |

**10. Find the average salary of employees in the IT department**

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT AVG(Salary)
FROM Employees
WHERE Department = 'IT';
```

Output

| AVG(Salary) |
| --- |
| 55000 |

**11. Count the number of employees in each department using GROUP BY.**

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT AVG(Salary)
FROM Employees
WHERE Department = 'IT';
```

Output

| AVG(Salary) |
| --- |
| 55000 |

**12. Display employees whose salary is greater than the average salary (nested subquery).**

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT Department, COUNT(*)
FROM Employees
GROUP BY Department;
```

Output

| Department | COUNT(*) |
|---|---|
| Finance | 1 |
| HR | 2 |
| IT | 2 |

**13. Write an SQL statement to insert a new employee record.**

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT Department, COUNT(*)
FROM Employees
GROUP BY Department;
```

Output

| Department | COUNT(*) |
|---|---|
| Finance | 1 |
| HR | 2 |
| IT | 2 |

**14. Write an SQL query to update the salary of employee with EmpID = 105 to 48000.**

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.
SELECT * FROM Employees
WHERE Salary > (SELECT AVG(Salary) FROM Employees);
```

Output

| EmpID | Name | Department | Salary | City |
|---|---|---|---|---|
| 103 | KV | IT | 60000 | |
| 104 | nithya | Finance | 55000 | Chennai |

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.

INSERT INTO Employee VALUES(106, 'divya', 'IT', 52000, 'Madurai');
SELECT * FROM Employee;
```

Output

Employee

| EmpID | Name | Department | Salary | City |
|---|---|---|---|---|
| 101 | kani | IT | 50000 | Chennai |
| 102 | karthi | HR | 45000 | Bangalore |
| 103 | KV | IT | 60000 | |
| 104 | nithya | Finance | 55000 | Chennai |
| 105 | paarkavi | HR | 40000 | Coimbatore |
| 106 | divya | IT | 52000 | Madurai |

Input

Run SQL

```sql
-- Online SQL Editor to Run SQL Online.
-- Use the editor to create new tables, insert data and all other SQL operations.

UPDATE Employee
SET Salary = 48000
WHERE EmpID = 105;
select * from Employee;
```

Output

| EmpID | Name | Department | Salary | City |
|---|---|---|---|---|
| 101 | kani | IT | 50000 | Chennai |
| 102 | karthi | HR | 45000 | Bangalore |
| 103 | KV | IT | 60000 | |
| 104 | nithya | Finance | 55000 | Chennai |
| 105 | paarkavi | HR | 48000 | Coimbatore |
| 106 | divya | IT | 52000 | Madurai |