AXENT

Open-source overlay for trading terminals

The current pair and its market data.
Inside your trading terminal.

JAVASCRIPT / BOOKMARKLETS / OPEN SOURCE

Product and architecture of the MVP

October 26, 2026

Product and purpose

Market context inside the terminal you already use

AXENT is an open-source JavaScript overlay launched from a browser bookmark. It identifies the token or liquidity pool open in a trading terminal and displays its pair, price, volume and liquidity alongside the existing interface. The primary workflow does not require manually entering a contract address.

The problem

Evaluating a token often means moving between the trading terminal, an analytics page and a copied contract address. When the trader switches to another asset, a separate analytics tab can remain on the previous market. The resulting friction is a context problem as much as a navigation problem.

The approach

AXENT ties a compact analytics panel to the current page. The user opens a token and clicks a saved bookmark. The panel reads a public address from the URL or explicitly marked page attributes, requests public market data and updates its context when the open market changes.

The first release

The MVP has one primary responsibility: show useful data about the market currently open. It does not connect to a wallet or submit orders. Automated sniping, automatic stop-loss execution and whale detection are outside the implemented scope.

Product readiness is measured by correct market identification, clear data presentation and reliable transitions between assets. Trading returns are not a verified product characteristic or an acceptance metric for this MVP.

Version 0.1 describes the open-source implementation as of October 26, 2026.

User experience

A dedicated bookmark for each terminal

Each platform has a self-contained bookmarklet. Its executable logic is embedded in the bookmark itself. Running it requires no browser extension, separate AXENT website or externally hosted JavaScript loader.

01 Save the bookmark

Paste the complete javascript: URL from the relevant terminal folder into a browser bookmark. An existing installation interface can expose the same URL as a draggable bookmark link.

02 Open a market

Navigate to a token or pool in the corresponding terminal and click the saved bookmark. The script checks the domain before opening the overlay.

03 Read the current context

The pair and its data load automatically. When the user navigates to another asset within the terminal, the overlay updates without being launched again.

Terminal	Domain	Folder
FOMO	fomo.family	terminals/fomo
Pump.fun	pump.fun	terminals/pump
Trojan	trojan.com	terminals/trojan
Padre	trade.padre.gg	terminals/padre
BasedBot	basedbot.app	terminals/basedbot
Axiom	axiom.trade	terminals/axiom

Separate builds and route fixtures exist for all six platforms. Full compatibility testing inside every authenticated terminal has not yet been completed.

Architecture

Readable source with clearly separated responsibilities

The implementation separates context detection, overlay behavior and platform configuration. The build process combines these components into a standalone JavaScript bookmarklet for each terminal.



Context detection

The src/detect.js module inspects supported URL parameters, address-like route segments and explicitly marked current-token attributes. The current route takes priority. Arbitrary page text, trending lists and private application state are not used to select the active contract.

Presentation and data

The src/overlay.js module creates a Shadow DOM panel and manages its position, market requests and active context. Style isolation reduces interference from the host page. Closing the panel stops its timers and cancels the active request.

Configuration and builds

The platforms.mjs file defines each terminal name, allowed domains and destination URL. The builder generates bookmarklet.js with readable executable source and bookmarklet.txt with the ready-to-save bookmark URL. The repository contains no HTML website, server or npm dependencies.

Third-party route formats and page markup can change. Context detection therefore requires ongoing maintenance even when the AXENT interface stays the same.

Market data

Resolve the active pair before presenting its numbers

The MVP uses the public DEX Screener API. Requests contain the network and the public token or pool address; terminal session credentials are not transmitted. A pool address resolves to that specific pair. A token contract resolves to its most liquid indexed market.

Field	What the overlay displays
Pair	Base asset, quote asset and network
Price	Latest received USD price of the base asset
Change	Five-minute price change, when supplied by the API
Volume	One-hour trading volume, when available
Liquidity	USD liquidity of the selected market
Market cap	Market capitalization, when returned by the provider

Interpretation rules

A missing value is displayed as a dash rather than a zero. If the network of an EVM address cannot be established from the page context, the user selects it in the panel. The current interface supports Solana, Ethereum, Base and BNB Chain. Network support does not imply that every token is indexed by the data provider.

Page context is checked once per second. Market data refreshes every 15 seconds, with a separate manual refresh action. The chart contains up to 60 samples collected during the current session; it is not a historical candlestick chart. Browser background throttling can increase these intervals.

For a token contract, the most liquid indexed market may differ from the pool open in the terminal. Exact pool matching requires a reliably identified pool address.

Security and reliability

Public context and transparent execution

The MVP reads public page context and requests public market data. It does not connect wallets, read private keys or session tokens, request signatures, or execute trades. It does not load external executable JavaScript at runtime.

Handling uncertainty

When no unambiguous market address is available, the panel waits for a token page and offers manual controls. When context changes, the previous pair data is hidden until the newly selected market loads. This prevents a previous asset price from being presented as the new asset price.

If an API request fails for the same market, the last successful figures may remain visible with a stale-data message. Rate limits, network errors and unindexed markets are not interpreted as zero prices or an absence of trading.

Local settings

The watchlist uses a dedicated localStorage key on the current origin and holds up to 10 tokens. Lists are separate across terminal domains. If storage is unavailable, the panel retains an in-memory list until it closes. A one-shot price movement alert appears inside the panel after a threshold is reached relative to the next successful sample. System notification permission is not requested.

Browser boundaries

A terminal Content Security Policy may block bookmarklet execution or API requests. AXENT does not bypass these controls. Internal browser pages and mobile installation are outside the first release environment. Shadow DOM isolates styles; it does not protect the overlay from malicious code running on the host page.

Implementation properties are not a substitute for an independent security audit. An audit and complete platform compatibility checks remain separate milestones.

Validation and roadmap

Readiness is defined by a verified user workflow

Current checks cover six generated bookmarklets, domain restrictions, repeat-click closure, route fixtures, exact-pool requests, context transitions and market-data handling. A local browser preview has also verified automatic loading of a live SOL / USDC market and context switching without a page reload.

Acceptance criteria for each terminal

01 Identify the correct market

Open a known pair, launch the bookmark and compare the address, network and asset names. Confirm that the loaded data belongs to that market.

02 Follow navigation correctly

Switch to another pair within the terminal. Previous figures must disappear, and the newly selected market must load automatically.

03 Fail predictably

Check a page without a token, an unavailable API, an unsupported network and panel closure. Errors must not be replaced with fabricated market data.

Proposed development sequence

Stage	Intended outcome
MVP stabilization	Real browser checks across all six platforms and refined detection rules
Reliability	Route and markup regression fixtures, with clear data freshness indicators
Broader analytics	Historical data and additional sources after API and constraint review
Trading integrations	Separate design of official integrations, permissions and order execution

This is a proposed work sequence, not a delivery-date commitment. Trading integrations are outside the first release and require their own security review.

Open development

Inspectable code and reproducible builds

The AXENT MVP source is distributed under the MIT license. Developers can inspect the implementation, maintain adapters and build their own bookmarklets under the license terms. Third-party platform names and trademarks remain the property of their owners.

Repository structure

src/detect.js

src/overlay.js

platforms.mjs

scripts/build.mjs

scripts/check.mjs

terminals/{fomo,pump,trojan,padre,basedbot,axiom}/

Each terminal folder contains bookmarklet.js and bookmarklet.txt. Changes are made in the shared source and regenerated with node scripts/build.mjs, then checked with node scripts/check.mjs. A generated bookmarklet embeds all required code and does not depend on an AXENT server.

Contribution priorities

The most useful early contributions are reproducible real-page examples, fixes to active-market detection and transition tests. An issue should identify the terminal, public URL, expected pair and observed behavior. Private keys, secrets and session data should not be included.

Sources and version

[1] AXENT MVP source: src/detect.js, src/overlay.js, platforms.mjs and scripts/check.mjs. Implementation snapshot: October 26, 2026.

[2] AXENT public website, used for product context and visual direction: getaxent.xyz.

[3] DEX Screener API Reference, describing the market-data source and fields: docs.dexscreener.com/api/reference.

This document describes an independent open-source MVP implementation. Marketing claims and performance figures from the public website are not test results for this implementation.