

Karachi Food Delivery Time Analysis — Auto Analysis

Business Analytics Report

Project: Karachi Food Delivery Time Analysis

Dataset: karachi_food_delivery_dataset.csv

Analysis date: 2026-09-25

Prepared by: kabeer ali

Generated by the AI Data Scientist Platform

Table of Contents

1. Executive Summary	4
Key verified findings	4
Top recommendations	4
2. About the Dataset	5
Column dictionary	5
3. Data Quality & Cleaning	7
Original dataset quality (as uploaded)	7
Duplicate Rows	7
Missing Values	7
Outliers	7
Impossible Values	8
Cleaning performed	8
4. Key EDA Findings	10
Trend over time (Order Time)	10
Items Count breakdown	11
5. Modeling Approach	12
Features used	12
Features excluded, and why	12
6. Model Performance	13
Model comparison	13
In plain language	13
Confusion Matrix	13
7. What Drives the Outcome	15
8. Future Outlook	16
9. AI Business Insights AI-generated	17
10. Limitations	18
11. Appendix	19
Full model metrics	19
Preprocessing	19
Hyperparameters	19
Dataset statistics	19

1. Executive Summary

This report analyzes **karachi_food_delivery_dataset.csv** (2,500 rows, 18 columns) covering 2025-07-01 to 2026-06-30 to answer the business question: *A synthetic dataset of 2,520 food delivery orders across eight Karachi areas (Jul 2025 to Jun 2026), with 18 columns covering order time, area, cuisine, weather, traffic, vehicle type, distance, items, order value, preparation time, rider rating and experience, delivery time, promised time, late delivery, tips, and customer rating. It includes missing values, duplicates, mixed data types, inconsistent text, impossible values, and outliers for testing data cleaning. Suitable for delivery time regression and late delivery classification..*

Key verified findings

- The original dataset contained 533 missing value(s) and 20 duplicate row(s), which have since been cleaned.
- A XGBoost model was trained to predict **Weather** (classification). The model correctly classifies about 47.0% of cases (Accuracy).
- 1 feature excluded as data leakage before training (Late Delivery) to avoid an artificially inflated score.

Model reliability, in plain terms: The model correctly classifies about 47.0% of cases (Accuracy). F1 score (balancing precision and recall) is 0.413. ROC-AUC is 0.591 (1.0 = perfect separation, 0.5 = no better than chance).

Top recommendations

- The most common observed outcome for Weather is 'Clear' (244 of 500 test cases).
- Among records, the 'Delivery Time Min: Higher' group shows the highest observed rate (183.3%, n=834), compared to 'Delivery Time Min: Lower' (155.3%, n=833).

2. About the Dataset

karachi_food_delivery_dataset.csv contains 2,500 rows and 18 columns. It spans the period 2025-07-01 to 2026-06-30 (based on Order Time).

Business question: A synthetic dataset of 2,520 food delivery orders across eight Karachi areas (Jul 2025 to Jun 2026), with 18 columns covering order time, area, cuisine, weather, traffic, vehicle type, distance, items, order value, preparation time, rider rating and experience, delivery time, promised time, late delivery, tips, and customer rating. It includes missing values, duplicates, mixed data types, inconsistent text, impossible values, and outliers for testing data cleaning. Suitable for delivery time regression and late delivery classification.

Column dictionary

Column	Type	Missing	Notes
Order Id	Identifier	0.0%	
Order Time	Identifier	0.0%	
Area	Category	0.0%	most common: DHA
Cuisine	Category	0.0%	most common: Desserts
Weather	Category	0.0%	most common: Clear
Traffic Level	Category	0.0%	most common: Medium
Vehicle Type	Category	0.0%	most common: Motorbike
Distance Km	Numeric	0.0%	typical range 0.73–22.01
Items Count	Numeric	0.0%	typical range 1.00–8.00
Order Value Pkr	Numeric	0.0%	typical range 351.00–7,115.
Prep Time Min	Numeric	0.0%	typical range 5.00–49.00
Rider Rating	Numeric	0.0%	typical range 3.30–5.00

Rider Experience Months	Numeric	0.0%	typical range 0.00–59.00
Delivery Time Min	Numeric	0.0%	typical range 10.00–354.00
Promised Time Min	Numeric	0.0%	typical range 55.00–70.00
Late Delivery	Category	0.0%	most common: No
Tip Pkr	Numeric	0.0%	typical range 0.00–200.00
Customer Rating	Numeric	0.0%	typical range 1.00–5.00

3. Data Quality & Cleaning

Original dataset quality (as uploaded)

Total rows	Missing cells	Duplicate rows	Issues detected
2,520	533	20	13

Duplicate Rows

Column	Finding	Affected
(whole dataset)	20 duplicate row(s) detected.	20

Missing Values

Column	Finding	Affected
order_time	'order_time' has 5 missing value(s) (0.2%).	5
weather	'weather' has 101 missing value(s) (4.0%).	101
traffic_level	'traffic_level' has 75 missing value(s) (3.0%).	75
prep_time_min	'prep_time_min' has 75 missing value(s) (3.0%).	75
rider_rating	'rider_rating' has 126 missing value(s) (5.0%).	126
customer_rating	'customer_rating' has 151 missing value(s) (6.0%).	151

Outliers

Column	Finding	Affected
prep_time_min	'prep_time_min' has 1 statistical outlier(s) outside [3.5, 47.5].	1
rider_rating	'rider_rating' has 1 statistical outlier(s) outside [3.35, 5.35].	1
delivery_time_min	'delivery_time_min' has 81 statistical outlier(s) outside [4.5, 96.5].	81
tip_pkr	'tip_pkr' has 391 statistical outlier(s) outside [-75.0, 125.0].	391
customer_rating	'customer_rating' has 38 statistical outlier(s) outside [2.5, 6.5].	38

Impossible Values

Column	Finding	Affected
delivery_time_min	'delivery_time_min' has 3 negative value(s) that are rare exceptions among otherwise non-negative values — likely a data-entry error, not real signal.	3

Cleaning performed



Problem	Before	Action	After	Reason
Duplicate rows	20 duplicate row(s)	Removed duplicate rows	0 duplicate rows	Duplicate records would otherwise double-count the same transaction/customer.
Missing Order Time	5 missing	Filled using the most frequent value (mode)	0 missing	The most representative value for a categorical field.
Missing Weather	101 missing	Filled using the most frequent value (mode)	0 missing	The most representative value for a categorical field.
Missing Traffic Level	75 missing	Filled using the most frequent value (mode)	0 missing	The most representative value for a categorical field.
Missing Prep Time Min	75 missing	Filled using the column median	0 missing	Reduces the influence of extreme values compared to the mean.
Missing Rider Rating	126 missing	Filled using the column median	0 missing	Reduces the influence of extreme values compared to the mean.
Missing Customer Rating	151 missing	Filled using the column median	0 missing	Reduces the influence of extreme values compared to the mean.
Impossible negative Delivery Time Min	3 impossible value(s)	Converted to missing, then filled	0 impossible values	A rare negative value in an otherwise non-negative column is almost always a data-entry error.
Text-formatted numbers in Distance Km	stored as text with units (e.g. '4.2 km')	Converted to a clean numeric value	numeric	100% of values matched a number-with-unit pattern.
Inconsistent capitalization in Weather	5 variant label(s) (e.g. 'rainy' vs 'Rainy')	Merged into a single canonical label	consistent labels	Values differing only by letter case would otherwise be treated as different categories.


After cleaning: 0 missing cell(s), 0 duplicate row(s), 2,500 rows remain. The original file itself was never modified — cleaning produced a separate working copy.

4. Key EDA Findings

Total Rows	Late Delivery Rate	Total Distance Km	Total Items Count
2,500	25.0%	13,095	10,969

Trend over time (Order Time)





Items Count breakdown

Average: 4.39 (range 1.0–8.0)

Value	Count	Percent
8	292	11.7%
7	306	12.2%
6	302	12.1%
5	293	11.7%
4	292	11.7%
3	336	13.4%
2	359	14.4%
1	320	12.8%

5. Modeling Approach

A **classification** model was trained to predict **Weather**, using 15 feature(s).

Features used

Order Time: Year, Order Time: Month, Order Time: Dayofweek, Area, Cuisine, Traffic Level, Vehicle Type, Distance Km, Items Count, Order Value Pkr, Prep Time Min, Rider Rating, Rider Experience Months, Delivery Time Min, Promised Time Min

Features excluded, and why

Column	Reason excluded
Order Id	Identifier column (e.g. an ID) — carries no predictive signal.
Order Time	Raw date — replaced with derived year / month / day-of-week features instead.
Late Delivery	Leakage. Named like post-outcome information AND predicts the target far better (15% correlated) than similarly-named features (avg 10% here) — statistically behaves like a leak on its own, so it's excluded automatically rather than only flagged for review.
Tip Pkr	Excluded by default 'tip_pkr' often represents information only available AFTER the outcome occurs (e.g. a rating or tip given once an order is complete), and shows a real (8% correlated) relationship with the target here. Review whether this would actually be known at prediction time — if not, exclude it below.
Customer Rating	Excluded by default 'customer_rating' often represents information only available AFTER the outcome occurs (e.g. a rating or tip given once an order is complete), and shows a real (7% correlated) relationship with the target here. Review whether this would actually be known at prediction time — if not, exclude it below.


Technical details

Algorithm: XGBoost · Preprocessing: 11 numeric + 4 categorical feature(s), scaled/encoded · Train/test split: 20.0% held out · Cross-validation folds: 5 · Random seed: 42

6. Model Performance

Model comparison

Model	Accuracy	Precision	Recall	F1 Score	ROC-AUC
Logistic Regression	0.4880	0.3175	0.4880	0.3550	0.6283
Decision Tree	0.3200	0.3296	0.3200	0.3245	0.5096
Random Forest	0.4700	0.2839	0.4700	0.3352	0.5505
Gradient Boosting	0.4680	0.3302	0.4680	0.3696	0.6096
XGBoost	0.4700	0.3987	0.4700	0.4129	0.5913
K-Nearest Neighbors	0.4280	0.3466	0.4280	0.3591	0.5193




In plain language


- The model correctly classifies about 47.0% of cases (Accuracy).
- F1 score (balancing precision and recall) is 0.413.
- ROC-AUC is 0.591 (1.0 = perfect separation, 0.5 = no better than chance).

Compared against a trivial baseline (F1 Score = 0.3201); this model clearly outperforms it.

Confusion Matrix



7. What Drives the Outcome



Feature	Relative importance
Traffic Level: High	3.9%
Cuisine: Biryani	3.9%
Delivery Time Min	3.7%
Traffic Level: Low	3.6%
Cuisine: Chinese	3.5%
Cuisine: Desserts	3.5%
Vehicle Type: Car	3.5%
Vehicle Type: Motorbike	3.4%
Area: Saddar	3.4%
Traffic Level: Jam	3.3%

8. Future Outlook

- The most common observed outcome for Weather is 'Clear' (244 of 500 test cases).
- Among records, the 'Delivery Time Min: Higher' group shows the highest observed rate (183.3%, n=834), compared to 'Delivery Time Min: Lower' (155.3%, n=833).

Group	Observed rate	Group size
Delivery Time Min: Lower	155.3%	833
Delivery Time Min: Middle	176.5%	833
Delivery Time Min: Higher	183.3%	834

9. AI Business Insights AI-generated

AI insights are unavailable right now (gemini: Gemini rate limit exceeded — too many requests. Try again shortly.; ollama fallback: The AI service is currently unavailable.). The rest of this report contains verified analytical results only.

10. Limitations

- The following column(s) were excluded as likely data leakage and could not be used: `late_delivery`. If any of these should genuinely be available before prediction time, review them manually.
- Cross-validation scores varied by ± 0.017 across folds — treat the headline metric as an estimate with this much natural uncertainty, not an exact figure.
- Model predictions are estimates based on historical patterns and may not hold if underlying business conditions change. They should inform, not replace, domain expertise.

11. Appendix

Full model metrics

Metric	Value
Accuracy	0.47
Precision	0.3987
Recall	0.47
F1 Score	0.4129
ROC-AUC	0.5913
Cv Mean	0.4005
Is Weak	False

Preprocessing

Setting	Value
Test Size	0.2
Cv Folds	5
Random seed	42
Model version	5

Hyperparameters

Parameter	Value
Random Seed	42

Dataset statistics

Statistic	Value
Rows	2,500
Columns	18