

PHP Global Variables (\$_GET)


PHP \$_GET can also be used to collect form data after submitting an HTML form with **method="GET"**

\$ GET can also collect data sent in the URL.

PRACTICAL EXAMPLE

The algorithm below shows the user's date of birth.

```
<html>
    <head>
                                                                  The PHP $_GET global
        <style>
             body{
                                                                         variable
                 font-family:verdana;
        </style>
    </head>
    <body>
        <form method="GET" action="index.php">
             <br/>
<b>Enter your Date of Birth:</b><br/>
<br/>
/><br/>
/><br/>
/><br/>
/>
/>
//
             Day:<br /><input type="text" name="day"//><br /><br />
             Month:<br /><input type="text" name="month" /><br />
             Year:<br /><input type="text" name="year" /><br /><br />
             <input type="submit" value="Check"//><br />
        </form>
             if(isset($_GET['day'], $_GET['month'], $_GET['year'])){
    $day = $_GET['day'];
                 $month = $_GET['month'];
                 $year = $_GET['year'];
                      if(!empty($day) && !empty($month) && !empty($year)){
                          echo 'Your Date of Birth is: '.$day.' '.$month.' '.$year;
                      }else{
                          echo 'Input fields empty...';
    </body>
</html>
```



NB: \$_GET can also collect data through the URL.