

USXF: A Unified State Exchange Format and Fluid Hypervisor for Cross-Hardware AI Agent Migration

K. Budu
PermeantOS Project Lead

June 17, 2026

Abstract

Long-running autonomous AI agents require the ability to migrate dynamically across heterogeneous cloud clusters and local edge environments. However, live state migration, specifically the transmission of large Key-Value (KV) caches, is bottlenecked by framework-specific layouts, vendor-locked hardware runtimes, and high context-reprefill latency. This paper presents PermeantOS, a state-fluid hypervisor, and USXF (Unified State Exchange Format) v1.1, an open interchange format that decouples KV cache state from underlying runtimes. USXF defines a versioned metadata schema alongside a cryptographic, compressed payload envelope. We describe layout transformations between canonical sequential representations and blocked execution formats, discuss transfer quantization, and define a warm-start decision boundary comparing prefill complexity to network transfer cost. In addition to analytical break-even estimates showing up to an 8x resume-latency reduction for contexts larger than 32k tokens over 25 Gbps links, we report a real cross-runtime validation: a local Apple Silicon MLX source migrated a Qwen2.5 KV cache and complex Agent Memory Graph package to an AWS NVIDIA g4dn.xlarge vLLM target using experimental QATQ transfer compression. The target seeded migrated KV state into vLLM prefix cache, matched the source continuation exactly for the 16-token validation horizon, resumed imported Agent Memory Graph activity, and returned AWS-updated graph/artifact evidence to the origin, where origin-side work continued from the remote proof.

1 Introduction

Autonomous agent architectures increasingly rely on continuous, multi-turn reasoning loops. In these workflows, the model context window becomes a persistent working memory. As conversation histories expand to 32k–128k tokens and beyond, the memory footprint of the KV cache grows into gigabytes.

When an agent migrates because of node eviction, scheduling optimization, cost control, or transition between edge and cloud devices, reconstructing the context normally requires recalculating prompt attention states. This process, known as re-prefilling, incurs substantial computational cost. A simplified model is:

$$T_{\text{prefill}} \propto \mathcal{O}(L \cdot S^2 \cdot D), \quad (1)$$

where L is the number of layers, S is the sequence length, and D is the hidden dimensionality. For long contexts, re-prefilling introduces seconds of latency, interrupting the agent’s interactive loop.

Prior systems have explored disaggregated KV caching, paged attention, and cache reuse [2, 6, 3]. These systems are typically optimized for a specific framework or cluster environment. PermeantOS

targets a complementary problem: cross-hardware and cross-runtime migration where an agent may move from Apple Silicon MLX to NVIDIA CUDA vLLM, while preserving verifiable state continuity.

This paper makes four contributions:

1. We define USXF, a runtime-neutral state exchange format for active KV cache migration.
2. We describe a PermeantOS hypervisor sidecar that performs capability exchange, encrypted transfer, tensor layout transformation, and two-phase commit.
3. We analyze break-even conditions under which KV migration outperforms local re-prefill.
4. We report a real MLX-to-vLLM end-to-end validation with exact short-horizon decode fidelity.

2 System Architecture

PermeantOS operates as a sidecar daemon alongside model inference runtimes. The migration pipeline follows a structured lifecycle:

1. **Capability exchange:** source and target negotiate model identity, attention mechanics, context length, and target allocation limits.
2. **Warm-start evaluation:** the orchestrator evaluates whether migration should beat local re-prefill.
3. **Extraction:** source adapters extract key-value tensors from active runtime caches.
4. **Transpilation and quantization:** tensors are converted from runtime-specific physical layouts into canonical USXF form and optionally transfer-quantized.
5. **Security wrapping:** the header and tensor chunks are sealed with an encrypt-then-sign envelope.
6. **Streaming:** payloads are sent as length-prefixed frames with CRC checks.
7. **Target injection:** the target decrypts, reshapes, allocates runtime KV blocks, writes migrated tensors, and attaches decode metadata.
8. **Two-phase commit:** validation succeeds or the migration is aborted before target activation.

In the validated vLLM path, PermeantOS allocates target KV blocks, writes migrated key/value tensors directly into physical cache slots, and seeds vLLM prefix-cache metadata so the next decode request attaches to the migrated prefix.

3 USXF v1.1 Specification

USXF separates at-rest archival snapshots from active wire-streaming envelopes. At rest, a USXF state may be serialized as a tensor archive plus JSON metadata. On the wire, USXF is streamed as length-prefixed JSON command frames followed by binary tensor chunks.

3.1 Metadata Header

The metadata header describes model identity, attention structure, sequence length, tensor dtype, transfer quantization, block hashes, and security metadata. A representative header is shown below:

```
{
  "usxf_version": "1.1",
  "model_architecture": "Qwen2.5-0.5B-Instruct",
  "attention_type": "gqa",
  "model_cache_spec": {
    "n_layers": 24,
    "n_q_heads": 14,
    "n_kv_heads": 2,
    "head_dim": 64,
    "max_position_embeddings": 32768
  },
  "seq_len": 2016,
  "batch_size": 1,
  "dtype": "bfloat16",
  "transfer_quantization": {"scheme": "none"},
  "block_size": 256,
  "block_hashes": ["sha256:..."],
  "checksum": "sha256:... ",
  "signature": "ed25519:... "
}
```

4 Layout Transformation

The core mathematical challenge is mapping between a canonical sequential layout and target blocked layouts used by paged attention runtimes.

4.1 Canonical Sequential Layout

USXF stores extracted key and value tensors for each layer in sequential representation:

$$K_{\text{canon}} \in \mathbb{R}^{S \times H_{\text{kv}} \times D_{\text{head}}}, \quad (2)$$

$$V_{\text{canon}} \in \mathbb{R}^{S \times H_{\text{kv}} \times D_{\text{head}}}, \quad (3)$$

where S is sequence length, H_{kv} is the number of KV heads, and D_{head} is the head dimension.

4.2 Blocked Target Layout

For a block size B , key states in a vLLM-like blocked layout can be represented as:

$$K_{\text{vllm}} \in \mathbb{R}^{M \times H_{\text{kv}} \times D_{\text{head}} \times B}, \quad (4)$$

where $M = \lceil S/B \rceil$. The canonical coordinate (s, h, d) maps to blocked coordinate (m, h, d, b) as:

$$m = \lfloor s/B \rfloor, \quad b = s \bmod B. \quad (5)$$

Thus:

$$K_{\text{vllm}}[m, h, d, b] = K_{\text{canon}}[s, h, d]. \quad (6)$$

Value states are commonly arranged as:

$$V_{\text{vllm}} \in \mathbb{R}^{M \times H_{\text{kv}} \times B \times D_{\text{head}}}, \quad (7)$$

with:

$$V_{\text{vllm}}[m, h, b, d] = V_{\text{canon}}[s, h, d]. \quad (8)$$

5 Security Architecture

AI agent memory may contain user text, tool outputs, private documents, and derived activations. PermeantOS therefore treats migration payloads as sensitive by default.

The transfer envelope follows an encrypt-then-sign construction:

1. Encrypt the header and payload using AES-256-GCM with a fresh nonce.
2. Sign ciphertext and nonce using Ed25519.
3. Stream frames with CRC checks for corruption detection.
4. Verify signature before decryption on the target.

The orchestrator also enforces resource policies such as maximum concurrent migrations and target allocation limits.

6 Performance and Break-Even Analysis

The warm-start decision evaluates:

$$T_{\text{transfer}} \leq \gamma \cdot T_{\text{prefill}}, \quad (9)$$

where $\gamma = 0.7$ is a conservative savings margin.

Network transfer time is modeled as:

$$T_{\text{transfer}} = \frac{8 \cdot S_{\text{bytes}}}{B_{\text{network}}} + \delta, \quad (10)$$

where S_{bytes} is payload size, B_{network} is bandwidth in bits per second, and δ is fixed handshake overhead.

Prefill time is modeled as:

$$T_{\text{prefill}} = \alpha S + \beta S^2. \quad (11)$$

6.1 Transition Analysis

For a Llama-3.1-8B-style cache with 32 layers, 8 KV heads, 128 head dimension, and BF16 precision, Table 1 gives illustrative transfer and prefill comparisons.

Under these assumptions, migration becomes attractive at contexts of approximately 32k tokens and above on 25 Gbps links with FP8 transfer quantization.

Context	BF16 cache	FP8 cache	10 Gbps	25 Gbps	Prefill
8,192	536 MB	268 MB	0.364 s	0.235 s	0.122 s
16,384	1.07 GB	536 MB	0.578 s	0.321 s	0.324 s
32,768	2.14 GB	1.07 GB	1.008 s	0.493 s	0.972 s
65,536	4.29 GB	2.14 GB	1.860 s	0.835 s	3.220 s
131,072	8.58 GB	4.29 GB	3.580 s	1.523 s	11.610 s

Table 1: Illustrative break-even analysis for KV migration versus re-prefill.

7 Real-Runtime End-to-End Validation

We validated PermeantOS against real source and target runtimes using an Apple Silicon laptop as the source host and an AWS GPU VM as the target host.

7.1 Experimental Setup

The source host ran MLX with Qwen/Qwen2.5-0.5B-Instruct. The target host was an AWS `g4dn.xlarge` instance running vLLM 0.23.0 with the same model. PermeantOS exported a 2016-token source prompt/cache, streamed the encrypted migration over an SSH-tunneled daemon connection, registered target KV blocks, seeded vLLM prefix-cache metadata, and generated a post-migration continuation from the migrated prefix.

The target context length was kept below the 2048-token model window to leave room for a 16-token validation continuation. An earlier run using a 2032-token source prefix produced an apparent mismatch after 11 tokens; analysis showed the target had reached its context limit and stopped early.

7.2 Results

These results validate the core live migration chain: MLX extraction, USXF transport, complex Agent Memory Graph transaction binding, target allocation, target KV write, hash validation, prefix-cache attachment, post-migration decode reuse, reverse vLLM-to-MLX runtime-state import, target-side graph activity resume, and origin return-home graph continuation. The result is intentionally scoped: it demonstrates exact fidelity for one model family and a 16-token continuation horizon using experimental lossy QATQ transfer. The latest graph package contained 27 nodes, 25 edges, four packaged artifacts, memory/retrieval state, credential rebinding requirements, and pending tool policy. After migration, the AWS target exported its target-generated decode boundary through a live reverse runtime API with proof hash prefix `sha256:cc27...cce2f`. The origin MLX runtime imported that boundary, materialized MLX-native KV state for the 2032-token target-advanced prompt, generated a new continuation, and emitted proof hash prefix `sha256:a4f0...38d7`. The AWS target also imported the graph package, resumed retry-safe pending work, executed an explicitly approved publish write, wrote a new artifact, appended post-import graph evidence, and emitted a proof hash. The origin then verified the AWS-updated graph/report/artifact evidence, wrote a new continuation artifact from that returned state, and emitted a round-trip graph proof hash.

A matched FP8 transfer-quantized run on the same graph-attached MLX-to-AWS-vLLM path reduced transferred bytes from 50,331,648 to 12,582,912 while preserving exact 16-token source/post-migration continuation fidelity. The measured transfer phase improved from 72.790 seconds to 63.020 seconds. Total migration time improved modestly, from 396.127 seconds to 389.690 seconds,

Metric	Result
Run ID	20260620-210358
Manifest	migration-20260620-211207-46427-manifest.json
Source runtime	MLX on Apple Silicon
Target runtime	vLLM 0.23.0 on AWS g4dn.xlarge
Model	Qwen/Qwen2.5-0.5B-Instruct
Migrated prefix length	2016 tokens
Transfer quantization	experimental qatq
Agent Memory Graph binding	27-node complex package aligned and resumed on target
Layer count	24
Hash validation	Passed
Slot-probe max key diff	0.006696999999999065
Slot-probe max value diff	0.0005581499999999813
vLLM prefix-cache seeded blocks	16
Source vs. post-migration decode	Exact match for 16 generated tokens
Target baseline vs. post-migration decode	Exact match for 16 generated tokens
Reverse runtime import	vLLM export API to MLX origin continuation
Target-side agent activity resume	Completed read-only and approved publish work
Post-resume proof hash	sha256:b066a1dba9ed250eb54e1344c8d0092d8ad2d90dfe68bbfc1a
Origin return-home continuation	Verified AWS evidence and wrote origin continuation
Round-trip proof hash	sha256:052add6058521a13902515f759499b1350d5be4055d070d4e5
Cleanup	AWS instance, security group, and key pair deleted

Table 2: Real MLX-to-vLLM end-to-end validation result.

because the cold disposable-host validation path is dominated by target commit/runtime attachment and vLLM initialization effects. Strict sampled slot equality failed under FP8 as expected for a lossy codec, with measured max sampled key/value delta of 0.0125.

The latest QATQ run reduced transferred bytes further to 6,294,528 from a 49,545,216-byte uncompressed KV payload, a compression ratio of 0.12704613095238096. QATQ is not numerically lossless: sampled slot probes reported maximum key/value deltas of 0.006696999999999065 and 0.0005581499999999813 respectively in the reverse runtime round-trip run. The validation claim is therefore bounded lossy transfer with exact observed decode fidelity over the configured short-horizon continuation, reverse runtime import, plus target-side and origin return-home Agent Memory Graph activity continuation.

8 Agent Memory Graph Roadmap

KV cache migration is necessary but not sufficient for full agent migration. A complete agent migration system must also preserve conversation turns, tool calls, tool results, files, retrieval memories, pending actions, provenance, and policy. PermeantOS therefore treats KV cache as one artifact within a future Agent Memory Graph.

The planned graph layer will include:

- message, tool-call, tool-result, artifact, memory, and plan nodes;
- causal, reference, produced, consumed, supersedes, and resumes edges;

- token-span mappings between graph nodes and KV cache ranges;
- idempotency keys and resume policies for pending tool calls;
- per-node hashes, graph-level checksums, and provenance signatures.

This layer will make it possible to migrate not merely model activations, but the structured continuity state of an agent.

9 Related Work

PermeantOS is related to paged attention and serving systems such as vLLM [2, 5], Apple Silicon runtime work such as MLX [1], distributed KV cache systems such as LMCache [4], and cache compression systems such as CacheGen [3]. It is also influenced by broader inference-serving systems work [6]. PermeantOS differs by targeting cross-hardware, cross-runtime state exchange with cryptographic manifests and an explicit migration protocol.

10 Limitations

The current system is a research preview. The real-runtime validation covers one model family, one source runtime, one target runtime, complex Agent Memory Graph transaction binding, target-side resume, reverse vLLM-to-MLX runtime-state import, origin return-home graph/artifact continuation, and a 16-token continuation horizon. The vLLM adapter uses internal implementation details that may change across vLLM versions. Cloud-host validation is currently dominated by cold installation and warmup costs unless prewarmed images are used. Durable target-side graph session storage, broader runtime coverage, broader reverse runtime coverage, and longer-horizon quantized-transfer fidelity evaluation remain future work.

11 Conclusion

USXF and PermeantOS provide a concrete path toward portable, verifiable AI agent state. The current prototype demonstrates that a real MLX source cache and complex Agent Memory Graph package can be migrated to a real vLLM target, written into target KV storage, attached through prefix-cache metadata, decoded with exact short-horizon fidelity, exported back through a live target reverse runtime API, imported into MLX as target-advanced runtime state, resumed on the AWS target with new policy-governed agent activity, returned to the origin as graph/artifact evidence, and continued on the origin from that remote proof. This result supports the broader thesis that AI agent state should be treated as migratable infrastructure rather than runtime-local ephemera.

References

- [1] Apple Machine Learning Research. MLx: An array framework for apple silicon. <https://github.com/ml-explore/mlx>, 2023.
- [2] Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the ACM Symposium on Operating Systems Principles*, 2023.

- [3] Yuhan Liu et al. Cachegen: Kv cache compression and streaming for fast large language model serving, 2024. Preprint.
- [4] LMCache Project. Lmcache: Efficient kv cache management for large language model serving. <https://github.com/LMCache/LMCache>, 2024.
- [5] vLLM Project. vllm: Easy, fast, and cheap llm serving with pagedattention. <https://github.com/vllm-project/vllm>, 2023.
- [6] Lianmin Zheng et al. Lmsys chatbot arena and large language model serving infrastructure, 2024. Project and systems documentation.