

Insights on the use of WRF in Cloud Systems

Diego A. Pérez Montes < kabute@uvigo.es >
Juan A. Añel Cabanelas < j.anel@uvigo.es >
Javier Rodeiro < jrodeiro@uvigo.es >

Prior Work

- Running large ensembles for ClimatePrediction.net (CPDN) on different public cloud providers [1] [2]

Montes et al. - Enabling BOINC in infrastructure as a service cloud system. Geoscientific Model Development, 2017

Añel et al. - Evaluation and intercomparison of Cloud Computing solutions for climate modelling. 2018. Submitted to PLoS ONE.


What? (Current Goals)

- Run WRFv3 on heterogeneous and dynamic (and ephemeral!) environments (e.g. Cloud).
- Run over Berkeley Open Infrastructure for Network Computing (BOINC).
- Fully Automated pipeline (Build → Computation).


Why?

- WRF popularity and it is Free Software.
- Add more possibilities on how to run WRF.
- Add the ability to run on the Cloud where no “local” HPC available.

Proposed Architecture



Pipeline



Some Implementation Details...

WRF:

- MPICH3, NetCDF4 and GCC/GFortran 4.9 (x86_64 Linux)
- Modified configurators and Makefiles.
- Static compilation: big binaries > 40MB

Some Implementation Details...

Infrastructure:

- Based on (very modified) images by Marius Millea [3].
- docker-compose and kubernetes
- Ran over instances but could be done over PaaS like GKE.

Work In Progress: Automation/UI

- Tweaks on pipeline automation.
- Improving BOINC Validation and Assimilation stages.
- UI Integration for workunit generation (e.g. variable perturbations).

Conclusions

- Completed a functional pipeline for WRF over BOINC.
- BOINC seems to be an adequate middleware for WRF distributed computing.
- Volunteer computing addition is going to present interesting challenges.

Thank You!

(Further discussion on Screen 11)

Appendix

Some Implementation Details...

BOINC:

- Big results and workunits.
- WRF needs/expects all input files on the slot (*<copy_file/>*)
- Running Inside the Wrapper (App).
- Target: x86_64-pc-linux-gnu

Running

```
===== Applications =====
1) -----
   name: wrf_full
   Project: boinc_wrf

===== Application versions =====
1) -----
   application: wrf_full
   version: 1.00
   project: boinc_wrf

===== Workunits =====
1) -----
   name: wrf_full_567_1523217695.675265
   FP estimate: 3.600000e+12
   FP bound: 8.640000e+13
   memory bound: 476.84 MB
   disk bound: 953.67 MB
2) -----
   name: wrf_full_515_1523217549.609134
   FP estimate: 3.600000e+12
   FP bound: 8.640000e+13
   memory bound: 476.84 MB
   disk bound: 953.67 MB
3) -----
   name: wrf_full_507_1523217382.011911
   FP estimate: 3.600000e+12
   FP bound: 8.640000e+13
   memory bound: 476.84 MB
   disk bound: 953.67 MB
4) -----
   name: wrf_full_575_1523217696.006498
   FP estimate: 3.600000e+12
   FP bound: 8.640000e+13
   memory bound: 476.84 MB
   disk bound: 953.67 MB
```

References

- [1] *Enabling BOINC in infrastructure as a service cloud system*. D Perez Montes, et al. - Geoscientific Model Development, 2017
- [2] *Use of several Cloud Computing approaches for climate modelling: performance, costs and opportunities*. D Perez Montes, et al. - EGU General Assembly Conference Abstracts, 2017
- [3] Boinc Server Docker, Millea M. , <https://github.com/marius311/boinc-server-docker/>
- [*] Front image by: [Victor Hermida Prada](#)