

NUMPY, MATPLOTLIB example

kacper.topolnicki@uj.edu.pl

Abstract

This directory contains a simple script, `compress.py`, that demonstrates the use of the `numpy` and `matplotlib` libraries. The code implements a simple compression method for binary images.

Running the script

To run the script simply navigate to this directory in the terminal and run:

```
<user> $ python compress.py
```

Alternatively you can make the script executable and run:

```
<user> $ ./compress.py
```

Comments

Comments can be added to *python* code using the `#` symbol. Any text following this symbol will be ignored by the *python* interpreter. If you take a look at `compress.py` you will notice that some comments begin with `#@`. This has no special meaning for *python* but these types of comments are read by an external program that generated this documentation.

Importing the libraries

The script begins with two import statements in [compress.py line: 55] :

```
import numpy
import matplotlib.pyplot as plt
```

The first line imports the `numpy` library. The second line imports the `pyplot` plotting functions from the `matplotlib` library and the code will refer to these functions using the shorthand `plt`.

Loading the binary image

In our example we will be working with a 720 by 1280 image. The individual pixels in this image will contain one of two values : 0 , 1. This means that 921600 bits or 115200 bytes are used to represent the image. The image data is stored in `image.npy` in a special format designed to store `numpy` arrays. This file was created using the `numpy.packbits` function and you can verify that it is almost exactly 115200 bytes long.

The file is loaded and stored in variable `a` in [compress.py line: 113] :

```
a = numpy.load("image.npy")
```

and next it is unpacked (we might cover packing and unpacking during the course) in [compress.py line: 116] :

```
a = numpy.unpackbits(a)
```

Information about `a` is printed to the standard output in [compress.py line: 120] :

```
print("a.shape : " , a.shape)
print("a.dtype : " , a.dtype)
```

The first print statement will result in:

```
a.shape : (921600,)
```

which means that we are dealing with a one dimensional array of size 921600. This is used in [compress.py line: 125] :

```
length = a.shape[0:1]
```

to assign the length of `a` to a variable. The second print statement will result in:

```
a.dtype : uint8
```

from which we can gather that all values in this one dimensional array are unsigned 8-bit integers.

The unpacked array of unsigned 8-bit integers can be saved to a file. This is done in [compress.py line: 129] :

```
numpy.save("image_unpacked" , a)
```

and the resulting file `image_unpacked.npy` contains 921728 bytes. This is almost eight times more than `image.npy`.

Compression method

The idea behind the compression method is simple. More formally the algorithm that will be implemented belongs to a family of *run time compression* algorithms.

Since the data we are working with is just a string of 0, 1 :

```
0 1 1 1 1 1 1 1 0 1 1 1 0 0 0 0 0 0 0 1 ...
```

it will be represented by the lengths of sequences of ones and zeros that appear the sequence:

```
1 8 1 3 8 ...
```

This information together with the value of the first element of the sequence :

```
0
```

can be used to reconstruct the original image.

The value of the first element of **a** is assigned to a variable in [compress.py line: 184] :

```
first = a[0:1]
```

Notice that the variable **first** points to a **numpy** array and not a single value. This array was created by taking a segment of **a** (**a**[0:1]), that is elements with indexes greater or equal to 0 and less than 1. This means that **first** is a one dimensional array with one element - the first value in **a**. The choice to use an array with a single element instead of a single value will be useful later when **first** will be concatenated with other arrays.

In order to obtain a lengths of sequences for the compression algorithm first a list of indexes with non zero elements (ones) is created and assigned to a variable in [compress.py line: 188] :

```
nonzero = numpy.nonzero(a)[0]
```

The next lines [compress.py line: 192] :

```
start = numpy.nonzero((numpy.roll(nonzero,1) + 1) - nonzero)[0]
end = numpy.nonzero((numpy.roll(nonzero,-1) - 1) - nonzero)[0]
ones = end - start + 1
```

result in the variable **ones** containing a list of lengths of 1 , 1 , 1 , ... sequences in **a**. This code uses a combination of **numpy** functions. The reader is encouraged to try this code out in **ipython** and read the documentation on these routines. The next lines of code [compress.py line: 198] :

```
ai = 1 - a
```

```
nonzero = numpy.nonzero(ai)[0]
```

```
start = numpy.nonzero((numpy.roll(nonzero,1) + 1) - nonzero)[0]
end = numpy.nonzero((numpy.roll(nonzero,-1) - 1) - nonzero)[0]
zeros = end - start + 1
```

result in the variable **zeros** containing a list of lengths of 0 , 0 , 0 , ... sequences in **a**.

Compressed data

All the data necessary to reconstruct the original image is concatenated in [compress.py line: 221] :

```
data = numpy.concatenate(
    (
        length ,
        first ,
        zeros.shape[0:1] ,
        zeros ,
        ones.shape[0:1] ,
        ones
    ))
```

In order to further save space, this array is rewritten using unsigned 32-bit integers in [compress.py line: 233] :

```
data = data.astype("uint32")
```

Finally the data is saved to `image_compressed.npy` in [compress.py line: 244] :

```
numpy.save("image_compressed" , data)
```

Notice that the size of this file is only 20892 bytes.

Reconstructing the original image

Now it is time to check if it is possible to reconstruct the original image from `image_compressed.npy`. In the first step this file is loaded from disk [compress.py line: 258] :

```
comp = numpy.load("image_compressed.npy")
```

Next in [compress.py line: 278] :

```
l = comp[0]
f = comp[1]
zs = comp[2]
z = comp[3 : 3 + zs]
os = comp[3 + zs]
o = comp[3 + zs + 1:]
```

the

- length of `a`
- first element
- length of list with 0 0 0 ... sequence lengths
- list of 0 0 0 ... sequence lengths
- length of list with 1 1 1 ... sequence lengths
- list of 1 1 1 ... sequence lengths

are assigned to variables.

Next in [compress.py line: 297] :

```
rif = numpy.empty(zs + os , dtype = z.dtype)
val = numpy.empty(zs + os , dtype = z.dtype)
```

```
if(first == 0):
    rif[0::2] = z
    rif[1::2] = o
    val[0::2] = 0
    val[1::2] = 1
else:
    rif[0::2] = o
    rif[1::2] = z
    val[0::2] = 1
    val[1::2] = 0
```

two, initially empty, `numpy` arrays are created. `rif` will contain interwoven 0 0 0 ... and 1 1 1 ... sequence lengths and `val` will contain the values (0 or 1) associated with the corresponding sequence length. Note the `[0::2]` and `[1::2]` operators used for achieve this. They allow assigning values to every second element of a `numpy` array starting with the first (index 0) or second (index 1) element.

The original array is reconstructed in [compress.py line: 324] :

```
reconstruct = numpy.repeat(val , rif)
reconstruct = reconstruct.astype("uint8")
```

and tested against the original array `a` in [compress.py line: 329] :

```
print("test against original : " ,
      numpy.array_equal(a , reconstruct))
```

using the `numpy.array_equal` function.

Drawing the images

In [compress.py line: 354] :

```
fig , axs = plt.subplots(2)
```

a plot containing two subplots is created. One subplot will contain the original image and the other one will contain the reconstructed image. In order to draw the images, the one dimensional arrays have to be reshaped first in: [compress.py line: 358] :

```
img_compressed = a.reshape((720 , 1280))
img_reconstruct = reconstruct.reshape((720 , 1280))
```

Finally in [compress.py line: 363] :

```
axs[0].imshow(img_compressed)
axs[1].imshow(img_reconstruct)
plt.show()
```

the arrays are plotted and shown.