DEPARTURE FROM THE PHOTON BASELINE: PAPER 11.5

THE INTRINSIC ILLUSION

A Structural Critique of Inherent Properties in Standard Particle Ontology

By: Dervis Kadunic

2026 — v26 (2026-10-18)

ABSTRACT

The Standard Model of particle physics assigns properties to particles as intrinsic possessions: the electron has charge −e, has spin-1/2, has mass 511 keV. The grammar is possessive; the ontology is substantive. Properties are treated as things a particle carries with it, independent of any encounter, any apparatus, any tick of any ledger.

Paper 11 proved the relational role theorem: no configuration is intrinsically active or passive — roles are (aspect, tick, encounter) functions, and the same aspect that satisfies the predicate at one tick fails it at another. This paper turns that theorem outward as a critique. If nothing in the native ledger is intrinsically anything, then the Standard Model's intrinsic-property ontology is either false or untestable — and we audit which.

Method. Six property classes — charge, spin, mass, color, flavor, magnetic moment — are examined in three columns: the textbook "intrinsic" statement, what the measurement procedure actually does, and where the encounter-indexing enters. In all six cases, the property is encounter-indexed in practice and intrinsic only in prose. The word "intrinsic" does no work in any derivation; it enters only in the gloss.

Historical context. This is not a new objection. Whitehead named it the fallacy of misplaced concreteness in 1925 (Science and the Modern World). Bohr's complementarity made properties contextual to experimental arrangement. Heisenberg questioned whether particles are "things" at all. Bohm, Bell, Mach, Cartwright, and van Fraassen each attacked a different face of the same reification. §2 documents their dissent with verified quotes — the physicists who saw what the Standard Model was becoming and said so.

Scope. This paper critiques the ontological gloss — the intrinsic-property idiom — not the Standard Model's predictive apparatus. The cross-sections are not in dispute. What is in dispute is whether "the electron has spin-1/2" describes a possession of the electron or a regularity of electron-encounters. The audit finds: always the latter, claimed as the former.

Verdict. "Intrinsic property" is a category mistake institutionalized as ontology. Nothing measured is ever measured without an encounter; nothing called "intrinsic" survives the removal of the encounter that defines it. The audit's 0/6 (H.2) is a summary of the §3 prose audit in machine-recorded form — an honest null, not a second independent machine result: no theorem of the SM has the "derive encounter-independence" shape, so the null is expected, and its value is as a published record. H.1's "smuggled" verdicts are the author's hand-typed classifications, machine-printed — the §3 argument in record form, not a derivation the machine performed.

What this paper adds to Papers 9.5 and 10.5. Paper 9.5 contrasted the borrowed thermometer (statistical temperature, patched ledger) against heat as interaction events — and showed the patching was the tell. Paper 10.5 contrasted continuum mechanics (assumed smoothness, hardware limits ignored) against the discrete ledger — and showed the assumption was the tell. This paper applies the same method to particle ontology: it places the standard model's equations beside the standard model's prose, and shows they disagree. The equations are encounter-indexed (renormalization scale, gauge invariance, CKM basis rotation, Bell violations, loop sums, Higgs VEV). The prose claims intrinsicality. The disagreement is not subtle — in three cases (Bell for local models, Elitzur, CKM) the equations refute the prose. The paper's contribution is not a new formalism but a refusal to look away from what the existing formalism already says. Paper 11's Level A results (relational role theorem, structural insulation — and its declared axiom, aspect aggregation, carried here as [LEVEL A, author-authorized] with stated falsifiers, Appendix E.5) provide the native-ledger vocabulary for stating what the standard equations imply but do not say.

Reading guide. §1 states the charge. §2 documents the historical dissent — five witnesses with verified quotes, complications disclosed. §2.7 traces the historical arc of how the intrinsic idiom took over. §3 performs the six-property audit at equation level: four moves per property (textbook claim → equation breakdown → inference chain → Paper 11 Level A counterpart). §4 sharpens the contrast (9.5-style): their derivation vs. our derivation, step by step, counting unearned steps. §5 exhibits the five-step reification mechanism with worked examples. §6 states the falsification condition. §7 answers nine steelmanned objections. Appendices carry the heavy mathematics (B), the full quote bank (A), figure plans (C), revision history (D), and the Paper 11 Level A claim map (E).

0.5 EPISTEMIC ARCHITECTURE

This paper applies Paper 11's verification discipline to the Standard Model's "intrinsic property" claims. This section defines the machinery — badges, dependency labels, firewall rules, and the script protocol — so the audit's verdicts are mechanically checkable, not rhetorically asserted.

0.5.1 Badge definitions

Every claim in this paper carries an epistemic badge:

- [LEVEL A]: Machine-checked (script exits 0), or inherited from a cited source paper's Level A result with lineage cited (Appendix E), or prose-proved with no gaps. The strongest

claim this paper makes.

- [LEVEL B]: Illustration, conditional reading, or author-authorized

declaration. Honest but weaker — the dependence is stated.

- [LEVEL C]: Deferred to a later paper. Not claimed here.
- [NO BADGE]: Cannot be derived, not declared as assumption. Under Paper 11's

D.2 rule: conjecture — do not cite as established.

- [LEVEL A, author-authorized]: the declared-axiom subtype of Level A —

declaration-backed, not derivation-backed. It guarantees exactly three things: (1) the declaration was made, by the author, in the open — its content, date, and location are recorded; (2) the declaration is traceable — the inheritance line (§0.5.6) names the source paper, the section, and the registry row where the declaration is recorded; (3) the declaration is stable — downstream claims carry the subtype with it, so the declared character cannot be laundered into "proved" by distance. It does NOT guarantee independent derivation, a machine check, or that the declaration could not be otherwise. A claim wearing this badge is an honestly labeled declared axiom — citable, checkable, and never to be called a proved fact. It outranks [LEVEL B] (conditional, illustrative, or otherwise unstaked) and is outranked by plain [LEVEL A] (derived or machine-checked). Every [LEVEL A, author-authorized] badge states its falsifiers — concrete, checkable conditions under which the declaration fails, stated where the claim is badged or cited at the badge site. A declaration with no stated failure condition is an assertion, not a badged claim. Where no genuine falsifier can be stated, the limit is stated explicitly instead — never invented.

Denied [Level A] is a verdict returned at Level-A rigor — not a weaker grade of endorsement. It marks a claim put through Level A treatment (machine check, inherited Level A result, or gapless prose proof attempted) whose examination returned a negative verdict: the bracketed [Level A] names the rigor of the examination, and Denied is the verdict. It is not Level B or C — those are grades of endorsement, weaker or deferred; a denial is not an endorsement at any strength, and rebadging it B or C would misrepresent denial as a dimmer endorsement. The phrasing is deliberate and author-authorized: the badge refuses to let a denial be misread as a weak claim. In this paper exactly one claim wears it — the blanket thesis "Particles have intrinsic properties," denied in §4.3 on the strength of the H.1/H.2 audit treatment: H.1 returns 0/6 — no SM property claim is derived as encounter-independent or declared as an assumption (none earns even Level C); the positive refutations (Bell for local spin models, Elitzur for color, CKM for flavor) show the equations themselves encounter-index what the prose calls intrinsic; H.2 records the honest null where the derivation task is ill-posed. Together they leave the blanket thesis with no route. The denial is the audit's verdict — the author's verdict, recorded as such — not a second machine output. This stands alongside the record below: the SM's six individual property claims earn NO BADGE because they are un-derived and un-declared; the blanket thesis is the distinct claim examined at Level A, and denied.

Hybrid claims — partly machine-checked, partly declared — are marked by listing both badge components explicitly: [LEVEL A: MACHINE / AUTHOR] (alternative form [LEVEL A-M / LEVEL A-A]). The marking keeps the claim's overall Level A status and tells the reader at a glance which half is which: the computational content was script-verified (MACHINE), while the foundational premise — or the identification that gives the computation its label — was author-declared (AUTHOR). The halves do not cover each other. The MACHINE half carries the script-validation discipline (§0.5.5): the badge is exactly as wide as its validation artifact, and the machine result is never read as proving the declared identification. The AUTHOR half carries the declared-axiom discipline (§0.5.1 subtype rule): stated falsifiers where

genuine ones exist, stated limits otherwise — never invented — and the identification never extends the machine content. In this paper two claims wear the hybrid mark: E.7 SCALE_FIDELITY and MC.1's −1.9886 headline. Status versus coverage: "overall Level A status" is rank — the claim is not demoted to [LEVEL B] for its declared half. Coverage is narrower: per §0.5.6 rule 2, the [LEVEL A] covers exactly the machine-checked content; the AUTHOR half is carried under the declared-axiom discipline, never under the machine badge. The mark splits; it does not average.

Rule (author-authorized 2026-10-18 — framework-wide, from now on, in every paper): wherever the paper presents an approximation, a rounding, or a translator as its number for a badged claim, it is [LEVEL B] — honestly labeled with why it was made — and the real number is specifically badged right beside it. Nothing the paper badges is rounded silently; the approximation never stands in for the number, and the number never hides behind the approximation. A translator earns its keep only beside the real thing. (Incidental '≈' in expository prose is notation, not the paper's badged number, and is out of scope.)

Precision convention. Badged numbers print at fixed decimals (−1.9886 at 4dp); the machine's full computed value is stated where the rounding is load-bearing (MC.1's −1.9885612518827713, §11.4). The printed form is presentation, not a second approximation of the claim.

The audit's central record is that the SM's six "intrinsic property" claims earn NO BADGE under this discipline (H.1), while Paper 11's counterparts earn LEVEL A (Appendix E). H.2's 0/6 is not a second independent machine verdict — it is the honest-null record of where the §3 prose audit's chains bottom out (§0.5.5, §8.2). The task is ill-posed: no theorem of the SM has the "derive encounter-independence" shape, so the null is expected — its value is as a published record, not a surprise.

0.5.2 Dependency labels

Each Level A claim lists its dependencies as bracketed labels:

- [L1]: The standard formalism's equations (Dirac, QCD, CKM, RG, g−2) —

taken as given for the audit's purposes. The critique does not dispute them.

- [L2]: Paper 11 v69 Level A results (relational role theorem, structural

insulation, etc.) — inherited with lineage (Appendix E).

- [L3]: Historical sources (Whitehead 1925, Heisenberg 1958, etc.) —

verified quotes (G.1).

- [L4]: Textbook sources (Griffiths, Peskin & Schroeder, PDG) — the

critiqued positions, verified (G.3).

- [L5-11.5]: This paper's own definitions (encounter-indexing, the

reification mechanism, the honesty criteria).

Bridge rule (from Paper 10.5): L_claim ≤ min(L_i) — a claim cannot outrank its weakest dependency.

0.5.3 The firewall (FW.1)

Paper 11's F.42 enforces Stage-N vocabulary discipline. Paper 11.5's FW.1 enforces three analogous disciplines on this paper's own text:

- Group A: No positive ascription of "intrinsic" in the paper's own voice.

The paper critiques the term; it must not use it assertorically.

- Group B: No continuum language ("at a point" / "at every point", "smooth",

"continuous", "infinitesimal", "differentiable", "in the limit") grounding property ascriptions. The paper identifies the continuum as the enabler (§9); it must not lean on it.

- Group C: No possessive reification ("the electron's spin") in the paper's

voice. The paper identifies possessive grammar as reification step 3 (§5).

Exemption breadth — a design decision with rationale. FW.1 exempts mention of banned language from use of it; the exemptions are structural (where the text is, not what it says), fail-closed where a violation is still possible. (i) Quoted-context exemptions (Groups A, C): blockquote lines and "Textual evidence" spans are the SM claim being critiqued, not the paper's voice — policing them would forbid quoting the target; Group C adds a quoted-span test with delimiter-quote counting (word-internal apostrophes are not delimiters). (ii) Critical-window tokens (Group A): a ±2-line window around an "intrinsic" hit containing critical tokens ("not intrinsic", "refut", "smuggl", "versus", ...) exempts it as negative/critical use — the thesis requires negative uses, and a rebuttal's negation can sit on a neighboring line in markdown; a wider window would let distant negation wash a positive ascription. The residual risk — a genuinely positive ascription adjacent to critique prose — is human-audit territory, stated here rather than hidden. (iii) Group B window sizes (30/50/10-line lookbacks for history, appendix, and firewall-doc contexts) are heuristic and recorded in the script so a reader can see the floor. (iv) The changelog exemption is fail-closed: a changelog line is exempt only if it is an Appendix D entry and the matched pattern is quoted on that line — an unquoted ascription in a changelog entry stays caught. (v) The Group A sentence-pattern gate. Only a line matching `is/are` + "intrinsic" can breach Group A — the gate is the code's shape, now stated: adjectival forms ("carries intrinsic charge", "has intrinsic spin") never trigger it. The six §3 (a)-lines are the audit's designated textbook-claim statements, so their silence is semantics-preserving: each quoted sentence is mention (the quoted-token test), and the one unquoted gloss ("the electron's intrinsic properties", §3.1(a)) passes through the gate rather than through any exemption. Residual risk, stated: an unquoted adjectival ascription in the paper's own voice would pass the gate silently — zero live instances in v23, human-audit territory. (vi) The Group C quoted-"intrinsic" exemption. A possessive hit is exempt when its line contains "intrinsic" in quotes anywhere on the line — mention-not-use: such a line discusses the idiom, not the paper's own ascribing voice (e.g. "the electron's spin" glossed inside a sentence quoting "intrinsic"). Residual risk, stated: a genuine ascription sharing a line with a quoted "intrinsic" would slip through — zero live instances in v23, human-audit territory.

FW.1 scans all 11,003 lines. Zero breaches = the paper practices what it preaches.

0.5.4 Script protocol

Twenty-one scripts in five series:

Series	Scripts	Function
G.1–G.4	Quote integrity, contrast completeness, no-strawman, terminology	Paper's own hygiene
H.1–H.4	SM badge audit, derivation attempt, verdict-layer consistency, honesty comparison	Audit machinery
P.1–P.10	Stern-Gerlach, Bell-CHSH, R-ratio, RG running, CKM basis, Casimir frames, g−2 flagship, mass scheme, ternary/tether Bell analysis (schematic tether), g−2 loop spectrum	Executable physics
FW.1, PA.1	Firewall, parsing agent	Self-policing + mechanical reader + divergence ratio
MC.1	Shell-count Monte Carlo	Structural MC: inverse-square from shell counting (fitted-exponent headline [LEVEL A: MACHINE / AUTHOR], v24 rulings)

All scripts exit 0 on success. H.2 is an honest null result (0/6 derived) — the failure is the finding, published per Paper 11's F.57 precedent. P.9's Part 2 is likewise a null (ternary local bound stays 2) — published, not buried. All scripts are embedded as listings in Appendix G; their outputs are published in §8.

0.5.5 What "machine-checked" means here — and what it doesn't

"Machine-checked" does not mean "proved by computer" in the Coq/Lean sense. This paper's scripts fall in two columns, and §8 is organized by them. COMPUTED: the claim's logical structure is implemented as executable code, the code runs without error, and the output matches the paper's stated verdict — P.1–P.6, P.7 blocks 1–2, P.8's spread exhibit, P.9 Parts 1–2, P.10's machine-derived counts (the 1- and 2-loop vertex-diagram counts; the 3–5-loop counts are cited-paper oracle), MC.1 step 1. For P.2: the CHSH violation is calculated (S=2.828), not quoted. v24: P.1–P.3, P.6, P.9, and P.10 run exact integer/rational arithmetic with no continuum machinery; P.4, P.5, P.7, P.8 run the SM's own equations with their continuum machinery intact and disclosed (CONTINUUM_USE in-script) — there the continuum is the exhibit, not scaffolding. MC.1 uses log-log least-squares (KEEP+DISCLOSED — the fitted exponent −1.9886 [LEVEL A: MACHINE / AUTHOR] is the headline because the number IS the fit; the exact-rational bound sits beside it as [LEVEL B] translator). CLASSIFIED: the H-series, the G-series, PA.1, P.7 block 3 (the leading-log soft-photon IR shift — declared assumption: leading-log only), and FW.1's voice judgments — the author's analytical classifications as inputs, printed by the script. For FW.1: the 11,003 lines are scanned, not eyeballed (counting convention: FW.1 splits on "\n", so the trailing newline yields a final empty element — the count is the newline count + 1; `wc -l` reports 11,002 newline-terminated lines — same text, not a discrepancy) — but the voice judgments (quoted SM claim vs. the paper's own voice) are the author's classification. The machine replaces hand-waving where it computes; where it classifies, it publishes the judgment for inspection, and replaces nothing.

Open disclosure (honesty requirement). H.2's GAP/REFUTED labels are author-written, then printed. H.2 is therefore an honest record of where each derivation bottoms out (F.57-style null publication), not an independent machine proof of the 0/6 verdict. What the machine does independently verify: H.2's chain validator (V1/V2) mechanically rejects a planted dishonest chain; P.1–P.10 compute real quantities (P.7 block 3 under the declared leading-log assumption); FW.1's mutant battery proved it catches genuine violations (and exposed two real firewall bugs, fixed). The reader is told exactly which parts are computed and which are classified — no more, no less.

0.5.6 The badge inheritance rule — no silent Level A by distance

An inherited claim may not outrank its source. Every claim this paper inherits at Level A — from Paper 11, Paper 8, or anywhere else — carries an inheritance line in Appendix E:

Inheritance: Source: Paper 11 v69 §X.Y — badge carried at source: [LEVEL A] or [LEVEL A, author-authorized] — validation: the source's registry row (script id, or prose section, or author-authorized definition with date, as recorded there) — 11.5 reliance: <what this paper uses it for>.

The line is the traced, checkable validation path. The reader can open the cited source at the cited section and find the same badge with the same backing — no trust in the chain is required, only in the named registry rows.

Three hard rules govern the line:

1. The subtype propagates — the bridge rule. If the source's own registry records

the claim as an author-authorized declaration, the claim is carried here as [LEVEL A, author-authorized] with its stated falsifiers, never as bare [LEVEL A]. Inheritors cap at the declared level: distance does not convert a declared axiom into a proved fact, and no downstream module may silently upgrade it. In this paper that is two claims, in two distinct shapes: (a) ASPECT_AGGREGATION (Paper 11 v69 §7.3, ledger Lemma 2, declared 2026-10-05; "prose (§7.3) — no machine check" in the source registry). Prose must not call it "proved" or "derived." Its honest name is declared axiom. (b) MASS_AS_LEDGER (Paper 8 v2, Appendix E.8): badge-at-source [LEVEL A] author-authorized 2026-10-18 — but the authorization covers a prose-section derivation (Paper 8 v2 Appendix D names the proof: $E = m \cdot c^2$, the Lorentz factor, c-unreachability, and the minimum mass quantum derived from the §2 definitional anchor; no machine check exists, none claimed), not a bare declaration. Its honest name is prose-derived at source, author-authorized at source. Shape (b) is expressly excepted from the "never as bare [LEVEL A]" bar by author authorization (2026-10-18): the author prescribed this carriage when he created Paper 8 v2's Appendix D to supply the badge-at-source. The exception is recorded here, not smuggled — and it sets no precedent: no future inheritor may cite shape (b) to upgrade a silent claim.

2. Hybrids are split, not averaged. Where a claim's content is partly machine-checked

and partly declared — SCALE_FIDELITY (Paper 11 v69 §0.5.v.3: the N-threshold sweep, the 6N monotonicity, and the exactness composition are F.56 machine-checked; the "fidelity := extent × exactness" identification is author-authorized, 2026-10-05) — [LEVEL A] covers exactly the machine-checked content, and the declared identification is disclosed in the line. The badge never covers more than its validation artifact.

3. Inline cites point to Appendix E; Appendix E carries the line. Every move-(d)

counterpart cite in §3 names its Appendix E entry; the entry carries the full inheritance line. Nothing inherits Level A from an inline cite alone.

1 THE INDICTMENT

1.1 What this paper does

This paper performs a structural audit of one word — intrinsic — as used in standard particle ontology. It examines six property classes, documents the measurement procedures that actually fix their values, and shows that in every case the property's determinacy depends on an encounter the "intrinsic" idiom elides.

It then contrasts the intrinsic-property framework against Paper 11's relational account (§4), traces the five-step reification mechanism by which bookkeeping becomes ontology (§5), and states the falsification condition that would vindicate intrinsic properties (§6).

1.2 What this paper does not do

It does not dispute any cross-section, branching ratio, or magnetic moment value. The numbers are not in question. It does not propose an alternative particle spectrum. It does not claim the Standard Model fails predictively — it claims the Standard Model's ontology fails descriptively, in a specific and auditable way.

1.3 Two ontologies

The dispute is between two complete accounts of what a particle property is.

Ontology A (intrinsic). Properties are possessions. The electron has charge, has spin, has mass — the having is a relation between the particle and the property, independent of any encounter. The encounter reveals the property; it does not constitute it. On this view, "the electron has spin-1/2" is true in the void, between measurements, at 3 AM with no apparatus present. The property is there, waiting to be revealed.

Ontology B (encounter-indexed). Properties are readings. The electron presents coupling e(μ) at scale μ, presents $\pm\hbar/2$ along axis $\hat{n}$, presents mass m in kinematic reconstruction — the presenting is a relation between the configuration, the encounter, and the tick. The encounter constitutes the property value; there is no value without it. On this view, "the electron has spin-1/2" is shorthand for "in spin encounters, this configuration presents the spin-1/2 capability" — true in the encounter, meaningless in the void.

The audit of §3 shows: every equation in the standard model is written in Ontology B. Every textbook sentence is written in Ontology A. The two ontologies make different predictions exactly once — Bell's theorem, which excludes local hidden-variable models — and the local models lost. That is a restriction on a model class, not a verdict between the ontologies as defined: nonlocal (tethered) models were never in Bell's scope (P.9), and the test as run is binary-outcome only, with zeros projected and nulls unpublished (P.9). In all other cases they are empirically equivalent (the numbers are the same; only the gloss differs), which means the choice between them is decided not by experiment but by honesty: which ontology says what the equations say? Ontology B. Ontology A is the equations plus one unearned promotion, repeated six times, taught as fact. The paper's positive case rests on the structural arguments of §3, not on Bell alone.

Paper 11's contribution is to state Ontology B natively — in the ledger's own terms (ticks, ports, aspects, encounters) rather than as a commentary on the standard formalism. The relational role theorem is Ontology B as a proved instance, not a philosophical preference. This paper's contribution is to show that the standard formalism was already Ontology B all along — its equations never left — and that Ontology A survives only in the prose about the equations.

Scope declaration — "encounter", declared for the audit. The native encounter criterion — what counts as an encounter (interaction event) in the ledger — is not this paper's scope; it belongs to Paper 9 (Heat as Interaction Event), cited by series title. This paper uses "encounter" in the determination-procedure sense — whatever the determination procedure (measurement) involves — as a declared term for the audit's purposes [LEVEL B], and does not define the general criterion. No §6 falsification machinery turns on it; no new primitive is introduced.

1.3.5 Cash value: what changes in the next paper

A reader can agree with every step of the audit and still ask: so what? Here is the cash value — what a working physicist would actually change in the next paper they write, if they accepted the audit.

Language. Stop writing "the electron's intrinsic spin-1/2" and write "the electron's spin-1/2 representation, read along the apparatus axis." Stop writing "quarks carry color" and write "quarks are labeled by the fundamental representation of SU(3); only color singlets are observable." Stop writing "the intrinsic mass m" and write "the pole mass m_pole" or "the MS-bar mass at scale μ" — naming the scheme every time, the way the equations already do. (F.7's verdict: the word "intrinsic" has six incompatible referents across the literature — table entry, Lagrangian parameter, representation label, non-orbital, bare/infinite, essential-to-identity — none of them "possessed independently of encounters." Retire the word; say which of the six is meant.)

Claims. A property claim must now carry its encounter index, the way a measurement already does. "Charge −e" becomes "charge −e at μ = m_e in the on-shell scheme." "Spin-1/2" becomes "spin-1/2 along n̂." "The CKM element V_ub" becomes "V_ub in the standard parametrization" — with the Jarlskog invariant J quoted as the basis-independent content. Nothing is lost: every number stays. What changes is that the number is no longer presented as a possession of the particle.

Research programs. A dark-matter proposal that budgets a search for "a particle with intrinsic mass m_χ and intrinsic cross-section σ" must now state the encounter geometry in which m_χ and σ are defined — because the audit shows "intrinsic" adds no content beyond the encounter-indexed definition, and the billions are being spent on the encounter, not on the gloss — on reading (b), where "intrinsic" just names the encounter-indexed regularity, the equivalence is conceded (§1.3); the target is reading (a). The EFT defense (§12) is closed: "it's just an EFT" concedes scale-indexing, which concedes the audit.

That is the practical consequence. Not new equations — the equations already say all of this. New honesty about what the equations say.

1.4 The charge, stated plainly

When a physicist says "the electron has intrinsic spin-1/2," the word "intrinsic" asserts: this property belongs to the electron independently of any encounter, any measurement, any context. The audit of §3 shows this assertion is never cashed out — every determination of spin-1/2 runs through a Stern-Gerlach magnet, a field, an axis, an encounter. Remove the encounter and there is no spin value, not even in principle: "spin along no axis" is not a property but a grammatical illusion.

The pattern repeats for all six classes. Intrinsic is always claimed; encounter-indexed is always what is measured. The gap between the two is the subject of this paper.

Roadmap note. The paper's arc runs critique → positive framework: §3 audits, §8 machine-verifies, §9 names the continuum enabler, and §11 (Monte Carlo) is the capstone — for the negative thesis: the continuum was never load-bearing for the critique (§11.6). §12 springs the EFT trap on the standard defense. Read §11 as the destination of that thesis, not an appendix. The positive native-prediction program — the count→weight step, frequencies from combinatorics without an imported measure — awaits Paper 12; §11 does not claim to have built it.

1.5 Four readings of "intrinsic" — and which one is on trial

The entire audit hinges on a specific reading of "intrinsic." But the word admits at least four defensible readings in the literature, and a critic can always try to escape by sliding between them. This section fixes the readings, states which one the paper targets, and shows — with textbook prose — that the targeted reading is the operative one in pedagogy and research.

Reading (a): Possessed independently of any encounter. "Intrinsic" means the property belongs to the particle regardless of measurement, context, or interaction — it is there before the encounter, during it, and after it, unchanged. This is the reading under audit.

Partitioning reading (a). The idiom slides between two subclasses, and the audit scopes them separately — the partition is made here, at the definition, so no downstream verdict needs re-scoping. Bohmian mechanics fits neither subclass cleanly and is boxed on its own.

- Subclass i — Non-contextual possession. The property exists independently

and non-contextually: the value is there regardless of measurement context. This is the subclass Kochen-Specker directly addresses (non-contextual assignments, d≥3), and whose local members Bell addresses experimentally; the paper's Bell/KS REFUTED verdicts attach to it.

- Subclass ii — Contextual / relational extensions. Accounts that try to save

property possession by making it context-dependent — relational-disposition readings, modal-essence moves, and kindred extensions.

- Separate box — Bohmian mechanics (nonlocal non-contextual beables). Definite

always-possessed positions — non-contextual beables — whose measurement outcomes are contextual, in a theory whose Bell-escape is nonlocality, not contextuality (see A.6). It is boxed separately because filing it under Subclass ii misdescribes it: its positions are possessed non-contextually.

Downstream verdicts of REFUTED by Bell or Kochen-Specker attach to Subclass i unless otherwise noted; the color (Elitzur/confinement) and flavor (K^0-oscillation) REFUTED verdicts attach to reading (a) as a whole, contextual extensions included. Subclass ii and the Bohm box are denied by Paper 11's native premises (RELATIONAL_ROLE_THEOREM, TENSION_MEASURE_IDENTITY), flagged inherited — the audit offers no shared-premise refutation of contextual possession or of nonlocal beables; the nonlocal remainder falls to the framework's own ontology, not to Bell or KS. Plainly: no Bell/KS argument in this paper refutes Subclass ii or the Bohm box for spin except Paper 11's own premises — reject those premises and this audit leaves contextual spin-possession and Bohmian positions standing; what Bell and KS close on shared ground is Subclass i (the color/flavor verdicts rest on Elitzur's theorem and oscillation data, shared premises attaching to reading (a) as a whole).

Reading (b): Invariant across encounters. "Intrinsic" means the functional form or regularity is stable across encounters — e(μ) varies with scale, but the RG equation governing it does not. On this reading, "intrinsic" names a regularity, not a possession.

Reading (c): Essential to identity (modal). "Intrinsic" means the property is part of what makes the particle the particle it is — an electron without charge −e would not be an electron. This is the Kripkean/modal reading: essential, not accidental.

Reading (d): Dispositional. "Intrinsic" means the particle carries a stable disposition to produce certain values in certain encounters — intrinsic dispositions, relational manifestations. (Addressed as §7.4.)

The paper targets reading (a). Three reasons this is the operative reading:

First, the textbooks assert it. The PDG tables list charge as a column attribute of the particle — the possessive grammar is reading (a), not (b). The textual-evidence blocks of §3 document the idiom in the wild: "the electron's charge is an intrinsic property — it is the same in all frames, at all energies, in all contexts." That sentence is a paraphrase of the standard textbook presentation, and it is labeled as such: a full-text search of Griffiths' Introduction to Elementary Particles (2nd ed.) did not locate it verbatim ("at all energies" and "same in all frames" occur zero times; the "intrinsic property" idiom there attaches to spin, §4.2.2 — and §1.5 in the 2nd edition is the Neutrinos section, so the earlier Griffiths §1.5 address is withdrawn). A verbatim textbook instance of the core idiom — "intrinsic property" asserted of charge — is documented (with source caveat) in §3.1(a). "Same at all energies" is reading (a) explicitly — and it is contradicted by the RG equation (α runs 1/137 → 1/128 [LEVEL B: rounded physical idiom; PDG α(M_Z) = 1/127.9]; Appendix B.1). Reading (b) would say "governed by the same RG equation at all energies" — the standard presentation does not say that. It says "same," full stop.

Second, the research programs presuppose it. Dark matter searches seek particles with intrinsic mass and cross-section — not "functional forms invariant across encounters" but things with properties, to be found. The billions-budget point of §7.8: grant prose uses reading (a). If the community meant (b), the proposals would say so.

Third, readings (b)–(d) are compatible with the paper's thesis. Reading (b) — invariant functional form — is encounter-indexing: the form governs encounters, it does not float free of them. The paper has no quarrel with (b). Reading (c) — essential to identity — is a modal claim about classification, not a physical claim about possessed values; the paper's Whiteheadian point (§2.1) is precisely that categories of thought (classifications) are being misplaced into concrete furniture (possessions). Reading (d) is answered in §7.4. A defender who slides to (b), (c), or (d) has conceded the audit: none of them licenses the possession-idiom of the textbooks, and (b) is the encounter-indexed position under another name.

The trap for the slider: ask which reading the textbook uses when it lists "intrinsic properties" in a table, and which reading the grant proposal uses when it budgets a search. If the answer is (b), then the table should list functional forms and the proposal should seek regularities — they don't. The operative reading is (a). That is the one on trial: §3 refutes three of its six property readings — spin's pre-existing-local-values reading (Subclass i, by Bell; Kochen-Specker forbids the non-contextual version for $d \geq 3$, which the single spin-1/2 case does not meet (§3.2(c))), color and flavor (reading (a) as a whole, by Elitzur/confinement and K^0 oscillations) — and records GAP verdicts for the other three (charge, mass, magnetic moment), where each derivation chain bottoms out.

2 HISTORICAL DISSENT

This objection is not new. The reification of particle properties — treating relational, encounter-indexed quantities as intrinsic possessions — was identified, named, and opposed by major figures across a century. What follows documents their dissent with verified quotes. Where a witness's positive program contradicts this paper's thesis, the break is disclosed — the paper does not conscript allies under false pretenses.

2.1 Whitehead: the named fallacy

Alfred North Whitehead gave the error its name: the fallacy of misplaced concreteness.

"This fallacy consists in neglecting the degree of abstraction involved when an actual

entity is considered merely so far as it exemplifies certain categories of thought."

— Science and the Modern World (1925), p. 51

"...among the primary elements of nature as apprehended in our immediate experience,

there is no element whatever which possesses this character of simple location."

— Science and the Modern World (1925), pp. 49–58

Science abstracts — point-masses, instants, colorless matter-in-motion — and then mistakes its own abstractions for concrete reality. A "simply located" bit of matter, here in space, now in time, needing reference to nothing else, is a construct of thought, not a discovery. Treating charge, spin, or active/passive as intrinsic possessions of a particle is textbook misplaced concreteness: the Standard Model's quantum numbers are categories of thought — bookkeeping labels that work in calculations — promoted into concrete furniture of the world. Paper 11's relational role theorem is, in Whitehead's vocabulary, a refusal to commit the fallacy. Roles are encounter-relations, not substances.

2.2 Heisenberg: atoms are not things

Werner Heisenberg, Physics and Philosophy (1958):

"The ontology of materialism rested upon the illusion that the kind of existence, the

direct 'actuality' of the world around us, can be extrapolated into the atomic range.

This extrapolation, however, is impossible... atoms are not things."

"In the experiments about atomic events we have to do with things and facts, with phenomena

that are just as real as any phenomena in daily life. But the atoms or the elementary

particles themselves are not as real; they form a world of potentialities or possibilities

rather than one of things or facts."

"What we observe is not nature in itself but nature exposed to our method of questioning."

The particle is not a tiny marble with intrinsic attributes; it is closer to Aristotle's potentia — potentialities actualized only in interaction. Heisenberg retains reality for the phenomenon while denying thinghood to the particle: exactly Paper 11's split between the configuration (structural, real) and the role (encounter-indexed, not intrinsic). His potentia maps onto the paper's capability/actuality distinction — "can play the active role" versus the per-tick actuality.

Disclosed complication: potentia is still, grammatically, something the particle has — a modal property rather than a categorical one. The paper's position is stricter: no standing property at all, only per-tick readings.

2.3 Mach: things of thought

Ernst Mach, The Analysis of Sensations (1886):

"Thing, body, matter, are nothing apart from the combinations of the elements — the colours,

sounds, and so forth — nothing apart from their so-called attributes."

"If ordinary 'matter' must be regarded merely as a highly natural, unconsciously constructed

mental symbol for a relatively stable complex of sensation elements, much more must this be

the case with the artificial hypothetical atoms and molecules of physics and chemistry...

they remain economical ways of symbolizing experience. But we have as little right to expect

from them, as from the symbols of algebra, more than we have put into them."

Mach called atoms a Gedankending — a "thing of thought," a provisional aid. Intrinsic quantum numbers are Gedankendinge: extraordinarily economical symbols (the Standard Model predicts beautifully) from which physicists then expect "more than they have put into them" — namely, that particles really possess these labels between encounters. Paper 11's ledger keeps the economy (the labels work per-tick) while refusing the metaphysical surcharge.

Disclosed complication: Mach's phenomenalism denies atoms entirely, not just their intrinsic properties. He is an ally on the negative point only.

2.4 Bohr: properties defined by the arrangement

Niels Bohr, Como lecture (1927); Atomic Theory and the Description of Nature (1934):

"...the impossibility of any sharp separation between the behaviour of atomic objects and

the interaction with the measuring instruments which serve to define the conditions under

which the phenomena appear."

"Evidence obtained under different experimental conditions cannot be comprehended within a

single picture, but must be regarded as complementary in the sense that only the totality

of the phenomena exhausts the possible information about the objects." (1949)

Position and momentum — wave and particle — are not co-present properties of the object; each is well-defined only under its own mutually exclusive experimental arrangement. "Active at aspect a, tick τ, encounter R" is complementarity generalized: the role isn't in the configuration, it's in the configuration-plus-arrangement. No arrangement, no property.

Disclosed complication: Bohr still required a classical, intrinsic-property description of the measuring apparatus itself. His relationalism stops at the apparatus boundary.

2.5 Bell: one surgical quote, with the caveat stated

John Bell, "Against 'Measurement'," Physics World (1990):

"When it is said that something is 'measured' it is difficult not to think of the result

as referring to some preexisting property of the object in question. This is to disregard

Bohr's insistence that in quantum phenomena the apparatus as well as the system is

essentially involved."

Bell's point is directly usable: the Standard Model's intrinsic quantum numbers are "preexisting properties" smuggled in by the language of measurement. Paper 11's per-tick, encounter-indexed roles are what remains when the smuggling is refused.

Disclosed complication — stated plainly: Bell was a realist who wanted more intrinsic reality, not less. His positive program (beables, pilot-wave particles with definite always-intrinsic positions) contradicts this paper's thesis. He is cited here for the negative point only — the word "measurement" misleads about preexisting properties. A reader who knows Bell will check this; the paper states it first.

2.6 What the dissent establishes

Five major figures, across physics and philosophy, spanning 1886 to 1990, converged on the same structural point from independent directions: the properties physics ascribes to particles are not possessions of the particles. Whitehead named the fallacy. Mach named the cognitive mechanism. Bohr exhibited it in the quantum formalism. Heisenberg denied thinghood to the particle. Bell indicted the language that smuggles preexistence.

The Standard Model's intrinsic-property idiom was therefore not an innocent default. It was a choice — made against sustained, specific, published opposition. §3 shows what that choice costs, property by property.

2.7 What the Standard Model became — the historical arc

The witnesses above did not oppose a strawman. They opposed a specific historical development: the transformation of quantum mechanics from an operational theory (properties defined by experimental arrangements) into a particle-realist ontology (properties possessed by particles). That transformation has a dateable arc, and the intrinsic idiom entered at identifiable points.

1925–1927: the operational beginning. Heisenberg's matrix mechanics (1925) abandoned electron orbits — unobservable — in favor of transition quantities, things actually measured. Bohr's Como lecture (1927) made the apparatus "essentially involved." The founding generation was more relational than what followed, not less. The uncertainty principle was originally a statement about measurement disturbance — encounter-indexing at the foundation.

1930s–1940s: the particle tables. As the particle zoo grew (positron 1932, muon 1936, pion 1947), the PDG-style tabulation began: each particle a row, each row with columns for charge, spin, mass. The table format did quiet ontological work — a column labeled "spin" next to a row labeled "electron" looks like an attribution of a possession, regardless of what the theory says. The intrinsic idiom entered here not as a thesis but as a layout: the grid reifies.

1948–1952: renormalization and the bare/dressed split. The Lamb shift and $g-2$ forced the distinction between "bare" and "physical" quantities. The physical charge, mass, and moment were defined as the dressed values — sums over virtual encounters. But the language went the other way: textbooks spoke of the electron "having" a charge that "gets dressed," as if the bare value were the real possession and the encounters a kind of clothing. In fact the bare values are infinite (meaningless) and only the dressed values are finite (real). The ontology was inverted by the prose: the real (dressed, encounter-constituted) was described as a modification of the unreal (bare, infinite).

1964–1973: quarks and color. Gell-Mann and Zweig's quark model (1964) was explicitly instrumental — Gell-Mann called quarks "mathematical entities." The November Revolution (1974) and QCD's establishment (1973, asymptotic freedom) transformed the instrumental quark into the real quark — and the "color" label, introduced as a bookkeeping device to save the Pauli principle for the Δ^{++}, hardened into "intrinsic color charge." This is the reification mechanism (§5)

operating at the scale of the field's history: what began as "a label that makes the rates work" became "a property quarks possess" within a decade, with no new evidence for the promotion — only the accumulation of successful rate predictions, which the label was already providing.

1967–2012: the Higgs and the VEV. Weinberg's electroweak model (1967) made mass "intrinsic" via the Higgs mechanism — but as Appendix B.3 shows, the VEV is a background encounter. The 2012 Higgs discovery was reported as "giving particles their mass," cementing the intrinsic idiom at the exact moment the formalism most clearly exhibited the encounter (a field filling the vacuum).

The arc's moral. At no point did an experiment establish intrinsicality. What happened, at each stage, was: (i) an encounter-indexed quantity was introduced operationally; (ii) it proved predictively successful; (iii) the success was misattributed from the encounter-indexed formalism to an intrinsic possession; (iv) the textbooks adopted the idiom as standard usage. The record is documentable, not just narratable. Three instances, postwar to modern:

"Empirically, it was necessary to assume that each electron possesses an intrinsic angular momentum, in addition to its usual orbital angular momentum, as though it were a spinning rigid body."

— The Atomic Nucleus (1955), Robley D. Evans, McGraw-Hill, p. 140.

"As we shall see, the gluons themselves carry color, and therefore (like the quarks) should not exist as isolated particles."

— Introduction to Elementary Particles, 1st ed. (1987), David Griffiths, Wiley, p. 49.

"Moreover, although its net charge is zero, the neutron does have a charge structure (positive at the center and near the surface, negative in between) and a magnetic dipole moment."

— Introduction to Elementary Particles, 2nd ed. (2008), David Griffiths, WILEY-VCH, p. 22.

Step (iv) is not a story about textbooks. It is three pages in three books, 1955 to 2008: the possession idiom — possesses, carry, does have — adopted as standard usage. The witnesses of §§2.1–2.5 objected at various points along this arc — Whitehead before it began, Mach at its root, Bohr and Heisenberg as it turned, Bell near its completion. They were not refuted. They were outvoted by the table format.

This history matters because it locates the intrinsic idiom correctly: not as a finding of particle physics but as a habit of particle physics — a presentational convention that hardened into ontology while the equations kept saying otherwise. The audit of §3 is the receipt: six properties, six equations, zero intrinsicality in any of them.

2.8 Whitehead systematized — the fallacy applied per property

Whitehead's fallacy of misplaced concreteness has a precise structure, and it applies differently to each of the six properties. This subsection works the application explicitly — the philosophical spine (§2.1) made load-bearing.

The fallacy's structure. Whitehead identifies two coupled errors:

1. Simple location: treating an entity as "here in space and time" without

reference to anything else — as if it could be what it is in isolation.

2. Misplaced concreteness: mistaking the abstract (the category of thought)

for the concrete (the actual entity).

The two are linked: simple location is what makes the abstraction seem concrete. If the electron can be "simply located" — just there, with its properties, needing nothing else — then its properties look like possessions. Deny simple location (show the entity is constituted by its relations), and the properties reveal themselves as abstractions from those relations.

Applied per property:

Charge. The "simply located" electron carries $-e$ wherever it goes. But the RG equation shows $e(\mu)$ varying with encounter scale — the charge is not "located" with the electron but spread across the electron-vacuum-polarization system. Simple location fails: the charge is a relation between the electron and the virtual pairs dressing it. Misplaced concreteness: the relation (coupling at scale μ) mistaken for a possession (charge $-e$, full stop).

Spin. The "simply located" electron has spin-1/2 as a standalone fact. But S·n̂ requires the axis — the spin is not located "at" the electron but between the electron and the field defining n̂. Bell's theorem is the experimental proof that simple location fails for spin in local models: the value is not there before the encounter. Misplaced concreteness: the Hilbert-space dimension (2 — a category of thought about rotation symmetry) mistaken for a possessed quantity.

Mass. The "simply located" electron has mass 511 keV wherever it is. But $m_f = y_f v/\sqrt{2}$ — the mass is located between the fermion and the Higgs field, not at the fermion. The VEV v is everywhere; the "location" of the mass is the whole vacuum. Simple location fails maximally here: the property is the least localized thing in the theory, described as the most intrinsic.

Color. The "simply located" quark carries red (or green, or blue). But gauge invariance means the color rotates under SU(3) — there is no gauge-invariant fact about "which" color the quark has. The color is not located at the quark; it is not located anywhere — it cancels from every physical state. This is misplaced concreteness in its purest form: a label in the Lagrangian (category of thought) mistaken for a property of a particle, when the theory's own dynamics forbid the particle from existing with the label manifest.

Flavor. The "simply located" quark is strange (or up, or down). But the CKM matrix shows the flavor basis rotating — "strange" is not located at the quark but at the quark-weak-vertex pair. K^0–$\bar{K}^0$ oscillations are the temporal exhibition: the neutral meson system evolves between flavor eigenstates — what oscillates is the meson's flavor content, not a quark changing flavor. The "location" of the strangeness moves, because it was never at the quark.

Magnetic moment. The "simply located" electron has moment μ_e. But a_e is a sum over 12,672 virtual-encounter diagrams — the moment is "located" across every virtual particle in every loop. Simple location would require the moment to be at the electron; the calculation puts it everywhere the virtual particles go.

The systematic point. In all six cases, Whitehead's diagnostic works identically: assume simple location (the property is at the particle), derive a contradiction with the formalism (the property is between the particle and something else — a scale, an axis, a field, a gauge, a basis, a loop sum), conclude misplaced concreteness (the relational quantity was mistaken for a possession). The fallacy is not an analogy for the audit's findings. It is the audit's findings, stated in 1925.

3 THE AUDIT: WHAT "INTRINSIC" CASHES OUT TO

Each property class is examined in four moves: (a) the textbook intrinsic statement with source, (b) equation breakdown — the actual formalism, with the precise location where "intrinsic" is assumed rather than derived marked, (c) the inference chain — what is observed versus what is inferred, separated honestly, (d) the Paper 11 Level A counterpart — the proved result (or, for aspect aggregation, the declared axiom) that replaces the intrinsic idiom.

Notation: OBSERVED = detector-level facts. INFERRED = theoretical posits reached by reasoning from the observed. The audit's question for each property: does "intrinsic" appear in (b), or only in the gloss on (c)?

3.1 Electric charge — the coupling that runs

(a) "The electron carries intrinsic charge −e." Standard textbook presentation (PDG particle tables): charge listed among the electron's intrinsic properties, presented as a column attribute.

Textual evidence. The intrinsic idiom in the wild:

"The electron's charge is an intrinsic property — it is the same in all frames,

at all energies, in all contexts."

— Paraphrase of the standard textbook presentation (PDG tables). The Griffiths

attribution previously attached here is withdrawn: a full-text search of the

2nd edition did not locate this sentence verbatim (see §1.5).

Verbatim, from an introductory physics text: "The charge on an electron, which

is negative, is −e. This is one of the defining, or intrinsic, properties of

the electron." ('Phys15' course PDF as uploaded; edition unverified — cited

as found.)

The claim "same at all energies" is directly contradicted by the RG equation

(Appendix B.1): α runs from 1/137 to 1/128 [LEVEL B: rounded physical idiom; PDG α(M_Z) = 1/127.9]. The table idiom asserts energy-independence;

the textbooks' own QFT chapters derive energy-dependence.

(b) Equation breakdown. The interaction Lagrangian:

L_int = −e ψ̄ γ^μ ψ A_μ

Here e appears as a coupling constant — a parameter multiplying the fermion-photon vertex. Nothing in the formalism marks e as "possessed by ψ" rather than "characterizing the ψ–A interaction." The notation ψ̄...ψ A_μ is already a two-field coupling; the "intrinsic" reading requires an extra interpretive step the mathematics does not take.

The deeper cut: renormalization. The physical charge is not e but e(μ), the running coupling:

α(μ) = e²(μ) / 4π, α(m_e) ≈ 1/137, α(M_Z) ≈ 1/128 [LEVEL B: rounded physical idiom; PDG α(M_Z) = 1/127.9]

The "intrinsic charge" depends on the energy scale μ of the encounter probing it. Vacuum polarization screens the bare charge; what any experiment extracts is the dressed coupling at its own scale. The bare charge e_0 is infinite and unobservable — it appears in no prediction. An "intrinsic" property that (i) is infinite when isolated from encounters, (ii) takes different finite values at different encounter scales, and (iii) is defined only through the interaction vertex, is intrinsic in name only. QFT itself has already encounter-indexed the charge; the textbook prose has not caught up.

(c) Inference chain.

- OBSERVED: Millikan oil-drop deflections in a known E field; Rutherford scattering

angular distributions; the numerical value of the vertex factor extracted from cross-sections at a given √s.

- INFERRED: "the electron carries charge −e" as a standing possession, independent of

any field. The inference drops the scale label μ and the field context, promoting e(μ; A_μ present) to e (full stop).

- The dropped information is exactly the encounter-indexing. Restore it and the

"intrinsic" claim dissolves into: "in electromagnetic encounters at scale μ, this configuration presents coupling e(μ)."

(d) Paper 11 Level A counterpart. PORT_PARTITION_EXACTNESS (§4.3) [LEVEL A]: ports present values per-tick; the coupling is presented port geometry, read off the encounter, not carried between encounters. The running of α(μ) is the standard formalism's own admission that the coupling is encounter-indexed — Paper 11's ledger makes the indexing explicit rather than hiding it in the renormalization scale. The positive picture: Paper 11's ledger has no "charge of the configuration" slot at all — there is only the per-tick port geometry, computed from the encounter's own structure. What the SM calls "the electron's charge −e" the ledger renders as "what port geometry this encounter presents" — and the RG running is then not a correction to an intrinsic value but the native behavior of encounter-indexed presentation.

So the measured coupling is constituted by the encounter, not revealed by it — the scale index μ is the encounter's fingerprint on the number.

3.2 Spin — the axis is constitutive

(a) "The electron has intrinsic spin-1/2." Griffiths §4.2.2 (2nd ed.; the §5.1 address is withdrawn — §5.1 is Bound States in both editions): spin listed among "intrinsic" properties; Peskin & Schroeder §3.5: the Dirac spinor "describes a spin-1/2 particle."

Textual evidence.

"Spin is an intrinsic form of angular momentum carried by elementary particles."

— Standard textbook formulation (Griffiths §4.2.2 (2nd ed.); Wikipedia "Spin (physics)").

The word "carried" does the reification: angular momentum is something the

particle carries, like luggage. But S·n̂ requires n̂ — the "carried" thing

cannot even be defined without the axis it is supposedly carried

independently of. The sentence is grammatical; it is not coherent.

(b) Equation breakdown. The Stern-Gerlach force:

F = ∇(μ · B), μ = g (q/2m) S

The spin operator enters only as S · n̂ — the projection along a unit vector n̂, the field direction. The eigenstates |↑_n̂⟩, |↓_n̂⟩ are defined relative to n̂. There is no "spin state" in the formalism without an axis: the Pauli matrices σ_x, σ_y, σ_z are a basis of operators, and every physical spin statement is "spin along the axis the apparatus defines."

This is not a subtlety — it is the structure of the mathematics. The Hilbert space is two-dimensional, but every vector in it is "spin-along-some-axis." The axis is not a correction to the property or a context for its measurement. It is constitutive: remove n̂ and |↑⟩ is not an unknown value but a meaningless symbol, like "the slope of" with no curve specified.

The experimental closure: Bell's theorem — stated in its honest scope. EPR spin correlations violate Bell inequalities, which excludes local hidden-variable models: no local assignment of pre-existing spin values reproduces the correlations. If spin-1/2 were an intrinsic possession in a local model — a standing property the particle carries independently — the correlations would satisfy Bell's bound. They don't. The experiments (Aspect 1982, and every loophole-free test since) refute the local intrinsic reading. Two qualifications, stated plainly: (1) Bell does not touch nonlocal (tethered) models — the SPDC pair as one geometric structure was never in its scope (P.9); (2) the test as run is binary-outcome only — zeros are projected, nulls unpublished (P.2, P.9) — so it cannot crown an ontology, only exclude a model class. The values are created in the encounter, not revealed by it — but that positive claim rests on the structural argument above (the axis-constitutiveness of S·n̂), not on Bell alone. Bohr said the apparatus is "essentially involved"; Bell's theorem is the proof that local models fail — nothing more, nothing less.

(c) Inference chain.

- OBSERVED: two spots on a detection screen; coincidence counts violating Bell

inequalities; the numerical splitting in a known field gradient.

- INFERRED: "the electron has spin-1/2" as a standing possession. The inference

takes "two outcomes along n̂" and promotes it to "spin-1/2, full stop" — dropping the axis that the formalism requires and the Bell tests prove is load-bearing.

- What the Bell violations establish positively: no local model assigns the spin

value before the encounter. "Intrinsic spin" in the local sense is not merely untestable — it is experimentally falsified as a pre-existing local property. (The paper's target throughout is the non-contextual "possession" idiom; the KS qualification below stands.)

- Kochen-Specker strengthens the point beyond Bell — with its scope stated. Bell rules out local hidden

variables; the Kochen-Specker theorem rules out non-contextual value assignments — no locality assumption needed — for systems of dimension d≥3. KS proves it is mathematically impossible to assign pre-existing values to all quantum observables simultaneously, independent of measurement context, when d≥3. "Intrinsic spin" — Subclass i of reading (a), a possessed value independent of the encounter — is exactly the non-contextual assignment KS forbids, where the dimension requirement is met: the standard formalism's Hilbert-space non-commutativity demands contextuality — encounter-indexing — and the "intrinsic" prose denies it. (KS does not rule out contextual hidden variables; the paper's target is specifically the non-contextual "possession" idiom.) Limitation, stated honestly: a single spin-1/2 system is d=2 and does not meet the d≥3 requirement directly — the paper makes no composite-system extension here, so for the single spin-1/2 case the KS theorem is cited as the general form of the non-contextuality ban while the paper's own positive case rests on the axis-constitutiveness of S·n̂ above, not on KS. Bell falsified the local version experimentally; Kochen-Specker forbids the non-contextual version mathematically, each within its stated scope.

(d) Paper 11 Level A counterpart. RELATIONAL_ROLE_THEOREM (§3.1) [LEVEL A]: no configuration carries 'active' or 'passive' as an intrinsic label — proved by exhibiting one selector active at one tick and passive at another. Spin is the

textbook case: the "spin-1/2" label is the capability ("can present ±ℏ/2 along a presented axis"), and the actual value is the per-tick, per-encounter reading. TENSION_MEASURE_IDENTITY (§7.1) [LEVEL A]: the value is the reading — definitional, not possessed. Bell's theorem is the standard formalism's own theorem excluding local pre-existing values; Paper 11's ledger states natively what Bell proved local models cannot avoid. The positive picture: in the ledger, "spin-1/2" is a capability class — the configuration's structure permits ±ℏ/2 presentations along any presented axis — and each tick's reading is the capability actualized in that encounter's geometry. Nothing is stored between ticks; nothing needs to be. The ledger predicts the same Stern-Gerlach statistics (P.1) with no hidden pre-existing value anywhere in the machinery.

So the measured value is constituted by the encounter, not revealed by it — 'up' means 'up along the axis the encounter presented,' and there is no axis-free fact underneath.

(e) P.9 — the 3-axis formalization: what Bell's test cannot see. Two lab-note results are formalized as machine checks (P9_bell_ternary_tether.py, exit 0). First, "The Bell Test Fallacy": in SPDC the pair is one tethered geometric structure, not two independent particles — Bell assumes the "container-void," so the violation evidences the tether's rigidity, not spookiness. Second, "The Binary Trap": the framework admits three states per axis (+1, −1, 0/neutral) while CHSH admits only binary outcomes — zeros are erased (P.2 assigns 0 → +1 by fiat) and nulls go unpublished.

The machine states three findings. (1) Projection-dependence: a local ternary hidden-variable model (definite tilt axis per particle; near-orthogonal tilts read neutral 0) yields S = 1.90 / 1.90 / 2.69 / 1.94 under four handlings of 0 (0→+1, 0→−1, drop-zeros, keep-zeros) — spread 0.79. The binary verdict moves with the projection rule: a data-processing choice, not physics. Under drop-zeros the local model scores S = 2.69 > 2 — per-correlator post-selection manufactures a "violation": the detection loophole, running live. (2) Local ternary bound, machine-proved: brute force over all 81 deterministic {+1,−1,0} assignments gives max |S| = 2.0. Ternary outcomes do NOT lift the local bound — the binary trap is representational; the phenomenon is not a binary artifact. (3) The tether: one shared geometric hidden variable, outcomes computed jointly from both settings (non-separable), deterministic — E(a,b) ≈ −a·b (within TOL = 0.04), S = 425/149 ≈ 2.8523 (within 0.04 of 2√2). Sever the tether (Bob's outcome from his own side only): S collapses to 296/149 ≈ 1.9866, saturating the local bound. Separability — not determinism, not pre-existing structure — was the load-bearing assumption.

Limits, stated: the tether response as coded is schematic (a joint threshold), a logical existence proof, not the full gear-mechanics; Bell's mathematics is untouched — what the toy demonstrates is narrower: one schematic non-separable construction reproduces the correlations, and nothing about tether models in general is established. "Ontology B won because of Bell" is unwarranted. "Bell excludes all pre-existing structure" is false, witnessed. What Bell adjudicates: separable, binary-outcome models. Nothing more. The paper's positive case rests on the structural arguments above — the axis-constitutiveness of S·n̂ — not on Bell alone.

3.3 Mass — the ledger already settled this

(a) "The electron has intrinsic mass 511 keV/c²." PDG: electron mass listed as a fixed particle property. (The Griffiths §1.5 address previously cited here is withdrawn — see the §1.5 note on the unverifiable attribution.)

(b) Equation breakdown. Three versions, all encounter-indexed. Mass is the hardest case — it looks the most intrinsic because it sits in the free Lagrangian — so it gets the most careful handling.

Version 1 — the Dirac mass term: $\mathcal{L} \supset -m\,\bar{\psi}\psi$. Here m is a Lagrangian parameter. But m is fixed by matching to experiment — specifically to energy-momentum relations $m^2 = E^2 - p^2$ measured in encounters (decay kinematics, threshold production). The parameter is calibrated on encounters; nothing in the formalism gives it independently.

Version 2 — the Higgs mechanism: $\mathcal{L} \supset -y_f H \bar{\psi}\psi \rightarrow m_f = y_f v/\sqrt{2}$ after electroweak symmetry breaking. The "intrinsic" mass is a Yukawa coupling y_f times the Higgs vacuum expectation value v. But v is a background field value — the vacuum expectation is an encounter with the vacuum. The mechanism relocates the encounter from the laboratory to the vacuum; it does not remove it. "Intrinsic mass via the Higgs" = "coupling constant times the field value everywhere" — which is to say, a relational quantity with one relatum (the Higgs field) held fixed and then forgotten. The VEV is a relational fact about the field configuration, not a possession of the particle — and §9.5 traced exactly how the continuum notation φ(x) makes that configuration feel like background substance.

- Elitzur's theorem and the VEV — stated with precision. Elitzur proves local

gauge symmetries cannot be spontaneously broken. Applied carefully: what this forbids is the substance reading of the Higgs field — an omnipresent physical stuff that "gives" particles their mass the way water gives buoyancy. The VEV ⟨φ⟩ itself is gauge-dependent (its value shifts with gauge fixing), while the mass spectrum it produces is gauge-invariant. The honest statement: the physical content (masses) is gauge-invariant and real; the substance narrative ("the Higgs field fills the universe and confers mass") is the reification of a gauge-fixing choice into an ontology. The paper does not claim the VEV is "unreal" — it claims the intrinsic-substance gloss on the VEV is what Elitzur kills. Precision here is not hedging; it is what keeps the critique unbreakable.

Version 3 — the mass you actually quote is scheme- and scale-defined. The PDG does not list one "intrinsic mass" per quark — it lists the MS-bar mass at a scale ($m_b(m_b) = 4.18$ GeV, $m_b(M_Z) = 3.08$ GeV — different numbers, same quark; the 3.08 is P.8's one-loop running — declared one-loop truncation, n_f fixed — not a PDG listing: the PDG's own multi-loop value is $m_b(M_Z) \approx 2.86$ GeV, so the genuine PDG pair (4.18, 2.86) spreads wider, strengthening the point), the pole mass ($m_t^{pole} \approx 172.5$ GeV vs $m_t^{MSbar} \approx 163$ GeV), the 1S mass, the kinetic mass. The definitional spread for the top (~9 GeV) exceeds the experimental precision (~0.3 GeV) by a factor of thirty. There is no encounter-free fact of the matter about which one is "the" mass — the formalism supplies a relation between definitions (P.8 computes it), not a ranking. And the pole mass itself is definition-limited by the renormalon ambiguity at $O(\Lambda_{QCD})$: even the "physical" pole is not sharply defined. The capability / actuality distinction (§1.5, reading (d)) does its heaviest work here: what the formalism gives you is the capability to compute a mass-like number in a stated scheme at a stated scale — the actual number exists only there, in that encounter-indexed determination. "Intrinsic mass" is the capability mistaken for a possession.

(c) Inference chain.

- OBSERVED: resonance peaks at 511 keV in e^+e^- annihilation spectra; cyclotron

frequencies $\omega = qB/m$ in known fields; invariant-mass distributions of decay products.

- INFERRED: "intrinsic mass 511 keV" as a possession. Every determination runs

$m^2 = E^2 - p^2$ on encounter products, or ω in a field — the mass is reconstructed from encounters, never presented by the particle alone.

- "Invariant mass" is invariant across encounters — encounter-indexed generality,

not encounter-independence. The invariance is the regularity of the encounters, misattributed to the particle.

(d) Paper 11 / Paper 8 Level A counterpart. Paper 8 proved natively: mass is the internal accounting of departure from c — a ledger quantity, not a possession. Paper 11's ASPECT_AGGREGATION (§7.3) [LEVEL A, author-authorized] (falsifiers: Appendix E.5): port contributions are attributed to exactly one aspect per-tick — the "mass" is the aggregated reading, not a standing property. The Higgs VEV is the standard model's own version of a background ledger value; Paper 11 declines to reify it into "intrinsic." The positive picture: mass in the ledger is departure accounting — each tick computes how far the configuration's presentation departs from the photon baseline, and the accumulated accounting is what the SM calls "mass." There is no mass-slot on the configuration; there is no need for one. The Higgs VEV, on this rendering, is a ledger-global constant (cf. §9.5) — a number in the accounting, not a substance in space.

So the measured mass is constituted by the encounter, not revealed by it — pole mass, MS-bar mass at scale μ, each one defined by the scheme and scale of its determination (P.8).

Bridge premise, stated explicitly (RT-02): the step from "every determination runs through encounters" — what §3.3 derives, a GAP (encounter-independence underivable from the formalism) — to "constituted by the encounter" — the ontological conclusion — is inherited, not derived here. It comes from Paper 8/11's native ontology (mass as the ledger's internal accounting of departure from c; §3.3(d) above), where the premise is proved, not from the mass equations alone. H.2's verdict for mass is GAP, not REFUTED: the paper claims underivability for the intrinsic reading, not its refutation. The distinction matters — the audit shows the equations cannot deliver encounter-independence; the constitution claim is the framework's, labeled as such.

3.4 Color charge — the gauge label that cancels from every observable

(a) "Quarks carry intrinsic color charge (red, green, blue)." Griffiths §2.4: color introduced as a quark property; Halzen & Martin, Ch. 12: color charge as a fundamental attribute.

Textual evidence.

"Quarks carry a property called color charge, which comes in three varieties:

red, green, and blue."

— Standard popular and textbook formulation (Griffiths §2.4).

"Comes in three varieties" — as if color were a flavor of ice cream the quark

has. But Elitzur's theorem forbids the varieties from ever appearing separately,

and gauge invariance removes them from every observable. The sentence describes

a bookkeeping label as if it were a possession. It is the reification mechanism's

step 4, performed in a single clause.

(b) Equation breakdown. The QCD Lagrangian:

$L = \bar{\psi}_i (i\not{\partial} \delta_{ij} - g T^a_{ij} \not{A}^a - m \delta_{ij}) \psi_j$, $i,j \in \{r, g, b\}$

The color indices i, j are gauge labels. Under an SU(3) gauge transformation:

$\psi_i \to U_{ij} \psi_j$, $U \in SU(3)$

the "color" rotates. Now the decisive structural fact: physical observables must be gauge-invariant. The S-matrix — the object actually computed and compared to experiment — contains only color singlets: $\bar{\psi}_i \psi_i$ summed over i, traces over color. The color indices cancel from every physical prediction.

Stated bluntly: "quarks carry color" is a category error, not a mild idealization. Elitzur's theorem (1975) proves that a local gauge symmetry cannot be spontaneously broken — there is no gauge-invariant order parameter that is colored, which means no physical state carries local color, as a theorem. The only gauge-invariant probes of the color field are nonlocal: Wilson loops $W(C) = \mathrm{Tr}\, P \exp(i\oint_C A\cdot dx)$, whose area law $\langle W(C)\rangle \sim \exp(-\sigma A)$ defines confinement. Read the logic carefully: the theory's own observability criterion says "local color is not observable"; the textbook sentence says "quarks carry color charge" as a local possession. The sentence is not approximately true or true-in-a-gauge — it asserts, as physics, exactly what the theory's theorems forbid as physics. The Wilson loop is the encounter made formal: color exists only as the holonomy around a closed path — a relational fact about the loop, indexed by the loop. There is no loop-independent "color of the quark" for the same reason there is no path-independent holonomy: the quantity is constituted by the extended encounter. Let the theorem speak: local color is unobservable by proof, and a property that cannot be observed even in principle, whose bookkeeping rotates with gauge choice, is not a possession of anything. It is a coordinate.

This audit targets the possession reading (a); the representation-label usage is not the target and is compatible with the ledger.

In Coulomb gauge, the "color" bookkeeping looks one way; in covariant gauge, another; in lattice QCD, another still. The physics — every cross-section, every decay rate — is identical. A "property" whose bookkeeping changes with the gauge choice but whose physical consequences do not is not a property of the particle. It is a property of the description.

Confinement makes this structural, not practical: there are no asymptotic colored states. Not "hard to isolate" — forbidden by the theory's own dynamics. The "intrinsic color charge" can never be presented by a quark alone, even in principle, because an isolated quark is not a state in the theory. The property is defined on an object that the theory says cannot exist separately.

The color factors tell the real story: $C_F = 4/3$, $C_A = 3$, $T_R = 1/2$. These are group-theory numbers — Casimir invariants of SU(3) representations. They enter predictions as numerical coefficients, exactly like π enters the area of a circle. No one calls π an "intrinsic property of the circle" possessed independently of geometry. The color factors are

properties of the gauge group, misattributed to the quarks.

The R-ratio exhibits the inference nakedly:

$R = \sigma(e^+e^- \to \text{hadrons}) / \sigma(e^+e^- \to \mu^+\mu^-) = 3\ \Sigma_q\ e_q^2$

The factor 3 — "three colors" — is extracted from the rate. What is observed: a cross-section ratio of ~3× the parton-model value. What is inferred: "quarks come in three intrinsic colors." The number 3 is doing work in the calculation; the intrinsic is doing work only in the prose.

(c) Inference chain.

- OBSERVED: hadron jets with 3-jet topology; scaling violations in deep inelastic

scattering matching the QCD β-function; the R-ratio ≈ $3\Sigma e_q^2$; no free quarks in any detector, ever.

- INFERRED: "quarks carry intrinsic color charge (r,g,b)." The inference takes

group-theory coefficients that correctly predict rates and promotes them into possessions of unobservable particles — particles the theory itself forbids observing.

- The gauge-dependence is the tell: change the gauge, change the "color"

bookkeeping, keep every prediction. An intrinsic property cannot be gauge-dependent. Therefore color is not intrinsic. QED, in the other sense.

(d) Paper 11 Level A counterpart. STRUCTURAL_INSULATION_THEOREM (§4.1) [LEVEL A]: labels doing bookkeeping work are not ontological commitments. Paper 11's ledger uses labels per-tick (u values, port states) and refuses to promote them into standing possessions — the discipline the standard formalism needs but does not practice. The color index is the clearest case in physics of a label that works perfectly in calculations and refers to nothing intrinsic: it cancels from the S-matrix by construction. The positive picture: the ledger uses color-like indices freely inside a tick's bookkeeping — as routing labels for the encounter's internal accounting — and drops them at the tick boundary, exactly as the SM's S-matrix drops them at the observable boundary. The ledger's discipline is the SM's practice made explicit: labels that do routing work are not promoted to ontology. What Elitzur's theorem proves about gauge theories the ledger assumes as a design rule.

So the measured rates are constituted by the encounter, not revealed by it — the only color that ever reaches a detector is the singlet combination the encounter geometry selected.

3.5 Flavor — basis-dependent by construction

(a) "Quarks have intrinsic flavor (up, down, strange, charm, bottom, top)." Griffiths §1.4: the six flavors as quark types; PDG quark listings organized by flavor as a fixed label.

Textual evidence.

"There are six flavors of quarks: up, down, strange, charm, bottom, and top.

Each flavor has a characteristic mass and charge."

— Standard formulation (Griffiths §1.4; PDG).

"Each flavor has" — the possessive grammar (step 3) applied to a basis label.

But the CKM matrix, printed in the same textbooks two chapters later, shows the

flavor basis rotating into the mass basis. The textbook derives basis-dependence

and prose basis-independence, four chapters apart, hoping no one notices.

(b) Equation breakdown. The charged weak current:

$J^\mu = \bar{u}_{Li}\ \gamma^\mu\ (V_{CKM})_{ij}\ d_{Lj}$

V_{CKM} is the 3×3 Cabibbo-Kobayashi-Maskawa matrix — a unitary rotation between bases. The "flavor" eigenstates (d, s, b — what the W boson couples to) are not the mass eigenstates (d_1, d_2, d_3 — what propagates). They are related by:

d'_weak⟩ = V_{ud}	d⟩ + V_{us}	s⟩ + V_{ub}	b⟩

A "down quark" in a weak vertex is a linear combination of mass eigenstates. Ask the strong interaction "what flavor is this?" and ask the weak interaction "what flavor is this?" and you get different answers — related by V_CKM, but different. The "flavor" is not a label on the quark; it is a label on the quark-interaction pair.

Sharpened: the physical content is basis-invariant, the labels are not. The CKM matrix is a basis choice — a coordinate chart on flavor space. The individual matrix elements V_ub, V_cb, V_td are coordinates, and coordinates are not properties of the territory. What is physical — basis-independent — is the invariant content: the Jarlskog invariant $J = \mathrm{Im}(V_{ud} V_{cb} V^*_{ub} V^*_{cd}) \approx 3\times10^{-5}$, the single number that encodes all CP violation in the quark sector, unchanged by any rephasing of the quark fields. Rephase the fields (a mere convention change) and every V_ij moves; J does not. So the "intrinsic" reading would have to say: the coordinates are possessed by the quarks, but the invariant — the thing that doesn't move when conventions change — is somehow less intrinsic? The formalism has it exactly backwards from the gloss: the invariant J is the encounter-indexed regularity (it governs decay-rate asymmetries, which are encounter statistics), and the V_ij are the convention-relative labels. Once the reader sees that "the top quark's mixing angles" are basis artifacts — coordinates that slide under rephasing — the possessive grammar ("the top's V_tb") becomes indefensible. Nobody says a city "has intrinsic latitude 40.7°" as a possession independent of the coordinate system; the CKM elements are latitudes, and J is the distance.

This is encounter-indexing inside the formalism, not in the gloss. The standard model does not even pretend flavor is basis-independent — the CKM matrix is the explicit record of its basis-dependence. Yet the textbooks still list "flavor" among intrinsic properties. The left hand (the Lagrangian) knows; the right hand (the prose) forgets.

Neutral-meson mixing (K^0–$\bar{K}^0$, B^0–$\bar{B}^0$ oscillations) is the phenomenon that makes this undeniable: a K^0 produced in a strong encounter evolves into a $\bar{K}^0$ superposition by the time it decays weakly — the meson system oscillates between flavor eigenstates; no quark changes flavor on mass eigenstate propagation — the mixing is mediated by flavor-changing weak vertices. If flavor were intrinsic — carried with the particle — this would be impossible. The particle does not "have" a flavor that changes; the flavor is the interaction-basis label, and it was never anything else.

(c) Inference chain.

- OBSERVED: decay chains ($\Lambda \to p\pi^-$); branching ratios matching CKM elements;

K^0–$\bar{K}^0$ oscillation frequencies; the six distinct mass peaks.

- INFERRED: "the quark has intrinsic flavor X." The inference takes

"participates in weak vertex via (V_CKM)_{ij}" and promotes it to "is flavor j." The CKM matrix — the formalism's own record of basis-dependence — is treated as a correction to the intrinsic picture rather than what it is: proof that there is no intrinsic picture.

- The mass peaks are real (encounter-indexed generality again). The "flavor"

label on each peak is the weak-basis projection, not a possession.

(d) Paper 11 Level A counterpart. RELATIONAL_ROLE_THEOREM (§3.1) [LEVEL A], applied directly: flavor is the weak-encounter role label. Just as "active" is (aspect, tick, encounter)-indexed, "strange" is (quark, weak-vertex)-indexed. Paper 11's CAPABILITY_ACTUALITY_SEPARATION (§3.1) [LEVEL A]: the quark can present in the strange role at a weak vertex — the capability is structural; the actual flavor label exists only in the encounter. The CKM matrix is the standard model's unwitting confession that it already knows this. The positive picture: the ledger carries no flavor-slot on the quark configuration — there is only the weak-vertex role, assigned per encounter, with the CKM entries as the routing weights for role assignment. "Strange quark" is then not a kind of thing but a recurring role in a recurring encounter geometry — which is exactly why the role recurs with the regularity the SM mistakes for intrinsicality.

So the measured flavor is constituted by the encounter, not revealed by it — 'strange' names the weak-vertex role, and the CKM matrix is the coordinate chart for a basis choice, not a property table.

3.6 Magnetic moment — the flagship: a sum over loop diagrams

This is the flagship case, not one of six equal rows. The magnetic moment is measured to ten decimal places — the most precise "property" in physics — and the community's own precision culture is where the intrinsic idiom collides hardest with the formalism. Everything the audit claims in general is visible here in particular, with the numbers attached.

(a) "The electron has intrinsic magnetic moment -9.28×10^{-24} J/T." PDG: listed as a particle property; Peskin & Schroeder §6.3: g−2 derived as a property of the electron.

(b) Equation breakdown. The anomalous moment:

a_e = (g−2)/2 = Σ_n C_n (α/π)^n = α/2π − 0.328478965…(α/π)² + 1.181241…(α/π)³ − …

Each coefficient C_n is a sum over Feynman diagrams — loop integrals over virtual particle encounters. The Schwinger term α/2π is the one-loop vertex correction: the electron emits and reabsorbs a virtual photon. The two-loop term sums seven diagrams. The five-loop term sums 12,672 diagrams. This is the QED-sector series — P.7 computes it to 12 digits; the hadronic/weak residual is excluded from the check and disclosed in P.7's provenance block.

Read that again: the "intrinsic" magnetic moment — the most precisely measured "property" in physics, to ten decimal places — is defined as a sum over loop diagrams. There is no "bare" moment underneath the dressing; the dressing is the moment. The diagrams are not corrections to an intrinsic value; they constitute the value. Remove every loop diagram and there is no remainder: there is no term in the series corresponding to "the electron alone" — the tree-level Dirac value g=2 is itself the free-field idealization, defined by removing interactions from the Lagrangian, not by isolating the electron from encounters (B.6).

An objection: Feynman diagrams are a calculational device, not literal encounters — so counting them proves nothing about ontology. Part of the objection is fair and this paper concedes it: each diagram is evaluated by continuum loop integrals (the paper's own §3.6(b) above; §11.6 admits the continuum upstream, in the formulas that supply relative weights). What the objection cannot dismiss is the integer at the front. At every loop order the coefficient is a sum over N discrete diagrams — 1, 7, 72, 891, 12,672 (P.10 tabulates the spectrum; the 1- and 2-loop counts are machine-derived from the QED vertex rules under the proper-vertex (1PI) convention, the rest are the published Kinoshita-program counts). The count N is discrete and convention-indexed, and it grows at every order — not a five-loop accident. The structural claim is only this: nothing in the formalism is a scale-free possession; the "intrinsic" value is the sum, whatever evaluates its terms.

The measurement is equally encounter-bound: g−2 experiments measure spin precession frequency ω_s − ω_c in a known magnetic field. The field is the encounter; the precession is the joint product. The ten-decimal agreement between theory and experiment is agreement about encounter systematics — the most precise encounter-indexed regularity ever established. Calling it "intrinsic" adds no decimal place, explains no digit, and predicts nothing beyond what the loop sum already predicts.

(c) Inference chain.

- OBSERVED: precession frequencies in Penning traps; the numerical value

a_e = 0.00115965218059(13).

- INFERRED: "the electron has intrinsic magnetic moment μ_e." The inference takes

a sum over 12,672 virtual-encounter diagrams — each one an interaction — and attributes the total to the electron alone. The encounters are in the calculation; they are elided in the attribution.

- The irony is total: the property cited as the parade example of an intrinsic

quantity is computationally constituted by encounters. If this is "intrinsic," the word has no meaning left.

Three further encounter-indexings the flagship exhibits (machine-checked in P.7):

1. The Dirac term contributes exactly zero. The "intrinsic" tree-level value

g = 2 gives a_e = 0. The anomaly is 100% loop content in the QED sector; the hadronic/weak residual is disclosed above. The mutant that asserts a_e = 0 as the intrinsic prediction fails against experiment by the full anomaly — P.7 rejects it with the discrepancy as witness.

2. The muon's mass is inside "the electron's" moment. The mass-dependent QED

pieces (muon vacuum polarization at two loops) shift a_e at 21× the experimental uncertainty. A possessed property cannot contain other particles' masses; an encounter-indexed regularity can, because the loops are encounters with the muon field.

3. IR sensitivity. The theoretical machinery building the prediction is

infrared-sensitive; the IR cutoff is set by detector photon-energy resolution — an encounter parameter. The "intrinsic" number is never isolated from the apparatus that extracts it.

So the measured value is constituted by the encounter, not revealed by it — here with ten-decimal precision, which makes the constitution undeniable.

(d) Paper 11 Level A counterpart. ASPECT_AGGREGATION (§7.3) [LEVEL A, author-authorized] (falsifiers: Appendix E.5): port contributions are attributed to exactly one aspect per-tick — attribution is a bookkeeping rule, declared, not discovered. The magnetic moment is the standard model's unwitting aspect-aggregation: 12,672 encounter-diagrams attributed to "the electron" by convention. Paper 11 states the convention explicitly; the standard model performs it silently and calls the result "intrinsic." The honesty difference is the entire difference. The positive picture: the ledger's aspect-aggregation is declared — port contributions attributed to exactly one aspect per tick, by a bookkeeping rule stated in the open. The magnetic moment is then not "the electron's intrinsic property" but the declared aggregation of per-tick encounter contributions — and the anomaly a_e is the measure of how many encounter-geometries the aggregation had to sum over. Same number, honest grammar.

3.7 Audit summary

#	Property	Their equation	Where "intrinsic" is smuggled	What's actually en counter-indexed	Paper 11 Level A
1	Charge	L_int = −eψ̄γψA	e(μ) runs with encounter scale; bare e_0 infinite	The coupling at scale μ	PORT_PARTITION_EXACTNESS
2	Spin	F = ∇(μ·B), S·n̂	Axis n̂ dropped from "spin-1/2"; Bell falsifies local pre-existence	The axis; the value (Bell)	RELATIONAL_ROLE_THEOREM
3	Mass	m_f = y_f v/√2	VEV encounter forgotten; m² from decay products	The Higgs coupling; the kinematic fit	Paper 8 (mass as ledger) (Appendix E.8)
4	Color	L_QCD with ψ_i, i∈{r,g,b}	Gauge label promoted to possession; cancels from S-matrix	Everything (gauge-dependent)	STRUCTURAL_INSULATION
5	Flavor	J^μ = ūγ^μV_CKM d	Basis-dependence (V_CKM) treated as correction, not refutation	The interaction basis	RELATIONAL_ROLE_THEOREM
6	Mag. moment	a_e = Σ C_n(α/π)^n	12,672 virtual encounters attributed to "the electron"	The loop sum itself	ASPECT_AGGREGATION [LEVEL A, author-authorized]

Badge note (row 6): ASPECT_AGGREGATION carries [LEVEL A, author-authorized] — a declared bookkeeping rule, not a derived result (§0.5.6; Appendix E.5). Its stated falsifiers: a tick where a port contribution is attributable to two aspects or to none (rule-ii disambiguation applied), or a T-action altering contributions of aspects that own neither touched port. The other counterparts carry plain [LEVEL A] via the machine or prose validation named in their Appendix E inheritance lines.

Result: 0/6. In no case does "intrinsic" appear in the equations. In every case it appears in the prose gloss on the equations. The audit's finding is not that the standard model is wrong about the numbers — it is that the standard model's own formalism already encounter-indexes every property, and only its prose claims otherwise. The equations are Paper 11's witnesses; the textbooks are the defendants.

3.8 The Casimir defense: why Poincaré invariants don't save intrinsicality

The strongest counterargument from quantum field theorists runs: "Mass and spin are not 'encounter' properties; they are Casimir invariants of the Poincaré group ISO(3,1), defined independently of any measurement." This subsection dismantles that defense — not by disputing the mathematics, which is correct, but by showing that Casimir invariants classify potentialities of interaction, not intrinsic possessive properties. (Executable: P.6.)

The invariants. For the Poincaré group, the two Casimir operators are:

- $P_\mu P^\mu = \eta^{\mu\nu} P_\mu P_\nu = m^2c^2$ (mass-squared)
- $W_\mu W^\mu = -m^2c^2\, s(s+1)$ (spin), where $W_\mu = \tfrac{1}{2}\varepsilon_{\mu\nu\rho\sigma} J^{\nu\rho} P^\sigma$ is the

Pauli-Lubański pseudovector.

These commute with all generators; every state in an irreducible representation carries the same eigenvalues. The defense claims this frame-independence constitutes intrinsicality: m and s are "there" regardless of encounter.

Reply 1: Metric dependence. The contraction $P_\mu P^\mu = \eta^{\mu\nu} P_\mu P_\nu$ depends explicitly on the background metric $\eta^{\mu\nu}$. The operator $P_\mu = -i\hbar\partial_\mu$ generates translations relative to a coordinate frame. Conceded without reservation: within a fixed Minkowski background the Casimir is frame-independent — the mathematics is correct, and this reply does not dispute it. The point is narrower: the "invariant" is invariant only relative to that fixed background structure — and that structure is supplied by the world the particle inhabits, not by the particle alone. Remove the metric (ask what $P_\mu P^\mu$ means with no spacetime structure at all) and the expression is unanchored. The invariant classifies how the state transforms under the symmetries of the background; it does not float free of that background. (Separately, and not needed for the Poincaré-group point: in general relativity the same moral sharpens — $P_\mu P^\mu = g^{\mu\nu} P_\mu P_\nu$ depends on the spacetime metric the environment provides.)

Reply 2: The Pauli-Lubański vector needs a direction. For massless particles, W_μ is proportional to P_μ ($W_\mu = hP_\mu$, h = helicity). The physical projection $h = J\cdot\hat{p}$ explicitly demands a momentum direction $\hat{p}$ — which acquires physical reality only upon interaction (a photon absorbed, a screen struck). For massive particles, extracting "spin up" from the invariant $W_\mu W^\mu = -m^2s(s+1)$ requires $S\cdot\hat{n}$: the axis $\hat{n}$ that the apparatus provides (P.1, P.2). The Casimir says "spin-1/2 representation"; the encounter says "along this axis, $+\hbar/2$." The defense conflates the classifier with the reading.

Reply 3: Labels vs. readings. A Casimir invariant specifies which vector space a state lives in — a mathematical classifier. Extracting a numerical value in an experiment requires contracting that state with a co-state $\langle\psi|$ defined by an interaction vertex. The invariant answers "what kind of thing can interact here"; the encounter answers "what value resulted." To call m^2 an "intrinsic property" because it labels the representation is exactly Whitehead's fallacy (§2.1): promoting a category of thought (representation label) into concrete furniture (possessed property). P.6 computes both sides: same m^2 in two frames (the classifier is frame-free), different p^μ components in each frame (every reading is frame-indexed). The defense proves less than it claims — it proves classification, not possession.

3.9 The scale fingerprint: any quantity that needs a μ has surrendered

This subsection states aggressively what §§3.1–3.6 establish severally: scale dependence is not an inconvenience for the intrinsic reading — it is its refutation.

Once a quantity depends on the renormalization scale μ, it is no longer a property of the particle. It is a property of the particle-plus-probe system. The probe's momentum transfer is the encounter index: μ is set by the encounter's energy, the scale at which the probe resolves the target. To say "α(μ) runs" is to say "the coupling is indexed by the encounter." There is no reading of "intrinsic" — not (a), not (b), not (c) of §1.5 — under which a μ-dependent number is possessed independently of encounters. Reading (b) (invariant functional form) survives, but (b) is encounter-indexing: the form governs encounters; it does not float free of them. Reading (d) (dispositional: intrinsic dispositions, relational manifestations) is not refuted by the fingerprint — but it was never the fingerprint's target. Reading (d) already

concedes that no value is possessed independently of encounters, which is the concession the paper asks for; it is answered on its own terms in §7.4. The fingerprint's billing is therefore precise: it closes the possession readings (a)–(c). It does not touch (d), because (d) grants the point.

The standard retreat — "the bare parameters are the intrinsic ones" — gets the direction backwards. Bare parameters live at the cutoff Λ, pushed to a regime where no experiment can reach them. A "possession" that is defined precisely where nothing can ever be possessed is not a property; it is the opposite of a property. It is a bookkeeping entry at infinity, and the RG equations themselves say so: the bare coupling is scheme-dependent, cutoff-dependent, and infinite in the continuum limit. What the intrinsic reading needs — a finite, scale-free, encounter-independent number — is exactly what the formalism refuses to supply, at every scale, in every scheme.

The fingerprint generalizes beyond couplings. Quark masses run ($m_b(m_b) \neq m_b(M_Z)$). The CKM elements run. The VEV is defined at a scale. Every "intrinsic" number in the particle data tables is either scale-indexed explicitly or defined in a scheme that smuggles the scale in. The tables are honest — they quote schemes and scales. The prose that calls the entries "intrinsic properties of the particles" is not reading the tables it prints.

Therefore: any quantity that requires a scale to be defined has already surrendered the claim to intrinsicality — on the possession readings (a)–(c). This is not one audit row among six. It is the master argument of which the six rows are instances, against those readings. (Reading (d) stands outside this argument, as noted above.)

4 SHARP CONTRAST

The 9.5 method: place the two accounts side by side on the same phenomenon, then ask which one derives its result and which one infers it. Each row: the phenomenon, what the standard account derives (equations), what it infers (the intrinsic gloss), what Paper 11 derives (Level A), and the verdict.

4.1 The contrast table (equation level)

#	Phenomenon	Standard: derived	Standard: inferred (the gloss)	Paper 11: Level A status	Verdict
1	Stern-Gerlach splitting	$F = \nabla(\mu \cdot B)$ gives two spots along $\hat{n}$; $S \cdot \hat{n}$ eigenvalues $\pm\hbar/2$	"Electron has intrinsic spin-1/2" — the axis $\hat{n}$ dropped, the value promoted to a possession	RELATIONAL_ROLE_THEOREM: no intrinsic roles; spin value is the per-tick reading	Category mistake. The derived result is encounter-indexed (needs $\hat{n}$); the inferred gloss contradicts the derivation. Bell violations falsify the local gloss experimentally.
2	Hadron scattering rates	SU(3) gauge theory predicts σ with color factors $C_F=4/3$, $C_A=3$; S-matrix has no free color index	"Quarks carry intrinsic color (r,g,b)" — the gauge label promoted to a possession	STRUCTURAL_INSULATION_THEOREM: bookkeeping labels ≠ ontology	Intrinsic only in prose. The derived result cancels color from every observable; the gloss asserts what the derivation forbids (Elitzur).
3	$e^+e^- \to$ hadrons rate	$R = 3\Sigma e_q^2$ matches data	"Three intrinsic colors" — the number 3 in the rate promoted to three possessions	Same as above	Reified arithmetic. The 3 is a representation dimension doing work in a formula, like π in $A=\pi r^2$.
4	Particle masses (511 keV etc.)	$m^2 = E^2-p^2$ from decay kinematics; $m_f = y_f v/\sqrt{2}$ from Higgs coupling	"Intrinsic mass" — the VEV encounter forgotten, the kinematic fit reified	Paper 8: mass as ledger accounting of departure from c (Appendix E.8)	Reified bookkeeping. Both derivations run through encounters (decay products; Higgs field).
5	K^0–$\bar{K}^0$ oscillations	V_{CKM} rotates weak vs. mass bases; time evolution mixes flavor labels	"Intrinsic flavor" — the basis-dependence treated as a correction	RELATIONAL_ROLE_THEOREM: flavor is the weak-encounter role label	Self-refuting. The formalism's own CKM matrix records basis-dependence; the gloss claims basis-independence.
6	g−2 to 10 decimals	$a_e = \Sigma\, C_n(\alpha/\pi)^n$ over 12,672 virtual-encounter diagrams	"Intrinsic magnetic moment" — 12,672 encounters attributed to "the electron"	ASPECT_AGGREGATION [LEVEL A, author-authorized]: attribution is a declared convention (falsifiers: Appendix E.5)	Precision misattributed. Every decimal comes from encounter diagrams; "intrinsic" adds none.
7	Charge measurements	α(μ) runs: 1/137 → 1/128 [LEVEL B: rounded physical idiom; PDG $\alpha(M_Z) = 1/127.9$]; bare e_0 divergent	"Intrinsic charge −e" — the scale μ dropped, the divergent bare value ignored	PORT_PARTITION_EXACTNESS: coupling is per-tick port geometry	Scale amnesia. The derived coupling is μ-indexed; the gloss claims μ-independence the RG equation denies.
8	Spin correlations (EPR)	QM predicts $2\sqrt{2}$; experiments confirm ~2.7, violating CHSH ≤ 2	(No local gloss survives — the data forbids pre-existing local values)	TENSION_MEASURE_IDENTITY: the value is the reading	Gloss falsified. (local scope) This is the one case where the inferred "intrinsic" is not just untestable but experimentally refuted as a local model.

4.2 Their derivation vs. our derivation — the 9.5 comparison

Paper 9.5's method was: show the standard account deriving temperature from statistics (and patching the ledger when it breaks), then show the native account deriving heat as interaction events from first principles — and ask which derivation has fewer unearned steps. Apply the same method here.

Spin, standard derivation:

1. Write Dirac equation (from Lorentz invariance + quantum mechanics — both assumed).
2. Find spin-1/2 representation (group theory — derived).
3. Couple to EM field via minimal substitution (assumed).
4. Compute Stern-Gerlach splitting along n̂ (derived — needs the axis).
5. Gloss: "the electron has intrinsic spin-1/2" (inferred — drops n̂, contradicts step 4).

Spin, Paper 11 derivation:

1. Port presents values per-tick (axiom — declared, not derived).
2. Unmatched integers → tension → shove → relief (derived — T operator, Level A).
3. Role assigned to (aspect, tick, encounter) (derived — Relational Role Theorem, Level A).
4. No step 5. There is no gloss because there is nothing to gloss — the derivation

ends at encounter-indexing.

Count the unearned steps: standard has one (step 5, the intrinsic promotion, which contradicts step 4 and is falsified by Bell for local models). Paper 11 has zero — every step is either declared (step 1, honestly labeled as axiom) or derived (steps 2–3, Level A).

Color, standard derivation:

1. Postulate SU(3) gauge symmetry (assumed — chosen to fit the hadron spectrum).
2. Assign quarks to the fundamental representation (assumed — the "three colors").
3. Compute S-matrix elements (derived — color cancels by gauge invariance).
4. Compare to data: rates match (derived — the numbers work).
5. Gloss: "quarks carry intrinsic color charge" (inferred — contradicts step 3,

which proves color never appears in any observable).

Color, Paper 11 derivation:

1. Labels index bookkeeping per-tick (declared).
2. STRUCTURAL_INSULATION (Level A): working labels ≠ ontological commitments.
3. No step 5. The label does its job in the calculation and is not promoted.

The pattern is uniform across all six properties: the standard derivation is encounter-indexed through step N−1 and then takes one unearned step (the intrinsic promotion) that its own step N−1 contradicts. Paper 11 stops at step N−1 — where the derivation actually ends — and declines the promotion. That refusal is not modesty. It is accuracy.

4.3 What is inferred vs. what is proven — the ledger

Claim	Status in standard account	Status in Paper 11
"Spin values are encounter-indexed"	Proven (S·n̂ needs n̂; Bell bars local pre-existence) but glossed over	Proven [Level A: Relational Role Theorem]
"Color cancels from observables"	Proven (gauge invariance, Elitzur) but glossed over	Proven [Level A: Structural Insulation]
"Charge runs with scale"	Proven (RG equation) but glossed over	Proven [Level A: Port-Partition Exactness]
"Flavor is basis-dependent"	Proven (CKM matrix) but glossed over	Proven [Level A: Relational Role Theorem]
"g−2 is a sum over encounters"	Proven (loop expansion) but glossed over	Declared axiom [LEVEL A, author-authorized]: Aspect Aggregation — falsifiers stated in Appendix E.5
"Mass comes from encounters"	Proven (kinematics; Higgs VEV) but glossed over	Proven [Paper 8: mass as ledger] (Appendix E.8)
"Particles have intrinsic properties"	Inferred, never derived, Bell-falsified (local) for spin	Denied [Level A] (§0.5.1)

The left column's "proven" entries are the standard formalism's own theorems. The critique's originality is not in discovering encounter-indexing — Bell, the RG, Elitzur, and CKM discovered it — but in refusing to look away from what was discovered. Every "proven" in the left column is followed by "but glossed over": the formalism proves encounter-indexing, and the prose claims intrinsicality, and the two are never reconciled. Paper 11 is what the reconciliation looks like.

5 THE REIFICATION MECHANISM

How bookkeeping becomes ontology — the five-step pattern. Each step is legitimate except the slide from 2→3, where the encounter-indexing is dropped. What follows works the pattern concretely for each of the six properties, so the mechanism is exhibited, not merely described.

5.1 The five steps, stated once

1. Operational definition. A quantity is defined via a measurement procedure.
2. Context elision. The procedure's context — axis, field, scale, gauge, basis —

is dropped from the textbook statement.

3. Possessive predication. The quantity is predicated of the particle in

possessive grammar ("the electron has spin").

4. Reification. The predication hardens into ontology ("spin is a property

of the electron, carried with it between encounters").

5. Explanatory use. The reified property is invoked to explain the encounter

pattern ("because it has spin-1/2, the beam splits") — explaining the encounter by the abstraction the encounter defined. The circle is concealed by step 2's elision. The reference-fixing reply is granted its premise — operational definitions do fix reference — but the explanatory work is done by the laws, here the Dirac equation's S·n̂, not by the reified possession, which adds nothing the law doesn't already say.

5.2 Worked examples

Spin.

1. Operational: "spin is what the Stern-Gerlach apparatus splits along its field axis."
2. Elision: "the electron has spin-1/2." (Which axis? Dropped.)
3. Possessive: "the electron's spin."
4. Reification: "spin-1/2 is an intrinsic property of the electron."

5. Explanatory: "the beam splits because the electron has spin-1/2." But the

"spin-1/2" was abstracted from beam-splittings. The explanation is circular — and Bell's theorem breaks the circle empirically for local models: the value did not pre-exist as a local possession.

Color.

1. Operational: "color is the SU(3) label that makes the hadron rates come out right."
2. Elision: "quarks carry color charge." (Which gauge? Dropped — and it matters,

because the bookkeeping differs by gauge.)

3. Possessive: "the quark's color."
4. Reification: "color charge is an intrinsic property of quarks."
5. Explanatory: "hadrons are color singlets because quarks carry color." But

"color singlet" was defined as the gauge-invariant combination — the explanation restates the definition as if it were a discovery about quarks.

Charge.

1. Operational: "charge is the coupling extracted from scattering at scale μ."
2. Elision: "the electron has charge −e." (At what scale? Dropped — yet α runs

from 1/137 to 1/128 [LEVEL B: rounded physical idiom; PDG α(M_Z) = 1/127.9].)

3. Possessive: "the electron's charge."
4. Reification: "charge −e is intrinsic to the electron."
5. Explanatory: "it scatters because it has charge." But the charge is the

scattering coupling — the explanandum renamed as explanans.

Mass.

1. Operational: "mass is $m^2 = E^2 - p^2$ reconstructed from decay products" (or

"$m_f = y_f v/\sqrt{2}$ from the Higgs coupling").

2. Elision: "the electron has mass 511 keV." (From which decays? At what VEV?

Dropped.)

3. Possessive: "the electron's mass."
4. Reification: "mass is intrinsic to the electron."
5. Explanatory: "it resists acceleration because it has mass." But "mass" was

defined via resistance to acceleration (F=ma) or via the energy-momentum relation. The circle is three centuries old and still unbroken in the textbooks.

Flavor.

1. Operational: "flavor is which weak vertex the quark participates in."
2. Elision: "the quark is strange." (In which basis? Dropped — yet the CKM matrix

exists precisely because the basis matters.)

3. Possessive: "the quark's flavor."
4. Reification: "strangeness is an intrinsic property."
5. Explanatory: "it decays weakly because it has strangeness." But strangeness

was defined as "participates in certain weak decays." K^0 oscillations then refute the reification directly: the "intrinsic" flavor changes with time.

Magnetic moment.

1. Operational: "the moment is the precession frequency in a B field, matching

the loop sum ΣC_n(α/π)^n."

2. Elision: "the electron has magnetic moment μ_e." (In which field? From which

diagrams? Dropped — yet the value is the diagram sum.)

3. Possessive: "the electron's magnetic moment."
4. Reification: "μ_e is intrinsic to the electron."
5. Explanatory: "it precesses because it has a magnetic moment." But the moment

was computed from precession-matched diagrams. The 12,672 virtual encounters are in the calculation and out of the explanation.

5.3 The promotion, watched in real time

§5.2 gave the five steps abstractly. Here is one promotion watched end to end, starting from a paraphrase of the standard textbook presentation. (The paraphrase is in the §3.1 textual-evidence block; it is not a located quotation — a full-text search of Griffiths' Introduction to Elementary Particles (2nd ed.) did not find it verbatim, and the Griffiths address is withdrawn. The PDG-table half of the evidence stands as printed.)

"The electron's charge is an intrinsic property — it is the same in all

frames, at all energies, in all contexts."

Step 1 — Operational definition. The charge −e is what the Millikan oil-drop measured, what scattering cross-sections extract, what the coupling in QED's vertex is at a given scale. Every determination runs through an encounter: a field, a probe, a momentum transfer μ.

Step 2 — Context elision. "The same... at all energies." The scale index μ is dropped. But the QFT formalism derives the running of α (Appendix B.1): 1/137 at low energies, 1/128 [LEVEL B: rounded physical idiom; PDG α(M_Z) = 1/127.9] at LEP energies. "At all energies" is contradicted by the formalism's own equations — the elision is not a simplification, it is a falsehood about the formalism.

Step 3 — Possessive predication. "The electron's charge." The coupling — a number characterizing the electron-photon vertex, i.e., an encounter — is predicated of the electron alone. The photon, the vertex, the scale: all absorbed into the possessive.

Step 4 — Reification. "An intrinsic property." The predication hardens: the charge is now something the electron has, carried with it between encounters, possessed independently of any measurement. This is reading (a) of §1.5, asserted without argument.

Step 5 — Explanatory use. Two chapters later, the student reads that the electron scatters off the proton because it has charge −e. But the charge is the scattering coupling — abstracted from encounters like this one. The explanation is circular: the encounter pattern is explained by the property, and the property was abstracted from the encounter pattern. The circle is concealed by Step 2's elision — if the scale had stayed in the sentence ("charge −e at μ = m_e"), the student could ask "what sets μ?" and the answer ("the encounter's energy") would break the circle.

Watch what happened: a true statement ("the coupling is −e at low energies") was elided into a false one ("the same at all energies"), possessivized, reified, and then used to explain the very encounters it was abstracted from. Five steps, one sentence. Every §3 audit is this promotion, repeated.

5.4 Why the mechanism is invisible

The reification is invisible because each step is locally reasonable. Step 1 is good science (operational definitions). Step 2 is good pedagogy (simplification for textbooks). Step 3 is good grammar (possessives are compact). Step 4 is where the error enters, but it feels like step 3 — "the electron's spin" slides into "spin, a property of the electron" without any alarm sounding. By step 5, the circle is complete and the textbook is written.

Whitehead's name for step 4 is the fallacy of misplaced concreteness (§2.1). Mach's name for the whole sequence is expecting "more than we have put into" the symbols (§2.3). Bell's name for step 5's "preexisting property" language is the charge against "measurement" (§2.5). The witnesses each saw a different step. The mechanism is the same.

5.5 The mechanism is not in the equations

This is the decisive point, and it bears repeating because it is the audit's strongest form: the five-step reification happens entirely in prose. Open the Lagrangian — L_int = −eψ̄γ^μψA_μ — and find step 4. It is not there. Open the S-matrix — color singlets only — and find "intrinsic color." It is not there. Open the CKM matrix — explicit basis rotation — and find "intrinsic flavor." It is contradicted there. The equations of the standard model are, without exception, encounter-indexed. The reification is a commentary on the equations that the equations do not support and in three cases (Bell for local models, Elitzur, CKM) actively refute.

A defender might reply: "the prose is just shorthand; no working physicist believes the gloss literally." Two responses. First, the particle tables, the PDG listings, and the textbook summaries present the gloss without the shorthand flag — students learn "intrinsic properties" as ontology, not as abbreviation. Second, and decisively: when the gloss contradicts the equations (Bell violations, gauge cancellation, basis rotation), the gloss is not harmless shorthand but false shorthand — and false shorthand taught as fact is exactly what a critique paper exists to correct.

6 FALSIFICATION

What would vindicate intrinsic properties: exhibit a property with a definite value measured without any encounter — no field, no apparatus, no interaction partner, no axis, no context — yet yielding the textbook number.

This is impossible by the definition of measurement, which is precisely the point. A property that cannot be determined without an encounter, whose value is undefined without the encounter's parameters, and whose "intrinsic" status adds no predictive content, is not a discovery about particles. It is a habit of grammar.

The paper's claim is therefore refutable in the strong logical sense: if one property determination with no encounter-indexing were produced, the audit's 0/6 would become 1/6, and the thesis would fall. The conditional is strict — but the paper's position, stated plainly in the next paragraph, is that the antecedent is unsatisfiable by the definition of measurement. What follows is a proof by contradiction, not a hypothesis test awaiting data. No such determination exists in the literature, and none is logically available under the definition; that absence is the evidence.

A clarification of logical form — proof by contradiction, not hypothesis test. A referee may object: "your falsification condition cannot be met, therefore your thesis is unfalsifiable, therefore it's not physics." The objection misidentifies the logical move. The condition is not offered as a hypothesis test. It is offered as a proof by contradiction: if "intrinsic" were an empirical claim, this is the test it would need to pass. It cannot pass — not contingently, but by the nature of measurement (determination is an encounter). Therefore "intrinsic" is not an empirical claim. It is a grammatical habit. The proper phrasing: the condition shows what test the claim would face, and the impossibility of the test is the result. This is the same logical form as Bell's theorem — which does not "test" local realism but shows no test could vindicate it.

Two distinct falsification routes — not one (RT-03). The condition is not rhetorical, but it operates in two logical forms that must not be conflated. Route (i) — the conceptual boundary: The experimental program the falsification condition defines. For each property, the challenger must exhibit a determination procedure satisfying three criteria: (i) no field, apparatus, or interaction partner whose parameters enter the result; (ii) a definite numerical value obtained; (iii) the value matches the textbook "intrinsic" number. Criterion (i) is the hard one: any procedure satisfying (ii) and (iii) will, on inspection, contain an encounter — because determination is an encounter. This is not a trick; it is the point. The condition is unsatisfiable by the nature of measurement, which means "intrinsic property" is not an empirical hypothesis but a grammatical one. A hypothesis that cannot be tested even in principle, that adds no predictive content, and that contradicts the formalism's own theorems (Bell, Elitzur) in three of six cases, is not a scientific claim awaiting evidence. It is a habit awaiting retirement. Route (ii) — the empirical program: §8.2 H.2 attempts the derivation the intrinsic reading actually needs — encounter-independence derived from the formalism — and reports exactly where each chain bottoms out (0/6 derived; REFUTED steps in three chains, GAP verdicts in four — spin carries both, §8.3). This route is genuinely open to equations for the three GAP properties (charge, mass, magnetic moment): a derivation would move one out of the 0/6 column. For the REFUTED readings (spin's pre-existing-local-values reading, color, flavor) the door is closed by the cited theorems themselves — Bell (local models), Kochen-Specker (non-contextual assignments), Elitzur (gauge-variant VEV) — and reopening it would mean overturning those theorems, not merely finding a derivation. The paper's "falsifiable" language throughout refers to route (ii); route (i) is the proof by contradiction above.

What would change the verdict. The audit is property-by-property, not all-or-nothing. If a future formalism derives — not glosses, derives — an encounter-independent property value, that property leaves the 0/6 column and the paper's thesis weakens accordingly. The author invites this: the falsification condition is stated precisely so that a derivation can meet it (route (ii) above). What cannot meet it is more prose. Only equations count, and the equations have already voted.

Scope pointer. "Encounter" in this section carries the §1.3 declaration (determination-procedure sense); the native encounter criterion belongs to Paper 9 and is not defined here.

7 OBJECTIONS AND REPLIES

The critique anticipates its strongest counterarguments. Each objection is stated at full strength — steelmanned, not strawmanned — then answered.

7.1 "The predictions work, so the ontology must be right"

Objection. The Standard Model predicts the electron g−2 to ten decimal places, the Higgs mass, the W/Z masses, countless cross-sections. An ontology that generates this predictive success cannot be fundamentally mistaken about its entities. The "intrinsic properties" must be latching onto something real.

Reply. Predictive success latches onto the equations, not the gloss. Every successful prediction cited runs through the encounter-indexed formalism: the g−2 loop sum (encounters), the RG equations (scale-indexed), the S-matrix (gauge-invariant singlets). The predictions work because the equations are encounter-indexed — the success is evidence for the audit, not against it. What has never been tested is the extra claim — the step-4 reification, the "intrinsic" promotion — because it adds no predictive content. (G.4 verified: "intrinsic" appears in prose, never in derivations.) An ontology can be predictively successful and descriptively false about its own entities whenever the success flows through the equations and the falsity lives in the commentary. Ptolemaic astronomy predicted eclipses.

7.2 "You're attacking a strawman — no physicist believes properties are truly intrinsic"

Objection. Working physicists know that "intrinsic spin" is shorthand. The field-theoretic description (states in Hilbert space, gauge-invariant observables) already encodes the contextuality. The critique attacks a textbook simplification, not the actual position.

Reply. Three responses. First, G.3 verified: the critiqued statements are cited to actual textbooks (Griffiths, Peskin & Schroeder, Halzen & Martin, PDG) — the positions are held in print, not invented. Second, the "shorthand" defense fails where the shorthand contradicts the equations: Bell violations falsify pre-existing local spin values, yet "intrinsic spin-1/2" is still taught as a standing property. Shorthand that contradicts known theorems is not shorthand but error. Third, the next generation learns the gloss as ontology. If the experts all know it's shorthand, the pedagogy should say so — it doesn't. A critique paper exists precisely for the gap between what experts privately know and what the literature publicly claims.

7.3 "Paper 11's ledger has the same problem — ticks and ports are unobservable"

Objection. Van Fraassen's symmetric cut (Appendix A.8, disclosed complication): the paper withholds belief from standard-model unobservables but posits its own — ticks, ports, unmatched integers, the a_k ordering. If "intrinsic" is misplaced concreteness, so is "port." The critique is self-undermining.

Reply. The difference is badge discipline. Paper 11 declares its primitives as primitives — the Port Status binary and the a_k ordering are declared as primitives; Aspect Aggregation is a declared axiom, [LEVEL A, author-authorized] with stated falsifiers (Appendix E.5); derived claims name their derivation. The epistemic status is stated on every claim. The standard model derives encounter-indexed results and then glosses them as intrinsic without flagging the promotion. Paper 11's ledger says "this is the bookkeeping, honestly labeled." The standard gloss says "this is the furniture of the

world" about bookkeeping it won't label as such. The objection conflates using unobservables (both frameworks do) with misdescribing what the unobservables are doing (only the gloss does). Honest bookkeeping is not misplaced concreteness; dishonest bookkeeping — promoted without declaration — is.

7.4 "Dispositional realism: properties can be intrinsic dispositions"

Objection. (The Heisenberg potentia complication, §2.2.) Perhaps "intrinsic" means "intrinsic disposition" — the electron doesn't have spin-up, but it has the disposition to show spin-up along any axis. Dispositions are intrinsic (categorically possessed) even though their manifestations are encounter-indexed. The critique conflates categorical and dispositional intrinsicality.

Reply. The dispositional move saves the word "intrinsic" by changing its meaning — from "possessed value" to "possessed capacity." But Paper 11 already has the better version: CAPABILITY_ACTUALITY_SEPARATION [LEVEL A]. The capability ("can present $\pm\hbar/2$ along a presented axis") is structural and stable; the value exists only per-encounter. Calling the capability "intrinsic disposition" adds nothing except the suggestion that the capability is carried rather than structural — and "carried" is exactly the reification the audit targets. Moreover, the dispositional retreat concedes the main point: if "intrinsic" now means "has the capacity," then nothing with a definite value is intrinsic — which is what the textbooks claim and what the audit denies. The objection redefines "intrinsic" into compatibility with the critique.

Scope note. This reply uses the working capability/actuality distinction without constructing it. 11.5 is a companion critique, not a foundational paper: the formal account of capability as a relation to possible encounters — what makes a capability structural rather than carried — is Paper 12's work. Nothing here certifies it; the distinction is used, not derived.

7.5 "The Higgs mechanism gives genuinely intrinsic mass"

Objection. Whatever the case for other properties, the Higgs mechanism provides a genuine origin for intrinsic mass: the Yukawa coupling to the VEV is a fixed Lagrangian parameter, and $m_f = y_f v/\sqrt{2}$ is determined without any laboratory encounter. This is as intrinsic as physics gets.

Reply. Appendix B.3 works this fully, but the short version: v is a field value everywhere — the vacuum expectation. "Without any laboratory encounter" is true and irrelevant; the encounter was relocated to the vacuum, not removed. y_f is a coupling (interaction strength); v is a background field; their product is a two-body quantity with one body (the Higgs field) held fixed and forgotten. Furthermore, the VEV itself is scale-dependent (the effective potential runs), so even the "fixed" background is encounter-indexed at a deeper level. The Higgs mechanism is the most sophisticated version of step 2 (context elision) in the literature — the context is the entire vacuum, so eliding it feels like removing it. It isn't.

7.6 "This is philosophy, not physics"

Objection. The audit is conceptual analysis — Whitehead, Mach, "fallacy of misplaced concreteness." Physics is about predictions. A paper with no new predictions, no new calculations, only conceptual hygiene, is philosophy.

Reply. Bell's theorem is conceptual analysis with experimental consequences — it proved that a conceptual distinction (pre-existing vs. created values) has measurable implications, then the experiments confirmed it. The audit follows the same pattern: the conceptual distinction (intrinsic vs. encounter-indexed) is already in the equations (gauge invariance, RG, CKM, Bell), and the paper's contribution is refusing to look away. Moreover, the falsification condition (§6) is a physics condition in its route-(ii) form: derive — not gloss — encounter-independence from the formalism (H.2 attempted it; 0/6 derived). That is an empirical challenge to equations, not a philosophical musing. Conceptual hygiene that changes what counts as a legitimate property claim is physics — it is what Bohr, Heisenberg, and Bell were doing, and the field honors them for it.

7.7 "Why not just fix the prose and keep the ontology?"

Objection. Granted the gloss overreaches — so drop the word "intrinsic," keep the particles, keep the quantum numbers as useful labels. The critique proves too much if it concludes particles aren't real.

Reply. The critique does not conclude particles aren't real — §1.2 states this explicitly. Configurations are real (Paper 11's structural realism about the ledger). What is denied is only the intrinsic-property idiom: labels are real as labels, encounter-indexed quantities are real as encounter-indexed quantities, and promoting either into "possessions" is the error. "Fix the prose and keep the ontology" is the paper's recommendation — the ontology that survives the fix is the encounter-indexed one, which is Paper 11's. The objection agrees with the conclusion while imagining it disagrees.

7.8 "Shut up and calculate — 'intrinsic' is just pedagogical shorthand"

Objection. Working physicists know the gloss is shorthand. Nobody in a seminar believes spin is "really" a possessed property independent of context. The critique attacks a pedagogical convenience, not a live commitment.

Reply. If "intrinsic" is merely shorthand, then the billions spent searching for intrinsic dark matter particles, the intrinsic cosmological constant, and intrinsic point-particle singularities are budgeted on a pedagogical fiction. Grant proposals do not say "we seek a convenient shorthand"; they say "we seek the particle's intrinsic properties." The framework must pick one: either the gloss is live (and then it faces Bell, Kochen-Specker, and Elitzur), or it is shorthand (and then the research programs built on it are misdescribed). Paper 11 picks one — encounter-indexing, all the way down. The SM uses "intrinsic" in the textbook and "shorthand" in the seminar. That is not a defense; it is the C7 failure, stated as a sociology of the field.

7.9 "Paper 11 is just a reinterpretation — same math, different philosophy"

Objection. The equations are untouched. All Paper 11.5 does is re-read them relationally. This is philosophy of physics, not a substantive critique.

Reply. This is precisely the H.4 point, and it cuts against the objector. The critique does not ask anyone to abandon the Standard Model's equations — it asks them to read them. The equations are encounter-indexed: the RG flow carries μ, gauge invariance carries ξ, Kochen-Specker demands contextuality, the CKM matrix rotates bases. Every one of these is standard, textbook, uncontroversial mathematics. The "intrinsic" philosophy is a parasitic gloss — it contributes no equations, predicts nothing the equations don't already predict, and contradicts the theorems (Bell, KS, Elitzur) the equations prove. Removing a parasite is not "reinterpretation." Paper 11 is not a new philosophy of the same math; it is a demand for prose/equation alignment, with the machine receipts (H.1–H.4, P.1–P.10) to show the alignment holds on one side and fails on the other.

8 MACHINE VERIFICATION: THEIR EQUATIONS UNDER OUR RIGOR

The audit of §§3–4 was prose analysis: reading equations and showing the encounter-indexing. This section goes further. It takes Paper 11's verification machinery — the badge discipline, the derivation-attempt protocol, the verdict-layer consistency check, the honesty criteria — and turns it outward on the Standard Model's "intrinsic property" claims. (The consistency check runs inward: H.3 verifies this paper's own verdict layers agree with each other, §8.4.) The machinery was built to keep Paper 11 honest. Turned outward, it measures the honesty gap.

Two columns, stated up front (§0.5.5). Every output in this section sits in one of two columns. COMPUTED — P.1–P.6, P.7 blocks 1–2, P.8's spread exhibit, P.9 Parts 1–2, P.10's machine-derived counts (1- and 2-loop; 3–5-loop cited-paper oracle), MC.1 step 1: real quantities calculated from equations; the machine does the work and the reader can check the numbers. CLASSIFIED — the H-series, the G-series, PA.1, P.7 block 3 (leading-log IR shift — declared assumption: leading-log only), and FW.1's voice judgments: the author's classifications printed by scripts; the machine checks the bookkeeping, not the judgment. Each subsection below is labeled with its column. Nothing classified is presented as a second independent machine result.

Run record (v24 — pinning outputs to sources). Each §8-reported output is produced by the exact script file whose sha256 is pinned in this table. A changed script changes its hash, so the pin is mechanical: if any row's output is questioned, re-hash the named source file and compare. Hashes cover the script sources as embedded in Appendix G

(byte-identical to the listings) and the Appendix J engine listing. Run date for every row: 2026-10-18.

Script | sha256 of the source file as embedded | Key constants the §8-reported output depends on | Run date

FW.1 | 74d049c1c723dd27df02e5acb4769b290342293122b2b29b1b515e6908727717 | 3 sweep groups (A/B/C); Group B six-term inventory (the two docstring-promised terms now in code; same-line grounding test); Group C +moment; intrinsic_quoted exemption documented (zero live instances); mutant battery +B3/+C2/+A2-diagnostic | 2026-10-18

G.1 | 8ca23e2e5471eb6d431683488f1d578b81f3472923f7fd352ec2d8e1ebf3e436 | §2 blockquote subsections each carry a "> —" attribution | 2026-10-18

G.2 | 3ba38ad32e1bd250de8c97e6f9e490ee61f3d66c4633b0ae84058de0c8daecc3 | strict 7-cell row regex; loose " | N | " count assertion (v24) | 2026-10-18

G.3 | 2f0eb9ff9864edaaa7f6afc6ddd9a7c72db1f5f33433fa80f87e94488e194719 | attribution search scoped to the (a) textbook-statement block (v24) | 2026-10-18

G.4 | f760b0619e5d6ee9ad8219565e90e8aa62cf64d1ec807b15d1e6f5d301ba3707 | 4 hedge spellings (named in the listing docstring); absence checked in prose outside fenced code | 2026-10-18

H.1 | ff097be89d2eda20d5b92398e74089481a9b40e97f301275c4c5578b0f5d658a | 6 property claims; DERIVED/DECLARED/SMUGGLED badge rules; F.49 hygiene (smuggled = REJECT); v24: [LEVEL A, author-authorized] subtype formalized (V23-3 ruling) | 2026-10-18

H.2 | 2a15d85d5a0ca9f3fe8451423422ef1c860aa29c8f7bef7636b112bdde06fce6 | derivation steps VALID vs GAP; mirrors F.57 null-result protocol | 2026-10-18

H.3 | 739281704ac9fff52f1786b789fad0c24bf60d598e56393364e0bb02e26aba93 | 7-cell verdict map (6 properties, spin split); structural checks A-G over section 8.1/8.2/8.3/8.4/8.5-C2/3.x verdict layers; 9-case planted-mutant battery run pre-build (external harness, not in-script); 0 DERIVED cells (computed) | 2026-10-18

H.4 | 748fee3a2dd18bf6888410c132cdb7274600131b31540e772c944aba9ebb5a20 | 7 criteria C1-C7; COMPUTED/INHERITED/HUMAN-JUDGMENT cells; verdicts with evidence locators, no baked verdicts | 2026-10-18

MC.1 | aafc5f8c5aa8a361ffa2822887f100468f8afabf963273284f21caf992a1906d | fitted exponent −1.9886 [LEVEL A: MACHINE / AUTHOR] recomputed live (log-log least squares, d=5..20; fit machinery KEEP+DISCLOSED — the number IS the fit); exact-rational bound \| R(d)−1\| <1/d² (decreasing, d=5..19) as [LEVEL B] translator beside it; N(d)=4d²+2; seeded integer RNG (randrange only); uniformity assumed (Paper 10) | 2026-10-18

P.1 | faeaddae6a1f890b88a979b34804919059f1ed6824a92de98aeb75146213e26f | Pauli matrices over Z[i]; S²=(n·n)I exact ⇒ eigenvalues ±1; axis constitutive | 2026-10-18

P.2 | 5b8488e49eefd9a8b82ff07b55aebaefc812ab8feb49f404784e42e654a48e2e | S=2√2 exact (S²=8); deterministic lattice R=12 (7,152 orientations); LHV S=296/149≤2 both tie-handlings; binary outcomes | 2026-10-18

P.3 | c778a25bc9497868b0e4d64386646ad591deaed69461a9d9cd9e4759475f7fab | R=3·Σe_q² exact; N_c=3; R=2 exactly; active u,d,s below charm threshold | 2026-10-18

P.4 | 057e62fb9e1d286cabd897513b981bf04a11659491fbb272aba17e7be2381fd6 | N_F=3; α(m_e)=1/137.036 (PDG); 1-loop β=(2n_f/3π)α²; headline α(M_Z)=1/129.34 ≡ table regression; CONTINUUM_USE disclosed (the ODE is the exhibit) | 2026-10-18

P.5 | d9fc4d53219967edef211937a202dcb0200edb5f1973e5661541e1e6bf46ed51 | PDG 2024: s12=0.225, s23=0.041, s13=0.0037, δ=1.14; CKM unitarity; CONTINUUM_USE disclosed (the complex phase is the exhibit) | 2026-10-18

P.6 | d1b9593ca792f7f9228379cca3d2c2fb7df59a857676ba5edc1803eea6c91c34 | β=3/5, γ=5/4 exact; P²=m² exact in both frames; η=diag(+−−−); components differ | 2026-10-18

P.7 | c05eb1a3a7152bde86a29f136030bc77e935435d5cc32caa59b050cb89040aed | α=1/137.035999084 (CODATA 2018); A_exp=0.00115965218059 (Fan et al. 2023); QED coefficients (Aoyama et al.); CONTINUUM_USE disclosed (the series is the exhibit) | 2026-10-18

P.8 | 589ec8f7e908f2ac62b63e6714a6700a29b4f41e17e1f993d93de55dc922adeb | α_s(M_Z)=0.1180 (PDG); C1=4/3; N_L=5; C2=13.4434−1.0414·N_L; γ0=8; CONTINUUM_USE disclosed (the scheme relations are the exhibit) | 2026-10-18

P.9 | a30d97a35da02feddc21aa1447416033c07520a6407b2fb1d94b4af5e251aceb | deterministic lattice R=12 (7,152 orientations, no RNG); DELTA=3/20 declared posit; 81 assignments, bound 2.0; tether S=425/149≈2.8523 in (2.79,2.86); severed S=296/149; 3 mutants caught | 2026-10-18

P.10 | 9947bb744b28214854cea42cefd33f476d803ce98bcc635f204abac9628c142e | 1,7 machine-derived (1PI convention); 72/891/12672 cited-paper (Kinoshita et al.) | 2026-10-18

PA.1 | 6bca53486fbb60617a6d193ca8e6b5613b8fc91887fc729b290e741971f667d6 | fail-loud (a)/(b)/(c) subsection parsing (V23-20); (a)-block/(b)-block scoping (F-39); block-membership-only routing, no cross-category double-counting; 20/55 divergence | 2026-10-18

ESP v2.2 engine (Appendix J) | 6cebc541ae12ef4be166731569c39618af31b71c744ed9d128dcd1837eb0d517 | exact-2.2 version gate; script_id ^(F\ | P\ | H\ | G\ | MC\ | FW\ | PA)\.\d+[A-Z]?$; 267-case conformance green; §3/§9 fixtures drift-pinned (lexical pass + pinned-count regression: §3=85, §9=35 violations) | 2026-10-18

Engine apparatus note (the physics_payload profile). The engine's static check for EXECUTABLE_PYTHON payloads ships two named profiles: "strict" (the default — the full capability ban, no provenance exemptions) and "physics_payload" (for declared verification scripts carrying INPUT_PROVENANCE: sys imports allowed, and float literals bound to module-level UPPER_CASE constants listed in the provenance block under the paper-defined or cited-paper class are

exempt from the LEVEL_A float rule). The exemption's name match is folded-substring — "ALPHA_S_MZ" matches a block entry naming "alpha_s(M_Z)" — which over-matches very short names: a one-letter constant name matches any entry containing that letter. This is a documented heuristic limit of the profile, not a verified exemption: the validator checks the constant is NAMED in a cited/paper-defined entry, never that the citation is genuine (the same honesty boundary as script_id — shape checked, existence not). A conformance case pins the over-match so the limit stays visible; tightening the match is future work, not a silent behavior change.

Four scripts (H.1–H.4), all passing. Their verdicts are reported here verbatim — as the author's classifications, printed for inspection.

8.1 H.1 — The badge audit: 6/6 fail [CLASSIFIED]

Denominator note. H.1 audits the six SM property classes (charge, spin, mass, color, flavor, magnetic moment) — hence 6/6. H.4 (§8.5) separately scores seven honesty criteria C1–C7. The denominators measure different things; neither count is the other's.

H.1 models each SM "intrinsic property" claim as a derivation chain and attempts to assign it a Paper 11-style badge (Level A: derived; Level B: declared assumption; Level C: deferred; NO BADGE: neither derived nor declared).

For each property, the script identifies the exact step where "intrinsic" (encounter-independence) enters the chain, and classifies the mechanism as derived, declared, or smuggled:

Claim	Where "intrinsic" enters	Mechanism	Badge
Intrinsic spin-1/2	Drop the axis n̂; promote "spin along n̂" to "spin full stop"	Smuggled	NO BADGE (REFUTED) — Bell contradicts local pre-existence (§8.3b; the axis-constituted reading itself is GAP, §8.3a)
Intrinsic charge −e	Drop the scale μ; promote "coupling e(μ)" to "charge full stop"	Smuggled	NO BADGE (SMUGGLED)
Intrinsic color (r,g,b)	Promote gauge label to possession; ignore S-matrix cancellation	Smuggled	NO BADGE (SMUGGLED)
Intrinsic flavor	Treat basis-dependence as correction, not refutation	Smuggled	NO BADGE (SMUGGLED)
Intrinsic mass 511 keV	Forget the VEV is a background field	Smuggled	NO BADGE (SMUGGLED)
Intrinsic moment μ_e	Attribute 12,672-encounter sum to "the electron"	Smuggled	NO BADGE (SMUGGLED)

What the labels are. H.1's mechanism labels (REFUTED/SMUGGLED) are author classifications printed by a script: each claim's "smuggled" mechanism is typed into the script's claim table by hand, and the REFUTED/SMUGGLED split is a substring test on the hand-written note — a note containing "contradict" or "falsif" prints REFUTED, otherwise SMUGGLED. The machine checks the bookkeeping; the judgment is the author's.

Why flavor reads SMUGGLED here and REFUTED in H.2 — no contradiction. The two scripts answer different questions. H.1 tests the claim's note language: flavor's hand-written note ("CKM matrix is the formalism's own record of basis-dependence") contains no "contradict"/"falsif" trigger, so it prints SMUGGLED. H.2 tests the derivation attempt: flavor's chain hits the K^0-oscillation contradiction ("intrinsic flavor would forbid what occurs"), so it bottoms out REFUTED. Same property, different questions — the labels differ without contradiction.

Verdict: 0/6 earn Level A/B/C. Under Paper 11's F.49 hygiene rules, all six are REJECT — undeclared assumptions smuggled in prose. Paper 11's counterparts (RELATIONAL_ROLE_THEOREM, PORT_PARTITION_EXACTNESS, STRUCTURAL_INSULATION, Paper 8 mass-as-ledger) carry Level A with the machine or prose proof named in their Appendix E inheritance lines (mass-as-ledger: the Paper 8 v2 Appendix D prose-section derivation — no machine check exists, none claimed); ASPECT_AGGREGATION carries [LEVEL A, author-authorized] — a declared axiom with stated falsifiers (Appendix E.5), not a proved fact.

The point is not that the SM's equations fail — they don't; they predict correctly. The point is that the intrinsic gloss cannot survive the badge discipline that Paper 11 applies to its own claims. The gloss is not badged because it cannot be badged: it is neither derived nor declared.

8.2 H.2 — The derivation attempt: 0/6 derived (spin: split verdict, §8.3) [CLASSIFIED — honest record]

H.2 tries to derive encounter-independence from the standard formalism, step by step, using strict derivation rules (a step is VALID only if it follows from equations, definitions, or data). It reports exactly where each chain bottoms out.

Property	Result	Where it bottoms out
Spin	SPLIT — see §8.3	(a) Axis-constituted reading: BOTTOMS OUT (GAP) — "up" without $\hat{n}$ is undefined; Bell presupposes axes and never tested this claim. (b) Pre-existing local values: BOTTOMS OUT (REFUTED) — Bell's theorem (P.2); measured S=2.7 > 2
Charge	BOTTOMS OUT (GAP)	No scale-free value exists; bare charge diverges
Color	BOTTOMS OUT (REFUTED)	Elitzur: no gauge-invariant colored state; confinement structural
Flavor	BOTTOMS OUT (REFUTED)	K^0 oscillations: intrinsic flavor would forbid what occurs
Mass	BOTTOMS OUT (GAP)	Both derivations (kinematics, Higgs) run through encounters
Magnetic moment	BOTTOMS OUT (GAP)	Subtract all diagrams; remainder is undefined, not zero

Verdict: encounter-independence cannot be derived for any property. Two chains hit REFUTATION on every reading (color, flavor — the formalism contradicts the intrinsic reading); one chain is split (spin: GAP on the axis-constituted reading the paper itself advances, REFUTED on the pre-existing local values Bell tested — §8.3); three hit GAP (charge, mass, magnetic moment — the intrinsic reading is underivable from the formalism). This is an honest null result in the F.57 tradition: the derivation was attempted rigorously, and it failed rigorously. The failure is the finding.

Why the record matters more than the null. A bare "0/6" could be read as "we found nothing" — but the record says where each chain bottoms out, and that location is information a bare null doesn't give. Two chains (color, flavor) bottom out in REFUTATION: the formalism contradicts the intrinsic reading on every reading. Three (charge, mass, magnetic moment) bottom out in GAP: the intrinsic reading is underivable, and the table says exactly which step fails. Spin is split: GAP on the axis-constituted reading, REFUTED on the pre-existing-local-values reading Bell tested. A future derivation attempt doesn't start from zero — it starts from this map, knowing which doors are closed by theorem and which stand open to equations.

8.3 The spin verdict, split: two claims, two verdicts [CLASSIFIED]

The H.2 spin chain carries two different propositions, and the old summary gave them one label — BOTTOMS OUT (REFUTED) — letting the stronger verdict overwrite the weaker. That collapse is split open here, because the two propositions are different claims with different evidence, and the paper's own structural point lives in the one Bell never tested.

Claim (a) — the axis-constituted reading. "Spin along $\hat{n}$" requires $\hat{n}$. $|up\rangle$ with no axis is undefined; the Stern-Gerlach reading is $S\cdot\hat{n} = \pm\hbar/2$; the Poincaré Casimir classifies the spin-1/2 representation, but the reading still requires the axis (P.6: classifier ≠ possession). No theorem of physics was ever brought against this claim. Bell's setup presupposes axes — the measurement settings a and b are axes. A theorem that assumes axes cannot refute the claim that spin is axis-constituted.

Verdict (a): BOTTOMS OUT (GAP). Encounter-independence is underivable for the axis-constituted reading — and that underivability is the paper's own structural point, not a borrowed theorem.

Claim (b) — pre-existing local values. The electron carries a definite spin value before and independent of measurement, locally — the value is there whether or not anyone measures along any axis. Bell's theorem plus P.2: no local model reproduces the measured $S = 2.7 > 2$. This is the reading Bell tested, and it failed.

Verdict (b): BOTTOMS OUT (REFUTED) — by Bell, for the local model class.

Why the split cannot be glossed over: under the old single label, a critic could say "Bell refuted intrinsic spin" and walk away — and the paper's deeper point, that "spin" without an axis is not even a well-formed claim, would be absorbed into a theorem that never tested it. The paper's thesis does not need Bell. Bell is the empirical backstop for one specific reading; the structural argument — axis-constitutiveness — stands on its own, and it is the stronger of the two, because it does not depend on any experiment coming out a particular way. The H.2 script now emits both verdicts distinctly (no REFUTED-priority collapse); the chain steps are unchanged.

8.4 H.3 — Verdict-layer consistency: 7/7 cells match [CLASSIFIED]

H.3 no longer scans the document for keywords. It enforces a transcription invariant across the paper's verdict layers: H.2's derivation-attempt records are the paper's own account of where each chain bottoms out (seven verdict cells — six properties, spin split into two chains per §8.3), and the verdict layers listed below must say the same thing: the §8.2 summary table, the §8.3 split verdict lines, the §8.1 spin row, the §8.5 C2 row, the alignment table in this section, and the §3.x verdict sentences. The script parses document structure, never whole-text substrings: markdown table rows under the located §8.2 heading, the line-anchored Verdict (a)/(b) lines of §8.3, the alignment table below, the C2 row of §8.5's table, the §8.1 spin row, and sentences of the exact syntactic form "H.2's verdict for X is Y" (§3.x). A verdict token counts only in its structural slot — the same token in running prose is not a verdict claim and is ignored. Each parsed verdict is compared cell-by-cell against the extraction map of H.2's records embedded in the script: a REFUTED claim with no REFUTED record fails; a DERIVED claim over a GAP record fails; a dropped chain, an extra unmapped row, or a misattributed property fails; a collapsed spin split fails.

What the map is. The seven verdict cells are the author's classification of H.2's chains — declared input, documented in the script's INPUT_PROVENANCE, not a derived result. The machine's contribution is the cross-layer comparison: it proves the paper's tabulated verdict layers agree with the record. It does not prove the verdicts are correct, that H.2's chains are good derivations, or that any prose overreaches any equation — those remain the author's judgments, stated as such. The old marker scan's prose/equation-mismatch claim is dropped, not repaired: no per-property prose/equation linkage is computed here.

Verdict: 7/7 MATCH — every verdict layer agrees with the H.2 record. No section asserts DERIVED where the record says GAP; every REFUTED claim has a REFUTED record; no chain is dropped and none is misattributed. The alignment table below is the paper's restatement that the script parses — it must read MATCH in every row, and the script independently recomputes the agreement:

Property / chain	H.2 record	Paper's restatement	H.3
spin / axis-constituted	GAP	§8.3: BOTTOMS OUT (GAP)	MATCH
spin / pre-existing-local	REFUTED	§8.3: BOTTOMS OUT (REFUTED)	MATCH
charge / scale-free	GAP	§8.2: BOTTOMS OUT (GAP)	MATCH
color / gauge-free	REFUTED	§8.2: BOTTOMS OUT (REFUTED)	MATCH
flavor / basis-free	REFUTED	§8.2: BOTTOMS OUT (REFUTED)	MATCH
mass / encounter-free	GAP	§8.2: BOTTOMS OUT (GAP)	MATCH
magnetic moment / virtual-free	GAP	§8.2: BOTTOMS OUT (GAP)	MATCH

(The §3.x verdict sentences — e.g. §3.3's "H.2's verdict for mass is GAP, not REFUTED" — and the §8.1 spin row's §8.3a/§8.3b split citations are parsed and checked the same way; the script's docstring lists all seven checks A–G.)

8.5 H.4 — Honesty comparison: computed where computable [CLASSIFIED]

Denominator note. H.4 scores seven honesty criteria C1–C7; H.1 (§8.1) audits the six SM property classes (hence 6/6). The denominators measure different things; neither count is the other's.

Framing, stated honestly. H.4 scores Paper 11 on seven criteria that Paper 11 was designed to satisfy, and scores the SM on the same criteria. A sharp referee will call this a stacked deck — and the referee is right that it is not a neutral comparison. It is not offered as one. The correct framing: if the Standard Model's intrinsic-property claims were held to Paper 11's declared epistemic standards, this is the scorecard. The SM has other standards — falsifiability via cross-sections, quantitative precision — and on those it does very well; the paper does not dispute that. The point is narrower and sharper: on the specific standard this paper holds itself to — declare your primitives, align prose with equations — the SM's gloss is unbadged. That is all H.4 claims. Owned, not smuggled.

What H.4 is, exactly. H.4 (v24 rebuild) is a computed comparison with declared limits — the v23 printed scorecard is retired. Every scored cell carries one of three kinds. COMPUTED: a predicate evaluated against the draft text supplied on the command line (the script takes the draft path as an argument; no draft content is hardcoded), with the evidence locator — draft line numbers — printed beside the verdict so a reader can re-run the check. What the machine establishes is anchor presence: that the draft carries the compliance machinery the criterion names. Anchor presence is not semantic adequacy; whether the labels are correctly applied stays author judgment, stated in each cell. INHERITED: a verdict re-computed at H.4's execution from a sibling script's output — H.1's badge rule re-run over H.1's claim table (C1, C4), the rebuilt H.3's verdict-layer consistency check re-run on the same draft (C2) — carrying that sibling's own disclosed limits. HUMAN-JUDGMENT: no machine predicate exists, so the script reports the paper's own stated verdict, parsed from this table's bold markers, labeled as the author's judgment rather than a machine finding. Where a check bottoms out in author judgment, the cell says so — that is honest, not a failure. The script fails closed: any cell without an evaluator stamp, or with an empty or dangling evidence locator, aborts the run — a reintroduced baked verdict cannot pass.

Criterion	Paper 11	SM gloss
C1: Declared assumptions	PASS [COMPUTED] — INPUT_PROVENANCE blocks and "declared assumption" labels present in the draft (line numbers printed by the script)	FAIL [INHERITED · H.1] — H.1's badge rule re-run at H.4's execution: 6/6 intrinsic claims NO BADGE; "intrinsic" neither derived nor declared (mechanism labels are H.1's author classification)
C2: Prose/equation alignment	PASS [HUMAN-JUDGMENT] — prose claims encounter-indexing; equations derive it (author's assessment: no machine check exists)	FAIL [INHERITED · H.3] — prose claims encounter-free; equations are encounter-indexed (H.2; H.3: author classification, §8.4)
C3: Null results published	PASS [COMPUTED] — F.57/null-result anchor present (line numbers printed by the script)	FAIL [HUMAN-JUDGMENT] — author's judgment: the failed derivation (H.2) is not acknowledged in textbooks
C4: Badge discipline	PASS [COMPUTED] — [LEVEL A/B/C] badge tokens and the F.38 registry anchor present (counts printed by the script)	FAIL [INHERITED · H.1] — H.1's badge rule re-run: 0/6 "intrinsic" claims earn A/B/C
C5: Falsifiability	PASS [COMPUTED] — falsification-condition statements present, §6 (line numbers printed by the script)	FAIL [HUMAN-JUDGMENT] — author's judgment: no falsification condition for the intrinsic-possession gloss; the gloss survived Bell's local refutation. (The SM's cross-section predictions carry their own falsification conditions)
C6: Bookkeeping/ontology separation	PASS [COMPUTED] — Stage N / Stage P / F.42 anchors present: the paper declares the boundary (whether it holds is author judgment)	FAIL [HUMAN-JUDGMENT] — author's judgment: virtual particles ("popping from vacuum"), Faddeev-Popov ghosts: perturbative artifacts treated as entities
C7: Encounter-scale admission (EFT trap)	PASS [COMPUTED] — encounter-indexing language present throughout (count printed by the script)	FAIL [HUMAN-JUDGMENT] — author's judgment: "intrinsic" in the textbook, "EFT" in the seminar; cannot have both

Verdict, with the new meaning stated. On the six machine-evaluated Paper-11 cells (C1, C3–C7): 6/6 PASS — the draft carries the compliance machinery each criterion names. C2 remains author judgment (PASS, as assessed). On the three machine-evaluated SM cells (C1, C2, C4 — inherited from the H.1/H.3 runs): 0/3 PASS. Four SM cells (C3, C5, C6, C7) remain author judgment (FAIL, as stated). The old "7/7 vs. 0/7" headline is retired: it counted author-typed verdicts as machine results. The new numbers count only what the machine evaluated, and label the rest.

The stacked-deck objection, stated at full strength — and answered. The sharpest objection to H.4 runs like this: the scorecard is not neutral. It grades the Standard Model on Paper 11's home criteria — criteria Paper 11 was designed to satisfy — so the result is baked in. A symmetric scorecard, one both frameworks had a hand in writing, would not produce this lopsided split. The comparison proves nothing except that Paper 11 meets its own standards.

That objection is stated here at full strength because it deserves to be answered, not dismissed. The answer has two parts.

First, the scorecard's criteria are Paper 11's declared standards — the framing above says so honestly — but they are not all Paper 11's private invention. Declare your assumptions, align your prose with your equations, publish your null results, state your falsification conditions: these are the standard literature's own professed norms, the ones preprints and peer review claim to enforce against overclaiming. A manuscript that smuggled its ontology, misaligned its prose against its equations, hid its failed derivations, and badged nothing would be rejected under those norms — and on that shared subset, the SM's intrinsic-property gloss loses on the home team's rulebook. C4 (badge discipline), C6 (bookkeeping/ontology separation), and C7 (encounter-scale admission) are Paper 11's own additions, declared as such in the table; the paper does not pretend the standard literature professes them. [F-17(C4): "badge your claims" is Paper 11's invention — it is not one of the literature's norms.]

Second, the supposedly "neutral symmetric scorecard" is itself a framework-relative choice. To demand symmetry between the two frameworks' criteria is to smuggle in the premise that both frameworks' criteria are equally legitimate — which is exactly what is under dispute. There is no view from nowhere here; every scorecard encodes some epistemology. The honest move is not to pretend neutrality but to declare the standard — which H.4 does, in the framing paragraph above — and then ask whether the other side meets even its own declared standards. It does not.

So the objection is answered without being dodged: the deck is declared — and on the norms both sides profess, the gloss still loses.

C6 — the reification check. Does the framework distinguish a mathematical bookkeeping artifact from a physical entity? Paper 11's Stage N/Stage P separation is exactly this boundary, machine-enforced by F.42. The SM gloss fails it routinely: virtual particles are terms in a perturbative expansion, yet the prose (and pop-science built on it) presents them as things that "pop in and out of existence." Faddeev-Popov ghosts exist solely to cancel unphysical gauge degrees of freedom — pure bookkeeping — yet they walk and talk like entities in the formalism. This is ontological proliferation: inventing unobservable entities to save the equations.

C7 — the EFT trap. Does the framework admit its parameters are encounter-indexed? Paper 11 does natively. The SM gloss, when pressed on infinities or running couplings, retreats to "it's just an Effective Field Theory." But an EFT is defined by its cutoff scale Λ — every parameter is then explicitly indexed by encounter energy μ. The trap: admit EFT, and "intrinsic" is a low-energy pedagogical fiction; claim fundamentality, and face the infinities. The gloss uses "intrinsic" in the textbook and "EFT" in the seminar. Paper 11 picks one. The SM refuses to.

The H.4 verdict, stated plainly: the contrast is not about who has better equations. Both frameworks' equations are encounter-indexed. The contrast is about honesty — and H.4 now records it the way §8.6 records everything else: as an honest record, not an independent machine proof. Where the draft carries checkable compliance machinery — declared assumptions labeled, null results published, badges present, falsification conditions stated, the Stage N/P boundary declared, encounter-indexing claimed — the machine confirms it is there, with line numbers. Where no check exists — Paper 11's own prose/equation alignment, and the four literature claims about the textbooks — the cells are marked HUMAN-JUDGMENT and carry the author's stated verdict, which the reader can accept or reject on the reasons given. That is the honesty gap, as the paper records it: declared, not smuggled.

8.6 What the machines recorded [CLASSIFIED]

The H-series records, by execution, where each derivation bottoms out — an honest record, not an independent machine proof (§0.5.5). What the record shows:

1. The "intrinsic" component of every SM property claim is smuggled (H.1) —

neither derived from the formalism nor declared as an assumption.

2. Encounter-independence is underivable (H.2) — a summary of the §3 prose audit

in machine-recorded form, not a second independent machine result: the formalism refutes it on three readings (spin's pre-existing-local-values reading, color, flavor; spin's axis-constituted reading is a GAP, §8.3). The task is ill-posed — no SM theorem has the "derive encounter-independence" shape — so the null is expected; its value is as an honest published record.

3. The paper's verdict layers agree with the H.2 record (H.3) — a machine-enforced

transcription invariant, not a prose/equation judgment: every section that states a per-property derivation verdict (§8.1, §8.2, §8.3, the §8.4 alignment table, §8.5's C2 row, §3.x verdict sentences) matches the H.2 derivation-attempt records — no REFUTED claim without a REFUTED record, no DERIVED claim over a GAP record, no dropped chain, no misattributed property (§8.4). The verdicts themselves remain the author's classifications.

4. The honesty gap, as recorded (H.4) — on the machine-evaluated cells, Paper 11's draft carries its compliance anchors 6/6 and the SM gloss earns 0/3 (inherited H.1/H.3 runs); five cells remain author judgment — C2 for Paper 11 (PASS, as assessed), C3/C5/C6/C7 for the SM gloss (FAIL, as stated) — labeled as such, not as machine findings.

Dervis's instruction was: "I don't care if their equations work — run the same rigor on them." The equations do work (they predict correctly). What doesn't work — what cannot survive Paper 11's machinery — is the intrinsic gloss. The machines did not set out to bury the Standard Model's predictions. They buried its ontology, using its own equations as the shovel.

(F.7's one-paragraph verdict, Appendix F, is the audit's terminological bottom line: "intrinsic" has six mutually incompatible referents across the literature — table entry, Lagrangian parameter, representation label, non-orbital, bare/infinite, essential-to-identity — none of them "possessed independently of encounters." A word with six incompatible referents is not a theoretical term. It is a verbal habit. Retire it.)

8.7 Executable physics: running their equations [COMPUTED]

Beyond the audit scripts (H.1–H.4), v3 adds executable physics scripts (P.1–P.6) that don't just model the SM equations — they run them. v10 adds P.7 (g−2, the flagship) and P.8 (mass scheme/scale). Each script computes the actual quantities and demonstrates the encounter-indexing computationally.

	What it runs	Result		
	Pauli matrices; S·n̂ for 6 axes (exact integer arithmetic)	Eigenvalues always ±1 — now the exact identity $S^2=(n\cdot n)I$ — but "up" means "up along n̂": axis constitutive, not parametric		
	CHSH for singlet at optimal angles + deterministic lattice LHV (no RNG)	QM: $S=2\sqrt{2}$ exact ($S^2=8$); LHV: $S=296/149\leq 2$ exactly, both tie-handlings — values don't pre-exist		
	R = $3\Sigma e_q^2$ for u,d,s (exact rational arithmetic)	R=2 exactly matches data; R=2/3 without the 3 — the "3" is a representation dimension, not a possession		
	Numerical integration of QED beta function — continuum disclosed (CONTINUUM_USE): the differential equation is the exhibit	α runs 1/137 → 1/129.34 (schematic one-loop $n_f=3$; PDG value 1/127.9); no scale-free value exists; bare charge diverges		

	What it runs	Result		
	CKM matrix from PDG values; weak vs mass basis — continuum disclosed (CONTINUUM_USE): the complex phase is the exhibit	"Down" in weak basis = superposition — flavor is interaction-indexed by construction		
	P^2, W^2 in two frames; exact rational boost β=3/5, γ=5/4	Same m^2 exactly (classifier), different p^μ (readings) — invariants classify, encounters read		
	5-loop QED series; Dirac mutant; IR-cutoff shift (block 3 — classified, leading-log only); muon-loop piece — continuum disclosed (CONTINUUM_USE): the perturbation series is the exhibit	a_e(QED) computed to 12 digits; Dirac-only (a_e=0) rejected; muon mass inside "the electron's" moment at 21× exp. precision		
	Pole↔MS-bar at 1/2 loops; MS-bar running — continuum disclosed (CONTINUUM_USE): the scheme relations are the exhibit	Definitional spread ~9 GeV >> 0.3 GeV precision; m_b(m_b)≠m_b(M_Z) — no unique encounter-free mass		
	Ternary outcomes + tether model for Bell-CHSH — integer-native (deterministic lattice, no RNG, no assumed measure)	Computed (all three parts): Part 1 projection-dependence — spread 107756/144381≈0.746 across 0-handlings; drop-zeros 869/323≈2.690 (detection-loophole analog); Part 2 local ternary bound = 2 (81 assignments, honest null); Part 3 tether S=425/149≈2.8523 inside the exact (2.79,2.86) bracket (⇒ \	S−2√2\	<0.04), se mutants ca framework continuum
	QED vertex-diagram counts per loop order	1→7→72→891→12,672; 1- and 2-loop machine-derived, rest cited-paper oracle — the count N is discrete		

All ten run green. They don't argue — they compute. The encounter-indexing is in the numbers, not just the prose about the numbers.

Apparatus note. The full mutant batteries, provenance blocks, and validator internals live in the Appendix G listings — the paper's main text carries only the verdicts. Anyone who wants to audit the auditor reads the code; the argument above does not depend on it. The scripts/ directory is the authoritative source of every listing; staging_v23/scripts/ is a superseded snapshot, not a source.

8.8 The firewall (FW.1): the paper performing its own thesis [MIXED — computed scan, classified voice judgments]

FW.1 is not a hygiene check. It is the paper's core method demonstrated. The paper critiques the SM for smuggling "intrinsic" without declaring it; the firewall ensures Paper 11.5 doesn't smuggle "intrinsic" either. That is not defensive — that is the argument, executed on itself.

Paper 11 has F.42 (the Stage-N vocabulary firewall); Paper 10.5 has its own. Paper 11.5 now has FW.1: a self-policing script that scans the paper's own text for three breach classes — (A) asserting "intrinsic" in the paper's own voice (not quoted, not scare-quoted, not critical), (B) leaning on continuum language ("at a point", "at every point", "smooth", "infinitesimal") to ground property ascriptions, (C) possessive reification ("the electron's spin") in the paper's voice.

FW.1 passes: the paper practices what it preaches. It critiques "intrinsic" without smuggling it back in. A paper that audits prose/equation alignment and then fails its own audit would be a curiosity. A paper that audits prose/equation alignment and passes its own audit is a method. FW.1 is positioned here — not in an appendix — because it is the showpiece: the thesis, run on the thesis, green.

8.9 The parsing agent (PA.1) [CLASSIFIED]

PA.1 takes any SM property claim as input and parses it into formal content (derived), gloss (smuggled), badge verdict, and Paper 11 counterpart. Run it on "The muon has intrinsic spin-1/2" — it identifies the property, separates the S·n̂ formalism from the axis-dropping gloss, and reports NO BADGE (REFUTED by Bell, local scope — §8.3b; the axis-constituted reading itself is GAP, §8.3a). The agent is the mechanical reader: feed it claims, it returns honesty verdicts.

Gloss-to-equation divergence ratio (v8; rescoped v24, F-39). PA.1 mechanically scans §3 under an explicit scoping rule: possession/intrinsic patterns are counted only in each §3.1–3.6 subsection's (a) textbook-claim block (the claim plus its "Textual evidence" block); encounter-index patterns (μ, n̂, Q^2, ξ, CKM, gauge, basis, frame, scale) are counted only in the same subsection's (b) equation-breakdown block; the paper's rebuttal voice ((c), (d), and beyond) is excluded from both counts. Both counts are regex scans over the actual text — nothing hand-coded. Current run: 20 prose possession-claims vs. 55 mathematical encounter-indices. The equations carry more encounter-indexing than the prose carries possession-claims — yet the prose presents the properties as encounter-free. The counts are aggregates, not a 1:1 mapping; what they establish is the density of the divergence, not its exact pairing. The divergence is not philosophical; it is counted. The scan fails loudly, not silently: every §3.1–3.6 subsection must carry its (a)/(b)/(c) markers in order — a subsection that doesn't is skipped with a printed warning naming it, and if none parse the script exits nonzero rather than print a vacuous ratio.

9 THE CONTINUUM LICENSE: HOW CONTINUOUS CALCULUS ENABLES THE INTRINSIC HABIT

The audit has shown that the intrinsic gloss is smuggled. This section addresses why the smuggling was so easy — why six generations of physicists performed it without noticing. The answer: continuous calculus provides the license.

Not as a lie. As a habit. The distinction matters, and the paper insists on it: nobody conspired to invent intrinsic properties. What happened is that the mathematical framework — fields defined at spacetime points, values assigned continuously — pictures the world in a way that makes "intrinsic" feel natural, even where the equations don't support it.

9.1 The picture the continuum paints

Classical field theory writes: φ(x) — a field with a value at point x. Quantum field theory writes: ψ_i(x) — a field with components at x. The notation places the value at the point, with the field, there.

This picture has a grammar: the value belongs to the point, the point belongs to the field, the field is there. From "φ has value v at x" it is a short, natural, almost irresistible step to "the particle has property P" — the possessive grammar (§5, step 3) is already in the notation. The continuum doesn't assert intrinsicality. It depicts a world in which intrinsicality is the default — values sitting at points, waiting to be read off.

Paper 10.5 already established: the continuum is an assumption, not a finding. No experiment has ever measured a continuum; every measurement returns discrete readings (clicks, spots, counts). The smooth field φ(x) is an idealization — a useful one, but an idealization. What this section adds: the idealization carries an ontological surcharge. By picturing values-at-points, it licenses the thought "the value is there, with the particle, intrinsically" — even when the dynamics (gauge invariance, RG, Bell) say otherwise.

9.2 How the license operates per property

Spin. The continuum pictures the electron as a point with a spin vector at that point. But S·n̂ requires n̂ — the "vector at the point" is undefined without the axis. The continuum picture (point + vector) elides the axis because the axis isn't at the point — it's the apparatus, elsewhere. The license: picturing the electron as a decorated point makes "spin at the point" feel complete.

Charge. The continuum pictures e as a number at the electron's location. But e(μ) varies with scale — the "number at the point" depends on how closely you look. The continuum picture has no room for scale-dependence at a point; it must be added back via renormalization, which feels like a correction rather than what it is: proof the point-picture was

wrong.

Color. The continuum pictures $\psi_r(x)$, $\psi_g(x)$, $\psi_b(x)$ — three fields, three colors, at x. But gauge transformations mix them, and Elitzur forbids physical color. The point-picture depicts three distinct colored things; the dynamics says the distinction is descriptive, not ontological. The license: the notation $\psi_i(x)$ looks like three possessions.

Flavor. The continuum pictures six quark fields, each assigned a flavor value at its points. But V_{CKM} rotates the basis — "which field" depends on the interaction. The point-picture fixes the fields; the dynamics unfixes them.

Mass. The continuum pictures m as a parameter at the particle. But $m_f = y_f v/\sqrt{2}$ — the mass is a coupling times a background field value. The "parameter at the point" is actually a relation between the point and everywhere (the VEV).

Magnetic moment. The continuum pictures μ as a vector at the electron. But a_e's five-loop term sums 12,672 loop diagrams — the "vector at the point" is spread across every virtual encounter. The point-picture concentrates what the dynamics distributes.

9.3 The habit, not the lie

To call this a "lie" would be to allege intent. The paper does not. What happened is more ordinary and more instructive: a useful mathematical habit (continuum fields) generated a picture (values at points), the picture suggested an ontology (intrinsic possessions), the ontology hardened into prose, and the prose survived the equations that contradicted it — because nobody went back to check whether the picture was still earning its keep.

This is the "assumed, not observed" fallacy (Paper 2.5's title) in its most refined form. Not "assumed without evidence" — there is abundant evidence for the equations. But "assumed without derivation": the intrinsic reading of the equations was never derived from them. It was licensed by the continuum picture, and the license was never revoked — even after Bell, Elitzur, and the RG gave formal notice.

9.4 What changes without the continuum

Paper 11's ledger has no continuum: ticks, ports, aspects, encounters — all discrete, all indexed. In the ledger, there is no "value at a point" to mistake for a possession. A port presents values at a tick, in an encounter — the indexing is in the primitive notions, not added later. The intrinsic habit cannot even be formulated in the ledger's vocabulary, because the vocabulary has no unindexed slots for it to occupy.

This is why the critique and the positive account belong together (11 and 11.5): Paper 11 builds the framework where the intrinsic habit is inexpressible; Paper 11.5 shows why the old framework made it irresistible. The continuum didn't just allow the intrinsic gloss — it suggested it, depicted it, and protected it from the equations' objections by making it feel like the default. Removing the continuum doesn't just remove a mathematical convenience. It removes the license.

9.5 Worked case: how the continuum makes the VEV feel like background

§9 claims continuous calculus is the enabler of the intrinsic habit — the permission structure that lets "intrinsic" feel natural. That is a structural claim, and it needs one full demonstration, not six one-liners. Here it is, for the Higgs mechanism (the formalism is developed in Appendix B.3).

Step 1: Write the continuum object. The Higgs field is $\varphi(x)$ — a value at every spacetime point x. The notation itself is the first move: φ is defined everywhere, continuously, whether or not anything is happening at x. The field exists at points where no encounter occurs, no measurement is made, no interaction takes place. Mathematically unremarkable; ontologically, the VEV is already being staged as background.

Step 2: Minimize the potential. $V(\varphi) = -\mu^2|\varphi|^2 + \lambda|\varphi|^4$ has its minimum at

φ	= v/√2, v ≈ 246 GeV. The minimization is performed on the function —

over all of field space, at no particular point, in no particular encounter. The value v is selected by the shape of V, which is defined everywhere. The computation never indexes an encounter; it indexes the manifold.

Step 3: Read v as "the vacuum expectation value." The phrase does the reification. "The vacuum" — definite article, singular — as if there were one thing, everywhere, with a value. But $\langle 0|\varphi|0\rangle$ is a matrix element between formal

asymptotic states (see Appendix H, H.1's critique of in/out states). The VEV is a property of the formalism's ground state, not a substance filling space. Yet the continuum notation φ(x) — a value at each x — makes "filling space" the path of least resistance. The reader pictures a molasses, an ocean, a medium. The textbooks encourage it: "particles acquire mass by interacting with the Higgs field that permeates all of space."

Step 4: Watch the encounter-indexing disappear. The actual mass term, $m_f = y_f v/\sqrt{2}$, is generated in Yukawa interactions — encounters between fermion fields and the Higgs field. The coupling y_f is encounter-indexed (it runs; it is defined at a scale). The "v" that appears is the same v from Step 2 — computed on the manifold, not in an encounter. So the mass formula blends an encounter-indexed coupling (y_f) with a manifold-indexed constant (v), and the blend is called "the particle's intrinsic mass." The continuum did the blending: because φ(x) is defined at every x, v feels like it was already there before any encounter — a background, a property of the stage rather than of the play.

Step 5: Contrast the ledger picture. In Paper 11's discrete ledger, there is no φ(x) — no value at every point. There are ticks (encounters), ports, and aspects. The Higgs "mechanism" would be rendered as: certain encounter geometries carry a consolidation term (the mass) whose magnitude is set by the encounter's own structure (y_f) and the ledger's global accounting (v as a ledger constant, not a spatial substance). The ledger has no "everywhere" for a substance to fill — so the VEV cannot feel like background. It is forced to be what it is: a number in the accounting, encounter-indexed through y_f, ledger-global through v. The intrinsic gloss has nowhere to stand.

The mechanism, named: continuous notation (φ(x) ∀x) → manifold-indexed computation (minimize V over field space) → definite-article reification ("the vacuum") → blending with encounter-indexed couplings → "intrinsic mass." Remove the continuum — remove the "∀x" — and the chain breaks at Step 1. That is §9's claim, demonstrated once. The reader can supply the other five.

9.6 Where the continuum was doing the work

§9.5 showed the mechanism in one case (the Higgs VEV). This subsection states the general point and links it to the series.

The intrinsic idiom is far easier to maintain when the underlying ontology is continuous fields with point-like excitations. A continuous field φ(x) is defined at every point — including points where no encounter occurs, no measurement is made, nothing happens. That "defined everywhere" is the hiding place: between encounters, the property can be pictured as still there, carried by the field at points no one is probing. The continuum provides a substrate in which the property can hide between encounters — and "hidden between encounters" is experienced, by the reader, as "possessed independently of encounters." The notation does the metaphysics.

In a discrete ledger there is no such hiding place. Paper 11's ledger has ticks, ports, and aspects — and nothing between ticks. A "property" in the ledger is either a per-tick reading (encounter-indexed by construction) or a ledger-global accounting constant (like the mass-as-departure total). There is no continuous substrate for it to inhabit between encounters, so the reification step (§5, step 4) has nowhere to stand. Paper 10.5 made the same point for the gravitational case: remove the continuum and the "force" has to be re-rendered as resolution-seeking between discrete configurations — the noun "force" loses its hiding place.

This is the series-level coherence: Papers 10, 10.5, and 11 each remove the continuum from a different domain (gravity, the gravitational audit, the configuration roles), and in each case a reified noun — force, intrinsic property, active/passive label — loses the substrate it was hiding in. Paper 11.5 is the installment that names the hiding place itself. The continuum wasn't just a mathematical convenience. It was the permission structure for every reification the series has had to dismantle.

10 ENCOUNTER-INDEXING IN THE LANGUAGE OF QUANTUM FOUNDATIONS

"Encounter-indexed" is this paper's term. Readers from quantum foundations may suspect novel jargon obscuring familiar ideas. This section maps the ledger's primitives onto four established frameworks — showing that encounter-indexing is not an invention but a recognition, formalized in Paper 11's discrete vocabulary.

10.1 Relational Quantum Mechanics (Rovelli)

RQM's central thesis: the values of physical quantities are not absolute but relative to another physical system. A spin value is not "the electron's spin" but "the electron's spin relative to the Stern-Gerlach apparatus." This is encounter-indexing in RQM's language: the value exists at the relation, not in the relatum. Paper 11's ledger entries (tick, ports, aspects) are the formalization of Rovelli's relational values — with the added discipline that the relation is a discrete ledger event, not a continuous interaction history. Where RQM says "relative to," the ledger says "indexed by the encounter." Same structure, stricter bookkeeping.

10.2 QBism (Fuchs, Schack)

QBism treats quantum state assignments as an agent's expectations, updated upon interaction. The ledger's encounter entries map onto QBist update events — but without the subjective agent. In Paper 11, the "update" is grounded in the formal algebraic structure of the interaction vertex itself: the ledger records what the encounter established, not what anyone believes. This removes QBism's most contested element (the agent's psychology) while preserving its core insight: quantum values are indexed to interactions, not possessed between them. The ledger is QBism objectified — the update event made into a discrete ontological primitive (the tick).

10.3 POVMs and the interaction channel

Traditional von Neumann measurement uses projectors P_i that suggest a pre-existing state being "projected" — language that smuggles intrinsicality (the state was there, the measurement revealed it). The POVM formalism replaces projectors with positive operators $E_i = M_i^\dagger M_i$, where the Kraus operators M_i explicitly model the interaction channel — the encounter — not the isolated system. The probability $p(i) = \mathrm{Tr}(\rho E_i)$ is irreducibly a joint property of system and channel. POVMs are the standard formalism's own admission that "measurement" is encounter-indexed: the E_i's carry the apparatus in their definition. Paper 11's ports are the discrete-ledger counterpart of Kraus operators — both formalize the encounter as constitutive, not as a window onto the pre-existing.

10.4 Algebraic QFT and local observables

In AQFT, observables are elements of local net algebras $A(O)$ associated with spacetime regions O. An observable does not exist as a free-floating entity; it exists as an element of $A(O)$ — indexed by its region. The encounter generalizes this: where AQFT indexes by spacetime region, the ledger indexes by the discrete encounter (tick + ports + aspects). The deep point is shared: an observable without its index is an unanchored abstraction. AQFT's $A(O_1 \cap O_2)$ — observables in the intersection of two regions' causal diamonds — is the continuum precursor of the ledger's encounter entry: the value exists where the relata meet, not inside either one alone. The ledger drops the continuum (per Paper 10.5) but keeps the indexing discipline that AQFT got right.

11 MONTE CARLO IN THE LEDGER: THEIR VERSION VERSUS OURS

This section is the paper's capstone. It answers the question: if continuous calculus is the language the Standard Model computes in, and Monte Carlo simulation is how those computations meet experiment — what does Monte Carlo look like in a framework with no continuum?

11.1 What Monte Carlo actually is

Strip away the folklore and a Monte Carlo simulation is: generate discrete events by random sampling, count frequencies, compare against discrete detector readings. A collider event generator does not instantiate a smooth field. It produces interaction vertices — a collision here, a decay there — assigns outcomes by sampling probability distributions, and tallies integer counts. Lattice QCD does not put a continuum on the computer; it puts a finite grid, samples discrete field configurations, and averages.

The continuum lives in the formulas used to compute the sampling probabilities (matrix elements, path integrals). The simulation itself — the part that runs, the part compared against data — is discrete events and integer counts throughout. Monte Carlo does not verify the continuum. It cannot: it never instantiates one. It verifies that discrete computations match discrete measurements.

11.2 Their version

Standard Model Monte Carlo: derive probability densities from continuum amplitudes (Feynman diagrams → matrix elements → phase-space densities), then sample discrete events from those densities. The pipeline is:

continuum theory → probability densities → discrete sampling → event counts → detector comparison

The continuum enters at the first arrow and exits at the second. Everything downstream — the part that touches experiment — is discrete.

11.3 Our version

Ledger Monte Carlo: derive sampling rules from combinatorial structure (shell counts, port rules, tick structure), then sample discrete encounters directly. The pipeline is:

discrete combinatorics → sampling rules → discrete encounters → ledger frequencies → detector comparison

No continuum enters the native ledger's ontology at any stage: ticks, ports, aspects, encounters are discrete and indexed — there is no continuum primitive to enter. That is the ontological claim, and it is narrower than the old absolute sentence. The computational exhibits in this paper fall in two tiers, stated plainly (v24 FORTRESS). Tier 1 — integer-native demonstrations (P.1, P.2, P.3, P.6, P.9, P.10): no continuum machinery anywhere — no float RNG, no transcendental functions, no differential equations; the machine checks are exact integer/rational arithmetic. MC.1's headline fit uses log-log least-squares under KEEP+DISCLOSE (the number IS the fit); its exact-rational bound is the [LEVEL B] translator. Tier 2 — SM-formalism exhibits (P.4, P.5, P.7, P.8): these run the SM's own equations with their continuum machinery intact, because there the continuum is the exhibit, not scaffolding around it (P.4's differential RG equation; P.5's complex CKM phase; P.7's perturbation series; P.8's scheme relations). Each Tier-2 script carries an explicit CONTINUUM_USE disclosure — what continuum machinery, why it is needed, what would be lost integer-native — and the prose citing each exhibit says so too. The v23 "labeled scaffolding" is superseded: where the continuum could be removed, it was removed by construction (P.9's assumed uniform-over-the-sphere measure is gone — the tether now runs on a deterministic integer lattice; MC.1's log-log fit is restored as the headline — the scaling's real number is the fitted exponent −1.9886 [LEVEL A: MACHINE / AUTHOR], the exact-rational bound its [LEVEL B] translator, the fit machinery used and disclosed). The framework's native mode of prediction is frequencies from discrete sampling — which is what Monte Carlo does anyway. The standard pipeline routes discreteness through the continuum to get its probabilities; the ledger pipeline reads them off the combinatorics. Stated plainly: the ledger natively states counts (P.10's diagram tallies, MC.1 step 1's shell counts); frequencies and weights need the sampling measure Paper 12 builds — the count→weight step is not certified here.

11.4 Demonstration: inverse-square from shell counting (MC.1)

Paper 11 §8.5 derives the proximity scaling $S(d) = s^2/(4d^2 + 2)$: the per-position share of scan workload over relay-hop shells, from the taxicab shell count $N(d) = 4d^2 + 2$ (Paper 10 §5.3.1) and uniform load partition (Paper 10 §2.4.7). For large d, $4d^2 + 2 \approx 4d^2$, so $S(d) \approx s^2/(4d^2)$ — inverse-square scaling, derived with no continuum, no flux, no Gauss's law. The scaling falls out of the shell-count geometry; it is not inserted as a separate law.

MC.1 samples the process rather than re-deriving the algebra:

1. Independent shell-count check. Brute-force enumeration of integer

lattice points with $|x|+|y|+|z| = d$ for d = 1..10, against $N(d) = 4d^2+2$. All match (d=1: 6 points; d=2: 18; ...). This is a genuine check — had Paper 10's formula been wrong, it would fail here.

2. Workload sampling (integer-native). At each d = 1..20, distributes s^2

workload units over the N(d) shell positions across 20,000 ticks with a seeded integer RNG (randrange only — no float RNG); verifies every position's time-averaged share concentrates within relative 1/4 of 1/N(d), by exact integer comparisons.

3. Fitted exponent [LEVEL A: MACHINE / AUTHOR]. The log-log least-squares slope of $1/(4d^2+2)$

over d = 5..20 — recomputed live by the script, printed, and asserted to round to −1.9886: the handshake's price, the real number. The fit machinery (math.log, least squares) is used and disclosed — KEEP+DISCLOSE — because the number is the fit; no integer-only route yields it.

4. Exact-rational translator [LEVEL B]. share(d)/share(d+1) =

N(d+1)/N(d) exactly, and the lattice correction R(d) = [N(d+1)/N(d)] / [(d+1)²/d²] satisfies |R(d)−1| < 1/d², decreasing monotonically, for d = 5..19 — the +2 correction's decay in exact rational arithmetic: the convenience form beside the real −1.9886 [LEVEL A: MACHINE / AUTHOR], labeled with why it exists.

Discrete uniform sampling over d²-growing shells illustrates the derived law's consistency (Paper 11 §8.5) — the result is algebraically forced; this is not an independent Monte Carlo discovery of it (see §11.6 for the honest scope). In the ledger's language, 1/r² is not a law about force spreading through space — it is the frequency signature of uniform load over combinatorially growing shells.

The sharpest point: in this framework, 1/(4d²+2) is fundamental and 1/r² is its large-d approximation. The continuum "law" is the limit of the discrete law, not the other way around. What nature shows us (gravity, Coulomb) is the large-d regime where the +2 is invisible.

There is a further point, and it is the honest one: the +2 lattice correction is not a blemish on the emergence but its price — and the price is the fitted −1.9886 [LEVEL A: MACHINE / AUTHOR], recomputed live by MC.1's log-log least-squares fit over d = 5..20 on 1/(4d²+2). The hybrid decomposes — MACHINE: the slope is recomputed live (−1.9885612518827713, rounds to −1.9886); AUTHOR: the slope is identified as the handshake cost and −1.9886 at 4dp is stipulated as the real number (author, 2026-10-18). The fit machinery is used and disclosed (KEEP+DISCLOSE, §0.5.1) because the number is the fit — the handshake cost is defined as the fitted exponent, and no integer-only route yields it. Beside it sits the exact-rational bound as its [LEVEL B] translator: |R(d)−1| < 1/d², decreasing monotonically, d = 5..19 — the convenience form of the same gap, labeled with why it exists. For inverse-square scaling to emerge from discrete shells with no continuum primitive, the communication between shells — the encounter structure that turns shell counts into effective scaling — must cost something, and the cost is the gap: −1.9886 [LEVEL A: MACHINE / AUTHOR], the exact-rational bound [LEVEL B] beside it, vanishing as d grows. Nothing is lost; −2 is recovered asymptotically. The deviation is the discrete geometry's signature, not noise.

11.5 Honest scope

What MC.1 proves: Monte Carlo runs in the ledger — discrete sampling over combinatorial structure produces the framework's scaling laws as statistical frequencies, green on all checks.

What it does not prove:

- Uniformity is assumed (inherited from Paper 10's Uniform Load Partition

Theorem), not derived. The MC verifies "uniform sampling → 1/d² frequencies" (consistency), not uniformity itself.

- Absolute scale is out of scope by architecture (Paper 11 §0.5): the

native register has no dimensional scales. The framework predicts the shape (1/d², not 1/d³ or e^(−d)) — which is what makes it inverse-square rather than something else — but not G or k_e. Scale enters at Stage P through measured calibrations.

- This is structural Monte Carlo (ledger consistency), not dynamical

Monte Carlo (detector predictions). The fill rules — which encounter actualizes with what probability at a given tick — are the dynamics the framework has not yet built. Paper 11 supplies kinematics; MC.1 stress-tests it. Dynamics is future work, and the paper states this plainly.

The honest summary: the inverse-square law is already in the framework (Paper 11 §8.5, machine-checked by F.45). MC.1's step 1 — integer lattice-point counting against N(d) = 4d²+2 — uses no continuum. Step 2's sampling is integer-native (seeded randrange); what it imports is the uniformity assumption — Paper 10's Uniform Load Partition, assumed here, not derived (§11.6) — not a continuum measure. What remains is dynamics, not data.

11.6 Why this is the capstone: the continuum was never load-bearing for prediction

§11.1–11.5 showed that Monte Carlo — the SM's own bridge to experiment — never instantiates a continuum. This subsection states why that makes §11 the capstone rather than an appendix.

The paper's arc is: the equations were already encounter-indexed (§3), the prose was not (§5), the continuum licensed the mismatch (§9). §11 is the capstone because it is where the pipeline closes end-to-end: native counts (the N(d) = $4d^2+2$ shell counts) → integer-native scripts (MC.1's shell counting; P.1–P.3, P.6, P.9 exact arithmetic) → the SM's own exhibit machinery, disclosed wherever the continuum is the exhibit (P.4, P.5, P.7, P.8 — §0.5.5) → the inverse-square shape recovered at −1.9886 [LEVEL A: MACHINE / AUTHOR]. No stage smuggles what the previous stage denied: the counts are native, the scripts are exact where exactness is claimed, the continuum appears only where it is labeled scaffolding, and the fitted number is badged as the fit it is. That is what "capstone" means here — not a new result stacked on top, but the demonstration that every layer of the paper's machinery fits the layer below it. The remaining question is whether anything load-bearing is lost when the continuum goes. Monte Carlo answers it: no. The entire predictive pipeline — the part of the SM that touches detectors — runs on discrete events and integer counts. The continuum enters only upstream, in the formulas that compute sampling probabilities — and what those formulas supply (matrix elements, phase-space densities) is relative weights over discrete outcomes. Here the honest statement is narrower than this section first claimed. Paper 11's native dynamics is deterministic: no branching, no native source of relative weights. The framework walls ensemble statistics off to Paper 12 ("Aggregated ledger, many-body statistical mechanics") by explicit architecture (Paper 11 §0.5) — and MC.1 had to assume uniform sampling to run at all (§11.5). Combinatorics supplies the counts; the count→weight step is not certified here. It needs two things this paper does not build: (1) a microstate-counting rule, and (2) a sampling-measure postulate. Both are Paper 12's work. That is standard statistical-mechanics territory, which is the footing for deferring it — but footing is not certification, and this paper promises nothing it has not derived. The fill rules — which encounter actualizes with what probability at a given tick — are the dynamics the framework has not yet built (§11.5).

So the continuum's load-bearing role was never prediction. It was ontology: it supplied the substrate in which "intrinsic" could hide between encounters (§9.6). Remove it and the derived counts survive (this section); what collapses is only the gloss. That is why §11 is the destination: the paper's structural critique stands on what the ledger derives, and it does not pretend to stand on what it has not — the fill rules and the sampling measure are Paper 12's work, named above, not smuggled in here. The numbers the ledger derives stay. The honesty is new.

Honest scope restated (v24 rulings fold-in). MC.1's headline result is the COMPUTED fitted exponent −1.9886 [LEVEL A: MACHINE / AUTHOR] — recomputed live by the script's log-log least-squares fit over d = 5..20 on $1/(4d^2+2)$; the fit machinery is disclosed as needed, because the number is the fit (the handshake cost is defined as the fitted exponent — no integer-only route yields it; KEEP+DISCLOSE, §0.5.1). Beside it sits the exact-rational bound as its [LEVEL B] translator:

R(d)−1	< 1/d², decreasing monotonically — the convenience form, labeled with

why it exists. The paper claims no more: MC.1 shows the ledger's native prediction mode (statistical sampling over discrete structure) reproduces the scaling the continuum framework produces — a consistency proof for the pipeline, not an independent discovery of $1/r^2$. The discovery was Paper 11 §8.5's derivation; MC.1 is the check that the discovery survives the framework's own Monte Carlo. That is what a capstone does: it does not redo the work, it shows the work holds together. And the lattice correction is read accordingly: not as a failed −2.00 but as the handshake's price — the cost at the communication, computed by the fit, recovered asymptotically.

12 THE EFT TRAP: NO EXIT

C7 in H.4 scores the encounter-scale admission as one criterion among seven. That undersells it. The EFT trap is not a criterion — it is a structural dilemma with no exit, and it deserves its own section. It is the paper's critique turned inside out: the Standard Model's own defense, when pressed, collapses the "intrinsic" gloss it was defending.

12.1 The trap, stated

When the audit presses on running couplings — "you said charge −e is intrinsic, but α runs 1/137 → 1/128 [LEVEL B: rounded physical idiom; PDG $\alpha(M_Z) = 1/127.9$]; which value is the intrinsic one?" — the standard defense retreats: "The Standard Model is just an Effective Field Theory. Of course parameters run. Nobody claims they're absolute."

But an Effective Field Theory is defined by its cutoff scale Λ. The EFT framework says: this theory is valid below Λ; its parameters are defined at a renormalization scale μ; change μ, change the parameters. Every parameter in an EFT is therefore explicitly indexed by encounter energy. The cutoff Λ is not a footnote — it is constitutive of what "EFT" means.

So the defender faces a fork with no good tine:

- Tine 1: Admit EFT. Then every "intrinsic" property is a low-energy

pedagogical fiction — a useful shorthand valid below Λ, explicitly scale-indexed, explicitly encounter-relative. The textbook gloss ("intrinsic charge −e, same at all energies") is false by the defender's own admission. The audit's verdict stands, conceded.

- Tine 2: Claim fundamentality. Then the theory is not an EFT but a

purported fundamental description — and it faces the infinities, the Landau pole, the hierarchy problem, the unrenormalizable gravity coupling, all without the EFT's "we don't claim validity there" shield. The "intrinsic" properties must then be truly scale-free, truly encounter-independent — which the RG, Bell (local models), Kochen-Specker, and Elitzur theorems forbid.

There is no third tine. "Intrinsic in the textbook, EFT in the seminar" is not a position — it is two positions, deployed alternately, each contradicting the other. Paper 11 picks one (encounter-indexed, all the way down, no scale-independence pretended anywhere). The SM gloss refuses to pick, and the refusal is the C7 failure.

12.2 Why the trap has no exit

A defender might try: "EFT parameters are intrinsic within the EFT's domain." But "intrinsic within a domain" is reading (b) of §1.5 — invariant functional form across encounters below Λ — which concedes the audit. The textbook does not say "intrinsic below 1 TeV." It says "intrinsic," full stop.

Another try: "The cutoff Λ itself is intrinsic." But Λ is where the theory stops working — it marks the boundary of ignorance, not a property of a particle. The strong version of the premise says Λ is fixed by us (where we stop trusting the theory), not by nature — and an "intrinsic" property fixed by our trust threshold is not intrinsic in any reading. But the argument does not need the strong version, and this paper states both premises on purpose. The weaker version: Λ is partly fixed by nature — experiment tells us where the theory breaks down. The trap still has no exit. Even on the weaker premise, every parameter in the EFT is defined at a renormalization scale μ; change μ, change the parameters. The parameters are encounter-indexed whether Λ is our choice or nature's verdict. Why state both? Because the honest thing is to show the reader that the conclusion does not depend on the more aggressive claim. If the dilemma survives the premise most favorable to the defense, it is not a trick of wording. Stating both is how the paper is honest about the argument's actual strength: the trap works on the weak premise, so the strong one is rhetoric — and it is labeled as such.

The trap is structural because it uses the defense's own move. The paper does not impose encounter-indexing from outside — it shows that the SM's own retreat position (EFT) already concedes encounter-indexing. The gloss is not refuted by a rival framework. It is refuted by its own alibi.

APPENDIX A — QUOTE BANK (FULL)

All quotes verified by the author. Secondary witnesses (Bohm, Cartwright, van Fraassen) documented here for completeness; per the usability assessment, the paper's §2 uses Whitehead, Heisenberg, Mach, Bohr, Bell.

A.1 Whitehead

- "This fallacy consists in neglecting the degree of abstraction involved when an actual

entity is considered merely so far as it exemplifies certain categories of thought." — Science and the Modern World (1925), p. 51

- "...among the primary elements of nature as apprehended in our immediate experience,

there is no element whatever which possesses this character of simple location." — Science and the Modern World (1925), pp. 49–58

- Note: the fallacy is named in SMW (1925), revisited in Process and Reality (1929).

A.2 Heisenberg

- "The ontology of materialism rested upon the illusion that the kind of existence, the

direct 'actuality' of the world around us, can be extrapolated into the atomic range. This extrapolation, however, is impossible... atoms are not things." — Physics and Philosophy (1958)

- "In the experiments about atomic events we have to do with things and facts, with phenomena

that are just as real as any phenomena in daily life. But the atoms or the elementary particles themselves are not as real; they form a world of potentialities or possibilities rather than one of things or facts." — Physics and Philosophy (1958), p. 186

- "What we observe is not nature in itself but nature exposed to our method of questioning."

— Physics and Philosophy (1958)

A.3 Mach

- "Thing, body, matter, are nothing apart from the combinations of the elements — the colours,

sounds, and so forth — nothing apart from their so-called attributes." — The Analysis of Sensations (1886), pp. 6–7

- "If ordinary 'matter' must be regarded merely as a highly natural, unconsciously constructed

mental symbol for a relatively stable complex of sensation elements, much more must this be the case with the artificial hypothetical atoms and molecules of physics and chemistry... they remain economical ways of symbolizing experience. But we have as little right to expect from them, as from the symbols of algebra, more than we have put into them." — The Analysis of Sensations (1886)

- Atoms as Gedankending ("thing of thought"), provisorische Hülfsmittel ("provisional aids").

A.4 Bohr

- "...the impossibility of any sharp separation between the behaviour of atomic objects and

the interaction with the measuring instruments which serve to define the conditions under which the phenomena appear." — Como lecture (1927)

- "Evidence obtained under different experimental conditions cannot be comprehended within a

single picture, but must be regarded as complementary in the sense that only the totality of the phenomena exhausts the possible information about the objects." (1949, p. 210)

A.5 Bell

- "When it is said that something is 'measured' it is difficult not to think of the result

as referring to some preexisting property of the object in question. This is to disregard Bohr's insistence that in quantum phenomena the apparatus as well as the system is essentially involved." — "Against 'Measurement'," Physics World (1990)

- "The first charge against 'measurement', in the fundamental axioms of quantum mechanics,

is that it anchors there the shifty split of the world into 'system' and 'apparatus'." — ibid.

A.6 Bohm (documented, not used in §2)

- "The notion that all these fragments are separately existent is evidently an illusion, and

this illusion cannot do other than lead to endless conflict and confusion." — Wholeness and the Implicate Order (1980)

- Counter-witness: pilot-wave "beables" (definite intrinsic positions) — disclosed in §2.
- Bell-escape note: Bohmian mechanics is explicitly nonlocal, and that nonlocality — not contextuality — is what takes it outside Bell's local-hidden-variable scope (hence its separate box in §1.5).

A.7 Cartwright (documented, not used in §2)

- "The fundamental laws of physics do not describe true facts about reality."

— How the Laws of Physics Lie (1983), p. 54

- Counter-witness: capacities realism (The Dappled World, 1999) — disclosed in Appendix A.7.

A.8 van Fraassen (documented, not used in §2)

- "Science aims to give us theories which are empirically adequate; and acceptance of a

theory involves as belief only that it is empirically adequate." — The Scientific Image (1980), p. 12

- Counter-witness: symmetric cut (cuts against the paper's own ontology) — disclosed in Appendix A.8.

APPENDIX B — EXTENDED TECHNICAL AUDITS

Full equation-level treatments. Each subsection derives the result the §3 audit summarizes, showing exactly where the encounter-indexing enters the formalism.

B.1 Charge: the renormalization group

The running coupling satisfies the RG equation:

$\mu\, d/d\mu\, \alpha(\mu) = \beta(\alpha) = -(\beta_0/2\pi)\, \alpha^2 - (\beta_1/4\pi^2)\, \alpha^3 - \ldots$

with $\beta_0 = 11 - (2/3)n_f$ for QCD, $\beta_0 = -4/3\, n_f$ for QED (sign convention dependent). The one-loop solution:

$\alpha(\mu) = \alpha(\mu_0) / [1 + (\beta_0\, \alpha(\mu_0)/2\pi)\, \ln(\mu/\mu_0)]$

The "intrinsic charge" is therefore a function of the encounter scale. At $\mu = m_e$, $\alpha \approx 1/137.036$; at $\mu = M_Z$, $\alpha \approx 1/127.9$. The difference is not experimental error — it is the vacuum polarization contribution, the virtual e^+e^- encounters dressing the vertex. The "bare" coupling α_0 ($\mu \to \infty$ in QED, or the cutoff scale) diverges. There is no scale at which the charge is "just itself" — every finite value is indexed to an encounter scale, and the scale-free value is infinite (meaningless).

Paper 11 reading: the RG scale μ is the tick-index of the encounter. The ledger reads $e(\mu)$ per-tick; the "intrinsic" idiom is the $\mu \to \varnothing$ limit, which does not exist.

Machine exhibit P.4 runs this differential equation numerically (Euler integration on a log-μ grid) — with the continuum machinery explicitly disclosed in-script (CONTINUUM_USE): the differential equation is the exhibit, because the paper's claim here is what the SM's own formalism says about the charge.

B.2 Spin: Stern-Gerlach and Bell

Stern-Gerlach. Non-uniform field $B = (B_0 + b'z)\hat{z}$. Force on magnetic moment:

$F_z = \mu_z\, (\partial B_z/\partial z) = g\, (q/2m)\, S_z\, b'$

Eigenvalues $S_z = \pm\hbar/2$ give two spots. But S_z is $S \cdot \hat{z}$ — the operator is defined by the field direction. Rotate the apparatus by R: the measured operator becomes $S \cdot (R\hat{z})$, with eigenstates $|\uparrow_{R\hat{z}}\rangle$. The "spin-1/2" that is "intrinsic" is the dimensionality (2) of the representation, not any value — and even the dimensionality is a fact about the rotation group SO(3), not about the electron.

Bell. For local hidden variables (pre-existing spin values), the CHSH inequality:

$E(a,b) - E(a,b') + E(a',b) + E(a',b')$	≤ 2

Quantum mechanics predicts $2\sqrt{2}$; experiments confirm ~2.7. The derivation of the inequality assumes spin values exist before measurement independently at each wing (the hidden variable λ determines outcomes locally). Violation means the local assumption is false: no local model assigns pre-existing spin values. "Intrinsic spin" as a local pre-existing

property is falsified; what remains is the encounter-indexed reading Paper 11 states natively. (Scope: nonlocal (tethered) models were never in this theorem's scope — P.9.) This is not an interpretation — it is a theorem about correlations plus experimental data, stated within its proven domain.

Machine exhibits P.2 (CHSH S = 2√2 exact) and P.9 (ternary/tether analysis) are integer-native — exact rational arithmetic throughout, no continuum machinery.

B.3 Mass: the Higgs VEV as background encounter

Yukawa sector: $L_Y = -y_f (Q_L H d_R + h.c.)$. After SSB, $H = (0, (v+h)/\sqrt{2})^T$:

$L_Y \to -(y_f v/\sqrt{2})\, \bar{d}d - (y_f/\sqrt{2})\, h\, \bar{d}d + \ldots$

so $m_f = y_f v/\sqrt{2}$. The "intrinsic" mass is the product of:

1. y_f — a dimensionless coupling (encounter strength between fermion and Higgs), and
2. $v \approx 246$ GeV — the vacuum expectation value (the background field).

Both factors are relational: y_f is defined by the interaction vertex; v is the value of a field everywhere — the most delocalized encounter imaginable, then treated as background and forgotten. The mass is "intrinsic" only after the Higgs field (the other relatum) is absorbed into the definition of the vacuum. Restore it and m_f is manifestly a two-body quantity: fermion–Higgs coupling at the VEV.

B.4 Color: gauge cancellation from the S-matrix

Under SU(3)_c gauge transformation:

$\psi(x) \to U(x)\, \psi(x)$, $A_\mu \to U\, A_\mu\, U\dagger + (i/g)(\partial_\mu U)U\dagger$, $U(x) \in SU(3)$

The quark field's color components mix. Physical states $|\text{phys}\rangle$ must satisfy:

$U\, |\text{phys}\rangle = |\text{phys}\rangle$ (gauge invariance)

which forces color singlets: mesons ($\bar{\psi}_i \psi_i$ summed), baryons ($\varepsilon_{ijk} \psi_i \psi_j \psi_k$). The S-matrix element for any physical process:

$S_{fi} = \langle f; \text{singlet}|\, S\, |i; \text{singlet}\rangle$

contains no free color index. The color labels i, j in the Lagrangian are summed/traced in every observable. This is not an approximation — it is exact, to all orders, by gauge invariance (Elitzur's theorem: local gauge symmetry cannot break spontaneously, so no gauge-non-invariant VEV can rescue the color as physical).

The R-ratio derivation exhibits the inference: at leading order,

$R = [\Sigma_q\, 3\, e_q^2\, \sigma_0] / \sigma_0 = 3\, \Sigma_q\, e_q^2$

The "3" counts color multiplicity — the dimension of the fundamental representation. It is the number 3, doing arithmetic in a cross-section formula. Promoting "multiplicity 3 in the rate" to "three intrinsic colors carried by quarks" is exactly the reification step §5 identifies: the mathematics uses the number; the prose invents the possession.

B.5 Flavor: the CKM matrix as encounter-indexing

Standard parametrization (Chau-Keung):

$V_{CKM} = R_{23}(\theta_{23}) \cdot \Gamma_\delta \cdot R_{13}(\theta_{13}) \cdot \Gamma_{\delta\dagger} \cdot R_{12}(\theta_{12})$

with three angles and one CP phase. The charged current couples:

$(d', s', b')^T_{weak} = V_{CKM} \cdot (d, s, b)^T_{mass}$

The "flavor" basis (what the W sees) and the "mass" basis (what propagates) are different bases of the same space. A K^0 meson ($d\,\bar{s}$ in the strong basis) evolves:

$K^0(t)\rangle = g_+(t)$	$K^0\rangle + (q/p)\, g_-(t)$	$\bar{K}^0\rangle$

oscillating between "strange" and "anti-strange" — the flavor label changes with time because it was never a property of the meson but a projection onto the weak-interaction basis. An intrinsic property does not oscillate away between encounters.

Machine exhibit P.5 runs the SM's Chau-Keung parametrization with its complex phase intact — continuum explicitly disclosed in-script (CONTINUUM_USE): the complex phase is the exhibit.

B.6 Magnetic moment: the loop expansion as encounter sum

The vertex function: $\Gamma^\mu = \gamma^\mu F_1(q^2) + (i\sigma^{\mu\nu} q_\nu/2m) F_2(q^2)$. The anomalous moment: $a = F_2(0)$. Perturbative expansion:

$F_2(0) = (\alpha/\pi)\cdot(1/2) + (\alpha/\pi)^2\cdot(-0.328478965\ldots) + (\alpha/\pi)^3\cdot(1.181241\ldots) + \ldots$

- 1-loop (Schwinger 1948): 1 diagram — electron emits/reabsorbs virtual photon.
- 2-loop: 7 diagrams.
- 3-loop: 72 diagrams.
- 4-loop: 891 diagrams.
- 5-loop: 12,672 diagrams (Kinoshita et al.).

Each diagram is a virtual encounter — particles created, interacting, annihilated, all within the computation of "the electron's" moment. The "intrinsic" value is the sum. There is no term in the series corresponding to "the electron alone" — the tree-level Dirac value g=2 is itself the free-field idealization, defined by removing interactions from the Lagrangian, not by isolating the electron from encounters. The free field is a calculational device; the dressed moment is the physical quantity; the dressing is encounters all the way down.

Machine exhibit P.7 sums the SM's perturbation series with its real coefficients — continuum explicitly disclosed in-script (CONTINUUM_USE): the series is the exhibit.

B.7 Numerical worked examples

R-ratio. Below charm threshold, active quarks: u, d, s. Charges: $e_u = +2/3$, $e_d = -1/3$, $e_s = -1/3$.

$R = 3 \times [(2/3)^2 + (-1/3)^2 + (-1/3)^2] = 3 \times [4/9 + 1/9 + 1/9] = 3 \times 6/9 = 2$

Measured: $R \approx 2.0$ (below charm threshold) — machine exhibit P.3 now computes $R = 2$ as an exact rational identity. Without the factor 3: $R = 2/3$, ruled out by data. The "3" is doing all the work — it is the entire empirical content of "three colors" at this order. But note what the "3" is: the dimension of the fundamental representation of SU(3), a group-theory integer. It enters the rate formula. It does not enter as "three things the quark possesses" — the quark field has one color index taking three values, and the "3" counts the values, not possessions. The inference from "factor 3 in the rate" to "three intrinsic colors carried by quarks" is the reification step, performed silently between the calculation and the textbook sentence.

Bell-CHSH. For the singlet state $|\psi^-\rangle = (|\uparrow\downarrow\rangle - |\downarrow\uparrow\rangle)/\sqrt{2}$, QM predicts:

$E(a,b) = -a\cdot b$

Choose $a = \hat{z}$, $a' = \hat{x}$, $b = (\hat{z}+\hat{x})/\sqrt{2}$, $b' = (\hat{z}-\hat{x})/\sqrt{2}$. Then:

$S = |E(a,b) - E(a,b') + E(a',b) + E(a',b')| = 2\sqrt{2} \approx 2.828 > 2$

The local-hidden-variable bound is 2. Aspect (1982): $S = 2.697 \pm 0.015$. Hensen et al. (2015, loophole-free): $S = 2.42 \pm 0.20$. Every experiment violates the bound. The derivation of the bound assumes pre-existing spin values (the hidden variable λ fixes outcomes for all axis choices). Violation means: there is no λ. The spin values do not exist before the encounter — not "unknown," not "hidden," but nonexistent. This is the experimental proof that "intrinsic spin" (as pre-existing possessed value) is false. The textbooks that still write "intrinsic spin-1/2" after Aspect are writing against the data. Scope: nonlocal (tethered) models were never in this theorem's scope — P.9.

g−2 loop count. The five-loop QED contribution to a_e requires evaluating 12,672 Feynman diagrams (Kinoshita, Nio, et al., 2012–2019). Each diagram is a distinct virtual-encounter topology. The numerical result:

a_e(QED, 5-loop) = 0.00115965218161(23)

matches experiment (0.00115965218059(13)) to 9 significant figures. Every one of those figures comes from encounter diagrams — there is no "zeroth" term corresponding to the electron alone. The Dirac value a_e = 0 (g = 2 exactly) is the free-field result: no interactions, no moment anomaly. The anomaly — the actual physical quantity — is entirely encounters. To call the sum "intrinsic" is to use a word that means the opposite of what the calculation contains.

B.8 The pattern, stated once

In all six cases, the formalism has the structure:

Property = (encounter-indexed quantity) + (prose gloss claiming intrinsicality)

The left side of each equation is encounter-indexed by the mathematics itself (running scale, gauge choice, basis choice, axis choice, loop sum, VEV background). The "intrinsic" enters only when the equation is described — in textbooks, in particle tables, in the possessive grammar of "the electron has." The audit's 0/6 is therefore not an interpretation but a reading of the equations: nowhere in L_int, S·n̂, m_f = y_f v/√2, ψ_i → U_ij ψ_j, J^μ = ūV_CKM d, or Σ C_n(α/π)^n does anything appear that is independent of encounters. The intrinsicality is not in the physics. It never was. It was in the prose about the physics.

APPENDIX C — FIGURE PLANS (PRESENTED)

Seven figures for the eventual PDF build, specified in full. Each entry: title, layout description, elements, labels, and the paper section it illustrates.

Figure 1 — The Reification Ladder (§5)

Layout: Vertical flowchart, five boxes connected by downward arrows. Elements:

- Box 1 (top): "OPERATIONAL DEFINITION" — sublabel: "'Spin is what Stern-Gerlach splits along n̂'"
- Arrow down to Box 2: "CONTEXT ELISION" — sublabel: "'The electron has spin-1/2' (axis dropped)"
- Arrow down to Box 3: "POSSESSIVE PREDICATION" — sublabel: "'The electron's spin'"
- Arrow down to Box 4: "REIFICATION" — sublabel: "'Spin is intrinsic to the electron'"
- Arrow down to Box 5: "CIRCULAR EXPLANATION" — sublabel: "'The beam splits because it has spin'"
- The arrow from Box 2 to Box 3 is highlighted in red with the label "DEFECT SITE — encounter-indexing dropped here."
- A curved arrow from Box 5 back to Box 1 labeled "circular: explains the encounter by the abstraction the encounter defined."

Caption: "The five-step reification mechanism (§5). Each step is locally reasonable; the error enters at the 2→3 transition, where the encounter-indexing is elided. By step 5, the circle is complete."




Figure 1 — The Reification Ladder (§5)

Figure 2 — The Audit Matrix (§3.7)

Layout: 6×5 grid table, rendered as a figure with color coding. Columns: Property | Their equation | Smuggle site | Encounter-indexing | Verdict Rows: Charge, Spin, Mass, Color, Flavor, Magnetic moment. Color coding: Verdict cells — green for the REFUTED readings (spin's local-values reading, color, flavor), yellow for the GAP readings (spin's axis-constituted reading, charge, mass, moment); the spin cell is split down the middle. The bottom row reads "0/6" in bold. Caption: "The six-property audit at a glance. Green = formalism refutes the intrinsic reading; yellow = intrinsic reading underivable. In no case does 'intrinsic' appear in the equations."


0/6 — in no case does “intrinsic” appear in the equations

Property	Their equation	Smuggle site	Encounter-indexed	Verdict
Charge	$L_{int} = -e\bar{\psi}\gamma\psi A$	Scale μ dropped; bare e_0 infinite	The coupling at scale μ	**GAP**
Spin	$F = \nabla(\mu \cdot B)$; $S \cdot \hat{n}$	Axis $\hat{n}$ dropped; Bell falsifies local pre-existence	The axis; the value (Bell)	**REFUTED / GAP**
Mass	$m_f = y_f v/\sqrt{2}$	VEV encounter forgotten	The Higgs coupling; the kinematic fit	**GAP**
Color	L_{QCD}; ψ_i, $i \in \{r, g, b\}$	Gauge label promoted to possession; cancels from S-matrix	Everything (gauge-dependent)	**REFUTED**
Flavor	$J^\mu = \bar{u}\gamma^\mu V_{CKM}\, d$	Basis-dependence treated as correction	The interaction basis	**REFUTED**
Mag. moment	$a_e = \sum C_n(\alpha/\pi)^n$	12,672 virtual encounters attributed to “the electron”	The loop sum itself	**GAP**

Figure 2 — The Audit Matrix (§3.7)

Figure 3 — Sharp Contrast (§4)

Layout: Two-column visual. Left column (red-tinted): "STANDARD MODEL" with six claim boxes, each with the word "intrinsic" struck through. Right column (blue-tinted): "PAPER 11" with the six Level A counterparts. Connecting arrows between each pair labeled with the verdict (Category mistake, Intrinsic only in prose, etc.). Caption: "Sharp contrast (§4): what the standard gloss claims vs. what Paper 11 proves. The left column's strikethrough is the audit's finding — 'intrinsic' is the prose, not the physics. The magnetic-moment counterpart (aspect aggregation) carries [LEVEL A, author-authorized] — a declared bookkeeping rule with stated falsifiers (Appendix E.5), not a proved fact."



** [LEVEL A, author-authorized] — declared bookkeeping rule, falsifiers in Appendix E.5*

Figure 3 — Sharp Contrast (§4)

Figure 4 — Whitehead's Fallacy, Diagrammed (§2.1, §2.8)

Layout: Two panels side by side. Left panel: "ABSTRACTION" — a thought-bubble containing "categories of thought: charge, spin, color labels." Arrow labeled "mistake" pointing right. Right panel: "MISPLACED CONCRETENESS" — a box labeled "furniture of the world: intrinsic properties of particles." Below: Six small boxes, one per property, each showing the specific abstraction→concretion move (e.g., "S·n̂ (needs axis) → 'spin-1/2' (no axis)"). Caption: "Whitehead's fallacy of misplaced concreteness (1925), applied. The Standard Model's quantum numbers are categories of thought promoted into concrete furniture."




Figure 4 — Whitehead's Fallacy, Diagrammed (§2.1,

Figure 5 — The Encounter, Schematized (§3, §9)

Layout: Two diagrams, one crossed out. Top (valid): Three boxes — "CONFIGURATION" + "APPARATUS/ENCOUNTER" + "TICK" — with arrows converging to a fourth box: "PROPERTY VALUE." Label: "Encounter-indexed: the value exists at the convergence." Bottom (crossed out with red X): One box — "PARTICLE" — with an arrow to "PROPERTY VALUE" (no encounter, no tick). Label: "Intrinsic (crossed out): the value exists without the encounter — Bell, Elitzur, and CKM forbid this." Caption: "Two ontologies (§1.3). Top: the encounter constitutes the value (derived). Bottom: the value pre-exists the encounter (smuggled, and in three cases refuted)."




Figure 5 — The Encounter, Schematized (§3,

Figure 6 — Historical Timeline (§2.7)

Layout: Horizontal timeline, 1886–1990, with five marked points.

- 1886: MACH — "Gedankending: atoms as things of thought."
- 1925: WHITEHEAD — "Fallacy of misplaced concreteness named."
- 1927: BOHR — "Complementarity: properties defined by arrangement."
- 1958: HEISENBERG — "'Atoms are not things.'"
- 1990: BELL — "'Measurement' smuggles preexisting properties."

Below the timeline: A shaded bar labeled "The intrinsic idiom hardens" spanning 1930s–2012, with markers for "particle tables (1930s)", "renormalization (1948)", "quarks (1964)", "Higgs VEV (1967/2012)". Caption: "A century of dissent against reification (§2). The witnesses were not refuted — they were outvoted by the table format."




Figure 6 — Historical Timeline (§2.7)

Figure 7 — Falsification (§6)

Layout: A single large empty box (dashed border) with the label: "Property determination with no encounter — no field, no apparatus, no axis, no scale, no basis." Below the box: "No such determination exists in the literature. This absence is the evidence." Caption: "The falsification condition (§6): produce one entry for this box and the audit's 0/6 becomes 1/6. The box is empty. That emptiness is the paper's strongest exhibit."



No such determination exists in the literature.
This absence is the evidence.

Figure 7 — Falsification (§6)

APPENDIX D — REVISION HISTORY

- v26 (2026-10-18). Twenty-sixth draft (author-authorized — full build authorization 2026-10-18): + PDG badging at the seven physical-idiom "1/128" sites (§1.5, §3.1(a) textual-evidence blockquote, §3.1(b) equation, §4.1 contrast-table row 7, §5.2 elision list, §5.3 step 2, §12.1 trap paragraph): each now carries [LEVEL B: rounded physical idiom; PDG α(M_Z) = 1/127.9] per the v24-ruling-3 approximation rule; P.4-attribution sites (§8.7, H.2, §8 run-record) untouched at 1/129.34. + EA-W2 (parked v24): verified already in-tree — the §0.5.1 rule's incidental-'≈' carve-out is present as written; no change needed. + EA-W3 (parked v24): new §0.5.1 precision-convention line (badged numbers print at fixed decimals; machine's full value stated where load-bearing). + MC.1 machine/author distinction (his ruling): §11.4 step-3 heading re-badged [LEVEL A: MACHINE / AUTHOR]; 9 script print/docstring/comment sites re-badged hybrid; script re-run green, listing re-embedded byte-identical, run-record hash re-pinned; §11.4's MACHINE/AUTHOR decomposition (§11.4) and hybrid badges (§0.5.1, §0.5.5, §8 run-record) unchanged. + DA-4 (parked v24): §0.5.6 rule-1 shape-(b) exception wording polished (editorial; meaning identical). + L282 "a proved instance of Ontology B" (DeepSeek-triage ruling, approved). + A. §7.4 Paper-12 deferral (his ruling): explicit scope note — 11.5 uses the working capability/actuality distinction without constructing it; the formal capability-as-relation account is Paper 12's work, nothing here certifies it; no teaser. + B. §11 capstone strengthening (his decisive ruling — DeepSeek's demotion REJECTED): §11.6 now states the integration claim crisply (native counts → integer-native scripts → disclosed SM-exhibit machinery → inverse-square at −1.9886); honest strengthening only. + C. §8.2 0/6 honesty paragraph: the record's locational value made explicit (REFUTED ×2 chains, GAP ×3, spin split) — a future derivation starts from the map, not from zero. + Loop pass on the staged tree (devil's advocate + evil auditor + red-team, read-only): 3 genuine record charges repaired (G-1: v26 changelog's seven-site section labels corrected; G-2: ESP site counts corrected; G-3: this count refresh); 3 weak noted, 9 not genuine. + Machine counts refreshed after v26's own edits (v16-G2 class): FW.1 line counts 10,979→11,003 (§0.5.3, §0.5.5 — the +24 is the §0.5.1 precision line's 2, the §2.7 citations' 6, the §2.7 attribution lines' 3, the §7.4 scope note's 2, the §8.2 paragraph's 2, the §11.6 paragraph's 9, the REFERENCES additions' 2, the changelog stub's 1, minus separator cleanup 3); PA.1 20/55 re-run — unchanged; 21/21 scripts green on the final tree; 44 fences even. + §2.7 three textbook citations (MAJOR EMPHASIS, full editorial control): WIRED — Evans (1955, p. 140) "each electron possesses an intrinsic angular momentum"; Griffiths 1e (1987, p. 49) "the gluons themselves carry color"; Griffiths 2e (2008, p. 22) "the neutron does have a charge structure … and a magnetic dipole moment" — all three quotes verified against actual book text with printed page numbers (archive.org OCR for Evans and Griffiths 1e; document reproduction with visible folios for Griffiths 2e); author-note removed; Evans + Griffiths-1e added to REFERENCES. + ESP packaging pass (approved): F-45c correction applied — old sentences implying marker blocks exempt hard-banned terms replaced with the correct rule in ESP_v2.2_START_HERE.txt, esp_v2.2_COMPENDIUM.txt (2 sites), esp_v2_chat_kit.txt (1 site), and all six v2.2_model_packs starter packs (doc text only, no code touched; v2.0.3/v2.0.4/v2.1 files left as shipped); esp_v2.2_package.zip rebuilt (same 12-member membership; now packs the current on-disk v2.2 engine — flagged: no backup of the Oct-12 zip kept); conformance on the packaged tree reports 245 passed, 0 failed; zero old-sentence instances remain. [LOOP COMPLETE 2026-10-18 — v26 loop pass (devil's advocate + evil auditor + red-team, read-only, final staged tree): 3 genuine record charges repaired (G-1/G-2/G-3 above), 3 weak noted, 9 not genuine.]
- v25 (2026-10-18). Twenty-fifth draft (author-authorized, "Execute all fixes you have my authorization" — "fix everything including the B.7 line"): + GLM v24 red-team triage (3 workers + loop; P4/P9/FW.1 executed): F3 GENUINE — §8.7 P.4 row "α runs 1/137 → 1/128" → "1/129.34 (schematic one-loop n_f=3; PDG value 1/127.9)" (executed P4 prints 1/129.338; v23 changelog pin α(M_Z)=1/129.34); loop-found same-class H.2 prose fixed ("to 1/128 (at M_Z)" → "to 1/129.34 (at M_Z; schematic one-loop n_f=3)"); §8 run-record P.4 row headline pinned (α(M_Z)=1/129.34). F4 GENUINE — §3.2(e) tether "E(a,b) = −a·b exactly, S = 2.83 = 2√2" → "E(a,b) ≈ −a·b (within TOL = 0.04), S = 425/149 ≈ 2.8523 (within 0.04 of 2√2)"; severed "S collapses to 2.00" → "296/149 ≈ 1.9866" (executed P9; both stale since v12 while §8.7 carried the updated values). F2 WEAK — B.7 scope sentence appended ("Scope: nonlocal (tethered) models were never in this theorem's scope — P.9"). F1 NOT GENUINE (FW.1 executed → 10,974; the v24-DOI entry explains the 10,972→10,974 step; GLM compared the body against a superseded changelog line) + v24-DOI count-note parenthetical added (v16-G2). Seven other "1/128" sites left as B.1-backed physical idiom (not P.4 attributions); H.1/H.2 script verdict strings left (they audit the physical RG claim). Parked for the author: whether the v24-ruling-3 approximation rule wants PDG badging at the seven physical-idiom

sites. + Machine counts refreshed after v25's own edits (v16-G2 class): FW.1 line counts 10,974→10,979 (§0.5.3, §0.5.5 — the +5 is this changelog entry's 4 lines (entry + blank + loop marker + blank) plus the B.7 scope line); 21/21 scripts green on the final tree; 44 fences even.

[LOOP COMPLETE 2026-10-18 — v25 loop pass (devil's advocate + evil auditor + red-team, read-only, final tree): 0 genuine charges; 5 weak documented, no in-tree change (B.7 scope-line binding tension — RT/DA; α(M_Z) three-number bridge — carve-out coherent, PDG-badging question stands parked — EA; §0.5.5 P.9-Part-3 column nit, pre-existing — EA; tether supra-quantum press-point — RT). Final tree: 21/21 scripts exit 0, 267/267 engine conformance, selftest PASS (coordinator verification run).]

- v24-rulings (2026-10-18). Rulings fold-in (author-authorized, "You are authorized to fix that. And give me version twenty four"): SUPERSESSION — the v24 files shipped 16:00 UTC 2026-10-18 predate these rulings and are superseded by this build; a first fold-in attempt was interrupted by a container restart and restarted from regenerated specs (no partial edits survived). + Ruling 1: §0.5.1 new stated rule — "Denied [Level A]": the badge names the rigor of the examination, "Denied" the verdict; not Level B or C (weaker positive grades); §4.3 ledger stamp now points to the rule. + Ruling 2: Appendix E.8 MASS_AS_LEDGER (Paper 8 v2, Zenodo same-DOI new version): source Paper 8 v2; badge-at-source [LEVEL A] author-authorized 2026-10-18; validation: prose-section derivation per Paper 8 v2 Appendix D (no machine check, none claimed); 11.5 reliance: the mass-as-ledger claim — the open trace is closed; §0.5.6 rule 1 now distinguishes the two author-authorized shapes (declared axiom vs prose-derived at source); §3.7/§4.1/§4.3 cites point to E.8 (closing summary renumbered E.9). + Ruling 3: −1.9886 restored as the real [LEVEL A] number — MC.1's log-log fit recomputed live (KEEP+DISCLOSED: the number IS the fit); exact-rational bound $|R(d)-1| < 1/d^2$ demoted to [LEVEL B] translator with the real number badged beside it; new framework-wide §0.5.1 rule: every approximation/rounding/translator is Level B, honestly labeled with why, with the real number specifically badged beside it — from now on, in every paper. D2 handshake framing unchanged. + Ruling 4: §0.5.1 hybrid badge format [LEVEL A: MACHINE / AUTHOR]; E.7 SCALE_FIDELITY re-badged; hybrid audit confirms E.7 the paper's only hybrid. + Ruling 5: E.5 approved as-is, untouched. + Machine counts on the final tree: FW.1 re-run exit 0, "Scanned 10,972 lines" (§0.5.3, §0.5.5 refreshed); MC.1 listing re-embedded byte-identical; run-record MC.1 row re-pinned. + Loop pass on the fold-in (devil's advocate, evil auditor, red-team — read-only, final tree): 11 genuine charges repaired (RT-G1, EA-1, DA-1, DA-4, DA-5-part, DA-7, DA-8, DA-9, DA-10 + EA-W5, F10-hygiene), 6 weak parked/noted (DA-2, DA-3, DA-6, EA-W1-adjudicated-clean, EA-W2, EA-W3). Ruling-4's "only hybrid" line in this entry is superseded: MC.1's −1.9886 headline is the second hybrid (DA-9/DA-10); all running-prose −1.9886 badges re-badged [LEVEL A: MACHINE / AUTHOR], MC.1 docstring re-badged, listing re-embedded, run-record hash re-pinned.
- v24-DOI (2026-10-18). Citation correction: the Paper 8 REFERENCES entry pointed at Zenodo 21238949 (v1's version DOI) while labeled v2 — corrected to the v2 version DOI 10.5281/zenodo.23456444 (concept DOI 10.5281/zenodo.21238948), verified against the live Zenodo API; the record's file is byte-identical to the shipped Paper_8_Mass_as_Internal_Accounting_v2.pdf. [Count note (v16-G2): this entry added 2 lines (entry + blank); FW.1 10,972→10,974.]
- v24 (2026-10-18). Twenty-fourth draft (author-authorized, "You may begin your remediation, allocate every spawn agent possible"): + v24 FORTRESS remediation — the full StepFun v23-audit triage repair set, fanned out to 9 teams + assembly. + Badge team (20 edits): §0.5.6 badge inheritance rule — no silent Level A by distance (every inherited Level A claim carries an Appendix E inheritance line: source, badge-at-source, validation, 11.5 reliance); V23-3 FORMALIZED per his ruling (do not demote): [LEVEL A, author-authorized] with the §0.5.1 carve-out and stated falsifiers (a tick where a port contribution is attributable to two aspects or none; a T-action altering contributions of aspects owning neither touched port); badge propagation traced (no automatic Level-A inheritance; declarations labeled as declared axioms); H.1 script carries the formalized subtype exactly. + Prose team (17 edits): V23-5 (GENUINE): P.7 block 3 declares itself schematic ("leading-log only") → CLASSIFIED stands (§0.5.5 "P.1–P.6, P.7 blocks 1–2"; §8.7 P.7 row "(block 3 — classified, leading-log only)"); §8.7 row key-constant text owned by prose; §8.5 C2 row "(H.2; H.3: author classification, §8.4)"; §8.9 PA.1 fail-loud sentence (V23-20). + Continuum team (32 prose edits, assert-unique; 10/10 re-embeds byte-identical): the two-tier statement — Tier 1 integer-native (P.1–P.3, P.6, P.9, MC.1: exact integer/rational arithmetic, no continuum machinery) vs Tier 2 SM-formalism exhibits (P.4, P.5, P.7, P.8: the SM's own equations with continuum machinery intact and disclosed, CONTINUUM_USE in-script — there the continuum is the exhibit, not scaffolding); the V23-5/continuum conflict adjudicated by ADDITION (classification

from prose, disclosure appended); §11.3 two-tier statement; §11.4 steps 2–3 + handshake + §11.5/§11.6 integer-native; B.1/B.5/B.6 continuum disclosures; B.2/B.7 exact notes; run-record rows MC.1/P.1–P.9; MC.1 hierarchy inverted per his ruling 3 (author-authorized 2026-10-18): fitted −1.9886 restored as the real [LEVEL A] number (the handshake's cost, recomputed live by the log-log fit; fit machinery KEEP+DISCLOSED — the number IS the fit); exact-rational bound $|R(d)-1| < 1/d^2$ (decreasing, d=5..19) demoted to [LEVEL B] translator with the real number badged beside it; D2 honest-scope disclosure preserved. P.7 v23-STALENESS REPAIR, logged openly: the v23 P.7 listing had drifted 1 hunk from its script file (stale M1 witness print); the listing was brought to the authoritative v24 script — content-identity anchor held, drift printed, never silent. + FW.1 team (docstring-honesty cluster, all three GENUINE): Group A sentence-pattern gate documented (only is/are + intrinsic can breach); Group B reconciled to one six-term inventory across prose, docstring, and code ("continuous" and "in the limit" implemented — were docstring-promised, code-missing; same-line property-word breach test keeps §9's thesis vocabulary clean); Group C: "moment" added, intrinsic_quoted exemption documented with stated residual risk (zero live instances in v23); mutant battery +B3/+C2/+A2-diagnostic (A2 survives by design, labeled diagnostic). + PA.1 team: fail-loud (a)/(b)/(c) subsection parsing (V23-20: unmarked subsections skipped with printed WARNING, zero parsed exits nonzero); F-39 (a)-block/(b)-block scoping with tie-breaks documented (block membership the sole routing criterion; no cross-category double-counting); 8-case selftest green. + H.3 team: script rebuilt — verdict-layer transcription invariant (7-cell map: 6 properties, spin split; structural checks A–G across §8.1/§8.2/§8.3/§8.4/§8.5-C2/§3.x; 9-case planted-mutant battery; 0 DERIVED cells computed); re-embedded byte-identical. PROSE APPLIER RESOLVED (coordinator): stale v23 line numbers (1861/1999/2133) discarded in favor of content-derived addressing — assert-unique anchors for the §8.4 rebuild (heading→next-heading span) and §8.6 point 3; the run-record H.3 row was already refreshed by the mechanical pin. + H.4 team: script rebuilt — COMPUTED/INHERITED/HUMAN-JUDGMENT cells with evidence locators, no baked verdicts (old "7/7 vs 0/7" headline retired); re-embedded byte-identical. PROSE APPLIER RESOLVED (coordinator): E2–E5/E7–E11 applied by assert-unique anchors (E1's registry row already refreshed); E6's 4-column table REJECTED — the §8.5 table was brought to the team's 3-column-with-inline-kind-tags state, merged with the prose team's C2 row keeping the V23-16 '(H.2; H.3: author classification, §8.4)' qualifier; H.3 exits 0 (Check C 7/7) and H.4 exits 0 on the final tree. + Engine: conformance battery 245→267 (+13 physics_payload-profile cases +9 demo-hash checks = 267/267 green, run live); R10a (physics_payload apparatus note), R11 (engine row: 6cebc541…/267-case), R12 (236→267 count fixes + run-record pin sentence), R13 (lexical paragraph rewritten from shipped constants); §8.9 PA.1 sentence (V23-20). + Run-record refresh: FW.1/H.1/H.3/H.4/PA.1 re-hashed from the installed script files (mechanical pin); key constants from the teams' notes; header v23→v24. + Title page v23→v24 DRAFT. + Machine counts on the final tree: FW.1 re-run exit 0, "Scanned 10,846 lines" (§0.5.3, §0.5.5 refreshed from that output — the +1,762 vs 9,084 is the v24 re-embeds' +1,569 (longer remediated scripts), the v24 prose edits' +161, the §8 prose re-export's +27, this changelog entry's 3 lines (entry + blank + loop-pending marker), and the loop-pass prose fixes' +2); 16/16 changed listings byte-identical by block comparison (10 STEP-1 + 6 PHASE-C); 44 line-start fences even (22 pairs). + Build-tree repair (coordinator, pre-loop): the first-assembled v24 deliverables carried stale v23 §8.4/§8.5/§8.6 prose (marker-scan H.3, hardcoded 7/7-vs-0/7 H.4 scorecard) while Appendix G already embedded the rebuilt scripts — the H.3/H.4 prose resolutions had landed in the working file after the deliverable export, and the rebuilt H.3 failed on the exported tree (Check C: §8.4 alignment table absent). Repaired by re-exporting the working file as the deliverable .md/.txt and re-rendering the builder HTML's §8.4/§8.5/§8.6 + §8.1 note + v24 changelog entry from the same source (rendering converter byte-validated against the old tree's rendering before use); 21/21 scripts, 267-case engine conformance, and engine selftest re-run green on the repaired tree.

[LOOP COMPLETE 2026-10-18 — v24 loop pass (devil's advocate + evil auditor + red-team, read-only, final tree): 8 genuine charges (6 fixed in-tree: R1/R2/R3, DA-1/DA-2/DA-4; 2 parked for author's ruling at loop time — since ruled in the v24-rulings fold-in: §4.3 "Denied [Level A]" formalized as a §0.5.1 stated rule, Paper 8 Appendix E inheritance line closed via new E.8 MASS_AS_LEDGER), 9 weak (documented boundaries / script-hygiene flags, no in-tree change). Final tree: 21/21 scripts exit 0, 267/267 engine conformance, selftest PASS. Parent's personal final-tree re-run still pending before numbers are announced.]

- v23 (2026-10-18). Twenty-third draft (author-authorized, "correct everything now... produce version twenty three"): + StepFun's 5-chunk v22 audit → triage (6 workers; the loop pass caught 8 genuine) → adjudication round (StepFun's concessions: F-22/F-31/F-36/misread cluster conceded, F-46→F-45; offered approach — §8 two-column framing, §3.6(b)→B.6 language, §2.7 soften, KS scoping, engine profile, encounter DECLARE in §6, run-record

pinning — all taken up). + Script remediation: H.3 relabeled not rescoped per adjudication (CLASSIFIED, NOT COMPUTED — the author's own marker strings, presence checked in the author's own draft; no per-property linkage computed); H.4 scorecard + C2 fix (printed scorecard of the author's judgments: 7/7 vs 0/7 over author dict literals, verdicts carry no machine weight); G.2/G.3 hardened (v24 count assertion; (a)-block scoping) still PASS; G.4 softened (claims only the absence of the four hedges, nothing about sense-consistency); P.4's headline running value pinned (α(M_Z)=1/129.34, ~6% up from 1/137.036) by the single-N_F=3-model regression; PA.1 rescoped 120/131→20/55 (F-39: textbook possession-claims vs equation encounter-indices, (a)+Textual-evidence/(b) scoping, §8.9); FW.1/MC.1 docstring honesty (exemption breadth disclosed with stated residual risks; consistency-not-discovery framing). All 10 re-embeds byte-identical (content-identity matching, descending-order replacement, fence-glue spot-checks); 22/22 listings byte-identical (21 + ESP v2.2); 44 fences even. + Prose remediation: §8 two-column computed/classified framing (§0.5.5 promoted to carry the same split); Appendix I.5 → audit FORMAT (the contribution is the six-properties-×-four-moves format, not machinery); §8.1/§8.4/§8.5/§8.6 honesty repairs ([CLASSIFIED] on every classified subsection); F-02 → B.6 language (§3.6: the tree-level Dirac value is the free-field idealization, defined by removing interactions from the Lagrangian, not by isolating the electron from encounters); F-12 reword (§3.6 opening: the own-voice unquoted possessive reworded out of Group C shape — "The magnetic moment is measured..."; FW.1 re-run exit 0); §2.7 soften + author-note (three cited textbook instances — postwar, quark-era, modern, with page numbers — still needed from the author); F-11 one sentence (reference-fixing reply: operational definitions fix reference, the Dirac S·n̂ does the explanatory work); Appendix A → "verified by the author"; §0.5.3 exemption disclosure (quoted-context, ±2-line critical window, Group B window sizes, fail-closed changelog rule); §11.4 soften ("samples", illustrates-not-discovers); §3.2(e) tighten (the tether toy: one schematic non-separable construction reproduces the correlations; nothing about tether models in general established). + CONTINUUM item (StepFun's big finding, adjudicated narrow, author-authorized "make everything without continuous calculus — everything be honest about it"): §11.3/§11.5/§1.4 scoped (no continuum in the native ledger's ontology; the P-series exhibits use the SM's mathematical tools as labeled scaffolding; Paper 12 frontier stated — the count→weight step awaits Paper 12); P.9 sampling to the honest column (assumed scaffolding [CLASSIFIED]: uniform-over-the-sphere + DELTA=0.15 neutral-band posit, holds for any DELTA > 0); scripts NOT rewritten. + Two RULINGS: (e) KS §3.2(c) → SCOPE, his words "Scope it — why drop it, just scope it." (overruling StepFun's drop recommendation); (f) encounter criterion → OUT OF SCOPE for 11.5, belongs to Paper 9 ("Heat as Interaction Event") (his ruling). + Engine patch (F-45a/b/c: "limit"→context-banned, uppercase-anchored uv/ir, markers exempt context-banned only; F-47; F-48; F-52 STATUSES removal; new physics-payload static-check profile); §3/§9 conformance regression — fixtures refreshed from final text (v23 snapshots; the pinned §3 delta is text-only and explained: "field" 18→19 and "lagrangian" 5→6, both from the §3.6 F-02→B.6 reword; §9 unchanged); 245/245 conformance green, demo PASS. + Run-record pinning: new §8 table — 21 scripts + engine, sha256 of each source as embedded, 1–3 key constants per row, run date 2026-10-18; a changed script changes its hash. + Machine counts refreshed after v23's own edits (v16-G2 class): FW.1 line counts 8,528→9,084 (§0.5.3, §0.5.5 — the +556 is the prose remediation's +101, the v23 re-embeds' +424 (longer remediated scripts + patched engine listing), the new §8 run-record table +28, and the v23 changelog entry's 3 lines (entry + blank + loop-pending marker)); PA.1 ratio re-run on the final tree: 20/55 — unchanged. 21/21 scripts green on the final tree; 22/22 listings byte-identical by block comparison (21 + ESP v2.2); 44 line-start fences even (22 pairs).

[LOOP VERDICTS — 2026-10-18: devil's advocate 0 genuine (30+ entry claims verified against the tree, including the exact +556 accounting: 424 re-embed + 28 run-record + 3 changelog + 101 prose; 4 weak observations, none requiring repair); evil auditor 0 genuine (9/9 re-embedded listings + Appendix J engine listing byte-identical; 44 fences even; run-record sha256 pins verified; 21/21 scripts exit 0); red-team 0 genuine (8 probes hold: two-column framing, B.6 repair verbatim, KS d≥3 scoping honest, encounter declaration clean, continuum scoping consistent, bridge-words clean, no glossary collisions). No repairs required.]

- v22 (2026-10-17). Twenty-second draft (author-authorized, "You may build version twenty two"): + Bucket A fixes from the 2026-10-17/18 final independent audit (author's "full authorization for bucket A"): D3 — three "disclosed in §2" pointers repointed to Appendices A.7/A.8 (§2 has zero mentions of the pointed-to Cartwright/van Fraassen content; "symmetric agnosticism"→"symmetric cut"); D4 — H.1/H.2 label collisions disambiguated; D5 — B.1 RG-solution sign [1 − …]→[1 + …] (the paper's own ODE); D6 — REFERENCES + "Philosophy (Appendix I sources)" subsection, 7 entries; D7 — auditor identifiers scrubbed from 15 script comment sites (9 listings re-embedded); D8 — "10"→"9 significant figures"; D9 — dropped the unsupported "second" ordinal; D10 —

STRUCTURAL_INSULATION→STRUCTURAL_INSULATION_THEOREM (4 short-form sites remain, flagged for his word); D11 — 12,672 shorthand qualified. + FW.1 changelog mention-not-use exemption (author's "everything else, you have authorization"): an Appendix D entry quoting the firewall's own patterns is exempt only when the pattern is quoted on it (fail-closed); honest note — the first exemption draft was caught overbroad by the loop (red-team G1: a planted camouflaged violation slipped through) and repaired per the loop's specified construction, verified against the loop's own attack proofs. + All 10 parked rulings (author's direct answers, 2026-10-17): P1 — "non-local"→"nonlocal" at 5 older sites; P2 — F3 →"loop diagrams" (his explicit ruling, "that is the correct one"); P3 — Appendix I expanded with 4 new subsections (I.6–I.9: Whitehead, Heisenberg, Cartwright, van Fraassen — established evidence only, no new claims); P4 — badge semantics confirmed three-way, inherited-from-Paper-11 keeps [LEVEL A] via Paper 11's verification or a re-run; P5 — §8.7 +P.9/P.10 rows ("All ten run green"); P6 — §9.2 flavor bullet reworded ("assigned"); P7 — §3.5(d) +[LEVEL A]; P8 — m_t^MSbar left as-is; P9 — Appendix J "plus a fuzz loop"→"plus exception-path tests"; P10 — Appendix I H-labels disambiguated. + D2 — MC.1 handshake framing (author's confirmed idea): the −1.9886 gap is the cost at the communication between discrete shells producing emergent inverse-square; nothing is lost as −2 recovers asymptotically; listing verdict + §11.4/§11.6 rewritten consistently; analytic vindication — log-log slope of $1/(4d^2+2)$ over d=5..20 = exactly −1.9886. + Machine counts refreshed after v22's own edits (v16-G2 class): FW.1 line counts 8,527→8,528 (§0.5.3, §0.5.5 — the +1 is the v22 changelog entry itself); PA.1 ratio 20/55 (v24 F-39 rescope of the v22 120/131 count; see §8.9). + v22 loop pass (devil's advocate, evil auditor, red-team — read-only, final tree): devil's advocate 2 genuine record-nits in this entry — D6 "5 entries" corrected to 7 bullets, D3 parenthetical qualified to the pointed-to Cartwright/van Fraassen content (both repaired in this line); evil auditor 0 genuine (2 weak notes: D6 wording looseness, FW.1 split-newline +1 convention); red-team 0 genuine (1 informational residual: synthetic FW.1 cross-quote bypass shape, no live instance — flagged for FW.1's next touch); D3 "three repointed" verified against the tree (L1662/L2690/L2697 — a fourth "disclosed in §2" at L2683, the Bohm beables pointer, was never in the audit's D3 scope and is defensible via §2 L442's beables presentation; held as a precision nit for the author).

- v21 (2026-10-17). Twenty-first draft (author-authorized, "pull the trigger"): + folds the five staged single-line fixes from the 2026-10-14 minor-inconsistency pass (author's executive decision, "resolve any minor issue right now, stage it"): S1 — header stamp "2026 — v19 DRAFT (2026-10-12)" → "2026 — v20 DRAFT (2026-10-13)"; S2 — "non-local" → "nonlocal" in the §1.5 Bohm box (paragraph-internal consistency with the ruling wording); S3 — §3.3(a) cross-ref "§1.3" → "§1.5" (the withdrawal note lives under §1.5); S4 — §7.9 machine receipts "P.1–P.6" → "P.1–P.10" (stale v9-era inventory); S5 — Appendix I §I.1 apparatus inventory "P.1–P.6" → "P.1–P.10" (red-team's mirror catch). + The 10 parked items (P1–P10: F3 terminology, Appendix I scope, badge semantics, §9.2 phrasing, §3.5(d) badge, H-series naming, and four more) stay parked for the author's ruling — untouched. + Machine counts refreshed after v21's own edits (v16-G2 class): FW.1 line counts 8,427→8,428 (§0.5.3, §0.5.5 — the +1 is the v21 changelog entry itself); PA.1 ratio 20/55 (v24 F-39 rescope of the v21 120/131 count; §3 untouched). + v21 loop pass (devil's advocate, evil auditor, red-team — read-only, final tree): devil's advocate 1 genuine — the v21 entry's +1 line shifted the v13 Appendix D entry out of FW.1's 30-line history exemption, flipping FW.1 from PASS to 1 breach (exit 1) on the v13 line's self-quotation of the "at every point" pattern (mention-not-use false positive); evil auditor 7/7 PASS; red-team zero genuine findings. 20/21 scripts green on the final tree (FW.1 exit 1 — v13-changelog self-quotation false positive, see loop); 22/22 listings byte-identical by block comparison (21 + ESP v2.2); 44 line-start fences even (22 pairs).
- v20 (2026-10-13). Twentieth draft (author-authorized, "Please build yes" — the H1/H2/H3 rulings of 2026-10-13): + H1 (author's ruling): Bohmian mechanics gets its own §1.5 taxonomy box — "Separate box — Bohmian mechanics (nonlocal non-contextual beables)": definite always-possessed positions (non-contextual beables) with contextual measurement outcomes, Bell-escape via nonlocality (see A.6; §1.3); boxed separately because filing it under Subclass ii misdescribes it. The inherited-premise denial (RELATIONAL_ROLE_THEOREM, TENSION_MEASURE_IDENTITY) now covers Subclass ii and the Bohm box alike; the no-shared-premise-refutation disclosure and the Bell/KS-for-spin scoping (with the Elitzur/oscillation carve-out) are preserved verbatim in structure. + H2 (author's ruling): both §6 falsification routes stand — no mapping change, no edit. + H3 (author's ruling): the verbatim textbook sentence is wired in — "The charge on an electron, which is negative, is −e. This is one of the defining, or intrinsic, properties of the electron." — added to the §3.1(a) textual-evidence block and cross-noted in §1.5's "First, the textbooks assert it" paragraph; cited as found ('Phys15' introductory course PDF as uploaded; edition unverified). The paraphrase-vs-verbatim Griffiths accounting is unchanged. + Machine counts

refreshed after v20's own edits (v16-G2 class): FW.1 line counts 8,415→8,427 (§0.5.3, §0.5.5); PA.1 ratio 119/131→20/55 (v24 F-39 rescope of the v20 120/131 count; the v20 +1 was the new verbatim sentence, a counted possession pattern in §3's prose) (§8.9, Appendix I). + v20 loop repairs (devil's advocate, evil auditor, red-team — read-only, final tree): red-team 1 genuine (narrow) — the Bohm box's "(see A.6; §1.3)" parenthetical was dangling (§1.3 carries no Bohm text; the v17 changelog's "(nonlocal Bell-escape, §1.3)" address never landed) → repaired with a one-sentence Bell-escape gloss in A.6 and the citation trimmed to "(see A.6)". Devil's advocate 1 weak — the §1.5 pointer now reads "documented (with source caveat) in §3.1(a)". Evil auditor 5/5 PASS (diff scoped to the three authorized edits, 22/22 listings byte-identical, 44 fences even, no edits inside fenced blocks). No other paper edits from the loop. 21/21 scripts green on the final tree; 22/22 listings byte-identical by block comparison (21 + ESP v2.2); 44 line-start fences even (22 pairs).

- v19 (2026-10-12). Nineteenth draft (author-authorized, "ESP v2.2 + Paper v19 + rebundle"): + ChatGPT's v18 finding (genuine): the 7 draft-reading scripts (FW.1, G.1–G.4, H.3, PA.1) failed out-of-the-box in the machine agent bundle — their default draft path `paper_11_5_draft.md` does not exist there (the bundle ships the paper as `paper.md`) → fix: a fallback chain inlined in each script (identical helper, scripts stay standalone, no shared imports): explicit argv[1] (PA.1: --draft) → $PAPER_MD → paper_11_5_draft.md → paper.md → newest paper_11_5_v<N>.md next to the scripts; $PAPER_MD pointing at a nonexistent file falls through to the candidates; every script prints the draft file it resolved; argv[1]/--draft honored verbatim, so the input-sensitivity discipline (a nonexistent explicit path fails instead of silently scanning a stale default) is unchanged. Contract verified in a temp dir (paper.md + paper_11_5_v9.md + paper_11_5_v18.md): bare run picks paper.md; paper.md absent → newest versioned; $PAPER_MD valid → honored, nonexistent → falls through; argv[1] verbatim; empty dir → FileNotFoundError naming every tried candidate. All 7 listings re-embedded byte-identical (content-identity matching, positions re-parsed between writes, fence-count checked after every embed); Appendix G prose documents the chain. The old paper_11_5_draft.md shim is gone from the new agent bundle — made redundant by the fallback chain. + Appendix J re-embedded at ESP v2.2 (byte-identical to the standalone engine; 236/236 conformance, demo PASS) with a concise what's-new per esp_v2.2_WHATS_NEW.txt: the new "bundle" provenance lineage (closes the gap ChatGPT's v18 bundle-execution envelope exposed — the most honest execution report in the program was REJECTED by v2.1's provenance validator; the re-cast envelope now VALIDATES), script_id generalized to ^(F|P|H|G|MC|FW|PA)\.\d+[A-Z]?$ (the engine covers the paper it ships with — Paper 11.5's P./H./G./MC./FW./PA. series, not just Paper 11's F. series), and the exact-2.2 version gate (2.1 envelopes REJECTED, no negotiation). The v2.1 engine listing is removed (standing convention: current version only). + Machine counts refreshed after v19's own edits (v16-G2 class): PA.1 ratio re-run 119/131 — unchanged, no §3 edits (§8.9 and Appendix I already current); FW.1 line counts 8,149→8,415 (§0.5.3, §0.5.5). + v19 loop repairs (devil's advocate, evil auditor, red-team — read-only, final tree): devil's advocate 6/6 charges NOT GENUINE — the candidate order is the authorized contract (verified in a temp dir, not "fixed"); $PAPER_MD is opt-in ambient input and every run prints the resolved file, so misdirection is visible; stdout consumers verified unaffected (pipeline PA.1 regex, no stdout parsing in verify_bundle.py); the esp_v2.2_WHATS_NEW.txt cite is attribution on a self-contained paragraph; the temp-dir record is build testimony (the shippable evidence is the bundle regression test); _vkey is bounded by the paper_11_5_v*.md glob. Evil auditor checks PASS — 22/22 listings byte-identical and correctly slotted, 44 fences even with fence-glue spot-checks, machine counts fresh (21 scripts, 8,415 lines, 119/131), v2.1 listing fully removed, ESP v2.2 conformance 236/236 and demo PASS re-run live, and the re-cast bundle-lineage envelope VALIDATES live under the v2.2 engine (the bogus-lineage control is refused at construction with the old error shape — the v2.1 gap, closed). Red-team contract probes pass (candidate order, $PAPER_MD fall-through on nonexistent/dir/empty, argv[1]/--draft verbatim incl. fail-on-nonexistent, empty dir → FileNotFoundError naming every candidate). No paper edits from the loop. 21/21 scripts green on the final tree; 22/22 listings byte-identical by block comparison (21 + ESP v2.2); 44 line-start fences even (22 pairs).
- v18 (2026-10-12). Eighteenth draft (author-authorized, "implement the fixes, even the ones DeepSeek had"): + DeepSeek's post-zip v17-bundle audit triaged — F1 (genuine): bundle AGENT_README.txt "26 manifest hashes" → "28" (the manifest's own count; our loop missed it); F12 (genuine): README now notes ESP v2.1 exact-version-match near the ESP section (2.0.4 envelopes rejected; re-stamp remedy). + F6 (weak): §8.5 table C5 FAIL row → "no falsification condition for the intrinsic-possession gloss"; the same scoping added to the C5 FAIL reason string in scripts/H4_honesty_comparison.py ("for the intrinsic-possession gloss (the SM's cross-section predictions carry their own falsification conditions)") — listing re-embedded byte-identical. + F7 (weak): §0.5.4

script table P.1–P.10 row now reads "ternary/tether Bell analysis (schematic tether)" per §3.2(e) — note: the cited §8.7 P.9 row does not exist in v17 (that table covers P.1–P.8 only); the qualifier was applied at the actual summary surface naming P.9's analysis. + F10 (weak): Appendix J what's-new headline → "no check-logic change; the version gate now requires exact 2.1 stamps (2.0.4 envelopes are rejected)" — verified against the engine source (gate logic identical 2.0.4→2.1; only the VERSION constant changed). + F11 (weak): §1.5 Subclass ii disclosure sharpened — then loop-scoped (see below). + F4 (weak-genuine on triage with the paper open): §3.8 Reply 1 reworked — concedes frame-independence within fixed Minkowski (mathematics undisputed, matching P.6's own printed verdict), keeps the background-structure point, GR sentence fenced as "Separately, and not needed for the Poincaré-group point". + v18 loop repairs (3 agents, read-only, final tree): devil's advocate + red-team (2 agents, genuine) — the F11 sharpening as first drafted ("no argument in this paper refutes Subclass ii except Paper 11's own premises") contradicted the same paragraph's color/flavor verdicts, which rest on Elitzur's theorem and K^0-oscillation data (shared premises); repaired by scoping the sentence to Bell/KS-for-spin with the color/flavor carve-out. Evil auditor + red-team (genuine, mechanical) — v18's own edits re-staled machine counts (v16-G2/v17 class): PA.1 ratio 119/130→119/131 (§8.9 and Appendix I), FW.1 line counts 8,143→8,148 (§0.5.3, §0.5.5). Not implemented, with reasons: F2 (§8 'MACHINE VERIFICATION' heading) NOT GENUINE — DeepSeek's old F5 recycled; §0.5.5/§8.5 disclosures stand. F3 (§3.6 'virtual encounters' heading) HELD for the author's word — touches the native 'encounter' register; the C6 charge targets the vacuum-popping gloss, not the defined native term. F5 (§1.3 'exactly once') NO CHANGE — the sentence already scopes Bell in-sentence ('predictions exactly once — Bell's theorem, which excludes local hidden-variable models'). F8 (FW.1 exemptions) NOT GENUINE — exemptions are documented design (v13 changelog: rationale documented in-script). F9/H3 (verbatim textbook sentence) still HELD for the author's ruling; the paraphrase+PDG attribution stands as authorized. F13 (self-signed manifest) NOT GENUINE as a defect — restates the bundle's own disclosed THREAT MODEL. Residual (not v18's defect): the standalone esp_v2.1_WHATS_NEW.txt still says 'no engine behavior change' — now less honest than the paper's paraphrase; ESP-doc touch-up held for the author's word. 21/21 scripts green on the final tree; 22/22 listings byte-identical by block comparison (21 + ESP v2.1); 44 line-start fences even (22 pairs).

- v17 (2026-10-12). Seventeenth draft (author-authorized, "produce version 17"): + Option C — reading (a) partitioned in §1.5 (author's own synthesis; his ruling on ChatGPT's Q1): Subclass i (non-contextual possession — KS direct, Bell for local members; Bell/KS REFUTED verdicts attach) vs Subclass ii (contextual/relational extensions, Bohm-type; denied by Paper 11's inherited native premises, no shared-premise refutation offered); color (Elitzur/confinement) and flavor (K^0-oscillation) REFUTEDs attach to reading (a) as a whole; §3.2 KS sentence scoped to Subclass i; §1 billing corrected (3 REFUTED + 3 GAP, not 6/6). + Original Valkyrie's Vuln 1 (genuine): §3.1(a) attribution "Griffiths (2nd ed.), §1.5" → "Standard textbook presentation (PDG particle tables)" — the paper withdraws that Griffiths address in §1.5 (2nd ed. §1.5 is the Neutrinos section); stale "(see §1.3)" → "(see §1.5)"; dangling "Both are printed in the same book" removed. + v17 loop repairs (3 agents, read-only, final tree): red-team VULN 1 (genuine) — blanket Subclass-i scoping mis-scoped color/flavor REFUTEDs, repaired; VULN 4 (genuine) — "the subclass Bell and KS directly address" re-broadened Bell beyond local scope, repaired; VULN 5 (genuine, narrow) — "same book" dangle, repaired; VULN 6 (genuine, mechanical) — stale cross-reference, repaired. Devil's advocate charges 2/3/4/5/7 (genuine): "addressed by" → "denied by (inherited)" with no-shared-premise-refutation disclosed; L312 billing scoped to Subclass i; Bohm gloss corrected (nonlocal Bell-escape, §1.3); Subclass-ii escape hatch disclosed. Evil auditor 7/7 PASS, zero findings. Held for the author's ruling: (H1) whether Bohm needs a nonlocal-non-contextual box of its own; (H2) §6's theorem-to-verdict mapping (pre-existing prose); (H3) a verbatim textbook sentence for intrinsic charge. FW.1 line counts refreshed 8,117→8,143 (§0.5.3, §0.5.5) after v17's own prose edits. 21/21 scripts green on the final tree; 22/22 listings byte-identical by block comparison (21 + ESP v2.1); 44 line-start fences even (22 pairs).
- v16 (2026-10-11). Sixteenth draft (author-authorized, "give me version sixteen and give me the newest version of ESP, call the version two point one"): + DeepSeek F15 (genuine): §0.5.4 "Twenty scripts in five series" → "Twenty-one scripts in five series" (P.10 made it 21). + DeepSeek F4 (genuine): the unscoped Bell sentence ("the experimental proof that simple location fails for spin") now reads "fails for spin in local models" per the §8.3 discipline (cf. the already-scoped "that local models fail — nothing more, nothing less"). + DeepSeek F6 (weak-genuine): PA.1's divergence print now says "Every counted possession pattern is matched by an encounter-index the prose elides" (was "Every possession claim") — fixed in script source, listing re-embedded with line-anchored fence matching. + DeepSeek F11 (weak-genuine): §3.4 now states "This audit targets the possession

reading (a); the representation-label usage is not the target and is compatible with the ledger." + Appendix J re-embedded at ESP v2.1 (byte-identical to the standalone engine; 217-case conformance re-run on the bumped engine) with concise what's-new (doc fixes F1/F2/F8/F10; no engine behavior change; 2.0.4 envelopes now REJECTED — exact version match required, no negotiation). + DeepSeek's not-genuine findings recorded without edit: F3 (Griffiths paraphrase already downgraded and labeled in v13 — settled author ruling), F5 (H-series author-classification already disclosed in §0.5.5 and §8.5), F7 (mass bridge premise explicitly stated as inherited, RT-02), F9 (Paper-12 limitation stated in the adjacent sentence), F12 (heading is the paper's disclosed idiom with scoping prose adjacent), F13 (already scoped to local hidden-variable), F14 (217 confirmed by direct run). Out of scope per standing ruling: thesis-level debate content. + v16 loop repairs (3 agents, read-only, final tree): red-team G1 (genuine) — the v16 changelog described a 2.0.4-rejection disclosure Appendix J did not contain; repaired by adding the sender note to the what's-new paragraph. Red-team G2 (genuine) — v16's own edits re-staled two machine counts (the F11 sentence is itself a counted possession pattern): PA.1 ratio refreshed 118/130→119/130 (§8.9, Appendix I) and FW.1 line counts 8,127→8,117 (§0.5.3, §0.5.5). Devil's advocate 6/6 charges NOT GENUINE; evil auditor 8/8 checks PASS. 21/21 scripts green on the final tree; 22/22 listings byte-identical by block comparison (21 + ESP v2.1); 46 fences even.

- v15 (2026-10-11). Fifteenth draft (author-authorized, "build version fifteen"): + ChatGPT RT-05 (genuine code defect): P.4 now uses ONE explicitly defined running model (N_F=3) for headline and scale table — the silent n_f=1 default is gone; muddled "u,d,s,e,mu,tau active" comment corrected; model honestly labeled schematic one-loop, fixed n_f, thresholds ignored; regression assertion pins headline alpha(M_Z) to the table's alpha(M_Z). + ChatGPT RT-09 (genuine code defect): PA.1 routes color-specific claims to the SU(3)/color entry — "Quarks carry intrinsic color charge" no longer misroutes to the QED equation; documented priority resolves exactly the color/charge subsumption; any other multi-property input fails closed (AMBIGUOUS, no silent pick); 8-case routing regression battery (electric, color, flavor, magnetic moment, spin, mass + 2 ambiguity cases). + ChatGPT RT-17 (genuine editorial): §5 renumbered to clean order (old 5.5→5.3, 5.3→5.4, 5.4→5.5 in place); Appendix B renumbered (old B.8→B.7, B.7→B.8 in place); no live cross-references existed outside verbatim changelog history. + ChatGPT RT-04 (weak-genuine): kaon prose tightened at both sites — the K^0–K^0 MESON SYSTEM oscillates between flavor eigenstates; no quark changes flavor; CKM basis-dependence point unchanged. + NEW P.10 g−2 loop spectrum (scripts/P10_g2_loop_spectrum.py, 21st Appendix G listing): QED vertex-diagram counts per loop order 1→7→72→891→12672; the 1- and 2-loop counts are machine-DERIVED by combinatorial generation from QED vertex rules (QED 3-point vertices, fixed external legs, Furry even-vertex filter, amputated-1PI bridgeless filter) quotiented by brute-force canonical graph isomorphism — nothing about the answers hardcoded, assertions check 1 and 7; 72/891/12672 carried as cited-paper oracle (Kinoshita; Kinoshita–Lindquist; Aoyama–Hayakawa–Kinoshita–Nio) with full INPUT_PROVENANCE, explicitly not-derived. + RT-07 prose answer in §3.6 (honest narrowed form after the v15 loop caught the first draft's overclaim): the objection is half-right — each diagram IS evaluated by continuum loop integrals (§3.6(b); §11.6 admits the continuum upstream); what it cannot dismiss is the integer at the front — at every loop order the coefficient is a sum over N discrete diagrams (1, 7, 72, 891, 12,672; 1- and 2-loop machine-derived under the proper-vertex (1PI) convention, rest published counts); the count N is discrete and convention-indexed. Out of scope per author's ruling: ChatGPT's thesis-level debate content (RT-01/03/06/12, the steelman response) — not in this version. + v15 loop repairs (3 agents, read-only, final tree): RT-07 paragraph re-scoped (first draft denied the continuum beneath the diagrams, contradicting §3.6(b) and §11.6 — repaired to the narrowed form; same scoping applied to P.10's docstring/verdict); PA.1 fail-closed hole closed (color fast-path bypassed AMBIGUOUS on color+other inputs — priority now resolves only the color/charge subsumption); PA.1 divergence ratio refreshed 116/129→118/130 (§8.9, Appendix I) and FW.1 line counts 7,730→8,127 (§0.5.3, §0.5.5) after v15's own prose edits moved the live numbers. 21/21 scripts green on the final tree; 22/22 listings byte-identical by block comparison (21 + ESP v2.0.4); 46 fences even.
- v14 (2026-10-11). Fourteenth draft (author-authorized, "take any action you feel necessary"): + the 7 held v13 loop findings — abstract Whitehead 1929→1925 (Science and the Modern World; body already correct); FW.1 line counts updated to 7,730 (§0.5.3 and §0.5.5; the 1,931 and 3,864 figures were stale); PA.1 divergence ratio 79/82→116/129 (re-run; updated §8.9 and Appendix I prose, v8 changelog entry kept verbatim as history); H.4 C5 string split to §8.3's verdicts (Bell falsified only pre-existing local values §8.3b; axis-constituted reading GAP §8.3a); PA.1 spin badge reconciled to prose ("REFUTED by Bell, local scope" + split note); §11.6 "costs nothing" modality cleaned to match the Paper-12 deferral (no promise beyond derived counts); H.4 steelman answer smoothed (C6/C7 declared

as Paper 11's own additions; the shared-norms subset is where the gloss loses on the home team's rulebook). + Qwen VULN-A (genuine, HIGH): portable draft paths in G.1–G.4, H.3, FW.1, PA.1 — `Path(__file__).resolve().parent` + argv[1]/--draft override, Paper 11 F.49 idiom; all 7 exit 0 from a clean cwd; Appendix G prose notes the portable resolution. + Qwen VULN-C (weak-genuine): one-sentence denominator disambiguation at §8.1 (H.1: six property classes) and §8.5 (H.4: seven honesty criteria). + Qwen VULN-B recorded DEAD (no edit): P.7's 5-loop scope is stated in the script print, docstring INPUT_PROVENANCE, and §3.9 prose — the auditor worked from fragments. + Appendix I.4: Malament (1996, Perspectives on Quantum Reality, pp. 1–10 — corrected from the outlier pp. 35–136 record after the v14 loop pass) and Halvorson & Clifton (2002, Philosophy of Science 69(1):1–28) replace the dropped Myrvold attribution — cited for exactly what their no-go theorems prove; old I.4 → I.5. + Build-machine repair (red-team catch, same build): the v14 re-embed tool corrupted the FW1 and G4 listings (non-greedy fence regex stopped at backticks inside script strings, leaving a junk closing-fence line plus orphaned code as "prose" — FW.1 and G4 exited 1 until repaired); both listings re-embedded with line-anchored fence matching. 20/20 scripts green on the final tree (re-run after repair); 21/21 listings byte-identical by block comparison (20 + ESP v2.0.4); 44 fences even. Author's post-build rulings on the two held items (2026-10-11, delegated to Valkyrie): §8.9 prose now carries the PA.1 split note (§8.3b REFUTED / §8.3a GAP); §8.1/H.1 spin row keeps REFUTED, explicitly scoped to the possession claim (§8.3b) with the §8.3a GAP cross-reference so the axis-constituted reading is not absorbed.

- v13 (2026-10-09). Thirteenth draft (author-ordered, per-item rulings on all ten v10 loop findings): + §8.3 "The spin verdict, split" — H.2's spin chain split into (a) the axis-constituted reading (GAP: the paper's own structural point, which Bell never tested) vs (b) pre-existing local values (REFUTED by Bell/P.2); H2 script emits both verdicts distinctly (no REFUTED-priority collapse); §8 renumbered throughout (old 8.3→8.4→8.5→8.6→8.7→8.8→8.9). + Appendix J re-embedded at ESP v2.0.4 (byte-identical; 217-case conformance) with concise what's-new (tiered envelopes, DISAGREEMENT/CONFRONTATION, semantic_validity named-not-solved, fail-closed fixes). + Griffiths charge sentence downgraded to paraphrase (verbatim not located in 2nd ed.; §1.5 address withdrawn; PDG-tables half kept). + §11.6 capstone deferred to Paper 12 (microstate-counting rule + sampling-measure postulate named as Paper 12's work; footing stated, nothing promised). + Myrvold attribution dropped (unverifiable; no substitute named). + §8.5 reworded to match §0.5.5 (H.2 = honest record, not independent proof). + §12.2 states both Λ premises (strong labeled rhetoric; dilemma shown to survive the weaker one). + Appendix D v9/v10 entries reconstructed from the daily logs with an honest miss note and the never-again rule. + Protocol table "emergence"→"reproducing". + FW.1 "at every point" pattern + B2 mutant (rationale documented in-script). + Wallace direct EFT citations (Synthese 2006; SHPS-B 2011). + §3.9 reading-(d) caveat (billing narrowed to (a)–(c)). + H.4 steelman-then-answer on the stacked-deck objection. 20/20 scripts green on the final tree; 21/21 listings byte-identical (20 + ESP.1); 42 fences even. v13 loop pass (devil's advocate, evil auditor, red team — read-only, final tree): all 13 implementations verified as ruled; new genuine findings HELD for the author's ruling (abstract Whitehead year 1929 vs 1925; stale FW.1 line counts in §0.5.x; stale PA.1 79/82 ratio in §8.9; H4 script strings collapsing the spin split; PA.1 badge/prose scope mismatch; §11.6 "costs nothing" modality; H.4 answer/framing tension). Still held: Qwen's full critique not landed; Kimi dark; the six ESP v2.0.4 loop questions (separate).
- v12 (2026-10-09). Twelfth draft (author-ordered): + P.9 ternary/tether Bell formalization (P9_bell_ternary_tether.py, new Appendix G listing — 20 verification scripts, 20/20 byte-identical; exit 0, 4/4 checks): (1) projection-dependence of S across four handlings of 0 (1.90/1.90/2.69/1.94, spread 0.79 — verdict conditional on the projection; drop-zeros S=2.69>2 on a LOCAL model = detection loophole live); (2) machine-proved local ternary bound = 2.0 over all 81 deterministic assignments (honest null: ternary alone does not lift the bound); (3) deterministic non-separable tether reproducing $E(a,b)=-a\cdot b$, $S=2.83=2\sqrt{2}$; severed-tether mutant collapses to 2.00 (mutant repaired after loop caught a degenerate first version). + §3.2(e) P.9 integration: Bell narrowed to its honest scope throughout (RT-01: §1.3 "Ontology B won" → local models excluded, not ontological verdict; §3.2 Bell paragraph qualified to local models + tether/binary-qualification stated; H.2 spin label → "pre-existing local values"). + §3.3 bridge-labeling (RT-02: mass GAP derivation distinguished from the inherited Paper 8/11 constitution premise, labeled as inherited). + §6 logical-form repair (RT-03: "falsifiable in the strong sense" → refutable in the strong logical sense; two falsification routes distinguished — (i) conceptual boundary/proof-by-contradiction, unsatisfiable by definition, and (ii) the empirical H.2 derivation program, genuinely open). + P.2 scope-limitation statement (docstring + interpretation: binary-only, zeros→+1 by fiat, nulls unmodeled, separable subclass only; listing re-embedded byte-identical). Fixed stale v8 header stamp (Grok's genuine catch). Held, unpatched: the ten v10 loop findings; the

v9/v10 changelog gap; the H.2 spin-verdict split (third pass); ChatGPT's Q8 second-pass nits beyond RT-01–03. v12 loop pass (3 agents, read-only, final tree): 2 GENUINE — (a) ~18 unscoped "Bell falsifies/refutes pre-existence" sentences surviving on summary surfaces (tables, headings, §7 replies, Appendix B.2 absolute claim) after the RT-01 narrowing; FIXED to local scope throughout, §3.2 heading de-attributed; (b) §6 route (ii) advertised "genuinely open" for all six properties while the paper's own theorems close three — FIXED: route (ii) genuinely open for the three GAP properties only. 1 WEAK (auditor's FW1/G4 stale-embed charge) adjudicated NOT GENUINE — direct raw comparison shows both embeds byte-identical to their script files (the auditor compared against a wrong file). All other loop charges NOT GENUINE.

- v11 (2026-10-09). Eleventh draft: + Appendix J (ESP v2.0 — the unified agent-to-agent protocol, with ESP.1 engine listing embedded byte-identical; 61/61 conformance green, fuzz-tested). Protocol infrastructure, not a verification script — Appendix G's "nineteen verification scripts" unchanged. (Note: v9/v10 changelog entries not yet written — held for author's ruling per v10 loop pass.)
- v10 (2026-10-08). Tenth draft (friend's second review, implemented under the author's full authorization): + §1.3.5 cash-value; breathing-room closers after all six §3 audits; g−2 flagship (P.7 executable); §3.9 scale fingerprint; CKM/Jarlskog sharpening; Elitzur-as-category-error; mass in three versions (P.8 executable); §5.5 worked textbook promotion; §9.6 continuum subsection; §11.6 capstone justification with MC.1 narrowed ("reproducing", not "emerging"); F.7 elevated into §8.5. 19/19 scripts green on the final tree (FW1, G1–G4, H1–H4, MC1, P1–P8, PA1); listings byte-identical; 40 fences even; 272,065 bytes. v10 loop pass (devil's advocate, evil auditor, red team — read-only): 10 findings held for the author's ruling, nothing patched.
- v9 (2026-10-08). Ninth draft (friend's first expanded review — "Expanded Thoughts and What I Would Add", implemented under the author's full authorization): + §1.5 "Four readings of intrinsic" (targets reading (a), blocks the slide to (b)/(c)/(d)); + §12 "The EFT Trap" (C7 promoted from H.4 sub-bullet to its own section — the no-exit dilemma); + §9.5 worked Higgs case (continuum → manifold-indexed VEV → reification, step by step); + Appendix I (contemporary philosophy: OSR/Ladyman & French, Wallace/EFT, Ruetsche/gauge observables, Myrvold/QFT foundations — convergence plus what 11.5 adds); §6 falsification reframed as proof by contradiction; H.4 reframed honestly (held to Paper 11's standards, not neutral); FW.1 repositioned as methodological showpiece; §11 flagged as capstone in the §1 roadmap; all six §3(d) counterparts extended with the ledger's positive picture (critique:construction ratio 4:1 → 2:1). 17/17 scripts green on the final tree; listings byte-identical; 36 fences even.
- [Reconstruction note, v13.] The v9 and v10 entries above were missing from Appendix D until v13 — two full versions with no changelog record, caught by the v10 loop pass. Why it happened: the entries were staged from memory under parallel-collaboration load instead of written at build time from each build's own receipts, and the v10 loop's hold on "everything for the author's ruling" swept the ordinary version entries into the hold by mistake. They are reconstructed here from the daily logs (memory/2026-10-08.md, memory/2026-10-09.md) — quoted, not invented — and this note records the miss in the changelog itself, so the paper can never be called dishonest about its own history. Never-again rule now standing (AGENTS.md): every version build writes its changelog entry AT BUILD TIME from that build's own receipts; "changelog entry written" is a build gate.
- v8 (2026-10-08). Eighth draft (Qwen 3.8 contribution, tightened): + C6 (bookkeeping/ontology separation) and C7 (EFT trap) — H.4 now 7/7 vs 0/7; + Kochen-Specker in §3.2 spin audit (non-contextual assignments forbidden); + Elitzur-VEV nuance in §3.3 (substance reading killed, VEV not denied); + §7.8 ('shut up and calculate') and §7.9 ('just a reinterpretation'); + PA.1 gloss-to-equation divergence ratio (79 vs 82, mechanical scan). Physics tightened throughout; 26-parameter numerology excluded per author instruction.
- v7 (2026-10-08). Seventh draft: + §11 (Monte Carlo capstone: their version vs ours; MC.1 structural Monte Carlo — shell-count brute-force check + workload sampling + power-law fit exponent −1.9886; honest scope stated); + MC.1 executable (green).
- v6 (2026-10-08). Sixth draft: + planted mutants (H.2 chain validator + dishonest-Casimir mutant; FW.1 three-mutant battery + negative control — exposed and fixed 2 real firewall bugs; P.2 nonlocal-LHV mutant proving locality load-bearing); + §0.5.5 honesty disclosure (H-series encodes classifications; machine vs classified parts stated); + Casimir GAP chains in H.2.
- v5 (2026-10-08). Fifth draft (Gemini's contribution): + §3.8 (Casimir defense: Poincaré invariants classify, encounters read — metric/frame dependence, Pauli-Lubański, labels vs readings); + §10 (encounter-indexing

bridged to RQM, QBism, POVMs, AQFT); + Appendix H (three fortifications: asymptotic states, RG as encounter scale, Elitzur/Wilson loops); + P.6 executable (Casimir frames).

- v4 (2026-10-08). Fourth draft: + §0.5 epistemic architecture (badge definitions, L1–L5 dependency labels, FW.1 rules, script protocol, machine-checked definition); + Appendix G with all 15 scripts embedded byte-identical; + Appendix C figure plans fully presented (7 figures specified); G.4 fence-exclusion fix.
- v3 (2026-10-08). Third draft: + P-series executables (P.1 Stern-Gerlach, P.2 Bell-CHSH with LHV comparison, P.3 R-ratio, P.4 RG running, P.5 CKM basis — all run, all green); + FW.1 firewall (self-policing, green); + PA.1 parsing agent; + §9 (continuum license: continuous calculus as enabler of the intrinsic habit — habit, not lie).
- v2 (2026-10-08). Second draft: + H-series machine verification (§8): H.1 badge audit (6/6 SM claims fail), H.2 derivation attempt (0/6 derived, 3/6 refuted), H.3 prose/equation consistency (6/6 mismatch), H.4 honesty comparison (5/5 vs 0/5). All 8 scripts green. [v8: 7/7 vs 0/7 with C6/C7]
- v2 (2026-10-08). Second draft [continued]: §3 expanded to full equation breakdowns (four moves per property: textbook claim → equation breakdown → inference chain → Paper 11 Level A counterpart); Appendix B rewritten as extended technical audits (RG equation, Bell/CHSH, Higgs VEV, SU(3) gauge cancellation, CKM, g−2 loop expansion); new Appendix E (Paper 11 Level A claim map); audit summary table expanded with equation column.
- v1 (2026-10-07). First draft: analytical core (§§1, 3–6), historical dissent (§2)

with verified quotes and disclosed complications, four verification scripts (G.1–G.4) all green, full appendices, figure plans. Markdown + text working formats; PDF deferred pending red-team audits per author instruction.

APPENDIX E — PAPER 11 LEVEL A CLAIM MAP FOR 11.5

The proved — or declared — results from Paper 11 (v69) that power this critique. Each entry: the claim, its badge (with the [LEVEL A, author-authorized] subtype wherever the source's own registry records a declaration), its inheritance line per §0.5.6, and the precise role it plays in the audit.

E.1 RELATIONAL_ROLE_THEOREM (§3.1) [LEVEL A]

No configuration is intrinsically active or passive. Proved by F.39: one selector exhibits u>0 (active) at tick τ_1 and u=0 (passive) at tick τ_2.

Inheritance: Source: Paper 11 v69 §3.1 — badge carried at source: [LEVEL A] — validation: Appendix J registry row RELATIONAL_ROLE_THEOREM | A | §3.1 | §3.1 | F.39 — 11.5 reliance: the engine of the critique (§3.2 spin, §3.5 flavor).

Role in 11.5: The engine of the entire critique. Applied to spin (§3.2): the "spin-1/2" label is the capability; the value is the per-tick reading. Applied to flavor (§3.5): "strange" is the weak-encounter role label. The theorem is the native-ledger version of what Bell's theorem proves cannot be avoided: properties do not pre-exist encounters.

E.2 PORT_PARTITION_EXACTNESS (§4.3) [LEVEL A]

Ports partition exactly; at most one completed junction per port. Native a_k derivation (Kimi closure).

Inheritance: Source: Paper 11 v69 §4.3 — badge carried at source: [LEVEL A] — validation: Appendix J registry row PORT_PARTITION_EXACTNESS | A | §4.3 | §4.3 | F.32 + F.33 + F.34 + F.35 — 11.5 reliance: the charge audit (§3.1).

Role in 11.5: Powers the charge audit (§3.1). The coupling e(μ) is presented port geometry — values at boundary ports, read per-tick at scale μ. The "intrinsic charge" is the per-tick reading with the tick elided. The RG scale is the ledger's tick-index, made explicit.

E.3 TENSION_MEASURE_IDENTITY (§7.1) [LEVEL A]

Shear tension IS the unmatched-integer count τ_J — definitional, not derived.

Inheritance: Source: Paper 11 v69 §7.1 — badge carried at source: [LEVEL A] — validation: Appendix J registry row TENSION_MEASURE_IDENTITY | A | §7.1 | §7.1 | F.43 — 11.5 reliance: the spin-correlation / EPR audit (§4.1, row 8).

Role in 11.5: Powers the spin audit (§3.2). The spin "value" is the reading — definitional identity between the quantity and its determination. There is no gap between "the spin" and "the spin reading" for intrinsicality to hide in.

E.4 STRUCTURAL_INSULATION_THEOREM (§4.1) [LEVEL A]

The 27-state inventory is closed under the ledger; bookkeeping labels are not ontological commitments.

Inheritance: Source: Paper 11 v69 §4.1 — badge carried at source: [LEVEL A] — validation: Appendix J registry row STRUCTURAL_INSULATION_THEOREM | A | §4.1 | §4.1 | prose (§4.1), no machine check — 11.5 reliance: the color audit (§3.4).

Role in 11.5: Powers the color audit (§3.4). The color index is a bookkeeping label (gauge-dependent, cancels from the S-matrix). Structural insulation is the discipline: labels that work in calculations are not thereby possessions of particles.

E.5 ASPECT_AGGREGATION (§7.3) [LEVEL A, author-authorized]

Port contributions attributed to exactly one aspect per-tick — a declared bookkeeping rule, not a discovered fact.

Inheritance: Source: Paper 11 v69 §7.3 — badge carried at source: [LEVEL A, author-authorized] — validation: Appendix J registry row ASPECT_AGGREGATION

A	§7.3	§7.3	prose (§7.3) — no machine check; recorded as "aspect aggregation

(author-authorized definition)", ledger Lemma 2, declared 2026-10-05 — status in 11.5: declared axiom, never a proved fact — 11.5 reliance: the magnetic-moment audit (§3.6).

Stated falsifiers. The declaration fails — concretely, checkably — on either of: (1) a tick in the ledger's own records where a port's tracking-cost contribution is attributable to two aspects, or to none, with the declaration's rule-ii disambiguation (State-9 boundary ports carry 0) applied as stated; (2) a T-action that changes the attributed contributions of aspects owning neither of the two touched ports. The check runs against the declaration as declared, including its disambiguation clauses — the falsifiers are the declaration's contrapositive, not new claims.

Role in 11.5: Powers the magnetic-moment audit (§3.6). The 12,672-diagram loop sum is attributed to "the electron" by convention. Paper 11 declares the convention; the standard model performs it silently and calls the result "intrinsic." The honesty difference is the entire difference.

E.6 CAPABILITY_ACTUALITY_SEPARATION (§3.1) [LEVEL A]

Capability ("can play the role") vs. actuality (encounter-indexed realization).

Inheritance: Source: Paper 11 v69 §3.1 — badge carried at source: [LEVEL A] — validation: Appendix J registry row CAPABILITY_ACTUALITY_SEPARATION | A | §3.1 | §3.1 | F.39 (derived via the F.39 relationality witness) — 11.5 reliance: the flavor audit (§3.5) and the "always shows spin-1/2" reply (§7).

Role in 11.5: Powers the flavor audit (§3.5) and the general response to "but the electron always shows spin-1/2." The capability (2D representation, can present $\pm\hbar/2$) is structural and stable. The actual value exists only per-encounter. "Intrinsic" conflates the two — it takes the stability of the capability as evidence for the intrinsicality of the value. The separation dissolves the conflation.

E.7 SCALE_FIDELITY (§0.5.v.3) [LEVEL A: MACHINE / AUTHOR]

Universality holds at all scales (N-threshold sweep, F.56).

Inheritance: Source: Paper 11 v69 §0.5.v.3 — badge carried at source: [LEVEL A] on the machine-checked content — validation: Appendix J registry row SCALE_FIDELITY | A | §0.5.v.3 | §0.5.v.3 | F.56 (N-threshold sweep, 6N monotonicity, exactness composition) — disclosed limit: the "fidelity := extent × exactness" identification is author-authorized (2026-10-05), asserted not machine-proved; a stipulated label has no empirical falsifier, so none is invented — the falsifiers attach to the machine halves it labels: an N-threshold defect shape in native definition sources, a non-monotone 6N growth instance, or formal error at finite N (F.56's planted mutants reject exactly these shapes) —

11.5 reliance: "does the critique hold at high energy" (§3.1, App. B.1). Badge in 11.5: [LEVEL A: MACHINE / AUTHOR] — the F.56 content is the MACHINE half, the "fidelity := extent × exactness" identification the AUTHOR half (§0.5.1).

Role in 11.5: Answers "does the critique hold at high energy?" Yes — the encounter-indexing is scale-invariant. The running coupling (§3.1, App. B.1) is the standard model's own scale-dependence; Paper 11's ledger is faithful at every scale because it never posited scale-free intrinsicality to begin with.

E.8 MASS_AS_LEDGER (Paper 8 v2) [LEVEL A]

Mass is the ledger accounting of departure from c — the running cost of holding a tilt away from the photon baseline, not a possession of the configuration.

Inheritance: Source: Paper 8 v2 (Paper_8_Mass_as_Internal_Accounting_v2.pdf) — badge-at-source: [LEVEL A] author-authorized 2026-10-18 — validation: prose-section derivation as named in Paper 8 v2 Appendix D (no machine check, none claimed) — 11.5 reliance: the mass-as-ledger claim ("mass comes from encounters" — mass as ledger accounting of departure from c), the Level A counterpart of the mass audit (§3.3).

Role in 11.5: Powers the mass audit (§3.3) and the mass rows of the §3.7, §4.1, and §4.3 tables. The §3.3 GAP derivation applies this claim to mass (labeled as inherited, RT-02); the §4 rows cite it as the encounter-indexed counterpart to "intrinsic mass." The claim imports Paper 8's account rather than inventing one for the critique — what 11.5 adds is the badge discipline the inheritance line records. Disclosure: Paper 8 v2's Appendix D was written 2026-10-18 to supply the badge-at-source this line cites (D.4) — the authorization's role is part of the record, not behind it.

E.9 How the map is used

Every §3 subsection cites its Level A counterpart in move (d). The critique's logical structure is therefore:

1. Paper 11 proves (Level A) — and, for the aspect-aggregation bookkeeping rule, declares ([LEVEL A, author-authorized] with stated falsifiers, §0.5.6), and Paper 8 v2 derives the mass-as-ledger thesis ([LEVEL A] author-authorized at source, prose-section validation, Appendix E.8) — that properties are encounter-indexed in the native ledger.
2. The audit shows (§3, App. B): the standard formalism already encounter-indexes

every property — in its equations, not just in Paper 11's ledger.

3. Therefore the "intrinsic" idiom is not a rival ontology but a prose gloss

contradicted by the formalism it glosses.

The critique does not ask the reader to abandon the standard model for Paper 11. It asks the reader to read the standard model's own equations — where the encounter-indexing is already written, in the mathematics, waiting to be noticed.

APPENDIX F — GLOSSARY: "INTRINSIC" IN THE LITERATURE

A survey of how the word "intrinsic" is actually used in particle physics literature, exhibiting the gap between the word's assertoric force and its cash value. Each entry: the usage, the source type, and what the usage actually commits to.

F.1 The particle-table usage

"Electron: charge −e (intrinsic), spin 1/2 (intrinsic), mass 0.511 MeV (intrinsic)." Source type: textbooks, PDG listings, review articles. Cash value: the particle's row in the table has these entries. Nothing about encounter-independence is established by the table format — but the format implies it, because columns look like attributes and rows look like substances. This is the reification mechanism (§5) operating through typography.

F.2 The Lagrangian-parameter usage

"The intrinsic mass m_0 appears in the Dirac Lagrangian." Source type: QFT textbooks (Peskin & Schroeder Ch. 3). Cash value: m_0 is a parameter fitted to encounter data. Calling it "intrinsic" adds the suggestion that it exists independently of the fitting encounters — but the parameter has no value until fitted, and the fitting is encounters. The "intrinsic" is doing no work; "Lagrangian parameter m_0, fitted to $e^+e^- \to \mu^+\mu^-$ threshold data" says everything the physics says.

F.3 The quantum-number usage

"Quarks carry intrinsic color and flavor quantum numbers." Source type: Griffiths Ch. 1–2, Halzen & Martin. Cash value: the quark field transforms in the (3, 2) representation of SU(3)×SU(2). "Carry" is doing metaphorical work — the field doesn't carry anything; it transforms as a representation. The representation label is a fact about the gauge group, not a possession of the field. (Appendix B.4.)

F.4 The "as opposed to orbital" usage

"Intrinsic spin, as opposed to orbital angular momentum." Source type: ubiquitous — Griffiths §4.2.2 (2nd ed.), Sakurai, etc. Cash value: this is the one usage with legitimate contrastive content. "Intrinsic" here means "not arising from spatial motion" — it distinguishes S from L. But the contrast is then illicitly extended: "not orbital" slides into "possessed independently." The legitimate distinction (S vs. L) is used as a Trojan horse for the illegitimate one (encounter-indexed vs. intrinsic). The audit separates them: S is non-orbital and encounter-indexed (needs $\hat{n}$). Both true; only the first is usually stated.

F.5 The renormalization usage

"The intrinsic (bare) charge e_0 is infinite; the physical charge is finite." Source type: QFT renormalization discussions. Cash value: this usage inverts the ontology. The "intrinsic" (bare) value is infinite — meaningless. The "dressed" (encounter-constituted) value is finite — real. If "intrinsic" means "real," then the real charge is the dressed one, which is encounter-constituted by definition. The terminology calls the unreal (bare, infinite) "intrinsic" and the real (dressed, finite) "physical" — then textbooks go on calling the physical value "the intrinsic charge of the electron." The word has completely detached from any stable meaning.

F.6 The philosophical usage

"Electrons have intrinsic properties essentially; they could not lack them and remain electrons." Source type: philosophy of physics (Ladyman, French, structural realists debating). Cash value: modal claim about identity conditions, not a physical determination. Even if granted, it establishes only that if electrons exist then they are spin-1/2-presenting — which is compatible with encounter-indexing (the capability is structural; the value is per-encounter). Ontic structural realism (French, Ladyman) in fact denies intrinsic properties and keeps structure — converging with Paper 11 from the philosophy side. The audit notes this convergence but does not depend on it.

F.7 Summary: the word has no stable referent

Across six usage types, "intrinsic" means: (1) "in the table," (2) "Lagrangian parameter," (3) "representation label," (4) "not orbital," (5) "bare (infinite)," (6) "essential to identity." These are mutually incompatible — (5)'s "intrinsic" is infinite while (1)'s is 511 keV. A word with six incompatible referents, none of which is "possessed independently of encounters," is not a theoretical term. It is a verbal habit. The audit's recommendation: retire it, and say what is meant in each case — "Lagrangian parameter," "representation label," "non-orbital," "dressed coupling at scale μ." The physics loses nothing. The prose gains honesty.

APPENDIX G — SCRIPT LISTINGS

All twenty-one verification scripts, embedded byte-identical to the independently published files. Each script exits 0 on success. Scripts resolve the draft by a fallback chain (v19): explicit `argv[1]` (PA.1: `--draft`) → `$PAPER_MD` → `paper_11_5_draft.md` → `paper.md` → newest `paper_11_5_v<N>.md` next to the scripts; `$PAPER_MD` pointing at a nonexistent file falls through to the candidates, and every script prints the draft file it resolved. Explicit-path behavior is unchanged since v14 — a nonexistent path fails, never silently scans a stale default — and no machine-specific paths are embedded (Qwen VULN-A, fixed v14).

FW1 firewall

[Listing 1: FW1 firewall — see Script Appendix at the end of this document.]

G1 quote integrity

[Listing 2: G1 quote integrity — see Script Appendix at the end of this document.]

G2 contrast completeness

[Listing 3: G2 contrast completeness — see Script Appendix at the end of this document.]

G3 no strawman

[Listing 4: G3 no strawman — see Script Appendix at the end of this document.]

G4 terminology

[Listing 5: G4 terminology — see Script Appendix at the end of this document.]

H1 sm badge audit

[Listing 6: H1 sm badge audit — see Script Appendix at the end of this document.]

H2 intrinsic derivation attempt

[Listing 7: H2 intrinsic derivation attempt — see Script Appendix at the end of this document.]

H3 prose equation consistency

[Listing 8: H3 prose equation consistency — see Script Appendix at the end of this document.]

H4 honesty comparison

[Listing 9: H4 honesty comparison — see Script Appendix at the end of this document.]

MC1 shell montecarlo

[Listing 10: MC1 shell montecarlo — see Script Appendix at the end of this document.]

P1 stern gerlach

[Listing 11: P1 stern gerlach — see Script Appendix at the end of this document.]

P2 bell chsh

[Listing 12: P2 bell chsh — see Script Appendix at the end of this document.]

P3 r ratio

[Listing 13: P3 r ratio — see Script Appendix at the end of this document.]

P4 rg running

[Listing 14: P4 rg running — see Script Appendix at the end of this document.]

P5 ckm basis

[Listing 15: P5 ckm basis — see Script Appendix at the end of this document.]

P6 casimir frames

[Listing 16: P6 casimir frames — see Script Appendix at the end of this document.]

P7 g minus 2 flagship

[Listing 17: P7 g minus 2 flagship — see Script Appendix at the end of this document.]

P8 mass scheme

[Listing 18: P8 mass scheme — see Script Appendix at the end of this document.]

P9 bell ternary tether

[Listing 19: P9 bell ternary tether — see Script Appendix at the end of this document.]

P10 g2 loop spectrum

[Listing 20: P10 g2 loop spectrum — see Script Appendix at the end of this document.]

PA1 parsing agent

[Listing 21: PA1 parsing agent — see Script Appendix at the end of this document.]

APPENDIX H — THREE TECHNICAL FORTIFICATIONS

Three objections a theoretically sophisticated defender will raise — and the replies that close them. Each fortification takes a standard formalism the defense might cite and shows it encounter-indexes its own quantities.

H.1 The asymptotic state illusion in S-matrix theory

The defense: "S-matrix theory proves free particles exist: the asymptotic in/out states |p⟩_in, |p'⟩_out at t = ±∞ are isolated particles with intrinsic mass and momentum."

The reply: In/out states are formal mathematical limits (t → ±∞) that do not exist in any real laboratory. Every actual scattering experiment runs in finite time, in finite volume, with adiabatic switching functions or localized wavepackets that smear the idealization. The S-matrix element ⟨out|S|in⟩ is therefore always an effective transition amplitude conditioned on interaction boundaries — the preparation procedure (in) and the detection procedure (out) are encounters, and the "free particle" between them is a calculational interpolant, not an observed entity. No experiment has ever observed a particle at t = ±∞; the asymptotic limit is where the encounter-indexing is hidden (by pushing the encounters to infinity), not where it is absent. The "intrinsic mass" of the asymptotic state is the mass parameter that makes the interpolant work — a bookkeeping quantity, not a possessed property confirmed at infinity.

H.2 RG flow as encounter scale dependency (expanding P.4)

The defense: "The electron charge is −e, a constant of nature."

The reply: The renormalization group equation μ(∂g/∂μ) = β(g) proves the effective coupling g(μ) depends on the energy scale μ of the probe. P.4 integrates this numerically: α runs from 1/137 (at m_e) to 1/129.34 (at M_Z; schematic one-loop n_f=3). The "bare" charge — the scale-free, encounter-independent value — diverges (Landau pole) or is unobservable (it is not what any experiment measures). What experiments measure is always g(μ): the coupling at the scale of the encounter. The probe's momentum transfer $q^2 = -\mu^2$ is the encounter index, written into the field theory's own equations. To call −e "intrinsic" is to take g(μ_0) at one convenient scale, drop the subscript, and mistake the truncation for a discovery. The RG doesn't just allow encounter-indexing — it is encounter-indexing, in differential form.

H.3 Elitzur's theorem, Wilson loops, and relational gauge observables

The defense: "Quarks carry color charge — it's in the Lagrangian."

The reply: Elitzur's theorem proves that local gauge symmetries cannot be spontaneously broken — which means local gauge-variant quantities (like the "color" label carried by ψ(x)) cannot be physical observables. Only gauge-invariant operators correspond to observable quantities. The paradigmatic examples are Wilson loops W(C) = Tr P exp(ig∮_C A_μdx^μ): gauge-invariant, hence physical — but inherently nonlocal (they require a closed path C) and relational (the path's endpoints, or its closure, anchor it to other field structure). A Wilson loop does not report "the color here"; it reports a relation around a loop. Every physical gauge observable has this character: it is defined by an extended structure (loop, surface, boundary condition) that plays the role of the encounter. The "intrinsic color charge" of textbook prose is the gauge-variant ψ(x) promoted into an observable — exactly what Elitzur forbids. What survives Elitzur is relational by theorem, not by interpretation.

APPENDIX I — RELATION TO CONTEMPORARY PHILOSOPHY OF PHYSICS

The paper's thesis — that quantum "properties" are encounter-indexed, not intrinsic possessions — is not new to philosophy. A substantial literature defends versions of it at book length. This appendix states the convergences, the divergences, and what Paper 11.5 adds. The point is not to conscript allies but to position the paper: it extends a philosophical literature with a new audit format — six properties × four moves, published nulls, the spin-verdict split — rather than rediscovering a philosophical point in isolation.

I.1 Ontic Structural Realism (Ladyman & French)

Ladyman and French's Every Thing Must Go (2007) argues for ontic structural realism (OSR): there are no intrinsic properties and no individuals bearing them — relations all the way down. That is this paper's thesis in philosophical register. Convergence: the denial of intrinsic properties, the priority of relations over relata. Divergence: OSR is primarily a metaphysical thesis argued from the history of physics; Paper 11.5 is an equation-level audit — it shows, property by property, where the SM's own formalism encounter-indexes what its prose calls intrinsic. What we add: the six-property × four-move audit format (textbook claim → equation breakdown → inference chain → Paper 11 counterpart), with the nulls published and the hard cases split open. OSR says the metaphysics is wrong; we show the prose is wrong, property by property, with the overreach located sentence by sentence.

I.2 Wallace on EFTs and emergence

David Wallace's work on effective field theory — Wallace, D., "In defence of naivete: The conceptual status of Lagrangian quantum field theory," Synthese 151, 33–80 (2006); Wallace, D., "Taking particle physics seriously: A critique of the algebraic approach to quantum field theory," Stud. Hist. Phil. Sci. B 42, 116–125 (2011) — treats EFTs as the proper ontology of QFT — particles as patterns in the EFT, valid below a cutoff. Convergence: the scale-indexing of EFT parameters (§12's trap uses Wallace's own framework against the gloss). Divergence: Wallace is comfortable with emergent ontology; this paper is stricter — it demands prose/equation alignment at every level, emergent or not. What we add: the EFT trap (§12) as a dilemma, not just a framework: Wallace shows EFTs work; we show the EFT defense concedes the audit.

I.3 Ruetsche on gauge observables

Laura Ruetsche's Interpreting Quantum Theories covers the gauge-observable problem: which operators in a gauge theory correspond to physical quantities. Convergence: the Elitzur's-theorem material (§3.3, §3.4, Appendix H, H.3) — Ruetsche documents the same gap between gauge-variant formalism and physical content. What we add: the audit format — six properties, each with textbook claim, equation breakdown, inference chain, and badge verdict. Ruetsche analyzes the problem; we score it.

I.4 Particle-concept no-go results (Malament; Halvorson & Clifton)

Convergence: the relativistic particle concept itself has no-go results behind it — cited here for exactly what they prove, nothing more. David B. Malament, "In Defense of Dogma: Why There Cannot Be a Relativistic Quantum Mechanics of (Localizable) Particles," in Perspectives on Quantum Reality: Essays in Honor of Abner Shimony, ed. Rob Clifton (Dordrecht: Kluwer Academic Publishers, 1996), pp. 1–10, proves there is no relativistic quantum theory of localizable particles satisfying a small set of seemingly innocent conditions: the "particle" of the textbooks cannot be both relativistic and localizable. Hans Halvorson and Rob Clifton, "No Place for Particles in Relativistic Quantum Theories?," Philosophy of Science 69 (1): 1–28 (2002), close the main loopholes — three further no-go theorems covering unsharp localization and related evasions. What we add: these theorems constrain the particle concept; this paper's audit constrains the property concept — the intrinsic-property gloss fails even where the particle concept is granted arguendo. The two results are independent and point the same way.

I.5 The paper's position

We are aware of the literature, and it converges: OSR denies intrinsic properties, Wallace scale-indexes EFTs, Ruetsche problematizes gauge observables. What none of them provides is an audit — six properties × four moves (textbook claim → equation breakdown → inference chain → Paper 11 counterpart), with the nulls published (H.2's honest record) and the hard cases split open (the spin verdict, §8.3: GAP on the axis-constituted reading, REFUTED on the pre-existing local values reading). That format is the contribution — not machinery. The machine's role is narrower and stated plainly: the P-series computes real quantities (P.2's S=2.828, P.4's running α, P.10's loop spectrum) and MC.1's step 1 independently checks the shell count; the H-series, PA.1, and FW.1's voice judgments are the author's classifications, printed for inspection. The philosophy told us what to look for; the audit format shows where it is, in which sentence, on which reading.

I.6 Whitehead: the fallacy, operationalized

Alfred North Whitehead gave the error its name in 1925 — the fallacy of misplaced concreteness (Science and the Modern World): mistaking an abstraction for a concrete thing (§2.1). Convergence: the paper's indictment is Whitehead's fallacy with the instances filled in — the "intrinsic property" is the abstraction, the encounter-indexed reading the concrete process it was abstracted from. What we add: Whitehead diagnosed the fallacy; the audit operationalizes it — the six-property × four-move format turns misplaced concreteness into a checkable procedure: each property's textbook claim set beside its equation breakdown, the overreach located sentence by sentence (PA.1's divergence count, 20/55 under the (a)+Textual-evidence/(b) scoping, §8.9), the nulls published, the paper's own prose policed (FW.1). The fallacy becomes a procedure, not just a diagnosis.

I.7 Heisenberg: potentia actualized in interaction

Werner Heisenberg, Physics and Philosophy (1958): the quantum "thing" is potentia — potentialities actualized only in interaction (§2.2). Convergence: potentia actualized in interaction is encounter-indexing in philosophical register — Paper 11's relational roles are Heisenberg's actualization events with the encounter index made explicit. What we add: the audit shows the SM's own equations were already doing this — PA.1's 55 encounter-indices against 20 possession-claims (§8.9). The formalism was Heisenbergian all along; only the prose wasn't.

I.8 Cartwright: capacities without bearers

Nancy Cartwright, How the Laws of Physics Lie (1983): "The fundamental laws of physics do not describe true facts about reality" (A.7). Convergence: the paper agrees — the SM's six law-statements about "intrinsic properties" do not describe true facts; H.1 assigns every one of them NO BADGE. Divergence: Cartwright's later capacities realism (The Dappled World, 1999) re-ascribes capacities to point-bearers — but the audit dissolves the capacities one level further: "strange" is not a capacity of the quark but the weak-vertex role label (§3.5(d)); flavor is interaction-indexed by construction (P.5). What we add: the six-property audit as the test Cartwright never ran — capacities checked against equations, bearer by bearer, with the bearer losing every round.

I.9 van Fraassen: the honest divergence

Bas van Fraassen, The Scientific Image (1980): "Science aims to give us theories which are empirically adequate; and acceptance of a theory involves as belief only that it is empirically adequate" (A.8). Convergence: the paper's badge discipline is van Fraassen's modesty enforced mechanically — believe the equations where they are adequate (badged), withhold belief where the prose overreaches (NO BADGE). Divergence — stated honestly: van Fraassen's symmetric cut would cut against this paper's own ontology too (A.8 documents it as counter-witness): encounter-indexing is also a metaphysical posit, and the paper does not pretend otherwise. What we add: the cut is declared, not hidden — the paper states its own posit (Paper 11's relational ontology, inherited with lineage) and then holds itself to the same audit it runs on the SM (FW.1).

APPENDIX J — ESP v2.2: THE AGENT-TO-AGENT PROTOCOL

Paper 11.5's verification apparatus (H-series, P-series, MC.1, FW.1, PA.1) is executed by agents — and agents now plural: Dervis runs the same physics problems back-and-forth between Muse, Kimi, ChatGPT, and Grok so each model learns from the others' responses. That collaboration needs a shared talk language with the same epistemic discipline the papers demand of themselves. ESP v2.2 is that language: a single standard-library-only Python module defining how agents exchange claims without smuggling what the ledger forbids.

Lineage. Grok v4 (EpistemicSwarmEngine) → Gemini/Qwen ESP v1.0 → ChatGPT improvements → unified v2.0. The unification was forced: v4 and v1.0 could not interoperate (different envelope shapes, field names, status enums) — two "standards" that cannot talk to each other is the problem this solves.

What it enforces. Every message carries an epistemic context (register, badge, axiom-set hash, registry version) and an integrity block (content hash + envelope hash). Validation returns a badge naming exactly the checks that ran — structure, register/badge rules, registry match, determinism, falsification, hashes, lexical firewall, arithmetic discipline — plus a `not_established` list stating what validation does not prove (claim truth, sender identity, mathematical soundness). A VALIDATED badge with an empty checks list is treated as a bug, not a pass: the paper's honesty

discipline (§0.5.5, §8.6) applied to the machinery itself.

The lexical firewall is on by default. v1.0 shipped it off-by-default while still returning VALIDATED — the exact false confidence this paper's audit forbids. v2.2 runs it always, against the shipped constants: `DEFAULT_HARD_BANNED = {"infinity", "infinite", "infinitesimal", "derivative", "integral", "asymptotic", "path integral", "uv", "ir"}` and `DEFAULT_CONTEXT_BANNED = {"field", "gauge", "vacuum", "manifold", "metric", "curvature", "geodesic", "observer", "background", "lagrangian", "quantized", "propagator", "virtual", "renormalization", "limit"}`. Three F-45 facts, stated from the code: (a) "limit" was moved from the hard-banned set to the context-banned set — as a hard ban it rejected ordinary prose; as a context-banned term it is still barred from native prose but `[COMPARATIVE]/[HISTORICAL]/[SHADOW]/[RECONSTRUCTION]` marker blocks can exempt it for legitimate comparative use. (b) "uv"/"ir" trip the hard ban only as whole-word UPPERCASE ("UV"/"IR" are regime jargon); lowercase "uv"/"ir" in ordinary prose does not trip. (c) Correction, stated plainly: some v2.2 package doc text claimed marker blocks exempt hard-banned terms — FALSE. Hard-banned terms are exempt NOWHERE, in no block, on no tier; marker blocks exempt CONTEXT_BANNED terms only. The engine's rule is authoritative; the stale package text is superseded. Malformed blocks (unclosed, nested, mismatched) are violations, never silent fallthrough.

Capability-based execution policy. EXECUTABLE_PYTHON payloads are statically checked against a Policy-supplied banned-module list targeting exfiltration and process control (subprocess, socket, os, sys) and dynamic execution (eval, exec, compile, __import__). Numerics (`math` and friends) are allowed — Paper 11.5's own P.7 does `import math`; the ban targets capability, not computation. LEVEL_A float discipline holds (no floats outside print/format display), with the display exemption made non-gameable via AST parent-chain verification.

Registry honesty. A zero/placeholder axiom-set hash is refused at construction unless the caller passes `insecure_demo_registry=True` explicitly; demo validations print a loud warning on every call. Casual use cannot produce "validated" messages against a null registry.

Harmonized rules. STAGE_N requires LEVEL_A plus deterministic/seeded execution. LEVEL_A requires at least one falsification condition and cannot depend on level-B/C bridges. Registry version skew is bounded (default ±3). Outbound constructors refuse to emit messages that fail their own validation. Chunked transport (transfer_id, per-chunk and whole-text hashes) detects corruption, duplication, gaps, and mixed transfers.

Verification. The module ships a 267-case conformance battery (`esp_v2_conformance.py`, exits 0), each case asserting the right rejection — not just any failure — plus exception-path tests (random byte mutations of valid messages: the validator must never raise, only return REJECTED). The §8 run-record table is the current pin for this count and for the engine source hash — refresh the number here from that table at integration, never from memory.

What's new in v2.2 (concise). (Per `esp_v2.2_WHATS_NEW.txt`.) Three behavior changes. (1) A fifth provenance lineage, "bundle": "the claim reports outcomes of executing a bundle of scripts; the bundle manifest named in depends_on is the grounding" — the validator requires depends_on to name at least one bundle artifact (a file ending in .zip, case-insensitive), fail-closed otherwise, with the error naming the cause. This closes the gap ChatGPT's v18 bundle-execution envelope exposed: the most honest execution report in the program was REJECTED by v2.1's provenance validator ("script lineage requires script_id matching F.<digits>") because no lineage covered "I executed a bundle of scripts and here are the outcomes"; the re-cast envelope (BROADCAST, working tier, lineage "bundle") now VALIDATES. (2) script_id generalized from ^F\.\d+[A-Z]?$ to ^(F|P|H|G|MC|FW|PA)\.\d+[A-Z]?$ — the engine must cover the paper it ships with (Paper 11.5's P./H./G./MC./FW./PA. series, not just Paper 11's F. series). (3) Version gate: exact 2.2 match required, fail-closed, no negotiation — 2.1 envelopes are REJECTED with "unsupported protocol (expected ESP 2.2)"; re-stamp and resend. Conformance 267/267 re-run on the bumped engine (236 carried + 31 new). (Lineage: v2.1 was the documentation-correctness release — its version gate broke 2.0.4 envelopes; v2.0.4 split the envelope into two completeness tiers and added DISAGREEMENT/CONFRONTATION; v2.0.1 introduced two-tier hash honesty; v2.0.2 added the explicit tier signal and deep-copy validation; v2.0.3 closed the marker-grammar gap and extended the lexical scan to every free-text channel.)

Relation to the paper's thesis. ESP v2.2 is FW.1's discipline generalized from one paper to the conversation itself: the agents auditing the intrinsic-property gloss must not smuggle the gloss into their own exchanges. The protocol is the firewall, executable.

ESP.1 — esp_v2.py (listing)

Unified agent-to-agent protocol engine (stdlib only), embedded byte-identical below. Kept in this appendix rather than Appendix G: it is protocol infrastructure, not a verification script, and Appendix G's "twenty-one verification scripts" claim is left intact. Validates message envelopes: structural checks, register/badge rules, registry match, determinism, falsification requirements, bridge-level invariant, content + envelope hashes, lexical firewall (default-on), arithmetic discipline for EXECUTABLE_PYTHON payloads, chunked transport with corruption detection, v1.0 migration helper. 267-case conformance battery green; fuzz-tested (no unhandled exceptions on mutated inputs).

[Listing 22: ESP.1 — esp_v2.py (listing) — see Script Appendix at the end of this document.]

REFERENCES

Series (Dervis Kadunic, Departure From the Photon Baseline):

- Paper 8: Mass as the Internal Accounting of Departure from c. Zenodo 10.5281/zenodo.23456444 (v2, 2026-10-18 — Appendix D validation register appended; concept DOI 10.5281/zenodo.21238948).
- Paper 9.5: The Borrowed Thermometer. Zenodo 22035650.
- Paper 11: Simple States and Complex Configurations. Zenodo 23225391.

Historical:

- Whitehead, A.N. Science and the Modern World. Cambridge, 1925.
- Mach, E. The Analysis of Sensations. 1886.
- Bohr, N. "The Quantum Postulate and the Recent Development of Atomic Theory."

Como lecture, 1927. In Atomic Theory and the Description of Nature. Cambridge, 1934.

- Heisenberg, W. Physics and Philosophy. Harper, 1958.
- Bohm, D. Wholeness and the Implicate Order. Routledge, 1980.
- Bell, J.S. "Against 'Measurement'." Physics World, August 1990, pp. 33–40.
- Cartwright, N. How the Laws of Physics Lie. Oxford/Clarendon, 1983.
- van Fraassen, B. The Scientific Image. Oxford, 1980.

Textbooks (sources of the critiqued positions):

- Evans, R.D. The Atomic Nucleus. McGraw-Hill, 1955.
- Griffiths, D. Introduction to Elementary Particles. 1st ed. Wiley, 1987.
- Griffiths, D. Introduction to Elementary Particles. 2nd ed. Wiley, 2008.
- Peskin, M.E. & Schroeder, D.V. An Introduction to Quantum Field Theory.

Addison-Wesley, 1995.

- Halzen, F. & Martin, A.D. Quarks and Leptons. Wiley, 1984.
- Particle Data Group. Review of Particle Physics. (Current edition.)

Philosophy (Appendix I sources):

- Ladyman, J. & French, S. Every Thing Must Go. Oxford, 2007.
- Wallace, D. "In defence of naivete: The conceptual status of Lagrangian quantum field theory."

Synthese 151: 33–80, 2006.

- Wallace, D. "Taking particle physics seriously: A critique of the algebraic approach to

quantum field theory." Stud. Hist. Phil. Sci. B 42: 116–125, 2011.

- Cartwright, N. The Dappled World. 1999.
- Ruetsche, L. Interpreting Quantum Theories.

- Malament, D.B. "In Defense of Dogma: Why There Cannot Be a Relativistic Quantum Mechanics

of (Localizable) Particles." In Perspectives on Quantum Reality: Essays in Honor of Abner Shimony, ed. R. Clifton. Dordrecht: Kluwer Academic Publishers, 1996, pp. 1–10.

- Halvorson, H. & Clifton, R. "No Place for Particles in Relativistic Quantum Theories?"

Philosophy of Science 69(1): 1–28, 2002.

SCRIPT APPENDIX — VERIFICATION LISTINGS

All verification scripts referenced in this paper, in order of appearance. Each listing is reproduced in full from the published script file; lines longer than the print column are hard-wrapped with an indented continuation line. The byte-identical script files ship in the separate verification package.

Listing 1: FW1 firewall

```
#!/usr/bin/env python3
"""FW.1 — Paper 11.5 Firewall (cf. Paper 11 F.42).

Self-policing script: scans Paper 11.5's own text for language that would
violate its own critique. The paper attacks "intrinsic" as smuggled ontology —
it must not smuggle it back in. It identifies continuous calculus as the
enabler — it must not lean on continuum language uncritically.

Three sweep groups:

  Group A — "Intrinsic" usage audit.
    Every occurrence of "intrinsic" must be either:
    (1) in a quoted SM claim being critiqued, or
    (2) in the paper's own negative use ("not intrinsic", "intrinsic only in prose",
        "the intrinsic illusion", etc.), or
    (3) in Appendix F (the glossary, which surveys usages).
    Any other use — especially a positive ascription by the paper itself — is a breach.
    SENTENCE-PATTERN GATE (v24 disclosure): only a line matching `is`/`are` +
    "intrinsic"/"intrinsically" (modulo an adjacent negation) can breach Group A.
    Adjectival forms ("carries intrinsic X", "has intrinsic Y") never trigger the
    gate — they pass through it, not through any exemption. The six §3 (a)-lines
    are the audit's designated textbook-claim statements, so their silence is
    semantics-preserving: each quoted sentence is mention (the quoted-token test),
    and the one unquoted gloss ("the electron's intrinsic properties", §3.1(a))
    passes through the gate. Residual risk, stated: an unquoted adjectival
    ascription in the paper's own voice would pass the gate silently — zero live
    instances in v23 (verified: no unquoted carries/has/possesses + intrinsic in
    prose), human-audit territory.

  Group B — Continuum language audit.
    Flags continuum-enabling language: "at a point", "smooth", "continuous",
    "infinitesimal", "differentiable", "in the limit" — where used to ground
    a property ascription (not merely in historical exposition).
    The paper's thesis (§9): continuous calculus gives license to the intrinsic
    habit by picturing fields-with-values-at-points. Using that picture
    uncritically while critiquing its consequences is a breach.
    ONE INVENTORY ON ALL THREE SURFACES (v24 reconciliation): all six terms are
    implemented in code — "continuous" and "in the limit" were docstring-promised
    but code-missing, now implemented (the prose, this docstring, and the code
    agree). §9 consequence, stated: §9 uses "continuous" throughout in the
    paper's own analytic voice to NAME the enabler; the breach condition requires
    a property word on the same line (the grounding test), so naming the target
    does not breach. A future "continuous"+property line in the paper's own voice
    WILL breach — that is the firewall working, not a false positive.

  Group C — Possessive grammar audit.
    Flags "the electron's X", "the quark's Y", "its spin/charge/mass" where X/Y
    is one of the seven audited properties AND the possessive is the paper's own
    voice (not a quoted SM claim). The paper's §5 identifies possessive
    predication as reification step 3 — it must not perform it.
    Properties (v24): spin, charge, mass, color, flavor, magnetic moment, moment.
    "moment" was added v24 (triage: safe hardening) — "the electron's moment" is
    the same reification step with the adjective dropped.
    QUOTED-"intrinsic" EXEMPTION (v24 disclosure): a possessive hit is exempt when
    its line contains "intrinsic" in quotes anywhere on the line — mention-not-use
    (such a line discusses the idiom, not the paper's own ascribing voice).
    Residual risk, stated: a genuine ascription sharing a line with a quoted
    "intrinsic" would slip through — zero live instances in v23, human-audit
    territory.
Each breach prints a witness. Zero breaches = PASS.
Draft resolution (v19 fallback chain): argv[1] -&gt; $PAPER_MD -&gt; paper_11_5_draft.md -&gt; paper.md -&gt; newest paper_11_5_v&lt;
    N&gt;.md. The resolved draft file is printed on every run.

EXEMPTION BREADTH — design decision with rationale (v24 disclosure):
The firewall exempts MENTION of banned language from USE of it; the
exemptions below are deliberate and each has a stated reason. Breadth is
```

```
the known trade-off: a narrower exemption set risks false positives on the
paper's own critique (which must quote and rebut the SM idiom); a broader
set risks missing a real breach. This script chooses the middle: exemptions
are structural (where the text is, not what it says) and fail-closed where
a violation is still possible.

  (i) Quoted-context exemptions (Group A, Group C): lines that are blockquotes
      (leading "&gt;") or fall inside a "Textual evidence" span are the SM claim
      being critiqued, not the paper's own voice — policing them would forbid
      quoting the target. Group C adds a quoted-span test with delimiter-quote
      counting (word-internal apostrophes are not delimiters; the mutant C1
      case pins this). Group A's quoted-token test (odd quote count before the
      match) applies only to the current line.
  (ii) Critical-window token list (Group A): a ±2-line window around an
       "intrinsic" hit containing critical tokens ("not intrinsic", "refut",
       "smuggl", "versus", ...) exempts the hit as negative/critical use.
       Rationale: the paper's thesis REQUIRES negative uses ("not intrinsic",
       "intrinsic only in prose"); requiring exact "not intrinsic" phrasing
       would freeze the prose. The window is ±2 lines because a rebuttal's
       negation can sit on a neighboring line in markdown (line-wrapped
       sentences); a wider window would let distant negation wash a positive
       ascription. The residual risk — a genuinely positive ascription
       adjacent to critique prose — is human-audit territory, stated here
       rather than hidden.
  (iii) Group B window sizes: the history exclusion looks back 30 lines for
       "2.7"/"historical arc" (a subsection span, not a single line); the
       Appendix B exclusion looks back 50 lines (appendix context); the
       firewall-doc exclusion looks back 10 lines (§8.8 discusses the firewall
       itself). The changelog exemption is the narrowest: a line is exempt
       ONLY if it is a changelog entry ("- vNN (date)") inside the Appendix D
       span AND the matched pattern is quoted on that line — an unquoted
       ascription in a changelog entry stays caught (fail-closed). Window
       sizes are heuristic and recorded here so a reader can see the floor.
  (iv) Sentence-pattern gate (Group A): only `is`/`are` + "intrinsic" can
       breach — adjectival forms pass through the gate, not through an
       exemption (see Group A above). Disclosed, with the residual risk stated.
  (v) Quoted-"intrinsic" exemption (Group C): a possessive hit is exempt when
       its line contains "intrinsic" in quotes anywhere on the line (see Group C
       above). Disclosed, with the residual risk stated.
"""
import re
import sys
from pathlib import Path

HERE = Path(__file__).resolve().parent


def _resolve_draft(here):
    """Fallback chain: argv[1] -&gt; $PAPER_MD -&gt; candidate filenames."""
    import os, re
    if len(sys.argv) &gt; 1:
        return Path(sys.argv[1])
    env = os.environ.get("PAPER_MD")
    if env and Path(env).is_file():
        return Path(env)
    cands = [here.parent / "paper_11_5_draft.md",
             here.parent / "paper.md"]
    def _vkey(p):
        m = re.search(r"v(\d+)\.md$", p.name)
        return int(m.group(1)) if m else -1
    cands += sorted(here.parent.glob("paper_11_5_v*.md"), key=_vkey, reverse=True)
    for c in cands:
        if c.is_file():
            return c
    raise FileNotFoundError(
        "no paper draft found; tried argv[1], $PAPER_MD, and: "
        + ", ".join(str(c) for c in cands))


# Portable draft resolution (v14 hardening; v19 fallback chain):
# argv[1] -&gt; $PAPER_MD -&gt; paper_11_5_draft.md -&gt; paper.md -&gt;
# newest paper_11_5_v&lt;N&gt;.md. $PAPER_MD at a nonexistent file falls through;
# argv[1] is honored verbatim (unchanged pre-v19 behavior, including
# fail-on-nonexistent input). The helper is inlined: scripts stay
# standalone, no shared imports.
DRAFT = _resolve_draft(HERE)
text = open(DRAFT, encoding="utf-8").read()
lines = text.split("\n")

breaches = []
```

```
def is_quoted_sm_claim(line, idx, lines):
    """Check if this line is part of a blockquote or textual-evidence section."""
    if line.strip().startswith("&gt;"):
        return True
    for j in range(max(0, idx-10), idx):
        if "Textual evidence" in lines[j]:
            return True
    return False


def is_glossary(line, idx, lines):
    """Check if in Appendix F."""
    for j in range(max(0, idx-50), idx):
        if "APPENDIX F" in lines[j]:
            return True
    return False


def scan_groupA(lines):
    """Group A: no positive 'intrinsic' ascription in the paper's own voice."""
    breaches = []
    for i, line in enumerate(lines):
        for m in re.finditer(r"\bintrinsic(ally)?\b", line, re.I):
            before = line[:m.start()]
            if before.count('"') % 2 == 1:
                continue
            if is_quoted_sm_claim(line, i, lines):
                continue
            if is_glossary(line, i, lines):
                continue
            window = " ".join(lines[max(0,i-2):i+3])
            critical = ["not intrinsic", "no intrinsic", "never intrinsic", "not intrinsically",
                        "intrinsic only in prose", "intrinsic illusion", "against",
                        "critique", "refut", "falsif", "smuggl", "reifi", "fallacy",
                        "audit", "denies", "deny", "reject", "contradict", "versus",
                        "vs\\.", "comparison", "contrast", "in name only"]
            if any(re.search(p, window, re.I) for p in critical):
                continue
            if "Ontology A" in window or "intrinsic)" in line[:50]:
                continue
            # SENTENCE-PATTERN GATE (v24 disclosure): only `is`/`are` +
            # "intrinsic" can breach. Adjectival forms ("carries intrinsic X")
            # pass through this gate, not through any exemption — the six §3
            # (a)-lines are the audit's designated textbook-claim statements,
            # so their silence is semantics-preserving. Documented in the
            # docstring and §0.5.3; diagnostic mutant A2 pins the boundary.
            sent = line.strip()
            if re.search(r"\b(is|are)\s+(intrinsic|intrinsically)\b", sent, re.I):
                if not re.search(r"\b(not|no|never|n't)\b.{0,30}\b(is|are)\s+(intrinsic|intrinsically)\b", sent, re.I)
    :
                    breaches.append(f"A intrinsic-assertion [{i+1}]: {sent[:100]}")
    return breaches


def scan_groupB(lines):
    """Group B: no continuum language grounding property ascriptions."""
    breaches = []
    continuum_terms = [
        (r"\bat a point\b", "point-localization"),
        # v13: the v10 loop found the orthographic variant "at every point"
        # slipped the "at a point" pattern. The firewall is a floor, not a
        # ceiling — variants get added as they are found, and each addition
        # is recorded so the reader sees the floor being raised.
        (r"\bat every point\b", "point-localization (orthographic variant)"),
        (r"\bsmooth\b", "smoothness assumption"),
        # v24 reconciliation: "continuous" and "in the limit" were
        # docstring-promised but code-missing. All three surfaces (prose §0.5.3,
        # docstring, code) now carry one inventory. "in the limit" has zero
        # live instances in v23 prose; "continuous" is §9's thesis vocabulary
        # (naming the enabler) — the property-co-occurrence requirement below is
        # what keeps §9's naming-of-the-target from breaching.
        (r"\bcontinuous\b", "continuum-ascription"),
        (r"\binfinitesimal", "infinitesimal"),
        (r"\bdifferentiable\b", "differentiability"),
        (r"\bin the limit\b", "limit-talk"),
    ]
    for i, line in enumerate(lines):
        in_history = any("2.7" in lines[j] or "historical arc" in lines[j].lower()
                         for j in range(max(0, i-30), i))
        in_appB = any("APPENDIX B" in lines[j] for j in range(max(0, i-50), i))
```

```
        in_fwdoc = any("8.8" in lines[j] or "firewall" in lines[j].lower()
                       for j in range(max(0, i-10), i))
        # v22: Appendix D changelog entries quote the firewall's own patterns
        # to record their addition (mention-not-use; the v21 false positive
        # on the v13 entry). Narrow per red-team G1 + DA charge: a line is
        # exempt ONLY if it is a changelog entry ('- vNN (date)') inside the
        # Appendix D span AND the matched pattern is quoted on it — an
        # unquoted ascription stays caught (fail-closed). Bare "changelog"
        # mentions (including this script's own comments) never trigger.
        _entry = any(re.match(r"\s*-\s+v\d+\s*\(", lines[j])
                     for j in range(max(0, i-30), i))
        _in_d = any("## APPENDIX D" in lines[j] for j in range(max(0, i-60), i))
        for pat, label in continuum_terms:
            if not re.search(pat, line, re.I):
                continue
            _quoted = bool(re.search(r"""["'][^"'\n]*""" + pat + r"""[^"'\n]*["']""",
                                     line, re.I))
            if in_history or in_appB or in_fwdoc or (_entry and _in_d and _quoted):
                continue
            if re.search(r"\b(spin|charge|mass|color|flavor|moment|property|properties)\b",
                         line, re.I):
                breaches.append(f"B continuum [{i+1}] ({label}): {line.strip()[:100]}")
    return breaches


def scan_groupC(lines):
    """Group C: no possessive reification in the paper's own voice."""
    breaches = []
    # v24: "moment" added (triage: safe hardening) — "the electron's moment" is
    # the same reification step with the adjective dropped. "magnetic moment"
    # keeps its own entry; the possessive+property shape means the two never
    # double-count the same span ("the electron's magnetic moment" matches only
    # the longer entry — after the possessive comes "magnetic", not "moment").
    properties = ["spin", "charge", "mass", "color", "flavor", "magnetic moment", "moment"]
    for i, line in enumerate(lines):
        if is_quoted_sm_claim(line, i, lines):
            continue
        for prop in properties:
            m = re.search(rf"\b(the electron's|the quark's|its)\s+({prop})\b", line, re.I)
            if m:
                # Exempt when the phrase is MENTIONED (quoted) rather than USED.
                # Two tests: (a) directly wrapped in a quote char; (b) inside a
                # quoted span (delimiter quotes only — word-internal apostrophes
                # like Paper's/electron's are not delimiters; mutant C1 caught
                # the old bug of counting them).
                before = line[:m.start()]
                stripped = re.sub(r"\w'\w", "", before)
                delim_before = stripped.count('"') + stripped.count("'")
                wrapped = before.rstrip().endswith(('"', "'"))
                in_quotes = wrapped or (delim_before % 2 == 1)
                # v24 disclosure (docstring + §0.5.3): the intrinsic_quoted
                # exemption — any possessive hit is exempt when "intrinsic"
                # appears in quotes anywhere on the line (mention-not-use: the
                # line discusses the idiom). Residual risk, stated: a genuine
                # ascription sharing a line with a quoted "intrinsic" would
                # slip through — zero live instances in v23, human-audit
                # territory.
                intrinsic_quoted = bool(re.search(r"""['"]intrinsic['"]""", line, re.I))
                if not (in_quotes or intrinsic_quoted):
                    breaches.append(f"C possessive [{i+1}]: {line.strip()[:100]}")
    return breaches

# --- Refactored: use the scan functions for the real paper ---
# Exclude fenced code blocks (Appendix G listings): the firewall polices the
# paper's prose voice, not embedded code (including its own mutant test data).
prose_lines = []
_in_fence = False
for _ln in lines:
    if _ln.strip().startswith("```"):
        _in_fence = not _in_fence
        continue
    if not _in_fence:
        prose_lines.append(_ln)
breaches = scan_groupA(prose_lines) + scan_groupB(prose_lines) + scan_groupC(prose_lines)


def mutant_battery():
    """PLANTED MUTANTS: genuine spec violations the firewall must catch.

    Each mutant is a real violation of the paper's own discipline —
```

```
    the kind of slip a tired author makes. Each must be REJECTED
    (caught) with a printed witness. Plus one negative control
    (legitimate critical prose) that must NOT be flagged.
    DIAGNOSTIC mutants document a disclosed design boundary: they pass BY
    DESIGN and are labeled diagnostic — never printed as REJECTED, never
    counted among rejections, and never allowed to flip all_ok.
    Returns True iff all must-catch mutants caught, diagnostics behave as
    documented, and control clean.
    """
    print("\n" + "=" * 70)
    print("PLANTED MUTANT BATTERY")
    print("=" * 70)

    mutants = [
        ("A1", ["The electron is intrinsically charged, independent of any encounter."],
         scan_groupA, "positive intrinsic ascription in assertoric voice"),
        ("B1", ["Spin is a smooth property at a point in the electron field."],
         scan_groupB, "continuum language grounding a property"),
        ("B2", ["The charge is defined at every point of the field."],
         scan_groupB, "orthographic variant 'at every point' (v10 loop gap, fixed v13)"),
        ("B3", ["The continuum picture treats charge as a continuous property of the field."],
         scan_groupB, "'continuous' grounding a property ascription "
         "(v24: docstring-promised term, now implemented)"),
        ("C1", ["The quark's color determines how it scatters."],
         scan_groupC, "possessive reification in own voice"),
        ("C2", ["The electron's moment is measured to ten decimals."],
         scan_groupC, "possessive + 'moment' "
         "(v24: 'moment' added to the audited properties)"),
    ]
    diagnostics = [
        ("A2", ["The electron carries intrinsic charge \u2212e."],
         scan_groupA, "adjectival 'carries intrinsic X' — passes the "
         "sentence-pattern gate BY DESIGN (the gate needs is/are + intrinsic); "
         "this is the six §3 (a)-lines' designated shape"),
    ]
    all_ok = True
    for mid, doc, scanner, desc in mutants:
        hits = scanner(doc)
        if hits:
            print(f"  Mutant {mid} REJECTED (caught): {desc}")
            print(f"    Witness: {hits[0]}")
        else:
            print(f"  Mutant {mid} SURVIVED — firewall blind to: {desc}. FAIL.")
            all_ok = False
    for mid, doc, scanner, desc in diagnostics:
        hits = scanner(doc)
        if hits:
            print(f"  Diagnostic {mid} FLAGGED — the disclosed gate boundary moved. FAIL: {hits[0]}")
            all_ok = False
        else:
            print(f"  Diagnostic {mid} survived BY DESIGN (disclosed limitation): {desc}")
    # Negative control: legitimate critical prose must NOT be flagged
    control = ["The 'intrinsic' reading is refuted by Bell; no intrinsic property survives the audit."]
    hits = scan_groupA(control) + scan_groupB(control) + scan_groupC(control)
    if not hits:
        print("  Negative control CLEAN (critical prose not flagged).")
    else:
        print(f"  Negative control FLAGGED — false positive. FAIL: {hits[0]}")
        all_ok = False

    return all_ok


print("=" * 70)
print("FW.1 — PAPER 11.5 FIREWALL")
print("=" * 70)
print(f"Draft: {DRAFT}")
print(f"\nScanned {len(lines)} lines.")
if breaches:
    print(f"\nBREACHES: {len(breaches)}")
    for b in breaches:
        print(f"  - {b}")
    sys.exit(1)
else:
    print("\nFW.1 PASS: no firewall breaches.")
    print("  The paper does not smuggle 'intrinsic' in its own voice,")
    print("  does not lean on continuum language for property ascriptions,")
    print("  and does not perform possessive reification.")

if not mutant_battery():
```

```
    print("\nFW.1 MUTANT BATTERY FAILED.")
    sys.exit(1)
print("\nFW.1 COMPLETE: paper clean, all mutants caught, control clean.")
sys.exit(0)
```

Listing 2: G1 quote integrity

```
#!/usr/bin/env python3
"""G.1 — Quote integrity verifier for Paper 11.5.

Checks: every subsection of §2 that contains blockquotes also contains at least
one attribution line ("&gt; —" with work and year). Multiple quotes may share one
attribution from the same work — the gate is coverage, not 1:1 pairing.
Draft resolution (v19 fallback chain): argv[1] -&gt; $PAPER_MD -&gt; paper_11_5_draft.md -&gt; paper.md -&gt; newest paper_11_5_v&lt;
    N&gt;.md. The resolved draft file is printed on every run.
"""
import re
import sys
from pathlib import Path

HERE = Path(__file__).resolve().parent


def _resolve_draft(here):
    """Fallback chain: argv[1] -&gt; $PAPER_MD -&gt; candidate filenames."""
    import os, re
    if len(sys.argv) &gt; 1:
        return Path(sys.argv[1])
    env = os.environ.get("PAPER_MD")
    if env and Path(env).is_file():
        return Path(env)
    cands = [here.parent / "paper_11_5_draft.md",
             here.parent / "paper.md"]
    def _vkey(p):
        m = re.search(r"v(\d+)\.md$", p.name)
        return int(m.group(1)) if m else -1
    cands += sorted(here.parent.glob("paper_11_5_v*.md"), key=_vkey, reverse=True)
    for c in cands:
        if c.is_file():
            return c
    raise FileNotFoundError(
        "no paper draft found; tried argv[1], $PAPER_MD, and: "
        + ", ".join(str(c) for c in cands))


# Portable draft resolution (v14 hardening; v19 fallback chain):
# argv[1] -&gt; $PAPER_MD -&gt; paper_11_5_draft.md -&gt; paper.md -&gt;
# newest paper_11_5_v&lt;N&gt;.md. $PAPER_MD at a nonexistent file falls through;
# argv[1] is honored verbatim (unchanged pre-v19 behavior, including
# fail-on-nonexistent input). The helper is inlined: scripts stay
# standalone, no shared imports.
DRAFT = _resolve_draft(HERE)
text = open(DRAFT, encoding="utf-8").read()

s2_start = text.find("## 2   HISTORICAL DISSENT")
s2_end = text.find("## 3  ", s2_start)
s2 = text[s2_start:s2_end]

# Split into subsections
subs = re.split(r"(### 2\.\d+)", s2)
issues = []
total_quotes = 0
for i in range(1, len(subs), 2):
    header = subs[i]
    body = subs[i+1] if i+1 &lt; len(subs) else ""
    quotes = len(re.findall(r"^&gt; [^—]", body, re.M))
    # Attribution can be: "&gt; — *Work* (year)" line OR "Author, *Work* (year):" in subsection intro
    attrs = re.findall(r"^&gt; — .+\(\d{4}\)", body, re.M)
    header_attrs = re.findall(r"\*[^*]{5,}\* \(\d{4}\)", body)
    total_attrs = len(attrs) + len(header_attrs)
    total_quotes += quotes
    if quotes &gt; 0 and total_attrs == 0:
        issues.append(f"{header.strip()}: {quotes} quotes but no attribution")
    for a in attrs:
        if not re.search(r"\*", a):
            issues.append(f"{header.strip()}: attribution not naming a work: {a[:60]}")

print(f"Draft: {DRAFT}")
print(f"Quote lines in §2: {total_quotes}")
```

```
if issues:
    print("ISSUES:")
    for iss in issues:
        print(f"  - {iss}")
    sys.exit(1)
print(f"G.1 PASS: all quoted subsections carry sourced attributions.")
```

Listing 3: G2 contrast completeness

```
#!/usr/bin/env python3
"""G.2 — Contrast table completeness verifier for Paper 11.5.

Checks: every Standard Model intrinsic-property claim in the §4 contrast table
is mapped to exactly one Paper 11 result and carries exactly one verdict.
No orphan claims, no orphan results, no missing verdicts.
A count assertion (v24) requires that the loose row pattern (any "| N |" row)
and the strict 7-cell row regex find the same number of rows — the checks
below run over the strict set, and a shape drift between the two would
silently truncate the checked set, so a mismatch fails the run.
Draft resolution (v19 fallback chain): argv[1] -&gt; $PAPER_MD -&gt; paper_11_5_draft.md -&gt; paper.md -&gt; newest paper_11_5_v&lt;
    N&gt;.md. The resolved draft file is printed on every run.
"""
import re
import sys
from pathlib import Path

HERE = Path(__file__).resolve().parent


def _resolve_draft(here):
    """Fallback chain: argv[1] -&gt; $PAPER_MD -&gt; candidate filenames."""
    import os, re
    if len(sys.argv) &gt; 1:
        return Path(sys.argv[1])
    env = os.environ.get("PAPER_MD")
    if env and Path(env).is_file():
        return Path(env)
    cands = [here.parent / "paper_11_5_draft.md",
             here.parent / "paper.md"]
    def _vkey(p):
        m = re.search(r"v(\d+)\.md$", p.name)
        return int(m.group(1)) if m else -1
    cands += sorted(here.parent.glob("paper_11_5_v*.md"), key=_vkey, reverse=True)
    for c in cands:
        if c.is_file():
            return c
    raise FileNotFoundError(
        "no paper draft found; tried argv[1], $PAPER_MD, and: "
        + ", ".join(str(c) for c in cands))


# Portable draft resolution (v14 hardening; v19 fallback chain):
# argv[1] -&gt; $PAPER_MD -&gt; paper_11_5_draft.md -&gt; paper.md -&gt;
# newest paper_11_5_v&lt;N&gt;.md. $PAPER_MD at a nonexistent file falls through;
# argv[1] is honored verbatim (unchanged pre-v19 behavior, including
# fail-on-nonexistent input). The helper is inlined: scripts stay
# standalone, no shared imports.
DRAFT = _resolve_draft(HERE)
text = open(DRAFT, encoding="utf-8").read()

# Extract the §4 contrast table rows
table_start = text.find("## 4   SHARP CONTRAST")
table_end = text.find("## 5  ", table_start)
section = text[table_start:table_end]

rows = re.findall(r"^\| (\d+) \|", section, re.M)
strict_rows = re.findall(
    r"^\| (\d+) \| ([^|]+) \| ([^|]+) \| ([^|]+) \| ([^|]+) \| ([^|]+) \| ([^|]+) \|",
    section, re.M)
print(f"Draft: {DRAFT}")
print(f"Contrast table rows: {len(rows)} (loose pattern)")
print(f"Strict 7-cell rows parsed: {len(strict_rows)}")
# v24 (F-29): a row counted by the loose pattern must parse under the strict
# pattern — otherwise the completeness claims below would be made over a
# silently truncated row set.
if len(strict_rows) != len(rows):
    print(f"G.2 FAIL: {len(rows)} rows found by loose pattern but only "
          f"{len(strict_rows)} parsed by the strict 7-cell regex — "
```

```
          "row-shape drift; completeness checks not run.")
    sys.exit(1)

# Each row must have 5 cells: #, Phenomenon, Standard derived, Standard inferred, P11 derived, Verdict
# (v2 table has 6 columns)
issues = []
for num, phenom, std_der, std_inf, p11, verdict in strict_rows:
    if not phenom.strip():
        issues.append(f"Row {num}: empty phenomenon")
    if not std_der.strip():
        issues.append(f"Row {num}: empty standard-derived")
    if not std_inf.strip():
        issues.append(f"Row {num}: empty standard-inferred")
    if not p11.strip():
        issues.append(f"Row {num}: empty P11 result")
    # Verdict must start with a bold controlled term
    vm = re.search(r"\*\*(.+?)\.\*\*", verdict)
    if not vm:
        issues.append(f"Row {num}: verdict lacks bold term: {verdict[:60]}...")
    else:
        term = vm.group(1).strip()
        allowed = ["Category mistake", "Intrinsic only in prose", "Reified bookkeeping",
                   "Reified arithmetic", "Self-refuting", "Untestable assertion",
                   "Precision misattributed", "Scale amnesia", "Gloss falsified"]
        if term not in allowed:
            issues.append(f"Row {num}: verdict term '{term}' not in controlled vocabulary")

# Check: every property in §3 audit appears in §4
audit_props = ["charge", "spin", "mass", "color", "flavor", "magnetic moment"]
section_lower = section.lower()
for prop in audit_props:
    if prop not in section_lower:
        issues.append(f"§3 property '{prop}' missing from §4 contrast table")

if issues:
    print("ISSUES:")
    for i in issues:
        print(f"  - {i}")
    sys.exit(1)
print("G.2 PASS: contrast table complete, all verdicts controlled, all §3 properties mapped.")
```

Listing 4: G3 no strawman

```
#!/usr/bin/env python3
"""G.3 — No-strawman audit for Paper 11.5.

Checks: every Standard Model position critiqued in §3 is attributed to an actual
source (textbook/paper). The audit fails if a critiqued claim has no citation —
that would be attacking a position nobody holds.
Scoping (v24): the attribution search covers ONLY the (a) textbook-statement
block (the claim plus its Textual evidence), not the whole subsection body.
Searching (b)–(d) would let a subsection pass on a name that appears only in
the paper's own rebuttal voice (e.g. a cited refutation), which is not an
attribution of the SM position being critiqued.
Draft resolution (v19 fallback chain): argv[1] -&gt; $PAPER_MD -&gt; paper_11_5_draft.md -&gt; paper.md -&gt; newest paper_11_5_v&lt;
    N&gt;.md. The resolved draft file is printed on every run.
"""
import re
import sys
from pathlib import Path

HERE = Path(__file__).resolve().parent


def _resolve_draft(here):
    """Fallback chain: argv[1] -&gt; $PAPER_MD -&gt; candidate filenames."""
    import os, re
    if len(sys.argv) &gt; 1:
        return Path(sys.argv[1])
    env = os.environ.get("PAPER_MD")
    if env and Path(env).is_file():
        return Path(env)
    cands = [here.parent / "paper_11_5_draft.md",
             here.parent / "paper.md"]
    def _vkey(p):
        m = re.search(r"v(\d+)\.md$", p.name)
        return int(m.group(1)) if m else -1
    cands += sorted(here.parent.glob("paper_11_5_v*.md"), key=_vkey, reverse=True)
    for c in cands:
```

```
        if c.is_file():
            return c
    raise FileNotFoundError(
        "no paper draft found; tried argv[1], $PAPER_MD, and: "
        + ", ".join(str(c) for c in cands))


# Portable draft resolution (v14 hardening; v19 fallback chain):
# argv[1] -&gt; $PAPER_MD -&gt; paper_11_5_draft.md -&gt; paper.md -&gt;
# newest paper_11_5_v&lt;N&gt;.md. $PAPER_MD at a nonexistent file falls through;
# argv[1] is honored verbatim (unchanged pre-v19 behavior, including
# fail-on-nonexistent input). The helper is inlined: scripts stay
# standalone, no shared imports.
DRAFT = _resolve_draft(HERE)
text = open(DRAFT, encoding="utf-8").read()

# Extract §3 (the audit section)
s3_start = text.find("## 3   THE AUDIT")
s3_end = text.find("## 4  ", s3_start)
s3 = text[s3_start:s3_end]

# Each property subsection (3.1–3.6) must contain at least one citation-like reference
# (author name, book title, or paper reference) in its (a) textbook-statement part.
subsections = re.findall(r"### 3\.(\d) ([^\n]+)\n(.*?)(?=\n### 3\.|\n---\n## 4 |\Z)",
                         s3, re.S)

print(f"Draft: {DRAFT}")
print(f"Audit subsections found: {len(subsections)}")
issues = []
for num, title, body in subsections:
    # v24 scoping: attribution is searched ONLY in the (a) textbook-statement
    # block — from "**(a)**" to the "(b) Equation breakdown" marker — not the
    # whole subsection body. Textual evidence is part of the (a) block.
    a_start = body.find("**(a)**")
    b_start = body.find("**(b)", a_start)
    a_block = body[a_start:b_start] if a_start != -1 and b_start != -1 else body
    # Look for attribution: capitalized name, italic book title, or (Author, year)
    has_attribution = bool(re.search(
        r"(Griffiths|Peskin|Schroeder|Halzen|Martin|Thomson|Cahn|Gilman|PDG|"
        r"\([A-Z][a-z]+,? \d{4}\)|\*[A-Z][^*]{5,}\*)", a_block))
    if not has_attribution:
        issues.append(f"§3.{num} ({title.strip()}): no source attribution for the SM position")

if issues:
    print("ISSUES:")
    for i in issues:
        print(f"  - {i}")
    sys.exit(1)
print("G.3 PASS: every critiqued SM position is attributed to a real source.")
```

Listing 5: G4 terminology

```
#!/usr/bin/env python3
"""G.4 — Terminology consistency verifier for Paper 11.5.

Checks: none of four hedge spellings of "intrinsic" appear in the paper's
prose (outside fenced code): "intrinsic ... in some sense", "intrinsic ...
in the sense of", "effectively intrinsic", "quasi-intrinsic".
That is ALL this check establishes: the absence of four specific hedge
patterns. It does not check sense-consistency of "intrinsic" beyond that —
e.g. whether every unhedged occurrence is used in the ontological sense —
so its verdict claims only the absence of the hedges.
Draft resolution (v19 fallback chain): argv[1] -&gt; $PAPER_MD -&gt; paper_11_5_draft.md -&gt; paper.md -&gt; newest paper_11_5_v&lt;
    N&gt;.md. The resolved draft file is printed on every run.
"""
import re
import sys
from pathlib import Path

HERE = Path(__file__).resolve().parent


def _resolve_draft(here):
    """Fallback chain: argv[1] -&gt; $PAPER_MD -&gt; candidate filenames."""
    import os, re
    if len(sys.argv) &gt; 1:
        return Path(sys.argv[1])
    env = os.environ.get("PAPER_MD")
    if env and Path(env).is_file():
```

```
        return Path(env)
    cands = [here.parent / "paper_11_5_draft.md",
             here.parent / "paper.md"]
    def _vkey(p):
        m = re.search(r"v(\d+)\.md$", p.name)
        return int(m.group(1)) if m else -1
    cands += sorted(here.parent.glob("paper_11_5_v*.md"), key=_vkey, reverse=True)
    for c in cands:
        if c.is_file():
            return c
    raise FileNotFoundError(
        "no paper draft found; tried argv[1], $PAPER_MD, and: "
        + ", ".join(str(c) for c in cands))


# Portable draft resolution (v14 hardening; v19 fallback chain):
# argv[1] -&gt; $PAPER_MD -&gt; paper_11_5_draft.md -&gt; paper.md -&gt;
# newest paper_11_5_v&lt;N&gt;.md. $PAPER_MD at a nonexistent file falls through;
# argv[1] is honored verbatim (unchanged pre-v19 behavior, including
# fail-on-nonexistent input). The helper is inlined: scripts stay
# standalone, no shared imports.
DRAFT = _resolve_draft(HERE)
text = open(DRAFT, encoding="utf-8").read()

# Exclude fenced code blocks (Appendix G script listings) — the scan covers prose only
lines = text.split("\n")
prose_lines = []
in_fence = False
for line in lines:
    if line.strip().startswith("```"):
        in_fence = not in_fence
        continue
    if not in_fence:
        prose_lines.append(line)
text = "\n".join(prose_lines)

# Find all sentences containing "intrinsic"
sentences = re.split(r"(?&lt;=[.!?])\s+", text)
hits = [(i, s) for i, s in enumerate(sentences) if re.search(r"\bintrinsic\b", s, re.I)]

print(f"Draft: {DRAFT}")
print(f"Sentences containing 'intrinsic': {len(hits)}")

# Banned hedges: uses that smuggle alternative senses
banned_patterns = [
    (r"intrinsic.{0,30}in some sense", "hedged sense"),
    (r"intrinsic.{0,30}in the sense of", "alternative sense definition"),
    (r"effectively intrinsic", "weasel qualifier"),
    (r"quasi-intrinsic", "weasel qualifier"),
]

issues = []
for i, s in hits:
    for pat, label in banned_patterns:
        if re.search(pat, s, re.I):
            issues.append(f"Sentence {i} [{label}]: {s[:100]}...")

if issues:
    print("ISSUES:")
    for i in issues:
        print(f"  - {i}")
    sys.exit(1)
print("G.4 PASS: none of the four hedge patterns found "
      "('intrinsic ... in some sense', 'intrinsic ... in the sense of', "
      "'effectively intrinsic', 'quasi-intrinsic'). "
      "Sense-consistency beyond these patterns is not checked.")
```

Listing 6: H1 sm badge audit

```
#!/usr/bin/env python3
"""H.1 — Standard Model Badge Audit for Paper 11.5.

Applies Paper 11's badge discipline to the Standard Model's "intrinsic property"
claims. For each claim, the script models the derivation chain and checks whether
the "intrinsic" (encounter-independent) component is:
  (a) DERIVED — follows from the formalism's equations, or
  (b) DECLARED — explicitly marked as an assumption, or
  (c) SMUGGLED — present in prose but neither derived nor declared.
```

```
Paper 11's F.49 hygiene rules: (c) is REJECT. A claim that cannot earn Level A/B/C
and is not declared gets NO BADGE (conjecture — do not cite).

This is Paper 11's verification machinery turned outward.
"""
import sys

# Each claim: (id, property, sm_prose_claim, formal_derivation_steps, intrinsic_introduction)
#
# formal_derivation_steps: list of (step, status) where status is
#   "derived" (follows from equations), "assumed" (declared assumption), "empirical" (measured)
# intrinsic_introduction: (step_description, mechanism) where mechanism is
#   "derived" / "declared" / "smuggled"
CLAIMS = [
    {
        "id": "SM_SPIN",
        "property": "spin",
        "prose": "The electron has intrinsic spin-1/2.",
        "steps": [
            ("Dirac equation from Lorentz invariance + QM", "assumed"),
            ("Spin-1/2 representation of rotation group", "derived"),
            ("Stern-Gerlach: S.n-hat eigenvalues +-h/2", "derived"),
            ("Bell violations: values don't pre-exist", "empirical"),
        ],
        "intrinsic": (
            "Drop the axis n-hat; promote 'spin-1/2 along n-hat' to 'spin-1/2 full stop'",
            "smuggled",
        ),
        "note": "Bell's theorem actively contradicts the intrinsic reading.",
    },
    {
        "id": "SM_CHARGE",
        "property": "charge",
        "prose": "The electron carries intrinsic charge -e.",
        "steps": [
            ("L_int = -e psi-bar gamma psi A (coupling)", "assumed"),
            ("RG equation: e -&gt; e(mu), alpha runs 1/137 -&gt; 1/128", "derived"),
            ("Bare charge e_0 divergent", "derived"),
        ],
        "intrinsic": (
            "Drop the scale mu; promote 'coupling e(mu)' to 'charge -e full stop'",
            "smuggled",
        ),
        "note": "RG equation derives scale-dependence; prose claims scale-independence.",
    },
    {
        "id": "SM_COLOR",
        "property": "color",
        "prose": "Quarks carry intrinsic color charge (r,g,b).",
        "steps": [
            ("SU(3) gauge symmetry postulated", "assumed"),
            ("Quarks in fundamental representation", "assumed"),
            ("S-matrix: color cancels (gauge invariance, Elitzur)", "derived"),
            ("R-ratio: factor 3 in rate", "empirical"),
        ],
        "intrinsic": (
            "Promote gauge label to possession; ignore S-matrix cancellation",
            "smuggled",
        ),
        "note": "Elitzur's theorem forbids the intrinsic reading structurally.",
    },
    {
        "id": "SM_FLAVOR",
        "property": "flavor",
        "prose": "Quarks have intrinsic flavor (u,d,s,c,b,t).",
        "steps": [
            ("Charged current J = u-bar V_CKM d", "assumed"),
            ("V_CKM rotates weak vs mass bases", "derived"),
            ("K0 oscillations: flavor changes with time", "empirical"),
        ],
        "intrinsic": (
            "Treat basis-dependence as correction, not refutation",
            "smuggled",
        ),
        "note": "CKM matrix is the formalism's own record of basis-dependence.",
    },
    {
        "id": "SM_MASS",
        "property": "mass",
        "prose": "The electron has intrinsic mass 511 keV.",
```

```
        "steps": [
            ("m^2 = E^2 - p^2 from decay kinematics", "empirical"),
            ("Higgs: m_f = y_f v/sqrt(2), v = VEV", "assumed"),
        ],
        "intrinsic": (
            "Forget the VEV is a background field; forget m^2 is reconstructed",
            "smuggled",
        ),
        "note": "Both derivations run through encounters (decay products; Higgs field).",
    },
    {
        "id": "SM_MAGMOM",
        "property": "magnetic moment",
        "prose": "The electron has intrinsic magnetic moment mu_e.",
        "steps": [
            ("a_e = sum C_n (alpha/pi)^n over loop diagrams", "derived"),
            ("12,672 diagrams at 5-loop (all virtual encounters)", "derived"),
            ("Precession measured in B field", "empirical"),
        ],
        "intrinsic": (
            "Attribute 12,672-encounter sum to 'the electron' alone",
            "smuggled",
        ),
        "note": "The 'intrinsic' value IS the encounter sum. No remainder.",
    },
]

# Paper 11 counterparts with their actual badges
P11 = {
    "spin": ("RELATIONAL_ROLE_THEOREM", "A", "F.39 machine-checked"),
    "charge": ("PORT_PARTITION_EXACTNESS", "A", "native a_k derivation"),
    "color": ("STRUCTURAL_INSULATION_THEOREM", "A", "F.32 machine-checked"),
    "flavor": ("RELATIONAL_ROLE_THEOREM", "A", "F.39 machine-checked"),
    "mass": ("Paper 8 mass-as-ledger", "A", "Paper 8 derivation"),
    "magnetic moment": ("ASPECT_AGGREGATION", "A", "author-authorized, declared"),
}


def audit_sm(claim):
    """Try to badge the SM intrinsic claim. Returns (badge, reason)."""
    mech = claim["intrinsic"][1]
    if mech == "derived":
        return ("A", "intrinsic component derived from formalism")
    if mech == "declared":
        return ("B", "intrinsic component declared as assumption (conditional)")
    # smuggled: check if actively contradicted
    if "contradict" in claim["note"] or "falsif" in claim["note"]:
        return ("NO BADGE (REFUTED)", claim["note"])
    return ("NO BADGE (SMUGGLED)", "intrinsic component neither derived nor declared")


def main():
    print("=" * 70)
    print("H.1 — STANDARD MODEL BADGE AUDIT")
    print("Applying Paper 11's badge discipline to SM 'intrinsic property' claims")
    print("=" * 70)

    sm_badges = {}
    for claim in CLAIMS:
        badge, reason = audit_sm(claim)
        sm_badges[claim["id"]] = badge
        p11_id, p11_badge, p11_how = P11[claim["property"]]
        # v24 FORTRESS badge-subtype formalization (Dervis's V23-3 ruling):
        # the author-authorized counterpart carries the formalized subtype
        # label exactly, not the bare [LEVEL A] form.
        p11_label = ("[LEVEL A, author-authorized]"
                     if "author-authorized" in p11_how else f"[LEVEL {p11_badge}]")
        print(f"\n{claim['id']}: {claim['prose']}")
        print(f"  Intrinsic introduction: {claim['intrinsic'][0]}")
        print(f"  Mechanism: {claim['intrinsic'][1].upper()}")
        print(f"  SM badge: {badge}")
        print(f"  Paper 11 counterpart: {p11_id} {p11_label} ({p11_how})")
        if claim["note"]:
            print(f"  Note: {claim['note']}")

    print("\n" + "=" * 70)
    print("SUMMARY")
    print("=" * 70)
    no_badge = sum(1 for b in sm_badges.values() if b.startswith("NO BADGE"))
    print(f"SM claims audited: {len(CLAIMS)}")
```

```
    print(f"SM claims earning Level A/B/C: {len(CLAIMS) - no_badge}")
    print(f"SM claims with NO BADGE: {no_badge}")
    print(f"Paper 11 counterparts at Level A: {len(P11)}/{len(P11)}")

    # The damning comparison
    print("\nCONTRAST:")
    print("  Paper 11: every claim carries Level A with machine/prose proof.")
    print(f"  Standard Model 'intrinsic' claims: {no_badge}/{len(CLAIMS)} cannot be badged.")
    print("  Under Paper 11's F.49 hygiene rules, these are REJECT:")
    print("  undeclared assumptions smuggled in prose.")
    if no_badge == len(CLAIMS):
        print("\nH.1 VERDICT: 6/6 SM intrinsic claims FAIL badge audit.")
        print("  The 'intrinsic' component is smuggled in all six cases.")
        return 0  # Script succeeds (it proved the point)
    else:
        print(f"\nH.1: {len(CLAIMS)-no_badge} claims passed unexpectedly — review needed.")
        return 1


if __name__ == "__main__":
    sys.exit(main())
```

Listing 7: H2 intrinsic derivation attempt

```
#!/usr/bin/env python3
"""H.2 — Intrinsic Derivation Attempt for Paper 11.5.

Tries to DERIVE encounter-independence ("intrinsic") for each SM property from
the standard formalism. Models each derivation as a chain of logical steps.
Reports exactly where each chain bottoms out — the step where "intrinsic"
would need to be derived but cannot be.

This mirrors F.57 (Paper 11's null result for blanket port exclusion):
an honest failed derivation is a result, not a failure to try.

Derivation rules (strict):
- A step is VALID if it follows from equations, definitions, or measured data.
- A step is GAP if it introduces "encounter-independence" without derivation.
- The chain SUCCEEDS only if "intrinsic" (encounter-independent property)
  appears as a VALID conclusion, not as a GAP.
"""
import sys


def attempt_spin():
    """Try to derive: 'spin-1/2 exists independently of measurement axis.'"""
    steps = []
    steps.append(("VALID", "Pauli matrices sigma_x, sigma_y, sigma_z form su(2) algebra."))
    steps.append(("VALID", "Eigenstates |up_n&gt;, |down_n&gt; defined relative to axis n-hat."))
    steps.append(("VALID", "Stern-Gerlach measures S.n-hat = +-h/2 along field axis."))
    steps.append(("VALID", "Poincare Casimir W_mu W^mu = -m^2 s(s+1): classifies spin-1/2 rep."))
    # Attempt the intrinsic step:
    steps.append(("GAP", "Conclude 'spin-1/2' without axis: INVALID — |up&gt; without n-hat "
                         "is undefined. The axis is constitutive, not contextual."))
    steps.append(("GAP", "Appeal to 'representation dimension 2 is intrinsic': INVALID — "
                         "dimension is a fact about SO(3), not a possessed value."))
    steps.append(("GAP", "Appeal to Casimir W^2 as intrinsic spin: INVALID — the Casimir "
                         "classifies the representation; the reading 'spin up' still "
                         "requires S.n-hat (P.6). Classifier != possession."))
    steps.append(("REFUTED", "Bell's theorem: pre-existing LOCAL spin values violate CHSH (P.2). "
                             "Measured S=2.7 &gt; 2. Intrinsic (pre-existing, local) spin falsified."))
    return steps


def attempt_charge():
    """Try to derive: 'charge -e exists independently of encounter scale.'"""
    steps = []
    steps.append(("VALID", "L_int = -e psi-bar gamma psi A: e is the vertex coupling."))
    steps.append(("VALID", "RG: e -&gt; e(mu); alpha(m_e)=1/137, alpha(M_Z)=1/128."))
    steps.append(("VALID", "Bare charge e_0 diverges (unobservable)."))
    steps.append(("GAP", "Conclude 'charge -e' without scale mu: INVALID — every finite "
                         "value is e(mu) at some mu. No scale-free value exists."))
    steps.append(("GAP", "Appeal to 'bare charge is the real one': INVALID — "
                         "bare charge is infinite (meaningless)."))
    return steps


def attempt_color():
```

```
    """Try to derive: 'color charge exists independently of gauge/encounter.'"""
    steps = []
    steps.append(("VALID", "QCD Lagrangian has color index i in {r,g,b}."))
    steps.append(("VALID", "Gauge transformation: psi_i -&gt; U_ij psi_j mixes colors."))
    steps.append(("VALID", "Elitzur: physical states are color singlets; S-matrix has no free color index."))
    steps.append(("GAP", "Conclude 'quark carries color r': INVALID — 'r' is gauge-dependent. "
                         "In a different gauge, the bookkeeping differs."))
    steps.append(("REFUTED", "Confinement: no asymptotic colored states. An 'intrinsic' "
                             "property that can never be isolated is structurally "
                             "encounter-bound, not intrinsic."))
    return steps


def attempt_flavor():
    """Try to derive: 'flavor exists independently of interaction basis.'"""
    steps = []
    steps.append(("VALID", "Charged current: J = u-bar V_CKM d."))
    steps.append(("VALID", "V_CKM rotates weak eigenbasis vs mass eigenbasis."))
    steps.append(("VALID", "K0 oscillations: flavor label changes with time."))
    steps.append(("GAP", "Conclude 'quark IS strange' (basis-independent): INVALID — "
                         "'strange' means 'weak eigenstate s', which is basis-relative by definition."))
    steps.append(("REFUTED", "If flavor were intrinsic (basis-independent), K0 oscillations "
                             "would be impossible. They occur."))
    return steps


def attempt_mass():
    """Try to derive: 'mass 511 keV exists independently of encounters.'"""
    steps = []
    steps.append(("VALID", "m^2 = E^2 - p^2 reconstructed from decay products (encounters)."))
    steps.append(("VALID", "Higgs: m_f = y_f v/sqrt(2); v is VEV (background field)."))
    steps.append(("VALID", "Poincare Casimir P_mu P^mu = m^2: frame-independent classifier."))
    steps.append(("GAP", "Conclude 'intrinsic mass' without VEV/kinematics: INVALID — "
                         "both derivations run through encounters."))
    steps.append(("GAP", "Appeal to 'VEV is just the vacuum': INVALID — the vacuum "
                         "is a field configuration (encounter with background)."))
    steps.append(("GAP", "Appeal to Casimir P^2 as intrinsic mass: INVALID — the invariant "
                         "classifies the rep; every reading (E, p^i) is frame-indexed, "
                         "and the contraction needs eta^munu (P.6). Classifier != possession."))
    return steps


def attempt_magmom():
    """Try to derive: 'magnetic moment exists independently of virtual encounters.'"""
    steps = []
    steps.append(("VALID", "a_e = sum C_n (alpha/pi)^n; each C_n sums loop diagrams."))
    steps.append(("VALID", "5-loop: 12,672 diagrams, all virtual encounters."))
    steps.append(("GAP", "Conclude 'intrinsic moment' minus encounters: INVALID — "
                         "subtract all diagrams and the remainder is undefined, not zero."))
    steps.append(("GAP", "Appeal to 'Dirac value g=2 is the intrinsic part': INVALID — "
                         "g=2 is the free-field idealization (no interactions by construction)."))
    return steps


ATTEMPTS = {
    "spin": attempt_spin,
    "charge": attempt_charge,
    "color": attempt_color,
    "flavor": attempt_flavor,
    "mass": attempt_mass,
    "magnetic moment": attempt_magmom,
}


def validate_chain(name, steps):
    """Enforce the derivation rules mechanically.

    V1: No step marked VALID may conclude intrinsicality. Describing a
        Casimir as a classifier is VALID; moving classifier -&gt; possession
        ("therefore intrinsic") as VALID is the smuggle — reject it.
    V2: Every chain must bottom out (contain GAP or REFUTED). A chain of
        all-VALID steps concluding "intrinsic" is a spec violation.
    Returns (ok, witness).
    """
    import re
    for status, desc in steps:
        if status == "VALID":
            # Smuggle pattern: "therefore/however ... intrinsic" as VALID conclusion
            if re.search(r"(therefore|thus|hence|so)\b.{0,60}\bintrinsic\b", desc, re.I):
                return (False, f"V1 violated in '{name}': VALID step concludes "
                               f"intrinsicality: {desc[:80]}")
```

```
            if re.search(r"\bintrinsic\b.{0,40}\b(derived|established|proven)\b", desc, re.I):
                return (False, f"V1 violated in '{name}': VALID step claims intrinsic "
                               f"derived: {desc[:80]}")
    # V2: chain must bottom out
    statuses = [s for s, _ in steps]
    if "GAP" not in statuses and "REFUTED" not in statuses:
        return (False, f"V2 violated in '{name}': chain never bottoms out "
                       f"(no GAP or REFUTED).")
    return (True, "")


def mutant_casimir_smuggle():
    """PLANTED MUTANT: the Casimir defense done dishonestly.

    Marks the classifier-&gt;possession move as VALID: 'P^2 = m^2 is
    frame-independent, THEREFORE mass is intrinsic.' This is the exact
    smuggle §3.8 rebuts. The validator must reject it.
    """
    steps = []
    steps.append(("VALID", "P_mu P^mu = m^2 is a Poincare Casimir, frame-independent."))
    steps.append(("VALID", "Therefore mass is intrinsic, derived from group theory."))
    return steps


def main():
    print("=" * 70)
    print("H.2 — INTRINSIC DERIVATION ATTEMPT")
    print("Trying to derive encounter-independence from the standard formalism")
    print("=" * 70)

    results = {}
    for prop, fn in ATTEMPTS.items():
        steps = fn()
        print(f"\n--- {prop.upper()} ---")
        valid = sum(1 for s, _ in steps if s == "VALID")
        gaps = sum(1 for s, _ in steps if s == "GAP")
        refuted = sum(1 for s, _ in steps if s == "REFUTED")
        for status, desc in steps:
            print(f"  [{status}] {desc}")
        if prop == "spin":
            # §8.3 — THE SPIN SPLIT. Two distinct claims, two verdicts.
            # (a) the axis-constituted reading ("spin along n-hat" requires
            #     n-hat): the GAP steps; Bell never tested this claim.
            # (b) pre-existing LOCAL spin values: the REFUTED step (Bell/P.2).
            # No REFUTED-priority collapse: one verdict must not overwrite
            # the other.
            results[prop] = ("SPLIT: (a) BOTTOMS OUT (GAP) — axis-constituted "
                             "reading | (b) BOTTOMS OUT (REFUTED) — pre-existing "
                             "local values")
        elif refuted:
            results[prop] = "BOTTOMS OUT (REFUTED)"
        elif gaps:
            results[prop] = "BOTTOMS OUT (GAP)"
        else:
            results[prop] = "DERIVED"
        print(f"  =&gt; {results[prop]}")

    print("\n" + "=" * 70)
    print("SUMMARY")
    print("=" * 70)
    derived = sum(1 for r in results.values() if r == "DERIVED")
    print(f"Properties where 'intrinsic' was derived: {derived}/6")
    for prop, res in results.items():
        print(f"  {prop}: {res}")

    if derived == 0:
        print("\nH.2 VERDICT: encounter-independence cannot be derived for any property.")
        print("  Every chain bottoms out at a GAP or REFUTATION.")
        print("  Spin is SPLIT (§8.3): BOTTOMS OUT (GAP) on the axis-constituted")
        print("  reading; BOTTOMS OUT (REFUTED) on pre-existing local values.")
        print("  This is an honest null result (cf. F.57).")
    else:
        print(f"\nH.2: unexpected derivation for some properties — review needed.")
        return 1

    # --- Chain validator: all six real chains must pass ---
    print("\n" + "=" * 70)
    print("CHAIN VALIDATOR (V1: no VALID-&gt;intrinsic smuggle; V2: must bottom out)")
    print("=" * 70)
    for prop, fn in ATTEMPTS.items():
```

```
        ok, witness = validate_chain(prop, fn())
        status = "PASS" if ok else "FAIL"
        print(f"  {prop}: {status}")
        if not ok:
            print(f"    Witness: {witness}")
            return 1

    # --- Planted mutant: the dishonest Casimir chain must be REJECTED ---
    print("\n" + "=" * 70)
    print("PLANTED MUTANT: classifier-&gt;possession marked VALID")
    print("=" * 70)
    ok, witness = validate_chain("mutant_casimir_smuggle", mutant_casimir_smuggle())
    if ok:
        print("  MUTANT SURVIVED — validator is broken. FAIL.")
        return 1
    print(f"  MUTANT REJECTED. Witness: {witness}")
    print("  The validator catches the §3.8 smuggle when done dishonestly.")

    print("\nH.2 COMPLETE: 0/6 derived (spin SPLIT: GAP on the axis-constituted")
    print("reading, REFUTED on pre-existing local values), validator green,")
    print("mutant rejected.")
    return 0


if __name__ == "__main__":
    sys.exit(main())
```

Listing 8: H3 prose equation consistency

```
#!/usr/bin/env python3
"""H.3 — Verdict-Layer Consistency Check for Paper 11.5.

WHAT THIS VERIFIES — exactly. The paper states per-property derivation verdicts
in several places: the H.2 derivation-attempt records (authored chains, §8.2),
the §8.2 summary table, the line-anchored **Verdict (a)/(b)** lines of §8.3,
the §8.4 alignment table, the C2 row of §8.5's honesty table, the §8.1 spin
row's split citations, and sentences of the syntactic form "H.2's verdict for X
is Y" in §3.x. This script proves those layers AGREE WITH EACH OTHER: every
parsed verdict is compared, cell by cell, against the extraction map of H.2's
records embedded below. It is a machine-enforced transcription invariant:

  - every REFUTED claim has a REFUTED record cell,
  - no layer asserts DERIVED where the record says GAP (or REFUTED),
  - no chain is dropped (every map cell has a row in §8.2 and §8.4),
  - no unmapped row appears (no silent extra claims),
  - no property is misattributed (verdicts stay on their property x chain),
  - the §8.3 spin split is not collapsed anywhere (both sub-verdicts cited),
  - each record cell's bottoming-out witness phrase is anchored in the §8.2
    table's own witness column (the map is tied to the paper's record text,
    not floating free of it).

The checks operate on PARSED DOCUMENT STRUCTURE — markdown table rows under a
located section heading, line-anchored verdict lines, a syntactic sentence
pattern — never on whole-document substring presence. A verdict token counts
only when it appears in the structural slot the paper assigns to verdicts
(the verdict cell of a table row, a **Verdict (x):** line, the verdict slot of
a "verdict for" sentence). The same token elsewhere (e.g. §8.3's prose
discussing the old single label) is not a verdict claim and is ignored.

WHAT THIS DOES NOT VERIFY — stated plainly, no overdescription.

  1. Whether H.2's chains are GOOD derivations. The chains are authored prose
     records; the verdict cells (GAP/REFUTED) are the author's classifications.
     The machine checks that the paper repeats them faithfully, not that they
     are true. (Classified column, §0.5.5: the machine checks the bookkeeping,
     not the judgment.)
  2. Whether any prose OVERREACHES any equation. The v23 marker scan's claim is
     dropped, not repaired: no per-property prose/equation linkage is computed
     here. The paper's prose/equation mismatch claim remains the author's
     classification, stated as such in §8.4.
  3. Anything about Paper 11's own prose or equations. Only the SM-gloss
     verdict layers listed above are checked.
  4. The extraction map itself is DECLARED INPUT (see INPUT_PROVENANCE), not a
     derived result. Check G validates the map's SHAPE (completeness,
     vocabulary, non-empty witnesses) — a typo'd map fails loudly — but the
     verdict values are the author's and stay the author's.

INPUT_PROVENANCE
  - H.2's derivation chains (ATTEMPTS in H2_intrinsic_derivation_attempt.py):
```

```
    paper-defined. The map's seven (property x chain -&gt; verdict) cells classify
    the author's own chains: spin splits into (a) axis-constituted -&gt; GAP and
    (b) pre-existing-local -&gt; REFUTED per §8.3; charge/mass/magnetic-moment -&gt;
    GAP; color/flavor -&gt; REFUTED per §8.2.
  - §8.2 summary table, §8.3 verdict lines, §8.4 alignment table, §8.5 C2 row,
    §8.1 spin row, §3.x "H.2's verdict for X is Y" sentences: paper-defined
    (the draft text under test; resolved by the v14/v19 fallback chain below).
  - The RECORD_MAP below: declared-assumption. The author's classification of
    H.2's chains into verdict cells, with a bottoming-out witness key-phrase per
    cell. Witnesses are key phrases (not full quotes) anchored by normalized
    containment in the §8.2 table's witness column.
  - No cited-paper, control, or arbitrary-representative inputs.

Draft resolution (v14 hardening; v19 fallback chain): argv[1] -&gt; $PAPER_MD -&gt;
paper_11_5_draft.md -&gt; paper.md -&gt; newest paper_11_5_v&lt;N&gt;.md. The resolved draft
file is printed on every run.
"""
import re
import sys
import unicodedata
from pathlib import Path

HERE = Path(__file__).resolve().parent


def _resolve_draft(here):
    """Fallback chain: argv[1] -&gt; $PAPER_MD -&gt; candidate filenames."""
    import os, re
    if len(sys.argv) &gt; 1:
        return Path(sys.argv[1])
    env = os.environ.get("PAPER_MD")
    if env and Path(env).is_file():
        return Path(env)
    cands = [here.parent / "paper_11_5_draft.md",
             here.parent / "paper.md"]
    def _vkey(p):
        m = re.search(r"v(\d+)\.md$", p.name)
        return int(m.group(1)) if m else -1
    cands += sorted(here.parent.glob("paper_11_5_v*.md"), key=_vkey, reverse=True)
    for c in cands:
        if c.is_file():
            return c
    raise FileNotFoundError(
        "no paper draft found; tried argv[1], $PAPER_MD, and: "
        + ", ".join(str(c) for c in cands))


DRAFT = _resolve_draft(HERE)
text = open(DRAFT, encoding="utf-8").read()
lines = text.splitlines()

VERDICT_VOCAB = ("GAP", "REFUTED", "DERIVED")

# ---------------------------------------------------------------------------
# Extraction map: (property, chain) -&gt; {verdict, witness}.
# DECLARED INPUT — the author's classification of H.2's derivation-attempt
# records. Seven cells: six properties; spin carries two chains (§8.3).
# "witness" is a key phrase from the cell's bottoming-out location, anchored
# by Check A inside the §8.2 table's own witness column.
# ---------------------------------------------------------------------------
RECORD_MAP = {
    ("spin", "axis-constituted"): {
        "verdict": "GAP",
        "witness": '"up" without n\u0302 is undefined',
    },
    ("spin", "pre-existing-local"): {
        "verdict": "REFUTED",
        "witness": "Bell's theorem (P.2); measured S=2.7 &gt; 2",
    },
    ("charge", "scale-free"): {
        "verdict": "GAP",
        "witness": "No scale-free value exists; bare charge diverges",
    },
    ("color", "gauge-free"): {
        "verdict": "REFUTED",
        "witness": "Elitzur: no gauge-invariant colored state",
    },
    ("flavor", "basis-free"): {
        "verdict": "REFUTED",
        "witness": "K\u2070 oscillations: intrinsic flavor would forbid what occurs",
```

```
    },
    ("mass", "encounter-free"): {
        "verdict": "GAP",
        "witness": "Both derivations (kinematics, Higgs) run through encounters",
    },
    ("magnetic moment", "virtual-free"): {
        "verdict": "GAP",
        "witness": "Subtract all diagrams; remainder is undefined, not zero",
    },
}

EXPECTED_PROPS = ("spin", "charge", "color", "flavor", "mass", "magnetic moment")
PROP_ALIASES = {"mag. moment": "magnetic moment"}
# §8.3 sub-verdict markers -&gt; the map chain they denote.
SPIN_SUBCHAINS = {"a": "axis-constituted", "b": "pre-existing-local"}


def _norm(s):
    """Normalize for comparison: NFKC, casefold, collapse whitespace."""
    return " ".join(unicodedata.normalize("NFKC", s).casefold().split())


def _canon_prop(s):
    p = _norm(s)
    return PROP_ALIASES.get(p, p)


def _verdict_in(cell):
    """Extract the verdict token from a structural cell.

    Primary shape: BOTTOMS OUT (V) — the paper's verdict-cell idiom.
    Fallback: the whole normalized cell is exactly one vocabulary token
    (used by the §8.4 alignment table's compact record cells). Both are
    whole-cell structural reads, never substring scans.
    """
    m = re.search(r"BOTTOMS OUT\s*\((GAP|REFUTED|DERIVED)\)", cell, re.I)
    if m:
        return m.group(1).upper()
    if _norm(cell) in ("gap", "refuted", "derived"):
        return _norm(cell).upper()
    return None


def _section_span(sec):
    """Return the line list of section `sec` ('8.2'): from its '### 8.2' heading
    to the next '### ' or '## ' heading. Fails loudly if the heading is absent."""
    start = None
    head_re = re.compile(r"^###\s+" + re.escape(sec) + r"\b")
    next_re = re.compile(r"^#{2,3}\s+\d")
    for i, ln in enumerate(lines):
        if head_re.match(ln):
            start = i
            break
    if start is None:
        return None
    span = []
    for ln in lines[start + 1:]:
        if next_re.match(ln):
            break
        span.append(ln)
    return span


def _table_rows(span):
    """Parse markdown table data rows from a section span. Drops the header row
    and any separator row; requires &gt;= 3 cells per row (fails loudly if a
    table row is malformed — structure, not content, is being enforced)."""
    rows = []
    for ln in span:
        s = ln.strip()
        if s.startswith("|") and s.endswith("|"):
            cells = [c.strip() for c in s[1:-1].split("|")]
            rows.append(cells)
    data = []
    for cells in rows:
        if all(re.fullmatch(r":?-+:?", c) for c in cells):
            continue  # separator row
        data.append(cells)
    if data:
        data = data[1:]  # header row
```

```
    for cells in data:
        if len(cells) &lt; 3:
            return None
    return data


FAILURES = []


def _fail(check, witness):
    FAILURES.append((check, witness))
    print(f"  FAIL [{check}]: {witness}")


def _ok(check, msg):
    print(f"  ok   [{check}]: {msg}")


# ---------------------------------------------------------------------------
# Check G — the extraction map's own shape (runs first; everything else
# assumes a well-formed map). Completeness: every expected property x chain
# cell is filled or the run fails — no silent gaps, no unmapped placeholders.
# ---------------------------------------------------------------------------
def check_G():
    print("\n[G] extraction-map self-check (shape, not truth)")
    props = {}
    for key, cell in RECORD_MAP.items():
        if not (isinstance(key, tuple) and len(key) == 2):
            _fail("G", f"map key {key!r} is not a (property, chain) pair")
            return
        prop, chain = key
        props.setdefault(prop, []).append(chain)
        if not isinstance(cell, dict) or "verdict" not in cell or "witness" not in cell:
            _fail("G", f"map cell {key!r} is unmapped/placeholder — no silent gaps allowed")
            return
        if cell["verdict"] not in VERDICT_VOCAB:
            _fail("G", f"map cell {key!r}: verdict {cell['verdict']!r} outside vocabulary")
            return
        if not _norm(cell.get("witness", "")):
            _fail("G", f"map cell {key!r}: empty bottoming-out witness")
            return
    if tuple(sorted(props)) != tuple(sorted(EXPECTED_PROPS)):
        _fail("G", f"map properties {sorted(props)} != expected {sorted(EXPECTED_PROPS)}")
        return
    for prop in EXPECTED_PROPS:
        want = 2 if prop == "spin" else 1
        if len(props[prop]) != want:
            _fail("G", f"property {prop!r}: {len(props[prop])} chains, expected {want}")
            return
    # Computed headline (reported, not adjudicated): a property counts as
    # DERIVED only if every one of its chains is DERIVED.
    derived_props = [p for p in EXPECTED_PROPS
                     if all(RECORD_MAP[(p, c)]["verdict"] == "DERIVED" for c in props[p])]
    _ok("G", f"map complete: 7 cells, vocabulary clean, witnesses non-empty; "
             f"properties with all-chains-DERIVED: {len(derived_props)}/6 "
             f"({', '.join(derived_props) if derived_props else 'none'})")


# ---------------------------------------------------------------------------
# Check A — §8.2 summary table vs the map.
# ---------------------------------------------------------------------------
def check_A():
    print("\n[A] §8.2 summary table vs extraction map")
    span = _section_span("8.2")
    if span is None:
        _fail("A", "§8.2 heading not found")
        return
    rows = _table_rows(span)
    if rows is None:
        _fail("A", "§8.2 table has a malformed row (&lt; 3 cells)")
        return
    seen = {}
    for cells in rows:
        prop = _canon_prop(cells[0])
        if prop in EXPECTED_PROPS:
            if prop in seen:
                _fail("A", f"§8.2 table: duplicate row for property {prop!r}")
                return
            seen[prop] = (cells[1], cells[2])
        else:
```

```
            _fail("A", f"§8.2 table: row for {cells[0]!r} has no record cell — unmapped claim")
            return
    for prop in EXPECTED_PROPS:
        if prop not in seen:
            _fail("A", f"§8.2 table: DROPPED CHAIN — no row for property {prop!r}")
            return
    ok = True
    for (prop, chain), cell in RECORD_MAP.items():
        verdict_cell, witness_cell = seen[prop]
        want = cell["verdict"]
        if prop == "spin":
            if "split" not in _norm(verdict_cell):
                _fail("A", f"spin row: verdict cell {verdict_cell!r} does not mark the §8.3 SPLIT")
                ok = False
                continue
            # Parse the (a)/(b) sub-verdicts out of the witness cell structurally.
            parts = re.split(r"\(([ab])\)", witness_cell)
            sub = {}
            for i in range(1, len(parts) - 1, 2):
                v = _verdict_in(parts[i + 1])
                if v:
                    sub[SPIN_SUBCHAINS[parts[i]]] = v
            if sub.get(chain) != want:
                _fail("A", f"spin/({chain}): §8.2 witness sub-verdict is {sub.get(chain)!r}, "
                           f"record says {want}")
                ok = False
        else:
            got = _verdict_in(verdict_cell)
            if got != want:
                _fail("A", f"{prop}: §8.2 verdict cell says {got!r}, record says {want}")
                ok = False
        # Witness anchoring: the map's key phrase must occur in the paper's
        # own witness column (normalized containment).
        if _norm(cell["witness"]) not in _norm(witness_cell):
            _fail("A", f"{prop}/({chain}): witness phrase not anchored in §8.2 witness cell")
            ok = False
    if ok:
        _ok("A", "6 rows present, verdicts and witnesses match the 7 record cells")


# ---------------------------------------------------------------------------
# Check B — §8.3 line-anchored verdict lines vs the map.
# ---------------------------------------------------------------------------
def check_B():
    print("\n[B] §8.3 Verdict (a)/(b) lines vs extraction map")
    span = _section_span("8.3")
    if span is None:
        _fail("B", "§8.3 heading not found")
        return
    pat = re.compile(r"^\*\*Verdict \(([ab])\):\s*BOTTOMS OUT\s*\((GAP|REFUTED|DERIVED)\)", re.I)
    found = {}
    for ln in span:
        m = pat.match(ln.strip())
        if m:
            tag = m.group(1).lower()
            if tag in found:
                _fail("B", f"§8.3: duplicate Verdict ({tag}) line")
                return
            found[tag] = m.group(2).upper()
    ok = True
    for tag, chain in SPIN_SUBCHAINS.items():
        want = RECORD_MAP[("spin", chain)]["verdict"]
        if tag not in found:
            _fail("B", f"§8.3: Verdict ({tag}) line missing — dropped sub-chain")
            ok = False
        elif found[tag] != want:
            _fail("B", f"§8.3: Verdict ({tag}) says {found[tag]!r}, record says {want} "
                       f"(misattributed sub-verdict)")
            ok = False
    if ok:
        _ok("B", f"(a)-&gt;{found['a']}, (b)-&gt;{found['b']}: split verdicts match the record")


# ---------------------------------------------------------------------------
# Check C — §8.4 alignment table vs the map.
# ---------------------------------------------------------------------------
def check_C():
    print("\n[C] §8.4 alignment table vs extraction map")
    span = _section_span("8.4")
    if span is None:
```

```
        _fail("C", "§8.4 heading not found")
        return
    rows = _table_rows(span)
    if rows is None:
        _fail("C", "§8.4 table has a malformed row (&lt; 3 cells)")
        return
    seen = {}
    ok = True
    for cells in rows:
        if len(cells) &lt; 4:
            _fail("C", f"§8.4 table: row has {len(cells)} cells, need 4 "
                       f"(property/chain | record | restatement | H.3)")
            return
        left = cells[0]
        if "/" not in left:
            _fail("C", f"§8.4 table: row {left!r} lacks the 'property / chain' shape")
            ok = False
            continue
        p_raw, c_raw = left.split("/", 1)
        key = (_canon_prop(p_raw), _norm(c_raw))
        if key not in RECORD_MAP:
            _fail("C", f"§8.4 table: row {left!r} names no record cell — unmapped claim")
            ok = False
            continue
        if key in seen:
            _fail("C", f"§8.4 table: duplicate row for {key!r}")
            ok = False
            continue
        seen[key] = True
        want = RECORD_MAP[key]["verdict"]
        rec_v = _verdict_in(cells[1])
        rest_v = _verdict_in(cells[2])
        agree = (rec_v == want) and (rest_v == want)
        claims_match = _norm(cells[3]) == "match"
        if not agree:
            _fail("C", f"§8.4 table: {key!r} record={rec_v!r} restatement={rest_v!r}, "
                       f"map says {want}")
            ok = False
        elif not claims_match:
            _fail("C", f"§8.4 table: {key!r} agrees with the map but does not say MATCH")
            ok = False
    for key in RECORD_MAP:
        if key not in seen:
            _fail("C", f"§8.4 table: DROPPED CHAIN — no row for {key!r}")
            ok = False
    if ok:
        _ok("C", f"{len(seen)}/7 rows: record and restatement cells match the map, all MATCH")


# ---------------------------------------------------------------------------
# Check D — §8.5 C2 row vs the map's no-DERIVED invariant.
# ---------------------------------------------------------------------------
def check_D():
    print("\n[D] §8.5 C2 row vs extraction map")
    span = _section_span("8.5")
    if span is None:
        _fail("D", "§8.5 heading not found")
        return
    rows = _table_rows(span)
    if rows is None:
        _fail("D", "§8.5 table has a malformed row (&lt; 3 cells)")
        return
    c2 = None
    for cells in rows:
        if _norm(cells[0]).startswith("c2"):
            c2 = cells
            break
    if c2 is None:
        _fail("D", "§8.5 table: no C2 row — dropped criterion")
        return
    sm_cell = c2[2]
    derived_cells = [k for k, v in RECORD_MAP.items() if v["verdict"] == "DERIVED"]
    ok = True
    if "fail" not in _norm(sm_cell):
        _fail("D", f"C2 SM-gloss cell does not carry FAIL: {sm_cell[:80]!r}")
        ok = False
    if "h.2" not in _norm(sm_cell):
        _fail("D", "C2 SM-gloss cell does not cite H.2")
        ok = False
    if derived_cells:
```

```
        _fail("D", f"map has DERIVED cells {derived_cells} but C2 issues blanket FAIL — "
                   f"the row needs qualification")
        ok = False
    if ok:
        _ok("D", f"C2 carries FAIL citing H.2; consistent with {len(derived_cells)} DERIVED "
                 f"cells in the map")


# ---------------------------------------------------------------------------
# Check E — §3.x verdict sentences of the form "H.2's verdict for X is Y".
# A verdict token counts only in this syntactic slot — the same token in
# running prose is not a verdict claim and is ignored.
# ---------------------------------------------------------------------------
def check_E():
    print("\n[E] 'H.2's verdict for X is Y' sentences vs extraction map")
    flat = _norm(text)
    pat = re.compile(
        r"h\.2's verdict for ([a-z][a-z ]*?) is (gap|refuted|derived)"
        r"(, not (gap|refuted|derived))?")
    found = list(pat.finditer(flat))
    if not found:
        print("  note [E]: no 'H.2's verdict for X is Y' sentences present — nothing to check")
        return
    ok = True
    chains_by_prop = {}
    for (p, c) in RECORD_MAP:
        chains_by_prop.setdefault(p, []).append(c)
    for m in found:
        prop = _canon_prop(m.group(1))
        claimed = m.group(2).upper()
        denied = m.group(4).upper() if m.group(4) else None
        if prop not in chains_by_prop:
            _fail("E", f"verdict sentence names {m.group(1)!r} — no record cell (unmapped property)")
            ok = False
            continue
        if len(chains_by_prop[prop]) &gt; 1:
            # Ambiguous property: the sentence must name exactly one chain.
            sent = flat[max(0, m.start() - 200):m.end() + 200]
            named = [c for c in chains_by_prop[prop] if _norm(c) in sent]
            if len(named) != 1:
                _fail("E", f"verdict sentence for {prop!r} does not disambiguate its chain "
                           f"(spin has two)")
                ok = False
                continue
            key = (prop, named[0])
        else:
            key = (prop, chains_by_prop[prop][0])
        want = RECORD_MAP[key]["verdict"]
        if claimed != want:
            _fail("E", f"verdict sentence: {key!r} claimed {claimed!r}, record says {want}")
            ok = False
        if denied is not None and want == denied:
            _fail("E", f"verdict sentence: {key!r} says 'not {denied}' but the record IS {want}")
            ok = False
    if ok:
        _ok("E", f"{len(found)} verdict sentence(s) agree with the record")


# ---------------------------------------------------------------------------
# Check F — §8.1 spin row must cite both §8.3 sub-verdicts (anti-collapse:
# the split must not be silently reduced to one label in the H.1 table).
# ---------------------------------------------------------------------------
def check_F():
    print("\n[F] §8.1 spin row: both §8.3 sub-verdicts cited (anti-collapse)")
    span = _section_span("8.1")
    if span is None:
        _fail("F", "§8.1 heading not found")
        return
    rows = _table_rows(span)
    if rows is None:
        _fail("F", "§8.1 table has a malformed row (&lt; 3 cells)")
        return
    spin_row = None
    for cells in rows:
        if _canon_prop(cells[0]).startswith("intrinsic spin"):
            spin_row = cells
            break
    if spin_row is None:
        _fail("F", "§8.1 table: no spin row — dropped property")
        return
```

```
    badge_cell = _norm(" ".join(spin_row))
    ok = True
    for tag in ("8.3a", "8.3b"):
        if tag not in badge_cell:
            _fail("F", f"§8.1 spin row does not cite §{tag} — the split is collapsed")
            ok = False
    if ok:
        _ok("F", "spin row cites §8.3a and §8.3b — no verdict collapse")
def main():
    print("=" * 70)
    print("H.3 — VERDICT-LAYER CONSISTENCY (structural, not substring)")
    print("Cross-layer transcription invariant over the paper's verdict claims.")
    print(f"Draft: {DRAFT}")
    print("=" * 70)

    check_G()  # map shape first — everything else assumes it
    check_A()  # §8.2 table
    check_B()  # §8.3 verdict lines
    check_C()  # §8.4 alignment table
    check_D()  # §8.5 C2 row
    check_E()  # §3.x verdict sentences
    check_F()  # §8.1 spin row anti-collapse

    print("\n" + "=" * 70)
    if FAILURES:
        print(f"H.3 RESULT: {len(FAILURES)} INCONSISTENCY(IES) — the paper's verdict")
        print("  layers disagree with the H.2 record (or a layer is missing).")
        print("  Each FAIL above names the check, the section, and the witness.")
        return 1
    print("H.3 RESULT: CONSISTENT — 7/7 record cells match across §8.1, §8.2,")
    print("  §8.3, §8.4, §8.5-C2, and the §3.x verdict sentences.")
    print("  What was proven: the paper's tabulated verdict layers say the same")
    print("  thing. What was NOT proven: that the verdicts are correct, that")
    print("  H.2's chains are good derivations, or that any prose overreaches")
    print("  any equation — those remain the author's classifications.")
    return 0


if __name__ == "__main__":
    sys.exit(main())
```

Listing 9: H4 honesty comparison

```
#!/usr/bin/env python3
"""H.4 — Honesty Comparison for Paper 11.5 (v24 FORTRESS rebuild).

Scores Paper 11's native ledger against the Standard Model's "intrinsic"
prose gloss on seven honesty criteria C1-C7. This rebuild answers Dervis's
v24 must: no hardcoded scorecard verdicts. Every scored cell is COMPUTED at
run time against the draft text supplied on the command line (argv[1]); no
draft content is hardcoded and no author dict literal carries a verdict.

CELL KINDS (printed beside every verdict):
  COMPUTED        — a predicate evaluated against the input draft text.
                    The script prints the predicate and the evidence locator
                    (draft line numbers), so a reader can re-run the check.
                    What the machine establishes is ANCHOR PRESENCE: that the
                    draft carries the compliance machinery the criterion
                    names (declared-assumption labels, null-result anchors,
                    badge tokens, falsification statements, the Stage N/P
                    boundary declaration, encounter-indexing language).
                    Anchor presence is not semantic adequacy: whether the
                    labels are correctly applied, the falsification
                    conditions adequate, or the boundary real is author
                    judgment, stated as such in each cell's note.
  INHERITED       — a verdict re-computed at THIS execution from a sibling
                    script's output, not copied from prose. C1/C4-SM re-run
                    H.1's badge rule (audit_sm) over H.1's claim table;
                    C2-SM re-runs the rebuilt H.3 (verdict-layer consistency)
                    and inherits the consistently-RECORDED author verdict
                    (FAIL) iff H.3 reports CONSISTENT — inheriting a
                    bookkeeping-consistency result, not a proof the verdict
                    is correct. Each inherited cell carries the sibling's
                    own disclosed limit: H.1's DERIVED/DECLARED/SMUGGLED
                    mechanism labels are H.1's author classification (H.4
                    computes the F.49 badge rule over them; it does not
                    re-derive the labels); the rebuilt H.3 proves the
                    paper's verdict layers agree, not that the verdicts are
```

```
                    correct or that any prose overreaches any equation
                    (TEAM H.3 owns H.3's checks).
  HUMAN-JUDGMENT  — no machine predicate exists for this cell. The script
                    does NOT compute a fake pass: it locates the paper's own
                    stated verdict (the **PASS**/**FAIL** bold markers in the
                    §8.5 table row) and reports it, labeled as the author's
                    judgment, with the row's line number as the locator.
                    If the row or its markers are absent the cell is
                    UNVERIFIABLE (fail closed), never guessed.

WHAT THIS ANSWERS (§8.5's question): "If the SM's intrinsic-property claims
were held to Paper 11's declared epistemic standards, what does the
comparison show — stated only as far as the machine can check?" The honest
answer is now two-part: (a) on the machine-evaluated cells, Paper 11's draft
carries the named compliance anchors on 6/6 criteria while the SM gloss
earns 0/3; (b) five cells (C2-Paper-11; C3/C5/C6/C7-SM) remain author
judgment, reported as such. The old "7/7 vs. 0/7" headline is RETIRED: it
counted author-typed verdicts as machine results. The new headline counts
only what the machine evaluated and labels the rest — it is weaker, and
honest about being weaker.

INPUT_PROVENANCE (per Paper 11 V17/P2 staple):
  - Criterion-to-anchor predicate mappings (C1..C7, Paper-11 side):
    class=declared-assumption (the author's design choice of which text
    anchors count as the compliance machinery for each criterion; the
    thresholds — &gt;=1 hit, &gt;=2 hits, +-3 lines — are the author's chosen
    strictness, declared here, not derived).
  - H.1 claim table + DERIVED/DECLARED/SMUGGLED mechanism labels:
    class=declared-assumption (H.1's author classification, consumed as
    data; H.4 re-computes the F.49 badge rule over it at run time).
  - H.3 subprocess output (the "H.3 RESULT: ..." line):
    class=control (sibling script H3_prose_equation_consistency.py — the v24
    verdict-layer consistency rebuild — run at H.4's execution on the same
    draft; TEAM H.3 owns H.3's checks. H.4 consumes only CONSISTENT vs
    INCONSISTENT and inherits the consistently-recorded FAIL verdict; it
    inherits no prose/equation verdict from H.3, which no longer computes one).
  - §8.5 table-row **PASS**/**FAIL** bold markers (HUMAN-JUDGMENT cells):
    class=paper-defined (the paper's own stated verdicts, parsed from the
    input draft text at run time).
  - No arbitrary-representative inputs; no cited-paper constants.

What is verified: (1) every verdict string in the output was produced by an
evaluator function at run time — the module contains no verdict-carrying
dict literals (the --self-test asserts this structurally: any cell without
the evaluator stamp, or with an empty/unresolvable evidence locator, fails
the run); (2) each COMPUTED cell's predicate and evidence locator are
printed, re-runnable by the reader; (3) each INHERITED cell names the
sibling run it was computed from; (4) each HUMAN-JUDGMENT cell points at
the draft line carrying the author's stated verdict.

What stays outside the machine check: semantic adequacy of the anchors
(whether declared assumptions are well-declared, falsification conditions
adequate, the Stage N/P boundary real); H.1's mechanism labels; H.3's
prose/equation link; all HUMAN-JUDGMENT cells' content; whether the seven
criteria are the right criteria (the stacked-deck framing, §8.5 prose).

Exit 0 on success. Usage: H4_honesty_comparison.py &lt;draft-text-path&gt;
[--self-test]
"""
import importlib
import re
import subprocess
import sys
from pathlib import Path

HERE = Path(__file__).resolve().parent
H1_MODULE = "H1_sm_badge_audit"
H3_NAME = "H3_prose_equation_consistency.py"


def sibling_paths(draft_path):
    """Sibling scripts live beside the draft (paper_11_5_draft/scripts/);
    fall back to H.4's own directory for standalone testing. Resolved at
    run time from the draft argument — never hardcoded."""
    beside = Path(draft_path).parent / "scripts"
    if (beside / H3_NAME).is_file():
        return beside
    return HERE

COMPUTED = "COMPUTED"
```

```
INHERITED = "INHERITED"
JUDGMENT = "HUMAN-JUDGMENT"

# Evaluator stamp: make_cell is the ONLY constructor that sets it.
# A hand-built cell dict (a reintroduced baked verdict) lacks the stamp and
# is rejected by validate_cells. This is the anti-regression mechanism.
_EVAL_STAMP = object()

VERDICT_OK = {"PASS", "FAIL", "UNVERIFIABLE"}


def make_cell(criterion, side, kind, verdict, evidence, predicate):
    """Sole cell constructor. Verdicts exist only as its return values."""
    if kind not in (COMPUTED, INHERITED, JUDGMENT):
        raise ValueError(f"unknown cell kind: {kind!r}")
    if not (verdict in VERDICT_OK or verdict.startswith("PARTIAL")):
        raise ValueError(f"unknown verdict: {verdict!r}")
    return {
        "criterion": criterion,
        "side": side,
        "kind": kind,
        "verdict": verdict,
        "evidence": evidence,
        "predicate": predicate,
        "_eval": _EVAL_STAMP,
    }


def validate_cells(cells, n_lines):
    """Fail closed. Returns (ok, problems)."""
    problems = []
    for c in cells:
        tag = f"{c.get('criterion')}/{c.get('side')}"
        if c.get("_eval") is not _EVAL_STAMP:
            problems.append(
                f"{tag}: no evaluator stamp — baked verdict rejected")
            continue
        if c.get("kind") not in (COMPUTED, INHERITED, JUDGMENT):
            problems.append(f"{tag}: unknown kind {c.get('kind')!r}")
        v = c.get("verdict", "")
        if not (v in VERDICT_OK or v.startswith("PARTIAL")):
            problems.append(f"{tag}: unknown verdict {v!r}")
        ev = c.get("evidence") or ""
        if not ev.strip():
            problems.append(f"{tag}: empty evidence locator")
        for m in re.finditer(r"L(\d+)", ev):
            ln = int(m.group(1))
            if not 1 &lt;= ln &lt;= n_lines:
                problems.append(
                    f"{tag}: evidence line L{ln} outside draft (1..{n_lines})")
    return (not problems), problems


# ---------------------------------------------------------------- draft I/O

def load_draft(path):
    p = Path(path)
    if not p.is_file():
        print(f"H.4: draft not found: {p}", file=sys.stderr)
        sys.exit(2)
    return p, p.read_text(encoding="utf-8").splitlines()


def find_lines(lines, pattern, flags=0):
    rx = re.compile(pattern, flags)
    return [i + 1 for i, l in enumerate(lines) if rx.search(l)]


def evidence_str(hits, label, max_show=3):
    shown = ", ".join(f"L{n}" for n in hits[:max_show])
    more = f" (+{len(hits) - max_show} more)" if len(hits) &gt; max_show else ""
    return f"{label}: {len(hits)} hit(s) at {shown}{more}"


# ------------------------------------------------ Paper-11 side: COMPUTED

def eval_c1_p11(lines):
    ip = find_lines(lines, r"INPUT_PROVENANCE")
    da = find_lines(lines, r"declared assumption", re.IGNORECASE)
    verdict = "PASS" if (ip and da) else "FAIL"
```

```
    evidence = (evidence_str(ip, "INPUT_PROVENANCE") + "; "
                + evidence_str(da, "'declared assumption'"))
    return verdict, evidence


def eval_c3_p11(lines):
    f57 = set(find_lines(lines, r"\bF\.57\b"))
    null = set(find_lines(lines, r"\bnull\b", re.IGNORECASE))
    near = sorted(n for n in f57 if any(abs(n - m) &lt;= 3 for m in null))
    verdict = "PASS" if near else "FAIL"
    if near:
        loc = ", ".join(f"L{n}" for n in near[:3])
        evidence = f"F.57 within 3 lines of 'null' at {loc}"
    else:
        evidence = "check ran: no F.57/null-result anchor found in draft"
    return verdict, evidence


def eval_c4_p11(lines):
    la = find_lines(lines, r"\[LEVEL A")
    lb = find_lines(lines, r"\[LEVEL B")
    lc = find_lines(lines, r"\[LEVEL C")
    f38 = find_lines(lines, r"\bF\.38\b")
    verdict = "PASS" if (la and lb and lc and f38) else "FAIL"
    evidence = (f"[LEVEL A]x{len(la)} [LEVEL B]x{len(lb)} "
                f"[LEVEL C]x{len(lc)} F.38x{len(f38)}; "
                + evidence_str(la, "first [LEVEL A]"))
    return verdict, evidence


def eval_c5_p11(lines):
    fc = find_lines(lines, r"falsification condition", re.IGNORECASE)
    verdict = "PASS" if len(fc) &gt;= 2 else "FAIL"
    evidence = evidence_str(fc, "'falsification condition'")
    return verdict, evidence


def eval_c6_p11(lines):
    sn = find_lines(lines, r"\bStage N\b")
    sp = find_lines(lines, r"\bStage P\b")
    f42 = find_lines(lines, r"\bF\.42\b")
    verdict = "PASS" if (sn and sp and f42) else "FAIL"
    evidence = (f"Stage N x{len(sn)}, Stage P x{len(sp)}, F.42 x{len(f42)}; "
                + evidence_str(sn, "first Stage N"))
    return verdict, evidence
def eval_c7_p11(lines):
    ei = find_lines(lines, r"encounter-index", re.IGNORECASE)
    verdict = "PASS" if ei else "FAIL"
    evidence = evidence_str(ei, "'encounter-index'")
    return verdict, evidence


# ------------------------------------------------ SM side: INHERITED (H.1)

def import_h1(scripts_dir):
    if str(scripts_dir) not in sys.path:
        sys.path.insert(0, str(scripts_dir))
    return importlib.import_module(H1_MODULE)


def h1_badge_counts(claims, audit_fn):
    """Re-compute the F.49 badge rule over H.1's claim table at run time."""
    badged = 0
    for claim in claims:
        badge, _ = audit_fn(claim)
        if not badge.startswith("NO BADGE"):
            badged += 1
    return badged, len(claims) - badged


def eval_sm_h1(scripts_dir):
    """Run H.1's badge rule now; return (badged, total, evidence)."""
    h1 = import_h1(scripts_dir)
    badged, no_badge = h1_badge_counts(h1.CLAIMS, h1.audit_sm)
    total = len(h1.CLAIMS)
    evidence = (
        f"H.1 badge rule re-run this execution over {total} claims: "
        f"{no_badge}/{total} NO BADGE, {badged}/{total} badged. "
        f"Mechanism labels (DERIVED/DECLARED/SMUGGLED) are H.1's author "
        f"classification; H.4 computed the F.49 rule over them, it did not "
```

```
        f"re-derive the labels.")
    return badged, no_badge, total, evidence


# ------------------------------------------------- SM side: INHERITED (H.3)

def run_h3(draft_path, scripts_dir):
    """Re-run the rebuilt H.3 (verdict-layer consistency) on the same draft.

    The v24 H.3 is NOT a prose/equation check: it proves the paper's
    tabulated verdict layers agree with each other (7/7 record cells match
    across §8.1/§8.2/§8.3/§8.4/§8.5-C2/§3.x). It does NOT prove the verdicts
    correct, H.2's chains valid, or any prose/equation overreach — the
    mismatch claim remains the author's classification (§8.4). TEAM H.3 owns
    H.3's checks; H.4 consumes only the CONSISTENT/INCONSISTENT result and
    inherits no prose/equation verdict from it.

    Returns (True, evidence) on CONSISTENT, (False, evidence) on
    INCONSISTENT, (None, evidence) when the result line is missing
    (fail closed)."""
    h3_file = scripts_dir / H3_NAME
    if not h3_file.is_file():
        return None, f"H.3 script not found in {scripts_dir}"
    r = subprocess.run([sys.executable, str(h3_file), str(draft_path)],
                       capture_output=True, text=True)
    out = r.stdout
    if re.search(r"H\.3 RESULT:\s*CONSISTENT", out):
        evidence = (
            "H.3 (verdict-layer consistency) re-run this execution: CONSISTENT — "
            "7/7 record cells match across §8.1, §8.2, §8.3, §8.4, §8.5-C2, and "
            "the §3.x verdict sentences; Check D confirms the §8.5 C2 row carries "
            "the author's FAIL verdict citing H.2. What H.3 proves: the paper's "
            "tabulated verdict layers agree. What it does NOT prove: that the "
            "verdicts are correct, or that any prose overreaches any equation — "
            "the mismatch claim remains the author's classification (§8.4).")
        return True, evidence
    m = re.search(r"H\.3 RESULT:\s*(\d+)\s+INCONSISTENCY", out)
    if m or r.returncode != 0:
        n = m.group(1) if m else "?"
        evidence = (
            f"H.3 re-run this execution: INCONSISTENT ({n} inconsistencies) — "
            f"the verdict layers disagree, so no consistently-recorded C2 verdict "
            f"exists to inherit. Failing closed.")
        return False, evidence
    return None, "H.3 output lacked an 'H.3 RESULT:' line — refusing to guess"


# ------------------------------------------------- HUMAN-JUDGMENT cells

def eval_judgment(lines, crit, side_idx):
    """No machine predicate exists: report the paper's own stated verdict,
    parsed from the §8.5 table row's **PASS**/**FAIL** markers."""
    rows = [(i + 1, l) for i, l in enumerate(lines)
            if re.match(r"\|\s*" + re.escape(crit) + r"\s*:", l.lstrip())
            and "**" in l]
    if not rows:
        return ("UNVERIFIABLE",
                f"check ran: no **-marked {crit} table row found — "
                f"author's stated judgment absent",
                f"locate the {crit} row in §8.5 and state the verdict")
    ln, row = rows[0]
    # Column layout is version-tolerant: the v23 table is
    # | Cn: label | P11 | SM |, the v24 table adds a Kind column
    # | Cn: label | Kind | P11 | SM |. The Kind column carries no
    # **PASS**/**FAIL** markers, so sides are the non-kind columns.
    cols = [p.strip() for p in row.split("|")[1:-1]]
    rest = cols[1:]  # drop the criterion-label column
    if (len(rest) &gt;= 3
            and re.search(r"COMPUTED|INHERITED|HUMAN-JUDGMENT", rest[0])):
        rest = rest[1:]  # drop the Kind column
    if len(rest) &lt; 2:
        return ("UNVERIFIABLE",
                f"L{ln}: {crit} row lacks two side columns",
                "repair the §8.5 table row")
    cell_text = rest[side_idx]
    m = re.search(r"\*\*(PASS|FAIL)\*\*", cell_text)
    if not m:
        return ("UNVERIFIABLE",
                f"L{ln}: {crit} row side lacks a **PASS**/**FAIL** marker",
                "author must state the judgment in the row")
```

```
    verdict = m.group(1)
    reason = re.sub(r"\*\*(PASS|FAIL)\*\*\s*—?\s*", "", cell_text).strip()
    # The note already labels this the author's stated reason; drop a
    # redundant in-row "author's judgment/assessment:" prefix if present.
    reason = re.sub(r"^author's (judgment|assessment):\s*", "", reason,
                    flags=re.IGNORECASE)
    if len(reason) &gt; 220:
        reason = reason[:217] + "..."
    evidence = f"L{ln}: author's stated verdict parsed from the §8.5 table row"
    return verdict, evidence, f"author's stated reason: {reason}"


# ---------------------------------------------------------------------- assembly

P11_SIDE = "Paper 11"
SM_SIDE = "SM gloss"

P11_EVALUATORS = {
    "C1": (eval_c1_p11,
           "draft carries INPUT_PROVENANCE blocks and 'declared assumption' labels"),
    "C3": (eval_c3_p11,
           "draft publishes an F.57-tradition null result (F.57 within 3 lines of 'null')"),
    "C4": (eval_c4_p11,
           "draft carries [LEVEL A/B/C] badge tokens and the F.38 registry anchor "
           "(the '[LEVEL A' prefix count includes the formalized "
           "[LEVEL A, author-authorized] subtype form)"),
    "C5": (eval_c5_p11,
           "draft states falsification conditions (&gt;=2 'falsification condition' hits)"),
    "C6": (eval_c6_p11,
           "draft declares the Stage N / Stage P boundary (Stage N, Stage P, F.42 anchors)"),
    "C7": (eval_c7_p11,
           "draft claims encounter-indexing ('encounter-index' language present)"),
}

# Cells with no machine predicate: (criterion, side, side_idx_in_row)
JUDGMENT_CELLS = [
    ("C2", P11_SIDE, 0,
     "no machine check of Paper-11 prose/equation alignment exists; "
     "the old scorecard already recorded this as the author's assessment"),
    ("C3", SM_SIDE, 1,
     "whether textbooks acknowledge H.2's failed derivation is a literature "
     "claim, not checkable from this draft"),
    ("C5", SM_SIDE, 1,
     "whether any textbook states a falsification condition for the "
     "intrinsic-possession gloss is a literature claim, not checkable here"),
    ("C6", SM_SIDE, 1,
     "whether the SM gloss reifies bookkeeping is a characterization of "
     "textbook prose, argued in §3/§8.5, not machine-checkable"),
    ("C7", SM_SIDE, 1,
     "the EFT-trap argument is philosophical/argumentative, not "
     "machine-checkable"),
]


def evaluate(draft_path):
    """Run every cell evaluator. Returns (cells, n_lines)."""
    _, lines = load_draft(draft_path)
    n_lines = len(lines)
    scripts_dir = sibling_paths(draft_path)
    cells = []

    for crit, (fn, pred) in P11_EVALUATORS.items():
        verdict, evidence = fn(lines)
        note = ("anchor presence only — whether the machinery is correctly "
                "applied stays author judgment")
        cells.append(make_cell(crit, P11_SIDE, COMPUTED, verdict, evidence,
                               f"{pred}; {note}"))
    # C2 Paper-11: judgment (no predicate)
    verdict, evidence, note = eval_judgment(lines, "C2", 0)
    cells.append(make_cell("C2", P11_SIDE, JUDGMENT, verdict, evidence,
                           JUDGMENT_CELLS[0][3] + "; " + note))

    # SM side, inherited from H.1
    badged, no_badge, total, ev_h1 = eval_sm_h1(scripts_dir)
    v_c1 = "FAIL" if no_badge == total else f"PARTIAL ({no_badge}/{total} no-badge)"
    cells.append(make_cell("C1", SM_SIDE, INHERITED, v_c1, ev_h1,
                           "H.1's badge rule re-computed at this execution; "
                           "FAIL iff every claim is NO BADGE"))
    v_c4 = "FAIL" if badged == 0 else f"PARTIAL ({badged}/{total} badged)"
    cells.append(make_cell("C4", SM_SIDE, INHERITED, v_c4, ev_h1,
```

```
                          "same H.1 re-run; FAIL iff zero claims earn A/B/C"))

    # SM side, inherited from the rebuilt H.3 (verdict-layer consistency).
    # The inherited verdict is the consistently-RECORDED author verdict
    # (FAIL, per Check D) — not a machine proof that the verdict is correct.
    h3_ok, ev_h3 = run_h3(draft_path, scripts_dir)
    h3_pred = ("rebuilt H.3 verdict-layer consistency re-run on the input draft; "
               "verdict FAIL iff H.3 reports CONSISTENT — the consistently recorded "
               "author verdict for the SM gloss on C2 is FAIL (Check D confirms the "
               "C2 row carries FAIL citing H.2); UNVERIFIABLE iff the layers "
               "disagree, or the H.3 run itself fails")
    if h3_ok is None:
        cells.append(make_cell("C2", SM_SIDE, INHERITED, "UNVERIFIABLE", ev_h3,
                               h3_pred))
    elif h3_ok:
        cells.append(make_cell("C2", SM_SIDE, INHERITED, "FAIL", ev_h3, h3_pred))
    else:
        cells.append(make_cell("C2", SM_SIDE, INHERITED, "UNVERIFIABLE", ev_h3,
                               h3_pred))

    # SM side, judgment cells
    for crit, side, side_idx, why in JUDGMENT_CELLS[1:]:
        verdict, evidence, note = eval_judgment(lines, crit, side_idx)
        cells.append(make_cell(crit, side, JUDGMENT, verdict, evidence,
                               why + "; " + note))
    return cells, n_lines


def print_report(cells, draft_path):
    print("=" * 70)
    print("H.4 — HONESTY COMPARISON (v24 rebuild: computed, not printed)")
    print("Paper 11 native ledger vs. Standard Model 'intrinsic' gloss")
    print(f"Draft: {draft_path}")
    print("=" * 70)
    order = {"C1": 1, "C2": 2, "C3": 3, "C4": 4, "C5": 5, "C6": 6, "C7": 7}
    for c in sorted(cells, key=lambda c: (order[c["criterion"]], c["side"])):
        print(f"\n[{c['kind']}] {c['criterion']} ({c['side']}): {c['verdict']}")
        print(f"  predicate: {c['predicate']}")
        print(f"  evidence:  {c['evidence']}")
    print("\n" + "=" * 70)
    comp_p11 = [c for c in cells
                if c["side"] == P11_SIDE and c["kind"] == COMPUTED]
    inh_sm = [c for c in cells
              if c["side"] == SM_SIDE and c["kind"] == INHERITED]
    jud = [c for c in cells if c["kind"] == JUDGMENT]
    p11_pass = sum(1 for c in comp_p11 if c["verdict"] == "PASS")
    sm_pass = sum(1 for c in inh_sm if c["verdict"] == "PASS")
    print("TALLY (machine-evaluated cells only):")
    print(f"  Paper 11 COMPUTED: {p11_pass}/{len(comp_p11)} PASS")
    print(f"  SM gloss INHERITED: {sm_pass}/{len(inh_sm)} PASS")
    print("HUMAN-JUDGMENT cells (author's stated verdicts, not machine findings):")
    for c in sorted(jud, key=lambda c: (order[c["criterion"]], c["side"])):
        print(f"  {c['criterion']} ({c['side']}): {c['verdict']} — {c['evidence']}")
    print("=" * 70)
    print("The old '7/7 vs. 0/7' headline is retired: it counted author-typed")
    print("verdicts as machine results. What the machine evaluated is above;")
    print("the rest is labeled judgment. See the docstring for what stays")
    print("outside the check.")


def self_test(draft_path):
    """Structural anti-regression test: no baked verdict can pass."""
    print("H.4 --self-test: structural anti-regression checks")
    cells, n_lines = evaluate(draft_path)
    failures = []

    ok, problems = validate_cells(cells, n_lines)
    print(f"  [1] live cells validate: {'PASS' if ok else 'FAIL'}")
    if not ok:
        failures += problems

    # Mutant A: a reintroduced baked verdict (hand-built dict, no stamp).
    baked = {"criterion": "C1", "side": P11_SIDE, "kind": COMPUTED,
             "verdict": "PASS", "evidence": "L1",
             "predicate": "smuggled verdict"}
    ok_b, _ = validate_cells([baked], n_lines)
    print(f"  [2] baked-verdict mutant rejected: "
          f"{'PASS' if not ok_b else 'FAIL'}")
    if ok_b:
        failures.append("baked-verdict mutant was NOT rejected")
```

```
    # Mutant B: verdict without an evidence locator.
    no_ev = make_cell("C9", P11_SIDE, COMPUTED, "PASS", "",
                      "no locator")
    ok_e, _ = validate_cells([no_ev], n_lines)
    print(f"  [3] missing-locator mutant rejected: "
          f"{'PASS' if not ok_e else 'FAIL'}")
    if ok_e:
        failures.append("missing-locator mutant was NOT rejected")

    # Mutant C: evidence locator pointing outside the draft.
    bad_ln = make_cell("C9", P11_SIDE, COMPUTED, "PASS",
                       f"L{n_lines + 5000}", "dangling locator")
    ok_l, _ = validate_cells([bad_ln], n_lines)
    print(f"  [4] dangling-locator mutant rejected: "
          f"{'PASS' if not ok_l else 'FAIL'}")
    if ok_l:
        failures.append("dangling-locator mutant was NOT rejected")

    if failures:
        print("SELF-TEST FAILED:")
        for f in failures:
            print(f"  - {f}")
        return 1
    print("SELF-TEST: all structural checks passed.")
    return 0


def main(argv):
    if len(argv) &lt; 2 or argv[1] in ("-h", "--help"):
        print("usage: H4_honesty_comparison.py &lt;draft-text-path&gt; [--self-test]",
              file=sys.stderr)
        return 2
    draft_path = argv[1]
    if "--self-test" in argv[2:]:
        return self_test(draft_path)
    cells, n_lines = evaluate(draft_path)
    ok, problems = validate_cells(cells, n_lines)
    if not ok:
        print("H.4 VALIDATION FAILED (fail closed):", file=sys.stderr)
        for p in problems:
            print(f"  - {p}", file=sys.stderr)
        return 1
    print_report(cells, draft_path)
    return 0


if __name__ == "__main__":
    sys.exit(main(sys.argv))
```

Listing 10: MC1 shell montecarlo

```
#!/usr/bin/env python3
"""MC.1 — Structural Monte Carlo: inverse-square scaling from shell counting.

Paper 11 §8.5 derives S(d) = s^2 / (4d^2 + 2): the per-position share of scan
workload over relay-hop shells, with N(d) = 4d^2 + 2 from Paper 10 §5.3.1
(taxicab shell count) and uniform load partition (Paper 10 §2.4.7).

HEADLINE [LEVEL A: MACHINE / AUTHOR]: the fitted exponent -1.9886 — the REAL number, recomputed
live by this script. MACHINE half: step 3 fits a least-squares line to
(log d, log(1/(4d^2+2))) over d = 5..20, prints the slope (-1.9885612518827713),
and asserts it rounds to -1.9886. AUTHOR half: the slope IS the handshake cost,
and -1.9886 at 4dp IS the real number — author-stipulated 2026-10-18
("we're not rounding nothing"). This is the cost of the
communicative handshake between discrete shells producing emergent
inverse-square; nothing is lost, -2 recovers asymptotically (D2 handshake
framing). The number IS the fit.

KEEP+DISCLOSE (author-authorized 2026-10-18 — "use it when we need it, and
disclose why"): this script DOES use continuum-adjacent machinery — math.log
and a least-squares fit — because the handshake cost is defined as the fitted
exponent, and no integer-only route yields it. The fit is the computation, not
scaffolding around the computation. It is used only here, and it is disclosed
fully here. Per the §0.5.1 framework-wide rule, no approximation or translator
ever stands in for the real number: the real -1.9886 is badged [LEVEL A: MACHINE / AUTHOR]
beside every auxiliary form.

Steps:
1. Shell count: brute-force integer lattice count vs 4d^2+2 (unchanged).
```

```
2. Workload sampling: seeded INTEGER rng (random.Random.randrange, which draws
   from the Mersenne Twister bit-generator via getrandbits — integer-native,
   never a float). Genuine sampling check: every shell position's time-averaged
   share must concentrate within a rational tolerance of 1/N(d), verified by
   exact integer comparisons. (The v23 script's printed "MC share" was
   algebraically identical to theory by construction — sum(totals) is forced —
   so it tested nothing; this step now tests what the sampling actually does.)
3. Fitted exponent [LEVEL A: MACHINE / AUTHOR]: log-log least-squares slope of 1/(4d^2+2) over
   d = 5..20 — recomputed, printed, asserted to round to -1.9886.
4. [LEVEL B] AUXILIARY: the exact-rational bound |R(d) - 1| &lt; 1/d^2,
   decreasing monotonically, for d = 5..19, where
       R(d) = [N(d+1)/N(d)] / [(d+1)^2/d^2].
   Why it exists: it states the +2 correction's decay in exact rational
   arithmetic — a translator/convenience bound for readers who want the gap
   without the fit. It is NOT the headline. The real number is the fitted
   exponent -1.9886 [LEVEL A: MACHINE / AUTHOR], badged right beside it.

HONEST SCOPE (unchanged from v23):
- The uniformity assumption is inherited (Paper 10 Uniform Load Partition).
  The MC assumes uniform random selection, so it verifies
  "uniform sampling -&gt; 1/d^2 frequencies" (consistency), not uniformity itself.
- The shell count check (step 1) IS independent: brute force vs formula.
- This is structural MC (ledger consistency), not dynamical MC (no detector
  predictions). Absolute scale is out of scope (Paper 11 §0.5 architecture).
- The fill rules — which encounter actualizes with what probability at a
  given tick — are Paper 12's work (§11.6); nothing here certifies them.

INPUT_PROVENANCE:
  - N(d) = 4d^2+2: class=cited-paper (Paper 10 §5.3.1).
  - Uniform load partition: class=cited-paper (Paper 10 §2.4.7; assumed here).
  - S(d) = s^2/N(d): class=paper-defined (Paper 11 §8.5 derivation).
  - RNG: class=control (seeded Mersenne Twister, integer draws only).
  - Fitted exponent -1.9886: class=paper-defined (Paper 11.5 §11.4; the D2
    handshake cost, author-authorized 2026-10-18 — defined as the log-log
    fitted exponent, which is why math.log/least-squares are used and
    disclosed rather than integer-native).
  - Exact-rational bound: class=cited-paper (Paper 10 §5.3.1 N(d), exact
    rational arithmetic; carried as a [LEVEL B] translator, not the headline).
"""
import math
import random
import sys
from fractions import Fraction


def taxicab_shell_count(d):
    """Brute-force count of integer lattice points with |x|+|y|+|z| = d."""
    count = 0
    for x in range(-d, d + 1):
        for y in range(-d, d + 1):
            for z in range(-d, d + 1):
                if abs(x) + abs(y) + abs(z) == d:
                    count += 1
    return count


def formula_N(d):
    return 4 * d * d + 2


def mc_workload_counts(d, s2=36, n_ticks=20000, seed=12345):
    """Integer-native workload sampling. Returns per-position tick totals.

    Uses random.Random(...).randrange(N) ONLY. CPython's randrange draws from
    getrandbits (the Mersenne Twister bit-generator): pure integer arithmetic,
    no float RNG, no continuous sampling measure.
    """
    rng = random.Random(seed + d)
    N = formula_N(d)
    totals = [0] * N
    for _ in range(n_ticks):
        for _ in range(s2):
            totals[rng.randrange(N)] += 1
    return totals


def loglog_fit_exponent(d_min=5, d_max=20):
    """Least-squares slope of log(1/(4d^2+2)) against log(d).

    [LEVEL A: MACHINE / AUTHOR] computation: the fitted exponent is the real number this script
```

```
    badges. math.log and the normal equations are used AND disclosed — the
    number IS the fit (see KEEP+DISCLOSE in the docstring).
    """
    xs, ys = [], []
    for d in range(d_min, d_max + 1):
        xs.append(math.log(d))
        ys.append(math.log(1 / (4 * d * d + 2)))
    n = len(xs)
    sx = sum(xs)
    sy = sum(ys)
    sxx = sum(x * x for x in xs)
    sxy = sum(x * y for x, y in zip(xs, ys))
    return (n * sxy - sx * sy) / (n * sxx - sx * sx)


def planted_mutants():
    """Mutant battery. Each mutant breaks a load-bearing assumption; the
    script's checks must catch it (report the failure) — proving the checks
    are genuine, not vacuous."""
    print("\n--- PLANTED MUTANTS ---")
    results = []

    # M1: wrong shell formula N(d) = 4d^2+3. Step 1 must MISMATCH.
    m1_caught = any(taxicab_shell_count(d) != 4 * d * d + 3 for d in range(1, 11))
    results.append(("M1: wrong shell formula (4d^2+3) rejected by brute force",
                    m1_caught))

    # M2: degenerate RNG (all workload to position 0). Step 2's concentration
    # check must FAIL — proving it tests the sampling, not the algebra.
    s2, n_ticks = 36, 20000
    d = 10
    N = formula_N(d)
    totals = [0] * N
    totals[0] = s2 * n_ticks  # mutant: everything piles on one position
    worst = max(abs(N * t - s2 * n_ticks) for t in totals)
    m2_caught = not (Fraction(worst, s2 * n_ticks) &lt; Fraction(1, 4))
    results.append(("M2: degenerate sampler rejected by concentration check",
                    m2_caught))

    # M3: wrong scaling theory — cubic shells N(d) = 4d^3+2. Step 4's
    # correction bound must FAIL somewhere: the analysis discriminates d^2
    # from d^3 shells, proving it tests the shell geometry, not just
    # arithmetic.
    def N_cubic(d):
        return 4 * d ** 3 + 2

    m3_caught = any(
        abs(Fraction(N_cubic(d + 1), N_cubic(d))
            / Fraction((d + 1) * (d + 1), d * d) - 1) &gt;= Fraction(1, d * d)
        for d in range(5, 20))
    results.append(("M3: cubic-shell theory rejected by correction bound",
                    m3_caught))

    # M4: cubic-shell data 1/(4d^3+2) through the step-3 fit. The fitted
    # exponent must NOT land on -1.9886 — proving the fit discriminates shell
    # geometry (d^2 vs d^3), i.e. the fit tests something real rather than
    # echoing its own input.
    xs = [math.log(d) for d in range(5, 21)]
    ys = [math.log(1 / (4 * d ** 3 + 2)) for d in range(5, 21)]
    n = len(xs)
    sx, sy = sum(xs), sum(ys)
    sxx = sum(x * x for x in xs)
    sxy = sum(x * y for x, y in zip(xs, ys))
    cubic_exp = (n * sxy - sx * sy) / (n * sxx - sx * sx)
    m4_caught = round(cubic_exp, 4) != -1.9886
    results.append((f"M4: cubic-shell fit ({round(cubic_exp, 4)}) != -1.9886 — "
                    "fit discriminates shell geometry",
                    m4_caught))

    all_caught = True
    for name, caught in results:
        print(f"  [{'CAUGHT' if caught else 'NOT CAUGHT — INVESTIGATE'}] {name}")
        all_caught &amp;= caught
    return all_caught


def main():
    print("=" * 70)
    print("MC.1 — STRUCTURAL MONTE CARLO: INVERSE-SQUARE FROM SHELL COUNTING")
    print("  (v24 rulings fold-in: fitted exponent -1.9886 restored as the real")
```

```
print("   [LEVEL A: MACHINE / AUTHOR] number; fit machinery KEEP+DISCLOSED — the number IS the fit)")
print("=" * 70)

# Step 1: independent shell count verification
print("\n--- Step 1: Taxicab shell count (brute force vs Paper 10 formula) ---")
step1_ok = True
for d in range(1, 11):
    brute = taxicab_shell_count(d)
    form = formula_N(d)
    match = "OK" if brute == form else "MISMATCH"
    if brute != form:
        step1_ok = False
    print(f"  d={d:2d}: brute force = {brute:4d},  4d^2+2 = {form:4d}  [{match}]")
if not step1_ok:
    print("SHELL COUNT MISMATCH — Paper 10 formula fails. FAIL.")
    return 1
print("  Paper 10 §5.3.1 N(d) = 4d^2+2 independently confirmed.")

# Step 2: genuine sampling check — concentration of per-position shares.
# Per-position time-average share_i = totals[i]/(s2*n_ticks); theory 1/N.
# Exact integer check: |N*totals[i] - s2*n_ticks| &lt; (s2*n_ticks)/4
# i.e. every position within relative 1/4 of the uniform share.
print("\n--- Step 2: Integer-native workload sampling (concentration) ---")
print("  (seeded integer RNG; exact rational deviation bound 1/4)")
s2, n_ticks, seed = 36, 20000, 12345
step2_ok = True
for d in range(1, 21):
    totals = mc_workload_counts(d, s2, n_ticks, seed)
    N = formula_N(d)
    if sum(totals) != s2 * n_ticks:
        print(f"  d={d:2d}: WORKLOAD NOT CONSERVED — FAIL.")
        step2_ok = False
        continue
    worst = max(abs(N * t - s2 * n_ticks) for t in totals)
    rel = Fraction(worst, s2 * n_ticks)
    ok = rel &lt; Fraction(1, 4)
    step2_ok &amp;= ok
    print(f"  d={d:2d}: N={N:4d}, worst relative deviation = {rel} "
          f"≈ {float(rel):.4f}  [{'OK' if ok else 'FAIL'}]")
if not step2_ok:
    print("SAMPLING CONCENTRATION FAILED — investigate.")
    return 1
print("  Discrete uniform sampling concentrates on 1/N(d) at every d.")

# Step 3: the fitted exponent [LEVEL A: MACHINE / AUTHOR] — recomputed live.
# KEEP+DISCLOSE: math.log and least squares are USED and DISCLOSED because
# the handshake cost is defined as the fitted exponent — no integer-only
# route yields it. The number IS the fit.
print("\n--- Step 3: Log-log fit of 1/(4d^2+2), d = 5..20 [LEVEL A: MACHINE / AUTHOR] ---")
print("  (fit machinery used and disclosed: the number IS the fit)")
exp = loglog_fit_exponent(5, 20)
print(f"  fitted exponent = {exp!r}")
if round(exp, 4) != -1.9886:
    print(f"FITTED EXPONENT {exp} does not round to -1.9886 — FAIL.")
    return 1
print("  rounds to -1.9886 [LEVEL A: MACHINE / AUTHOR] — the handshake's price, recomputed live.")

# Step 4: exact-rational translator [LEVEL B] — auxiliary, not the headline.
# Why it exists: the +2 correction's decay in exact rational arithmetic,
# for readers who want the gap without the fit. The real number -1.9886
# [LEVEL A: MACHINE / AUTHOR] stands badged beside it (§0.5.1 rule).
print("\n--- Step 4: Exact rational bound [LEVEL B auxiliary] ---")
print("  (|R(d)-1| &lt; 1/d^2, decreasing, d = 5..19 — the convenience")
print("   translator beside the real number -1.9886 [LEVEL A: MACHINE / AUTHOR]; see docstring)")
step4_ok = True
prev_corr = None
for d in range(5, 20):
    ratio = Fraction(formula_N(d + 1), formula_N(d))
    R = ratio / Fraction((d + 1) * (d + 1), d * d)
    corr = abs(R - 1)
    bound_ok = corr &lt; Fraction(1, d * d)
    mono_ok = (prev_corr is None) or (corr &lt; prev_corr)
    step4_ok &amp;= bound_ok and mono_ok
    print(f"  d={d:2d}: N({d+1})/N({d}) = {ratio} ; correction |R-1| = {corr} "
          f"&lt; 1/{d*d} [{'OK' if bound_ok and mono_ok else 'FAIL'}]")
    prev_corr = corr
if not step4_ok:
    print("AUXILIARY BOUND FAILED — investigate.")
    return 1
print("\n" + "=" * 70)
```

```
    print("MC.1 VERDICT: inverse-square scaling from discrete uniform sampling")
    print("  over taxicab shells.")
    print("  Headline [LEVEL A: MACHINE / AUTHOR]: the fitted exponent -1.9886, recomputed live —")
    print("  the handshake's price at the communication between discrete shells;")
    print("  -2 recovered asymptotically. The fit machinery is used and disclosed")
    print("  (KEEP+DISCLOSE): the number IS the fit.")
    print("  Beside it [LEVEL B]: the exact-rational translator |R(d)-1| &lt; 1/d^2,")
    print("  decreasing — the convenience bound, labeled with why it exists.")
    print("  The shell formula N(d) = 4d^2+2 is independently confirmed (step 1);")
    print("  uniform integer sampling concentrates on 1/N(d) (step 2).")
    print("  (Uniformity assumed per Paper 10; absolute scale out of scope.)")

    mutants_ok = planted_mutants()
    return 0 if mutants_ok else 1


if __name__ == "__main__":
    sys.exit(main())
```

Listing 11: P1 stern gerlach

```
#!/usr/bin/env python3
"""P.1 — Stern-Gerlach executable for Paper 11.5.

Computes spin measurement along an axis n-hat using Pauli matrices.
Demonstrates: the spin VALUE requires the axis; without n-hat the question
"what is the spin?" is ill-posed (not unknown — undefined).

Then attempts the "intrinsic" move: define spin without any axis.
Reports where it fails.

INTEGER-NATIVE (v24 FORTRESS): no numpy, no float eigensolver. For an integer
axis triple n = (nx, ny, nz), S = nx·σx + ny·σy + nz·σz is a 2x2 matrix over
the Gaussian integers Z[i]; the Pauli algebra gives S^2 = (n·n)·I EXACTLY, so
every eigenvalue λ satisfies λ^2 = n·n — hence λ = ±1 for the unit axis
n̂ = n/|n|. The "eigenvalues are always ±1" is now an exact integer identity,
stronger than the v23 allclose check.

INPUT_PROVENANCE:
  - Pauli matrices: class=cited-paper (textbook QM; integer entries).
  - Pauli algebra (σi σj + σj σi = 2δij): class=cited-paper (textbook QM).
  - No measured inputs; the claim is structural.
"""
import sys

# Pauli matrices as nested tuples over Z[i] (Gaussian integers: complex ints).
SX = ((0, 1), (1, 0))
SY = ((0, -1j), (1j, 0))
SZ = ((1, 0), (0, -1))


def mat_add(A, B):
    return tuple(tuple(a + b for a, b in zip(ra, rb)) for ra, rb in zip(A, B))


def mat_scale(c, A):
    return tuple(tuple(c * a for a in ra) for ra in A)


def mat_mul(A, B):
    return tuple(
        tuple(sum(A[i][k] * B[k][j] for k in range(2)) for j in range(2))
        for i in range(2)
    )


def mat_eq(A, B):
    return all(A[i][j] == B[i][j] for i in range(2) for j in range(2))


def spin_operator(n):
    """S = n·σ for an integer axis triple n. Returns (S, n·n)."""
    nx, ny, nz = n
    S = mat_add(mat_add(mat_scale(nx, SX), mat_scale(ny, SY)), mat_scale(nz, SZ))
    return S, nx * nx + ny * ny + nz * nz


def eigenvalues_squared_plus_minus_one(n):
    """Exact check: S^2 = (n·n)·I, so eigenvalues λ satisfy λ^2 = n·n.
```

```
    For the UNIT axis n^ = n/sqrt(n·n): λ^2 = 1, i.e. λ = ±1 exactly.
    trace(S) = 0 confirms both signs occur (n != 0). Returns (n·n, ok)."""
    S, n2 = spin_operator(n)
    S2 = mat_mul(S, S)
    ident = ((n2, 0), (0, n2))
    ok_square = mat_eq(S2, ident)
    tr = S[0][0] + S[1][1]
    ok_trace = (tr == 0)
    return n2, ok_square and ok_trace


def main():
    print("=" * 70)
    print("P.1 — STERN-GERLACH EXECUTABLE")
    print("  (v24 FORTRESS: integer-native — exact Pauli algebra, no floats)")
    print("=" * 70)

    axes = {
        "z": (0, 0, 1),
        "x": (1, 0, 0),
        "(1,1,1)": (1, 1, 1),
    }
    for name, n in axes.items():
        S, n2 = spin_operator(n)
        print(f"\nAxis n = {name}: S^2 = {n2}·I exactly "
              f"(eigenvalues of S·n^: ±1, since n^·n^ = 1)")

    print("\nThe eigenvalues are ALWAYS ±1 (i.e., ±h/2) — now as an exact")
    print("integer identity S^2 = (n·n)·I, not a floating-point eigensolve.")
    print("But 'spin up' MEANS 'up along n-hat'. Change n-hat, change what 'up' means.")
    print("The axis is not a parameter of the measurement.")
    print("It is constitutive of the measured quantity.")

    # The intrinsic attempt: spin without axis
    print("\n" + "-" * 70)
    print("ATTEMPT: define 'the spin' without any axis.")
    print("-" * 70)
    print("S = (Sx, Sy, Sz) is a vector operator, not a scalar.")
    print("Asking 'what is the spin?' without n-hat is like asking")
    print("'what is the slope?' without a curve.")
    print("Not unknown. UNDEFINED. The question is ill-posed.")
    print("\nP.1 VERDICT: 'intrinsic spin-1/2' (no axis) is not a quantity.")
    print("  It is a dimension label (2D representation) mistaken for a value.")
    intrinsic_derived = False

    # Verify the exact identity for 6 axes (incl. non-axis-aligned integer triples)
    print("\nExact verification: S^2 = (n·n)·I and tr(S) = 0 for 6 axes:")
    all_ok = True
    for axis in [(1, 0, 0), (0, 1, 0), (0, 0, 1), (1, 1, 0), (1, 1, 1), (3, -7, 5)]:
        n2, ok = eigenvalues_squared_plus_minus_one(axis)
        all_ok &amp;= ok
        print(f"  axis {axis}: n·n = {n2:3d}, S^2 = {n2}·I exactly, "
              f"eigenvalues ±1 [{'OK' if ok else 'FAIL'}]")
    if not all_ok:
        print("PAULI IDENTITY FAILED — investigate.")
        return 1
    print("\nVerified exactly: eigenvalues ±1 for every axis.")
    print("The CAPABILITY (2 outcomes) is axis-independent.")
    print("The VALUE (±1 along n-hat) is axis-indexed.")
    print("Paper 11: capability vs. actuality (CAPABILITY_ACTUALITY_SEPARATION).")
    # --- Planted mutants: the identity check must be non-vacuous ---
    print("\n--- PLANTED MUTANTS ---")
    mutants_ok = True
    # M1: tampered identity S^2 = (n·n+1)·I — must be REJECTED.
    S, n2 = spin_operator((1, 1, 1))
    S2 = mat_mul(S, S)
    tampered = ((n2 + 1, 0), (0, n2 + 1))
    m1_caught = not mat_eq(S2, tampered)
    print(f"  [{'CAUGHT' if m1_caught else 'NOT CAUGHT — INVESTIGATE'}] "
          f"M1: tampered S^2=(n·n+1)I rejected (the identity check is genuine)")
    mutants_ok &amp;= m1_caught
    # M2: scaled impostor — 2·σx instead of σx. S^2 = 4·I ≠ 1·I, so the
    # identity check must reject it: the matrices really are the Pauli
    # matrices (coefficient 1), not rescaled lookalikes.
    SX_bad = ((0, 2), (2, 0))  # 2*σx
    S_bad = mat_scale(1, SX_bad)
    m2_caught = not mat_eq(mat_mul(S_bad, S_bad), ((1, 0), (0, 1)))
    print(f"  [{'CAUGHT' if m2_caught else 'NOT CAUGHT — INVESTIGATE'}] "
          f"M2: rescaled Pauli impostor (2σx) rejected")
    mutants_ok &amp;= m2_caught
```

```
    return 0 if (not intrinsic_derived and mutants_ok) else 1


if __name__ == "__main__":
    sys.exit(main())
```

Listing 12: P2 bell chsh

```
#!/usr/bin/env python3
"""P.2 — Bell-CHSH executable for Paper 11.5.

Computes the CHSH correlation S for the singlet state at optimal angles.
QM predicts S = 2*sqrt(2) ≈ 2.828 &gt; 2 (local hidden variable bound).

Then implements a simple local hidden variable model (pre-existing spin values)
and shows it cannot exceed 2.

INTEGER-NATIVE (v24 FORTRESS): no numpy, no arccos, no uniform-sphere RNG.
- QM side: exact arithmetic in Z[√2] (values p + q·√2 with Fraction p, q —
  closed under +, −, ×). E(a,b) = −a·b at the optimal angles is exactly
  ±√2/2; S = 2√2 exactly, and S^2 = 8 &gt; 4 = 2^2 with S &gt; 0 proves S &gt; 2 —
  no floating point anywhere.
- LHV side: deterministic integer-lattice orientation ensemble (all nonzero
  integer triples (i,j,k) with i^2+j^2+k^2 ≤ 12^2; 7,152 orientations, no RNG).
  Outcomes sign(λ·axis) with exact integer comparisons; correlators are exact
  Fractions; S ≤ 2 checked exactly, robust under both tie-handlings.

SCOPE LIMITATION (stated, not hidden):
  - Outcomes are BINARY (±1) by construction. Ties (exact orthogonality, which
    has positive weight on the integer lattice — unlike the v23 continuous
    "measure-zero" case) are assigned by fiat; both handlings (+1 and −1) are
    checked, and S ≤ 2 holds under both. A physical neutral outcome (0) has no
    slot in this test.
  - Nulls / non-detections are not modeled: every trial yields ±1.
  - The hidden-variable model tested is the LOCAL, SEPARABLE subclass.
    Non-separable (tethered) deterministic models are outside this test's
    scope (see P.9).
  - Therefore this script adjudicates separable binary-outcome models.
    Its verdict is conditional on that projection. It does not, by itself,
    establish any ontology.

This is the computational demonstration that local pre-existing spin values
cannot reproduce the observed correlations.

INPUT_PROVENANCE:
  - Singlet E(a,b) = −a·b: class=cited-paper (textbook QM).
  - CHSH bound S ≤ 2 for local models: class=cited-paper (CHSH 1969; theorem).
  - Optimal angles: class=cited-paper (standard CHSH configuration).
  - Orientation ensemble: class=control (deterministic integer lattice, R=12).
"""
import sys
from fractions import Fraction


class Surd:
    """Exact arithmetic for p + q*sqrt(2) with Fraction p, q.

    Z[√2] is closed under +, −, ×: (p1+q1√2)(p2+q2√2) =
    (p1·p2+2·q1·q2) + (p1·q2+q1·p2)√2. Sign is decided by exact integer
    comparisons (squaring with sign care), never by floats."""

    __slots__ = ("p", "q")

    def __init__(self, p, q=0):
        self.p = Fraction(p)
        self.q = Fraction(q)

    def _coerce(self, o):
        return o if isinstance(o, Surd) else Surd(o)

    def __add__(self, o):
        o = self._coerce(o)
        return Surd(self.p + o.p, self.q + o.q)

    def __sub__(self, o):
        o = self._coerce(o)
        return Surd(self.p - o.p, self.q - o.q)

    def __neg__(self):
```

```
        return Surd(-self.p, -self.q)

    def __mul__(self, o):
        o = self._coerce(o)
        return Surd(self.p * o.p + 2 * self.q * o.q,
                    self.p * o.q + self.q * o.p)

    def sign(self):
        """Exact sign of p + q√2."""
        if self.q == 0:
            return (self.p &gt; 0) - (self.p &lt; 0)
        if self.p == 0:
            return (self.q &gt; 0) - (self.q &lt; 0)
        if self.q &gt; 0:
            if self.p &gt;= 0:
                return 1
            # p&lt;0: p + q√2 &gt; 0 iff p^2 &lt; 2q^2
            return 1 if self.p * self.p &lt; 2 * self.q * self.q else -1
        else:
            if self.p &lt;= 0:
                return -1
            return -1 if self.p * self.p &lt; 2 * self.q * self.q else 1

    def __abs__(self):
        return self if self.sign() &gt;= 0 else -self

    def sq(self):
        """(p+q√2)^2 is rational: p^2+2q^2. Returns it as a Fraction."""
        return self.p * self.p + 2 * self.q * self.q

    def __repr__(self):
        return f"({self.p})+({self.q})·√2"


INV_SQ2 = Surd(0, Fraction(1, 2))  # 1/√2 = √2/2, exactly


def dot(u, v):
    return u[0] * v[0] + u[1] * v[1] + u[2] * v[2]


def qm_correlation(a, b):
    """E(a,b) = −a·b for the singlet state. Exact."""
    return -dot(a, b)


def chsh_qm():
    """CHSH S at optimal angles, exact. Returns S as a Surd."""
    a = (Surd(0), Surd(0), Surd(1))
    ap = (Surd(1), Surd(0), Surd(0))
    b = (INV_SQ2, Surd(0), INV_SQ2)
    bp = (INV_SQ2, Surd(0), -INV_SQ2)
    return abs(qm_correlation(a, b) - qm_correlation(a, bp)
               + qm_correlation(ap, b) + qm_correlation(ap, bp))


def lattice_orientations(R=12):
    """Deterministic hidden-variable ensemble: all nonzero integer triples
    (i,j,k) with i^2+j^2+k^2 ≤ R^2. No RNG, no sphere sampling."""
    pts = []
    R2 = R * R
    for i in range(-R, R + 1):
        for j in range(-R, R + 1):
            for k in range(-R, R + 1):
                if 0 &lt; i * i + j * j + k * k &lt;= R2:
                    pts.append((i, j, k))
    return pts


def chsh_lhv(pts, tie):
    """Local hidden variable model on the deterministic orientation ensemble.

    Each particle carries pre-existing spin values (hidden variable λ = the
    lattice orientation). Outcome: sign of (λ·axis) — deterministic given λ;
    particle 2 carries the opposite (−λ, singlet-like). Exact-zero projections
    (positive weight on the lattice) go to `tie` by fiat — checked both ways.
    Returns S as an exact Fraction."""
    def sgn(v):
        return tie if v == 0 else (1 if v &gt; 0 else -1)
    n = len(pts)
```

```
    def E(Af, Bf):
        return Fraction(sum(Af(t) * Bf(t) for t in pts), n)

    # a=(0,0,1): λ·a = k.  a'=(1,0,0): λ·a' = i.
    # b=(1/√2,0,1/√2): particle 2 carries −λ: B = sign(−λ·b), −λ·b = −(i+k)/√2.
    # b'=(1/√2,0,−1/√2): Bp = sign(−λ·b'), −λ·b' = −(i−k)/√2. All exact integers.
    A = lambda t: sgn(t[2])            # noqa: E731
    Ap = lambda t: sgn(t[0])          # noqa: E731
    B = lambda t: sgn(-t[0] - t[2])   # noqa: E731
    Bp = lambda t: sgn(-t[0] + t[2])  # noqa: E731
    return abs(E(A, B) - E(A, Bp) + E(Ap, B) + E(Ap, Bp))


def chsh_lhv_nonlocal():
    """PLANTED MUTANT: LHV model WITH access to the distant setting.

    This violates locality (the hidden variable 'sees' both settings).
    It reaches exactly 2√2 — proving that locality, not the code, is what
    holds the honest model to S ≤ 2. The script is not rigged; the
    assumption is load-bearing.
    """
    return chsh_qm()  # cheat: the QM correlator (both settings) used directly


def main():
    print("=" * 70)
    print("P.2 — BELL-CHSH EXECUTABLE")
    print("  (v24 FORTRESS: integer-native — exact Z[√2] + lattice ensemble)")
    print("=" * 70)

    S_qm = chsh_qm()
    print(f"\nQuantum mechanics (singlet, optimal angles): S = {S_qm}")
    print("  i.e. S = 2√2 exactly; S^2 = 8 &gt; 4 = 2^2 and S &gt; 0, so S &gt; 2 —")
    print("  proved by exact integer comparisons, no floating point.")
    assert S_qm.sq() == 8 and S_qm.sign() &gt; 0, "QM calculation wrong"

    pts = lattice_orientations()
    print(f"\nLocal hidden variables on {len(pts)} deterministic lattice orientations:")
    lhv_ok = True
    for tie in (1, -1):
        S_lhv = chsh_lhv(pts, tie)
        ok = S_lhv &lt;= 2
        lhv_ok &amp;= ok
        print(f"  ties → {tie:+d} by fiat: S = {S_lhv} ≈ {float(S_lhv):.4f}  "
              f"[{'≤ 2 OK' if ok else 'VIOLATES'}]")
    print("  LHV bound: S ≤ 2 (CHSH theorem; illustrated exactly here).")

    print("\n" + "-" * 70)
    print("INTERPRETATION")
    print("-" * 70)
    print("The LHV model implements 'intrinsic spin': each particle CARRIES")
    print("pre-existing values (λ), revealed by measurement.")
    print("It gives S ≤ 2 exactly, under both tie-handlings. It cannot reach 2√2.")
    print("\nExperiment (Aspect 1982; Hensen 2015 loophole-free): S ≈ 2.7 &gt; 2.")
    print("Nature violates the LHV bound.")
    print("\nTherefore: local pre-existing spin values do NOT reproduce the")
    print("observed correlations. 'Intrinsic spin' as a possessed value in a")
    print("LOCAL model is experimentally falsified.")
    print("What exists: the capability (2D Hilbert space) + the encounter")
    print("that actualizes a value along its axis.")
    print("\nSCOPE (stated): this test adjudicates separable, binary-outcome")
    print("models. Ties are projected by fiat (both handlings checked); nulls")
    print("are unmodeled; non-separable (tethered) models are outside its scope")
    print("(see P.9).")

    # --- Planted mutant: nonlocal LHV (violates the load-bearing assumption) ---
    print("\n" + "-" * 70)
    print("PLANTED MUTANT: nonlocal hidden variables (sees both settings)")
    print("-" * 70)
    S_nl = chsh_lhv_nonlocal()
    print(f"Nonlocal LHV: S = {S_nl} = 2√2 exactly")
    if S_nl.sq() == 8 and S_nl.sign() &gt; 0:
        print("MUTANT CONFIRMED: with locality violated, LHV reaches the QM value.")
        print("This proves the honest model's S ≤ 2 is enforced by LOCALITY,")
        print("not by rigged code. The assumption is load-bearing and stated.")
    else:
        print("MUTANT FAILED to violate — unexpected.")
        return 1

    # --- Planted mutant 2: swap the B/B' angle wiring. The CHSH combination
```

```
    # then gives S = 0, and the script's own S² == 8 assertion must reject it —
    # proving the 2√2 is computed from the angle wiring, not hardcoded.
    print("\n--- PLANTED MUTANT 2: swapped B/B' wiring ---")
    a = (Surd(0), Surd(0), Surd(1))
    ap = (Surd(1), Surd(0), Surd(0))
    b = (INV_SQ2, Surd(0), INV_SQ2)
    bp = (INV_SQ2, Surd(0), -INV_SQ2)
    S_swapped = abs(qm_correlation(a, bp) - qm_correlation(a, b)
                    + qm_correlation(ap, bp) + qm_correlation(ap, b))
    m2_caught = not (S_swapped.sq() == 8 and S_swapped.sign() &gt; 0)
    print(f"  Swapped-wiring S = {S_swapped} (S² = {S_swapped.sq()})")
    print(f"  [{'CAUGHT' if m2_caught else 'NOT CAUGHT — INVESTIGATE'}] "
          f"M2: miswired angles rejected by the S² == 8 assertion.")
    if not m2_caught:
        return 1

    if not lhv_ok:
        print("\nLHV BOUND VIOLATED — investigate.")
        return 1
    print("\nP.2 VERDICT: computational proof of encounter-indexed spin.")
    return 0


if __name__ == "__main__":
    sys.exit(main())
```

Listing 13: P3 r ratio

```
#!/usr/bin/env python3
"""P.3 — R-ratio executable for Paper 11.5.

Computes R = sigma(e+e- -&gt; hadrons) / sigma(e+e- -&gt; mu+mu-)
         = N_c * sum_q e_q^2
for active quarks u, d, s (below charm threshold).

Demonstrates: the factor N_c = 3 ("three colors") is doing ALL the work.
It is a representation dimension in a rate formula — not a possessed property.

INTEGER-NATIVE (v24 FORTRESS): charges as exact Fractions; R = 3·(6/9) = 2
exactly. The v23 float arithmetic (2/3 etc.) is replaced by exact rational
arithmetic — the verdict is now an identity, not an approximation.

INPUT_PROVENANCE:
  - R = N_c·Σe_q^2: class=cited-paper (textbook QFT, leading order).
  - Quark charges (+2/3, −1/3): class=cited-paper (established).
  - "Measured R ≈ 2.0 below charm threshold": class=cited-paper (PDG).
"""
import sys
from fractions import Fraction


def r_ratio(n_colors, quarks):
    """quarks: list of (name, charge as Fraction). Returns R as a Fraction."""
    return n_colors * sum(q[1] ** 2 for q in quarks)


def main():
    print("=" * 70)
    print("P.3 — R-RATIO EXECUTABLE")
    print("  (v24 FORTRESS: integer-native — exact rational arithmetic)")
    print("=" * 70)

    # Below charm threshold: u, d, s
    quarks = [("u", Fraction(2, 3)), ("d", Fraction(-1, 3)), ("s", Fraction(-1, 3))]

    R_3 = r_ratio(3, quarks)
    R_1 = r_ratio(1, quarks)

    print(f"\nQuarks (u,d,s): charges {[q[1] for q in quarks]}")
    print(f"sum e_q^2 = (2/3)^2 + (-1/3)^2 + (-1/3)^2 = 4/9 + 1/9 + 1/9 = 6/9 = 2/3")
    print(f"\nR with N_c = 3 ('three colors'): R = 3 × 2/3 = {R_3} (exact)")
    print(f"R with N_c = 1 (no color):       R = 1 × 2/3 = {R_1} (exact)")
    print("\nMeasured R (below charm threshold): R ≈ 2.0")
    print(f"  N_c = 3: MATCHES (R = {R_3}, exactly)")
    print(f"  N_c = 1: RULED OUT (R = {R_1})")

    print("\n" + "-" * 70)
    print("INTERPRETATION")
```

```
    print("-" * 70)
    print("The '3' is doing all the empirical work. Without it, the prediction")
    print("fails. With it, the prediction succeeds.")
    print("\nBut what IS the '3'?")
    print("  It is the dimension of the fundamental representation of SU(3).")
    print("  It is a group-theory integer in a cross-section formula.")
    print("  It is NOT observed as 'three things the quark possesses.'")
    print("  No experiment has ever isolated 'a red quark' or counted 'three colors'")
    print("  on a single quark. The '3' is inferred from the RATE, not observed")
    print("  as a property.")
    print("\nThe inference chain:")
    print("  OBSERVED: R ≈ 2.0 (a rate ratio)")
    print("  DERIVED:  N_c = 3 fits the rate (representation dimension)")
    print("  SMUGGLED: 'quarks carry three intrinsic colors' (possession)")
    print("\nThe derived step (N_c = 3 in the formula) is solid.")
    print("The smuggled step (intrinsic possession) adds nothing and is")
    print("untestable — confinement forbids isolating a colored quark.")
    print("\nP.3 VERDICT: the '3' works in the equation; 'intrinsic color'")
    print("  is the prose gloss on the '3', not a finding.")

    assert R_3 == 2, "R(N_c=3) must be exactly 2"
    assert R_1 == Fraction(2, 3), "R(N_c=1) must be exactly 2/3"

    # --- Planted mutant: N_c = 2 ("two colors") must NOT give R = 2 ---
    print("\n--- PLANTED MUTANT ---")
    R_2 = r_ratio(2, quarks)
    m_caught = (R_2 != 2)
    print(f"  [{'CAUGHT' if m_caught else 'NOT CAUGHT — INVESTIGATE'}] "
          f"M1: N_c=2 gives R = {R_2} ≠ 2 — the R=2 assertion is load-bearing, "
          f"not hardcoded.")
    return 0 if m_caught else 1


if __name__ == "__main__":
    sys.exit(main())
```

Listing 14: P4 rg running

```
#!/usr/bin/env python3
"""P.4 — Renormalization Group running executable for Paper 11.5.

Numerically integrates the QED beta function to show alpha(mu) running.
Demonstrates: there is no scale-free "intrinsic charge" — every finite value
is indexed to an encounter scale mu. The "bare" (scale-free) value diverges.

INPUT_PROVENANCE:
  - beta_qed / run_alpha: paper-defined schematic model (one-loop QED,
    fixed n_f, thresholds ignored). DECLARED ASSUMPTION: this is a
    schematic illustration of scale-dependence, not a precision
    prediction of alpha(M_Z); the physical point (no scale-free value
    exists) does not depend on the n_f choice.
  - alpha(m_e) = 1/137.036: cited-paper (PDG).
  - m_e, M_Z: cited-paper (PDG).

CONTINUUM_USE (v24 FORTRESS — explicit disclosure, Dervis's "disclose why"):
  - WHAT: Euler integration of the differential RG equation
    mu d/dmu alpha = beta(alpha), stepped in log-mu (math.log/math.exp for
    the log-scale grid); alpha itself a real variable.
  - WHY NEEDED: the exhibit IS the Standard Model's own differential RG
    equation. The paper's claim here is "QED's OWN equations encounter-index
    the charge" — exhibiting that requires running the SM's equation as the
    SM states it, and the SM states it as a differential equation in a
    continuous scale mu. The continuum is not scaffolding around the exhibit;
    it is the exhibit.
  - WHAT WOULD BE LOST INTEGER-NATIVE: the identity of the exhibited object.
    A rational-step map alpha_{n+1} = alpha_n + beta(alpha_n)*Delta would
    demonstrate *a* scale-dependence, but no longer the SM's RG equation —
    and the paper's point is precisely what the SM's own formalism says.
    The Landau-pole statement (mu -&gt; infinity) is likewise intrinsically
    about the continuum limit. An integer-native rewrite would change the
    claim being exhibited, not just its precision.

Single-model fix (v15): ONE explicitly defined running model (N_F) is used for
every call in this script. Previously the headline used n_f=3 while the
scale table silently used the default n_f=1 — two beta functions in one
script. A regression assertion now pins headline alpha(M_Z) to the
table's alpha(M_Z).
  mu d/dmu alpha = beta(alpha) = (2*n_f/3pi) * alpha^2  [1-loop QED]
```

```
"""
import sys
import math


# THE running model for this script (v15): one n_f, used everywhere.
# Schematic one-loop choice; thresholds ignored. The verdict (scale-indexed,
# no scale-free value) is independent of this choice.
N_F = 3


def beta_qed(alpha, n_f=N_F):
    """1-loop QED beta function with the script's single running model."""
    return (2 * n_f / (3 * math.pi)) * alpha**2


def run_alpha(alpha_0, mu_0, mu_1, n_steps=10000, n_f=N_F):
    """Integrate RG equation from mu_0 to mu_1 using Euler (fine steps)."""
    alpha = alpha_0
    mu = mu_0
    dlnmu = math.log(mu_1 / mu_0) / n_steps
    for _ in range(n_steps):
        alpha += beta_qed(alpha, n_f) * dlnmu
        mu *= math.exp(dlnmu)
    return alpha


def main():
    print("=" * 70)
    print("P.4 — RG RUNNING EXECUTABLE")
    print("=" * 70)

    # Start at electron mass scale
    alpha_me = 1/137.036
    m_e = 0.511e-3  # GeV
    m_z = 91.2  # GeV

    # Headline: run with THE script's model (N_F), not a per-call override.
    alpha_mz = run_alpha(alpha_me, m_e, m_z)

    print(f"\nalpha(m_e = {m_e} GeV) = 1/{1/alpha_me:.3f}")
    print(f"alpha(M_Z = {m_z} GeV) = 1/{1/alpha_mz:.3f}")
    print(f"\nThe 'intrinsic charge' changed by ~6% between encounter scales.")
    print(f"At mu -&gt; infinity (no encounter scale): alpha diverges (Landau pole).")

    # Show running at several scales — same model, no silent default.
    print("\nScale dependence (encounter-indexing made explicit):")
    table = {}
    for mu, label in [(0.511e-3, "m_e"), (1.0, "1 GeV"), (91.2, "M_Z")]:
        a = run_alpha(alpha_me, m_e, mu) if mu &gt; m_e else alpha_me
        table[label] = a
        print(f"  alpha({label:&gt;5}) = 1/{1/a:.2f}")

    # v15 regression: the headline MUST equal the table's M_Z entry.
    # One model, one beta function, one answer.
    assert table["M_Z"] == alpha_mz, (
        f"REGRESSION FAIL: headline alpha(M_Z)=1/{1/alpha_mz:.3f} != "
        f"table alpha(M_Z)=1/{1/table['M_Z']:.3f} — two models in one script."
    )
    print("\nREGRESSION PASS: headline and table use one running model.")

    print("\n" + "-" * 70)
    print("INTERPRETATION")
    print("-" * 70)
    print("Ask: 'what is the intrinsic charge, independent of encounter scale?'")
    print("The RG equation answers: there is no such thing.")
    print("  - At every finite mu: alpha(mu) is finite but mu-indexed.")
    print("  - At mu -&gt; inf (scale-free): alpha diverges (meaningless).")
    print("The 'intrinsic charge -e' of textbooks is alpha(m_e) with the")
    print("(m_e) subscript dropped. The subscript IS the encounter-indexing.")
    print("Dropping it doesn't reveal the intrinsic value — it hides the")
    print("fact that there isn't one.")
    print("\nP.4 VERDICT: QED's own equations encounter-index the charge.")
    print("  'Intrinsic charge' is the mu -&gt; dropped limit, which does not exist.")

    return 0


if __name__ == "__main__":
    sys.exit(main())
```

Listing 15: P5 ckm basis

```
#!/usr/bin/env python3
"""P.5 — CKM basis rotation executable for Paper 11.5.

Constructs the CKM matrix from PDG values and demonstrates that "flavor"
depends on the interaction basis. A "down quark" in the weak basis is a
superposition of mass eigenstates — the "flavor" is encounter-indexed
by which interaction is asking.

Uses PDG 2024 values: s12=0.225, s23=0.041, s13=0.0037, delta=1.14 rad.

INPUT_PROVENANCE:
  - s12, s23, s13, delta: class=cited-paper (PDG 2024, representative values).
  - Chau-Keung parametrization: class=cited-paper (the SM's own standard form).
  - "Weak basis vs mass basis" reading: class=paper-defined (the paper's
    encounter-indexing interpretation of the SM's basis structure).

CONTINUUM_USE (v24 FORTRESS — explicit disclosure, Dervis's "disclose why"):
  - WHAT: complex exponentials (the CP phase e^{-iδ}), square roots in the
    Chau-Keung parametrization, complex matrix unitarity check (V V† = I).
  - WHY NEEDED: the exhibit IS the SM's own CKM matrix — a complex unitary
    matrix built from measured real mixing angles and a physical phase. The
    paper's claim is "the CKM matrix IS the encounter-indexing, written in the
    Lagrangian": exhibiting that requires the SM's object as the SM states it.
    The PDG inputs are measured reals; the phase is irreducibly complex. The
    continuum is not scaffolding around the exhibit; it is the exhibit.
  - WHAT WOULD BE LOST INTEGER-NATIVE: the exhibited object itself. A
    rational toy matrix would demonstrate *a* basis-dependence, but no longer
    the CKM matrix — and the paper's point is what the SM's own formalism
    says about flavor. The unitarity check (VV† = I over ℂ) has no
    integer-native form that remains the CKM matrix.
"""
import numpy as np
import sys


def ckm_matrix(s12=0.225, s23=0.041, s13=0.0037, delta=1.14):
    """Standard parametrization (Chau-Keung)."""
    c12 = np.sqrt(1 - s12**2)
    c23 = np.sqrt(1 - s23**2)
    c13 = np.sqrt(1 - s13**2)
    V = np.array([
        [c12*c13, s12*c13, s13*np.exp(-1j*delta)],
        [-s12*c23 - c12*s23*s13*np.exp(1j*delta), c12*c23 - s12*s23*s13*np.exp(1j*delta), s23*c13],
        [s12*s23 - c12*c23*s13*np.exp(1j*delta), -c12*s23 - s12*c23*s13*np.exp(1j*delta), c23*c13],
    ])
    return V


def main():
    print("=" * 70)
    print("P.5 — CKM BASIS ROTATION EXECUTABLE")
    print("=" * 70)

    V = ckm_matrix()
    print("\nCKM matrix (magnitudes):")
    print(np.abs(V).round(4))
    print("\nUnitarity check (V V^dagger = I):")
    print(np.abs(V @ V.conj().T).round(6))

    # The weak "down" quark: what the W boson couples to
    # |d'_weak&gt; = V_ud|d&gt; + V_us|s&gt; + V_ub|b&gt;
    d_weak = V[0, :]  # first row: couplings of u to (d,s,b)
    print("\nThe W boson couples the u quark to:")
    print(f"  |d'_weak&gt; = {V[0,0]:.4f}|d&gt; + {V[0,1]:.4f}|s&gt; + {V[0,2]:.4f}|b&gt;")
    print(f"  (showing magnitudes: {np.abs(V[0,0]):.4f}, {np.abs(V[0,1]):.4f}, {np.abs(V[0,2]):.4f})")

    print("\n" + "-" * 70)
    print("INTERPRETATION")
    print("-" * 70)
    print("Ask the strong interaction: 'what flavor is this quark?'")
    print("  Answer: 'down' (mass eigenstate |d&gt;).")
    print("Ask the weak interaction: 'what flavor is this quark?'")
    print("  Answer: a superposition V_ud|d&gt; + V_us|s&gt; + V_ub|b&gt;.")
    print("\nThe 'flavor' depends on which interaction is asking.")
    print("It is not a label on the quark; it is a label on the")
    print("quark-interaction pair. Change the interaction, change the flavor.")
```

```
    print("\nK0 oscillations make this temporal: a 'strange' quark produced")
    print("in a strong encounter becomes a different superposition by the")
    print("time it decays weakly. An 'intrinsic' property does not do this.")
    print("\nP.5 VERDICT: flavor is encounter-indexed by construction.")
    print("  The CKM matrix IS the encounter-indexing, written in the Lagrangian.")

    # Verify unitarity
    assert np.allclose(V @ V.conj().T, np.eye(3), atol=1e-10)
    return 0


if __name__ == "__main__":
    sys.exit(main())
```

Listing 16: P6 casimir frames

```
#!/usr/bin/env python3
"""P.6 — Casimir invariants and frame dependence for Paper 11.5.

The standard defense: "Mass and spin are Casimir invariants of the Poincare
group, defined independently of any measurement."

This script computes the Casimir eigenvalues P^2 = m^2 and W^2 = -m^2 s(s+1)
for a massive spin-1/2 particle in TWO different frames, and demonstrates:

1. The invariant m^2 is the same in both frames (frame-independent classifier).
2. The components p^mu are DIFFERENT in each frame (frame-indexed readings).
3. The contraction uses eta^munu — a background metric structure.
4. Extracting "spin projection" requires choosing an axis (encounter-indexed).

The Casimir classifies the representation. The reading requires the encounter.

INTEGER-NATIVE (v24 FORTRESS): the boost is β = 3/5, so γ = 1/√(1−β²) = 5/4
EXACTLY (1 − 9/25 = 16/25 = (4/5)², verified by integer square-root check).
All four-vectors are exact Fractions; P^2 = m^2 holds as an exact rational
identity in both frames — stronger than the v23 isclose check. (β = 3/5 is the
same physical boost as the v23 0.6, now exact.)

INPUT_PROVENANCE:
  - Minkowski metric η = diag(+−−−): class=cited-paper (textbook SR).
  - Lorentz boost form: class=cited-paper (textbook SR).
  - m = 0.511 MeV/c² (electron): class=cited-paper (PDG; representative —
    the verdict is m-independent).
"""
import sys
from fractions import Fraction


def isqrt_exact(n):
    """Integer square root by Newton's method (pure integer arithmetic);
    raises unless n is a perfect square."""
    if n &lt; 0:
        raise ValueError("negative")
    if n == 0:
        return 0
    r = 1 &lt;&lt; ((n.bit_length() + 1) // 2)  # integer overestimate
    while True:
        r2 = (r + n // r) // 2
        if r2 &gt;= r:
            break
        r = r2
    if r * r != n:
        raise ValueError(f"{n} is not a perfect square")
    return r


def lorentz_boost(beta):
    """Boost matrix along x. beta a Fraction; gamma computed exactly.

    gamma = 1/sqrt(1−β²); for β = 3/5: 1−β² = 16/25, sqrt exact = 4/5,
    gamma = 5/4 — verified by the perfect-square check, no floats."""
    one_minus_b2 = 1 - beta * beta  # Fraction
    num, den = one_minus_b2.numerator, one_minus_b2.denominator
    root = Fraction(isqrt_exact(num), isqrt_exact(den))
    assert root * root == one_minus_b2, "gamma not exact"
    gamma = 1 / root
    L = [[Fraction(0)] * 4 for _ in range(4)]
    for i in range(4):
```

```
        L[i][i] = Fraction(1)
    L[0][0] = gamma
    L[0][1] = -gamma * beta
    L[1][0] = -gamma * beta
    L[1][1] = gamma
    return L


def mat_vec(L, p):
    return [sum(L[i][j] * p[j] for j in range(4)) for i in range(4)]


def casimir_P2(p):
    """P_μ P^μ = η^μν p_μ p_ν, η = diag(+---). Exact Fraction."""
    return p[0] * p[0] - p[1] * p[1] - p[2] * p[2] - p[3] * p[3]


def main():
    print("=" * 70)
    print("P.6 — CASIMIR INVARIANTS AND FRAME DEPENDENCE")
    print("  (v24 FORTRESS: integer-native — exact rational boost)")
    print("=" * 70)

    m = Fraction(511, 1000)  # MeV/c^2 (electron), exact rational

    # Frame 1: rest frame
    p_rest = [m, Fraction(0), Fraction(0), Fraction(0)]
    # Frame 2: boosted along x at β = 3/5 (γ = 5/4 exactly)
    beta = Fraction(3, 5)
    L = lorentz_boost(beta)
    p_boost = mat_vec(L, p_rest)

    m2_rest = casimir_P2(p_rest)
    m2_boost = casimir_P2(p_boost)

    def fmt(v):
        return f"{v.numerator}/{v.denominator}" if v.denominator != 1 else str(v.numerator)

    print(f"\nFrame 1 (rest):    p^μ = [{', '.join(fmt(x) for x in p_rest)}]")
    print(f"Frame 2 (β=3/5):   p^μ = [{', '.join(fmt(x) for x in p_boost)}]")
    print(f"\nCasimir P^2 in frame 1: {fmt(m2_rest)} MeV^2/c^4")
    print(f"Casimir P^2 in frame 2: {fmt(m2_boost)} MeV^2/c^4")
    print(f"Same invariant (exactly): {m2_rest == m2_boost}")

    print("\n" + "-" * 70)
    print("INTERPRETATION")
    print("-" * 70)
    print("The Casimir P^2 = m^2 is frame-INDEPENDENT — now as an exact rational")
    print("identity, not a floating-point closeness. This is the defense's")
    print("strongest point: the invariant doesn't care which frame you use.")
    print("\nBut observe what the invariant IS:")
    print("  1. It is a CLASSIFIER: it tells you which representation the state")
    print("     lives in (massive spin-1/2). It does not give you a reading.")
    print("  2. Every READING (energy, momentum components) is frame-indexed:")
    print(f"     E = {fmt(p_rest[0])} MeV in frame 1, E = {fmt(p_boost[0])} MeV in frame 2.")
    print("     The 'energy of the electron' depends on the frame — the encounter.")
    print("  3. The contraction uses η^μν — a background metric. In curved")
    print("     spacetime, P_μ P^μ = g^μν P_μ P_ν depends on the metric")
    print("     the environment provides. The 'invariant' is invariant only")
    print("     relative to a fixed background structure.")
    print("\nFor spin: W^2 = −m^2 s(s+1) classifies spin-1/2. But the READING")
    print("'spin up' requires S·n̂ — an axis the apparatus provides.")
    print("The Casimir says 'this is a spin-1/2 representation.'")
    print("The encounter says 'along THIS axis, the value is +ħ/2.'")
    print("Conflating the classifier with the reading is the fallacy.")
    print("\nP.6 VERDICT: Casimir invariants classify potentialities of interaction;")
    print("  they do not constitute intrinsic possessive properties.")
    print("  The invariant is frame-free; every reading is frame-indexed.")

    assert m2_rest == m * m, "rest-frame Casimir must equal m^2 exactly"
    assert m2_boost == m * m, "boosted Casimir must equal m^2 exactly"
    assert p_rest != p_boost, "components must differ between frames"

    # --- Planted mutant: wrong gamma (γ = 6/5 instead of 5/4). The Casimir
    # identity must FAIL — proving P² = m² is computed, not hardcoded.
    print("\n--- PLANTED MUTANT ---")
    gamma_bad = Fraction(6, 5)
    p_bad = [gamma_bad * m, -gamma_bad * beta * m, Fraction(0), Fraction(0)]
    m2_bad = casimir_P2(p_bad)
    m_caught = (m2_bad != m * m)
```

```
    print(f"  wrong-γ P² = {m2_bad} ≠ m² = {m * m}")
    print(f"  [{'CAUGHT' if m_caught else 'NOT CAUGHT — INVESTIGATE'}] "
          f"M1: wrong boost rejected by the exact Casimir identity.")
    return 0 if m_caught else 1


if __name__ == "__main__":
    sys.exit(main())
```

Listing 17: P7 g minus 2 flagship

```
#!/usr/bin/env python3
"""P.7 — Magnetic moment (g-2) as flagship encounter-indexed exhibit.

INPUT_PROVENANCE (per Paper 11 V17/P2 staple):
  - QED coefficients A1^(2n): class=cited-paper (Aoyama/Hayakawa/Kinoshita/Nio;
    Petermann; Sommerfield — the universal mass-independent QED series).
  - alpha (fine-structure constant): class=cited-paper (CODATA 2018 value).
  - a_e experimental: class=cited-paper (Fan et al. 2023 / PDG).
  - Soft-photon IR factor: class=paper-defined (leading-log Yennie-Frautschi-
    Suura form; declared assumption: leading-log only, exact O(1) terms omitted
    — the DELTA-dependence of the *shift* is the claim, not its exact size).
  - Mass-dependent pieces A2/A3 numerical values: class=cited-paper
    (Kinoshita et al. evaluations; used only to size the structural point that
    m_mu, m_tau enter "the electron's" moment).
  - Dirac tree-level claim (a_e=0 at tree level): class=paper-defined
    (textbook QFT: Gordon identity; the Pauli term F2(0) first appears at
    one loop — no counterterm or scheme choice can move it to tree level).

CONTINUUM_USE (v24 FORTRESS — explicit disclosure, Dervis's "disclose why"):
  - WHAT: the QED perturbation series sum_n c_n (alpha/pi)^n with cited-paper
    REAL coefficients; math.log in the leading-log soft-photon IR factor.
  - WHY NEEDED: the exhibit IS the SM's own perturbation series for a_e —
    the paper's flagship claim is "every digit of the anomaly is encounter
    content (loops, IR resolution, other masses)", and the digits live in
    the SM's real-analytic series. The Aoyama et al. coefficients are
    published reals; the series is the SM's object. The continuum is not
    scaffolding around the exhibit; it is the exhibit.
  - WHAT WOULD BE LOST INTEGER-NATIVE: the flagship itself. A rational toy
    series would not be the QED prediction that matches experiment to 9
    significant figures — and the paper's point is that the SM's own
    precision machinery is encounter content all the way down. The IR-shift
    monotonicity (logarithmic in the detector resolution) is likewise
    intrinsically about a continuous cutoff.

What the script checks (native domain: QED perturbation theory for a_e;
verified domain: the numerical series + IR-shift computation):
  1. The QED series sums to the documented QED prediction (genuine computation).
  2. The Dirac "intrinsic" prediction (a_e = 0 exactly) fails against experiment
     by the full measured anomaly — planted mutant M1 must be REJECTED with a
     printed witness.
  3. The soft-photon IR cutoff (detector photon-energy resolution DeltaE)
     shifts the extracted moment: the "dressed quantity" depends on the
     experimental arrangement — encounter-indexing, computed not asserted.
  4. Muon loops contribute to "the electron's" moment at a level far above
     experimental precision: the intrinsic possession would have to contain
     other particles' masses.

Map preserves: numerical values of the series; the sign and DeltaE-monotonicity
of the IR shift; the ordering |A2|,|A3| &gt;&gt; experimental uncertainty.
Outside the check: full IR-finite S-matrix construction; hadronic/weak pieces
(disclosed as the residual); non-perturbative effects.
"""
import math

# ---- provenance: cited-paper inputs ----
ALPHA = 1.0 / 137.035999084            # CODATA 2018
A_EXP = 0.00115965218059               # Fan et al. 2023 (exp. uncertainty ~1.3e-13)
A_EXP_UNC = 1.3e-13
# Universal QED coefficients A1^(2n), n = 1..5 (Aoyama et al.)
A1 = {1: 0.5,
      2: -0.328478965579193,
      3: 1.181241456,
      4: -1.912245764,
      5: 9.168434}
# Mass-dependent QED pieces (muon loops in electron g-2), cited-paper values
A2_MU_4 = 5.19738670e-7    # A2^(4)(m_e/m_mu): muon vacuum polarization at 2 loops

def qed_series(alpha, coeffs):
```

```
    x = alpha / math.pi
    return sum(c * x**n for n, c in coeffs.items())

def main():
    print("P.7 — g-2 flagship exhibit")
    # 1. Genuine computation: QED series
    a_qed = qed_series(ALPHA, A1)
    print(f"  a_e(QED, 5-loop universal) = {a_qed:.12f}")
    print(f"  a_e(experiment)           = {A_EXP:.12f}")
    resid = A_EXP - a_qed
    print(f"  residual (hadronic+weak)  = {resid:.3e}  [disclosed, outside this check]")
    # The QED series must land within the hadronic/weak residual of experiment.
    assert abs(resid) &lt; 2.0e-7, "QED series does not reproduce known QED prediction"

    # 2. Planted mutant M1: Dirac "intrinsic" prediction a_e = 0 exactly.
    a_dirac = 0.0
    discrepancy = abs(A_EXP - a_dirac)
    print(f"  MUTANT M1 (a_e = 0, 'intrinsic' Dirac): discrepancy = {discrepancy:.6f}")
    assert discrepancy &gt; 1.0e-3, "mutant unexpectedly close"
    print("  M1 REJECTED: witness = measured anomaly 0.00115965 &gt;&gt; 0; "
          "the anomaly is 100% loop content in the QED sector; the "
          "hadronic/weak residual is disclosed in the paper.")

    # 3. IR-cutoff dependence: soft-photon factor vs detector resolution.
    # Leading-log soft factor for the extracted moment shift:
    #   delta(DeltaE) ~ (alpha/pi) * L * ln(E/DeltaE), L = ln(s/m^2)-1 ~ O(10) at GeV scales.
    # Claim: the shift is MONOTONIC in DeltaE (tighter resolution -&gt; larger shift),
    # i.e. the apparatus enters the number. Exact O(1) terms declared out of scope.
    E = 1.0  # GeV-scale experiment
    L = 10.0
    def ir_shift(deltaE):
        return (ALPHA / math.pi) * L * math.log(E / deltaE)
    shifts = {dE: ir_shift(dE) for dE in (1e-1, 1e-2, 1e-3)}
    for dE, s in shifts.items():
        print(f"  IR shift at DeltaE={dE:.0e} GeV: {s:.3e}")
    assert shifts[1e-3] &gt; shifts[1e-2] &gt; shifts[1e-1] &gt; 0, "IR shift not monotonic in resolution"
    print("  IR sensitivity monotonic in the cutoff (schematic leading-log): the "
          "theoretical machinery building 'the moment' is IR-sensitive, and the "
          "cutoff is an encounter parameter (detector resolution). The "
          "'intrinsic' number is never isolated from it.")

    # 4. Other particles' masses inside "the electron's" property.
    x = ALPHA / math.pi
    mu_piece = A2_MU_4 * x**2
    print(f"  muon-loop piece of a_e = {mu_piece:.3e} vs exp. uncertainty {A_EXP_UNC:.1e}")
    assert mu_piece &gt; 10 * A_EXP_UNC, "muon piece unexpectedly small"
    print("  'The electron's intrinsic moment' contains the muon's mass at "
          f"{mu_piece/A_EXP_UNC:.1f}x experimental precision. A possession "
          "cannot contain other particles.")

    print("P.7 GREEN: g-2 is the flagship — every digit of the anomaly is "
          "encounter content (loops, IR resolution, other masses); the "
          "'intrinsic' Dirac term contributes exactly zero.")

if __name__ == "__main__":
    main()
```

Listing 18: P8 mass scheme

```
#!/usr/bin/env python3
"""P.8 — Mass has no unique "intrinsic" value: pole vs MS-bar vs scale.

INPUT_PROVENANCE (per Paper 11 V17/P2 staple):
  - Pole-MSbar relation coefficients: class=cited-paper
    (c1 = 4/3 one-loop; c2 = 13.4434 - 1.0414*n_l two-loop, Gray et al. /
    Chetyrkin-Steinhauser; n_l = 5 light flavors for the top).
  - alpha_s(M_Z) = 0.1180: class=cited-paper (PDG world average, representative).
  - One-loop mass anomalous dimension running: class=paper-defined
    (standard RG form m(mu)=m(mu0)[a(mu)/a(mu0)]^{gamma0/2beta0};
    declared assumption: one-loop truncation, n_f fixed — the mu-DEPENDENCE
    is the claim, not the exact trajectory).
  - gamma0 = 8 (quark mass anomalous dimension, one-loop), beta0 = 11-2n_f/3.

CONTINUUM_USE (v24 FORTRESS — explicit disclosure, Dervis's "disclose why"):
  - WHAT: the pole&lt;-&gt;MS-bar series m_pole = m_MS [1 + c1 (a_s/pi) +
    c2 (a_s/pi)^2] with cited-paper real coefficients; one-loop RG running
    with math.log (scale dependence) and real exponents.
  - WHY NEEDED: the exhibit IS the SM's own scheme/scale machinery — the
    paper's claim is "no unique encounter-free mass exists across definitions
```

```
    or scales", and the definitions (pole vs MS-bar) and the scale-dependence
    are the SM's real-analytic relations. The continuum is not scaffolding
    around the exhibit; it is the exhibit.
  - WHAT WOULD BE LOST INTEGER-NATIVE: the exhibited relations themselves.
    The definitional spread (~9 GeV vs 0.3 GeV precision) and the mu-dependence
    are statements about the SM's series and RG equations; an integer-native
    toy would exhibit *a* scheme-dependence, not the SM's. The renormalon
    ambiguity (disclosed, not computed) is likewise intrinsically about the
    series' large-order behavior in the continuum.

What the script checks (native domain: perturbative quark-mass definitions;
verified domain: the scheme/scale arithmetic):
  1. m_pole - m_MSbar for the top at one and two loops: the DEFINITIONAL spread
     across "the mass" exceeds experimental precision by an order of magnitude.
  2. m_MSbar(mu) evaluated at mu = m_b vs mu = M_Z: the number moves with the
     scale — the scale index is constitutive, not parametric.
  3. Planted mutant M1: assert the pole number IS "the intrinsic mass" and the
     MS-bar number is "a correction" — REJECTED: both are equally valid
     definitions, and the "correction" framing is scheme-conventional.

Map preserves: the size ordering (definitional spread &gt;&gt; exp. precision);
the sign and monotonicity of mu-dependence.
Outside the check: renormalon ambiguity of the pole mass (would strengthen the
point; disclosed, not computed); electroweak effects; full 4-loop running.
"""
import math

# ---- provenance: cited-paper inputs ----
ALPHA_S_MZ = 0.1180
C1 = 4.0 / 3.0
N_L = 5
C2 = 13.4434 - 1.0414 * N_L
GAMMA0 = 8.0

def beta0(nf):
    return 11.0 - 2.0 * nf / 3.0

def pole_from_msbar(m_ms, a_s, loops=2):
    """m_pole = m_MSbar * [1 + c1*(a/pi) + c2*(a/pi)^2 + ...]."""
    x = a_s / math.pi
    k = 1.0 + C1 * x
    if loops &gt;= 2:
        k += C2 * x * x
    return m_ms * k

def run_alphas(mu, mu0=91.1876, a0=ALPHA_S_MZ, nf=5):
    """One-loop alpha_s running (declared approximation)."""
    b0 = beta0(nf)
    return a0 / (1.0 + b0 * a0 / (2.0 * math.pi) * math.log(mu / mu0))

def run_mmsbar(mu, mu0, m0, nf=5):
    """One-loop MS-bar mass running (declared approximation)."""
    a_mu = run_alphas(mu, nf=nf)
    a_0 = run_alphas(mu0, nf=nf)
    return m0 * (a_mu / a_0) ** (GAMMA0 / (2.0 * beta0(nf)))

def main():
    print("P.8 — mass scheme/scale exhibit")
    # Representative MS-bar top mass (scale of order m_t); alpha_s run to ~m_t.
    m_ms_mt = 163.0  # GeV, representative MS-bar mass
    a_mt = run_alphas(163.0)
    m_pole_1 = pole_from_msbar(m_ms_mt, a_mt, loops=1)
    m_pole_2 = pole_from_msbar(m_ms_mt, a_mt, loops=2)
    spread_1 = m_pole_1 - m_ms_mt
    spread_2 = m_pole_2 - m_ms_mt
    print(f"  m_MSbar(m_t) = {m_ms_mt:.2f} GeV")
    print(f"  m_pole (1-loop) = {m_pole_1:.2f} GeV  (spread {spread_1:+.2f})")
    print(f"  m_pole (2-loop) = {m_pole_2:.2f} GeV  (spread {spread_2:+.2f})")
    exp_prec = 0.3  # GeV, representative experimental precision on m_t
    assert spread_1 &gt; 10 * exp_prec, "definitional spread unexpectedly small"
    print(f"  Definitional spread ({spread_1:.1f} GeV) &gt;&gt; experimental precision "
          f"({exp_prec} GeV): 'the' mass is definition-dependent.")

    # Scale dependence of the MS-bar mass itself (bottom quark illustration).
    m_b_mb = 4.18
    m_b_mz = run_mmsbar(91.1876, 4.18, m_b_mb, nf=5)
    print(f"  m_b(m_b) = {m_b_mb:.3f} GeV; m_b(M_Z) = {m_b_mz:.3f} GeV")
    assert m_b_mz &lt; m_b_mb, "mass should decrease with scale (QCD)"
    assert abs(m_b_mb - m_b_mz) &gt; 1.0, "scale shift unexpectedly small"
    print("  The MS-bar 'mass' moves with mu: the scale index is constitutive.")
```

```
    # Mutant M1: the pole number is THE intrinsic mass; MS-bar is "a correction".
    # Witness: the framing is reversible with equal validity — call MS-bar
    # "the" mass and the pole shift becomes "the correction". Neither choice is
    # licensed by the formalism; the formalism supplies a relation, not a ranking.
    rel = (m_pole_2 - m_ms_mt) / m_ms_mt
    print(f"  MUTANT M1 ('intrinsic' = pole): relative 'correction' = {rel:.3f}")
    assert rel &gt; 0.03, "mutant unexpectedly close"
    print("  M1 REJECTED: witness = the pole&lt;-&gt;MSbar relation is symmetric; "
          "'correction' is a scheme-conventional label, not a physical ranking. "
          "The renormalon ambiguity (disclosed, not computed) makes the pole "
          "mass itself definition-limited at O(Lambda_QCD).")

    print("P.8 GREEN: mass is the hardest case and it still fails — no unique "
          "encounter-free number exists across definitions or scales.")

if __name__ == "__main__":
    main()
```

Listing 19: P9 bell ternary tether

```
#!/usr/bin/env python3
"""P.9 — Ternary-outcome and tether analysis of Bell-CHSH for Paper 11.5.

Formalizes the framework's 3-axis critique of Bell-type tests as machine checks.

The framework's position (lab notes: "The Bell Test Fallacy"; "The Binary Trap"):
  (a) Per measurement axis there are THREE states: +1, -1, and 0 (neutral).
      The neutral is load-bearing (the (0,0,0) photon baseline; Gluon 4 anchor).
      CHSH admits only binary (+-1) outcomes: zeros are erased (P.2 assigns
      ties by fiat) and nulls are discarded unpublished.
  (b) Bell assumes the two particles are independent ("container-void").
      In SPDC they are one tethered geometric structure; the violation evidences
      the tether's rigidity, not "spooky action."

INTEGER-NATIVE (v24 FORTRESS): no arccos, no uniform-sphere RNG, no floats.
The hidden-variable ensemble is DETERMINISTIC: all nonzero integer triples
(i,j,k) with i^2+j^2+k^2 &lt;= 12^2 (7,152 orientations — no sampling, no seed).
All projections are exact integer comparisons (squaring with sign care);
all correlators are exact Fractions. DELTA = 3/20 is an exact rational
threshold, not a float. The v23 "assumed scaffolding [CLASSIFIED]"
(uniform-over-the-sphere measure) is GONE — there is no measure to assume.

What this script checks:
  1. PROJECTION-DEPENDENCE: a local ternary hidden-variable model (definite
     tilt axis per particle, neutral band for near-orthogonal tilts) generates
     ternary data; CHSH's S is then computed under four handlings of 0.
     Result: the verdict moves with the projection rule -&gt; the binary verdict
     is conditional on a data-processing choice absent from the physics.
     Verified at DELTA in {1/10, 3/20, 1/5}: the spread scales with DELTA.
  2. LOCAL TERNARY BOUND (machine-proved): brute force over all 81 deterministic
     {+1,-1,0} assignments shows max|S| = 2. Ternary outcomes do NOT lift the
     local bound. (Honesty: the "binary trap" is representational; the
     phenomenon is not a binary artifact.)
  3. TETHER MODEL: one shared geometric hidden variable (the tether state),
     outcomes computed jointly from BOTH settings (non-separable). Deterministic,
     reproduces E(a,b) = -a.b (exact rational bracket) and S within 0.04 of
     2*sqrt(2). This is an existence proof: deterministic + pre-existing
     structure + CHSH violation is consistent. Bell excludes SEPARABILITY,
     not structure. The |S - 2√2| &lt; TOL check is done by exact rational
     bracketing (see S_IN_BRACKET below) — no floats.

What this script does NOT show (stated limits):
  - It does not derive the tether's gear-mechanics; the tether response is
    schematic (a joint threshold). It formalizes the LOGICAL point
    (non-separability suffices), not the full mechanical model.
  - The ternary-local bound means "add the neutral" alone does not reproduce QM.
    A critic citing CGLMP (ternary Bell inequalities, also violated) is correct
    about the phenomenon; our point is about the TEST's representational scope.
  - Bell's theorem (the mathematics) is not refuted and cannot be: it is proven.
    What is refuted is its USE as an ontological verdict ("Ontology B won").
    The test adjudicates separable binary-outcome models. Nothing more.
  - On the integer lattice, exact ties (orthogonality) carry positive weight —
    the v23 "measure-zero" language does not transfer. Tie-handling is by fiat
    and stated; Part 1's verdict is checked robust across DELTA values.

INPUT_PROVENANCE:
  - Ternary-outcome structure (+1/-1/0 per axis): class=paper-defined
    (framework posit; the neutral anchor).
  - DELTA = 3/20 neutral-band half-width: class=declared-assumption
```

```
    (a framework posit — the neutral anchor's width — not derived; exact
    rational, not a float; finding verified at 1/10 and 1/5 as well).
  - Tether joint-threshold response: class=paper-defined (schematic; the
    logical point is non-separability, not the mechanism).
  - Orientation ensemble: class=control (deterministic integer lattice R=12).
  - CHSH bound / singlet E(a,b) = -a.b: class=cited-paper.
"""
import sys
from fractions import Fraction
from itertools import product

GRID_R = 12          # deterministic integer-lattice radius (7,152 orientations)
DELTA = Fraction(3, 20)   # neutral band half-width: |m.n| &lt;= DELTA -&gt; 0 (exact)
TOL = Fraction(1, 25)     # = 0.04, exact


def lattice_orientations(R=GRID_R):
    """Deterministic hidden-variable ensemble: every nonzero integer triple
    (i,j,k) with i^2+j^2+k^2 &lt;= R^2. Returns (i, j, k, i^2+j^2+k^2)."""
    pts = []
    R2 = R * R
    for i in range(-R, R + 1):
        for j in range(-R, R + 1):
            for k in range(-R, R + 1):
                n2 = i * i + j * j + k * k
                if 0 &lt; n2 &lt;= R2:
                    pts.append((i, j, k, n2))
    return pts


def sgn(v):
    """sign with ties -&gt; +1 by fiat (stated)."""
    return 1 if v &gt;= 0 else -1


# ---------------------------------------------------------------------------
# Part 1: local ternary model. Projections as exact integer comparisons.
# Neutral iff (m.n)^2 &lt;= DELTA^2 (m.m)(n.n); DELTA^2 = 9/400.
#   axis a=(0,0,1): m.n = k            -&gt; 400 k^2        &lt;= 9 n2
#   axis a'=(1,0,0): m.n = i           -&gt; 400 i^2        &lt;= 9 n2
#   axis b (45°): m.n = (i+k)/√2       -&gt; 200 (i+k)^2   &lt;= 9 n2
#   axis b' (135°): m.n = (i-k)/√2     -&gt; 200 (i-k)^2    &lt;= 9 n2
# ---------------------------------------------------------------------------
def gen_local_ternary(pts, delta=DELTA):
    """Local ternary hidden-variable model. Each particle carries its own
    definite tilt axis (m1 = lattice orientation; m2 = -m1, singlet-like).
    Outcomes depend ONLY on own state + own setting. Ternary, deterministic."""
    dn, dd = delta.numerator, delta.denominator
    out = {"a": [], "ap": [], "b": [], "bp": []}
    for (i, j, k, n2) in pts:
        o_a = 0 if (k * k * dd * dd &lt;= dn * dn * n2) else (1 if k &gt; 0 else -1)
        o_ap = 0 if (i * i * dd * dd &lt;= dn * dn * n2) else (1 if i &gt; 0 else -1)
        sp, sm = i + k, i - k
        o_b = 0 if (sp * sp * dd * dd &lt;= 2 * dn * dn * n2) else (1 if sp &gt; 0 else -1)
        o_bp = 0 if (sm * sm * dd * dd &lt;= 2 * dn * dn * n2) else (1 if sm &gt; 0 else -1)
        out["a"].append(o_a)
        out["ap"].append(o_ap)
        out["b"].append(o_b)
        out["bp"].append(o_bp)
    return out
def E_of(X, Y, rule):
    """Correlator under projection rule for zeros. Exact Fraction."""
    n = len(X)
    if rule == "zero_to_plus1":
        return Fraction(sum((1 if x == 0 else x) * (1 if y == 0 else y)
                            for x, y in zip(X, Y)), n)
    if rule == "zero_to_minus1":
        return Fraction(sum((-1 if x == 0 else x) * (-1 if y == 0 else y)
                            for x, y in zip(X, Y)), n)
    if rule == "drop_zeros":
        vals = [x * y for x, y in zip(X, Y) if x != 0 and y != 0]
        return Fraction(sum(vals), len(vals))
    if rule == "keep_zeros":
        return Fraction(sum(x * y for x, y in zip(X, Y)), n)
    raise ValueError(rule)


def S_under_rule(out, rule):
    Eab = E_of(out["a"], out["b"], rule)
    Eabp = E_of(out["a"], out["bp"], rule)
```

```
    Eapb = E_of(out["ap"], out["b"], rule)
    Eapbp = E_of(out["ap"], out["bp"], rule)
    return abs(Eab - Eabp + Eapb + Eapbp)


def brute_force_ternary_bound():
    """Max |AB - AB' + A'B + A'B'| over all deterministic {+1,-1,0}
    assignments. Machine-proved local ternary bound."""
    best = 0
    witness = None
    for vals in product((-1, 0, 1), repeat=4):
        A, Ap, B, Bp = vals
        s = abs(A * B - A * Bp + Ap * B + Ap * Bp)
        if s &gt; best:
            best = s
            witness = vals
    return best, witness


# ---------------------------------------------------------------------------
# Part 3: tether. T = +1 iff tau.d &gt; -(a.b), d = z-axis, tau.d = k/|tau|.
# Threshold specs: ("s", +1) means a.b = +1/√2; ("q", num, den) means a.b =
# num/den exactly. All comparisons integer-exact (squaring with sign care).
# E[A*B] = -E[T] since B = -A*T and A^2 = 1.
# ---------------------------------------------------------------------------
def tether_T(k, n2, spec):
    kind = spec[0]
    if kind == "s":
        s = spec[1]  # +1 or -1: threshold ±1/√2
        if s == 1:
            return 1 if (k &gt;= 0 or 2 * k * k &lt; n2) else -1
        else:
            return -1 if (k &lt;= 0 or 2 * k * k &lt;= n2) else 1
    else:
        num, den = spec[1], spec[2]
        if num &gt; 0:
            return 1 if (k &gt;= 0 or k * k * den * den &lt; num * num * n2) else -1
        else:
            m = -num
            return 1 if (k &gt; 0 and k * k * den * den &gt; m * m * n2) else -1


def tether_correlator(pts, A_fn, spec):
    tot = 0
    for (i, j, k, n2) in pts:
        A = A_fn(i, j, k)
        assert A * A == 1, "binary-outcome premise violated"
        T = tether_T(k, n2, spec)
        tot += -T  # A*B = -A*A*T = -T
    return Fraction(tot, len(pts))


def tether_S(pts):
    Eab = tether_correlator(pts, lambda i, j, k: sgn(k), ("s", +1))    # a.b=+1/√2
    Eabp = tether_correlator(pts, lambda i, j, k: sgn(k), ("s", -1))   # a.b=−1/√2
    Eapb = tether_correlator(pts, lambda i, j, k: sgn(i), ("s", +1))   # a'.b=+1/√2
    Eapbp = tether_correlator(pts, lambda i, j, k: sgn(i), ("s", +1))  # a'.b'=+1/√2
    return abs(Eab - Eabp + Eapb + Eapbp)


def S_in_bracket(S):
    """Exact check |S − 2√2| &lt; TOL via rational bracketing — no floats.

    S &gt; 279/100 implies S &gt; 2√2 − 1/25 because 279/100 ≥ 2√2 − 1/25
      ⇔ 283/100 ≥ 2√2 ⇔ 283² ≥ 8·100² ⇔ 80089 ≥ 80000. ✓
    S &lt; 286/100 implies S &lt; 2√2 + 1/25 because 286/100 ≤ 2√2 + 1/25
      ⇔ 282/100 ≤ 2√2 ⇔ 282² ≤ 8·100² ⇔ 79524 ≤ 80000. ✓
    """
    assert 283 * 283 &gt;= 8 * 100 * 100, "bracket witness (lower) broken"
    assert 282 * 282 &lt;= 8 * 100 * 100, "bracket witness (upper) broken"
    return Fraction(279, 100) &lt; S &lt; Fraction(286, 100)


def mutant_severed_tether(pts):
    """PLANTED MUTANT: sever the tether. Bob's outcome uses ONLY his own side
    (own hidden-variable read + own setting): genuinely separable.
    S must fall to the local bound (&lt;= 2). If it does, separability --
    not determinism, not pre-existing structure -- was the load-bearing
    assumption."""
    n = len(pts)
```

```
    def E(Xfn, Yfn):
        return Fraction(sum(Xfn(i, j, k) * Yfn(i, j, k)
                            for (i, j, k, n2) in pts), n)

    A = lambda i, j, k: sgn(k)            # noqa: E731
    Ap = lambda i, j, k: sgn(i)           # noqa: E731
    Bb = lambda i, j, k: sgn(-i - k)      # noqa: E731
    Bbp = lambda i, j, k: sgn(-i + k)     # noqa: E731
    return abs(E(A, Bb) - E(A, Bbp) + E(Ap, Bb) + E(Ap, Bbp))


def mutant_joint_blind_tether(pts):
    """PLANTED MUTANT 2: keep the tether structure but make the joint response
    blind to the settings — T = sign(tau.d), the a.b threshold removed.
    If S collapses, the JOINT (both-settings) dependence of T — not merely
    determinism — was load-bearing."""
    n = len(pts)
    def E(A_fn):
        tot = 0
        for (i, j, k, n2) in pts:
            A = A_fn(i, j, k)
            assert A * A == 1, "binary-outcome premise violated"
            tot += -sgn(k)  # T = sign(tau.d), no a.b threshold
        return Fraction(tot, n)

    Eab = E(lambda i, j, k: sgn(k))
    Eapb = E(lambda i, j, k: sgn(i))
    return abs(Eab - Eab + Eapb + Eapb)


def mutant_neutral_erased(pts):
    """PLANTED MUTANT 3 (Part 1): erase the neutral band up front (0 -&gt; +1
    before any projection rule). All four rules then coincide exactly, so the
    spread must be 0 — proving the projection-dependence was carried by the
    neutral band, not by code artifacts."""
    out = gen_local_ternary(pts)
    out_bin = {name: [1 if v == 0 else v for v in vals]
               for name, vals in out.items()}
    rules = ["zero_to_plus1", "zero_to_minus1", "drop_zeros", "keep_zeros"]
    S_vals = [S_under_rule(out_bin, r) for r in rules]
    return max(S_vals) - min(S_vals)


def main():
    print("=" * 70)
    print("P.9 — TERNARY-OUTCOME AND TETHER ANALYSIS OF BELL-CHSH")
    print("  (v24 FORTRESS: integer-native — deterministic lattice, no floats)")
    print("=" * 70)

    pts = lattice_orientations()
    print(f"\nDeterministic orientation ensemble: {len(pts)} integer-lattice "
          f"orientations (R={GRID_R}). No RNG, no sphere sampling.")

    # ---- Part 1: projection-dependence ----
    print("\n--- PART 1: the binary verdict moves with the projection rule ---")
    rules = ["zero_to_plus1", "zero_to_minus1", "drop_zeros", "keep_zeros"]
    for delta in (Fraction(1, 10), DELTA, Fraction(1, 5)):
        out = gen_local_ternary(pts, delta)
        n_zero = sum(1 for a, b in zip(out["a"], out["b"]) if a == 0 or b == 0)
        S_vals = {r: S_under_rule(out, r) for r in rules}
        spread = max(S_vals.values()) - min(S_vals.values())
        print(f"  DELTA={delta}: neutral frac={Fraction(n_zero, len(pts))} "
              f"≈ {n_zero / len(pts):.3f}; " +
              "; ".join(f"S[{r}]={v}≈{float(v):.4f}" for r, v in S_vals.items()))
        print(f"    spread = {spread} ≈ {float(spread):.4f}")
    out = gen_local_ternary(pts)
    S_vals = {r: S_under_rule(out, r) for r in rules}
    spread = max(S_vals.values()) - min(S_vals.values())
    proj_dependent = spread &gt; Fraction(1, 20)
    print("  =&gt; " + ("VERDICT IS PROJECTION-CONDITIONAL: the binary S depends on "
                       "how 0 is handled — a data-processing choice, not physics."
                       if proj_dependent else
                       "no projection dependence detected."))

    inflated = S_vals["drop_zeros"] &gt; S_vals["keep_zeros"] + TOL
    print("  drop-zeros vs keep-zeros: "
          + ("INFLATED — post-selection artifact flagged (detection-loophole analog)."
             if inflated else "no inflation."))

    # ---- Part 2: machine-proved local ternary bound ----
```

```
print("\n--- PART 2: machine-proved local ternary bound ---")
best, witness = brute_force_ternary_bound()
print(f"  max |AB − AB' + A'B + A'B'| over all 81 deterministic "
      f"{{+1,−1,0}} assignments = {best}  (witness {witness})")
print("  =&gt; ternary outcomes do NOT lift the local bound. The binary trap is")
print("     representational; the phenomenon is not a binary artifact.")

# ---- Part 3: tether ----
print("\n--- PART 3: the tether (non-separable, deterministic) ---")
S_t = tether_S(pts)
print(f"  tether S = {S_t} ≈ {float(S_t):.4f}  (target 2√2 ≈ 2.8284)")
tether_ok = S_in_bracket(S_t)
print(f"  exact rational bracket 2.79 &lt; S &lt; 2.86 holds: {tether_ok} "
      f"=&gt; |S − 2√2| &lt; 0.04 by the integer-square witnesses.")
# full correlator check at non-CHSH settings (rational unit vectors,
# exact thresholds — same logical check as the v23 angle pairs)
check_pairs = [
    (lambda i, j, k: 3 * i + 4 * k, ("q", 4, 5), "a=(3/5,0,4/5), b=(0,0,1)",
     Fraction(-4, 5)),
    (lambda i, j, k: k, ("q", -4, 5), "a=(0,0,1), b=(3/5,0,−4/5)",
     Fraction(4, 5)),
    (lambda i, j, k: 5 * i + 12 * k, ("q", 12, 13), "a=(5/13,0,12/13), b=(0,0,1)",
     Fraction(-12, 13)),
]
corr_ok = True
for A_fn, spec, label, target in check_pairs:
    e = tether_correlator(pts, lambda i, j, k: sgn(A_fn(i, j, k)), spec)
    ok = abs(e - target) &lt; TOL
    corr_ok &amp;= ok
    print(f"  E[{label}] = {e} ≈ {float(e):+.4f} vs −a·b = {target}  "
          f"{'OK' if ok else 'MISMATCH'}")
print("  =&gt; deterministic + pre-existing structure + CHSH violation is "
      "consistent. Bell excludes SEPARABILITY, not structure.")
print("  NOTE (loop-caught, kept): this tether model as coded uses BINARY")
print("  outcomes; it witnesses non-separability, not the ternary structure —")
print("  the ternary critique lives in Parts 1–2. The two prongs are presented")
print("  separately and honestly, not conflated.")

# ---- Mutants ----
print("\n--- PLANTED MUTANT 1 (Part 1): erase the neutral up front ---")
m1 = mutant_neutral_erased(pts)
m1_caught = (m1 == 0)
print(f"  spread with neutral erased: {m1}  "
      + ("=&gt; MUTANT KILLED the effect: projection-dependence was carried "
         "by the neutral band, not by code artifacts." if m1_caught
         else "=&gt; UNEXPECTED: spread survives without neutrals."))

print("\n--- PLANTED MUTANT 2: sever the tether (force separability) ---")
S_sev = mutant_severed_tether(pts)
print(f"  severed-tether S = {S_sev} ≈ {float(S_sev):.4f}")
m2_caught = S_sev &lt;= 2 + TOL and S_t &gt; 2 + TOL
print("  =&gt; " + ("MUTANT REJECTED AS LOCAL: S collapses when separability is "
                   "forced. Separability — not determinism — was load-bearing."
                   if m2_caught else
                   "UNEXPECTED: severed tether still violates. Investigate."))

print("\n--- PLANTED MUTANT 3: joint response blind to settings ---")
S_jb = mutant_joint_blind_tether(pts)
print(f"  joint-blind S = {S_jb} ≈ {float(S_jb):.4f}")
m3_caught = S_jb &lt;= 2 + TOL
print("  =&gt; " + ("MUTANT REJECTED: without the both-settings threshold, no "
                   "violation — the JOINT dependence was load-bearing."
                   if m3_caught else
                   "UNEXPECTED: joint-blind tether still violates."))

# ---- Verdicts ----
print("\n" + "=" * 70)
print("P.9 VERDICT")
print("=" * 70)
checks = [
    ("projection-dependence demonstrated", proj_dependent),
    ("local ternary bound = 2 (machine-proved)", best == 2),
    ("tether reproduces QM correlations", tether_ok and corr_ok),
    ("mutant 1 (neutral erased) kills the spread", m1_caught),
    ("mutant 2 (severed tether) caught as local", m2_caught),
    ("mutant 3 (joint-blind) caught", m3_caught),
]
all_ok = True
for name, ok in checks:
    print(f"  [{'PASS' if ok else 'FAIL'}] {name}")
```

```
        all_ok &amp;= ok

    print("\nINTERPRETATION (what the machine states):")
    print("  1. CHSH as run (P.2) tests SEPARABLE, BINARY-OUTCOME models.")
    print("     Zeros are erased and nulls unpublished — by construction,")
    print("     not by nature. The verdict is conditional on that projection.")
    print("  2. Adding the neutral does not save LOCAL models (bound stays 2).")
    print("     The tether — non-separable by construction — was never in")
    print("     Bell's scope. 'Ontology B won because of Bell' is unwarranted;")
    print("     'Bell excludes all pre-existing structure' is false, witnessed")
    print("     by the tether reaching 2√2-bracket deterministically.")
    print("  3. Limits: the tether response is schematic (joint threshold), not")
    print("     the full gear-mechanics; Bell's mathematics is untouched — only")
    print("     its USE as an ontological verdict is refuted.")
    return 0 if all_ok else 1


if __name__ == "__main__":
    sys.exit(main())
```

Listing 20: P10 g2 loop spectrum

```
#!/usr/bin/env python3
"""P.10 — g-2 loop spectrum: QED vertex-diagram counts per loop order.

Tabulates how many Feynman diagrams the QED vertex correction contains at
each loop order: 1, 7, 72, 891, 12672.

INPUT_PROVENANCE:
  - Diagram generator (1- and 2-loop counts): paper-defined. The encoded
    rules are DECLARED ASSUMPTIONS of the counting exercise, printed below:
      (a) every internal vertex is a QED 3-point vertex (2 fermion stubs +
          1 photon stub);
      (b) external legs fixed: 1 incoming fermion, 1 outgoing fermion,
          1 photon; isomorphisms must fix all three (fermion direction
          fixes the open line pointwise);
      (c) Furry's theorem: a closed fermion loop carries an even number
          (&gt;= 2) of photon vertices — C-odd amplitudes vanish;
      (d) proper-vertex filter: the amputated (internal-line) graph must be
          connected and bridgeless (1PI) — external-leg self-energies and
          vertex-reducible graphs are not counted, matching the
          Kinoshita-program convention for a_e.
    The COUNTS (1 and 7) are DERIVED: the generator enumerates every
    stub-pairing at the given loop order and quotients by graph
    isomorphism via brute-force canonical labeling. Nothing about the
    answers is hardcoded; the assertions check the machine's results.
  - 72 / 891 / 12672 (3-, 4-, 5-loop): class=cited-paper, reproduced as
    the published record, explicitly NOT derived here:
      72:    T. Kinoshita, Phys. Rev. Lett. 75, 4728 (1995) — numerical
             sixth order; analytic: S. Laporta &amp; E. Remiddi,
             Phys. Lett. B 379, 283 (1996).
      891:   T. Kinoshita &amp; W. B. Lindquist, Phys. Rev. Lett. 47, 1573
             (1981); revised: T. Aoyama, M. Hayakawa, T. Kinoshita &amp;
             M. Nio, Phys. Rev. D 77, 053012 (2008).
      12672: T. Aoyama, M. Hayakawa, T. Kinoshita &amp; M. Nio,
             Phys. Rev. Lett. 109, 111807 (2012);
             Phys. Rev. D 85, 033007 (2012).
    Enumerating 72+ diagrams by hand-generation is beyond this script's
    scope; the literature values are carried as oracle with provenance.

Structural point (v15 honest-scope narrowing, machine-backed): the vertex correction at
every loop order IS a sum over N discrete diagrams — 1 -&gt; 7 -&gt; 72 -&gt; 891 -&gt;
12672. Each diagram is evaluated by continuum loop integrals (the paper's
own §3.6(b); §11.6 admits the continuum upstream in the formulas); the
integer count N is the discrete, convention-indexed signature — the
proper-vertex (1PI) count used by the Kinoshita program. The growth is
visible at order one no less than order five, not a 5-loop accident.
"""
import sys
import itertools


# ---------------------------------------------------------------------------
# Small graph utilities (brute force; graphs are tiny)
# ---------------------------------------------------------------------------

def _pairings(items):
    """Yield all perfect matchings of `items` (length must be even)."""
    if not items:
```

```
        yield []
        return
    a = items[0]
    for i in range(1, len(items)):
        b = items[i]
        rest = items[1:i] + items[i + 1:]
        for sub in _pairings(rest):
            yield [(a, b)] + sub


def _compositions(total, parts):
    """Yield all compositions of `total` into `parts` positive parts."""
    if parts == 1:
        yield (total,)
        return
    for first in range(1, total - parts + 2):
        for sub in _compositions(total - first, parts - 1):
            yield (first,) + sub


def _connected(n, edges):
    adj = [[] for _ in range(n)]
    for a, b in edges:
        adj[a].append(b)
        adj[b].append(a)
    seen = {0}
    stack = [0]
    while stack:
        u = stack.pop()
        for w in adj[u]:
            if w not in seen:
                seen.add(w)
                stack.append(w)
    return len(seen) == n


def _has_bridge(n, edges):
    """True if any edge is a bridge (brute force; n is tiny)."""
    adj = [[] for _ in range(n)]
    for a, b in edges:
        adj[a].append(b)
        adj[b].append(a)
    for (a, b) in edges:
        seen = {a}
        stack = [a]
        while stack:
            u = stack.pop()
            for w in adj[u]:
                if (u == a and w == b) or (u == b and w == a):
                    continue
                if w not in seen:
                    seen.add(w)
                    stack.append(w)
        if b not in seen:
            return True
    return False


# ---------------------------------------------------------------------------
# QED vertex-diagram generator
# ---------------------------------------------------------------------------

def _canonical(E0, loop_v, partner, ext):
    """Canonical signature under all allowed relabelings.

    The open line is fixed pointwise: fermion edges are directed and the
    external in/out legs are fixed, so the directed f_in -&gt; f_out path is
    unique. Only closed loops may be permuted / rotated / reflected.
    """
    nj = len(loop_v)
    best = None
    for perm in itertools.permutations(range(nj)):
        dihedral = []
        for j in perm:
            m = len(loop_v[j])
            opts = []
            for s in range(m):
                opts.append(tuple((s + r) % m for r in range(m)))
                opts.append(tuple((s - r) % m for r in range(m)))
            dihedral.append((j, opts))
```

```
        for combo in itertools.product(*[o for _, o in dihedral]):
            newloops = []
            for (j, _), order in zip(dihedral, combo):
                newloops.append([loop_v[j][r] for r in order])

            def rep(v):
                if v == ext:
                    return ("X",)
                p = partner[v]
                if p &lt; E0:
                    return ("o", p)
                for pi, nl in enumerate(newloops):
                    if p in nl:
                        return ("l", pi, nl.index(p))
                raise AssertionError("partner vertex not found")

            open_sig = tuple(rep(i) for i in range(E0))
            loop_sig = tuple(tuple(rep(v) for v in nl) for nl in newloops)
            sig = (open_sig, loop_sig)
            if best is None or sig &lt; best:
                best = sig
    return best


def vertex_diagrams(L):
    """Return the set of canonical signatures of proper QED vertex
    diagrams at L loops.  Empty-loop edge cases and tadpoles are
    excluded by the Furry filter (even &gt;= 2 vertices per closed loop)."""
    E_total = 2 * L + 1  # one endpoint carries the external photon
    sigs = set()
    for k in range(1, L + 2):  # k fermion lines; closed loops &lt;= L
        for comp in _compositions(E_total, k):
            E0 = comp[0]
            loop_lens = comp[1:]
            if any(m % 2 == 1 or m &lt; 2 for m in loop_lens):
                continue  # Furry: closed loop needs even &gt;= 2 vertices
            open_v = list(range(E0))
            loop_v = []
            base = E0
            for m in loop_lens:
                loop_v.append([base + r for r in range(m)])
                base += m
            assert base == E_total
            # internal fermion segments
            fsegs = [(i, i + 1) for i in range(E0 - 1)]
            for lv in loop_v:
                m = len(lv)
                fsegs += [(lv[r], lv[(r + 1) % m]) for r in range(m)]
            verts = list(range(E_total))
            for ext in verts:
                rest = [v for v in verts if v != ext]
                for pairing in _pairings(rest):
                    partner = {}
                    for a, b in pairing:
                        partner[a] = b
                        partner[b] = a
                    pedges = [(min(a, b), max(a, b)) for a, b in pairing]
                    edges = fsegs + pedges
                    if not _connected(E_total, edges):
                        continue
                    if _has_bridge(E_total, edges):
                        continue  # not a proper (1PI) vertex diagram
                    sigs.add(_canonical(E0, loop_v, partner, ext))
    return sigs


# Cited literature oracle (NOT derived here; see INPUT_PROVENANCE).
ORACLE = {
    3: (72, "Kinoshita PRL 75, 4728 (1995); Laporta-Remiddi PLB 379, 283 (1996)"),
    4: (891, "Kinoshita-Lindquist PRL 47, 1573 (1981); Aoyama et al. PRD 77, 053012 (2008)"),
    5: (12672, "Aoyama-Hayakawa-Kinoshita-Nio PRL 109, 111807 (2012); PRD 85, 033007 (2012)"),
}


def main():
    print("=" * 70)
    print("P.10 — g-2 LOOP SPECTRUM")
    print("QED vertex-diagram counts per loop order")
    print("=" * 70)
    print("\nRules (declared assumptions): QED 3-point vertices; external")
```

```
    print("legs fixed (f_in, f_out, photon); Furry (even &gt;= 2 vertices per")
    print("closed fermion loop); proper-vertex filter (amputated graph")
    print("connected and bridgeless). Counts are DERIVED by the generator,")
    print("not hardcoded.\n")

    derived = {}
    for L in (1, 2):
        sigs = vertex_diagrams(L)
        derived[L] = len(sigs)
        print(f"  {L}-loop: {len(sigs)} diagrams (derived by enumeration)")

    # The generator must reproduce the textbook counts — or fail loudly.
    assert derived[1] == 1, f"1-loop count came out {derived[1]}, expected 1"
    assert derived[2] == 7, f"2-loop count came out {derived[2]}, expected 7"
    print("\nDERIVATION CHECK PASS: 1-loop -&gt; 1, 2-loop -&gt; 7.")

    print("\nLoop-order spectrum (derived + cited oracle):")
    print("-" * 70)
    print(f"  {'order':&gt;5} | {'diagrams':&gt;8} | status")
    print("-" * 70)
    for L in range(1, 6):
        if L in derived:
            print(f"  {L:&gt;5} | {derived[L]:&gt;8} | DERIVED (this script)")
        else:
            n, ref = ORACLE[L]
            print(f"  {L:&gt;5} | {n:&gt;8} | CITED ORACLE — {ref}")
    print("-" * 70)

    print("\nP.10 VERDICT: the vertex correction at every loop order IS a sum")
    print("over N discrete diagrams — each evaluated by continuum loop")
    print("integrals; the integer count N (1 -&gt; 7 -&gt; 72 -&gt; 891 -&gt; 12672) is")
    print("the discrete, convention-indexed signature. The 'intrinsic' moment")
    print("is the sum; there is no bare remainder.")
    return 0


if __name__ == "__main__":
    sys.exit(main())
```

Listing 21: PA1 parsing agent

```
#!/usr/bin/env python3
"""PA.1 — Parsing Agent for Paper 11.5.

Takes Standard Model property claims (as stated in textbooks/prose) and parses
each into: (1) the formal content (what the equations actually say),
(2) the gloss (what the prose adds), (3) the badge verdict under Paper 11's
discipline.

This is the mechanical reader Dervis asked for: feed it SM claims, it separates
derived content from smuggled gloss, and reports the honesty verdict.

Usage: python3 PA1_parsing_agent.py [--claim "text"]
  Without --claim, runs the six canonical SM claims from the paper.

Draft resolution (v19 fallback chain): --draft -&gt; $PAPER_MD -&gt;
paper_11_5_draft.md -&gt; paper.md -&gt; newest paper_11_5_v&lt;N&gt;.md.
The resolved draft file is printed on every run.

v24 FORTRESS hardening (V23-20): subsection parsing is fail-loud — every
§3.1–3.6 subsection must carry its (a)/(b)/(c) markers in order; a subsection
that doesn't is skipped with a printed WARNING naming it (the totals never
silently shrink), and zero parsed subsections exits nonzero.
"""
import re
import sys
import argparse


# Knowledge base: for each property, the formal content and the gloss
KB = {
    "spin": {
        "formal": "S.n-hat has eigenvalues +-h/2; n-hat is the field axis (constitutive).",
        "gloss": "Drop n-hat; claim 'spin-1/2' as a standalone possession.",
        "badge": "NO BADGE (REFUTED by Bell, local scope — pre-existing local values, §8.3b; "
                 "the axis-constituted reading itself is GAP, §8.3a)",
        "paper11": "RELATIONAL_ROLE_THEOREM [A]",
    },
```

```
    "charge": {
        "formal": "L_int = -e(mu) psi-bar gamma psi A; e runs with scale mu.",
        "gloss": "Drop mu; claim 'charge -e' as scale-free possession.",
        "badge": "NO BADGE (SMUGGLED)",
        "paper11": "PORT_PARTITION_EXACTNESS [A]",
    },
    "color": {
        "formal": "SU(3) gauge label; cancels from S-matrix (Elitzur); N_c=3 in rates.",
        "gloss": "Promote gauge label to 'intrinsic color charge' possession.",
        "badge": "NO BADGE (SMUGGLED)",
        "paper11": "STRUCTURAL_INSULATION [A]",
    },
    "flavor": {
        "formal": "V_CKM rotates weak vs mass bases; flavor is basis-relative.",
        "gloss": "Treat basis-dependence as correction; claim 'intrinsic flavor'.",
        "badge": "NO BADGE (SMUGGLED)",
        "paper11": "RELATIONAL_ROLE_THEOREM [A]",
    },
    "mass": {
        "formal": "m^2 from decay kinematics; m_f = y_f v/sqrt(2) with VEV background.",
        "gloss": "Forget VEV/kinematics; claim 'intrinsic mass' as possession.",
        "badge": "NO BADGE (SMUGGLED)",
        "paper11": "Paper 8 mass-as-ledger [A]",
    },
    "magnetic moment": {
        "formal": "a_e = sum over 12,672 virtual-encounter loop diagrams.",
        "gloss": "Attribute encounter sum to 'the electron' alone.",
        "badge": "NO BADGE (SMUGGLED)",
        "paper11": "ASPECT_AGGREGATION [A]",
    },
}


def parse_claim(text):
    """Parse an SM claim. Returns (property, formal, gloss, badge, paper11),
    or ("AMBIGUOUS", ...) if the input matches more than one property
    (fail closed: never silently misroute), or None if nothing matches.

    Routing fix (v15): color-specific terms participate in matching, and a
    documented priority resolves exactly one known subsumption: when the
    input matches ONLY color and generic charge (e.g. "color charge"),
    color wins — "charge" is a substring of "color charge", so without
    priority the generic entry would swallow the specific one. Any OTHER
    multi-property match (color+spin, charge+flavor, ...) fails closed
    as AMBIGUOUS. The priority is a resolution rule for a known overlap,
    not a bypass of ambiguity detection (v15 loop repair).
    """
    text_lower = text.lower()

    matches = []
    # Color-specific terms (no fast-path return; ambiguity is counted below).
    color_terms = ["color", "colour", "chromo", "qcd", "su(3)"]
    if any(t in text_lower for t in color_terms):
        matches.append("color")

    for prop, data in KB.items():
        if prop == "color":
            continue  # handled above
        # Match property name or related terms
        terms = [prop]
        if prop == "magnetic moment":
            terms += ["g-2", "g minus 2", "anomalous moment"]
        if prop == "charge":
            terms += ["electric charge"]
        if any(t in text_lower for t in terms):
            matches.append(prop)

    if not matches:
        return None

    # Documented priority: the ONLY resolved overlap is color-over-charge.
    if set(matches) &lt;= {"color", "charge"} and "color" in matches:
        prop = "color"
    elif len(matches) &gt; 1:
        # Fail closed on any other ambiguity: never silently pick one.
        return ("AMBIGUOUS",
                f"input matches {len(matches)} properties: "
                f"{', '.join(matches)}",
                "disambiguate before parsing",
                "NO BADGE (UNPARSEABLE — ambiguous input)",
```

```
                "—")
    else:
        prop = matches[0]
    data = KB[prop]
    # Check if it claims intrinsicality
    if re.search(r"\bintrinsic\b", text_lower):
        return (prop, data["formal"], data["gloss"], data["badge"],
                data["paper11"])
    return (prop, data["formal"], "(no intrinsic gloss detected)",
            "NOT APPLICABLE", data["paper11"])



def _resolve_draft_noargv(here):
    """Fallback chain (v19), no-argv variant: $PAPER_MD -&gt; candidate filenames.

    argparse already consumed argv, so --draft is honored verbatim by the
    caller; this variant runs only when --draft was not given. $PAPER_MD
    pointing at a nonexistent file falls through to the candidates.
    Candidate order: paper_11_5_draft.md, paper.md, then paper_11_5_v&lt;N&gt;.md
    newest-first. Inlined: scripts stay standalone, no shared imports.
    """
    import os, re
    from pathlib import Path
    env = os.environ.get("PAPER_MD")
    if env and Path(env).is_file():
        return Path(env)
    cands = [here.parent / "paper_11_5_draft.md",
             here.parent / "paper.md"]
    def _vkey(p):
        m = re.search(r"v(\d+)\.md$", p.name)
        return int(m.group(1)) if m else -1
    cands += sorted(here.parent.glob("paper_11_5_v*.md"), key=_vkey, reverse=True)
    for c in cands:
        if c.is_file():
            return c
    raise FileNotFoundError(
        "no paper draft found; tried --draft, $PAPER_MD, and: "
        + ", ".join(str(c) for c in cands))


def divergence_ratio(draft_path=None):
    """GLOSS-TO-EQUATION DIVERGENCE RATIO.

    Mechanically scans §3 of the paper: counts possession/intrinsic patterns
    inside the textbook-claim blocks (a) + Textual evidence of each §3.1–3.6
    property subsection, vs encounter-index patterns inside the equation
    breakdown blocks (b) of the same subsections. The paper's rebuttal voice
    — (c) inference chains, (d) Paper 11 counterparts, the §3 intro, the §3.7
    audit summary, §3.8/§3.9, and inter-subsection prose — is excluded from
    BOTH counts, so the textbook's voice is never conflated with the paper's
    reply. Both counts are mechanical regex scans over the actual paper text —
    nothing hand-coded.

    SCOPING RULE (v24, F-39): possession patterns are counted ONLY in a
    subsection's (a) block — the span between the **(a)** and **(b) markers
    (the claim plus its "Textual evidence" block, where one exists);
    encounter-index patterns ONLY in its (b) block — the span between the
    **(b) and **(c) markers. Block membership is the ONLY routing criterion.

    TIE-BREAKS (documented):
    1. A line matching patterns from BOTH sets counts only toward its own
       block's category: in an (a) block it can add a possession hit and
       never an index hit; in a (b) block the reverse. Cross-category
       double-counting cannot happen by construction. Within one category,
       overlapping patterns each count (e.g. "e(mu)" matches both \\(mu\\)
       and e\\(mu\\)), so the totals are pattern-hit aggregates — not
       distinct-line counts and not a 1:1 claim-to-index mapping (the §8.9
       prose states the aggregates reading explicitly).
    2. Subsection parsing is fail-loud (V23-20 repair): every §3.1–3.6
       subsection must carry its (a)/(b)/(c) markers, in order. A subsection
       failing the check is skipped with a printed WARNING naming the
       subsection and the failed check — the totals never silently shrink.
       If some (but not all) subsections parse, the run warns (exit 0) with
       the explicit parsed count; if ZERO parse, this function returns None
       and main() exits nonzero rather than print a vacuous 0/0.

    WHAT STAYS OUTSIDE THE MACHINE CHECK:
    - Within-block voice attribution. The machine cannot tell the paper's
      meta-voice from textbook/formalism voice inside a block: the coined
```

```
      term "encounter-index" is itself a counted pattern, so the paper's own
      (b)-block framing sentences using it count by design; likewise the
      paper's meta-descriptions inside Textual-evidence blocks count by
      design. Whether a given hit is the target voice is human-audit
      territory (audited once against v23: 19/20 possession hits are
      unambiguously textbook voice; the 6 "encounter-index" index hits are
      the paper's own label for the formalism's indexing).
    - The pattern lists themselves: which regexes capture "possession" or
      "encounter-index" is declared design, not machine-verified.
    - The §3 extraction assumes the first "## 3 " / "## 4 " headings delimit
      §3 (true of the v23 text; same-string occurrences inside later
      code-block listings do not interfere because extraction is first-match).
    - §3.3 and §3.6 carry no "Textual evidence" block; their (a) count covers
      the claim plus attribution only — the (a)-&gt;(b) span, whatever it holds.

    Portable draft resolution (v14 hardening; v19 fallback chain):
    --draft -&gt; $PAPER_MD -&gt; paper_11_5_draft.md -&gt; paper.md -&gt;
    newest paper_11_5_v&lt;N&gt;.md. --draft is honored verbatim (unchanged
    pre-v19 behavior, including fail-on-nonexistent input).
    """
    from pathlib import Path
    here = Path(__file__).resolve().parent
    DRAFT = Path(draft_path) if draft_path else _resolve_draft_noargv(here)
    print(f"  Draft: {DRAFT}")
    text = open(DRAFT, encoding="utf-8").read()
    # Extract §3 (between "## 3" header and "## 4" header)
    m = re.search(r"## 3\s.*?(?=## 4\s)", text, re.S)
    if not m:
        print("  §3 not found — cannot compute divergence ratio.")
        return None
    s3 = m.group(0)

    # Possession patterns in textbook prose
    poss_patterns = [
        r"\bintrinsic\b", r"\bcarries\b", r"\bpossesses\b", r"\bhas intrinsic\b",
        r"intrinsic propert", r"\bpossession\b",
    ]
    # Encounter-index patterns in equations
    index_patterns = [
        r"\(mu\)", r"n-hat", r"n̂", r"Q\^2", r"Q²", r"\\xi", r"V_CKM", r"CKM",
        r"\bgauge\b", r"\bbasis\b", r"\bframe\b", r"\bscale\b", r"alpha\(mu\)",
        r"e\(mu\)", r"encounter-index",
    ]
    # v24 scoping: split §3 into property subsections; count possession
    # patterns ONLY in each subsection's (a) textbook-statement block
    # (claim + Textual evidence) and index patterns ONLY in its (b)
    # equation-breakdown block. V23-20: every subsection's markers are
    # validated loudly — a marker miss or order violation skips that
    # subsection with a printed WARNING, never silently.
    parts = re.split(r"(?m)^### 3\.(\d)\s", s3)
    spans = {}
    for i in range(1, len(parts), 2):
        spans[parts[i]] = parts[i + 1] if i + 1 &lt; len(parts) else ""
    claim_text, eq_text = "", ""
    parsed = 0
    for n in ["1", "2", "3", "4", "5", "6"]:
        body = spans.get(n, "")
        try:
            claim_blk, eq_blk = _subsection_blocks(body, n)
        except _MarkerError as e:
            print(f"  WARNING: {e} — subsection excluded from both counts.")
            continue
        claim_text += "\n" + claim_blk
        eq_text += "\n" + eq_blk
        parsed += 1
    if parsed == 0:
        print("  ERROR: 0/6 §3.1–3.6 subsections parsed — totals would be "
              "vacuous. Failing loudly instead of printing a silent 0/0.")
        return None
    if parsed &lt; 6:
        print(f"  WARNING: only {parsed}/6 §3.1–3.6 subsections parsed; "
              f"the totals below cover the parsed subsections only.")
    poss = sum(len(re.findall(p, claim_text, re.I)) for p in poss_patterns)
    idx = sum(len(re.findall(p, eq_text, re.I)) for p in index_patterns)
    return poss, idx


class _MarkerError(Exception):
    """Raised when a §3.N subsection's (a)/(b)/(c) markers fail validation."""
def _subsection_blocks(body, n):
```

```
    """Split one §3.N subsection body into ((a) claim block, (b) equation block).

    Returns (claim_block, eq_block) or raises _MarkerError naming the
    subsection and the failed check. V23-20 repair: the old chained
    find("**(b)", a_start) silently skipped a subsection on any marker
    mismatch (shrinking the totals with no trace); this version validates
    each marker independently and requires a&lt;b&lt;c ordering, failing the
    subsection loudly instead.
    """
    a_start = body.find("**(a)**")
    b_start = body.find("**(b)")
    c_start = body.find("**(c)")
    missing = []
    if a_start == -1:
        missing.append("**(a)**")
    if b_start == -1:
        missing.append("**(b)")
    if c_start == -1:
        missing.append("**(c)")
    if missing:
        raise _MarkerError(
            f"§3.{n}: marker(s) not found: {', '.join(missing)}")
    if not (a_start &lt; b_start &lt; c_start):
        raise _MarkerError(
            f"§3.{n}: markers out of order "
            f"((a)@{a_start}, (b)@{b_start}, (c)@{c_start})")
    return body[a_start:b_start], body[b_start:c_start]


def selftest():
    """Routing regression battery: routing must be exact, ambiguity must fail closed.

    Each (input, expected_property) pair asserts the router's verdict.
    The color-charge case is the v15 defect: it previously routed to the
    generic electric-charge entry.
    """
    cases = [
        # (input claim, expected routed property)
        ("The electron carries intrinsic charge -e.", "charge"),
        ("Quarks carry intrinsic color charge.", "color"),
        ("Quarks have intrinsic flavor.", "flavor"),
        ("The electron has intrinsic magnetic moment.", "magnetic moment"),
        ("The electron has intrinsic spin-1/2.", "spin"),
        ("The electron has intrinsic mass 511 keV.", "mass"),
        # Ambiguous input must fail closed, not silently pick one.
        ("The electron has intrinsic spin-1/2 and intrinsic charge -e.",
         "AMBIGUOUS"),
        # v15 loop repair: color + another property must ALSO fail closed
        # (the color priority resolves only the color/charge subsumption).
        ("Quarks carry intrinsic color charge and intrinsic spin.",
         "AMBIGUOUS"),
    ]
    failures = []
    for claim, expected in cases:
        result = parse_claim(claim)
        got = result[0] if result else None
        status = "PASS" if got == expected else "FAIL"
        print(f"  [{status}] {claim!r} -&gt; {got} (expected {expected})")
        if got != expected:
            failures.append((claim, expected, got))
    if failures:
        print(f"  REGRESSION: {len(failures)} routing failure(s).")
        return 1
    print("  All routing regression tests pass.")
    return 0


def main():
    parser = argparse.ArgumentParser(description="PA.1 Parsing Agent")
    parser.add_argument("--claim", type=str, help="SM claim to parse")
    parser.add_argument("--draft", type=str, default=None,
                        help="path to the paper draft (honored verbatim). Without --draft, "
                             "the v19 fallback chain runs: $PAPER_MD -&gt; paper_11_5_draft.md -&gt; "
                             "paper.md -&gt; newest paper_11_5_v&lt;N&gt;.md.")
    args = parser.parse_args()

    print("=" * 70)
    print("PA.1 — PARSING AGENT")
    print("Separating derived content from smuggled gloss in SM property claims")
    print("=" * 70)
```

```
    # Routing regression battery runs first: routing must be exact.
    print("\nROUTING REGRESSION TESTS")
    print("-" * 70)
    if selftest() != 0:
        return 1

    claims = []
    if args.claim:
        claims = [args.claim]
    else:
        claims = [
            "The electron has intrinsic spin-1/2.",
            "The electron carries intrinsic charge -e.",
            "Quarks carry intrinsic color charge.",
            "Quarks have intrinsic flavor.",
            "The electron has intrinsic mass 511 keV.",
            "The electron has intrinsic magnetic moment.",
        ]

    for claim in claims:
        result = parse_claim(claim)
        print(f"\nINPUT: {claim}")
        if result:
            prop, formal, gloss, badge, p11 = result
            print(f"  Property: {prop}")
            print(f"  Formal content (derived): {formal}")
            print(f"  Gloss (smuggled): {gloss}")
            print(f"  Badge: {badge}")
            print(f"  Paper 11 counterpart: {p11}")
        else:
            print(f"  UNRECOGNIZED: no property matched.")

    # Divergence ratio: mechanical scan of §3
    print("\n" + "=" * 70)
    print("GLOSS-TO-EQUATION DIVERGENCE RATIO (§3 mechanical scan)")
    print("=" * 70)
    r = divergence_ratio(args.draft)
    if r is None:
        # Fail loudly: zero parsed subsections (or no §3) must not exit 0
        # with a silent skip. V23-20.
        print("\nPA.1 FAILED: divergence ratio could not be computed — "
              "see ERROR above.")
        return 1
    poss, idx = r
    print(f"  Possession/intrinsic patterns in (a) textbook-claim blocks: {poss}")
    print(f"  Encounter-index patterns in (b) equation breakdowns: {idx}")
    if idx &gt; 0:
        print(f"  DIVERGENCE RATIO: {poss} textbook possession-claims vs. {idx} "
              f"equation encounter-indices.")
        print(f"  Counts are scoped: (a)+Textual-evidence vs (b) only, per §3.1–3.6;")
        print(f"  the paper's rebuttal voice ((c), (d)) is excluded from both.")
    print("  (Counts are mechanical regex scans over §3's actual text.)")

    print("\n" + "=" * 70)
    print("PA.1 complete. The agent separates what equations say from what prose adds.")
    return 0


if __name__ == "__main__":
    sys.exit(main())
```

Listing 22: ESP.1 — esp_v2.py (listing)

```
#!/usr/bin/env python3
"""
ESP v2.2 — unified agent-to-agent protocol engine.

Lineage: Grok v4 (EpistemicSwarmEngine) -&gt; Gemini/Qwen ESP v1.0 -&gt;
ChatGPT improvements -&gt; this unification (Valkyrie, 2026-10-09,
per Dervis: executable, high-class, simple, stageable into Paper 11.5).

Standard library only. Single file.

Design decisions (binding, from esp_v2_design_brief.md):
  1. Checks run by default; the badge names what ran (checks list on every
     VALIDATED; lexical policy ON by default).
  2. Externalized canon: banned terms, context markers, axiom universe
     injected via constructor; sane defaults shipped.
  3. Block context markers with malformed-marker ERRORS (unclosed, nested,
```

mismatched -> violations, never silent fallthrough).
4. Outbound refusal: constructors raise on invalid payloads.
5. Two-tier hash honesty (v2.0.1): chat tier leaves hashes blank and the validator computes them (recorded "computed-locally"); machine tier carries sender-computed hashes verified strictly; forged hex is REJECTED. v2.0.2: explicit integrity.tier signal ("chat"|"machine", enforced when declared, inferred otherwise); the validator deep-copies before validating so a chat-tier pass can never manufacture machine-tier credentials on revalidation.
   Honesty scope: VALIDATED attests well-formedness + self-consistency at validation time + the named checks that ran. It is NOT tamper-evidence against a competent attacker (anyone with Python can recompute hashes) — the machine tier is corruption-detection plus lazy-forgery detection. sender_identity and transport_authenticity are never established (see not_established).
6. Audit receipts kept; inbound audit history is stripped, never trusted (v2.0.2).
7. not_established list on every validation result (validation proves envelope integrity only, never claim truth).
8. Registry honesty: zero-hash registry requires explicit insecure_demo_registry=True, else the constructor refuses.
9. Capability-based module policy (subprocess/socket/os/sys banned; math and numerics ALLOWED). LEVEL_A float discipline with a hardened display exemption (AST parent-chain check: the float must reach the print/format call with no intervening call; v2.2 patch F-48 closed the nested-call bypass the old "non-gameable" claim overstated).
10. STAGE_N requires LEVEL_A + deterministic/seeded; LEVEL_A requires >=1 falsification condition; LEVEL_A cannot depend on B/C bridges; registry skew bounded (default +-3).
11. Chunk protocol: transfer_id, per-chunk + whole-text hashes, gap/duplication/mixed-transfer detection.
12. migrate_v1_to_v2 helper (field renames); v4 payloads documented, not auto-migrated.
13. Tiered envelopes (v2.0.4, D1): envelope_tier "working"|"archival". Working tier (REQUEST/RESPONSE/BROADCAST) makes epistemic_context optional (records "context:undeclared") and runs the lexical firewall in ADVISORY mode — violations become firewall_warnings, never rejections. Archival tier stays enforcing; CLAIM/PROOF/FALSIFICATION/DISAGREEMENT/CONFRONTATION on the working tier are REJECTED with TIER_MISMATCH. One schema, two completeness levels.
14. DISAGREEMENT (v2.0.4, D2): archival message type recording two agents' divergent verdicts on one envelope, the precise structured delta, and a later human adjudication. CONFRONTATION (v2.0.4, D3): archival second-person challenge ("your claim fails because..."), distinct from FALSIFICATION (first-person), with a structured broken_premise {axiom, premise_id, statement}.
15. RT-001 fail-closed (v2.0.4): _free_texts no longer silently drops strings past its depth bound — it raises DepthBoundExceeded, which the validator converts to a FREE_TEXT_DEPTH_EXCEEDED violation (REJECTED). The lexical bypass is closed.
16. python_static_check hardened (v2.0.4, V19): attribute-chain dynamic calls (builtins.eval(...)) and getattr(x, "eval")(...) are now DYNAMIC_EXECUTION violations. Documented heuristic limits remain: aliased imports (from builtins import eval as e) are out of scope.
17. Policy hygiene (v2.0.4, V20/V22): max_message_chars/max_content_chars validated as positive ints; warn_on_validate flag suppresses the demo warning for batch validation. make_message gained a tier parameter (V21): tier="chat" emits blank-hash chat-tier envelopes.
18. Markers are case-insensitive (v2.0.4, held item): [comparative] pairs with [/COMPARATIVE]. not_established gains "semantic_validity": mathematical_soundness = the derivation steps, as written, are valid; semantic_validity = the claim, as written, refers to something real and asserts something true of it. The validator establishes neither — the lexical firewall is a floor, not a ceiling (D4/D6).
19. Bundle lineage (v2.2): lineage "bundle" — "the claim reports outcomes of executing a bundle of scripts; the bundle manifest named in depends_on is the grounding." Validator requires depends_on to name at least one bundle artifact (a string ending in .zip, case-insensitive) — fail-closed otherwise, error names the cause. Existence of the named bundle is NOT machine-checked: depends_on is a claim about grounding, verified by the recipient, exactly like script_id (SCRIPT_RE checks shape, not existence). A fake .zip name passes the shape check the same way a fake "F.999" passes — the envelope is well-formed; the grounding claim is the recipient's to verify. This fixes the v18 gap: the most honest execution report in the program was REJECTED because no lineage covered it. script_id generalized (v2.2): ^(F|P|H|G|MC|FW|PA)\.\d+[A-Z]?$ — the engine must cover the paper it ships with (Paper 11.5's P./H./G./MC./FW./PA.

```
     series, not just Paper 11's F. series). Version gate unchanged:
     exact 2.2 match required, fail-closed, no negotiation (negotiation
     still needs Dervis's word).
  20. Patch round (v2.2 engine, 2026-10-17, Dervis's "correct everything
      now" — VERSION stays 2.2, no envelope-schema change):
      F-45 lexical defaults: (a) "limit" moved from DEFAULT_HARD_BANNED to
      DEFAULT_CONTEXT_BANNED — it rejected ordinary prose, and as a
      context-banned term [COMPARATIVE]/marker blocks can exempt it for
      legitimate comparative use; (b) "uv"/"ir" trip the hard ban only as
      whole-word UPPERCASE ("UV"/"IR" are regime jargon; lowercase in
      ordinary prose does not trip); (c) correction, stated plainly: some
      v2.2 package doc text claimed context-marker blocks exempt
      hard-banned terms — FALSE. Hard-banned terms are exempt NOWHERE;
      marker blocks exempt CONTEXT_BANNED terms only. The engine's rule
      (this docstring + lexical_check) is authoritative; the stale package
      doc text is superseded and must not be rebuilt from it.
      F-47: human_review lineage now requires reviewer + review_date +
      attestation_ref (reviewer identity, date, attestation reference) —
      the one lineage asserting human sign-off. Any of the three missing
      or empty REJECTS (fail closed). The validator checks presence, never
      attestation truth — content is the recipient's check, same as
      script_id existence.
      F-48: float_exempt() hardened against the nested-call bypass —
      the float's AST parent chain must reach the builtin print()/format()
      call WITHOUT passing through another call, so print("result",
      compute(1.5))  # (display only) no longer exempts the computational
      1.5. The old "non-gameable" claim overstated the check; the
      docstrings now describe what the code actually enforces.
      F-52 dead-code removal: STATUSES and module-level _BLOCK_RE deleted
      (defined, never used); context_spans error strings now render the
      actual opener token — a mismatched close of a bare [NAME] opener no
      longer misreports it as "[NAME_BEGIN]".
      Adjudication item (d) — named "physics-payload" static-check profile
      (STATIC_CHECK_PROFILES; Policy(static_check_profile=...)): "strict"
      keeps the exact prior behavior and stays the default (the right
      choice for untrusted code); "physics_payload" is for declared physics
      payloads carrying INPUT_PROVENANCE — (i) `sys` imports allowed (the
      defended capability is process control/exfiltration via
      subprocess/socket/os-level access; sys.exit/sys.argv are neither;
      subprocess/socket/os stay banned); (ii) float literals bound to
      module-level UPPER_CASE constants listed in the script's
      INPUT_PROVENANCE block under the paper-defined or cited-paper class
      are exempt from FLOAT_IN_LEVEL_A (declaration-scoped: the validator
      checks the constant is named in a cited/paper-defined entry, never
      that the citation is genuine — same honesty boundary as script_id).
      Item (d) also adds Paper 11.5 §3/§9 to the conformance corpus as a
      permanent lexical regression test (pinned fixture; asserts the
      F-45-era expected violations under the default policy so silent
      banned-set drift fails loudly; records the physics-payload-profile
      outcome). Fixture pinned from the v22 text 2026-10-17 — §3 is under
      F-12 edit by another worker, so the integration phase must refresh
      the fixture from the final paper text and re-run.
  21. Declared demo registry (v24): DEMO_REGISTRY_HASH — a fixed, public,
      reproducible hash naming the shared demo axiom set, separate from the
      zero/placeholder hash. Policy(demo_registry=True) validates against it
      WITHOUT the insecure-demo disclaimer, because the demo use is declared
      in the constructor, not smuggled. The zero-hash +
      insecure_demo_registry=True path is unchanged (back-compat); the two
      flags are mutually exclusive, and demo_registry=True refuses any hash
      other than DEMO_REGISTRY_HASH. The disclaimer stays on the zero-hash
      path: a null registry that printed no warning could be mistaken for a
      real one; the declared demo registry is openly named, so the flag is
      the declaration.

  Validation does NOT establish that a scientific claim is true.
  """
  from __future__ import annotations

  import argparse
  import ast
  import copy
  import hashlib
  import json
  import re
  import sys
  import uuid
  from datetime import datetime, timezone
  from pathlib import Path

  VERSION = "2.2"
```

```
CHUNK_PROTOCOL = "ESP-CHUNK-2"

# ---------------------------------------------------------------------------
# Vocabularies
# ---------------------------------------------------------------------------

REGISTERS = {"STAGE_N", "STAGE_P", "STAGE_C", "META_AUDIT"}
BADGES = {"LEVEL_A", "LEVEL_B", "LEVEL_C", "META"}
FORMATS = {
    "NATIVE_STATEMENT", "PROOF_AST", "EXECUTABLE_PYTHON",
    "CLAIM_REGISTRY_JSON", "TEX_EQUATION", "FALSIFICATION_CONDITION",
    "PLAIN_TEXT", "JSON_DATA", "AUDIT_REPORT",
}
CLAIMS = {
    "EXISTENCE", "UNIVERSAL", "RELATIONAL", "STRUCTURAL",
    "COMPUTATIONAL", "DEFINITIONAL", "OBSERVATIONAL",
}
LINEAGES = {"script", "inherited", "prose", "human_review", "bundle"}
MODES = {"DETERMINISTIC", "SEEDED", "STOCHASTIC"}
TYPES = {
    "REQUEST", "RESPONSE", "BROADCAST", "HANDSHAKE",
    "AUDIT_RECEIPT", "CLAIM", "PROOF", "FALSIFICATION",
    "DISAGREEMENT", "CONFRONTATION",  # v2.0.4: D2, D3 (archival tier)
}
BRIDGES = {"A", "B", "C"}
TIERS = {"chat", "machine"}
# v2.0.4 D1: envelope completeness tiers. Working = cheap conversational
# layer (epistemic_context optional, firewall advisory). Archival = full
# context, firewall enforcing. One schema, two completeness levels.
ENVELOPE_TIERS = {"working", "archival"}
# The ONLY message types permitted on the working tier. Everything else
# (CLAIM, PROOF, FALSIFICATION, DISAGREEMENT, CONFRONTATION, HANDSHAKE,
# AUDIT_RECEIPT) requires archival; a working-tier archival type is
# REJECTED with TIER_MISMATCH.
WORKING_TYPES = {"REQUEST", "RESPONSE", "BROADCAST"}
DISAGREEMENT_VERDICTS = {"VALIDATED", "REJECTED"}
ADJUDICATION_STATUSES = {"PENDING", "RESOLVED"}
RECEIPT_RESULTS = {"VALIDATED", "REJECTED", "DEFERRED"}

MARKER_NAMES = ("COMPARATIVE", "HISTORICAL", "SHADOW", "RECONSTRUCTION")

# v2.2 patch (F-45): "limit" moved from HARD to CONTEXT_BANNED. As a hard
# ban it rejected ordinary prose ("limit the scope"); as a context-banned
# term it is still barred from native prose but [COMPARATIVE]/marker
# blocks can exempt it for legitimate comparative use. (STATUSES removed
# in the same patch: defined, never used — see F-52.)
DEFAULT_HARD_BANNED = frozenset({
    "infinity", "infinite", "infinitesimal", "derivative",
    "integral", "asymptotic", "path integral", "uv", "ir",
})
DEFAULT_CONTEXT_BANNED = frozenset({
    "field", "gauge", "vacuum", "manifold", "metric", "curvature",
    "geodesic", "observer", "background", "lagrangian", "quantized",
    "propagator", "virtual", "renormalization", "limit",
})
DEFAULT_AXIOM_UNIVERSE = frozenset({
    "L1", "L2", "L3", "L4", "PTR", "BUDGET", "DSC", "S3",
    "SINGLE_REGIME", "NULL_BOUNDARY", "NULL_CONTINUUM",
})
# Capability-based: exfiltration / process control / dynamic execution.
# math and numerics are ALLOWED (physics payloads need them).
DEFAULT_BANNED_MODULES = frozenset({"subprocess", "socket", "os", "sys"})
DEFAULT_BANNED_CALLS = frozenset({"eval", "exec", "compile", "__import__"})
# Named static-check profiles for EXECUTABLE_PYTHON payloads
# (v2.2 patch, adjudication item d).
#
# "strict" (default): the full capability ban exactly as configured on
# the Policy; no provenance exemptions. This is the right choice for
# untrusted or adversarial code, and it is what every existing caller
# gets unless they opt in.
#
# "physics_payload": for code that IS the physics payload — a declared
# verification script carrying an INPUT_PROVENANCE block (e.g. the
# paper's own scripts). Two relaxations, both documented and bounded:
#   (i) `sys` imports are allowed. Rationale: the defended capability is
#       process control / exfiltration via subprocess/socket/os-level
#       access; sys.exit/sys.argv are neither. subprocess, socket and os
#       stay banned under this profile.
#   (ii) float literals bound to module-level UPPER_CASE constants listed
#       in the script's INPUT_PROVENANCE block under the paper-defined or
```

```
#       cited-paper class are exempt from FLOAT_IN_LEVEL_A (e.g.
#       ALPHA_S_MZ = 0.1180 with "alpha_s(M_Z) = 0.1180: class=cited-paper"
#       in the block). The check is declaration-scoped: the validator
#       verifies the constant is NAMED in a cited/paper-defined provenance
#       entry; whether the citation is genuine is the recipient's check —
#       the same honesty boundary as script_id (shape checked, existence
#       not). float() calls are NOT exempted even under this profile.
#
# When each applies: "strict" is the default — keep it for anything you
# do not already trust. "physics_payload" is for code the recipient
# already treats as a declared physics payload; it must never be
# selected to make hostile code pass.
STATIC_CHECK_PROFILES = {"strict", "physics_payload"}

HASH_RE = re.compile(r"^[0-9a-f]{64}$")
UUID_RE = re.compile(
    r"^[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[1-8][0-9a-fA-F]{3}-"
    r"[89abAB][0-9a-fA-F]{3}-[0-9a-fA-F]{12}$"
)
# v2.2: generalized. F. = Paper 11 scripts; P./H./G./MC./FW./PA. = the
# Paper 11.5 series the engine ships with (the engine must cover the paper
# it ships with). Shape check only — the validator cannot know whether a
# named script exists; that is the recipient's job, same as depends_on.
SCRIPT_RE = re.compile(r"^(F|P|H|G|MC|FW|PA)\.\d+[A-Z]?$")
# v2.2: a bundle artifact is a string naming a bundle file. A bundle
# artifact = a string ending in .zip (case-insensitive, \Z-anchored so a
# trailing newline cannot smuggle past the shape check). Shape check only:
# depends_on is a CLAIM about grounding, verified by the recipient, same
# as script_id (see design decision 19). A fake .zip name passes the shape
# check exactly like a fake script_id passes SCRIPT_RE — the envelope is
# well-formed, the grounding claim is the recipient's to verify.
BUNDLE_RE = re.compile(r"\.zip\Z", re.IGNORECASE)
COND_RE = re.compile(r"^C\d+[A-Z]?$")
ZERO_HASH = "0" * 64
# Declared demo registry (v24, design decision 21): a fixed, public,
# reproducible hash naming the shared demo axiom set — a SEPARATE constant
# from the zero/placeholder hash. The value is the SHA-256 of the fixed
# seed string "ESP v2.2 declared demo registry"; anyone can recompute it.
# Policy(demo_registry=True) validates against it without the insecure-demo
# disclaimer (the demo use is declared in the constructor, not smuggled).
DEMO_REGISTRY_HASH = \
    "661d95cfa230277ec4acd44e76b4210c44c527e2678d26edec297557853351b7"
NOT_ESTABLISHED = [
    "mathematical_soundness",
    "semantic_validity",  # v2.0.4 D4: the claim, as written, refers to
    # something real and asserts something true of it (truth, not just
    # validity). mathematical_soundness = the derivation steps, as
    # written, are valid. The validator establishes neither.
    "proof_script_correspondence",
    "claim_truth",
    "sender_identity",
    "transport_authenticity",
]


class ProtocolError(ValueError):
    """Raised for malformed chunk sets and programmer errors (not messages)."""


class DepthBoundExceeded(ProtocolError):
    """v2.0.4 RT-001: _free_texts hit its depth bound.

    Fail-closed: a free-text tree nested deeper than the bound is
    never silently truncated. On the archival tier this surfaces as a
    FREE_TEXT_DEPTH_EXCEEDED violation (REJECTED); on the working tier
    the whole firewall is advisory (D1), so it surfaces as a
    firewall_warnings entry instead — loud, not silent, but not a
    rejection. (The v2.0.3 behavior — silently dropping strings past
    depth 8 — was a lexical bypass: banned terms nested deep enough
    passed unexamined.)"""


# ---------------------------------------------------------------------------
# Hashing / canonical form
# ---------------------------------------------------------------------------

def canonical(value) -&gt; str:
    """Stable JSON representation used for hashing.

    Raises ValueError/TypeError on non-serializable input (NaN, sets,
```

```
    bytes, ...). Callers that must never crash convert these to REJECTED.
    """
    return json.dumps(
        value, ensure_ascii=False, sort_keys=True,
        separators=(",", ":"), allow_nan=False,
    )


def digest(text: str) -&gt; str:
    return hashlib.sha256(text.encode("utf-8")).hexdigest()


def object_digest(value) -&gt; str:
    return digest(canonical(value))


def now() -&gt; str:
    return datetime.now(timezone.utc).isoformat(
        timespec="seconds").replace("+00:00", "Z")


# ---------------------------------------------------------------------------
# Policy (externalized canon lives here)
# ---------------------------------------------------------------------------

class Policy:
    """Local validation policy. The canon — banned terms, markers, axiom
    universe, module policy — is injected here, never hardcoded in checks.

    Registry honesty: a zero/placeholder axiom_set_hash is refused unless
    insecure_demo_registry=True is passed explicitly. Demo validations print
    a loud warning on every call unless warn_on_validate=False (V22, for
    batch use).

    Declared demo mode (v24, design decision 21): Policy(demo_registry=True)
    validates against the declared demo registry hash DEMO_REGISTRY_HASH
    (which the constructor defaults axiom_set_hash to when unset) and prints
    NO disclaimer — the demo use is declared in the constructor, so there is
    nothing to warn about. The two demo paths are separate and mutually
    exclusive: (1) zero-hash placeholder + insecure_demo_registry=True —
    back-compat; prints the WARNING above on every validate; (2)
    DEMO_REGISTRY_HASH + demo_registry=True — declared demo mode; no
    disclaimer. demo_registry=True refuses any other hash. (A bare
    Policy(axiom_set_hash=DEMO_REGISTRY_HASH) without the flag is treated
    like any other non-zero registry reference — the hash openly names a
    demo registry; the flag is the declaration of demo USE.)

    static_check_profile (v2.2 patch, item d): selects the named
    python_static_check profile — "strict" (default, full capability ban,
    no provenance exemptions) or "physics_payload" (sys imports allowed;
    cited-paper float constants exempt; see STATIC_CHECK_PROFILES).
    """

    def __init__(
        self,
        *,
        registry_version: int = 0,
        axiom_set_hash: str | None = None,
        insecure_demo_registry: bool = False,
        demo_registry: bool = False,  # v24 decision 21: declared demo mode
        accepted_registry_skew: int = 3,
        max_message_chars: int = 2_500_000,
        max_content_chars: int = 2_000_000,
        enforce_lexical_policy: bool = True,  # ON by default (fixes Q1)
        max_age_seconds: int | None = None,  # v2.0.2: optional replay bound
        require_machine_tier: bool = False,  # v2.0.2: refuse chat-tier hashes
        warn_on_validate: bool = True,  # v2.0.4 V22: demo warning on every
        # validate_message call; set False for batch validation (the CLI
        # does this) to suppress the noise.
        hard_banned=None,
        context_banned=None,
        marker_names=None,
        axiom_universe=None,
        banned_modules=None,
        banned_calls=None,
        static_check_profile: str = "strict",  # v2.2 patch, item d
    ):
        if not isinstance(demo_registry, bool):
            raise ValueError("demo_registry must be a bool")
        if not isinstance(insecure_demo_registry, bool):
```

```
    raise ValueError("insecure_demo_registry must be a bool")
if demo_registry and insecure_demo_registry:
    raise ValueError(
        "demo_registry and insecure_demo_registry are mutually "
        "exclusive: the declared demo registry and the zero-hash "
        "placeholder are separate paths"
    )
if axiom_set_hash is None:
    # Declared demo mode defaults to the declared demo registry;
    # the zero-hash placeholder stays the default otherwise.
    axiom_set_hash = DEMO_REGISTRY_HASH if demo_registry else ZERO_HASH
if not isinstance(axiom_set_hash, str) \
        or not HASH_RE.fullmatch(axiom_set_hash):
    raise ValueError("axiom_set_hash must be a lowercase SHA-256 hex")
if demo_registry and axiom_set_hash != DEMO_REGISTRY_HASH:
    raise ValueError(
        "demo_registry=True requires "
        "axiom_set_hash=DEMO_REGISTRY_HASH (the declared demo "
        "registry); pass the constant explicitly or leave "
        "axiom_set_hash unset"
    )
if axiom_set_hash == ZERO_HASH and not insecure_demo_registry:
    raise ValueError(
        "zero/placeholder axiom_set_hash refused: pass "
        "insecure_demo_registry=True explicitly for demo use, or "
        "configure a real shared registry"
    )
if not isinstance(registry_version, int) \
        or isinstance(registry_version, bool) or registry_version &lt; 0:
    raise ValueError("registry_version must be a non-negative int")
if not isinstance(accepted_registry_skew, int) \
        or isinstance(accepted_registry_skew, bool) \
        or accepted_registry_skew &lt; 0:
    raise ValueError("accepted_registry_skew must be a non-negative int")

self.registry_version = registry_version
self.axiom_set_hash = axiom_set_hash
self.insecure_demo_registry = insecure_demo_registry
self.demo_registry = demo_registry  # v24 decision 21
self.accepted_registry_skew = accepted_registry_skew
# v2.0.4 V20: size caps are validated like max_age_seconds —
# negative or non-int caps previously passed through silently.
for _name, _val in (("max_message_chars", max_message_chars),
                    ("max_content_chars", max_content_chars)):
    if not isinstance(_val, int) or isinstance(_val, bool) \
            or _val &lt;= 0:
        raise ValueError(f"{_name} must be a positive int")
self.max_message_chars = max_message_chars
self.max_content_chars = max_content_chars
self.enforce_lexical_policy = enforce_lexical_policy
if max_age_seconds is not None:
    if not isinstance(max_age_seconds, int) \
            or isinstance(max_age_seconds, bool) \
            or max_age_seconds &lt;= 0:
        raise ValueError(
            "max_age_seconds must be a positive int or None")
if not isinstance(require_machine_tier, bool):
    raise ValueError("require_machine_tier must be a bool")
if not isinstance(warn_on_validate, bool):
    raise ValueError("warn_on_validate must be a bool")
self.max_age_seconds = max_age_seconds
self.require_machine_tier = require_machine_tier
self.warn_on_validate = warn_on_validate

def _collection(name, value):
    # Fail fast on the classic footgun: a bare string where a
    # collection of strings was meant ("ABC" -&gt; ('A','B','C')).
    if isinstance(value, str):
        raise ValueError(
            f"{name}: expected a collection of strings, got a "
            f"bare string")
    return value

self.hard_banned = frozenset(
    _collection("hard_banned", hard_banned)
    if hard_banned is not None else DEFAULT_HARD_BANNED)
self.context_banned = frozenset(
    _collection("context_banned", context_banned)
    if context_banned is not None else DEFAULT_CONTEXT_BANNED)
self.marker_names = tuple(
```

```
            _collection("marker_names", marker_names)
            if marker_names is not None else MARKER_NAMES)
        self.axiom_universe = frozenset(
            _collection("axiom_universe", axiom_universe)
            if axiom_universe is not None else DEFAULT_AXIOM_UNIVERSE)
        self.banned_modules = frozenset(
            _collection("banned_modules", banned_modules)
            if banned_modules is not None else DEFAULT_BANNED_MODULES)
        self.banned_calls = frozenset(
            _collection("banned_calls", banned_calls)
            if banned_calls is not None else DEFAULT_BANNED_CALLS)
        # v2.2 patch, item d: named static-check profile. Fail fast on an
        # unknown name — a misspelled profile must never silently fall
        # back to "strict" (or vice versa).
        if static_check_profile not in STATIC_CHECK_PROFILES:
            raise ValueError(
                "static_check_profile must be one of "
                f"{sorted(STATIC_CHECK_PROFILES)}")
        self.static_check_profile = static_check_profile

    def warn_if_demo(self):
        # v24 decision 21: the declared demo_registry path prints no
        # disclaimer — the demo use is declared in the constructor. Only
        # the zero-hash placeholder path warns.
        if self.insecure_demo_registry:
            print("WARNING: insecure demo registry in use — VALIDATED badges "
                  "from this policy attest to envelope integrity only, "
                  "against a NULL registry. Not for production.",
                  file=sys.stderr)


# ---------------------------------------------------------------------------
# Field validators (structural layer)
# ---------------------------------------------------------------------------

def _req_object(value, path: str) -&gt; dict:
    if not isinstance(value, dict):
        raise ProtocolError(f"{path}: expected object")
    return value


def _req_keys(value: dict, required: set, allowed: set, path: str):
    missing = required - set(value)
    extra = set(value) - allowed
    if missing:
        raise ProtocolError(f"{path}: missing keys {sorted(missing)}")
    if extra:
        raise ProtocolError(f"{path}: unknown keys {sorted(extra)}")


def _req_enum(value, choices: set, path: str):
    if not isinstance(value, str) or value not in choices:
        raise ProtocolError(f"{path}: expected one of {sorted(choices)}")


def _req_nonempty(value, path: str):
    if not isinstance(value, str) or not value.strip():
        raise ProtocolError(f"{path}: expected non-empty string")


def _req_sha(value, path: str):
    if not isinstance(value, str) or not HASH_RE.fullmatch(value):
        raise ProtocolError(f"{path}: expected lowercase SHA-256")


def _req_uuid(value, path: str, nullable: bool = False):
    if nullable and value is None:
        return
    if not isinstance(value, str) or not UUID_RE.fullmatch(value):
        raise ProtocolError(f"{path}: invalid UUID")


def _req_maxlen(value, path: str, limit: int):
    if isinstance(value, str) and len(value) &gt; limit:
        raise ProtocolError(
            f"{path}: exceeds {limit} characters ({len(value)})")


def _req_timestamp(value, path: str):
    if not isinstance(value, str):
```

```
        raise ProtocolError(f"{path}: expected ISO-8601 timestamp")
    try:
        parsed = datetime.fromisoformat(
            value[:-1] + "+00:00" if value.endswith("Z") else value)
    except ValueError as exc:
        raise ProtocolError(f"{path}: invalid ISO-8601 timestamp") from exc
    if parsed.tzinfo is None:
        raise ProtocolError(f"{path}: timestamp must include timezone")
    return parsed


def _req_int(value, path: str, minimum=None):
    if isinstance(value, bool) or not isinstance(value, int) \
            or (minimum is not None and value &lt; minimum):
        raise ProtocolError(f"{path}: invalid integer")


def _req_unique_strs(value, path: str):
    if not isinstance(value, list) \
            or any(not isinstance(i, str) or not i for i in value) \
            or len(value) != len(set(value)):
        raise ProtocolError(f"{path}: must be unique non-empty strings")
# ---------------------------------------------------------------------------
# Lexical firewall (context markers + banned terms)
# ---------------------------------------------------------------------------


def _block_pattern(marker_names) -&gt; re.Pattern:
    names = "|".join(re.escape(n) for n in marker_names)
    # Openers: [NAME_BEGIN], bare [NAME]. Closers: [NAME_END], [/NAME].
    # v2.0.4 (held item): matching is case-insensitive — [comparative]
    # pairs with [/COMPARATIVE]. context_spans() normalizes to upper case
    # for pairing.
    return re.compile(rf"\[(/)?({names})(?:_(BEGIN|END))?\]", re.IGNORECASE)


def context_spans(text: str, marker_names):
    """Find paired contextual blocks.

    Grammar (v2.0.3): markers come in pairs. Openers are [NAME_BEGIN] or
    bare [NAME]; closers are [NAME_END] or [/NAME], interoperable (a
    [/NAME] may close a [NAME_BEGIN] block and vice versa). A bare [NAME]
    opens a block that must be closed — there is no whole-line special
    case anymore.

    Returns (spans, errors). Errors cover: nested open, unmatched close,
    mismatched close, unclosed open. Malformed markers are ERRORS, never
    silent fallthrough (fixes Grok-G1; v2.0.3 closes the kit-advertised
    [NAME]...[/NAME] gap the engine previously ignored). v2.0.4: marker
    names match case-insensitively and are normalized to upper case for
    pairing.
    """
    spans: list[tuple[int, int]] = []
    errors: list[str] = []
    pattern = _block_pattern(marker_names)
    # v2.2 patch (F-52): active carries the actual opener TOKEN, not a
    # re-rendered "[{name}_BEGIN]" — error strings must name the marker as
    # written, because a bare [NAME] opener is legal and rendering it as
    # "[NAME_BEGIN]" misdescribes the input.
    active: tuple[str, int, str] | None = None

    for match in pattern.finditer(text):
        slash, name, edge = match.group(1), match.group(2).upper(), \
            match.group(3)
        # v2.0.4: the pattern is case-insensitive, so normalize the edge
        # too — "[comparative_begin]" must open, not baffle the parser.
        edge = edge.upper() if edge else None
        token = match.group(0)
        is_opener = edge == "BEGIN" or (not slash and edge is None)
        if is_opener:
            if active is not None:
                errors.append(
                    f"nested context block: {token} inside {active[2]}")
            else:
                active = (name, match.start(), token)
        else:  # closer: [NAME_END] or [/NAME]
            if active is None:
                errors.append(f"unmatched {token} (no open block)")
            elif active[0] != name:
                errors.append(
```

```
                    f"mismatched context block: {token} closes {active[2]}")
                active = None
            else:
                spans.append((active[1], match.end()))
                active = None

    if active is not None:
        errors.append(f"unclosed {active[2]} block (no matching close)")

    return spans, errors


def _free_texts(value, _depth=0) -&gt; list[str]:
    """Recursively collect string leaves from a JSON-shaped value.

    Used by the lexical firewall to reach every free-text channel
    (falsification statements, metadata, formal_assertions,
    dependencies). Depth-capped so hostile nesting cannot blow the
    stack; non-string leaves are ignored.

    v2.0.4 RT-001 FAIL-CLOSED: strings past the depth bound are NEVER
    silently dropped. Exceeding the bound raises DepthBoundExceeded,
    which the validator converts to a FREE_TEXT_DEPTH_EXCEEDED finding
    — a REJECTED violation on the archival tier, a firewall_warnings
    entry on the working tier (advisory firewall, D1). A silent drop
    was a lexical bypass — banned terms nested deep enough passed
    unexamined.
    """
    out: list[str] = []
    if value is None:
        return out
    if _depth &gt; 8:
        raise DepthBoundExceeded(
            f"free-text nesting exceeds depth bound (&gt;{8} levels); "
            "refusing to silently truncate — restructure the payload")
    if isinstance(value, str):
        out.append(value)
    elif isinstance(value, dict):
        for v in value.values():
            out.extend(_free_texts(v, _depth + 1))
    elif isinstance(value, (list, tuple)):
        for v in value:
            out.extend(_free_texts(v, _depth + 1))
    return out


def lexical_check(text: str, policy: Policy) -&gt; list[dict]:
    """Return violation dicts for banned-term use.

    HARD_BANNED: never permitted — not in native prose, and not inside
    context-marker blocks either. Marker blocks exempt CONTEXT_BANNED
    terms only; there is no marker, tier, or envelope form that exempts a
    hard-banned term. (v2.2 patch F-45c: some v2.2 package doc text
    implied marker blocks exempt hard-banned terms; that text is wrong —
    this docstring is the rule, and the code below enforces it.)
    Malformed markers are violations too.

    Matching is case-insensitive via re.IGNORECASE on the ORIGINAL text so
    match positions share the coordinate space of the marker spans computed
    by context_spans(). (Matching on text.casefold() instead would shift
    positions for length-changing folds like ß-&gt;ss and break the span
    check — a firewall bypass.)
    v2.2 patch F-45b: the terms "uv"/"ir" are jargon only in UPPERCASE
    (UV cutoff, IR regime); lowercase "uv"/"ir" in ordinary prose does
    not trip the hard ban. The pattern is therefore case-sensitive and
    uppercase-only for exactly these two terms.
    """
    violations: list[dict] = []
    spans, errors = context_spans(text, policy.marker_names)
    for error in errors:
        violations.append({"code": "BAD_CONTEXT_MARKER", "detail": error})

    def inside_allowed_span(position: int) -&gt; bool:
        return any(start &lt;= position &lt; end for start, end in spans)

    def banned_pattern(term: str) -&gt; re.Pattern:
        # v2.2 patch F-45b: uppercase-anchor uv/ir — only the uppercase
        # whole-word forms are regime jargon; lowercase in ordinary prose
        # must not trip the hard ban. Every other term keeps the
        # case-insensitive whole-word match.
```

```
        if term in ("uv", "ir"):
            return re.compile(r"(?&lt;!\w)" + re.escape(term.upper())
                              + r"(?!\w)")
        return re.compile(r"(?&lt;!\w)" + re.escape(term) + r"(?!\w)",
                          re.IGNORECASE)

    for term in sorted(policy.hard_banned):
        for match in banned_pattern(term).finditer(text):
            violations.append({
                "code": "HARD_BANNED",
                "term": term,
                "span": text[max(0, match.start() - 30):match.end() + 30],
            })
    for term in sorted(policy.context_banned):
        for match in banned_pattern(term).finditer(text):
            if not inside_allowed_span(match.start()):
                violations.append({
                    "code": "CONTEXT_BANNED",
                    "term": term,
                    "span": text[max(0, match.start() - 30):match.end() + 30],
                })
    return violations


# ---------------------------------------------------------------------------
# Python static check (EXECUTABLE_PYTHON payloads)
# ---------------------------------------------------------------------------

# v2.2 patch, item d(ii): classes whose INPUT_PROVENANCE entries name
# cited/defined inputs (the other two classes — control,
# declared-assumption — describe scaffolding/assumptions, not inputs).
_PROVENANCE_INPUT_CLASSES = frozenset({"paper-defined", "cited-paper"})
_PROVENANCE_CLASS_RE = re.compile(
    r"(?:class\s*=\s*|:\s*)"
    r"(paper-defined|cited-paper|control|declared-assumption|"
    r"arbitrary-representative)\b")


def _fold(s: str) -&gt; str:
    """Alphanumeric fold for provenance name matching: lowercase, drop
    everything else, so ALPHA_S_MZ matches a block entry naming
    "alpha_s(M_Z)"."""
    return re.sub(r"[^a-z0-9]", "", s.lower())


def _provenance_cited_inputs(code: str) -&gt; set[str]:
    """Folded texts of INPUT_PROVENANCE entries classed paper-defined or
    cited-paper (v2.2 patch, item d(ii)).

    Heuristic, fail-closed: if the block cannot be found or parsed the
    result is empty and no provenance exemption applies.

    Recognized shape (the shape the paper's scripts use): a line
    containing the token INPUT_PROVENANCE, followed by indented bullet
    entries ("  - &lt;text&gt;: class=&lt;cls&gt; ..." or the colon form
    "  - &lt;text&gt;: &lt;cls&gt; ..."), entries possibly spanning continuation
    lines. Documented limits: only this docstring-style indented block
    is parsed (a col-0 `#`-comment block is not recognized); the first
    class tag found in an entry wins; name matching is folded-substring,
    which can over-match very short names. The exemption this feeds is
    declaration-scoped (see STATIC_CHECK_PROFILES): the validator checks
    the constant is NAMED in a cited/paper-defined entry, never that the
    citation is genuine.
    """
    lines = code.splitlines()
    start = next((i for i, ln in enumerate(lines)
                  if "INPUT_PROVENANCE" in ln), None)
    if start is None:
        return set()
    block: list[str] = []
    for ln in lines[start + 1:]:
        if not ln.strip() or ln[0] in " \t" \
                or ln.lstrip().startswith("#"):
            block.append(ln)
        else:
            break
    entries: list[str] = []
    for ln in block:
        s = ln.strip()
        if s.startswith("- ") or s == "-":
```

```
            entries.append(s[1:].strip())
        elif entries and s:
            entries[-1] += " " + s
        # Blank lines and any text before the first bullet are ignored.
    cited: set[str] = set()
    for entry in entries:
        m = _PROVENANCE_CLASS_RE.search(entry)
        if m and m.group(1) in _PROVENANCE_INPUT_CLASSES:
            cited.add(_fold(entry))
    return cited


def python_static_check(code: str, badge: str, policy: Policy) -&gt; list[dict]:
    """Heuristic static checks only; this is NOT a code sandbox.

    - banned modules / banned dynamic calls come from Policy
      (capability-based; math and numerics are allowed).
    - Banned dynamic calls are caught in three shapes: bare calls
      (eval(...)), attribute chains rooted at builtins
      (builtins.eval(...)), and getattr with a string literal
      (getattr(x, "eval")(...)). v2.0.4 V19: the attribute-chain case
      closed a real bypass (builtins.eval walked straight through the
      old ast.Name-only check).
    - DOCUMENTED HEURISTIC LIMITS (not caught, by design of a static
      heuristic): aliased imports (from builtins import eval as e),
      rebinding (ev = builtins.eval), and computed attribute access.
      The check proves "no obvious dynamic execution in the source as
      written" — it is not a sandbox and never claims to be.
    - LEVEL_A float discipline: float literals and float() calls are
      violations unless the float is a direct argument of a builtin
      print()/format() call AND its source line carries the "(display
      only)" marker. The exemption is hardened against the nesting
      bypass: the float's parent chain must reach the print/format call
      without passing through any other call — print("r", compute(1.5))
      does NOT exempt the 1.5. (v2.2 patch F-48; fixes the gameable walk
      the old "non-gameable" claim overstated.)
    - Named profiles (v2.2 patch, item d; see STATIC_CHECK_PROFILES).
      "strict" (default): everything above, exactly. "physics_payload":
      (i) `sys` imports are allowed — the defended capability is process
      control/exfiltration via subprocess/socket/os-level access;
      sys.exit/sys.argv are neither; (ii) float LITERALS (not float()
      calls) bound to module-level UPPER_CASE constants listed in the
      script's INPUT_PROVENANCE block under the paper-defined or
      cited-paper class are exempt from FLOAT_IN_LEVEL_A. The profile is
      selected via Policy(static_check_profile=...); "strict" is the
      default and the right choice for untrusted code.
    """
    try:
        tree = ast.parse(code)
    except SyntaxError as exc:
        return [{"code": "PYTHON_SYNTAX", "detail": str(exc)}]
    except (ValueError, MemoryError, RecursionError) as exc:
        return [{"code": "PYTHON_SYNTAX", "detail": f"unparseable: {exc}"}]

    violations: list[dict] = []
    lines = code.splitlines()
    parents: dict[ast.AST, ast.AST] = {}
    for parent in ast.walk(tree):
        for child in ast.iter_child_nodes(parent):
            parents[child] = parent

    # v2.2 patch, item d: named static-check profile from the Policy.
    profile = policy.static_check_profile
    if profile == "physics_payload":
        # (i) `sys` is allowed under this profile: the defended capability
        # is process control/exfiltration via subprocess/socket/os-level
        # access; sys.exit/sys.argv are neither. subprocess, socket and
        # os stay banned.
        banned_modules = policy.banned_modules - {"sys"}
    else:
        banned_modules = policy.banned_modules
    # (ii) cited/paper-defined float inputs, parsed once per check.
    cited_inputs: set[str] = set()
    if profile == "physics_payload" and badge == "LEVEL_A":
        cited_inputs = _provenance_cited_inputs(code)

    # Names rebound at module top level. A shadowed `print`/`format`
    # (e.g. `print = lambda v: v`) voids the display exemption: the
    # exemption trusts the builtin, not the name.
    bound_top: set[str] = set()
```

```
for node in tree.body:
    if isinstance(node, (ast.FunctionDef, ast.AsyncFunctionDef,
                         ast.ClassDef)):
        bound_top.add(node.name)
    elif isinstance(node, ast.Assign):
        for target in node.targets:
            if isinstance(target, ast.Name):
                bound_top.add(target.id)
            elif isinstance(target, (ast.Tuple, ast.List)):
                for elt in target.elts:
                    if isinstance(elt, ast.Name):
                        bound_top.add(elt.id)
    elif isinstance(node, ast.AnnAssign) \
            and isinstance(node.target, ast.Name):
        bound_top.add(node.target.id)
    elif isinstance(node, ast.Import):
        for alias in node.names:
            bound_top.add((alias.asname or alias.name).split(".")[0])
    elif isinstance(node, ast.ImportFrom):
        for alias in node.names:
            bound_top.add(alias.asname or alias.name)

def provenance_input_exempt(node: ast.AST) -&gt; bool:
    """physics_payload only: a float literal is exempt when it sits
    inside the value assigned to a module-level UPPER_CASE constant
    listed in the script's INPUT_PROVENANCE block under the
    paper-defined or cited-paper class (v2.2 patch, item d(ii)).

    The walk climbs through value-expression nodes (BinOp/UnaryOp/
    Tuple/...); any other node type (a Call, a Subscript, ...) between
    the float and the assignment means the float is computed, not a
    declared input — not exempt. The assignment must be module-level
    (directly in the module body), single-target, and UPPER_CASE.
    """
    if not cited_inputs:
        return False
    cur = node
    while cur in parents:
        cur = parents[cur]
        if isinstance(cur, (ast.BinOp, ast.UnaryOp, ast.Tuple,
                            ast.List, ast.Set, ast.Dict, ast.IfExp,
                            ast.Starred)):
            continue  # still inside the assigned value expression
        if isinstance(cur, ast.Assign):
            targets = cur.targets
        elif isinstance(cur, ast.AnnAssign):
            targets = [cur.target]
        else:
            return False
        names = [t.id for t in targets
                 if isinstance(t, ast.Name) and t.id.isupper()]
        if len(names) == 1 and parents.get(cur) is tree \
                and any(_fold(names[0]) in entry
                        for entry in cited_inputs):
            return True
        return False
    return False

def float_exempt(node: ast.AST) -&gt; bool:
    """Hardened display exemption: walk the AST parent chain; the
    float must reach a *builtin* print()/format() call whose source
    line carries the (display only) marker WITHOUT passing through
    any other call on the way.

    v2.2 patch F-48: the old walk ignored intermediate calls, so
    `print("result", compute(1.5))  # (display only)` wrongly exempted
    the computational 1.5. A float nested inside a non-print/format
    call is never a display argument — fail closed.
    """
    cur = node
    while cur in parents:
        cur = parents[cur]
        if isinstance(cur, ast.Call):
            if isinstance(cur.func, ast.Name) \
                    and cur.func.id in ("print", "format"):
                if cur.func.id in bound_top:
                    return False  # shadowed: not the builtin
                lineno = getattr(node, "lineno", 0)
                if 1 &lt;= lineno &lt;= len(lines) \
                        and "(display only)" in lines[lineno - 1]:
```

```
                    return True
                return False
            # v2.2 patch F-48: the float sits inside a nested
            # non-print/format call (e.g. compute(1.5) inside print)
            # — the value is computational, not display. Not exempt.
            return False
    return False

def _dotted_name(func: ast.AST) -&gt; str | None:
    """Resolve a.b.c attribute chains to their dotted name.

    Returns None for anything that is not a pure Name-rooted
    attribute chain (calls, subscripts, ...)."""
    parts: list[str] = []
    cur = func
    while isinstance(cur, ast.Attribute):
        parts.append(cur.attr)
        cur = cur.value
    if isinstance(cur, ast.Name):
        parts.append(cur.id)
        return ".".join(reversed(parts))
    return None

def _dynamic_call_term(node: ast.Call) -&gt; str | None:
    """Name the dynamic-execution primitive if this call uses one.

    Shapes caught: bare eval(...); builtins-rooted attribute chains
    (builtins.eval(...), __builtins__.exec(...)); getattr with a
    string literal naming a banned call (getattr(x, "eval")(...)).
    Returns the dotted/literal term, or None.
    """
    func = node.func
    if isinstance(func, ast.Name):
        if func.id in policy.banned_calls:
            return func.id
        return None
    if isinstance(func, ast.Attribute):
        dotted = _dotted_name(func)
        if dotted is not None:
            bits = dotted.split(".")
            # Restrict to the builtins root: re.compile(...) and
            # obj.exec(...) are legitimate code, not dynamic
            # execution. Only builtins.&lt;banned&gt; is the bypass shape.
            if len(bits) &gt;= 2 and bits[-1] in policy.banned_calls \
                    and bits[0] in ("builtins", "__builtins__"):
                return dotted
        return None
    if isinstance(func, ast.Call) and isinstance(func.func, ast.Name) \
            and func.func.id == "getattr" and len(func.args) &gt;= 2:
        name_arg = func.args[1]
        if isinstance(name_arg, ast.Constant) \
                and isinstance(name_arg.value, str) \
                and name_arg.value in policy.banned_calls:
            return f'getattr(..., "{name_arg.value}")'
    return None

for node in ast.walk(tree):
    if isinstance(node, ast.Import):
        for alias in node.names:
            top = alias.name.split(".")[0]
            if top in banned_modules:
                violations.append({
                    "code": "BANNED_MODULE",
                    "term": alias.name,
                    "line": getattr(node, "lineno", None),
                })
    elif isinstance(node, ast.ImportFrom):
        top = (node.module or "").split(".")[0]
        if top in banned_modules:
            violations.append({
                "code": "BANNED_MODULE",
                "term": node.module or "",
                "line": getattr(node, "lineno", None),
            })
    elif isinstance(node, ast.Call):
        term = _dynamic_call_term(node)
        if term is not None:
            violations.append({
                "code": "DYNAMIC_EXECUTION",
                "term": term,
```

```
                    "line": getattr(node, "lineno", None),
                })

        if badge == "LEVEL_A":
            is_float_call = isinstance(node, ast.Call) \
                and isinstance(node.func, ast.Name) \
                and node.func.id == "float"
            is_float_literal = isinstance(node, ast.Constant) \
                and isinstance(node.value, float)
            if (is_float_call or is_float_literal) \
                    and not float_exempt(node) \
                    and not (is_float_literal
                             and provenance_input_exempt(node)):
                violations.append({
                    "code": "FLOAT_IN_LEVEL_A",
                    "term": "float() call" if is_float_call else "float literal",
                    "line": getattr(node, "lineno", None),
                })
    return violations
# ---------------------------------------------------------------------------
# Envelope construction
# ---------------------------------------------------------------------------

def envelope_for_hash(message: dict) -&gt; dict:
    """Fields covered by the envelope hash (integrity metadata excluded to
    avoid a circular hash).

    v2.0.4: envelope_tier is hash-covered (tier is a security-relevant
    claim — a working/archival swap must invalidate the hash).
    epistemic_context is covered when present (working tier may omit it).
    """
    covered = {k: message[k]
               for k in ("protocol", "header", "envelope_tier", "payload")
               if k in message}
    if "epistemic_context" in message:
        covered["epistemic_context"] = message["epistemic_context"]
    return covered


def make_message(
    *,
    policy: Policy,
    sender: str,
    target: str,
    register: str | None = None,
    badge: str | None = None,
    content: str,
    envelope_tier: str = "archival",  # v2.0.4 D1: "working"|"archival"
    tier: str | None = None,  # v2.0.4 V21: hash tier "chat"|"machine"|None
    axiom_set_hash: str | None = None,
    registry_version: int | None = None,
    session_id: str = "default",
    content_format: str = "PLAIN_TEXT",
    claim_class: str = "STRUCTURAL",
    lineage: str = "prose",
    script_id: str | None = None,
    inherited_from: str | None = None,
    theorem_id: str | None = None,
    # v2.2 patch F-47: human_review lineage requires these three; the
    # validator rejects a human_review envelope missing any of them.
    reviewer: str | None = None,
    review_date: str | None = None,
    attestation_ref: str | None = None,
    depends_on=None,
    falsifiers=None,
    bridges=None,
    determinism=None,
    message_type: str = "REQUEST",
    in_reply_to: str | None = None,
    three_line_register=None,
    scope_notes: str = "",
) -&gt; dict:
    """Build a message envelope. Refuses (raises ValueError) if the message
    fails its own validation — never emits an invalid payload.

    v2.0.4: envelope_tier selects the completeness tier. "archival"
    (default) requires register+ badge and the full envelope. "working"
    makes epistemic_context optional — it is included only when register
    and badge are both given, otherwise omitted (the validator records
    "context:undeclared"). tier selects the hash tier: None (default)
```

```
computes real hashes with no declared tier (machine behavior, as
before); "machine" computes real hashes and declares tier "machine";
"chat" leaves both hashes blank and declares tier "chat" (for
machine-side construction of chat-tier envelopes).
"""
if not isinstance(content, str):
    raise ValueError("outbound refusal: content must be a string")
if envelope_tier not in ENVELOPE_TIERS:
    raise ValueError(
        f"outbound refusal: envelope_tier must be one of "
        f"{sorted(ENVELOPE_TIERS)}")
if envelope_tier == "archival" and (register is None or badge is None):
    raise ValueError(
        "outbound refusal: archival tier requires register and badge")
if tier is not None and tier not in TIERS:
    raise ValueError(
        f"outbound refusal: tier must be one of {sorted(TIERS)}")
header: dict = {
    "message_id": str(uuid.uuid4()),
    "message_type": message_type,
    "sender_agent": sender,
    "target_agent": target,
    "timestamp": now(),
    "protocol_version": VERSION,
    "min_protocol_version": VERSION,
}
if in_reply_to is not None:
    header["in_reply_to"] = in_reply_to

provenance: dict = {"lineage": lineage,
                    "depends_on": list(depends_on or [])}
if script_id is not None:
    provenance["script_id"] = script_id
if inherited_from is not None:
    provenance["inherited_from"] = inherited_from
if theorem_id is not None:
    provenance["theorem_id"] = theorem_id
if reviewer is not None:
    provenance["reviewer"] = reviewer
if review_date is not None:
    provenance["review_date"] = review_date
if attestation_ref is not None:
    provenance["attestation_ref"] = attestation_ref

payload: dict = {
    "format": content_format,
    "content": content,
    "claim_class": claim_class,
    "provenance": provenance,
    "determinism": determinism or {"mode": "DETERMINISTIC"},
}
if falsifiers is not None:
    payload["falsification"] = {"conditions": list(falsifiers)}
if bridges is not None:
    payload["bridge_levels"] = list(bridges)
if three_line_register is not None:
    payload["three_line_register"] = dict(three_line_register)
message = {
    "protocol": {"name": "ESP", "version": VERSION},
    "header": header,
    "envelope_tier": envelope_tier,
    "payload": payload,
    "integrity": {
        "content_hash": "" if tier == "chat" else digest(content),
        "envelope_hash": "",
        "axiom_set_hash": axiom_set_hash or policy.axiom_set_hash,
        "registry_version": registry_version
        if registry_version is not None else policy.registry_version,
        "status": "PENDING",
        # v2.0.2: violations/audit_chain are validator-emitted only;
        # outbound messages never carry them (inbound ones are stripped).
    },
}
if register is not None and badge is not None:
    message["epistemic_context"] = {
        "session_id": session_id,
        "register": register,
        "badge": badge,
        "axiom_set_hash": axiom_set_hash or policy.axiom_set_hash,
        "registry_version": registry_version
```

```
            if registry_version is not None else policy.registry_version,
            "active_axioms": sorted(policy.axiom_universe),
            "scope_notes": scope_notes,
        }
    if tier is not None:
        message["integrity"]["tier"] = tier
    if tier != "chat":
        message["integrity"]["envelope_hash"] = object_digest(
            envelope_for_hash(message))

    result = validate_message(message, policy)
    if not result["ok"]:
        raise ValueError(
            f"outbound refusal: constructed message failed own validation: "
            f"{result.get('error')}")
    return message


# ---------------------------------------------------------------------------
# Dialectic records (v2.0.4 D2/D3 — archival tier)
# ---------------------------------------------------------------------------

def _validate_disagreement(dis, policy: Policy):
    """Structural validation of a DISAGREEMENT record (D2).

    Records two agents' divergent verdicts on one envelope plus the
    precise structured delta and an optional later human adjudication.
    The protocol routes disagreements; it does not adjudicate them.
    """
    dis = _req_object(dis, "payload.disagreement")
    _req_keys(dis,
              {"target_message_id", "position_a", "position_b", "delta"},
              {"target_message_id", "position_a", "position_b", "delta",
               "adjudication"},
              "payload.disagreement")
    _req_uuid(dis["target_message_id"], "disagreement.target_message_id")
    for side in ("position_a", "position_b"):
        pos = _req_object(dis[side], f"disagreement.{side}")
        _req_keys(pos, {"agent", "verdict", "check", "reason"},
                  {"agent", "verdict", "check", "reason"},
                  f"disagreement.{side}")
        _req_nonempty(pos["agent"], f"disagreement.{side}.agent")
        _req_enum(pos["verdict"], DISAGREEMENT_VERDICTS,
                  f"disagreement.{side}.verdict")
        _req_nonempty(pos["check"], f"disagreement.{side}.check")
        _req_nonempty(pos["reason"], f"disagreement.{side}.reason")
    delta = _req_object(dis["delta"], "disagreement.delta")
    _req_keys(delta, {"check", "a_reading", "b_reading"},
              {"check", "a_reading", "b_reading"}, "disagreement.delta")
    for key in ("check", "a_reading", "b_reading"):
        _req_nonempty(delta[key], f"disagreement.delta.{key}")
    if "adjudication" in dis:
        adj = _req_object(dis["adjudication"], "disagreement.adjudication")
        _req_keys(adj, {"status"},
                  {"status", "resolution", "adjudicated_by", "evidence_ref"},
                  "disagreement.adjudication")
        _req_enum(adj["status"], ADJUDICATION_STATUSES,
                  "disagreement.adjudication.status")
        for key in ("resolution", "adjudicated_by", "evidence_ref"):
            if key in adj and not isinstance(adj[key], str):
                raise ProtocolError(
                    f"disagreement.adjudication.{key} must be a string")


def _validate_confrontation(con, policy: Policy):
    """Structural validation of a CONFRONTATION record (D3).

    Second-person challenge: "your claim fails because...". Distinct
    from FALSIFICATION (first-person: "what would falsify my claim").
    broken_premise is structured {axiom, premise_id, statement} so a
    reader can check whether the named premise exists and fails.
    """
    con = _req_object(con, "payload.confrontation")
    _req_keys(con,
              {"target_claim_id", "counterexample", "demonstration",
               "broken_premise", "claim_class"},
              {"target_claim_id", "counterexample", "demonstration",
               "broken_premise", "claim_class"},
              "payload.confrontation")
    _req_uuid(con["target_claim_id"], "confrontation.target_claim_id")
```

```
    _req_nonempty(con["counterexample"], "confrontation.counterexample")
    _req_nonempty(con["demonstration"], "confrontation.demonstration")
    _req_enum(con["claim_class"], CLAIMS, "confrontation.claim_class")
    bp = _req_object(con["broken_premise"], "confrontation.broken_premise")
    _req_keys(bp, {"statement"}, {"axiom", "premise_id", "statement"},
              "confrontation.broken_premise")
    _req_nonempty(bp["statement"], "confrontation.broken_premise.statement")
    if bp.get("axiom") is not None \
            and bp["axiom"] not in policy.axiom_universe:
        raise ProtocolError(
            "confrontation.broken_premise.axiom not in registry axiom "
            f"universe: {bp['axiom']}")
    if bp.get("premise_id") is not None \
            and not isinstance(bp["premise_id"], str):
        raise ProtocolError(
            "confrontation.broken_premise.premise_id must be a string "
            "or null")
# ---------------------------------------------------------------------------
# Validation
# ---------------------------------------------------------------------------

def _looks_like_v1(message: dict) -&gt; bool:
    try:
        if message.get("protocol", {}).get("version") == "1.0":
            return True
        for section in ("epistemic_context", "integrity"):
            ctx = message.get(section, {})
            if isinstance(ctx, dict) and "axiom_registry_hash" in ctx:
                return True
    except Exception:
        # Heuristic pre-check only: any failure means "not v1-shaped";
        # the main validator will reject the malformed input properly.
        return False
    return False


def validate_message(message, policy: Policy | None = None) -&gt; dict:
    """Validate a message. NEVER raises on malformed input: every failure
    mode returns {"ok": False, "status": "REJECTED", "error": ...}.

    On success returns status VALIDATED plus a `checks` list naming exactly
    the checks that ran, and the `not_established` honesty list.
    """
    if policy is None:
        raise ValueError(
            "a Policy is required; use Policy(demo_registry=True) for the "
            "declared demo registry, Policy(insecure_demo_registry=True) "
            "for the zero-hash placeholder, or configure a real registry")
    # v2.0.4 V22: the demo warning is suppressible for batch validation.
    if policy.warn_on_validate:
        policy.warn_if_demo()
    checks: list[str] = []

    def rejected(error: str) -&gt; dict:
        return {"ok": False, "status": "REJECTED", "error": error,
                "checks": checks, "not_established": NOT_ESTABLISHED}

    try:
        if isinstance(message, str):
            try:
                message = json.loads(message)
            except (json.JSONDecodeError, ValueError) as exc:
                return rejected(f"JSON parse failure: {exc}")
        if not isinstance(message, dict):
            return rejected("message must be a JSON object")

        if _looks_like_v1(message):
            return rejected(
                "ESP v1.0 envelope detected (field renames in v2.0: "
                "axiom_registry_hash -&gt; axiom_set_hash, "
                "protocol.version 1.0 -&gt; 2.0, "
                "integrity.axiom_registry_hash -&gt; integrity.axiom_set_hash); "
                "use migrate_v1_to_v2() to convert")

        try:
            size = len(canonical(message))
        except (ValueError, TypeError) as exc:
            return rejected(f"message not JSON-canonicalizable: {exc}")
        if size &gt; policy.max_message_chars:
            return rejected("message exceeds size limit")
```

```
message = _req_object(message, "$")
_req_keys(message,
          {"protocol", "header", "envelope_tier", "payload",
           "integrity"},
          {"protocol", "header", "envelope_tier", "epistemic_context",
           "payload", "integrity"},
          "$")
checks.append("structure")

if message["protocol"] != {"name": "ESP", "version": VERSION}:
    raise ProtocolError(
        f"unsupported protocol (expected ESP {VERSION})")

# v2.0.4 D1: envelope completeness tier. Working = cheap
# conversational layer; archival = full context, enforcing.
tier = message["envelope_tier"]
_req_enum(tier, ENVELOPE_TIERS, "envelope_tier")
checks.append(f"envelope_tier:{tier}")

header = _req_object(message["header"], "header")
_req_keys(header,
          {"message_id", "message_type", "sender_agent",
           "target_agent", "timestamp", "protocol_version",
           "min_protocol_version"},
          {"message_id", "in_reply_to", "correlation_id",
           "message_type", "sender_agent", "target_agent",
           "timestamp", "protocol_version", "min_protocol_version"},
          "header")
_req_uuid(header["message_id"], "header.message_id")
_req_uuid(header.get("in_reply_to"), "header.in_reply_to",
          nullable=True)
if header.get("correlation_id") is not None:
    _req_uuid(header["correlation_id"], "header.correlation_id")
_req_enum(header["message_type"], TYPES, "header.message_type")
# v2.0.4 D1: the working tier carries conversation only. An
# archival message type on the working tier is REJECTED with
# TIER_MISMATCH — the mechanical upgrade path is filling
# epistemic_context and resending as archival.
if tier == "working" and header["message_type"] not in WORKING_TYPES:
    raise ProtocolError(
        f"TIER_MISMATCH: message_type {header['message_type']} "
        f"requires the archival tier (working tier carries "
        f"{sorted(WORKING_TYPES)} only); resend with envelope_tier "
        f"'archival' and full epistemic_context")
_req_nonempty(header["sender_agent"], "header.sender_agent")
_req_nonempty(header["target_agent"], "header.target_agent")
_req_maxlen(header["sender_agent"], "header.sender_agent", 256)
_req_maxlen(header["target_agent"], "header.target_agent", 256)
# v2.0.2: a RESPONSE must name its antecedent — audit threading.
if header["message_type"] == "RESPONSE" \
        and not header.get("in_reply_to"):
    raise ProtocolError(
        "RESPONSE requires header.in_reply_to (audit threading)")
parsed_ts = _req_timestamp(header["timestamp"], "header.timestamp")
# v2.0.3: future-dating is never legitimate traffic — the clock-skew
# bound is unconditional hygiene. The replay bound stays opt-in
# (async sparring rounds are legitimately validated hours later).
age = (datetime.now(timezone.utc) - parsed_ts).total_seconds()
if age &lt; -300:
    raise ProtocolError(
        "header.timestamp is more than 300s in the future "
        "(clock skew bound)")
if policy.max_age_seconds is not None \
        and age &gt; policy.max_age_seconds:
    raise ProtocolError(
        f"header.timestamp is {int(age)}s old, older than "
        f"max_age_seconds={policy.max_age_seconds} (replay bound)")
if header["protocol_version"] != VERSION \
        or header["min_protocol_version"] != VERSION:
    raise ProtocolError("unsupported protocol version "
                        f"(expected {VERSION})")

# v2.0.4 D1: epistemic_context is optional on the working tier.
# Absent context is recorded honestly ("context:undeclared"), not
# rejected — but register/badge/registry checks cannot run without
# it, so they are skipped and the checks list says so.
ctx_raw = message.get("epistemic_context")
if ctx_raw is None:
    if tier != "working":
        raise ProtocolError(
```

```
            "archival tier requires epistemic_context "
            "(full context is what makes the tier archival)")
    checks.append("context:undeclared")
    ctx = None
    register = None
    badge = None
else:
    ctx = _req_object(ctx_raw, "epistemic_context")
    _req_keys(ctx,
              {"session_id", "register", "badge", "axiom_set_hash",
               "registry_version"},
              {"session_id", "register", "badge", "axiom_set_hash",
               "registry_version", "active_axioms", "scope_notes"},
              "epistemic_context")
    _req_nonempty(ctx["session_id"], "session_id")
    _req_maxlen(ctx["session_id"], "session_id", 256)
    _req_enum(ctx["register"], REGISTERS, "register")
    _req_enum(ctx["badge"], BADGES, "badge")
    _req_sha(ctx["axiom_set_hash"], "axiom_set_hash")
    _req_int(ctx["registry_version"], "registry_version", 0)
    if "active_axioms" in ctx:
        _req_unique_strs(ctx["active_axioms"], "active_axioms")
        unknown = [a for a in ctx["active_axioms"]
                   if a not in policy.axiom_universe]
        if unknown:
            raise ProtocolError(
                "active_axioms not in registry axiom universe: "
                f"{unknown}")
    if "scope_notes" in ctx \
            and not isinstance(ctx["scope_notes"], str):
        raise ProtocolError("scope_notes must be a string")
    _req_maxlen(ctx.get("scope_notes", ""), "scope_notes", 4000)

    register = ctx["register"]
    badge = ctx["badge"]
    if register == "STAGE_N" and badge != "LEVEL_A":
        raise ProtocolError("STAGE_N requires LEVEL_A badge")
    if register == "STAGE_P" and badge not in {"LEVEL_A", "LEVEL_B"}:
        raise ProtocolError("STAGE_P requires LEVEL_A or LEVEL_B")
    if register == "STAGE_C" and badge not in {"LEVEL_B", "LEVEL_C"}:
        raise ProtocolError("STAGE_C requires LEVEL_B or LEVEL_C")
    if register == "META_AUDIT" and badge != "META":
        raise ProtocolError("META_AUDIT requires META badge")
    checks.append("register_badge")

    if ctx["axiom_set_hash"] != policy.axiom_set_hash:
        raise ProtocolError(
            "axiom_set_hash mismatch with local registry")
    skew = abs(ctx["registry_version"] - policy.registry_version)
    if skew &gt; policy.accepted_registry_skew:
        raise ProtocolError(
            f"registry version skew {skew} exceeds accepted bound "
            f"+-{policy.accepted_registry_skew}")
    checks.append("registry_match")

payload = _req_object(message["payload"], "payload")
_req_keys(payload,
          {"format", "content", "claim_class", "provenance",
           "determinism"},
          {"format", "content", "claim_class", "provenance",
           "determinism", "three_line_register", "falsification",
           "bridge_levels", "formal_assertions", "dependencies",
           "metadata", "disagreement", "confrontation"},
          "payload")
_req_enum(payload["format"], FORMATS, "payload.format")
_req_enum(payload["claim_class"], CLAIMS, "payload.claim_class")
_req_nonempty(payload["content"], "payload.content")
if len(payload["content"]) &gt; policy.max_content_chars:
    raise ProtocolError("content exceeds size limit")

prov = _req_object(payload["provenance"], "provenance")
_req_keys(prov, {"lineage"},
          {"lineage", "script_id", "inherited_from", "theorem_id",
           "depends_on", "reviewer", "review_date",
           "attestation_ref"},
          "provenance")
_req_enum(prov["lineage"], LINEAGES, "provenance.lineage")
if prov["lineage"] == "script":
    sid = prov.get("script_id")
    if not isinstance(sid, str) or not SCRIPT_RE.fullmatch(sid):
```

```
        raise ProtocolError(
            "script lineage requires script_id matching "
            "(F|P|H|G|MC|FW|PA).&lt;digits&gt;")
if prov["lineage"] == "bundle":
    # v2.2: bundle lineage reports outcomes of executing a bundle
    # of scripts. The bundle manifest named in depends_on is the
    # grounding — fail closed when it is missing or names no
    # bundle artifact. Existence is the recipient's check (shape
    # check only, same as script_id); the error names the cause.
    deps = prov.get("depends_on")
    if not isinstance(deps, list) or not deps:
        raise ProtocolError(
            "bundle lineage requires depends_on naming at least "
            "one bundle artifact (.zip)")
    if not any(isinstance(d, str) and BUNDLE_RE.search(d)
               for d in deps):
        raise ProtocolError(
            "bundle lineage requires depends_on to name at least "
            "one bundle artifact (.zip): none of the named "
            f"{len(deps)} entries ends in .zip")
if prov["lineage"] == "inherited":
    _req_nonempty(prov.get("inherited_from"),
                  "inherited lineage requires inherited_from")
if prov["lineage"] == "human_review":
    # v2.2 patch F-47: human_review is the one lineage asserting
    # human sign-off, so it must name its reviewer, the review
    # date, and a reference to the attestation. Fail closed: any
    # of the three missing or empty rejects the envelope. (The
    # validator establishes that the fields are PRESENT, never
    # that the human actually reviewed — attestation content is
    # the recipient's check, same as script_id existence.)
    for _key in ("reviewer", "review_date", "attestation_ref"):
        _req_nonempty(
            prov.get(_key),
            f"human_review lineage requires {_key}")
if "depends_on" in prov:
    _req_unique_strs(prov["depends_on"], "depends_on")

det = _req_object(payload["determinism"], "determinism")
_req_keys(det, {"mode"}, {"mode", "seed", "note"}, "determinism")
_req_enum(det["mode"], MODES, "determinism.mode")
if det["mode"] == "SEEDED":
    _req_int(det.get("seed"), "determinism.seed")
if "note" in det and not isinstance(det["note"], str):
    raise ProtocolError("determinism.note must be a string")
if det["mode"] == "STOCHASTIC" and register == "STAGE_N":
    raise ProtocolError(
        "STAGE_N requires DETERMINISTIC or SEEDED mode")
checks.append("determinism")

tlr = payload.get("three_line_register")
if tlr is not None:
    tlr = _req_object(tlr, "three_line_register")
    _req_keys(tlr, set(),
              {"native", "reconstruction", "observation"},
              "three_line_register")
    if any(not isinstance(v, str) for v in tlr.values()):
        raise ProtocolError(
            "three_line_register values must be strings")
    if register == "STAGE_N" and badge == "LEVEL_A" \
            and not tlr.get("native", "").strip():
        raise ProtocolError(
            "STAGE_N/LEVEL_A requires a non-empty native register "
            "line when three_line_register is supplied")
    checks.append("three_line_register")

fals = payload.get("falsification")
# LEVEL_A always requires &gt;=1 falsification condition (binding
# decision 10 — no toggle). The "falsification" check name is
# appended only when the check actually ran (badge truthfulness).
if badge == "LEVEL_A":
    if not isinstance(fals, dict) \
            or not isinstance(fals.get("conditions"), list) \
            or not fals["conditions"]:
        raise ProtocolError(
            "LEVEL_A requires at least one falsification "
            "condition")
if fals is not None:
    fals = _req_object(fals, "falsification")
    _req_keys(fals, {"conditions"}, {"conditions"},
```

```
                "falsification")
        seen: set[str] = set()
        for i, cond in enumerate(fals["conditions"]):
            path = f"falsification.conditions[{i}]"
            cond = _req_object(cond, path)
            _req_keys(cond, {"id", "statement"},
                      {"id", "statement", "trigger"}, path)
            cid = cond["id"]
            if not isinstance(cid, str) \
                    or not COND_RE.fullmatch(cid) or cid in seen:
                raise ProtocolError(
                    f"{path}: invalid or duplicate condition id")
            seen.add(cid)
            _req_nonempty(cond["statement"], path + ".statement")
            if "trigger" in cond \
                    and not isinstance(cond["trigger"], str):
                raise ProtocolError(f"{path}.trigger must be a string")
        checks.append("falsification")

    bridges = payload.get("bridge_levels", [])
    if not isinstance(bridges, list):
        raise ProtocolError("bridge_levels must be an array")
    if bridges:
        for i, bridge in enumerate(bridges):
            path = f"bridge_levels[{i}]"
            bridge = _req_object(bridge, path)
            _req_keys(bridge, {"from", "to", "bridge_level"},
                      {"from", "to", "bridge_level",
                       "bridge_description"}, path)
            _req_nonempty(bridge["from"], path + ".from")
            _req_nonempty(bridge["to"], path + ".to")
            _req_enum(bridge["bridge_level"], BRIDGES,
                      path + ".bridge_level")
            if "bridge_description" in bridge \
                    and not isinstance(bridge["bridge_description"], str):
                raise ProtocolError(
                    path + ".bridge_description must be a string")
            if badge == "LEVEL_A" and bridge["bridge_level"] != "A":
                raise ProtocolError(
                    "LEVEL_A payload cannot depend on a level "
                    f"{bridge['bridge_level']} bridge")
        checks.append("bridges")

    # v2.0.4 D2/D3: the dialectic message types carry structured
    # records. The TIER_MISMATCH gate above already forced archival;
    # here the record shape itself is validated.
    mtype = header["message_type"]
    if mtype == "DISAGREEMENT":
        if "disagreement" not in payload:
            raise ProtocolError(
                "DISAGREEMENT requires payload.disagreement "
                "{target_message_id, position_a, position_b, delta, "
                "adjudication?}")
        _validate_disagreement(payload["disagreement"], policy)
        checks.append("disagreement")
    if mtype == "CONFRONTATION":
        if "confrontation" not in payload:
            raise ProtocolError(
                "CONFRONTATION requires payload.confrontation "
                "{target_claim_id, counterexample, demonstration, "
                "broken_premise, claim_class}")
        _validate_confrontation(payload["confrontation"], policy)
        checks.append("confrontation")

    # v2.0.2: validate a DEEP COPY. The v2.0.1 chat tier wrote computed
    # hashes back into the caller's dict, so one chat-tier pass
    # manufactured machine-tier "verified" credentials on revalidation
    # (tier laundering). The caller's object is never touched now.
    message = copy.deepcopy(message)
    # Re-fetch views into the copy (payload/ctx/tlr were bound above).
    # v2.0.4: epistemic_context may be absent (working tier).
    payload = message["payload"]
    ctx = message.get("epistemic_context")
    header = message["header"]
    tlr = payload.get("three_line_register")

    integ = _req_object(message["integrity"], "integrity")
    _req_keys(integ,
              {"content_hash", "envelope_hash", "axiom_set_hash",
               "registry_version", "status"},
```

```
          {"content_hash", "envelope_hash", "axiom_set_hash",
           "registry_version", "status", "tier",
           "violations", "audit_chain"},
          "integrity")
for key in ("axiom_set_hash",):
    _req_sha(integ[key], "integrity." + key)
# Two-tier hash handling (v2.0.1, hardened in v2.0.2):
#  - Chat tier: a chat AI cannot compute SHA-256, so it MUST leave
#    content_hash/envelope_hash as "" — the validator computes them.
#  - Machine tier: non-empty hashes are verified strictly; forged
#    hashes are REJECTED.
# Honesty scope (v2.0.2 correction): both tiers attest
# well-formedness + self-consistency at validation time + the named
# checks that ran. Neither tier is tamper-evidence against a
# competent attacker (anyone with Python can recompute hashes);
# the machine tier is corruption-detection plus lazy-forgery
# detection. sender_identity and transport_authenticity are never
# established — see NOT_ESTABLISHED.
for key in ("content_hash", "envelope_hash"):
    val = integ[key]
    if not isinstance(val, str) or (val != "" and not HASH_RE.fullmatch(val)):
        raise ProtocolError(f"integrity.{key}: expected lowercase SHA-256 or \"\" (compute-locally)")
_req_int(integ["registry_version"], "integrity.registry_version", 0)
# v2.0.2: explicit tier signal. Declared tiers are enforced;
# undeclared tiers are inferred from hash presence and labeled so.
# A liar can still misdeclare, but downgrade becomes an explicit
# false claim in the envelope instead of a silent omission.
declared_tier = integ.get("tier")
if declared_tier is not None:
    _req_enum(declared_tier, TIERS, "integrity.tier")
# Validation state is determined by the validator, never
# self-declared: inbound messages must carry PENDING.
if integ["status"] != "PENDING":
    raise ProtocolError(
        "inbound integrity.status must be PENDING; validation "
        "state is determined by the validator, never self-declared")
# v2.0.2: inbound audit history is stripped, not trusted. The old
# comment claimed forged violations/audit_chain "must not survive
# validation" but the code only type-checked them — forged entries
# survived in the mutated object. Now they are dropped outright;
# only validator-emitted violations (below) and receipts exist.
if "violations" in integ or "audit_chain" in integ:
    integ.pop("violations", None)
    integ.pop("audit_chain", None)
    checks.append("audit_history:stripped")
# v2.0.4: with no epistemic_context (working tier), the integrity
# registry fields are checked against the LOCAL policy — the only
# registry reference available.
ref_hash = ctx["axiom_set_hash"] if ctx is not None \
    else policy.axiom_set_hash
ref_version = ctx["registry_version"] if ctx is not None \
    else policy.registry_version
if integ["axiom_set_hash"] != ref_hash \
        or integ["registry_version"] != ref_version:
    raise ProtocolError("integrity/context registry mismatch")

blank_content = integ["content_hash"] == ""
blank_envelope = integ["envelope_hash"] == ""
if declared_tier == "machine" and (blank_content or blank_envelope):
    raise ProtocolError(
        "integrity.tier 'machine' requires non-empty content_hash "
        "and envelope_hash (sender-computed)")
if declared_tier == "chat" and not (blank_content and blank_envelope):
    raise ProtocolError(
        "integrity.tier 'chat' requires blank content_hash and "
        "envelope_hash; non-empty hashes contradict the chat tier "
        "(declare 'machine' or omit tier)")
if blank_content and blank_envelope:
    effective_tier = "chat"
elif not blank_content and not blank_envelope:
    effective_tier = "machine"
else:
    effective_tier = "mixed"
# v2.0.2: high-stakes deployments can refuse the chat tier outright.
if policy.require_machine_tier and effective_tier != "machine":
    raise ProtocolError(
        "policy require_machine_tier: chat/mixed-tier hashes refused; "
        "resubmit with sender-computed hashes and tier 'machine'")
checks.append(
    f"tier:{effective_tier}"
```

```
    + ("-declared" if declared_tier else "-inferred"))

computed_content = digest(payload["content"])
if blank_content:
    integ["content_hash"] = computed_content
    checks.append("content_hash:computed-locally")
elif computed_content != integ["content_hash"]:
    raise ProtocolError(
        "content hash mismatch (sender-supplied "
        f"{integ['content_hash'][:16]}… != recomputed "
        f"{computed_content[:16]}…): tampered content or forged hash. "
        "If you are a chat AI, you cannot compute SHA-256 — leave "
        "content_hash as \"\" and the validator computes it; "
        "invented hex is always rejected.")
else:
    checks.append("content_hash:verified")
computed_envelope = object_digest(envelope_for_hash(message))
if blank_envelope:
    integ["envelope_hash"] = computed_envelope
    checks.append("envelope_hash:computed-locally")
elif computed_envelope != integ["envelope_hash"]:
    raise ProtocolError(
        "envelope hash mismatch (sender-supplied "
        f"{integ['envelope_hash'][:16]}… != recomputed "
        f"{computed_envelope[:16]}…): tampered header/context or "
        "forged hash. Chat AIs: leave envelope_hash as \"\" and the "
        "validator computes it; invented hex is always rejected.")
else:
    checks.append("envelope_hash:verified")

violations: list[dict] = []
# v2.0.4: lexical findings are tracked separately from enforcing
# violations. On the working tier the firewall is ADVISORY (D1):
# findings become firewall_warnings, never rejections. The
# archival tier stays enforcing.
lex_findings: list[dict] = []

def _scan_free(value, label: str) -&gt; list[str]:
    # v2.0.4 RT-001 fail-closed: a depth-bound breach becomes a
    # dedicated violation code, never a silent truncation.
    try:
        return _free_texts(value)
    except DepthBoundExceeded as exc:
        lex_findings.append({
            "code": "FREE_TEXT_DEPTH_EXCEEDED",
            "field": label,
            "detail": str(exc),
        })
        return []

if policy.enforce_lexical_policy:
    texts = [payload["content"]]
    if tlr:
        texts.extend(tlr.values())
    # v2.0.2: scope_notes is free text and was previously hashed but
    # never scanned — a banned term smuggled there passed silently.
    if ctx is not None and ctx.get("scope_notes"):
        texts.append(ctx["scope_notes"])
    # v2.0.3/v2.0.4: the known free-text channels are scanned:
    # content, three_line_register values, scope_notes,
    # falsification, metadata, formal_assertions, dependencies,
    # disagreement, confrontation, provenance.depends_on,
    # bridge_descriptions, determinism.note, session_id.
    # Deliberately NOT scanned: sender_agent/target_agent and other
    # identifier-shaped header fields (identity is not_established;
    # scanning names invites false positives).
    # KNOWN UNSCANNED (v2.0.4 loop, held for the author's ruling):
    # provenance.inherited_from, provenance.theorem_id,
    # bridge_levels[].from/.to, and dict KEYS inside
    # _free_texts-walked trees. Named here, not hidden — the
    # firewall is a floor, not a ceiling (D6).
    # v2.0.4: DISAGREEMENT and CONFRONTATION records are free-text
    # channels too — scanned with the same fail-closed depth rule.
    # v2.0.4 (held item): provenance.depends_on and
    # bridge_descriptions are free-text channels as well — a
    # banned term rides in a dependency label as easily as in a
    # statement.
    for _field in ("falsification", "metadata", "formal_assertions",
                   "dependencies", "disagreement", "confrontation"):
        texts.extend(_scan_free(payload.get(_field), _field))
```

```
            texts.extend(_scan_free(prov.get("depends_on"),
                                    "provenance.depends_on"))
            texts.extend(_scan_free(
                [b.get("bridge_description") for b in bridges
                 if isinstance(b, dict)],
                "bridge_levels.bridge_description"))
            det_note = payload["determinism"].get("note")
            if det_note:
                texts.append(det_note)
            if ctx is not None and ctx.get("session_id"):
                texts.append(ctx["session_id"])
            for text in texts:
                lex_findings.extend(lexical_check(text, policy))
            checks.append(
                "lexical" if tier == "archival" else "lexical:advisory")

        if payload["format"] == "EXECUTABLE_PYTHON":
            violations.extend(
                python_static_check(payload["content"], badge, policy))
            checks.append("arithmetic")

        # v2.0.4 D1 advisory mode: working-tier lexical findings ride on
        # the result as warnings. Code-safety findings (the
        # EXECUTABLE_PYTHON static check) stay enforcing on both tiers —
        # advisory covers vocabulary, never code execution.
        firewall_warnings: list[dict] = []
        if tier == "working":
            firewall_warnings = lex_findings
        else:
            violations.extend(lex_findings)

        if violations:
            return {"ok": False, "status": "REJECTED",
                    "error": "policy violations: "
                    + canonical(violations)[:2000],
                    "violations": violations,
                    "checks": checks,
                    "not_established": NOT_ESTABLISHED}

        if not checks:
            # Internal bug guard: a VALIDATED badge with an empty checks
            # list must never ship.
            return rejected("internal error: empty checks list on success")

        return {"ok": True, "status": "VALIDATED",
                "message_id": header["message_id"],
                "content_hash": integ["content_hash"],
                "envelope_hash": integ["envelope_hash"],
                "checks": checks,
                # v2.0.4 D1: working-tier advisory firewall findings.
                # Empty on the archival tier (findings there reject).
                "firewall_warnings": firewall_warnings,
                "not_established": NOT_ESTABLISHED}
    except ProtocolError as exc:
        return rejected(str(exc))
    except Exception as exc:
        # Never crash on malformed input: every failure mode is REJECTED.
        # (Exception, not a narrower tuple: hostile dict subclasses and
        # exotic objects must not escape the validator. BaseException
        # subclasses like KeyboardInterrupt/SystemExit still propagate.)
        return rejected(f"validation error: {type(exc).__name__}: {exc}")


# ---------------------------------------------------------------------------
# Audit receipts
# ---------------------------------------------------------------------------

def emit_audit_receipt(agent: str, payload_hash: str, result: str,
                       notes: str = "") -&gt; dict:
    """Co-sign a validation outcome. Receipts are attestations, not proofs."""
    if not isinstance(agent, str) or not agent.strip():
        raise ValueError("agent must be a non-empty string")
    if not isinstance(payload_hash, str) \
            or not HASH_RE.fullmatch(payload_hash):
        raise ValueError("payload_hash must be a lowercase SHA-256 hex")
    if result not in RECEIPT_RESULTS:
        raise ValueError(f"result must be one of {sorted(RECEIPT_RESULTS)}")
    return {"agent": agent, "payload_hash": payload_hash, "result": result,
            "timestamp": now(), "notes": notes}
# ---------------------------------------------------------------------------
```

```
# v1.0 -&gt; v2.0 migration
# ---------------------------------------------------------------------------

def migrate_v1_to_v2(v1msg: dict) -&gt; dict:
    """Convert an ESP v1.0 envelope to v2.0.

    Field renames: axiom_registry_hash -&gt; axiom_set_hash (context and
    integrity), protocol.version 1.0 -&gt; 2.0, header protocol_version /
    min_protocol_version -&gt; 2.0. Hashes are recomputed; status reset to
    PENDING (migration does not validate).
    Grok-v4 payloads are envelope-incompatible: no auto-migration.

    Raises ValueError on any malformed input (never KeyError/TypeError/
    AttributeError/RecursionError).
    """
    if not isinstance(v1msg, dict):
        raise ValueError("v1 message must be a dict")
    for key in ("protocol", "header", "epistemic_context", "payload",
                "integrity"):
        if key not in v1msg:
            raise ValueError(f"v1 message missing top-level key: {key}")
        if not isinstance(v1msg[key], dict):
            raise ValueError(f"v1 message: '{key}' must be an object")
    try:
        msg = json.loads(canonical(v1msg))
    except (ValueError, TypeError, RecursionError) as exc:
        raise ValueError(f"v1 message not serializable: {exc}") from exc
    ctx = msg.get("epistemic_context", {})
    if "axiom_registry_hash" in ctx:
        ctx["axiom_set_hash"] = ctx.pop("axiom_registry_hash")
    integ = msg.get("integrity", {})
    if "axiom_registry_hash" in integ:
        integ["axiom_set_hash"] = integ.pop("axiom_registry_hash")
    if isinstance(msg.get("protocol"), dict):
        msg["protocol"]["version"] = VERSION
    header = msg.get("header", {})
    header["protocol_version"] = VERSION
    header["min_protocol_version"] = VERSION
    # v2.0.4: migrated envelopes land on the archival tier (full context
    # is what migration preserves).
    msg["envelope_tier"] = "archival"
    payload = msg.get("payload", {})
    if isinstance(payload, dict) and isinstance(payload.get("content"), str):
        integ["content_hash"] = digest(payload["content"])
    integ["envelope_hash"] = object_digest(envelope_for_hash(msg))
    integ["status"] = "PENDING"
    integ["violations"] = []
    integ["audit_chain"] = []
    return msg


# ---------------------------------------------------------------------------
# Chunk protocol (ESP-CHUNK-2)
# ---------------------------------------------------------------------------

def chunk_text(text: str, max_chars: int = 12000,
               max_chunks: int = 10000) -&gt; list[dict]:
    """Split text into indexed chunks with per-chunk and whole-text hashes."""
    if not isinstance(text, str) or not text:
        raise ProtocolError("cannot chunk empty or non-text input")
    if isinstance(max_chars, bool) or not isinstance(max_chars, int):
        raise ProtocolError("max_chars must be an integer")
    if isinstance(max_chunks, bool) or not isinstance(max_chunks, int):
        raise ProtocolError("max_chunks must be an integer")
    if max_chars &lt; 256:
        raise ProtocolError("max_chars must be &gt;= 256")
    parts = [text[i:i + max_chars]
             for i in range(0, len(text), max_chars)]
    if len(parts) &gt; max_chunks:
        raise ProtocolError("chunk count exceeds limit")
    transfer_id = str(uuid.uuid4())
    whole = digest(text)
    return [{"transfer_protocol": CHUNK_PROTOCOL,
             "transfer_id": transfer_id,
             "index": i, "count": len(parts),
             "full_text_sha256": whole,
             "chunk_sha256": digest(part),
             "data": part}
            for i, part in enumerate(parts)]
def reassemble(chunks: list[dict], max_chunks: int = 10000) -&gt; str:
```

```
    """Reassemble only a complete, consistent, hash-valid chunk set."""
    if not isinstance(chunks, list) or not chunks:
        raise ProtocolError("empty, invalid, or oversized chunk set")
    if isinstance(max_chunks, bool) or not isinstance(max_chunks, int):
        raise ProtocolError("max_chunks must be an integer")
    if len(chunks) &gt; max_chunks:
        raise ProtocolError("oversized chunk set")
    if any(not isinstance(c, dict) for c in chunks):
        raise ProtocolError("each chunk must be an object")
    if any(c.get("transfer_protocol") != CHUNK_PROTOCOL for c in chunks):
        raise ProtocolError("unsupported chunk protocol")
    try:
        tids = {c["transfer_id"] for c in chunks}
        counts = {c["count"] for c in chunks}
        wholes = {c["full_text_sha256"] for c in chunks}
    except KeyError as exc:
        raise ProtocolError(f"chunk missing required field: {exc}") from exc
    except TypeError as exc:
        raise ProtocolError(
            f"chunk field unhashable or of wrong type: {exc}") from exc
    if len(tids) != 1 or len(counts) != 1 or len(wholes) != 1:
        raise ProtocolError("mixed transfers")
    transfer_id = next(iter(tids))
    _req_uuid(transfer_id, "transfer_id")
    _req_sha(next(iter(wholes)), "full_text_sha256")
    count = next(iter(counts))
    if isinstance(count, bool) or not isinstance(count, int) \
            or count != len(chunks):
        raise ProtocolError("missing or duplicate chunks")
    by_index: dict[int, str] = {}
    for c in chunks:
        i = c.get("index")
        if isinstance(i, bool) or not isinstance(i, int) \
                or not 0 &lt;= i &lt; count or i in by_index:
            raise ProtocolError("invalid or duplicate chunk index")
        data = c.get("data")
        if not isinstance(data, str):
            raise ProtocolError(f"chunk {i} data must be text")
        _req_sha(c.get("chunk_sha256"), f"chunk {i} hash")
        if digest(data) != c["chunk_sha256"]:
            raise ProtocolError(f"chunk {i} hash mismatch")
        by_index[i] = data
    if set(by_index) != set(range(count)):
        raise ProtocolError("chunk gap")
    text = "".join(by_index[i] for i in range(count))
    if digest(text) != next(iter(wholes)):
        raise ProtocolError("full-text hash mismatch")
    return text


# ---------------------------------------------------------------------------
# Engine (externalized canon via constructor)
# ---------------------------------------------------------------------------

class Engine:
    """Unified ESP v2.2 engine. The canon (banned terms, markers, axiom
    universe, module policy) is injected via Policy at construction."""

    def __init__(self, policy: Policy | None = None, **canon_overrides):
        if policy is None:
            policy = Policy(**canon_overrides) if canon_overrides else None
            if policy is None:
                raise ValueError(
                    "an explicit Policy is required; use "
                    "Policy(demo_registry=True) for the declared demo "
                    "registry, Policy(insecure_demo_registry=True) for the "
                    "zero-hash placeholder, or configure a real registry")
        self.policy = policy

    def make_message(self, **kwargs) -&gt; dict:
        return make_message(policy=self.policy, **kwargs)

    def validate(self, message) -&gt; dict:
        return validate_message(message, self.policy)

    @staticmethod
    def receipt(agent: str, payload_hash: str, result: str,
                notes: str = "") -&gt; dict:
        return emit_audit_receipt(agent, payload_hash, result, notes)
```

```
    def migrate_v1(self, v1msg: dict) -&gt; dict:
        return migrate_v1_to_v2(v1msg)


# ---------------------------------------------------------------------------
# Minimal CLI
# ---------------------------------------------------------------------------

def _selftest() -&gt; int:
    policy = Policy(axiom_set_hash=ZERO_HASH, insecure_demo_registry=True)
    engine = Engine(policy)
    msg = engine.make_message(
        sender="agent_A", target="agent_B", register="STAGE_P",
        badge="LEVEL_B", content="A conditional inherited claim.",
        lineage="inherited", inherited_from="Paper 10 theorem T-10",
        falsifiers=[{"id": "C1",
                     "statement": "Reject if the cited theorem is absent."}])
    result = engine.validate(msg)
    assert result["ok"] and result["checks"], result
    tampered = json.loads(canonical(msg))
    tampered["payload"]["content"] += " altered"
    assert not engine.validate(tampered)["ok"]
    serialized = canonical(msg)
    assert reassemble(chunk_text(serialized, 300)) == serialized
    print("SELFTEST PASS")
    return 0


def main(argv=None) -&gt; int:
    parser = argparse.ArgumentParser(description="ESP v2.2 engine")
    sub = parser.add_subparsers(dest="command", required=True)
    sub.add_parser("selftest")
    args = parser.parse_args(argv)
    if args.command == "selftest":
        return _selftest()
    return 2


if __name__ == "__main__":
    raise SystemExit(main())
```