Assignment 1: Report

Martina Carminati, Sanna Plomp, Keval Mehta

November 5, 2026

1 Learning the Basics of PyTorch

1.1 MLP

Started with a baseline model with hidden_size = 256, dropout = 0.2, optimizer = SGD, and learning_rate = 0.01. Used a batch of 64 and 10 epochs. Here, we varied the activation layers. Tried out ReLU, LeakyReLU, and GELU. Using a 90/10 split for training and validation, LeakyReLU resulted in the highest validation accuracy 0.$\bar{9}$018.

Will continue varying the optimizers, using LeakyReLU as the activation function. Tried out SGD, Adam, and AdamW. Again using a 90/10 split for training and validation, AdamW resulted in the highest validation accuracy 0.8650.

Tried out learning rate [0.001, 0.01, 0.1]. Learning rate 0.$\bar{0}$1 resulted in the highest validation accuracy of 0.9025.

Tried out hidden sizes of 128, 256, and 512. Hidden size of 128 was the best, with a validation accuracy of 0.8722.

Tried out dropout values of 0.0, 0.2, and 0.5. Dropout 0.$\bar{0}$ resulted in the highest validation accuracy of 0.8788.

1.2 Convolutional Neural Networks

We started by setting seeds for reproducibility, and then importing the MNIST dataset from `torchvision.datasets`. After importing the train and test separately, we split the training dataset into two subsets: what we will use for training (90%), and validation (10%). Setting batch size to 64, we created data loaders that will then load the data into the models.

We set up a basic convolutional neural network, similar to the one depicted in Figure 1, with two convolutional layers and max pooling between, with a customisable activation function.

Defining functions for training, validating, and testing, we then moved to the systematic testing of parameters.

We tested different activation functions:

ReLU

$$f(x) = \begin{cases} x & x \geqslant 0 \\ 0 & \text{otherwise} \end{cases}.$$

Leaky ReLU

$$f(x) = \begin{cases} x & x \geqslant 0 \\ mx & \text{otherwise} \end{cases}.$$




Figure 1: Sample Convolutional Neural Network

GeLU

$$f(x) = x \cdot \Phi(x).$$

We performed this testing with 10 epochs for training, and 5 for validation, which saved the state of the best model to a directory. The test performance of that model was then calculated. The performance of the different activation functions is given in Table 1.

Activation	Optimiser	Validation Accuracy
ReLU	SGD	
Leaky ReLU	SGD	
GELU	SGD	

Table 1: Performance on validation dataset by different activation functions

As we can see in the table, ReLU performed best, so we will use it to fit the rest.
From Table 2, we can see Adam with L2-regularisation does best, so we will use that.

Activation	Optimiser	Validation Accuracy
ReLU	SGD(lr= 0.001, momentum= 0.9)	
ReLU	SGD(lr= 0.005, momentum= 0.7)	
ReLU	Adam(lr= 0.003, betas= (0.9, 0.995))	
ReLU	Adam(lr= 0.0001, weight_decay= 10^{-5})	
ReLU	AdamW	

Table 2: Performance on validation dataset by different optimisers