

Support Vector Machines


CMT307 Session 5

Yuhua Li

liy180@cardiff.ac.uk

Support Vector Machines


- Linear classifiers for binary classes



$$f(x, w, b) = \text{sign}(w \cdot x + b)$$





$$1.5x_1 - x_2 - 0.1 = 0$$

$$w = (1.5, -1), \quad b = -0.1$$



For a point $(-0.8, 1)$, $\text{sign}(1.5 \cdot (-0.8) - 1 - 0.1) = \text{sign}(-2.3) = -1$

For a point $(0.1, -2)$, $\text{sign}(1.5 \cdot 0.1 - (-2) - 0.1) = \text{sign}(2.05) = +1$



Support Vector Machines


- As the 2-d example shown on previous slide, the two classes can be separated by different lines.
- The points nearest to the separation/decision line (or plane in 3-d or **hyperplane** in higher dimension) define the **margin**(i.e., gap) between classes.
- Those points are called **support vectors**.
- Support vector machine aims to maximise the margin.

Maximum Margin: Formalization

- \mathbf{w} : decision hyperplane normal vector
- \mathbf{x}_i : data point i
- y_i : class of data point i (+1 or -1) **NB: Not 1/0**
- Classifier is: $f(\mathbf{x}_i) = \text{sign}(\mathbf{w}^T \mathbf{x}_i + b)$
- Functional margin of \mathbf{x}_i is: $y_i(\mathbf{w}^T \mathbf{x}_i + b)$
 - But note that we can increase this margin simply by scaling \mathbf{w} , b
- Functional margin of dataset is **twice** the minimum functional margin for any point
 - The factor of 2 comes from measuring the whole width of the margin

Geometric Margin

- Distance from example to the separator is $r = y \frac{\mathbf{w}^T \mathbf{x} + b}{\|\mathbf{w}\|}$
- Examples closest to the hyperplane are **support vectors**.
- Margin** ρ of the separator is the width of separation between support vectors of classes.



Derivation of finding r :

Dotted line $\mathbf{x}' - \mathbf{x}$ is perpendicular to decision boundary so parallel to \mathbf{w} .

Unit vector is $\mathbf{w}/\|\mathbf{w}\|$, so line is $r \mathbf{w}/\|\mathbf{w}\|$.

$$\mathbf{x}' = \mathbf{x} - yr\mathbf{w}/\|\mathbf{w}\|.$$

\mathbf{x}' satisfies $\mathbf{w}^T \mathbf{x}' + b = 0$.


$$\text{So } \mathbf{w}^T(\mathbf{x} - yr\mathbf{w}/\|\mathbf{w}\|) + b = 0$$

Recall that $\|\mathbf{w}\| = \sqrt{\mathbf{w}^T \mathbf{w}}$.

$$\text{So } \mathbf{w}^T \mathbf{x} - yr\|\mathbf{w}\| + b = 0$$

So, solving for r gives:

$$r = y(\mathbf{w}^T \mathbf{x} + b)/\|\mathbf{w}\|$$



Linear SVM Mathematically

The linearly separable case

Sec 1.5

- Assume that all data is at least distance 1 from the hyperplane, then the following two constraints follow for a training set $\{(\mathbf{x}_i, y_i)\}$

$$\mathbf{w}^T \mathbf{x}_i + b \geq 1 \quad \text{if } y_i = 1$$

$$\mathbf{w}^T \mathbf{x}_i + b \leq -1 \quad \text{if } y_i = -1$$

- For support vectors, the inequality becomes an equality
- Then, since each example's distance from the hyperplane is

$$r = y \frac{\mathbf{w}^T \mathbf{x} + b}{\|\mathbf{w}\|}$$

- The margin is:

$$r = \frac{2}{\|\mathbf{w}\|}$$

Linear Support Vector Machine (SVM)

- **Hyperplane**

$$\mathbf{w}^T \mathbf{x} + b = 0$$


- **Extra scale constraint:**

$$\min_{i=1,\dots,n} |\mathbf{w}^T \mathbf{x}_i + b| = 1$$

- This implies:

$$\mathbf{w}^T (\mathbf{x}_a - \mathbf{x}_b) = 2$$

$$\rho = \|\mathbf{x}_a - \mathbf{x}_b\|_2 = 2/\|\mathbf{w}\|_2$$



Linear SVMs Mathematically (cont.)

- Then we can formulate the *quadratic optimization problem*:

Find \mathbf{w} and b such that

$$r = \frac{2}{\|\mathbf{w}\|} \quad \text{is maximized; and for all } \{(\mathbf{x}_i, y_i)\}$$
$$\mathbf{w}^T \mathbf{x}_i + b \geq 1 \text{ if } y_i = 1; \quad \mathbf{w}^T \mathbf{x}_i + b \leq -1 \text{ if } y_i = -1$$

- A better formulation ($\min \|\mathbf{w}\| = \max 1/\|\mathbf{w}\|$):

Find \mathbf{w} and b such that

$$L(\mathbf{w}) = \frac{1}{2} \mathbf{w}^T \mathbf{w} \quad \text{is minimized;}$$

$$\text{and for all } \{(\mathbf{x}_i, y_i)\}: \quad y_i (\mathbf{w}^T \mathbf{x}_i + b) \geq 1$$

Solving the Optimization Problem

Find \mathbf{w} and b such that

$L(\mathbf{w}) = \frac{1}{2} \mathbf{w}^T \mathbf{w}$ is minimized;

and for all $\{(\mathbf{x}_i, y_i)\}$: $y_i (\mathbf{w}^T \mathbf{x}_i + b) \geq 1$

- This is now optimizing a *quadratic* function subject to *linear* constraints
- Quadratic optimization problems are a well-known class of mathematical programming problem, and many (intricate) algorithms exist for solving them (with many special ones built for SVMs)
- The solution involves constructing a *dual problem* where a *Lagrange multiplier* α_i is associated with every constraint in the primary problem:

Find $\alpha_1 \dots \alpha_N$ such that

$Q(\boldsymbol{\alpha}) = \sum \alpha_i - \frac{1}{2} \sum \sum \alpha_i \alpha_j y_i y_j \mathbf{x}_i^T \mathbf{x}_j$ is maximized and

(1) $\sum \alpha_i y_i = 0$

(2) $\alpha_i \geq 0$ for all α_i

The Optimization Problem Solution

- The solution has the form:

$$\mathbf{w} = \sum \alpha_i y_i \mathbf{x}_i \quad b = y_k - \mathbf{w}^T \mathbf{x}_k \text{ for any } \mathbf{x}_k \text{ such that } \alpha_k \neq 0$$


- Each non-zero α_i indicates that corresponding \mathbf{x}_i is a support vector.
- Then the classifying function will have the form:

$$f(\mathbf{x}) = \sum \alpha_i y_i \mathbf{x}_i^T \mathbf{x} + b$$

- Notice that it relies on an *inner product* between the test point \mathbf{x} and the support vectors \mathbf{x}_i
 - We will return to this later.
- Also keep in mind that solving the optimization problem involved computing the inner products $\mathbf{x}_i^T \mathbf{x}_j$ between all pairs of training points.

Soft Margin Classification

- If the training data is not linearly separable, *slack variables* ξ_i can be added to allow misclassification of difficult or noisy examples.
- Allow some errors
 - Let some points be moved to where they belong, at a cost
- Still, try to minimize training set errors, and to place hyperplane “far” from each class (large margin)



Soft Margin Classification Mathematically

- The old formulation:

Find \mathbf{w} and b such that

$$L(\mathbf{w}) = \frac{1}{2} \mathbf{w}^T \mathbf{w} \text{ is minimized and for all } \{(\mathbf{x}_i, y_i)\}$$

$$y_i (\mathbf{w}^T \mathbf{x}_i + b) \geq 1$$

- The new formulation incorporating slack variables:

Find \mathbf{w} and b such that

$$L(\mathbf{w}) = \frac{1}{2} \mathbf{w}^T \mathbf{w} + C \sum \xi_i \text{ is minimized and for all } \{(\mathbf{x}_i, y_i)\}$$

$$y_i (\mathbf{w}^T \mathbf{x}_i + b) \geq 1 - \xi_i \text{ and } \xi_i \geq 0 \text{ for all } i$$

- Parameter C can be viewed as a way to control overfitting
 - A regularization term

Regularisation

- Support vector machines

- Training SVM involves regularization by default, its strength of regularization is determined by the penalty parameter $C > 0$.

$$\min \quad \frac{1}{2} w^T w + C \sum_{i=1}^N \xi_i$$

- Larger values of C : less regularization
 - Fit the training data as well as possible
 - Each individual data point is important to classify correctly
- Smaller values of C : more regularization
 - More tolerant of errors on individual data points

Soft Margin Classification – Solution

- The dual problem for soft margin classification:

Find $\alpha_1 \dots \alpha_N$ such that

$Q(\boldsymbol{\alpha}) = \sum \alpha_i - \frac{1}{2} \sum \sum \alpha_i \alpha_j y_i y_j \mathbf{x}_i^T \mathbf{x}_j$ is maximized and

(1) $\sum \alpha_i y_i = 0$

(2) $0 \leq \alpha_i \leq C$ for all α_i

- Neither slack variables ξ_i nor their Lagrange multipliers appear in the dual problem!
- Again, \mathbf{x}_i with non-zero α_i will be support vectors.
- Solution to the dual problem is:

$$\mathbf{w} = \sum \alpha_i y_i \mathbf{x}_i$$

$$b = y_k (1 - \xi_k) - \mathbf{w}^T \mathbf{x}_k \text{ where } k = \underset{k'}{\operatorname{argmax}} \alpha_k,$$


\mathbf{w} is not needed explicitly for classification!

$$f(\mathbf{x}) = \sum \alpha_i y_i \mathbf{x}_i^T \mathbf{x} + b$$

Classification with SVMs

- Given a new point \mathbf{x} , we can score its projection onto the hyperplane normal:
 - I.e., compute score: $\mathbf{w}^T \mathbf{x} + b = \sum \alpha_i y_i \mathbf{x}_i^T \mathbf{x} + b$
 - Decide class based on whether $<$ or > 0
 - Can set confidence threshold t .

Score $> t$ yes
Score $< -t$ no
Else: don't know



Linear SVMs: Summary

- The classifier is a *separating hyperplane*.
- The most “important” training points are the support vectors; they define the hyperplane.
- Quadratic optimization algorithms can identify which training points \mathbf{x}_i are support vectors with non-zero Lagrangian multipliers α_i .
- Both in the dual formulation of the problem and in the solution, training points appear only inside inner products:

Find $\alpha_1 \dots \alpha_N$ such that

$Q(\boldsymbol{\alpha}) = \sum \alpha_i - \frac{1}{2} \sum \sigma \alpha_i \alpha_j y_i y_j \mathbf{x}_i^T \mathbf{x}_j$ is maximized and


(1) $\sum \alpha_i y_i = 0$

(2) $0 \leq \alpha_i \leq C$ for all α_i

$$f(\mathbf{x}) = \sum \alpha_i y_i \mathbf{x}_i^T \mathbf{x} + b$$

Non-linear SVMs



- Datasets that are linearly separable (with some noise) work out great:



- But what are we going to do if the dataset is just too hard?




- How about ... mapping data to a higher-dimensional space:



Non-linear SVMs: Feature spaces

- General idea: the original feature space can always be mapped to some higher-dimensional feature space where the training set is separable:



The “Kernel Trick”

- The linear classifier relies on an inner product between vectors $K(\mathbf{x}_i, \mathbf{x}_j) = \mathbf{x}_i^T \mathbf{x}_j$
- If every datapoint is mapped into high-dimensional space via some transformation $\Phi: \mathbf{x} \rightarrow \phi(\mathbf{x})$, the inner product becomes:

$$K(\mathbf{x}_i, \mathbf{x}_j) = \phi(\mathbf{x}_i)^T \phi(\mathbf{x}_j)$$

- A *kernel function* is some function that corresponds to an inner product in some expanded feature space.
- Example:

2-dimensional vectors $\mathbf{x} = [x_1 \ x_2]$; let $K(\mathbf{x}_i, \mathbf{x}_j) = (1 + \mathbf{x}_i^T \mathbf{x}_j)^2$,

Need to show that $K(\mathbf{x}_i, \mathbf{x}_j) = \phi(\mathbf{x}_i)^T \phi(\mathbf{x}_j)$:

$$\begin{aligned} K(\mathbf{x}_i, \mathbf{x}_j) &= (1 + \mathbf{x}_i^T \mathbf{x}_j)^2 = 1 + x_{i1}^2 x_{j1}^2 + 2 x_{i1} x_{j1} x_{i2} x_{j2} + x_{i2}^2 x_{j2}^2 + 2 x_{i1} x_{j1} + 2 x_{i2} x_{j2} \\ &= [1 \ x_{i1}^2 \ \sqrt{2} x_{i1} x_{i2} \ x_{i2}^2 \ \sqrt{2} x_{i1} \ \sqrt{2} x_{i2}]^T [1 \ x_{j1}^2 \ \sqrt{2} x_{j1} x_{j2} \ x_{j2}^2 \ \sqrt{2} x_{j1} \ \sqrt{2} x_{j2}] \\ &= \phi(\mathbf{x}_i)^T \phi(\mathbf{x}_j) \quad \text{where } \phi(\mathbf{x}) = [1 \ x_1^2 \ \sqrt{2} x_1 x_2 \ x_2^2 \ \sqrt{2} x_1 \ \sqrt{2} x_2] \end{aligned}$$

Non-linear SVMs: Feature spaces

- SVM uses a **kernel function** (which is a similarity measure between data points) to map data from input feature space to a higher-dimensional feature space
- Why use kernels?
 - Make non-separable problem separable.
 - Map data into better representational space
- Common kernels
 - Linear $K(\mathbf{x}_i, \mathbf{x}_j) = \mathbf{x}_i^T \mathbf{x}_j$
 - Polynomial $K(\mathbf{x}_i, \mathbf{x}_j) = (1 + \mathbf{x}_i^T \mathbf{x}_j)^d$
 - Radial basis function $K(\mathbf{x}_i, \mathbf{x}_j) = e^{-\frac{\|\mathbf{x}_i - \mathbf{x}_j\|^2}{2\sigma^2}} = e^{-\gamma \|\mathbf{x}_i - \mathbf{x}_j\|^2}$

Reading

- Aurélien Géron. Hands-On Machine Learning with Scikit-Learn and TensorFlow: Concepts, Tools and Techniques to Build Intelligent Systems. O'Reilly, 2017.
Chapter 5, Appendix C for a rudimentary introduction.
- Christopher Bishop. Pattern Recognition and Machine Learning. Springer 2006.
<https://www.microsoft.com/en-us/research/uploads/prod/2006/01/Bishop-Pattern-Recognition-and-Machine-Learning-2006.pdf>
Section 7.1 for a more rigorous introduction.