

Methods

We kindly ask to report results preprocessed with this tool using the following boilerplate.

Arterial Spin-Labeled MRI Preprocessing and Cerebral Blood Flow Computation

Arterial spin-labeled MRI images were preprocessed using *ASLPrep* 0.2.7beta, which is based on *Nipype* 1.6.1 (Gorgolewski et al. 2011).

Anatomical data preprocessing

sMRIPrep 0.6.1 was used to process the anatomical data. A total of 1 T1-weighted (T1w) image was found within the input BIDS dataset. The T1-weighted (T1w) image was corrected for intensity non-uniformity (INU) with **N4BiasFieldCorrection** (Tustison et al. 2010), which is distributed with *ANTs* 2.3.1 (Avants et al. 2008). *sMRIPrep* uses this T1w reference throughout the workflow. The T1w-reference was then skull-stripped with a *Nipype* implementation of the **antsBrainExtraction.sh** workflow using OASIS3oANTs as the target template. Brain tissue segmentation of cerebrospinal fluid (CSF), white-matter (WM) and gray-matter (GM) was performed on the brain-extracted T1w reference image using *FSL*'s **FAST** (Zhang, Brady, and Smith 2001). Nonlinear registration of the brain-extracted T1w reference image to the brain-extracted template was accomplished using **antsRegistration**. The following template was selected for spatial normalization: *ICBM 152 Nonlinear Asymmetrical template version 2009c* (Fonov et al. 2011),

ASL data preprocessing

For the 1 ASL run found per subject (across all tasks and sessions), the following preprocessing was performed. First, the middle volume of the ASL timeseries was selected as the reference volume and brain extracted using *Nipype*'s custom brain extraction workflow. Head-motion parameters were estimated using *FSL*'s **mcflirt** (Jenkinson et al. 2002). Next, ASLPrep wrote head-motion parameters to the ASL run's confound file.

Susceptibility distortion correction (SDC) was omitted. ASLPrep co-registered the ASL reference to the T1w reference using *FSL*'s **flirt** (Jenkinson and Smith 2001), which implemented the boundary-based registration cost-function (Greve and Fischl 2009). Co-registration used 6 degrees of freedom. The quality of co-registration and normalization to template was quantified using the Dice and Jaccard indices, the cross-correlation with the reference image, and the overlap between the ASL and reference images (e.g., image coverage). Several confounding timeseries were calculated, including both framewise displacement (FD) and DVARS. FD and DVARS are calculated using the implementations in *Nipype* (following the definition by (Power et al. 2014)) for each ASL run. ASLPrep summarizes in-scanner motion as the mean framewise displacement and relative root-mean square displacement.

Cerebral blood flow computation and denoising

ASLPrep was configured to calculate cerebral blood flow (CBF) using the following methods.

The cerebral blood flow (CBF) was quantified from preprocessed ASL data using a general kinetic model (Detre et al. 1992; Alsop et al. 2015).

Structural Correlation based Outlier Rejection (SCORE) algorithm was applied to the CBF timeseries to discard CBF volumes with outlying values (Dolui et al. 2017) before computing the mean CBF. Following SCORE, the Structural Correlation with RobUst Bayesian (SCRUB) algorithm was applied to the CBF maps using structural tissue probability maps to reweight the mean CBF (Dolui et al. 2017; Dolui, Wolk, et al. 2016).

CBF was also computed with Bayesian Inference for Arterial Spin Labeling (BASIL) (Chappell et al. 2009), as implemented in *FSL* 6.0.3. BASIL computes CBF using a spatial regularization of the estimated perfusion image and additionally calculates a partial-volume corrected CBF image (Chappell et al. 2011). For each CBF map, the ROIs for the following atlases were extracted: the Harvard-Oxford and the Schaefer 200 and 400-parcel resolution atlases.

The Quality evaluation index (QEI) was computed for each CBF map (Dolui, Wolf, et al. 2016). QEI is based on the similarity between the CBF and the structural images, the spatial variability of the CBF image, and the percentage of grey matter voxels containing negative CBF values.

All resampling in *ASLPrep* uses a single interpolation step that concatenates all transformations. Gridded (volumetric) resampling was performed using **antsApplyTransforms**, configured with *Lanczos* interpolation to minimize the smoothing effects of other kernels (Lanczos 1964). Many internal operations of *ASLPrep* use *Nilearn* 0.8.0 (Abraham et al. 2014), *NumPy* (Harris et al. 2020), and *SciPy* (Virtanen et al. 2020). For more details of the pipeline, see [the ASLPrep documentation](#).

Copyright Waiver

The above methods description was automatically generated by *ASLPrep* with the express intention that users should copy and paste this text into their manuscripts unchanged. It is released under the unchanged [CCo](#) license.

References

- Abraham, Alexandre, Fabian Pedregosa, Michael Eickenberg, Philippe Gervais, Andreas Mueller, Jean Kossaifi, Alexandre Gramfort, Bertrand Thirion, and Gael Varoquaux. 2014. "Machine Learning for Neuroimaging with Scikit-Learn." *Frontiers in Neuroinformatics* 8. <https://doi.org/10.3389/fninf.2014.00014>.
- Alsop, David C., John A. Detre, Xavier Golay, Matthias Günther, Jeroen Hendrikse, Luis Hernandez-Garcia, Hanzhang Lu, et al. 2015. "Recommended Implementation of Arterial Spin Labeled Perfusion MRI for Clinical Applications: A Consensus of the ISMRM Perfusion Study Group and the European Consortium for Asl in Dementia." *Magnetic Resonance in Medicine*, no. 1. <https://doi.org/10.1002/mrm.25197>.
- Avants, B. B., C. L. Epstein, M. Grossman, and J. C. Gee. 2008. "Symmetric Diffeomorphic Image Registration with Cross-Correlation: Evaluating Automated Labeling of Elderly and Neurodegenerative Brain." *Medical Image Analysis* 12 (1): 26–41. <https://doi.org/10.1016/j.media.2007.06.004>.
- Chappell, M. A., A. R. Groves, B. J. MacIntosh, M. J. Donahue, P. Jezzard, and M. W. Woolrich. 2011. "Partial Volume Correction of Multiple Inversion Time Arterial Spin Labeling MRI Data." *Magnetic Resonance in Medicine* 65 (4). <https://doi.org/10.1002/mrm.22641>.
- Chappell, Michael A., Adrian R. Groves, Brandon Whitcher, and Mark W. Woolrich. 2009. "Variational Bayesian Inference for a Nonlinear Forward Model." *IEEE Transactions on Signal Processing* 57 (1). <https://doi.org/10.1109/TSP.2008.2005752>.
- Detre, John A., John S. Leigh, Donald S. Williams, and Alan P. Koretsky. 1992. "Perfusion Imaging." *Magnetic Resonance in Medicine* 23 (1). <https://doi.org/10.1002/mrm.1910230106>.
- Dolui, Sudipto, Ze Wang, Russell T. Shinohara, David A. Wolk, John A. Detre, and for the Alzheimer's Disease Neuroimaging Initiative. 2017. "Structural Correlation-Based Outlier Rejection (SCORE) Algorithm for Arterial Spin Labeling Time Series: SCORE: Denoising Algorithm for ASL." *Journal of Magnetic Resonance Imaging* 45 (6): 1786–97. <https://doi.org/10.1002/jmri.25436>.
- Dolui, Sudipto, Ronald Wolf, Seyed Ali Nabavizadeh, David A. Wolk, and John A. Detre. 2016. "Automated Quality Evaluation Index for 2D Asl Cbf Maps." *International Society for Magnetic Resonance in Medicine*, no. 1. <https://doi.org/http://indexsmart.mirasmart.com/ISMRM2017/PDFfiles/0682.html>.
- Dolui, Sudipto, David A. Wolk, David A. Wolk, and John A. Detre. 2016. "SCRUB: A Structural Correlation and Empirical Robust Bayesian Method for Asl Data." *International Society for Magnetic Resonance in Medicine*, no. 1. <https://doi.org/http://archive.ismrm.org/2016/2880.html>.
- Fonov, Vladimir, Alan C. Evans, Kelly Botteron, C. Robert Almli, Robert C. McKinsty, and D. Louis Collins. 2011. "Unbiased Average Age-Appropriate Atlases for Pediatric Studies." *NeuroImage* 54 (1): 313–27. <https://doi.org/10.1016/j.neuroimage.2010.07.033>.
- Gorgolewski, Krzysztof, Christopher D. Burns, Cindee Madison, Dav Clark, Yaroslav O. Halchenko, Michael L. Waskom, and Satrajit S. Ghosh. 2011. "Nipype: A Flexible, Lightweight and Extensible Neuroimaging Data Processing Framework in Python." *Frontiers in Neuroinformatics* 5. <https://doi.org/10.3389/fninf.2011.00013>.
- Greve, Douglas N., and Bruce Fischl. 2009. "Accurate and Robust Brain Image Alignment Using Boundary-Based Registration." *NeuroImage* 48 (1): 63–72. <https://doi.org/10.1016/j.neuroimage.2009.06.060>.
- Harris, Charles R., Jarrod K. Millman, Stéfan J. van der Walt, Ralf Gommers, Pauli Virtanen, David Cournapeau, Eric Wieser, et al. 2020. "Array Programming with NumPy." *Nature* 585 (7825): 357–62. <https://doi.org/10.1038/s41586-020-2649-2>.
- Jenkinson, Mark, Peter Bannister, Michael Brady, and Stephen Smith. 2002. "Improved Optimization for the Robust and Accurate Linear Registration and Motion Correction of Brain Images." *NeuroImage* 17 (2): 825–41. [https://doi.org/10.1016/s1053-8119\(02\)91132-8](https://doi.org/10.1016/s1053-8119(02)91132-8).
- Jenkinson, Mark, and Stephen Smith. 2001. "A Global Optimisation Method for Robust Affine Registration of Brain Images." *Medical Image Analysis* 5 (2): 143–56. [https://doi.org/10.1016/S1361-8415\(01\)00036-6](https://doi.org/10.1016/S1361-8415(01)00036-6).
- Lanczos, C. 1964. "Evaluation of Noisy Data." *Journal of the Society for Industrial and Applied Mathematics Series B Numerical Analysis* 1 (1): 76–85. <https://doi.org/10.1137/0701007>.
- Power, Jonathan D., Anish Mitra, Timothy O. Laumann, Abraham Z. Snyder, Bradley L. Schlaggar, and Steven E. Petersen. 2014. "Methods to Detect, Characterize, and Remove Motion Artifact in Resting State fMRI." *NeuroImage* 84 (January): 320–41. <https://doi.org/10.1016/j.neuroimage.2013.08.048>.
- Tustison, Nicholas J., Brian B. Avants, Philip A. Cook, Yuanjie Zheng, Alexander Egan, Paul A. Yushkevich, and James C. Gee. 2010. "N4ITK: Improved N3 Bias Correction." *IEEE Transactions on Medical Imaging* 29 (6): 1310–20. <https://doi.org/10.1109/TMI.2010.2046908>.
- Virtanen, Pauli, Ralf Gommers, Travis E. Oliphant, Matt Haberland, Tyler Reddy, David Cournapeau, Evgeni Burovski, et al. 2020. "SciPy 1.0: Fundamental Algorithms for Scientific Computing in Python." *Nature Methods* 17 (3): 261–72. <https://doi.org/10.1038/s41592-019-0686-2>.

Zhang, Y., M. Brady, and S. Smith. 2001. “Segmentation of Brain MR Images Through a Hidden Markov Random Field Model and the Expectation-Maximization Algorithm.” *IEEE Transactions on Medical Imaging* 20 (1): 45–57. <https://doi.org/10.1109/42.906424>.

Errors

No errors to report!