

## **Group 4:**

### **Group Members:**

**1.Zahir Ayub Khan(Group Leader)**

**2.Jamal khan**

**3.Nauman Ali**

**4.Syed Shan E Ali**

## **Table of Contents**

Lab 5 Common Solution .....	2
Zahir Ayub Khan .....	4
Jamal Khan .....	6
Update And Delete Common Solution.....	7
Zahir Ayub Khan .....	10
Jamal Khan .....	12
Lab 6 Common Solution .....	13
Zahir Ayub Khan .....	15
Jamal Khan .....	15
Lab 7 Common Solution .....	16
Zahir Ayub khan .....	18
Jamal Khan .....	18
LAB 8 Common Solution .....	19
Zahir Ayub Khan .....	21
Jamal Khan .....	22
LAB 9 CommonSolution: .....	24
Zahir Ayub Khan:.....	25
Jamal Khan: .....	25
LAB 10 CommonSolution: .....	26
Zahir Ayub Khan:.....	33
Jamal Khan: .....	33
LAB 11 CommonSolution: .....	36

Zahir Ayub Khan: .....	38
Jamal Khan: .....	39
LAB 12 CommonSolution: .....	39
Zahir Ayub Khan: .....	39
Jamal Khan: .....	40
Lab 13 Common Solution      2	
Zahir Ayub Khan .....	4
Jamal Khan .....	6
Lab 14 Common Solution .....	7
Zahir Ayub Khan .....	10
Jamal Khan .....	12
Lab 15 Common Solution .....	13
Zahir Ayub Khan .....	15
Jamal Khan .....	15
Lab 16 Common Solution .....	16
Zahir Ayub khan .....	18
Jamal Khan .....	18
Lab 18 Common Solution .....	16
Zahir Ayub khan .....	18
Jamal Khan .....	18

## Lab 5 Common Solution :

```
create table Student (  
ID nchar(30),  
Name varchar(30),  
);
```

```
create table Transcript (  
Subject nchar(30),  
GPA nchar(30),  
ID nchar(30),  
);
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-001', 'ahmad khan');
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-002', 'Hassan ali');
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-003', 'Bilal Khan');
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-004', 'Rana Noon');
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-005', 'Zoya Yusufzai');
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-006', 'Zain Ahmad');
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-007', 'Ghulam mujtaba');
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-008', 'Hamza ali khan');
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-009', 'Ali Joiya');
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-010', 'Alex markovich');
```

```
INSERT INTO Transcript(Subject,GPA,ID)  
VALUES ('Math', '2.3', 'Sp17-bse-001');
```

```
INSERT INTO Transcript(Subject,GPA,ID)  
VALUES ('English', '3.3', 'Sp17-bse-002');
```

```
INSERT INTO Transcript(Subject,GPA,ID)  
VALUES ('Database system', '2.7', 'Sp17-bse-003');
```

```
INSERT INTO Transcript(Subject,GPA,ID)  
VALUES ('OOP', '3.7', 'Sp17-bse-004');
```

```

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Islamic studies','3.0','Sp17-bse-005');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('CA','2.0','Sp17-bse-006');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Advance OOP','2.7','Sp17-bse-007');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('statistics','2.3','Sp17-bse-008');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Call','2.3','Sp17-bse-009');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('SQE','2.7','Sp17-bse-010');

/* Above work is Zahir Ayub Khan. Work Below Is Jamal Khan*/

```

```

create database StudentTranscriptDB
use StudentTranscriptDB

```

```

create table Student(
StudentId nchar(30),
Name(30))

insert into Student(StudentId,Name) values
('fa20-bcs-001','ali')
insert into Student(StudentId,Name) values
('fa20-bcs-002','Aftab')
insert into Student(StudentId,Name) values
('fa20-bcs-003','Ammar')
insert into Student(StudentId,Name) values
('fa20-bcs-004','Mohsin')
insert into Student(StudentId,Name) values
('fa20-bcs-005','Zubair')
insert into Student(StudentId,Name) values
('fa20-bcs-006','Daniyal')
insert into Student(StudentId,Name) values
('fa20-bcs-007','Usman')
insert into Student(StudentId,Name) values
('fa20-bcs-008','Abbass')
insert into Student(StudentId,Name) values
('fa20-bcs-009','Saddique')
insert into Student(StudentId,Name) values
('fa20-bcs-010','Umar')

```

```

create table Transcript(
CourseName nchar(30),
GPA float(30),
StudentId nchar(30)

```

```
);

insert into Transcript (CourseName,GPA,StudentId) values
('Database Systems','1.3','fa20-bcs-001')
insert into Transcript (CourseName,GPA,StudentId) values
('Database Systems','1.3','fa20-bcs-002')
insert into Transcript (CourseName,GPA,StudentId) values
('Database System','2.7','fa20-bcs-003')
insert into Transcript (CourseName,GPA,StudentId) values
('Database Systems','3.3','fa20-bcs-004')
insert into Transcript (CourseName,GPA,StudentId) values
('Database System','4.0','fa20-bcs-005')
insert into Transcript (CourseName,GPA,StudentId) values
('Operating Systems','2.7','fa20-bcs-006')
insert into Transcript (CourseName,GPA,StudentId) values
('Database Systems','2.0','fa20-bcs-007')
insert into Transcript (CourseName,GPA,StudentId) values
('Database Systems','3.7','fa20-bcs-008')
insert into Transcript (CourseName,GPA,StudentId) values
('Operating Systems','2.5','fa20-bcs-009')
insert into Transcript (CourseName,GPA,StudentId) values
('Database Systems','3.0','fa20-bcs-010')
```

```
Select Count(*) As [Number of std]
FROM [StudentTranscriptDB].[dbo].[Transcript]

Group By CourseName

Select CourseName, AVG(GPA) As [AVG GPA]
FROM [StudentTranscriptDB].[dbo].[Transcript]

Group By CourseName
```

**Zahir Ayub Khan:**

```
create table Student (
ID nchar(30),
Name varchar(30),
);

create table Transcript (
Subject nchar(30),
GPA nchar(30),
ID nchar(30),
);

INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-001', 'ahmad khan');

INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-002', 'Hassan ali');
```

```

INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-003', 'Bilal Khan');

INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-004', 'Rana Noon');

INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-005', 'Zoya Yusufzai');

INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-006', 'Zain Ahmad');

INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-007', 'Ghulam mujtaba');

INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-008', 'Hamza ali khan');

INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-009', 'Ali Joiya');

INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-010', 'Alex markovich');

```

```

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Math', '2.3', 'Sp17-bse-001');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('English', '3.3', 'Sp17-bse-002');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Database system', '2.7', 'Sp17-bse-003');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('OOP', '3.7', 'Sp17-bse-004');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Islamic studies', '3.0', 'Sp17-bse-005');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('CA', '2.0', 'Sp17-bse-006');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Advance OOP', '2.7', 'Sp17-bse-007');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('statistics', '2.3', 'Sp17-bse-008');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Cal1', '2.3', 'Sp17-bse-009');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('SQE', '2.7', 'Sp17-bse-010');

```

Jamal Khan:

```
create database StudentTranscriptDB
use StudentTranscriptDB
```

```
create table Student(
StudentId nchar(30),
Name(30))
```

```
insert into Student(StudentId,Name) values
('fa20-bcs-001','ali')
insert into Student(StudentId,Name) values
('fa20-bcs-002','Aftab')
insert into Student(StudentId,Name) values
('fa20-bcs-003','Ammar')
insert into Student(StudentId,Name) values
('fa20-bcs-004','Mohsin')
insert into Student(StudentId,Name) values
('fa20-bcs-005','Zubair')
insert into Student(StudentId,Name) values
('fa20-bcs-006','Daniyal')
insert into Student(StudentId,Name) values
('fa20-bcs-007','Usman')
insert into Student(StudentId,Name) values
('fa20-bcs-008','Abbass')
insert into Student(StudentId,Name) values
('fa20-bcs-009','Saddique')
insert into Student(StudentId,Name) values
('fa20-bcs-010','Umar')
```

```
create table Transcript(
CourseName nchar(30),
GPA float(30),
StudentId nchar(30)
);
```

```
insert into Transcript (CourseName,GPA,StudentId) values
('Database Systems','1.3','fa20-bcs-001')
insert into Transcript (CourseName,GPA,StudentId) values
('Database Systems','1.3','fa20-bcs-002')
insert into Transcript (CourseName,GPA,StudentId) values
('Database System','2.7','fa20-bcs-003')
insert into Transcript (CourseName,GPA,StudentId) values
('Database Systems','3.3','fa20-bcs-004')
insert into Transcript (CourseName,GPA,StudentId) values
('Database System','4.0','fa20-bcs-005')
insert into Transcript (CourseName,GPA,StudentId) values
('Operating Systems','2.7','fa20-bcs-006')
insert into Transcript (CourseName,GPA,StudentId) values
('Database Systems','2.0','fa20-bcs-007')
insert into Transcript (CourseName,GPA,StudentId) values
('Database Systems','3.7','fa20-bcs-008')
insert into Transcript (CourseName,GPA,StudentId) values
('Operating Systems','2.5','fa20-bcs-009')
insert into Transcript (CourseName,GPA,StudentId) values
```

```
( 'Database Systems', '3.0', 'fa20-bcs-010' )
```

```
Select Count(*) As [Number of std]  
FROM [StudentTranscriptDB].[dbo].[Transcript]
```

```
Group By CourseName
```

```
Select CourseName, AVG(GPA) As [AVG GPA]  
FROM [StudentTranscriptDB].[dbo].[Transcript]
```

```
Group By CourseName
```

## Update And Delete Common Solution:

```
create table Student (  
ID nchar(30),  
Name varchar(30),  
);
```

```
create table Transcript (  
Subject nchar(30),  
GPA nchar(30),  
ID nchar(30),  
);
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-001', 'ahmad khan');
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-002', 'Hassan ali');
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-003', 'Bilal Khan');
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-004', 'Rana Noon');
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-005', 'Zoya Yusufzai');
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-006', 'Zain Ahmad');
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-007', 'Ghulam mujtaba');
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-008', 'Hamza ali khan');
```

```
INSERT INTO Student (ID, Name)  
VALUES ('Sp17-bse-009', 'Ali Joiya');
```



```

INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-010', 'Alex markovich');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Math', '2.3', 'Sp17-bse-001');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('English', '3.3', 'Sp17-bse-002');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Database system', '2.7', 'Sp17-bse-003');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('OOP', '3.7', 'Sp17-bse-004');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Islamic studies', '3.0', 'Sp17-bse-005');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('CA', '2.0', 'Sp17-bse-006');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Advance OOP', '2.7', 'Sp17-bse-007');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('statistics', '2.3', 'Sp17-bse-008');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Call', '2.3', 'Sp17-bse-009');

INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('SQE', '2.7', 'Sp17-bse-010');

UPDATE Transcript
Set GPA='2.7'
WHERE ID='Sp17-bse-001';

UPDATE Transcript
Set GPA='1.7'
WHERE ID='Sp17-bse-006';

UPDATE Transcript
Set GPA='2.3'
WHERE ID='Sp17-bse-010';

DELETE FROM Transcript WHERE ID='Sp17-bse-009';
DELETE FROM Transcript WHERE ID='Sp17-bse-008';

/* Above work is Zahir Ayub Khan. Work Below is Jamal khan*/

create database StudentTranscriptDB
use StudentTranscriptDB

```

```
create table Student(  
StudentId nchar(30),  
Name(30))
```

```
insert into Student(StudentId,Name) values  
( 'fa20-bcs-001', 'ali' )  
insert into Student(StudentId,Name) values  
( 'fa20-bcs-002', 'Aftab' )  
insert into Student(StudentId,Name) values  
( 'fa20-bcs-003', 'Ammar' )  
insert into Student(StudentId,Name) values  
( 'fa20-bcs-004', 'Mohsin' )  
insert into Student(StudentId,Name) values  
( 'fa20-bcs-005', 'Zubair' )  
insert into Student(StudentId,Name) values  
( 'fa20-bcs-006', 'Daniyal' )  
insert into Student(StudentId,Name) values  
( 'fa20-bcs-007', 'Usman' )  
insert into Student(StudentId,Name) values  
( 'fa20-bcs-008', 'Abbass' )  
insert into Student(StudentId,Name) values  
( 'fa20-bcs-009', 'Saddique' )  
insert into Student(StudentId,Name) values  
( 'fa20-bcs-010', 'Umar' )
```

```
create table Transcript(  
CourseName nchar(30),  
GPA float(30),  
StudentId nchar(30)  
);
```

```
insert into Transcript (CourseName,GPA,StudentId) values  
( 'Database Systems', '1.3', 'fa20-bcs-001' )  
insert into Transcript (CourseName,GPA,StudentId) values  
( 'Database Systems', '1.3', 'fa20-bcs-002' )  
insert into Transcript (CourseName,GPA,StudentId) values  
( 'Database System', '2.7', 'fa20-bcs-003' )  
insert into Transcript (CourseName,GPA,StudentId) values  
( 'Database Systems', '3.3', 'fa20-bcs-004' )  
insert into Transcript (CourseName,GPA,StudentId) values  
( 'Database System', '4.0', 'fa20-bcs-005' )  
insert into Transcript (CourseName,GPA,StudentId) values  
( 'Operating Systems', '2.7', 'fa20-bcs-006' )  
insert into Transcript (CourseName,GPA,StudentId) values  
( 'Database Systems', '2.0', 'fa20-bcs-007' )  
insert into Transcript (CourseName,GPA,StudentId) values  
( 'Database Systems', '3.7', 'fa20-bcs-008' )  
insert into Transcript (CourseName,GPA,StudentId) values  
( 'Operating Systems', '2.5', 'fa20-bcs-009' )  
insert into Transcript (CourseName,GPA,StudentId) values  
( 'Database Systems', '3.0', 'fa20-bcs-010' )
```

```
DELETE FROM Transcript WHERE StudentId='fa20-bcs-008';
```

```

select * from Transcript

UPDATE Transcript set GPA='3.3'WHERE StudentId='fa20-bcs-010';
select * from Transcript

DELETE FROM Transcript WHERE StudentId='fa20-bcs-002';
select * from Transcript

UPDATE Transcript set GPA='3.3'WHERE StudentId='fa20-bcs-004';
select * from Transcript

DELETE FROM Transcript WHERE StudentId='fa20-bcs-001';
select * from Transcript

UPDATE Transcript set GPA='1.3'WHERE StudentId='fa20-bcs-003';
select * from Transcript

DELETE FROM Transcript WHERE StudentId='fa20-bcs-006';
select * from Transcript

UPDATE Transcript set GPA='0'WHERE StudentId='fa20-bcs-009';
select * from Transcript

```

*Zahir Ayub Khan:*

```

create table Student (
ID nchar(30),
Name varchar(30),
);

create table Transcript (
Subject nchar(30),
GPA nchar(30),
ID nchar(30),
);

INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-001', 'ahmad khan');

INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-002', 'Hassan ali');

INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-003', 'Bilal Khan');

INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-004', 'Rana Noon');

INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-005', 'Zoya Yusufzai');

INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-006', 'Zain Ahmad');

```

```
INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-007', 'Ghulam mujtaba');
```

```
INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-008', 'Hamza ali khan');
```

```
INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-009', 'Ali Joiya');
```

```
INSERT INTO Student (ID, Name)
VALUES ('Sp17-bse-010', 'Alex markovich');
```

```
INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Math', '2.3', 'Sp17-bse-001');
```

```
INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('English', '3.3', 'Sp17-bse-002');
```

```
INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Database system', '2.7', 'Sp17-bse-003');
```

```
INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('OOP', '3.7', 'Sp17-bse-004');
```

```
INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Islamic studies', '3.0', 'Sp17-bse-005');
```

```
INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('CA', '2.0', 'Sp17-bse-006');
```

```
INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Advance OOP', '2.7', 'Sp17-bse-007');
```

```
INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('statistics', '2.3', 'Sp17-bse-008');
```

```
INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('Cal1', '2.3', 'Sp17-bse-009');
```

```
INSERT INTO Transcript(Subject,GPA,ID)
VALUES ('SQE', '2.7', 'Sp17-bse-010');
```

```
UPDATE Transcript
Set GPA='2.7'
WHERE ID='Sp17-bse-001';
```

```
UPDATE Transcript
Set GPA='1.7'
WHERE ID='Sp17-bse-006';
```

```
UPDATE Transcript
Set GPA='2.3'
WHERE ID='Sp17-bse-010';
```

```
DELETE FROM Transcript WHERE ID='Sp17-bse-009';
DELETE FROM Transcript WHERE ID='Sp17-bse-008';
```

Jamal Khan:

```
create database StudentTranscriptDB
use StudentTranscriptDB
```

```
create table Student(
StudentId nchar(30),
Name(30))
```

```
insert into Student(StudentId,Name) values
('fa20-bcs-001','ali')
insert into Student(StudentId,Name) values
('fa20-bcs-002','Aftab')
insert into Student(StudentId,Name) values
('fa20-bcs-003','Ammar')
insert into Student(StudentId,Name) values
('fa20-bcs-004','Mohsin')
insert into Student(StudentId,Name) values
('fa20-bcs-005','Zubair')
insert into Student(StudentId,Name) values
('fa20-bcs-006','Daniyal')
insert into Student(StudentId,Name) values
('fa20-bcs-007','Usman')
insert into Student(StudentId,Name) values
('fa20-bcs-008','Abbass')
insert into Student(StudentId,Name) values
('fa20-bcs-009','Saddique')
insert into Student(StudentId,Name) values
('fa20-bcs-010','Umar')
```

```
create table Transcript(
CourseName nchar(30),
GPA float(30),
StudentId nchar(30)
);
```

```
insert into Transcript (CourseName,GPA,StudentId) values
('Database Systems','1.3','fa20-bcs-001')
insert into Transcript (CourseName,GPA,StudentId) values
('Database Systems','1.3','fa20-bcs-002')
insert into Transcript (CourseName,GPA,StudentId) values
('Database System','2.7','fa20-bcs-003')
insert into Transcript (CourseName,GPA,StudentId) values
('Database Systems','3.3','fa20-bcs-004')
insert into Transcript (CourseName,GPA,StudentId) values
('Database System','4.0','fa20-bcs-005')
insert into Transcript (CourseName,GPA,StudentId) values
('Operating Systems','2.7','fa20-bcs-006')
```

```

insert into Transcript (CourseName,GPA,StudentId) values
('Database Systems','2.0','fa20-bcs-007')
insert into Transcript (CourseName,GPA,StudentId) values
('Database Systems','3.7','fa20-bcs-008')
insert into Transcript (CourseName,GPA,StudentId) values
('Operating Systems','2.5','fa20-bcs-009')
insert into Transcript (CourseName,GPA,StudentId) values
('Database Systems','3.0','fa20-bcs-010')

```

```

DELETE FROM Transcript WHERE StudentId='fa20-bcs-008';
select * from Transcript

```

```

UPDATE Transcript set GPA='3.3'WHERE StudentId='fa20-bcs-010';
select * from Transcript

```

```

DELETE FROM Transcript WHERE StudentId='fa20-bcs-002';
select * from Transcript

```

```

UPDATE Transcript set GPA='3.3'WHERE StudentId='fa20-bcs-004';
select * from Transcript

```

```

DELETE FROM Transcript WHERE StudentId='fa20-bcs-001';
select * from Transcript

```

```

UPDATE Transcript set GPA='1.3'WHERE StudentId='fa20-bcs-003';
select * from Transcript

```

```

DELETE FROM Transcript WHERE StudentId='fa20-bcs-006';
select * from Transcript

```

```

UPDATE Transcript set GPA='0'WHERE StudentId='fa20-bcs-009';
select * from Transcript

```

## Lab 6 Common Solution:

```

select * from branch;
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B005',
'H#88 j-13/3', 'ABT', '54000');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B006',
'H#77 k-14/6', 'KARI', '56000');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B007',
'H#89 m-11/7', 'QUA', '63000');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B008',
'H#69 l-10/2', 'ISL', '52200');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B009',
'H#35 l-61/2', 'HAR', '73000');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0010',
'H#66 l-01/5', 'MUL', '32100');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0011',
'H#99 l-11/3', 'ABT', '53300');

```

```

INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0012',
'H#12 I-10/2', 'SWA', '57700');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0013',
'H#19 I-13/6', 'KARI', '56600');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0014',
'H#35 I-62/2', 'HAR', '73800');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0015',
'H#66 I-02/5', 'MUL', '23700');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0016',
'H#99 I-17/3', 'ABT', '81900');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0017',
'H#12 I-80/6', 'SWA', '65100');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0018',
'H#19 I-93/6', 'KARI', '89100');

```

/\* Above work is Zahir Ayub Khan. Work Below Is Jamal Khan\*/

```

create database DreamHome;
use Dreamhome;
create table Branch(branchNo varchar(20) NOT NULL PRIMARY KEY, street varchar(50)
NOT NULL, city varchar(50) NOT NULL,
postcode varchar(20) NOT NULL);

```

```

INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0019', 'X#11 Y-11/1', 'ABBOTTABAD', '22500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0020', 'X#77 Y-22/2', 'MANSERA', '23400');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0021', 'X#89 Y-33/3', 'PESHAWER', '24500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0022', 'X#69 Y-44/4', 'MARDAN', '26500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0023', 'X#35 Y-55/5', 'KOHAT', '27500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0024', 'X#66 Y-66/6', 'NOWSHERA', '28500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0025', 'X#99 Y-77/7', 'SWABI', '29500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0026', 'X#12 Y-88/8', 'ISLAMABAD', '31500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0027', 'X#19 Y-99/9', 'RAWALPINDI', '32500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0028', 'X#35 Y-12/1', 'LAHORE', '33500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0029', 'X#66 Y-13/2', 'KARACHI', '34500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0030', 'X#99 Y-14/3', 'MULTAN', '35500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0031', 'X#12 Y-15/4', 'HYDERABAD', '36500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0032', 'X#19 Y-16/5', 'OKHARA', '37500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0033', 'X#35 Y-12/1', 'LAHORE', '8000');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0034', 'X#66 Y-13/2', 'KARACHI', '9000');

```

```

INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0035', 'X#99 Y-14/3', 'MULTAN', '11000');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0036', 'X#12 Y-15/4', 'HYDERABAD', '15000');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0037', 'X#19 Y-16/5', 'OKHARA', '34500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0038', 'X#35 Y-12/1', 'LAHORE', '1000');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0039', 'X#66 Y-13/2', 'KARACHI', '19000');

```

*Zahir Ayub Khan:*

```

select * from branch;
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B005',
'H#88 j-13/3', 'ABT', '54000');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B006',
'H#77 k-14/6', 'KARI', '56000');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B007',
'H#89 m-11/7', 'QUA', '63000');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B008',
'H#69 l-10/2', 'ISL', '52200');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B009',
'H#35 l-61/2', 'HAR', '73000');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0010',
'H#66 l-01/5', 'MUL', '32100');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0011',
'H#99 l-11/3', 'ABT', '53300');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0012',
'H#12 l-10/2', 'SWA', '57700');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0013',
'H#19 l-13/6', 'KARI', '56600');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0014',
'H#35 l-62/2', 'HAR', '73800');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0015',
'H#66 l-02/5', 'MUL', '23700');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0016',
'H#99 l-17/3', 'ABT', '81900');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0017',
'H#12 l-80/6', 'SWA', '65100');
INSERT into Branch (branchNo, street, city, postcode) VALUES ('B0018',
'H#19 l-93/6', 'KARI', '89100');

```

*Jamal Khan:*

```

create database DreamHome;
use Dreamhome;
create table Branch(branchNo varchar(20) NOT NULL PRIMARY KEY, street varchar(50)
NOT NULL, city varchar(50) NOT NULL,

```



postcode varchar(20) NOT NULL);

```
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0019', 'X#11 Y-11/1', 'ABBOTTABAD', '22500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0020', 'X#77 Y-22/2', 'MANSERA', '23400');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0021', 'X#89 Y-33/3', 'PESHAWER', '24500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0022', 'X#69 Y-44/4', 'MARDAN', '26500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0023', 'X#35 Y-55/5', 'KOHAT', '27500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0024', 'X#66 Y-66/6', 'NOWSHERA', '28500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0025', 'X#99 Y-77/7', 'SWABI', '29500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0026', 'X#12 Y-88/8', 'ISLAMABAD', '31500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0027', 'X#19 Y-99/9', 'RAWALPINDI', '32500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0028', 'X#35 Y-12/1', 'LAHORE', '33500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0029', 'X#66 Y-13/2', 'KARACHI', '34500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0030', 'X#99 Y-14/3', 'MULTAN', '35500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0031', 'X#12 Y-15/4', 'HYDERABAD', '36500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0032', 'X#19 Y-16/5', 'OKHARA', '37500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0033', 'X#35 Y-12/1', 'LAHORE', '8000');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0034', 'X#66 Y-13/2', 'KARACHI', '9000');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0035', 'X#99 Y-14/3', 'MULTAN', '11000');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0036', 'X#12 Y-15/4', 'HYDERABAD', '15000');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0037', 'X#19 Y-16/5', 'OKHARA', '34500');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0038', 'X#35 Y-12/1', 'LAHORE', '1000');
INSERT into Branch (branchNo, street, city, postcode) VALUES
('B0039', 'X#66 Y-13/2', 'KARACHI', '19000');
```

Lab 7 Common Solution:

Q1: Print the list of postcodes without any repetition  
 Select distinct(postcode) from Branch;

Q2: Print all fName from Staff without repetition  
 Select distinct(fName) from Staff;

Q3: List all staff with renaming all its columns in results  
 Select staffNo as ID, fName as FirstName, lName as LastName, [position]  
 as Allocation, sex as Gender, DOB as Birth, salary as Wages, branchNo as  
 Branch from Staff;

Q4: List all clients with re-naming all its columns to synonyms.  
 Select clientNo as StakeHolderID, fName as  
 FirstName, lName as LastName, telNo as PhoneNo, prefType as  
 Preference, maxRent as MaximumRent from Client;

Q5: List all staff with a salary greater than 10,000.  
 Select salary from Staff where salary >10000;

Q6: List all managers and supervisors.  
 Select [position] from Staff Where [position] = 'supervisor' OR [position]  
 ='manager'

/\* Above work is Zahir Ayub Khan. Work Below is Jamal Khan\*/

Q1: Print the list of postcodes without any repetition  
 ANS: Select distinct(postcode) from Branch;

Q2: Print all fName from Staff without repetition  
 ANS: Select distinct(fName) from Staff;

Q3: List all staff with renaming all its columns in results  
 ANS: Select staffNo as ID, fName as FirstName, lName  
 as LastName, [position] as Allocation, sex as Gender,  
 DOB as Birth, salary as Wages, branchNo as Branch  
 from Staff;

Q4: List all clients with re-naming all its columns to synonyms.  
 ANS: SELECT clientNo as StakeHolderID, fName as  
 FirstName, lName as LastName, telNo as PhoneNo,  
 prefType as Preference, maxRent as MaximumRent  
 FROM Client;

**Q5: List all staff with a salary greater than 10,000.**

**ANS SELECT salary FROM Staff where salary >10000;**

**Q6: List all managers and supervisors.**

**ANS: SELECT [position] FROM Staff Where [position] = 'supervisor' OR [position] ='manager'**

*Zahir Ayub khan:*

**Q1: Print the list of postcodes without any repetition**

**Select distinct(postcode) from Branch;**

**Q2: Print all fName from Staff without repetition**

**Select distinct(fName) from Staff;**

**Q3: List all staff with renaming all its columns in results**

**Select staffNo as ID, fName as FirstName, lName as LastName, [position] as Allocation, sex as Gender, DOB as Birth, salary as Wages, branchNo as Branch from Staff;**

**Q4: List all clients with re-naming all its columns to synonyms.**

**Select clientNo as StakeHolderID, fName as FirstName, lName as LastName, telNo as PhoneNo, prefType as Preference, maxRent as MaximumRent from Client;**

**Q5: List all staff with a salary greater than 10,000.**

**Select salary from Staff where salary >10000;**

**Q6: List all managers and supervisors.**

**Select [position] from Staff Where [position] = 'supervisor' OR [position] ='manager'**

*Jamal Khan:*

**Q1: Print the list of postcodes without any repetition**

**ANS: Select distinct(postcode) from Branch;**

**Q2: Print all fName from Staff without repetition**

**ANS: Select distinct(fName) from Staff;**

Q3: List all staff with renaming all its columns in results

ANS: Select staffNo as ID, fName as FirstName, lName as LastName, [position] as Allocation, sex as Gender, DOB as Birth, salary as Wages, branchNo as Branch from Staff;

Q4: List all clients with re-naming all its columns to synonyms.

ANS: SELECT clientNo as StakeholderID, fName as FirstName, lName as LastName, telNo as PhoneNo, prefType as Preference, maxRent as MaximumRent FROM Client;

Q5: List all staff with a salary greater than 10,000.

ANS SELECT salary FROM Staff where salary >10000;

Q6: List all managers and supervisors.

ANS: SELECT [position] FROM Staff Where [position] = 'supervisor' OR [position] ='manager'

## LAB 8 CommonSolution:

Q1:

select staffNo,fName,lName,salary from staff order by salary desc

Q2:

select propertyNo,type,rooms,rent from PropertyForRent order by type

select propertyNo,type,rooms,rent from PropertyForRent order by type,rent desc

Q3:

select count(\*) as myCount from PropertyForRent where rent<=500

Q4:

select count(Distinct propertyNo) As myCount from

Viewing where viewDate BETWEEN '1-May-04' AND '31-May-04';

Q5:

select count(staffNo) as myCount,sum(salary) as mySalary from staff where position='Manager'

Q6:

select MIN(salary) as myMin, MAX(salary) as MyMax, AVG(salary) as myAVG from Staff

Q7:

select staffNo, fName, lName, position, salary from Staff where (select AVG(salary) from Staff) < salary;

Q8:

select \*from Staff where salary> any(select salary from Staff where branchNo='B002')

Qno9:-

select \*from Staff where salary> all(select salary from Staff where branchNo='B002')

/\* Above work is Zahir Ayub Khan. Work Below is Jamal Khan\*/

Q1:

Ans: select staffNo,fName,lName,salary from staff order by salary desc

Q2:

Ans: select propertyNo,type,rooms,rent from PropertyForRent order by type  
select propertyNo,type,rooms,rent from PropertyForRent order by type,rent desc

Q3:

Ans: select count(\*) as myCount from PropertyForRent where rent<=500

Q4:

Ans: select count(Distinct propertyNo) As myCount from Viewing WHERE viewDate BETWEEN '1-May-04' AND '31-May-04';

Q5:

Ans: select count(staffNo) as myCount,sum(salary) as mySalary from staff where position='Manager'

Q6:

Ans: select MIN(salary) as myMin, MAX(salary) as myMax, AVG(salary) as myAVG from Staff

Q7:

Ans: SELECT staffNo, fName, lName, position, salary FROM Staff WHERE (SELECT AVG(salary) FROM Staff) < salary;

Q8:

Ans: select \*from Staff where salary> any(select salary from Staff where branchNo='B003')

Q9:

Ans: select \*from Staff where salary> all(select salary from Staff where branchNo='B003')

*Zahir Ayub Khan:*

Q1:

select staffNo,fName,lName,salary from staff order by salary desc

Q2:

select propertyNo,type,rooms,rent from PropertyForRent order by type

select propertyNo,type,rooms,rent from PropertyForRent order by type,rent desc

Q3:

select count(\*) as myCount from PropertyForRent where rent<=500

Q4:

select count(Distinct propertyNo) As myCount from

Viewing where viewDate BETWEEN '1-May-04' AND '31-May-04';

Q5:

select count(staffNo) as myCount,sum(salary) as mySalary from staff where position='Manager'

Q6:

select MIN(salary) as myMin, MAX(salary) as MyMax, AVG(salary) as myAVG from Staff

Q7:

```
select staffNo, fName, lName, position,  
salary from Staff where (select AVG(salary) from Staff) < salary;
```

Q8:

```
select *from Staff where salary> any(select salary from Staff  
where branchNo='B002')
```

Qno9:-

```
select *from Staff where salary> all(select salary from Staff  
where branchNo='B002')
```

Jamal Khan:

Q1:

Ans: select staffNo,fName,lName,salary from staff order by salary desc

Q2:

Ans: select propertyNo,type,rooms,rent from PropertyForRent order by  
type select propertyNo,type,rooms,rent from PropertyForRent order by  
type,rent desc

Q3:

Ans: select count(\*) as myCount from PropertyForRent where  
rent<=500

Q4:

Ans: select count(Distinct propertyNo) As myCount from Viewing  
WHERE viewDate BETWEEN '1-May-04' AND '31-May-04';

Q5:

Ans: select count(staffNo) as myCount,sum(salary) as mySalary from  
staff where position='Manager'

Q6:

Ans: select MIN(salary) as myMin, MAX(salary) as myMax, AVG(salary)  
as myAVG from Staff

Q7:

Ans: SELECT staffNo, fName, lName, position, salary FROM Staff WHERE  
(SELECT AVG(salary) FROM Staff) < salary;

Q8:

Ans: select \*from Staff where salary> any(select salary from Staff where  
branchNo='B003')

Q9:

Ans: select \*from Staff where salary> all(select salary from Staff where  
branchNo='B003')

LAB 9 Common Solution:

CREATE DATABASE employeeese;

SELECT FIRST\_NAME, LAST\_NAME, SALARY

FROM employees

WHERE SALARY >

(SELECT salary FROM employees WHERE last\_name = 'popp');

SELECT first\_name, last\_name

FROM employees

WHERE department\_id

IN (SELECT department\_id FROM departments WHERE  
department\_name='IT');

/\* Above work is Zahir Ayub Khan. Work Below is Jamal Khan\*/

Q1:

SELECT \* FROM employees;



Q2:

```
SELECT FIRST_NAME, LAST_NAME, SALARY
FROM employees
WHERE SALARY >
(SELECT salary FROM employees WHERE last_name = 'Bull');
```

Q3:

```
SELECT first_name, last_name
FROM employees
WHERE department_id
IN (SELECT department_id FROM departments WHERE
department_name='IT');
```

*Jamal Khan:*

Q1:

```
SELECT * FROM employees;
```

Q2:

```
SELECT FIRST_NAME, LAST_NAME, SALARY
FROM employees
WHERE SALARY >
(SELECT salary FROM employees WHERE last_name = 'Bull');
```

Q3:

```
SELECT first_name, last_name
FROM employees
WHERE department_id
IN (SELECT department_id FROM departments WHERE
department_name='IT');
```

Zahir Ayub Khan:

*CREATE DATABASE employeeese;*

*SELECT FIRST\_NAME, LAST\_NAME, SALARY*

*FROM employees*

*WHERE SALARY >*

*(SELECT salary FROM employees WHERE last\_name = 'popp');*

```
SELECT first_name, last_name  
FROM employees  
WHERE department_id  
IN (SELECT department_id FROM departments WHERE  
department_name='IT');
```

## LAB 10 Common Solution:

1.1

```
SELECT first_name, last_name FROM employees  
WHERE manager_id in (select employee_id  
FROM employees WHERE department_id  
IN (SELECT department_id FROM departments WHERE  
location_id  
IN (select location_id from locations where country_id='US')));
```

1.2

```
SELECT first_name, last_name  
FROM employees  
WHERE (employee_id IN (SELECT manager_id FROM  
employees));
```

1.3

```
SELECT first_name, last_name, salary FROM employees  
WHERE salary > (SELECT AVG(salary) FROM employees);
```

1.4

```
SELECT first_name, last_name, salary
FROM employees
WHERE employees.salary = (SELECT min_salary
FROM jobs
WHERE employees.job_id = jobs.job_id);
```

1.5

```
SELECT first_name, last_name, salary
FROM employees
WHERE department_id IN
(SELECT department_id FROM departments WHERE
department_name LIKE 'IT')
AND salary > (SELECT avg(salary) FROM employees);
```

1.6

```
SELECT first_name, last_name, salary
FROM employees
WHERE salary >
(SELECT salary FROM employees WHERE last_name = 'Bell')
ORDER BY first_name;
```

1.7

```
SELECT * FROM employees
WHERE salary = (SELECT MIN(salary) FROM employees);
```

1.8

```
SELECT * FROM employees
WHERE salary >
ALL(SELECT avg(salary)FROM employees GROUP BY
department_id);
```

1.12

```
SELECT employee_id, first_name, last_name,
(SELECT department_name FROM departments d
WHERE e.department_id = d.department_id) department
FROM employees e ORDER BY department;
```

1.13

```
SELECT employee_id FROM employees
WHERE employee_id%2 = 0;
```

1.14

```
SELECT DISTINCT salary
FROM employees e1
WHERE 5 = (SELECT COUNT(DISTINCT salary)
FROM employees e2
```

WHERE e2.salary >= e1.salary);

1.15

SELECT DISTINCT salary

FROM employees e1

WHERE 4 = (SELECT COUNT(DISTINCT salary)

FROM employees e2

WHERE e2.salary <= e1.salary);

1.16

SELECT \* FROM (

SELECT \* FROM employees ORDER BY employee\_id DESC  
LIMIT 10) sub

ORDER BY employee\_id ASC;

1.17

SELECT \* FROM departments

WHERE department\_id

NOT IN (select department\_id FROM employees);

1.18

SELECT DISTINCT salary

FROM employees a

WHERE 3 >= (SELECT COUNT(DISTINCT salary)

FROM employees b

WHERE b.salary >= a.salary)

```
ORDER BY a.salary DESC;
```

1.19

```
SELECT DISTINCT salary
```

```
FROM employees a
```

```
WHERE 3 >= (SELECT COUNT(DISTINCT salary)
```

```
FROM employees b
```

```
WHERE b.salary <= a.salary)
```

```
ORDER BY a.salary DESC;
```

1.20

```
SELECT *
```

```
FROM employees emp1
```

```
WHERE (1) = (
```

```
SELECT COUNT(DISTINCT(emp2.salary))
```

```
FROM employees emp2
```

```
WHERE emp2.salary > emp1.salary);
```

```
/* Above work is Zahir Ayub Khan. Work Below is Jamal Khan*/
```

Q1:

```
SELECT first_name, last_name FROM employees
```

```
WHERE manager_id in (select employee_id
```

```
FROM employees WHERE department_id
```

```
IN (SELECT department_id FROM departments WHERE location_id
```

```
IN (select location_id from locations where
```

```
country_id='US')));
```

Q2:

```
SELECT first_name, last_name
FROM employees
WHERE (employee_id IN (SELECT manager_id FROM employees));
```

Q3:

```
SELECT first_name, last_name, salary FROM employees
WHERE salary > (SELECT AVG(salary) FROM employees);
```

Q4:

```
SELECT first_name, last_name, salary
FROM employees
WHERE employees.salary = (SELECT min_salary
FROM jobs
WHERE employees.job_id = jobs.job_id);
```

Q5:

```
SELECT first_name, last_name, salary
FROM employees
WHERE department_id IN
(SELECT department_id FROM departments WHERE department_name
LIKE 'IT%')
AND salary > (SELECT avg(salary) FROM employees);
```

Q6:

```
SELECT first_name, last_name, salary
FROM employees
WHERE salary >
(SELECT salary FROM employees WHERE last_name = 'Bell') ORDER
BY first_name;
```

Q7:

```
SELECT * FROM employees
WHERE salary = (SELECT MIN(salary) FROM employees);
```

Q8: Write a query to find the names (first\_name, last\_name), the salary of the employees whose salary greater than the average salary of all departments?

```
SELECT * FROM employees
WHERE salary >
ALL(SELECT avg(salary) FROM employees GROUP BY department_id);
```

Q9: Write a query to find the names (first\_name, last\_name) and salary of the employees who earn a salary that is higher than the salary of all the Shipping Clerk (JOB\_ID = 'SH\_CLERK'). Sort the results of the salary of the lowest to highest.

```
SELECT first_name, last_name, job_id, salary
FROM employees
WHERE salary >
ALL (SELECT salary FROM employees WHERE job_id = 'SH_CLERK')
```

ORDER BY salary;

Q10: Write a query to find the names (first\_name, last\_name) of the employees who are not supervisors?

```
SELECT b.first_name,b.last_name
FROM employees b
WHERE NOT EXISTS (SELECT 'X' FROM employees a WHERE
a.manager_id = b.employee_id);
```

Q11: Write a query to display the employee ID, first name, last names, and department names of all employees.

```
SELECT employee_id, first_name, last_name,
(SELECT department_name FROM departments d
WHERE e.department_id = d.department_id) department
FROM employees e ORDER BY department;
```

Q12: Write a query to display the employee ID, first name, last names, salary of all employees whose salary is above average for their departments.

```
SELECT employee_id, first_name
FROM employees AS A
WHERE salary >
(SELECT AVG(salary) FROM employees WHERE department_id =
A.department_id);
```

Q13: Write a query to fetch even numbered records from employees table.

```
SET @i = 0;
SELECT i, employee_id
FROM (SELECT @i := @i + 1 AS i, employee_id FROM employees)
a WHERE MOD(a.i, 2) = 0;
```

Q14: Write a query to find the 5th maximum salary in the employees table.

```
SELECT DISTINCT salary
FROM employees e1
WHERE 5 = (SELECT COUNT(DISTINCT salary)
FROM employees e2
WHERE e2.salary >= e1.salary);
```

Q15: Write a query to find the 4th minimum salary in the employees table.

```
SELECT DISTINCT salary
FROM employees e1
WHERE 4 = (SELECT COUNT(DISTINCT salary)
FROM employees e2
WHERE e2.salary <= e1.salary);
```

Q16: Write a query to select last 10 records from a table.

```
SELECT * FROM (
SELECT * FROM employees ORDER BY employee_id DESC LIMIT 10)
sub
ORDER BY employee_id ASC;
```



Q17: Write a query to list department number, name for all the departments in which there are no employees in the department.

```
SELECT * FROM departments
WHERE department_id
NOT IN (select department_id FROM employees);
```

Q18: Write a query to get 3 maximum salaries.

```
SELECT DISTINCT salary
FROM employees a
WHERE 3 >= (SELECT COUNT(DISTINCT salary)
FROM employees b
WHERE b.salary >= a.salary)
ORDER BY a.salary DESC;
```

Q19: Write a query to get 3 minimum salaries.

```
SELECT DISTINCT salary
FROM employees a
WHERE 3 >= (SELECT COUNT(DISTINCT salary)
FROM employees b
WHERE b.salary <= a.salary)
ORDER BY a.salary DESC;
```

Q20: Write a query to get nth max salaries of employees. Further practice with nested queries

```
SELECT *
FROM employees emp1
WHERE (1) = (
SELECT COUNT(DISTINCT(emp2.salary))
FROM employees emp2
WHERE emp2.salary > emp1.salary);
```

*Zahir Ayub Khan:*

Jamal Khan:

Q1:

```
SELECT first_name, last_name FROM employees
WHERE manager_id in (select employee_id
FROM employees WHERE department_id
IN (SELECT department_id FROM departments WHERE location_id
IN (select location_id from locations where
country_id='US'))));
```

Q2:

```
SELECT first_name, last_name
FROM employees
```

```
WHERE (employee_id IN (SELECT manager_id FROM employees));
```

Q3:

```
SELECT first_name, last_name, salary FROM employees  
WHERE salary > (SELECT AVG(salary) FROM employees);
```

Q4:

```
SELECT first_name, last_name, salary  
FROM employees  
WHERE employees.salary = (SELECT min_salary  
FROM jobs  
WHERE employees.job_id = jobs.job_id);
```

Q5:

```
SELECT first_name, last_name, salary  
FROM employees  
WHERE department_id IN  
(SELECT department_id FROM departments WHERE department_name  
LIKE 'IT%')  
AND salary > (SELECT avg(salary) FROM employees);
```

Q6:

```
SELECT first_name, last_name, salary  
FROM employees  
WHERE salary >  
(SELECT salary FROM employees WHERE last_name = 'Bell') ORDER  
BY first_name;
```

Q7:

```
SELECT * FROM employees  
WHERE salary = (SELECT MIN(salary) FROM employees);
```

Q8: Write a query to find the names (first\_name, last\_name), the salary of the employees whose salary greater than the average salary of all departments?

```
SELECT * FROM employees  
WHERE salary >  
ALL(SELECT avg(salary) FROM employees GROUP BY department_id);
```

Q9: Write a query to find the names (first\_name, last\_name) and salary of the employees who earn a salary that is higher than the salary of all the Shipping Clerk (JOB\_ID = 'SH\_CLERK'). Sort the results of the salary of the lowest to highest.

```
SELECT first_name, last_name, job_id, salary  
FROM employees  
WHERE salary >  
ALL (SELECT salary FROM employees WHERE job_id = 'SH_CLERK')  
ORDER BY salary;
```

Q10: Write a query to find the names (first\_name, last\_name) of the employees who are not supervisors?

```
SELECT b.first_name,b.last_name
FROM employees b
WHERE NOT EXISTS (SELECT 'X' FROM employees a WHERE
a.manager_id = b.employee_id);
```

Q11: Write a query to display the employee ID, first name, last names, and department names of all employees.

```
SELECT employee_id, first_name, last_name,
(SELECT department_name FROM departments d
WHERE e.department_id = d.department_id) department
FROM employees e ORDER BY department;
```

Q12: Write a query to display the employee ID, first name, last names, salary of all employees whose salary is above average for their departments.

```
SELECT employee_id, first_name
FROM employees AS A
WHERE salary >
(SELECT AVG(salary) FROM employees WHERE department_id =
A.department_id);
```

Q13: Write a query to fetch even numbered records from employees table.

```
SET @i = 0;
SELECT i, employee_id
FROM (SELECT @i := @i + 1 AS i, employee_id FROM employees)
a WHERE MOD(a.i, 2) = 0;
```

Q14: Write a query to find the 5th maximum salary in the employees table.

```
SELECT DISTINCT salary
FROM employees e1
WHERE 5 = (SELECT COUNT(DISTINCT salary)
FROM employees e2
WHERE e2.salary >= e1.salary);
```

Q15: Write a query to find the 4th minimum salary in the employees table.

```
SELECT DISTINCT salary
FROM employees e1
WHERE 4 = (SELECT COUNT(DISTINCT salary)
FROM employees e2
WHERE e2.salary <= e1.salary);
```

Q16: Write a query to select last 10 records from a table.

```
SELECT * FROM (
SELECT * FROM employees ORDER BY employee_id DESC LIMIT 10)
sub
ORDER BY employee_id ASC;
```

Q17: Write a query to list department number, name for all the departments in which there are no employees in the department.

```
SELECT * FROM departments
```

```
WHERE department_id  
NOT IN (select department_id FROM employees);
```

Q18: Write a query to get 3 maximum salaries.

```
SELECT DISTINCT salary  
FROM employees a  
WHERE 3 >= (SELECT COUNT(DISTINCT salary)  
FROM employees b  
WHERE b.salary >= a.salary)  
ORDER BY a.salary DESC;
```

Q19: Write a query to get 3 minimum salaries.

```
SELECT DISTINCT salary  
FROM employees a  
WHERE 3 >= (SELECT COUNT(DISTINCT salary)  
FROM employees b  
WHERE b.salary <= a.salary)  
ORDER BY a.salary DESC;
```

Q20: Write a query to get nth max salaries of employees. Further practice with nested queries

```
SELECT *  
FROM employees emp1  
WHERE (1) = (  
SELECT COUNT(DISTINCT(emp2.salary))  
FROM employees emp2  
WHERE emp2.salary > emp1.salary);
```

LAB 11 Common Solution:

```
CREATE TABLE table_name (
```

```
    Name VARCHAR(20),
```

```
    Family_name VarChar(20),
```

```
);
```

```
Insert into table_name(Name,Family_name)
```

select

'Ali' as Name,

'Khan' as Family\_name;

Insert into table\_name(Name,Family\_name)

select

'Ahmad' as Name,

'Iqbal' as Family\_name;

Insert into table\_name(Name,Family\_name)

select

'Zubar' as Name,

'Akram' as Family\_name;

SELECT Name,Family\_name ,Name+" "+Family\_name as fullname

FROM table\_name;

/\* Above work is Zahir Ayub Khan. Work Below Is Jamal Khan\*/

```
Use dreamhome;
create table Name (FName varchar(50) NOT NULL,familyName varchar (50) NOT NULL);
insert into Name
values ('Jamal', 'Nawaz'),
('Aftab', 'Kurshid'),
('Abdul', 'Rehman');
-- CONCATINATION
SELECT CONCAT("Ali ", "Shoukat") AS full String;
-- extra string funtions
SELECT LENGTH(Fname) AS LengthOfString from Name;
select LOCATE("i", "Ali");
SELECT upper("Abdullah");
SELECT lower("Saifullah");
SELECT REPEAT(familyName, 3) from Name;
SELECT STRCMP("Afaaq", "Afaq");
SELECT SUBSTR("Jawad", 4) AS ExtractString;
SELECT LEFT("Amaan", 5) AS ExtractString;
SELECT ASCII(FName) from Name;
```

*Zahir Ayub Khan:*

```
CREATE TABLE table_name (
```

```
    Name VARCHAR(20),
```

```
    Family_name VarChar(20),
```

```
);
```

```
Insert into table_name(Name,Family_name)
```

```
select
```

```
'Ali' as Name,
```

```
'Khan' as Family_name;
```

```
Insert into table_name(Name,Family_name)
```

```
select
```

```
'Ahmad' as Name,
```

```
'Iqbal' as Family_name;
```

```
Insert into table_name(Name,Family_name)
```

```
select
```

```
'Zubar' as Name,
```

```
'Akram' as Family_name;
```

```
SELECT Name,Family_name ,Name+"+Family_name as fullname
```

```
FROM table_name;
```

Jamal Khan:

```
Use dreamhome;
create table Name (FName varchar(50) NOT NULL,familyName varchar (50) NOT NULL);
insert into Name
values ('Jamal', 'Nawaz'),
('Aftab', 'Kurshid'),
('Abdul', 'Rehman');
-- CONCATINATION
SELECT CONCAT("Ali ", "Shoukat") AS full String;
-- extra string funtions
SELECT LENGTH(Fname) AS LengthOfString from Name;
select LOCATE("i", "Ali");
SELECT upper("Abdullah");
SELECT lower("Saifullah");
SELECT REPEAT(familyName, 3) from Name;
SELECT STRCMP("Afaaq", "Afaq");
SELECT SUBSTR("Jawad", 4) AS ExtractString;
SELECT LEFT("Amaan", 5) AS ExtractString;
SELECT ASCII(FName) from Name;
```

## LAB 12 CommonSolution:

Q1

```
select CountryCode,sum(Percentage) from countrylanguage
group by CountryCode;
```

Q2

```
select sum(Population) from country;
```

Q3

```
select count(*) from country;
```

Q4

```
select count(distinct Language) from countrylanguage;
```

*/\* Above work is Zahir Ayub Khan. Work Below Is JamaI khan\*/*

Q1:

```
SELECT country_code, sum(percentage)
FROM country_language group by country_code;
```

Q2:

```
SELECT sum(Population) From country;
```

Q3:

```
SELECT count(*) From country;
```

Q4:

```
SELECT count(distinct language)
from country_language;
```

*Zahir Ayub Khan:*

Q1

```
select CountryCode,sum(Percentage) from countrylanguage
group by CountryCode;
```

Q2

```
select sum(Population) from country;
```

Q3

```
select count(*) from country;
```

Q4

```
select count(distinct Language) from countrylanguage;
```

Jamal Khan:

Q1:

```
SELECT country_code, sum(percentage)
FROM country_language group by country_code;
```

Q2:

```
SELECT sum(Population) From country;
```

Q3:

```
SELECT count(*) From country;
```

Q4:

```
SELECT count(distinct language)
from country_language;
```



## Lab 13 Common Solution:

Q1

```
SELECT customers.customerNumber,customers.customerName,  
payments.checkNumber,payments.paymentDate, payments.amount FROM  
customers inner JOIN payments ON  
customers.customerNumber=payments.customerNumber;
```

Q2

```
SELECT products.productName, orderdetails.quantityOrdered ,  
orderdetails.priceEach FROM orderdetails INNER JOIN products ON  
orderdetails.productCode=products.productCode;
```

Q3

```
SELECT products.productName, productlines.productLine FROM products  
Right JOIN productlines ON products.productLine=productlines.productLine;
```

Q4

```
SELECT customers.customerName, orders.orderNumber FROM  
customers inner JOIN orders ON  
customers.customerNumber=orders.customerNumber and  
customers.customerNumber=103;
```

*/\* Above work is Zahir Ayub Khan. Work Below is Jamaal Khan\*/*

Q1:

```
SELECT Customers.Customer_Number,Customers.Customer_Name,  
Payments.Check_Number,Payments.Payment_Date,  
Payments.Payments_amount FROM customers inner JOIN payments ON  
Customers.Customer_Number=Payments.Customer_Number;
```

Q2:

```
SELECT Products.Product_Name, Order_details.Quantity_Ordered ,  
Order_details.Price_Each FROM Order_details INNER JOIN products ON  
Order_details.Product_Code=Products.Product_Code;
```

Q3:

```
SELECT Products.Product_Name, Product_lines.Product_Line FROM  
products Right JOIN Product_lines ON  
Products.Product_Line=Product_lines.Product_Line;
```

Q4:

```
SELECT Customers.Customer_Name, Orders.Order_Number FROM  
Customers inner JOIN orders ON  
Customers.Customer_Number=Orders.Customer_Number and  
Customers.Customer_Number=103;
```

*Zahir Ayub Khan:*

```
SELECT customers.customerNumber,customers.customerName,  
payments.checkNumber,payments.paymentDate, payments.amount FROM  
customers inner JOIN payments ON  
customers.customerNumber=payments.customerNumber;
```

Q2

```
SELECT products.productName, orderdetails.quantityOrdered ,  
orderdetails.priceEach FROM orderdetails INNER JOIN products ON  
orderdetails.productCode=products.productCode;
```

Q3

```
SELECT products.productName, productlines.productLine FROM products  
Right JOIN productlines ON products.productLine=productlines.productLine;
```

Q4

```
SELECT customers.customerName, orders.orderNumber FROM  
customers inner JOIN orders ON  
customers.customerNumber=orders.customerNumber and  
customers.customerNumber=103;
```

Jamal Khan:

Q1:

```
SELECT Customers.Customer_Number,Customers.Customer_Name,  
Payments.Check_Number,Payments.Payment_Date,  
Payments.Payments_amount FROM customers inner JOIN payments ON  
Customers.Customer_Number=Payments.Customer_Number;
```

Q2:

```
SELECT Products.Product_Name, Order_details.Quantity_Ordered ,  
Order_details.Price_Each FROM Order_details INNER JOIN products ON  
Order_details.Product_Code=Products.Product_Code;
```

Q3:

```
SELECT Products.Product_Name, Product_lines.Product_Line FROM  
products Right JOIN Product_lines ON  
Products.Product_Line=Product_lines.Product_Line;
```

Q4:

```
SELECT Customers.Customer_Name, Orders.Order_Number FROM  
Customers inner JOIN orders ON  
Customers.Customer_Number=Orders.Customer_Number and  
Customers.Customer_Number=103;
```

## Lab 14 Common Solution:

Q1 update employees set firstName='office number 6' where  
employeeNumber=1002;

Q2

update customers set customerName= 10124 where  
customerNumber=112;

Q3

select orderNumber, status from orders union select  
orderNumber,productCode from orderdetails;

Q4

select officecode from offices where officecode=5 union select  
officecode from employees where officecode=5;

*/\* Above work is Zahir Ayub Khan. Work Below Is Jamal Khan\*/*

Q1:

update employees set first\_Name='office number 6' where  
employee\_Number=1002;

Q2:

update customers set customer\_Name= 10124 where  
customer\_Number=112;

Q3:

select order\_Number, status from orders union select  
order\_Number,product\_Code from order\_details;

Q4:

select office\_code from offices where office\_code=5 union select  
office\_code from employees where office\_code=5;

*Zahir Ayub Khan:*

Q1 update employees set firstName='office number 6' where  
employeeNumber=1002;

Q2

update customers set customerName= 10124 where  
customerNumber=112;

Q3

```
select orderNumber, status from orders union select  
orderNumber,productCode from orderdetails;
```

Q4

```
select officecode from offices where officecode=5 union select  
officecode from employees where officecode=5;
```

Jamal Khan:

Q1:

```
update employees set first_Name='office number 6' where  
employee_Number=1002;
```

Q2:

```
update customers set customer_Name= 10124 where  
customer_Number=112;
```

Q3:

```
select order_Number, status from orders union select  
order_Number,product_Code from order_details;
```

Q4:

```
select office_code from offices where office_code=5 union select  
office_code from employees where office_code=5;
```

Lab 15 Common Solution:

Q1

```
update country set Name='Canada' where Code='ABW';
```

Q2

```
delete from city where id='2831' ;
```

Q3

```
update orders set comments='no longer null' where orderNumber=10100;
```

Q5

```
insert into customers  
values(90,'AliKhan','ahmad','Rana',03775645891,'E_11','jinanabad','Islamab  
ad','Punjab',4400,'Pak istan',1000,15000.00);
```

/\* Above work is Zahir Ayub Khan. Work Below is Jamal Khan\*/

Q1:

update country set Name='Dubai' where Code='ABC';

Q2:

delete from city where id='2211' ;

Q3:

update orders set comments='no longer null' where order\_Number=1122;

Q4:

insert into customers

values(11,'AftabAhmad','Khan','Ali',03558945685,'F\_10','Islamabad','Abbott  
abad','Sindh',4455,'Pakistan',1000,10000.00);

*Zahir Ayub Khan:*

Q1

update country set Name='Canada' where Code='ABW';

Q2

delete from city where id='2831' ;

Q3

update orders set comments='no longer null' where orderNumber=10100;

Q5

insert into customers

values(90,'AliKhan','ahmad','Rana',03775645891,'E\_11','jinanabad','Islamab  
ad','Punjab',4400,'Pak istan',1000,15000.00);

Jamal Khan:

Q1:

update country set Name='Dubai' where Code='ABC';

Q2:

delete from city where id='2211' ;

Q3:

update orders set comments='no longer null' where order\_Number=1122;

Q4:

insert into customers

values(11,'AftabAhmad','Khan','Ali',03558945685,'F\_10','Islamabad','Abbott  
abad','Sindh',4455,'Pakistan',1000,10000.00);

## Lab 16 Common Solution:

create database suppliers

```
Create table suppliers (supplier_id int(10) not null,  
supplier_name varchar(50),  
address varchar(50),  
primary key (supplier_id));  
Create table Item  
(itemname varchar(50) ,  
supplier_id int(10),  
itemprice int(10),  
FOREIGN KEY (supplier_id) REFERENCES suppliers(supplier_id) );
```

*/\* Above work is Zahir Ayub Khan. Work Below Is Jamal Khan\*/*

Create database Supplier

```
Create table supplier (supplier_id int(10) not null,  
Supplier_name varchar(50),  
Address varchar(50),  
Primary key (supplier_id));  
Create table Item  
(itemname varchar(50) ,  
supplier_id int(10),  
itemprice int(10),  
FOREIGN KEY (Supplier_id) REFERENCES Supplier(Supplier_id) );
```

*Zahir Ayub Khan:*

create database suppliers

```
Create table suppliers (supplier_id int(10) not null,  
supplier_name varchar(50),  
address varchar(50),  
primary key (supplier_id));  
Create table Item  
(itemname varchar(50) ,  
supplier_id int(10),  
itemprice int(10),  
FOREIGN KEY (supplier_id) REFERENCES suppliers(supplier_id) );
```

Jamal Khan:

```
Create database Supplier
Create table supplier (supplier_id int(10) not null,
Supplier_name varchar(50),
Address varchar(50),
Primary key (supplier_id));
Create table Item
(itemname varchar(50) ,
supplier_id int(10),
itemprice int(10),
FOREIGN KEY (Supplier_id) REFERENCES Supplier(Supplier_id) );
```

## Lab 18 Common Solution:

Q1

```
create view crust as
select customerNumber,customerName from customers;
update crust
set customerName='zahir khan'
where customerNumber=103;
```

Q2

```
create view duckgo as
select customerNumber,amount from payments;
select avg(amount) from duckgo;
select avg(amount) from duckgo where customerNumber <151 ;
```

*Zahir Ayub Khan:*

Q1

```
create view crust as
select customerNumber,customerName from customers;
update crust
set customerName='zahir khan'
where customerNumber=103;
```

Q2

```
create view duckgo as
select customerNumber,amount from payments;
select avg(amount) from duckgo;
select avg(amount) from duckgo where customerNumber <151 ;
```

Jamal Khan: