

Class 14: Pathway Analysis from RNA-Seq Results

Kaif Yenepoya (A17497464)

Table of contents

Overview	1
Section 1. Differential Expression Analysis	2
Q1. Complete the code to remove the troublesome first column from countData . . .	3
Q2. Filter countData to exclude genes where we have 0 read count across all samples	3
Running DESeq2	4
Q3. Call summary() on the DESeq2 results	6
Volcano Plot	6
Q4. Improve the volcano plot with color, axis labels, and cutoff lines	7
Adding Gene Annotation	8
Q5. Use mapIds() to add SYMBOL, ENTREZID, and GENENAME annotation . .	9
Q6. Reorder results by p-value and save them to a CSV file	10
Section 2. Pathway Analysis	10
Q7. Can you do the same procedure to plot the pathview figures for the top 5 down-regulated pathways?	14
Section 3. Gene Ontology Analysis	20
Section 4. Reactome Analysis	22
Q8. What pathway has the most significant Entities p-value? Do the most significant pathways listed match your previous KEGG results? What factors could cause differences between the two methods?	22
Final Interpretation	23
Session Information	23

Overview

In this lab, we analyze RNA-seq data from the GSE37704 dataset. This experiment studies lung fibroblasts after HOXA1 knockdown. We will use DESeq2 to find differentially expressed

genes, then use KEGG, Gene Ontology, and Reactome pathway analysis to understand the biological meaning of the gene expression changes.

Section 1. Differential Expression Analysis

Load DESeq2.

```
library(DESeq2)
```

Load our data files.

```
metaFile <- "GSE37704_metadata.csv"
countFile <- "GSE37704_featurecounts.csv"

colData <- read.csv(metaFile, row.names = 1)
head(colData)
```

```
      condition
SRR493366 control_sirna
SRR493367 control_sirna
SRR493368 control_sirna
SRR493369      hoxa1_kd
SRR493370      hoxa1_kd
SRR493371      hoxa1_kd
```

```
countData <- read.csv(countFile, row.names = 1)
head(countData)
```

	length	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370
ENSG00000186092	918	0	0	0	0	0
ENSG00000279928	718	0	0	0	0	0
ENSG00000279457	1982	23	28	29	29	28
ENSG00000278566	939	0	0	0	0	0
ENSG00000273547	939	0	0	0	0	0
ENSG00000187634	3214	124	123	205	207	212
SRR493371						
ENSG00000186092		0				
ENSG00000279928		0				
ENSG00000279457		46				
ENSG00000278566		0				
ENSG00000273547		0				
ENSG00000187634		258				

The count data has an extra `length` column that does not match the metadata samples, so we need to remove it.

Q1. Complete the code to remove the troublesome first column from `countData`

```
countData <- as.matrix(countData[, -1])  
head(countData)
```

	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370	SRR493371
ENSG00000186092	0	0	0	0	0	0
ENSG00000279928	0	0	0	0	0	0
ENSG00000279457	23	28	29	29	28	46
ENSG00000278566	0	0	0	0	0	0
ENSG00000273547	0	0	0	0	0	0
ENSG00000187634	124	123	205	207	212	258

I removed the first column using `-1` because the first column is the gene length column, not a sample count column.

Q2. Filter `countData` to exclude genes where we have 0 read count across all samples

```
countData <- countData[rowSums(countData) > 0, ]  
head(countData)
```

	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370	SRR493371
ENSG00000279457	23	28	29	29	28	46
ENSG00000187634	124	123	205	207	212	258
ENSG00000188976	1637	1831	2383	1226	1326	1504
ENSG00000187961	120	153	180	236	255	357
ENSG00000187583	24	48	65	44	48	64
ENSG00000187642	4	9	16	14	16	16

`rowSums(countData)` adds the counts across all samples for each gene. If the row sum is 0, that gene has no reads in any sample, so it should be removed.

Running DESeq2

Now we can set up the DESeqDataSet object and run the DESeq2 pipeline.

```
dds <- DESeqDataSetFromMatrix(countData = countData,  
                              colData = colData,  
                              design = ~ condition)
```

Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in design formula are characters, converting to factors

```
dds <- DESeq(dds)
```

estimating size factors

estimating dispersions

gene-wise dispersion estimates

mean-dispersion relationship

final dispersion estimates

fitting model and testing

```
dds
```

```
class: DESeqDataSet  
dim: 15975 6  
metadata(1): version  
assays(4): counts mu H cooks  
rownames(15975): ENSG00000279457 ENSG00000187634 ... ENSG00000276345  
               ENSG00000271254  
rowData names(22): baseMean baseVar ... deviance maxCooks  
colnames(6): SRR493366 SRR493367 ... SRR493370 SRR493371  
colData names(2): condition sizeFactor
```

Get the DESeq2 results.

```
res <- results(dds)
res
```

log2 fold change (MLE): condition hoxa1 kd vs control sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 15975 rows and 6 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.9136	0.1792571	0.3248215	0.551863	5.81042e-01
ENSG00000187634	183.2296	0.4264571	0.1402658	3.040350	2.36304e-03
ENSG00000188976	1651.1881	-0.6927205	0.0548465	-12.630156	1.43993e-36
ENSG00000187961	209.6379	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.2551	0.0405765	0.2718928	0.149237	8.81366e-01
...	...	...	...	...	...
ENSG00000273748	35.30265	0.674387	0.303666	2.220817	2.63633e-02
ENSG00000278817	2.42302	-0.388988	1.130394	-0.344118	7.30758e-01
ENSG00000278384	1.10180	0.332991	1.660261	0.200565	8.41039e-01
ENSG00000276345	73.64496	-0.356181	0.207716	-1.714752	8.63908e-02
ENSG00000271254	181.59590	-0.609667	0.141320	-4.314071	1.60276e-05
	padj				
	<numeric>				
ENSG00000279457	6.86555e-01				
ENSG00000187634	5.15718e-03				
ENSG00000188976	1.76553e-35				
ENSG00000187961	1.13413e-07				
ENSG00000187583	9.19031e-01				
...	...				
ENSG00000273748	4.79091e-02				
ENSG00000278817	8.09772e-01				
ENSG00000278384	8.92654e-01				
ENSG00000276345	1.39761e-01				
ENSG00000271254	4.53647e-05				

Check the result names.

```
resultsNames(dds)
```

```
[1] "Intercept" "condition_hoxa1_kd_vs_control_sirna"
```

Q3. Call `summary()` on the DESeq2 results

```
summary(res)
```

```
out of 15975 with nonzero total read count
adjusted p-value < 0.1
LFC > 0 (up)      : 4349, 27%
LFC < 0 (down)    : 4396, 28%
outliers [1]      : 0, 0%
low counts [2]    : 1237, 7.7%
(mean count < 0)
[1] see 'cooksCutoff' argument of ?results
[2] see 'independentFiltering' argument of ?results
```

The summary shows how many genes are up-regulated and down-regulated at the default adjusted p-value cutoff of 0.1. This helps us quickly see that HOXA1 knockdown caused many gene expression changes.

Volcano Plot

A volcano plot shows log2 fold change on the x-axis and statistical significance on the y-axis.


```
library(ggplot2)
```

Make a basic volcano plot.

```
res_df <- as.data.frame(res)

ggplot(res_df) +
  aes(x = log2FoldChange,
       y = -log(padj)) +
  geom_point()
```

Warning: Removed 1237 rows containing missing values or values outside the scale range (`geom\_point()`).



Q4. Improve the volcano plot with color, axis labels, and cutoff lines


```
mycols <- rep("gray", nrow(res_df))

mycols[abs(res_df$log2FoldChange) > 2] <- "blue"

mycols[res_df$padj > 0.01 | is.na(res_df$padj)] <- "gray"

ggplot(res_df) +
  aes(x = log2FoldChange,
      y = -log(padj)) +
  geom_point(color = mycols) +
  xlab("Log2(FoldChange)") +
  ylab("-Log(P-value)") +
  geom_vline(xintercept = c(-2, 2)) +
  geom_hline(yintercept = -log(0.01)) +
  ggtitle("Volcano Plot of Differential Expression")
```

Warning: Removed 1237 rows containing missing values or values outside the scale range (`geom\_point()`).



The improved volcano plot highlights genes with large fold changes and strong statistical significance. The blue points are the genes with large expression changes and low adjusted p-values, so these are like the most important genes to focus on.

Adding Gene Annotation

Since the results currently only have Ensembl gene IDs, we will add gene symbols, Entrez IDs, and gene names.

```
library(AnnotationDbi)
library(org.Hs.eg.db)
```

Check the available annotation columns.

```
columns(org.Hs.eg.db)
```

[1]	"ACCNUM"	"ALIAS"	"ENSEMBL"	"ENSEMBLPROT"	"ENSEMBLTRANS"
[6]	"ENTREZID"	"ENZYME"	"EVIDENCE"	"EVIDENCEALL"	"GENENAME"
[11]	"GENETYPE"	"GO"	"GOALL"	"IPI"	"MAP"
[16]	"OMIM"	"ONTOLOGY"	"ONTOLOGYALL"	"PATH"	"PFAM"
[21]	"PMID"	"PROSITE"	"REFSEQ"	"SYMBOL"	"UCSCKG"
[26]	"UNIPROT"				

Q5. Use mapIds() to add SYMBOL, ENTREZID, and GENENAME annotation

```
res$symbol <- mapIds(org.Hs.eg.db,  
  keys = row.names(res),  
  keytype = "ENSEMBL",  
  column = "SYMBOL",  
  multiVals = "first")
```

'select()' returned 1:many mapping between keys and columns

```
res$entrez <- mapIds(org.Hs.eg.db,  
  keys = row.names(res),  
  keytype = "ENSEMBL",  
  column = "ENTREZID",  
  multiVals = "first")
```

'select()' returned 1:many mapping between keys and columns

```
res$name <- mapIds(org.Hs.eg.db,  
  keys = row.names(res),  
  keytype = "ENSEMBL",  
  column = "GENENAME",  
  multiVals = "first")
```

'select()' returned 1:many mapping between keys and columns

```
head(res, 10)
```

log2 fold change (MLE): condition hoxa1 kd vs control sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 10 rows and 9 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.913579	0.1792571	0.3248215	0.551863	5.81042e-01
ENSG00000187634	183.229650	0.4264571	0.1402658	3.040350	2.36304e-03
ENSG00000188976	1651.188076	-0.6927205	0.0548465	-12.630156	1.43993e-36
ENSG00000187961	209.637938	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.255123	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.979750	0.5428105	0.5215598	1.040744	2.97994e-01

ENSG00000188290	108.922128	2.0570638	0.1969053	10.446970	1.51281e-25
ENSG00000187608	350.716868	0.2573837	0.1027266	2.505522	1.22271e-02
ENSG00000188157	9128.439422	0.3899088	0.0467164	8.346302	7.04333e-17
ENSG00000237330	0.158192	0.7859552	4.0804729	0.192614	8.47261e-01
	padj	symbol	entrez		name
	<numeric>	<character>	<character>		<character>
ENSG00000279457	6.86555e-01	NA	NA		NA
ENSG00000187634	5.15718e-03	SAMD11	148398	sterile alpha motif ..	
ENSG00000188976	1.76553e-35	NOC2L	26155	NOC2 like nucleolar ..	
ENSG00000187961	1.13413e-07	KLHL17	339451	kelch like family me..	
ENSG00000187583	9.19031e-01	PLEKHN1	84069	pleckstrin homology ..	
ENSG00000187642	4.03379e-01	PERM1	84808	PPARGC1 and ESRR ind..	
ENSG00000188290	1.30538e-24	HES4	57801	hes family bHLH tran..	
ENSG00000187608	2.37452e-02	ISG15	9636	ISG15 ubiquitin like..	
ENSG00000188157	4.21970e-16	AGRN	375790		agrin
ENSG00000237330	NA	RNF223	401934	ring finger protein ..	

The annotation step adds more useful gene information to the DESeq2 results. This is important because pathway analysis uses Entrez gene IDs, and gene symbols/names make the results easier to understand.

Q6. Reorder results by p-value and save them to a CSV file

```
res <- res[order(res$pvalue), ]
write.csv(res, file = "deseq_results.csv")
```

The results are now ordered by p-value and saved as `deseq_results.csv` in the project folder.

Section 2. Pathway Analysis

Now we will use the `gage` package for KEGG pathway analysis and `pathview` to draw pathway diagrams. This helps us understand which biological pathways are changing, instead of only looking at individual genes.

```
library(pathview)
library(gage)
library(gageData)
```

Load the KEGG pathway datasets.

```
data(kegg.sets.hs)
data(sigmet.idx.hs)

kegg.sets.hs <- kegg.sets.hs[sigmet.idx.hs]

head(kegg.sets.hs, 3)
```

\$`hsa00232 Caffeine metabolism`

```
[1] "10"    "1544" "1548" "1549" "1553" "7498" "9"
```

\$`hsa00983 Drug metabolism - other enzymes`

```
[1] "10"    "1066" "10720" "10941" "151531" "1548" "1549" "1551"
[9] "1553" "1576" "1577" "1806" "1807" "1890" "221223" "2990"
[17] "3251" "3614" "3615" "3704" "51733" "54490" "54575" "54576"
[25] "54577" "54578" "54579" "54600" "54657" "54658" "54659" "54963"
[33] "574537" "64816" "7083" "7084" "7172" "7363" "7364" "7365"
[41] "7366" "7367" "7371" "7372" "7378" "7498" "79799" "83549"
[49] "8824" "8833" "9" "978"
```

\$`hsa00230 Purine metabolism`

```
[1] "100"    "10201" "10606" "10621" "10622" "10623" "107" "10714"
[9] "108"    "10846" "109" "111" "11128" "11164" "112" "113"
[17] "114"    "115" "122481" "122622" "124583" "132" "158" "159"
[25] "1633" "171568" "1716" "196883" "203" "204" "205" "221823"
[33] "2272" "22978" "23649" "246721" "25885" "2618" "26289" "270"
[41] "271" "27115" "272" "2766" "2977" "2982" "2983" "2984"
[49] "2986" "2987" "29922" "3000" "30833" "30834" "318" "3251"
[57] "353" "3614" "3615" "3704" "377841" "471" "4830" "4831"
[65] "4832" "4833" "4860" "4881" "4882" "4907" "50484" "50940"
[73] "51082" "51251" "51292" "5136" "5137" "5138" "5139" "5140"
[81] "5141" "5142" "5143" "5144" "5145" "5146" "5147" "5148"
[89] "5149" "5150" "5151" "5152" "5153" "5158" "5167" "5169"
[97] "51728" "5198" "5236" "5313" "5315" "53343" "54107" "5422"
[105] "5424" "5425" "5426" "5427" "5430" "5431" "5432" "5433"
[113] "5434" "5435" "5436" "5437" "5438" "5439" "5440" "5441"
[121] "5471" "548644" "55276" "5557" "5558" "55703" "55811" "55821"
[129] "5631" "5634" "56655" "56953" "56985" "57804" "58497" "6240"
[137] "6241" "64425" "646625" "654364" "661" "7498" "8382" "84172"
[145] "84265" "84284" "84618" "8622" "8654" "87178" "8833" "9060"
[153] "9061" "93034" "953" "9533" "954" "955" "956" "957"
```

```
[161] "9583"    "9615"
```

Create a named vector of fold changes. The values are the DESeq2 log2 fold changes, and the names are the Entrez gene IDs.

```
foldchanges <- res$log2FoldChange
names(foldchanges) <- res$entrez

head(foldchanges)
```

```
      1266      54855      1465      2034      2150      6659
-2.422719  3.201955 -2.313738 -1.888019  3.344508  2.392288
```

Run the GAGE pathway analysis.

```
keggres <- gage(foldchanges, gsets = kegg.sets.hs)

attributes(keggres)
```

```
$names
[1] "greater" "less"    "stats"
```

Look at the top down-regulated pathways.

```
head(keggres$less)
```

	p.geomean	stat.mean	p.val
hsa04110 Cell cycle	8.995727e-06	-4.378644	8.995727e-06
hsa03030 DNA replication	9.424076e-05	-3.951803	9.424076e-05
hsa03013 RNA transport	1.375901e-03	-3.028500	1.375901e-03
hsa03440 Homologous recombination	3.066756e-03	-2.852899	3.066756e-03
hsa04114 Oocyte meiosis	3.784520e-03	-2.698128	3.784520e-03
hsa00010 Glycolysis / Gluconeogenesis	8.961413e-03	-2.405398	8.961413e-03

	q.val	set.size	exp1
hsa04110 Cell cycle	0.001448312	121	8.995727e-06
hsa03030 DNA replication	0.007586381	36	9.424076e-05
hsa03013 RNA transport	0.073840037	144	1.375901e-03
hsa03440 Homologous recombination	0.121861535	28	3.066756e-03
hsa04114 Oocyte meiosis	0.121861535	102	3.784520e-03
hsa00010 Glycolysis / Gluconeogenesis	0.212222694	53	8.961413e-03

Look at the top up-regulated pathways.

```
head(keggres$greater)
```

	p.geomean	stat.mean	p.val
hsa04640 Hematopoietic cell lineage	0.002822776	2.833362	0.002822776
hsa04630 Jak-STAT signaling pathway	0.005202070	2.585673	0.005202070
hsa00140 Steroid hormone biosynthesis	0.007255099	2.526744	0.007255099
hsa04142 Lysosome	0.010107392	2.338364	0.010107392
hsa04330 Notch signaling pathway	0.018747253	2.111725	0.018747253
hsa04916 Melanogenesis	0.019399766	2.081927	0.019399766

	q.val	set.size	exp1
hsa04640 Hematopoietic cell lineage	0.3893570	55	0.002822776
hsa04630 Jak-STAT signaling pathway	0.3893570	109	0.005202070
hsa00140 Steroid hormone biosynthesis	0.3893570	31	0.007255099
hsa04142 Lysosome	0.4068225	118	0.010107392
hsa04330 Notch signaling pathway	0.4391731	46	0.018747253
hsa04916 Melanogenesis	0.4391731	90	0.019399766

The top down-regulated pathways are expected to include cell cycle-related pathways. This makes sense because HOXA1 is connected to cell cycle progression.

Plot the Cell Cycle pathway.

```
pathview(gene.data = foldchanges, pathway.id = "hsa04110")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/kaifyenepoya/Desktop/BIMM143/LAB_14

Info: Writing image file hsa04110.pathview.png

Add the Cell Cycle pathway image to the report.


```
down.ids <- substr(down.pathways, start = 1, stop = 8)
down.ids
```

```
[1] "hsa04110" "hsa03030" "hsa03013" "hsa03440" "hsa04114"
```

Use `pathview()` to draw the top 5 down-regulated pathway figures.

```
pathview(gene.data = foldchanges, pathway.id = down.ids, species = "hsa")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/kaifyenepoya/Desktop/BIMM143/LAB_14

Info: Writing image file hsa04110.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/kaifyenepoya/Desktop/BIMM143/LAB_14

Info: Writing image file hsa03030.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/kaifyenepoya/Desktop/BIMM143/LAB_14

Info: Writing image file hsa03013.pathview.png

'select()' returned 1:1 mapping between keys and columns


Info: Working in directory /Users/kaifyenepoya/Desktop/BIMM143/LAB_14

Info: Writing image file hsa03440.pathview.png

'select()' returned 1:1 mapping between keys and columns



Info: Working in directory /Users/kaifyenepoya/Desktop/BIMM143/LAB_14

Add the pathway images to the report.





DNA REPLICATION



Replication complex (Bacteria)




Replication complex (Archaea)



Replication complex (Eukaryotes)



Data on KEGG graph
Rendered by Pathview



Run GAGE analysis on Biological Process GO terms.

```
gobpres <- gage(foldchanges, gsets = gobpsets)

lapply(gobpres, head)
```

\$greater

	p.geomean	stat.mean	p.val
G0:0007156 homophilic cell adhesion	8.519724e-05	3.824205	8.519724e-05
G0:0002009 morphogenesis of an epithelium	1.396681e-04	3.653886	1.396681e-04
G0:0048729 tissue morphogenesis	1.432451e-04	3.643242	1.432451e-04
G0:0007610 behavior	1.925222e-04	3.565432	1.925222e-04
G0:0060562 epithelial tube morphogenesis	5.932837e-04	3.261376	5.932837e-04
G0:0035295 tube development	5.953254e-04	3.253665	5.953254e-04

	q.val	set.size	exp1
G0:0007156 homophilic cell adhesion	0.1951953	113	8.519724e-05
G0:0002009 morphogenesis of an epithelium	0.1951953	339	1.396681e-04
G0:0048729 tissue morphogenesis	0.1951953	424	1.432451e-04
G0:0007610 behavior	0.1967577	426	1.925222e-04
G0:0060562 epithelial tube morphogenesis	0.3565320	257	5.932837e-04
G0:0035295 tube development	0.3565320	391	5.953254e-04

\$less

	p.geomean	stat.mean	p.val
G0:0048285 organelle fission	1.536227e-15	-8.063910	1.536227e-15
G0:0000280 nuclear division	4.286961e-15	-7.939217	4.286961e-15
G0:0007067 mitosis	4.286961e-15	-7.939217	4.286961e-15
G0:0000087 M phase of mitotic cell cycle	1.169934e-14	-7.797496	1.169934e-14
G0:0007059 chromosome segregation	2.028624e-11	-6.878340	2.028624e-11
G0:0000236 mitotic prometaphase	1.729553e-10	-6.695966	1.729553e-10

	q.val	set.size	exp1
G0:0048285 organelle fission	5.841698e-12	376	1.536227e-15
G0:0000280 nuclear division	5.841698e-12	352	4.286961e-15
G0:0007067 mitosis	5.841698e-12	352	4.286961e-15
G0:0000087 M phase of mitotic cell cycle	1.195672e-11	362	1.169934e-14
G0:0007059 chromosome segregation	1.658603e-08	142	2.028624e-11
G0:0000236 mitotic prometaphase	1.178402e-07	84	1.729553e-10

\$stats

	stat.mean	exp1
G0:0007156 homophilic cell adhesion	3.824205	3.824205
G0:0002009 morphogenesis of an epithelium	3.653886	3.653886

GO:0048729	tissue morphogenesis	3.643242	3.643242
GO:0007610	behavior	3.565432	3.565432
GO:0060562	epithelial tube morphogenesis	3.261376	3.261376
GO:0035295	tube development	3.253665	3.253665

The GO results show enriched biological processes. The down-regulated GO terms are related to M phase, organelle fission, nuclear division, mitosis, and chromosome segregation. This matches the KEGG results because both show that cell cycle and cell division processes are strongly affected by HOXA1 knockdown.

Section 4. Reactome Analysis

Now we will create a plain text file of significant genes at the adjusted p-value 0.05 level. This file can be uploaded to Reactome for online pathway analysis.

```
sig_genes <- res[res$padj <= 0.05 & !is.na(res$padj), "symbol"]
print(paste("Total number of significant genes:", length(sig_genes)))
```

```
[1] "Total number of significant genes: 8147"
```

```
write.table(sig_genes,
            file = "significant_genes.txt",
            row.names = FALSE,
            col.names = FALSE,
            quote = FALSE)
```

The file `significant_genes.txt` is now saved in the project folder. This file can be uploaded to Reactome.

Q8. What pathway has the most significant Entities p-value? Do the most significant pathways listed match your previous KEGG results? What factors could cause differences between the two methods?

The most significant Reactome pathway is related to cell cycle regulation, especially mitotic cell cycle and DNA replication. This matches the KEGG results because KEGG also showed Cell cycle and DNA replication as top affected pathways. Differences between Reactome and KEGG can happen because they use different pathway databases, pathway definitions, gene annotations, and statistical methods.

Final Interpretation

Overall, the DESeq2 results show that HOXA1 knockdown caused many gene expression changes. The pathway results strongly point toward changes in cell cycle, DNA replication, mitosis, and chromosome segregation. This supports the idea that HOXA1 is important for cell cycle progression in lung fibroblasts.

Session Information

```
sessionInfo()
```

```
R version 4.5.3 (2026-03-11)
Platform: aarch64-apple-darwin20
Running under: macOS Sonoma 14.4.1
```

```
Matrix products: default
```

```
BLAS: /Library/Frameworks/R.framework/Versions/4.5-arm64/Resources/lib/libRblas.0.dylib
```

```
LAPACK: /Library/Frameworks/R.framework/Versions/4.5-arm64/Resources/lib/libRlapack.dylib;
```

```
locale:
```

```
[1] en_US.UTF-8/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8
```

```
time zone: America/Los_Angeles
```

```
tzcode source: internal
```

```
attached base packages:
```

```
[1] stats4      stats      graphics  grDevices  utils      datasets  methods
[8] base
```

```
other attached packages:
```

```
[1] gageData_2.48.0          gage_2.60.0
[3] pathview_1.50.0          org.Hs.eg.db_3.22.0
[5] AnnotationDbi_1.72.0     ggplot2_4.0.2
[7] DESeq2_1.50.2            SummarizedExperiment_1.40.0
[9] Biobase_2.70.0           MatrixGenerics_1.22.0
[11] matrixStats_1.5.0        GenomicRanges_1.62.1
[13] Seqinfo_1.0.0            IRanges_2.44.0
[15] S4Vectors_0.48.1        BiocGenerics_0.56.0
[17] generics_0.1.4
```

loaded via a namespace (and not attached):

[1] KEGGREST_1.50.0	gtable_0.3.6	xfun_0.57
[4] lattice_0.22-9	bitops_1.0-9	vctrs_0.7.2
[7] tools_4.5.3	parallel_4.5.3	tibble_3.3.1
[10] RSQLite_3.52.0	blob_1.3.0	pkgconfig_2.0.3
[13] Matrix_1.7-4	RColorBrewer_1.1-3	S7_0.2.1
[16] graph_1.88.1	lifecycle_1.0.5	compiler_4.5.3
[19] farver_2.1.2	Biostrings_2.78.0	codetools_0.2-20
[22] htmltools_0.5.9	RCurl_1.98-1.18	yaml_2.3.12
[25] GO.db_3.22.0	pillar_1.11.1	crayon_1.5.3
[28] BiocParallel_1.44.0	DelayedArray_0.36.1	cachem_1.1.0
[31] abind_1.4-8	tidyselect_1.2.1	locfit_1.5-9.12
[34] digest_0.6.39	dplyr_1.2.1	labeling_0.4.3
[37] fastmap_1.2.0	grid_4.5.3	cli_3.6.5
[40] SparseArray_1.10.10	magrittr_2.0.5	S4Arrays_1.10.1
[43] XML_3.99-0.23	withr_3.0.2	scales_1.4.0
[46] bit64_4.8.0	rmarkdown_2.31	XVector_0.50.0
[49] httr_1.4.8	bit_4.6.0	png_0.1-9
[52] memoise_2.0.1	evaluate_1.0.5	knitr_1.51
[55] rlang_1.2.0	Rcpp_1.1.1	glue_1.8.0
[58] DBI_1.3.0	Rgraphviz_2.54.0	KEGGgraph_1.70.0
[61] jsonlite_2.0.0	R6_2.6.1	