

class 5 Data Viz with ggplot 2

Kaif (A17497464)

Table of contents

Background	1
Add some custom features	4
Gene expression figure	6
Going Further	7

Background

There are many graphic systems in R for making plots and figures. These include so-called “*base R graphics*” like the ‘plot()’ function and add on packages like **ggplot2**.


lets compare how we make a simple figure with these two systems:

We can use the in-built ‘cars’ dataset:

```
head( cars )
```

```
  speed dist
1     4    2
2     4   10
3     7    4
4     7   22
5     8   16
6     9   10
```

```
plot(cars)
```




Before I can use ggplot2 I need to install it on my computer. To do this we can use the function `install.packages("ggplot2")`

N.B. We never run `install.packages()` in our quarto doc (we run it once only in our R console) as it would re-install the package every time we render it. The main function in the **ggplot2** package is called `ggplot()`

Once installed we need to load up the package into our R brain:

```
library(ggplot2)
```


```
ggplot(cars)
```



Every ggplot has at least 3 layers:

- the **data** (a data.frame of the stuff we want to plot)
- the **aesthetics** (how the data maps to the plot)
- the **geom** layer (how we want the plot drawn, e.g. points, lines, etc.)

```
ggplot(cars) +  
  aes(x=speed , y=dist)+  
  geom_point()
```




Add some custom features

Let's add a trend line that shows the relationship between speed and distance.


```
ggplot(cars) +  
  aes(x=speed , y=dist)+  
  geom_point() +  
  geom_smooth() +  
  theme_bw() +  
  labs(title= "Stopping Dist Of Old Cars" ,  
        x= "Speed (MPH)" ,  
        y= "Distance (ft)")
```

``geom_smooth()`` using `method = 'loess'` and `formula = 'y ~ x'`



```
ggplot(cars) +  
  aes(x=speed , y=dist)+  
  geom_point() +  
  geom_smooth(method= "lm", se= FALSE) +  
  theme_bw() +  
  labs(title= "Stopping Dist Of Old Cars" ,  
        x= "Speed (MPH)" ,  
        y= "Distance (ft)")
```

``geom_smooth()`` using formula = `'y ~ x'`



Q. Can you make the 'geom_smooth()' function produce a linear straight line fit to the data and turn off the "gray" error region.

Gene expression figure

Import the data to plot

```
url <- "https://bioboot.github.io/bimm143_S20/class-material/up_down_expression.txt"
genes <- read.delim(url)
head(genes)
```

	Gene	Condition1	Condition2	State
1	A4GNT	-3.6808610	-3.4401355	unchanging
2	AAAS	4.5479580	4.3864126	unchanging
3	AASDH	3.7190695	3.4787276	unchanging
4	AATF	5.0784720	5.0151916	unchanging
5	AATK	0.4711421	0.5598642	unchanging
6	AB015752.4	-3.6808610	-3.5921390	unchanging

```
sum(genes$State == "up")
```

```
[1] 127
```


A useful new function in this context is the 'table()' function:

```
table(genes$State)
```

```
down  unchanging    up
   72      4997    127
```

My first plot attempt

```
ggplot(genes) +  
  aes(Condition1, Condition2, col = State) +  
  geom_point() +  
  scale_color_manual(values = c("purple", "gray", "orange")) +  
  theme_bw() +  
  labs(x = "No drug", y = "Drug",  
       title = "Expression changes upon GLP-1 inhibitor treatment")
```



Going Further

Here we read the famous gapminder dataset

```
# File location online
url <- "https://raw.githubusercontent.com/jennybc/gapminder/master/inst/extdata/gapminder.tsv"

gapminder <- read.delim(url)
head(gapminder)
```

	country	continent	year	lifeExp	pop	gdpPercap
1	Afghanistan	Asia	1952	28.801	8425333	779.4453
2	Afghanistan	Asia	1957	30.332	9240934	820.8530
3	Afghanistan	Asia	1962	31.997	10267083	853.1007
4	Afghanistan	Asia	1967	34.020	11537966	836.1971
5	Afghanistan	Asia	1972	36.088	13079460	739.9811
6	Afghanistan	Asia	1977	38.438	14880372	786.1134

Q. How many entries (i.e. rows) are in this dataset

```
nrow(gapminder)
```

```
[1] 1704
```

Q. How many different “country” entries are in this dataset?

```
length(table(gapminder$country) )
```

```
[1] 142
```

```
length (unique(gapminder$country))
```

```
[1] 142
```


Lets’s make our first plot of the entire dataset:

Plot of “gdpPercap” vs “lifeExp” colored by “continent”

```
p <- ggplot(gapminder) +
  aes(gdpPercap, lifeExp, col = continent) +
  geom_point(alpha = 0.3)
```

I can add more layers to ‘p’


```
p +  
  facet_wrap(~continent)
```



Make a plot for 1977 and 2007 only (not all the years in the dataset)

Q. First use the **dplyr** package and the 'filter()' function from that package to extract the rows from the year 2007.

```
library(dplyr)
```


```
gap2007 <- filter(gapminder, year == 2007)
```

```
gap_77_07 <- filter(gapminder, year %in% c(1977, 2007))
```

```
table(gap_77_07$year)
```

```
1977 2007  
142  142
```


```
ggplot(gap_77_07) +
  aes(gdpPercap, lifeExp, col = continent) +
  geom_point(alpha = 0.3) +
  facet_wrap(~year)
```



Q. Make a histogram of lifeExp colored by continent (try using fill=continent or "col=continent") Q. Make a histogram of lifeExp faceted by continent


```
ggplot(gapminder)+
  aes(lifeExp) +
  geom_histogram()
```

`stat\_bin()` using `bins = 30`. Pick better value `binwidth`.




```
ggplot(gapminder) +  
  aes(lifeExp, fill = continent) +  
  geom_histogram()
```

``stat_bin()`` using ``bins = 30``. Pick better value ``binwidth``.



```
ggplot(gapminder) +  
  aes(lifeExp) +  
  geom_histogram() +  
  facet_wrap(~continent)
```

``stat_bin()`` using ``bins = 30``. Pick better value ``binwidth``.



```
ggplot(gapminder) +
  aes(lifeExp, fill = continent) +
  geom_histogram(alpha = 0.6, position = "identity")
```

`stat\_bin()` using `bins = 30`. Pick better value `binwidth`.

