# Updated Route File Responsibilities (Backend)

## 1️⃣ `authRoutes.js`

**Purpose:**
Handles authentication and basic user account operations.

**When to put routes here:**

- User login
- User registration
- Profile updates
- Password changes
- Uploading profile pictures
- Fetching user info
- Fetching users

**Example endpoints**

POST /api/auth/register
POST /api/auth/login
GET  /api/auth/user/:id
GET  /api/auth/users
POST /api/auth/change-password
POST /api/auth/update-profile
POST /api/auth/upload-pfp

**Rule of thumb:**
If the feature involves logging in or managing the general user account, it belongs here.

---

## 2️⃣ adminRoutes.js

**Purpose:**
Handles system administration features.

These routes are used by the admin dashboard.

**When to put routes here:**

- Approving issuers
- Rejecting issuers
- Enabling/disabling issuers
- Enabling/disabling users
- Viewing system logs
- Viewing issuer lists
- Managing subordinate approvals
- Triggering admin-only maintenance actions

**Example endpoints**

GET /api/admin/pending-issuers
GET /api/admin/approved-issuers
POST /api/admin/approve-issuer/:issuerId
POST /api/admin/reject-issuer/:issuerId
POST /api/admin/disable-issuer/:issuerId
POST /api/admin/enable-user/:userId
GET /api/admin/status-logs
POST /api/admin/trigger-expiry-check

**Rule of thumb:**
If the feature is only accessible from the Admin Dashboard or is an admin-only action, it belongs here.

---

## 3️⃣ issuerRoutes.js

**Purpose:**
Handles issuer-specific operations.

Used by issuer dashboards, including root authorities and subordinates.

**When to put routes here:**

- Issuer registration
- Issuer login
- Issuer document viewing
- Checking issuer requirements
- Fetching issuer credentials
- Creating credential templates
- Viewing eligible users
- Viewing issuer credential history

**Example endpoints**

POST /api/issuer/register
POST /api/issuer/login
GET /api/issuer/issuer-requirements/:category
GET /api/issuer/issuer/:issuerId/documents
GET /api/issuer/issuer/templates/:templateId/eligible-users
POST /api/issuer/credentials/create
GET /api/issuer/credentials/history

**Rule of thumb:**
If the feature is something an issuer does or something tied to issuer onboarding/dashboard behavior, it belongs here.

---

## 4️⃣ `credentialRoutes.js`

**Purpose:**
Handles the credential lifecycle.

This file now focuses only on credential-related operations, not wallet UI behavior.

**When to put routes here:**

- Issuing credentials
- Revoking credentials
- Fetching credential templates
- Fetching issued credentials
- Fetching credential history
- Credential verification actions tied directly to a credential ID

**Example endpoints**

GET /api/credentials/templates
GET /api/credentials/issued
POST /api/credentials/:credentialId/issue
POST /api/credentials/:credentialId/revoke
GET /api/credentials/:credentialId/history
GET /api/credentials/:credentialId/verify
POST /api/credentials/:credentialId/log-verification

**Rule of thumb:**
If the route directly manipulates or reads the credential itself, it belongs here.

---

## 5️⃣ walletRoutes.js

**Purpose:**
Handles student wallet-specific operations.

This is for wallet display/state management, not credential issuance logic.

**When to put routes here:**

- Fetching a student's wallet credentials
- Updating credential visibility

- Updating credential display order

**Example endpoints**

GET /api/wallet/credentials/:holderID
PATCH /api/wallet/visibility/:credentialId
PATCH /api/wallet/order/:credentialId

**Rule of thumb:**
If the feature is specifically about how credentials appear or behave in the student wallet UI, it belongs here.

---

## 6️⃣ `verificationRoutes.js`

**Purpose:**
Handles credential verification.

Used by verifiers and public verification systems.

**When to put routes here:**

- Verifying credentials
- Fetching verification logs
- Verification statistics

**Example endpoints**

GET /api/verify/verify/:credentialID
POST /api/verify/verify
GET /api/verify/verification-logs
GET /api/verify/verification-logs/:logId
GET /api/verify/verify-stats

**Rule of thumb:**
If the feature involves checking whether a credential is valid, it belongs here.

---

## 7️⃣ `systemRoutes.js`

**Purpose:**
Handles system-level endpoints.

Currently used for server health checks.

**Example endpoint**

GET /api/health

**Rule of thumb:**
Used for diagnostics, health checks, or server monitoring — not application business logic.

---

# Quick Mental Model

Think of your routes like departments:

| Route File | Department |
|---|---|
| `authRoutes` | User Accounts / Login |
| `adminRoutes` | Platform Administration |
| `issuerRoutes` | Issuer Management / Onboarding |
| `credentialRoutes` | Credential Lifecycle |
| `walletRoutes` | Student Wallet |
| `verificationRoutes` | Credential Verification |
| `systemRoutes` | System Health |

---

# Example: Where should a new endpoint go?

**Feature:**
Admin wants to download a list of disabled issuers
➡ `adminRoutes.js`

**Feature:**
Issuer wants to create a new credential template
➡ `issuerRoutes.js`

**Feature:**
Student wants to hide a credential from their wallet
➡ `walletRoutes.js`

**Feature:**
Verifier scans a QR code and checks credential validity
➡ `verificationRoutes.js`

**Feature:**
Issuer wants to revoke a credential
➡ `credentialRoutes.js`