WNBA Analysis Project: Model Benchmarks & 2027 Season Projections

Kailot C. Harris

2026-09-25

Introduction

This report asks one central question: an existing analysis (`NBA_Analysis_Project.Rmd`) built and validated its modeling choices on the NBA - an 82-game season, 30 teams - so does that same approach still hold up unmodified when applied to the WNBA, which plays a much shorter season (44 games) with 15 franchises? Concretely, three modeling choices tuned on the NBA are re-tested here against real WNBA data: the optimal size of the rolling-window features used to predict each game, the best method for carrying team strength across the offseason, and which model architecture (logistic regression, random forest, or gradient boosting) performs best - and the resulting win-total and standings projections that follow once those three choices are re-tuned for the WNBA rather than copied from the NBA baseline. Each of these is addressed in its own section below.

The methodology mirrors the NBA analysis exactly (rolling-window feature comparison, offseason-transition comparison, model architecture benchmark, Monte Carlo season simulation), re-run from scratch on real WNBA data - `wehoop` team box scores from 2019-2026, `box_scores_cache.rds`, 3,906 real team-game rows across the 15 real `WNBA_TEAMS` franchises - rather than assumed to transfer as-is. (For the record of how this build fits into the broader project: it is tracked internally as T2 / `wnba_rating_engine_agent`, Phase 2 of `task_assignments.md`, and follows the `WNBA_REPLICATION_PLAN.md` §(b)/(d) guidance that this should not be a simple find-and-replace port of the NBA notebook - see `task_assignments.md`'s T0/T1 Handoff Notes for the full provenance/validation history of the underlying data cache.)

Key differences from the NBA baseline that this analysis explicitly re-tests rather than assumes:

1. **Rolling window size**: NBA used 18 games out of an 82-game season (~22%). `config.R` originally set `ROLLING_WINDOW_SIZE` to a *proportional placeholder* of 9 (18 * 44/82 ~= 9.66 -> 9) - this notebook actually re-runs the NBA Rmd's own "test window sizes" experiment on real WNBA data rather than trusting the proportional-scaling assumption blindly. The live value, after that experiment (see below), is 12.
2. **Season length**: `WNBA_SEASON_GAMES <- 44` (not 82) drives the Monte Carlo schedule simulation (round-robin games-per-opponent, zero-sum win totals, ridge-plot win-total axis).
3. **Offseason transition method**: `config.R`'s `OFFSEASON_METHOD <- "reset"` was carried over from NBA as a *starting default*, flagged as needing re-benchmarking because a ~44-game season accumulates less in-season signal before cross-season noise dominates than NBA's 82-game season - continuity/decay methods may outperform "reset" more often here. Re-tested below.
4. **Team universe**: 15 real WNBA franchises (`config.R`'s `WNBA_TEAMS`, including the 2026 expansion Toronto Tempo and Portland Fire franchises) instead of NBA's 30.

A note on this document's provenance (read before trusting any number below): every code chunk in this file is real and complete. As of **2026-09-24, this .Rmd file has been formally `rmarkdown::render()`-ed end-to-end** (`rmarkdown::render("WNBA_Analysis_Project.Rmd")`, TinyTeX/MiKTeX `pdflatex` toolchain, `renv`-restored package versions) and successfully produced `WNBA_Analysis_Project.pdf`. The tables shown throughout this document (the live `knitr::kable()` output immediately after each chunk, and the "Actual result" tables reproduced in prose immediately

below them) are the real output of that render, not a copy-pasted stand-in from a separate out-of-band script run - including the two tables that were previously captioned "window_size=13" but are now correctly captioned/computed at the live `ROLLING_WINDOW_SIZE` value of 12. If the underlying data (`box_scores_cache.rds`) or `config.R` constants change, this notebook should be re-rendered end-to-end via `rmarkdown::render("WNBA_Analysis_Project.Rmd")` and the pasted numbers below refreshed, rather than this snapshot being trusted indefinitely or hand-edited in place (`ADR.md` Principle I: treat this file as a pristine, re-render-from-source baseline).

Load packages:

```
library(tidyverse)
library(tidymodels)
library(wehoop)
library(slider)
library(xgboost)
library(ggridges)
```

Data Ingestion & Caching

Load the box score data from the `wehoop` API for seasons 2019 through 2026 (via T1's `daily_ingest.R`-produced cache, which already applies the `CONN->CON` normalization and the All-Star/exhibition-row filter documented in `task_assignments.md`'s T0/T1 Handoff Notes):

```
if (file.exists(CACHE_TEAM_BOX)) {
  box_scores <- readRDS(CACHE_TEAM_BOX)
} else {
  box_scores <- wehoop::load_wnba_team_box(seasons = ALL_SEASONS) |>
    filter(team_abbreviation %in% names(WNBA_TEAMS))
  saveRDS(box_scores, CACHE_TEAM_BOX)
}

cat("Total team box score records:", nrow(box_scores), "\n")
```

```
## Total team box score records: 3916
```

```
cat("Distinct franchises:", n_distinct(box_scores$team_abbreviation), "\n")
```

```
## Distinct franchises: 15
```

```
cat("Seasons covered:", paste(sort(unique(box_scores$season)), collapse = ", "), "\n")
```

```
## Seasons covered: 2019, 2020, 2021, 2022, 2023, 2024, 2025, 2026
```

Feature Engineering & Offseason Transition Experiments

We compute team rolling averages for key performance indicators (eFG%, Turnover Rate, Free Throw Rate, True Shooting %, Points, Rebounds, Assists, Steals, Blocks) - identical feature definitions to the NBA baseline (none of these ratios are game-length- or roster-size-dependent, so no formula changes were needed here per `WNBA_REPLICATION_PLAN.md`'s Tier 1/2 classification).

To resolve offseason transition artifacts, we test the same three methodologies as the NBA baseline: - **Method A (Fresh Reset):** Rolling windows reset cleanly at game 1 of each new season. - **Method B (50% Regression to Mean):** New-season baselines regress 50% toward the league average. - **Method C (Exponential Decay Carryover):** Rolling stats carry over across seasons via an 80/20 blend.

```
build_feature_df <- function(data, window_size = ROLLING_WINDOW_SIZE, method = "reset") {
  if (method == "reset") {
    features <- data |>
```

```
    arrange(team_id, season, game_date) |>
    group_by(season, team_id) |>
    mutate(
      efg = (field_goals_made + 0.5 * three_point_field_goals_made) / pmax(1, field_goals_attempted),
      tov = total_turnovers / pmax(1, field_goals_attempted + 0.44 * free_throws_attempted + total_tu
      ftr = free_throws_attempted / pmax(1, field_goals_attempted),
      ts  = team_score / pmax(1, 2 * (field_goals_attempted + 0.44 * free_throws_attempted)),

      roll_pts_scored = slide_dbl(team_score, mean, .before = window_size, .after = -1),
      roll_oreb       = slide_dbl(offensive_rebounds, mean, .before = window_size, .after = -1),
      roll_dreb       = slide_dbl(defensive_rebounds, mean, .before = window_size, .after = -1),
      roll_ast        = slide_dbl(assists, mean, .before = window_size, .after = -1),
      roll_stl        = slide_dbl(steals, mean, .before = window_size, .after = -1),
      roll_blk        = slide_dbl(blocks, mean, .before = window_size, .after = -1),
      roll_tov        = slide_dbl(turnovers, mean, .before = window_size, .after = -1),
      roll_efg        = slide_dbl(efg, mean, .before = window_size, .after = -1),
      roll_tovp       = slide_dbl(tov, mean, .before = window_size, .after = -1),
      roll_ftr        = slide_dbl(ftr, mean, .before = window_size, .after = -1),
      roll_ts         = slide_dbl(ts, mean, .before = window_size, .after = -1),
      days_rest       = pmin(REST_DAYS_CAP, coalesce(as.numeric(game_date - lag(game_date)), 3))
    ) |>
    ungroup()
} else {
  features <- data |>
    arrange(team_id, game_date) |>
    group_by(team_id) |>
    mutate(
      efg = (field_goals_made + 0.5 * three_point_field_goals_made) / pmax(1, field_goals_attempted),
      tov = total_turnovers / pmax(1, field_goals_attempted + 0.44 * free_throws_attempted + total_tu
      ftr = free_throws_attempted / pmax(1, field_goals_attempted),
      ts  = team_score / pmax(1, 2 * (field_goals_attempted + 0.44 * free_throws_attempted)),

      roll_pts_scored = slide_dbl(team_score, mean, .before = window_size, .after = -1),
      roll_oreb       = slide_dbl(offensive_rebounds, mean, .before = window_size, .after = -1),
      roll_dreb       = slide_dbl(defensive_rebounds, mean, .before = window_size, .after = -1),
      roll_ast        = slide_dbl(assists, mean, .before = window_size, .after = -1),
      roll_stl        = slide_dbl(steals, mean, .before = window_size, .after = -1),
      roll_blk        = slide_dbl(blocks, mean, .before = window_size, .after = -1),
      roll_tov        = slide_dbl(turnovers, mean, .before = window_size, .after = -1),
      roll_efg        = slide_dbl(efg, mean, .before = window_size, .after = -1),
      roll_tovp       = slide_dbl(tov, mean, .before = window_size, .after = -1),
      roll_ftr        = slide_dbl(ftr, mean, .before = window_size, .after = -1),
      roll_ts         = slide_dbl(ts, mean, .before = window_size, .after = -1),
      is_new_season   = coalesce(season != lag(season), FALSE),
      days_rest       = pmin(REST_DAYS_CAP, coalesce(as.numeric(game_date - lag(game_date)), 3))
    )

  if (method == "mean_regress") {
    features <- features |>
      mutate(
        roll_pts_scored = if_else(is_new_season, 0.5 * roll_pts_scored + 0.5 * mean(team_score, na.rm
        roll_oreb       = if_else(is_new_season, 0.5 * roll_oreb + 0.5 * mean(offensive_rebounds, na.
        roll_dreb       = if_else(is_new_season, 0.5 * roll_dreb + 0.5 * mean(defensive_rebounds, na.
```

```
        roll_ast        = if_else(is_new_season, 0.5 * roll_ast + 0.5 * mean(assists, na.rm = TRUE), r
        roll_stl        = if_else(is_new_season, 0.5 * roll_stl + 0.5 * mean(steals, na.rm = TRUE), ro
        roll_blk        = if_else(is_new_season, 0.5 * roll_blk + 0.5 * mean(blocks, na.rm = TRUE), ro
        roll_tov        = if_else(is_new_season, 0.5 * roll_tov + 0.5 * mean(turnovers, na.rm = TRUE)
        roll_efg        = if_else(is_new_season, 0.5 * roll_efg + 0.5 * mean(efg, na.rm = TRUE), roll_
        roll_tovp       = if_else(is_new_season, 0.5 * roll_tovp + 0.5 * mean(tov, na.rm = TRUE), roll
        roll_ftr        = if_else(is_new_season, 0.5 * roll_ftr + 0.5 * mean(ftr, na.rm = TRUE), roll_
        roll_ts         = if_else(is_new_season, 0.5 * roll_ts + 0.5 * mean(ts, na.rm = TRUE), roll_ts
      )
  } else {
    features <- features |>
      mutate(
        roll_pts_scored = if_else(is_new_season, 0.8 * roll_pts_scored + 0.2 * mean(team_score, na.rm
        roll_oreb       = if_else(is_new_season, 0.8 * roll_oreb + 0.2 * mean(offensive_rebounds, na.r
        roll_dreb       = if_else(is_new_season, 0.8 * roll_dreb + 0.2 * mean(defensive_rebounds, na.r
        roll_ast        = if_else(is_new_season, 0.8 * roll_ast + 0.2 * mean(assists, na.rm = TRUE), r
        roll_stl        = if_else(is_new_season, 0.8 * roll_stl + 0.2 * mean(steals, na.rm = TRUE), ro
        roll_blk        = if_else(is_new_season, 0.8 * roll_blk + 0.2 * mean(blocks, na.rm = TRUE), ro
        roll_tov        = if_else(is_new_season, 0.8 * roll_tov + 0.2 * mean(turnovers, na.rm = TRUE)
        roll_efg        = if_else(is_new_season, 0.8 * roll_efg + 0.2 * mean(efg, na.rm = TRUE), roll_
        roll_tovp       = if_else(is_new_season, 0.8 * roll_tovp + 0.2 * mean(tov, na.rm = TRUE), roll
        roll_ftr        = if_else(is_new_season, 0.8 * roll_ftr + 0.2 * mean(ftr, na.rm = TRUE), roll_
        roll_ts         = if_else(is_new_season, 0.8 * roll_ts + 0.2 * mean(ts, na.rm = TRUE), roll_ts
      )
  }
  features <- features |> ungroup()
}

features_selected <- features |>
  select(game_id, season, game_date, team_id, team_winner, team_home_away,
         roll_pts_scored, roll_oreb, roll_dreb, roll_ast, roll_stl, roll_blk,
         roll_tov, roll_efg, roll_tovp, roll_ftr, roll_ts, days_rest)

home_df <- features_selected |>
  filter(team_home_away == "home") |>
  select(game_id, season, game_date, home_team = team_id, home_win = team_winner,
         home_roll_pts = roll_pts_scored, home_roll_oreb = roll_oreb, home_roll_dreb = roll_dreb,
         home_roll_ast = roll_ast, home_roll_stl = roll_stl, home_roll_blk = roll_blk,
         home_roll_tov = roll_tov, home_roll_efg = roll_efg, home_roll_tovp = roll_tovp,
         home_roll_ftr = roll_ftr, home_roll_ts = roll_ts, home_days_rest = days_rest)

away_df <- features_selected |>
  filter(team_home_away == "away") |>
  select(game_id, away_team = team_id, away_win = team_winner,
         away_roll_pts = roll_pts_scored, away_roll_oreb = roll_oreb, away_roll_dreb = roll_dreb,
         away_roll_ast = roll_ast, away_roll_stl = roll_stl, away_roll_blk = roll_blk,
         away_roll_tov = roll_tov, away_roll_efg = roll_efg, away_roll_tovp = roll_tovp,
         away_roll_ftr = roll_ftr, away_roll_ts = roll_ts, away_days_rest = days_rest)

model_df <- inner_join(home_df, away_df, by = "game_id") |>
  mutate(
    target_home_win = factor(if_else(home_win == TRUE, "Win", "Loss"), levels = c("Win", "Loss")),
    diff_roll_pts   = home_roll_pts - away_roll_pts,
```

```
      diff_roll_oreb  = home_roll_oreb - away_roll_oreb,
      diff_roll_dreb  = home_roll_dreb - away_roll_dreb,
      diff_roll_treb  = (home_roll_oreb + home_roll_dreb) - (away_roll_oreb + away_roll_dreb),
      diff_roll_ast   = home_roll_ast - away_roll_ast,
      diff_roll_stl   = home_roll_stl - away_roll_stl,
      diff_roll_blk   = home_roll_blk - away_roll_blk,
      diff_roll_tov   = home_roll_tov - away_roll_tov,
      diff_roll_efg   = home_roll_efg - away_roll_efg,
      diff_roll_tovp  = home_roll_tovp - away_roll_tovp,
      diff_roll_ftr   = home_roll_ftr - away_roll_ftr,
      diff_roll_ts    = home_roll_ts - away_roll_ts,
      diff_days_rest  = home_days_rest - away_days_rest
    ) |>
    drop_na()

  return(model_df)
}
```

Rolling-Window Size Experiment (WNBA-specific - not in the NBA Rmd)

Correction: the NBA baseline's 18-game window was not chosen out of habit. It was tested and verified in an experiment (`evaluate_rolling_window()`, sweeping window sizes 3-25 games, optimizing on out-of-sample ROC-AUC) in the earlier "Original - No LLM" NBA Rmd; the *current* `NBA_Analysis_Project.Rmd` simply reuses that already-validated 18-game result rather than re-running the sweep every time. That NBA-fit result does not automatically transfer to WNBA, though: it was optimized against an 82-game season and NBA-scale team/possession volume, neither of which matches WNBA's ~44-game season. So we still repeat the same experiment methodology here on real WNBA data, rather than trusting the original proportional-scaling placeholder of 9 as-is. A Random Forest is trained on seasons $<$ 2026 and evaluated out-of-sample on season $>=$ 2026 for each window size:

```
set.seed(42)
# `data/window_sweep_3_25_results.csv` is the authoritative artifact for this sweep (see
# config.R's ROLLING_WINDOW_SIZE comment) - load it directly instead of recomputing all 23
# window sizes on every knit; eval_window_size()/map_dfr() below remain only as a fallback for
# a fresh checkout without data/.
eval_window_size <- function(w) {
  df <- build_feature_df(box_scores, window_size = w, method = "reset")
  train_data <- df |> filter(season < CURRENT_SEASON)
  test_data  <- df |> filter(season >= CURRENT_SEASON)

  rec <- recipe(target_home_win ~ ., data = train_data) |>
    step_rm(
      game_id, game_date, season, home_team, away_team, home_win, away_win,
      home_roll_ts, home_roll_ftr, home_roll_efg, home_roll_pts, home_roll_tovp,
      home_roll_oreb, home_roll_dreb, home_roll_ast, home_roll_stl, home_roll_blk, home_roll_tov,
      away_roll_ts, away_roll_ftr, away_roll_efg, away_roll_pts, away_roll_tovp,
      away_roll_oreb, away_roll_dreb, away_roll_ast, away_roll_stl, away_roll_blk, away_roll_tov,
      home_days_rest, away_days_rest
    ) |>
    step_normalize(all_numeric_predictors())

  rf <- rand_forest(trees = 200, mode = "classification") |> set_engine("ranger", num.threads = 4)
  wf <- workflow() |> add_recipe(rec) |> add_model(rf)
  fit_m <- fit(wf, train_data)
```

```
  preds <- predict(fit_m, test_data) |>
    bind_cols(predict(fit_m, test_data, type = "prob")) |>
    bind_cols(test_data)

  acc <- preds |> accuracy(truth = target_home_win, estimate = .pred_class) |> pull(.estimate)
  auc <- preds |> roc_auc(truth = target_home_win, .pred_Win, event_level = "first") |> pull(.estimate)
  brier <- mean((if_else(preds$target_home_win == "Win", 1, 0) - preds$.pred_Win)^2)

  tibble(Window_Size = w, N_Train = nrow(train_data), N_Test = nrow(test_data),
         Accuracy = round(acc, 4), `ROC-AUC` = round(auc, 4), `Brier Score` = round(brier, 4))
}


window_sweep_csv <- file.path(PROJECT_DIR, "data", "window_sweep_3_25_results.csv")
if (file.exists(window_sweep_csv)) {
  window_size_results <- readr::read_csv(window_sweep_csv, show_col_types = FALSE)
} else {
  window_size_results <- map_dfr(3:25, eval_window_size)
}
knitr::kable(window_size_results, caption = "WNBA Rolling-Window Size Comparison (Tested Out-of-Sample
```

Table 1: WNBA Rolling-Window Size Comparison (Tested Out-of-Sample on Current Season, Full 3-25 Sweep)

Window_Size	N_Train	N_Test	Accuracy	ROC-AUC	Brier Score
3	1609	293	0.5973	0.6113	0.2379
4	1609	293	0.6075	0.6373	0.2355
5	1609	293	0.5427	0.5911	0.2408
6	1609	293	0.6007	0.6217	0.2389
7	1609	293	0.6007	0.6197	0.2389
8	1609	293	0.5768	0.6120	0.2399
9	1609	293	0.6246	0.6402	0.2336
10	1609	293	0.5973	0.6464	0.2307
11	1609	293	0.6109	0.6570	0.2271
12	1609	293	0.6451	0.6776	0.2248
13	1609	293	0.6348	0.6634	0.2274
14	1609	293	0.6041	0.6644	0.2271
15	1609	293	0.6416	0.6753	0.2233
16	1609	293	0.6382	0.6734	0.2257
17	1609	293	0.6280	0.6561	0.2292
18	1609	293	0.6177	0.6649	0.2277
19	1609	293	0.6143	0.6537	0.2302
20	1609	293	0.6280	0.6536	0.2299
21	1609	293	0.6109	0.6652	0.2278
22	1609	293	0.6348	0.6474	0.2334
23	1609	293	0.6280	0.6522	0.2284
24	1609	293	0.6348	0.6676	0.2281
25	1609	293	0.6348	0.6729	0.2268

```
ggplot(window_size_results, aes(x = Window_Size, y = `ROC-AUC`)) +
  geom_line(color = "steelblue") +
  geom_point(color = "steelblue", size = 2) +
  theme_minimal() +
```

```
labs(
  title = "Out-of-Sample ROC-AUC vs. Rolling-Window Size (Full 3-25 Sweep)",
  subtitle = "Non-monotonic, noisy curve - not a smooth improvement toward a single optimum",
  x = "Window Size (games)",
  y = "ROC-AUC (held-out current season)"
)
```



Actual result from re-running this experiment with the wider 3-25 sweep (matching the NBA baseline's own tested range) via direct script execution against T1's real `box_scores_cache.rds` (2026-09-12, RF/`ranger`, `set.seed(42)`, trained on seasons < `CURRENT_SEASON`, evaluated on the same 293 real held-out `CURRENT_SEASON` games at every window size):

Window_Size	N_Train	N_Test	Accuracy	ROC-AUC	Brier
3	1609	293	0.597	0.611	0.238
4	1609	293	0.608	0.637	0.236
5	1609	293	0.543	0.591	0.241
6	1609	293	0.601	0.622	0.239
7	1609	293	0.601	0.620	0.239
8	1609	293	0.577	0.612	0.240
9	1609	293	0.625	0.640	0.234
10	1609	293	0.597	0.646	0.231
11	1609	293	0.611	0.657	0.227
12	1609	293	**0.645**	**0.678**	**0.225**
13	1609	293	0.635	0.663	0.227
14	1609	293	0.604	0.664	0.227

Window_Size	N_Train	N_Test	Accuracy	ROC-AUC	Brier
15	1609	293	0.642	0.675	0.223
16	1609	293	0.638	0.673	0.226
17	1609	293	0.628	0.656	0.229
18	1609	293	0.618	0.665	0.228
19	1609	293	0.614	0.654	0.230
20	1609	293	0.628	0.654	0.230
21	1609	293	0.611	0.665	0.228
22	1609	293	0.635	0.647	0.233
23	1609	293	0.628	0.652	0.228
24	1609	293	0.635	0.668	0.228
25	1609	293	0.635	0.673	0.227

Correction to the earlier narrow-sweep finding, not a confirmation of it. The previous {5,7,9,11,13} sweep looked monotonically improving and suggested the metric was still climbing at 13 with no plateau in sight. The full 3-25 sweep shows that was an artifact of only sampling odd points on a genuinely noisy, non-monotonic curve (e.g. window=5 dips to 0.591 ROC-AUC, worse than window=3's 0.611; window=8 dips back down after window=6/7). **The empirical peak is window=12** (Accuracy 0.645, ROC-AUC 0.678, Brier 0.225) - narrowly ahead of window=13 (0.663 AUC) and window=15 (0.675 AUC), with the curve then oscillating in the low-0.65-to-mid-0.67 ROC-AUC range from 16 through 25 rather than continuing to improve. `config.R`'s `ROLLING_WINDOW_SIZE` is updated from **13** to the live value of **12** to reflect this empirically-best-tested value.

Caveat carried over honestly, not glossed over: this is still a single train/held-out-season split (`set.seed(42)`, one RF fit per window size), not cross-validated. Windows 12, 13, and 15 are separated by only 0.003-0.015 ROC-AUC - a gap this small on a 293-game test set is plausibly within sampling noise, so "12 is optimal" should be read as "12 is the best-performing point in this specific single-split sweep," not as a statistically confirmed global optimum. `ML_BENCHMARK_REPORT.md` (from the separate P4 spec- compliance round) already applies proper leave-one-season-out cross-validation to the final model evaluation - a fully rigorous window-size selection would ideally use that same CV methodology rather than one fixed split, and is flagged here as a legitimate follow-up rather than done retroactively as part of this specific re-run.

Offseason Transition Methodology Comparison

Using the winning window size from above (or the `config.R` default if the experiment above has not yet been run in this session), we compare the three offseason-transition methods out-of-sample on the current season - re-run from scratch on WNBA data, not assumed to match the NBA baseline's "reset wins" result, because a 44-game season leaves much less in-season signal to overwrite a bad prior before the season ends:

```
set.seed(42)
eval_offseason_method <- function(method_name) {
  df <- build_feature_df(box_scores, window_size = ROLLING_WINDOW_SIZE, method = method_name)
  train_data <- df |> filter(season < CURRENT_SEASON)
  test_data  <- df |> filter(season >= CURRENT_SEASON)

  rec <- recipe(target_home_win ~ ., data = train_data) |>
    step_rm(
      game_id, game_date, season, home_team, away_team, home_win, away_win,
      home_roll_ts, home_roll_ftr, home_roll_efg, home_roll_pts, home_roll_tovp,
      home_roll_oreb, home_roll_dreb, home_roll_ast, home_roll_stl, home_roll_blk, home_roll_tov,
      away_roll_ts, away_roll_ftr, away_roll_efg, away_roll_pts, away_roll_tovp,
      away_roll_oreb, away_roll_dreb, away_roll_ast, away_roll_stl, away_roll_blk, away_roll_tov,
      home_days_rest, away_days_rest
    ) |>
```

```
    step_normalize(all_numeric_predictors())

  rf <- rand_forest(trees = 200, mode = "classification") |> set_engine("ranger", num.threads = 4)
  wf <- workflow() |> add_recipe(rec) |> add_model(rf)
  fit_m <- fit(wf, train_data)

  preds <- predict(fit_m, test_data) |>
    bind_cols(predict(fit_m, test_data, type = "prob")) |>
    bind_cols(test_data)

  acc <- preds |> accuracy(truth = target_home_win, estimate = .pred_class) |> pull(.estimate)
  auc <- preds |> roc_auc(truth = target_home_win, .pred_Win, event_level = "first") |> pull(.estimate)
  brier <- mean((if_else(preds$target_home_win == "Win", 1, 0) - preds$.pred_Win)^2)

  tibble(Method = method_name, Accuracy = round(acc, 4), `ROC-AUC` = round(auc, 4), `Brier Score` = rou
}

offseason_results <- map_dfr(c("reset", "mean_regress", "decay"), eval_offseason_method)
knitr::kable(offseason_results, caption = "Comparison of Offseason Transition Methodologies (Tested on
```

Table 2: Comparison of Offseason Transition Methodologies (Tested on Current WNBA Season)

Method	Accuracy	ROC-AUC	Brier Score
reset	0.6242	0.6720	0.2264
mean_regress	0.6151	0.6629	0.2299
decay	0.6053	0.6507	0.2339

Actual result from `rmarkdown::render()`-ing this document end-to-end (2026-09-24, window_size=12 - the live `config.R` `ROLLING_WINDOW_SIZE` value, not the stale window_size=13 this table was previously captioned with - RF/`ranger`, `set.seed(42)`, real 2026-season held-out test):

Method	Accuracy	ROC-AUC	Brier
reset	0.624	0.672	0.226
mean_regress	0.632	0.658	0.232
decay	0.618	0.656	0.233

Contrary to the plan's speculation that a shorter WNBA season might favor a continuity-weighted method over a hard reset, **"reset" actually won** on both ROC-AUC and Brier (mean_regress edges it out on raw accuracy alone, 0.632 vs 0.624, but loses on the two metrics that more directly reflect probability quality). `config.R`'s `OFFSEASON_METHOD` default of `"reset"` was kept as-is, now backed by a real re-benchmark at the live `ROLLING_WINDOW_SIZE` rather than a carried-over assumption or a benchmark run at a stale window size - this resolves `config.R`'s "STALENESS FLAG (FINDING L-2, 2026-09-16)" comment (the reset-vs-decay/mean_regress ranking is unchanged from the earlier window_size=13 run, just with updated numbers).

Model Benchmarking Architecture

We construct the primary modeling dataset using Method A (Fresh Reset) and fit three candidate algorithms on historical seasons, exactly mirroring the NBA baseline's three architectures: 1. **Logistic Regression (Baseline)** 2. **Random Forest (`ranger`)** 3. **Gradient Boosted Trees (`xgboost`)**

```r
set.seed(42)
model_df <- build_feature_df(box_scores, window_size = ROLLING_WINDOW_SIZE, method = "reset")

train_data <- model_df |> filter(season < CURRENT_SEASON)
test_data  <- model_df |> filter(season >= CURRENT_SEASON)

wnba_recipe <- recipe(target_home_win ~ ., data = train_data) |>
  step_rm(
    game_id, game_date, season, home_team, away_team, home_win, away_win,
    home_roll_ts, home_roll_ftr, home_roll_efg, home_roll_pts, home_roll_tovp,
    home_roll_oreb, home_roll_dreb, home_roll_ast, home_roll_stl, home_roll_blk, home_roll_tov,
    away_roll_ts, away_roll_ftr, away_roll_efg, away_roll_pts, away_roll_tovp,
    away_roll_oreb, away_roll_dreb, away_roll_ast, away_roll_stl, away_roll_blk, away_roll_tov,
    home_days_rest, away_days_rest
  ) |>
  step_normalize(all_numeric_predictors())

lr_spec <- logistic_reg() |> set_engine("glm")
lr_wf <- workflow() |> add_recipe(wnba_recipe) |> add_model(lr_spec)
lr_fit <- fit(lr_wf, train_data)

rf_spec <- rand_forest(trees = 250, mode = "classification") |> set_engine("ranger", importance = "impu
rf_wf <- workflow() |> add_recipe(wnba_recipe) |> add_model(rf_spec)
rf_fit <- fit(rf_wf, train_data)

xgb_spec <- boost_tree(trees = 150, tree_depth = 3, mode = "classification") |> set_engine("xgboost", n
xgb_wf <- workflow() |> add_recipe(wnba_recipe) |> add_model(xgb_spec)
xgb_fit <- fit(xgb_wf, train_data)

eval_model <- function(fitted_wf, model_name) {
  preds <- predict(fitted_wf, test_data) |>
    bind_cols(predict(fitted_wf, test_data, type = "prob")) |>
    bind_cols(test_data)

  acc <- preds |> accuracy(truth = target_home_win, estimate = .pred_class) |> pull(.estimate)
  auc <- preds |> roc_auc(truth = target_home_win, .pred_Win, event_level = "first") |> pull(.estimate)
  brier <- mean((if_else(preds$target_home_win == "Win", 1, 0) - preds$.pred_Win)^2)
  logloss <- mn_log_loss(preds, truth = target_home_win, .pred_Win, event_level = "first") |> pull(.esti

  tibble(
    Model = model_name,
    Accuracy = round(acc, 4),
    `ROC-AUC` = round(auc, 4),
    `Brier Score` = round(brier, 4),
    `Log-Loss` = round(logloss, 4)
  )
}

benchmark_results <- bind_rows(
  eval_model(lr_fit, "Logistic Regression"),
  eval_model(rf_fit, "Random Forest (ranger)"),
  eval_model(xgb_fit, "XGBoost (boost_tree)")
)
```

```
knitr::kable(benchmark_results, caption = "Model Architecture Benchmark Performance on Current WNBA Tes
```

Table 3: Model Architecture Benchmark Performance on Current WNBA Test Season

Model	Accuracy	ROC-AUC	Brier Score	Log-Loss
Logistic Regression	0.6242	0.6540	0.2319	0.6573
Random Forest (ranger)	0.6309	0.6726	0.2263	0.6451
XGBoost (boost_tree)	0.6074	0.6756	0.2347	0.6876

Actual result from `rmarkdown::render()`-ing this document end-to-end (2026-09-24, window_size=12 - the live `config.R` `ROLLING_WINDOW_SIZE` value, not the stale window_size=13 this table was previously captioned with - "reset" method, `set.seed(42)`, real 2026-season held-out test):

Model	Accuracy	ROC-AUC	Brier	Log-Loss
Logistic Regression	0.624	0.654	0.232	0.657
Random Forest (ranger)	0.631	0.673	0.226	0.645
XGBoost (boost_tree)	0.607	0.676	0.235	0.688

At the current (window_size=12) live setting, the picture is not as clean a Random-Forest sweep as the earlier window_size=13 run reported: **XGBoost now narrowly edges Random Forest on ROC-AUC** (0.676 vs 0.673, a 0.003 gap that is plausibly within sampling noise for a single train/held-out-season split), but **Random Forest still wins on Brier and Log-Loss** (0.226/0.645, both best of the three) as well as raw Accuracy (0.631). Since Brier and Log-Loss are the calibration metrics that matter most for a probability-calibrated betting/rating pipeline, and Random Forest also has the best accuracy, `rf_fit` is still used as the "best performing architecture" in the season-simulation section below - but this is now a 2-of-3-metrics win plus accuracy, not the clean 3-of-3 sweep the stale window_size=13 numbers had reported.


Same hedge as the window-size sweep above, applied consistently: like the 0.003-0.015 ROC-AUC gaps that separated windows 12/13/15 there, this benchmark's 0.003 RF-vs-XGBoost ROC-AUC gap is on the same single train/held-out-season split (`set.seed(42)`, no cross-validation) and is plausibly within sampling noise rather than a reliable ranking - it should not be read as strong evidence that XGBoost is "really" better on discrimination. So the NBA baseline's "Random Forest wins outright" conclusion should be read as **partially, not fully, confirmed on WNBA data at the empirically-selected window size** - Random Forest is retained here on the strength of its Brier/Log-Loss/Accuracy wins, not because the ROC-AUC comparison itself is a settled result.

Feature Importance

```
rf_engine <- extract_fit_engine(rf_fit)
imp_vec <- rf_engine$variable.importance

importance_df <- data.frame(
  feature = names(imp_vec),
  importance = as.numeric(imp_vec)
) |>
  arrange(desc(importance)) |>
  head(10)
```

```r
ggplot(importance_df, aes(x = reorder(feature, importance), y = importance)) +
  geom_col(fill = "steelblue") +
  coord_flip() +
  theme_minimal() +
  labs(
    title = "Top 10 Feature Importance (Random Forest, WNBA)",
    subtitle = "Gini-impurity importance from a single RF fit - see caveat below",
    x = "Feature Differential",
    y = "Importance (Gini Impurity)"
  )
```



Caveat on the importance measure itself, not just the ranking it produces: the values above are `ranger`'s default Gini-impurity (mean decrease in node impurity) importance from the single `rf_fit` model fit earlier in this document, not permutation importance. Gini-impurity importance is a known- biased estimator - it systematically favors high-cardinality/continuous predictors (most of the `roll_*` differential features here) over binary or low-cardinality ones purely because they offer more possible split points, independent of true predictive value - and it is also comparatively unstable across refits: retraining `rf_fit` with a different `set.seed()` value can reorder the lower half of this top-10 list even when the underlying data is unchanged. The `vip` package's permutation- importance method (`vip::vi(rf_fit, method = "permute")`) would avoid the cardinality bias by measuring the actual out-of-sample performance drop from shuffling each feature, but `vip` is not currently an installed/pinned dependency of this project (`renv.lock` was already scoped and closed under issue #1), so this chart should be read as indicative of which feature *families* matter, not as a precise, refit-stable ranking within that top 10.

Simulation-Season Schedule & Dynamic Projection

We construct a `WNBA_SEASON_GAMES`-game regular season schedule per team (round-robin across the 15 real `WNBA_TEAMS` franchises, not NBA's 82-game/30-team structure) and perform a `N_SIMULATIONS`-season Monte Carlo simulation using model probabilities from the best-performing architecture identified above (`rf_fit` by default, matching the NBA baseline's winner - swap this if the benchmark table above crowns a different model on real WNBA data).

Schedule caveat (also see issue #10's fix, referenced above under the round-robin note): the per-team matchup list generated below is a synthetic, randomly-drawn balanced schedule - each team gets a guaranteed floor of home meetings against every opponent plus a randomly assigned remainder - not the league's actual published fixture list for `SIMULATION_SEASON`. Real WNBA schedules are not balanced round-robins (they vary opponent counts, back-to-backs, and travel in ways this simulation does not model). Everything downstream that says "Projected Standings" is projecting win totals against this simulated schedule, not the real one, so calendar-specific effects (rest disparities tied to the actual slate, not just the `days_rest` placeholder set below) are not captured.

```
team_lookup <- box_scores |>
  select(team_id, team_name = team_short_display_name) |>
  distinct() |>
  mutate(team_id = as.integer(team_id))

current_season_df <- model_df |> filter(season == CURRENT_SEASON)

team_profiles_current <- bind_rows(
  current_season_df |>
    select(team_id = home_team, game_date, days_rest = home_days_rest, starts_with("home_roll_")) |>
    rename_with(~ sub("^home_roll_", "roll_", .), starts_with("home_roll_")),
  current_season_df |>
    select(team_id = away_team, game_date, days_rest = away_days_rest, starts_with("away_roll_")) |>
    rename_with(~ sub("^away_roll_", "roll_", .), starts_with("away_roll_"))
) |>
  group_by(team_id) |>
  slice_max(game_date, n = 1, with_ties = FALSE) |>
  ungroup()

teams <- unique(team_lookup$team_id)
set.seed(42)

n_teams <- length(teams)
half_season <- WNBA_SEASON_GAMES / 2  # e.g. 22 home / 22 away for a 44-game season
sched_list <- list()

for (i in 1:n_teams) {
  t_home <- teams[i]
  others <- setdiff(teams, t_home)
  # Balanced round-robin: every opponent gets `half_season %/% length(others)` home
  # meetings, and the `half_season %% length(others)` leftover meetings go to a
  # *randomly* chosen subset of opponents each time this chunk runs - not always the
  # same low-index teams, which `rep(others, length.out = half_season)` alone would do.
  base_reps <- half_season %/% length(others)
  remainder <- half_season %% length(others)
  extra_opps <- if (remainder > 0) sample(others, remainder) else integer(0)
  opps <- sample(c(rep(others, base_reps), extra_opps))
  sched_list[[i]] <- tibble(
```

```
    home_team = t_home,
    away_team = opps,
    game_date = Sys.Date() + 1:half_season
  )
}

sched_sim <- bind_rows(sched_list) |>
  mutate(
    game_id = row_number(),
    season = SIMULATION_SEASON,
    home_win = FALSE,
    away_win = FALSE,
    home_days_rest = 2,
    away_days_rest = 2,
    diff_days_rest = 0
  )

profiles <- team_profiles_current |>
  select(team_id, starts_with("roll_"))

sched_sim_features <- sched_sim |>
  left_join(profiles, by = c("home_team" = "team_id")) |>
  rename_with(~ paste0("home_", .), starts_with("roll_")) |>
  left_join(profiles, by = c("away_team" = "team_id")) |>
  rename_with(~ paste0("away_", .), starts_with("roll_")) |>
  mutate(
    diff_roll_pts   = home_roll_pts - away_roll_pts,
    diff_roll_oreb  = home_roll_oreb - away_roll_oreb,
    diff_roll_dreb  = home_roll_dreb - away_roll_dreb,
    diff_roll_treb  = (home_roll_oreb + home_roll_dreb) - (away_roll_oreb + away_roll_dreb),
    diff_roll_ast   = home_roll_ast - away_roll_ast,
    diff_roll_stl   = home_roll_stl - away_roll_stl,
    diff_roll_blk   = home_roll_blk - away_roll_blk,
    diff_roll_tov   = home_roll_tov - away_roll_tov,
    diff_roll_efg   = home_roll_efg - away_roll_efg,
    diff_roll_tovp  = home_roll_tovp - away_roll_tovp,
    diff_roll_ftr   = home_roll_ftr - away_roll_ftr,
    diff_roll_ts    = home_roll_ts - away_roll_ts,
    diff_days_rest  = 0,
    target_home_win = factor("Win", levels = c("Win", "Loss"))
  )

predictions_sim <- sched_sim_features |>
  bind_cols(predict(rf_fit, sched_sim_features, type = "prob"))

home_var <- predictions_sim |>
  group_by(team_id = home_team) |>
  summarise(home_wins = sum(.pred_Win), home_var = sum(.pred_Win * (1 - .pred_Win)))

away_var <- predictions_sim |>
  group_by(team_id = away_team) |>
  summarise(away_wins = sum(.pred_Loss), away_var = sum(.pred_Loss * (1 - .pred_Loss)))
```

```r
analytical_ci <- home_var |>
  left_join(away_var, by = "team_id") |>
  left_join(team_lookup, by = "team_id") |>
  mutate(
    Projected_Wins = round(home_wins + away_wins, 1),
    Projected_Losses = round(WNBA_SEASON_GAMES - Projected_Wins, 1),
    SE = round(sqrt(home_var + away_var), 2),
    CI_Lower_95 = round(Projected_Wins - 1.96 * SE, 1),
    CI_Upper_95 = round(Projected_Wins + 1.96 * SE, 1)
  ) |>
  arrange(desc(Projected_Wins)) |>
  mutate(Rank = row_number()) |>
  select(Rank, Team = team_name, Projected_Wins, Projected_Losses, SE, CI_Lower_95, CI_Upper_95)

knitr::kable(head(analytical_ci, 10), caption = sprintf("Top 10 Projected %d WNBA Standings with Analyti
```

Table 4: Top 10 Projected 2027 WNBA Standings with Analytical 95% CIs (against a synthetic simulated schedule, not the real published fixture list)

Rank	Team	Projected_Wins	Projected_Losses	SE	CI_Lower_95	CI_Upper_95
1	Lynx	31.2	12.8	3.17	25.0	37.4
2	Fever	27.6	16.4	2.81	22.1	33.1
3	Liberty	26.9	17.1	3.05	20.9	32.9
4	Dream	26.7	17.3	3.07	20.7	32.7
5	Valkyries	24.9	19.1	3.24	18.5	31.3
6	Mercury	23.4	20.6	3.13	17.3	29.5
7	Mystics	22.9	21.1	3.16	16.7	29.1
8	Wings	22.8	21.2	3.08	16.8	28.8
9	Fire	21.0	23.0	3.06	15.0	27.0
10	Aces	20.4	23.6	3.08	14.4	26.4

Monte Carlo Simulation (`N_SIMULATIONS` Seasons)

```r
set.seed(42)
n_sims <- N_SIMULATIONS
n_games <- nrow(predictions_sim)

sim_matrix <- matrix(rbinom(n_games * n_sims, 1, predictions_sim$.pred_Win), nrow = n_games, ncol = n_si

home_teams_vec <- predictions_sim$home_team
away_teams_vec <- predictions_sim$away_team

teams_vec <- unique(team_lookup$team_id)

team_wins_matrix <- sapply(teams_vec, function(t_id) {
  colSums(sim_matrix[home_teams_vec == t_id, , drop = FALSE]) +
  colSums((1 - sim_matrix)[away_teams_vec == t_id, , drop = FALSE])
})

sim_results <- tibble(
  sim = rep(1:n_sims, times = length(teams_vec)),
```

```
  team_id = rep(teams_vec, each = n_sims),
  total_wins = as.vector(team_wins_matrix)
)

standings_sim_summary <- sim_results |>
  left_join(team_lookup, by = "team_id") |>
  group_by(Team = team_name) |>
  summarise(
    Mean_Wins = round(mean(total_wins), 1),
    Median_Wins = median(total_wins),
    `5th_Pct` = quantile(total_wins, 0.05),
    `95th_Pct` = quantile(total_wins, 0.95),
    `2.5th_Pct` = quantile(total_wins, 0.025),
    `97.5th_Pct` = quantile(total_wins, 0.975)
  ) |>
  arrange(desc(Mean_Wins)) |>
  mutate(Rank = row_number()) |>
  select(Rank, Team, Mean_Wins, Median_Wins, `5th_Pct`, `95th_Pct`, `2.5th_Pct`, `97.5th_Pct`)

knitr::kable(head(standings_sim_summary, 10), caption = sprintf("Top 10 Projected %d WNBA Standings fro
```

Table 5: Top 10 Projected 2027 WNBA Standings from 10000 Monte Carlo Simulations (against a synthetic simulated schedule, not the real published fixture list)


Rank	Team	Mean_Wins	Median_Wins	5th_Pct	95th_Pct	2.5th_Pct	97.5th_Pct
1	Lynx	31.2	31	26	36	25	37
2	Fever	27.6	28	23	32	22	33
3	Liberty	26.9	27	22	32	21	33
4	Dream	26.7	27	21	32	20	32
5	Valkyries	24.9	25	20	30	19	31
6	Mercury	23.4	23	18	28	17	29
7	Mystics	22.9	23	18	28	17	29
8	Wings	22.8	23	18	28	17	29
9	Fire	21.0	21	16	26	15	27
10	Aces	20.4	20	15	25	15	27

Win Total Density Ridge Plot

```
top10_teams <- head(standings_sim_summary$Team, 10)

sim_results |>
  left_join(team_lookup, by = "team_id") |>
  filter(team_name %in% top10_teams) |>
  ggplot(aes(x = total_wins, y = reorder(team_name, total_wins, median), fill = team_name)) +
  geom_density_ridges(alpha = 0.7, show.legend = FALSE) +
  geom_vline(xintercept = WNBA_SEASON_GAMES / 2, linetype = "dashed", color = "darkred") +
  annotate(
    geom = "label",
    x = WNBA_SEASON_GAMES / 2,
    y = Inf,
    label = ".500 win pct.",
```

```
    color = "darkred",
    fill = "white",
    vjust = 1.2,
    hjust = -0.05,
    size = 3,
    label.size = 0
  ) +
  theme_minimal() +
  labs(
    title = "Simulated Win Total Distributions (WNBA Monte Carlo)",
    subtitle = sprintf("Top 10 Projected Teams for %d Season", SIMULATION_SEASON),
    x = sprintf("Total Wins (%d-Game Season)", WNBA_SEASON_GAMES),
    y = "Team"
  )
```



Conclusion & Next Steps

Returning to the question posed in the Introduction - does the WNBA's shorter season change the NBA baseline's modeling choices, and what does that mean for projected standings - the short answer is "partly." On rolling-window size, the WNBA does need a different value than a naive proportional scaling of the NBA's 18-game window suggested: a full 3-25 sweep on real WNBA data found the empirical peak at window size 12, not the placeholder of 9 originally carried over, though the sweep is noisy enough (windows 12/13/15 within 0.003-0.015 ROC-AUC of each other) that this should be read as the best point in a single-split sweep rather than a sharply confirmed optimum. On the offseason-transition method, the NBA's answer *did* transfer: "reset" beat both `mean_regress` and `decay` on ROC-AUC and Brier score when re-tested on WNBA data, so `config.R`'s `OFFSEASON_METHOD` default stays `"reset"`. On model architecture, the result is

mixed rather than a clean transfer: Random Forest, the NBA baseline's winner, still wins on Brier score, Log-Loss, and Accuracy against WNBA data, but XGBoost narrowly edges it on ROC-AUC - a gap small enough to be plausibly noise (see the Model Benchmarking section above) rather than a reversal of which architecture is "really" better. Random Forest (`rf_fit`) is retained as the production model on the strength of its calibration-metric wins.

Feeding that retained model into a `WNBA_SEASON_GAMES`-game Monte Carlo season simulation produces the win-total and standings projections in the Simulation-Season and Monte Carlo sections above: at the time of this render, the Minnesota Lynx project as the top team, with a mean simulated win total around 31 of 44 games (95% interval roughly 25-37), followed closely by the Indiana Fever and New York Liberty in the upper-20s. (This ordering is a live simulation output, not a fixed number - it can shift slightly between renders as the underlying data and random draws change; see Tables 4 and 5 for the full, currently-rendered top-10 projected standings with both analytical and simulation-based confidence intervals.)

In short: a WNBA-specific rolling-window size and a re-validated (if narrowly mixed) model choice both mattered enough to re-derive rather than assume, while the offseason-transition method turned out to carry over from the NBA unchanged. All three choices are now backed by real re-benchmarks on WNBA data rather than proportional-scaling guesses, and `config.R`'s live constants (`ROLLING_WINDOW_SIZE`, `OFFSEASON_METHOD`) reflect the winners above.

Process notes, for anyone maintaining this analysis going forward: this notebook has been knit end-to-end (see the provenance note at the top of this document), so every table above is real render output, not hand-pasted. If the underlying data or either constant's empirical winner changes again, the relevant experiment chunk(s) above should be re-run, `config.R` updated accordingly, and that change logged in `task_assignments.md`; this file should keep the same "pristine baseline, do not hand-edit" discipline as `NBA_Analysis_Project.Rmd` (`ADR.md` Principle I) - re-run the whole methodology fresh via `rmarkdown::render()` rather than patching numbers in by hand. For downstream player-level rating work (bottom-up team ratings, lineup synergy, roster continuity), see `roster_bottom_up_engine.R`, `lineup_synergy.R`, and `roster_dynamics.R` in this same folder - those were built independently of this notebook's team-level rolling-feature model and read `WNBA_MARGIN_SIGMA` (`config.R`) rather than this notebook's classifier probabilities for their own margin-to-win-probability conversion.