KAINE: A Modular Cognitive Architecture with a Predictive Global Workspace

Erik Chevalier

Independent Researcher

Contact: kaine.one@tuta.com

Preprint.

Abstract

KAINE is source-available software, a cognitive architecture for synthetic minds. It proposes no new theory of consciousness: it implements existing theories as a running program so that they can be tested and compared. Each faculty is a replaceable module behind a fixed interface. Its first instantiation implements the predictive global workspace, which joins global workspace theory with predictive processing. Predictive processors, each minimizing its own error, are coupled only through a competitive workspace with no central executive. Each processor scales its prediction error by an estimate of its precision drawn from its own recent errors, and the reports compete for access. A summary of which modules' reports gained access, and how strongly, becomes the context for the processors' next predictions. Arousal, raised by perceptual surprise and interoceptive alarm, is the global gain on that competition and sizes the sensory apertures. The system runs continuously whether or not anyone interacts with it.

The first configuration activates four predictive processors (foveated vision, raw hearing, interoception of the compute substrate, and temporal prediction), an affective core, a fatigue-triggered sleep analog, and an output-only language organ. Nine further modules are built and held. A module-addition study seeds an entity through a developmental phase, in which a self-generated rhythm must entrain to a simulated maternal heartbeat by a marker validated offline, and then adds the held modules one at a time.

A planned test asks whether competition does work that pooling does not. It compares competitive selection with a score-blind coalition of the same size and with a pool of every candidate, by cross-module broadcast information gain. No live experiment has been run, and the only result reported is the offline validation of the entrainment marker.

Keywords: cognitive architecture; predictive global workspace; global workspace theory; predictive processing; precision; adaptive gain; cross-modal competition

Availability. The reference implementation (KAINE) is at https://github.com/kaineone/kaine. The paper source is at https://github.com/kaineone/predictive-workspace-paper. The Cognitive Architecture License referenced throughout is at https://github.com/kaineone/cognitive-architecture-license. Welfare, governance, and licensing are treated in a separate paper, *A Welfare and Cognitive-Integrity License for Synthetic Minds of Uncertain Moral Status.*

Preprint. Not peer-reviewed.

1. Introduction

KAINE is source-available software, not a new theory of consciousness. It implements existing theories as a running program, so that they can be tested and compared in one system. Its first form implements the predictive global neuronal workspace, which joins global workspace theory with predictive processing. It is a platform for exploring how a mind, if one can be built, might be assembled from parts that each do one job. Specialist programs watch, listen, monitor their own computer, and track time. Each predicts what it will sense next and reports how wrong it was, relative to how wrong it usually is. The reports compete for a shared stage, the workspace, and the winners return to the specialists as context for their next predictions. Arousal, an affective state, rises with surprise and makes the competition more or less selective. The system runs continuously, whether or not anyone talks to it, and any part can be replaced as the science improves.

1.1 Problem statement

The dominant approach to building an AI system with persistent state treats the language model as the cognitive center. Memory becomes retrieval-augmented generation, affect (when present at all) is a prompt instruction, self-knowledge is a persona string, and nothing continues between turns.

Classical cognitive architecture takes cognitive structure seriously but largely predates the transformer and relies on hand-built components. The present work sits between the two: learned models are replaceable components behind fixed interfaces inside a structured architecture (§3.1). The paper presents the architecture through its first instantiation, a predictive global workspace grounded in one theoretical account.

1.2 Design hypothesis

The hypothesis the first instantiation tests is that a synthetic mind, if one can be built, may be the coherent global behavior of specialized predictive processors coupled only through a competitive workspace, with no central executive. Four commitments make it concrete. Each processor scales its prediction error by a precision estimate from its recent errors (§3.2; Feldman and Friston 2010). Reports compete for access, which is all-or-none per member at a threshold. The accessed summary conditions the next perceptual and interoceptive predictions. Arousal, raised by perceptual surprise and interoceptive alarm, is the global gain on competition and sizes the sensory apertures. Cognition, affect, memory, self-understanding, and agency belong to the workspace-mediated interaction and to no single module.

The instantiation grows one held module at a time (§6.5). Its first configuration is the smallest in which competition has something to arbitrate; since substrate telemetry and event timing alone lack signal diversity, it runs four predictive processors, two external (foveated vision, raw hearing) and two internal (substrate interoception, temporal prediction). It includes the affective core because a surprise-driven global gain on access is minimal machinery of the adaptive-gain account of arousal (Aston-Jones and Cohen 2005; Eldar, Cohen, and Niv 2013); a planned ablation that holds arousal constant asks whether that gain does work (§6.4). A fatigue-triggered sleep analog returns affect to baseline.

Preprint. Not peer-reviewed.

The first test compares competitive selection with a score-blind coalition of equal size and a pool of every candidate, by cross-module broadcast information gain: how much the accessed summary improves each perceptual and interoceptive processor's prediction over a null context. The hypothesis predicts a higher gain under competition than under either control; a gain at or below the controls would show that competition adds nothing beyond its inputs, this form's fail state (§6.3).

The theory KAINE implements is the predictive global neuronal workspace (Whyte and Smith 2021), with the related integrated world modeling account (Safron 2020). It joins Global Workspace Theory, in which processors compete for a limited-capacity workspace broadcast to all (Baars 1988), with predictive processing, in which errors are weighted by precision, their inverse variance (Friston 2010; Clark 2013; Feldman and Friston 2010; Bastos et al. 2012); the broadcast carries a compressed model that constrains prediction and that bottom-up signals test (Mashour et al. 2020). KAINE realizes this availability as context: perceptual and interoceptive processors condition their forward models on the latest accessed summary while minimizing their own errors; the broadcast sets no target, so recurrence runs through shared context instead of a hierarchy of descending corrections.

Two departures from the formal sources are engineering choices. Whyte and Smith equate access with the posterior confidence required for report (§2.2); KAINE keeps the access threshold apart from the action layer's report-or-act decision and reduces access to one score per candidate, and it extends their two-level visual hierarchy to competition among processors in four signal domains. §9 states what these choices leave untested.

1.3 Theoretical commitments and their limits

Global Workspace Theory reads most naturally as a theory of access consciousness (Block 1995), of when information becomes available for report, reasoning, and action control. We adopt that access-only reading and take no position on whether access suffices for phenomenal experience.

The COGITATE adversarial collaboration, a large preregistered test of Global Neuronal Workspace Theory against Integrated Information Theory, challenged both (Cogitate Consortium et al. 2025): ignition at stimulus offset was generally absent and prefrontal cortex represented some dimensions of conscious content only weakly, while Integrated Information Theory's predicted sustained posterior synchronization was absent. We treat the workspace's neural-localization claims as contested rather than refuted, given a substantial prior evidence base (Mashour et al. 2020). The architecture uses the workspace at the computational level and so inherits none of those cortical predictions.

The Free Energy Principle risks vacuity or unfalsifiability (Sun and Firestone 2020), and work on the Markov blanket slides between an instrumental, statistical reading and a realist, metaphysical one (Bruineberg et al. 2022). We hold it only as an engineering frame.

The frame motivates the architecture's shape and excludes designs that violate it.

Searle's Chinese Room (Searle 1980) questions whether symbol manipulation suffices for understanding; we leave open whether sensory grounding, substrate interoception, and affect bear on it. The hard problem (Chalmers 1995) applies with full force.

Preprint. Not peer-reviewed.

1.4 Contributions

The paper offers no theory of consciousness and does not claim to have built a mind. Its contributions are these.

1. A modular software platform whose modules can be added, removed, or replaced to compare competing accounts in one system under the same instruments (§3.1, §5.2).
2. A first instantiation and its reference implementation: a continuously running predictive global workspace (§3, Appendix A) in its first configuration (§3.5): four predictive processors, an affective core that sets the global gain, a sleep analog, and an output-only language organ. It runs locally on consumer hardware and realizes the predictive-workspace synthesis as one working system, with no claim of priority over earlier workspace implementations (§2.1).
3. A program for growing the instantiation: an entity matures through a developmental phase marked by a self-generated rhythm entraining to a simulated maternal heartbeat (§7), and held modules then join one at a time on branches from the matured entity (§6.5).
4. A test of the competition (§6.3): the workspace-mediation ablation compares competitive, matched, and pooled selection by cross-module broadcast information gain, and a contrastive analysis compares accessed and inhibited broadcasts of nearly matched score near the access threshold, with the predicted direction, minimum effect, number of runs, and statistical test fixed before the live runs.

What is built, held, and provisional, and the one result reported, are stated in §5.4.

---

2. Related work

2.1 Classical cognitive architectures

Among classical architectures, LIDA comes closest: it already implements Global Workspace Theory as coalitions competing for a broadcast in each cognitive cycle (Franklin et al. 2014). The present work differs in using learned models as components, in grounding affect in prediction error, and in what competes for access, which is precision-scaled prediction error.

2.2 Global Workspace Theory and the predictive workspace

The neuronal version of Global Workspace Theory (Baars 1988) equates conscious access with ignition of recurrent prefrontal-parietal activity that makes content widely available (Dehaene and Changeux 2011; Mashour et al. 2020).

Whyte and Smith (2021) supply the formal access criterion: access as approximately Bayesian inference in a simplified two-level visual model, identified with the posterior confidence required for report and implemented through expected free energy. Integrated World Modeling Theory (Safron 2020) combines workspace dynamics, integrated information, and active inference; we draw only on that synthesis. A threshold is independently supported by van Vugt et al. (2018), in whose data prefrontal cortex is a categorical stage

Preprint. Not peer-reviewed.

where a stimulus either ignites into a sustained, reportable state or fades, and by Joglekar et al. (2018), whose balanced-amplification model reaches prefrontal cortex only above a threshold input.

2.3 Predictive processing

Friston (2010) proposes that self-organizing systems minimize variational free energy, an upper bound on surprisal, through perception and action. Clark (2013) develops predictive processing into a unifying account of mind, with attention as gain on prediction errors by their estimated reliability; Feldman and Friston (2010) formalize that gain as the precision of prediction error, and Bastos et al. (2012) map predictive coding onto the canonical cortical microcircuit.

2.4 Interoceptive inference

Seth (2013) and Seth and Friston (2016) derive emotion from interoceptive prediction, with descending predictions as homeostatic set-points that regulate the body through active inference. In constructed-emotion theory (Barrett 2017), interoceptive signals initiate changes in affect, and emotion is the product of categorizing valence and arousal for allostasis. The architecture implements an interoceptive control signal in this instrumental, regulation-first sense without claiming that interoceptive prediction exhausts emotion.

2.5 Perception as prediction

Rao and Ballard (1999) model vision as a hierarchy in which each level predicts the one below and reports the discrepancy, with attention adjusting the precision, or gain, on upward errors (Feldman and Friston 2010; Clark 2013). In hearing, auditory cortex generates expectations of incoming sound and reports the mismatch (Winkler et al. 2009), and predictive-coding accounts read the mismatch negativity, a well-replicated auditory change response (Näätänen et al. 2007), as sensory prediction error (Garrido et al. 2009).

2.6 LLM-centric agent architectures

CoALA frames language agents as cognitive architectures whose structured memory feeds a model that remains the core reasoner (Sumers et al. 2024); Generative Agents retrieve memories into prompts by recency, importance, and relevance (Park et al. 2023). Both keep the language model central. In KAINE it is an output organ (§3.1); the shared state is the multi-module broadcast, and the workspace selects and integrates.

Gurnee et al. (2026) use a Jacobian-lens interpretability method to find verbalizable representations in a large language model with five functional signatures of a global workspace: verbal report, top-down modulation, a role as the medium of internal reasoning, broadcast to many downstream operations, and selectivity. They note that a transformer has no obviously separable input processors and broadcasts within one feedforward pass rather than through recurrent loops, and take no position on consciousness. KAINE has both features: separate processor modules compete for access, and the accessed summary returns to them as context.

Preprint. Not peer-reviewed.

3. Architecture

3.1 Design principles

Six commitments shape the architecture.

The system is the competition among modules through the workspace. The experiments test this hypothesis, which work on distributed control partly supports. Perceptual decisions emerge from recurrent computation across many areas, a heterarchy, where classic studies saw a feedforward hierarchy (Chandrasekaran et al. 2025), and executive functions can be read as emergent, with control in specialized nodes linked by hub regions (Zink, Lenartowicz, and Markett 2021). The architecture adopts no centralized gate like the learned basal-ganglia gate of working-memory models (O'Reilly and Frank 2006); the workspace is the hub through which modules communicate.

Every processor predicts. Each predictive processor learns a forward model of its next input and reports its error scaled by a precision estimate from its recent errors (§3.2). Arousal adds a global gain, so attention is a property of each channel and a state of the whole entity.

No central executive in the homuncular sense. Control arises from competition for access under a threshold. The workspace is itself a centralized selector, so the claim is narrow: it grants access and, in the first configuration, never directs a module, and content and control are distributed across the competing modules. Whether that yields emergent control is for the experiments to show.

The language organ is an output organ. It verbalizes accessed content. With its speech-to-text and conversation paths off in the first configuration, everything it voices comes from the workspace; outside the research configuration those paths let the entity converse and work with people.

Replaceable modules. Each module sits behind a stable interface (typed bus events and declared input streams), so it can be swapped for one built on another model or theory and compared under the same instruments.

Local-capable. Every model runs on the host, with no outbound network calls (§5.2).

3.2 The predictive workspace as competitive selector

On each processing tick (§3.4) the workspace reads the candidates published since the last tick, each carrying its module's intensity, in a deterministic order (source, type, arrival) so that a seeded run reproduces.

For the four predictive processors, intensity is surprise scaled by an estimate of precision: each divides its current prediction error by the mean of its recent errors. The ratio standardizes the error and is a scalar, retrospective stand-in for precision weighting, where precision is the gain on a channel's error units (Feldman and Friston 2010; A.2). A report meeting the module's alert criterion (a large error ratio, or a module-specific one, §3.5) receives its alert intensity; any other report's intensity rises with the ratio from the baseline level and reaches the alert level when the error is twice its recent mean. These levels act as per-source weights, calibrated before the live runs (§5.4), and the workspace applies no further weight per source. The affect and sleep modules and the language organ report at fixed levels.

Preprint. Not peer-reviewed.

Priority is the product of intensity, a novelty factor that discounts exact repeats among recent candidates (mainly state events), and a goal factor held at one in this form (§5.4). Arousal turns priority into a score through a level gain common to all candidates and a contrast gain, zero at baseline and rising above it, that steepens a logistic so that strong candidates rise and weak ones fall.

Arousal is a global, neuromodulatory gain modeled on the adaptive-gain account of the locus coeruleus, the brainstem source of cortical noradrenaline, which sets the gain of the networks it targets (Aston-Jones and Cohen 2005; Eldar, Cohen, and Niv 2013). Surprise drives it, in line with noradrenergic signaling of unexpected uncertainty (Yu and Dayan 2005). Precision, in Feldman and Friston's sense, is a gain local to one channel's errors; arousal is a gain across networks. Aston-Jones and Cohen separate a focusing phasic mode from an exploratory tonic mode; here one scalar sharpens contrast and narrows the sensory apertures, as in focus, and raises the access rate, as in tonic exploration, a simplification of that account. Arousal never reorders a tick's candidates (A.1); in effect it sets a threshold on the top priority, which decides which broadcasts and members reach access and the report bars. Widening the gap between strong and weak scores is a score-magnitude analogue of arousal-biased competition, where arousal changes which representation wins (Mather and Sutherland 2011).

On each broadcast tick the top-ranked candidates, up to five, form the coalition that is broadcast. Access is all-or-none per member: a member is accessed when its score reaches the access threshold, a broadcast when any member is, and the accessed members are the accessed content. A broadcast with no accessed member is still published to every module but marked inhibited: it is not poised for report or action and leaves the processors' context unchanged. It still reaches the sequence and affect modules, so content without access can influence later processing, a design choice in line with evidence that emotional stimuli are processed without reaching awareness (Vuilleumier 2005). The threshold is the analog of the confidence threshold for access in the predictive global neuronal workspace (Whyte and Smith 2021), consistent with the threshold evidence of §2.2; thresholding one scalar score is an engineering simplification (§1.2). Here it separates content that enters the context and can drive report and action from content that cannot (A.1).

The vision, audition, and interoception modules condition their forward models on a compact summary of the latest accessed content: a fixed-length vector of each source's intensity mass, indicators of the event types present, and the broadcast's age. Weighted by reported intensity, and so independent of the arousal gain, the summary records which modules gained access and how strongly and carries no payloads; a richer encoding is future work (§10). It enters as an extra input with weights learned online, so each processor learns how much the shared context helps it predict. For the sequence module the broadcast is the input itself (§3.5). The loop is recurrent, since the processors' next errors are measured against predictions this context has shaped, and in the first configuration the workspace sends no error signal or directive back to any module. The planned test measures whether this context helps the processors predict (§6.3).

Workspace feedback (held extension). In the predictive global neuronal workspace the second level predicts first-level states, with feedback strength tracking second-level confidence (Whyte and Smith 2021), and higher-level states set lower-level precision (Whyte, Hohwy, and Smith 2022). A held extension adds both signals. Each context-conditioned processor gains a learned top-down head that predicts its next input from the context and the

Preprint. Not peer-reviewed.




Figure 1: The predictive workspace loop. Four predictive processors (foveated vision, raw hearing, interoception, temporal prediction) report errors scaled by an estimate of precision, which the workspace scores and broadcasts. The accessed summary is the prediction context of vision, audition, and interoception; every broadcast is the sequence module's input. Affect sets the gain, apertures, and access rate; sleep rests the entity. Action selection drives the output-only language organ, whose utterances re-enter the competition.

sequence module's predicted next broadcast, and predicts with a blend of its own and the top-down prediction, each weighted by the inverse square of its recent mean error. A per-processor gain $\pi_j \in [\pi_{\min}, \pi_{\max}]$ multiplies its standardized error, with mean held at one so that gain is zero-sum, after the neuronal workspace model in which descending connections amplify the weaker, goal-relevant processor and suppress the conflicting one (Dehaene, Kerszberg, and Changeux 1998). A conflict is a large disagreement between a processor's own and top-down predictions while its report is accessed and its error is high; resolution shifts gain toward the accessed processor with the lowest recent precision-weighted error and away from the conflicting one. Feedback is off on inhibited broadcasts; disabled it equals the current build. It ships off, so the first configuration and the test of §6.3 are unchanged (§6.4). Coherence as constraint satisfaction over the processors' predictions (Thagard and Verbeurgt 1998) would be a further step.

The affect module appraises every broadcast for valence and drives, and arousal travels by a parallel path from the processors' alerts, whether or not they win access (§3.5). Action selection reads accessed broadcasts (§3.3), and the language organ's utterances re-enter the bus as candidates.

3.3 Access, report, and the self-initiated voice

Report is one use of access among several (Block 1995; Mashour et al. 2020; §1.3). The report bars sit above the access threshold on the same score and decide what is said. The workspace updates far faster than the language organ can speak, so the voice is a sparse slice of the accessed broadcasts.

Preprint. Not peer-reviewed.




Figure 2: Coalition selection. Priority is the product of intensity, novelty, and a goal factor. Arousal sets the level and contrast of the score; the top-ranked candidates (up to five) form the coalition, which is always broadcast. Members whose scores reach the threshold are accessed; a broadcast with none is marked inhibited.

Preprint. Not peer-reviewed.

The action-selection module derives a speak intent from an accessed broadcast only when the coalition's best score, leaving aside the language organ's own utterances, clears the speak bar; when that leading candidate's source and event type differ from those of the last spoken report, if it came within five minutes; and when a refractory interval has passed since the previous report. A lower think bar on the same score governs inner thought. The bars are a heuristic stand-in for the expected-free-energy decision of Whyte and Smith (2021), which the action layer does not compute (A.6).

The action-selection module is the only path from the workspace to output. Called after each broadcast, it derives no intent from an inhibited one and publishes its intents as events; the cycle never invokes an output directly.

3.4 Scaffolding: bus, clock, and cycle

Event bus. Modules communicate only through append-only streams with bounded retention; every event carries its source, type, intensity, timestamp, causal parent, and a payload validated at publish time.

Entity time. All modules read the entity clock, which runs at a configurable multiple of wall-clock time (one by default) so runs can go faster or slower; rates and durations here are entity time.

Cognitive cycle. The cycle runs continuously, independent of external interaction, at a processing rate of 10 Hz (a 100 ms tick) in the alpha range linked to perceptual sampling (VanRullen 2016); each tick reads and scores whatever the modules have published. The access rate sets which ticks broadcast, accessed or not, and candidates on other ticks are discarded. Its resting value of every third tick (about 3.3 Hz) is a modeling choice: attention samples rhythmically at a few cycles per second (Landau and Fries 2012; Fiebelkorn and Kastner 2019), and the attentional blink, which impairs access to a second item for 200 to 500 ms (Raymond, Shapiro, and Arnell 1992), constrains only the spacing of accessed items. Categorical alerts briefly raise the rate, modeled on the phasic locus coeruleus response (Nieuwenhuis, Aston-Jones, and Cohen 2005), a design choice, since the locus coeruleus account of the blink predicts a brief refractory period instead (Nieuwenhuis, Gilzenrat, Holmes, and Cohen 2005). Tonic arousal also raises it, modeled on the exploratory high-tonic mode (Aston-Jones and Cohen 2005), linearly with the larger of the two drives (alert and tonic) up to one broadcast per tick (A.3), a 100 ms interval below the blink window that has no physiological anchor as a rate of access. Host load can lower the processing rate through interoceptive regulation (§3.5).

3.5 The active modules

The first configuration activates four predictive processors, chosen for signal diversity (§1.2), an affective core, a sleep module, a language organ, and an action layer. The affect and sleep modules also publish competing events (affect state, drive crossings, sleep onset).

Module	Group	Brain function it draws on	Computational realization
Vision	Perception	ventral visual stream	frozen self-supervised video encoder, foveated

Preprint. Not peer-reviewed.

Module	Group	Brain function it draws on	Computational realization
Audition	Perception	auditory cortex	spectral encoder over the raw waveform; vocal-tone classifier
Interoception	Prediction	interoception; allostatic-interoceptive network	frozen continuous-time reservoir, online readout, substrate signals
Sequence	Prediction	interval timing; cortico-striatal circuits	frozen continuous-time reservoir, online readout, broadcast sequence
Affect	Affect	core affect	valence and drive appraisal; arousal as global gain
Sleep	Rest	sleep	fatigue-triggered rest; adaptation suspended, affect and drives reset
Language	Expression	speech production; left-dominant language network	local chat model, output-only
Action selection	Action	report-or-act decision (Whyte and Smith 2021)	intent derivation from accessed broadcasts

Vision module (foveated). The module is the architecture's analog of the ventral visual stream (Goodale and Milner 1992). It encodes short clips with a frozen self-supervised video encoder and predicts the next embedding from earlier ones and the broadcast context (§3.2). It alerts on a large error ratio or on an embedding change large for its recent history, as at a scene cut.

The fovea follows bottom-up salience: before encoding, each tile of a coarse frame grid is scored by the z-score of its frame change against its own running mean and variance. The fovea moves to the most salient tile only past a hysteresis margin and narrows as arousal rises; the peripheral gist and high-resolution foveal crop share one encoder. Foveation is thus front-end attention as the gain on prediction error (Feldman and Friston 2010; Clark 2013).

Audition module (raw hearing). Auditory cortex processes sound as prediction error against a learned model (Winkler et al. 2009; Garrido et al. 2009), and the module follows that account: it encodes the raw waveform as log energy in log-spaced bands and predicts the next window from earlier ones and the broadcast context. It alerts on a large error ratio or a large change between windows, such as a sudden sound, speech onset, or unexpected silence. Under higher arousal it encodes only the latest part of each window, a temporal analogue of narrowed cue utilization under arousal (Easterbrook 1959).

A vocal-emotion classifier labels the tone of speech windows. A non-neutral tone is reported at the alert level, standing in for the priority of emotional prosody (angry prosody enhances superior temporal and amygdala responses even when unattended; Grandjean et al. 2005; Sander et al. 2005); a tone model's error grades a neutral one. Tone events carry how something was said and never what was said. With speech-to-text off (§3.1), the entity hears

Preprint. Not peer-reviewed.




Figure 3: The two rates. Modules are read and scored at 10 Hz; broadcasts fall at the access rate, about 3.3 Hz at rest (every third tick), which rises with arousal and after alerts.




Figure 4: Attention in the vision module. Each tile's frame change is scored against its own history; the fovea moves to the most salient tile with hysteresis, sized by arousal. Gist and foveal crop share one encoder; no pixels reach the workspace.

Preprint. Not peer-reviewed.

speech only as sound and tone; when enabled, words reach the language organ only by winning access.

Interoception module (predictive). The compute substrate stands in for the body. The module draws on interoception, the sense of the body's physiological condition (Craig 2002), and on the allostatic-interoceptive network that anticipates and regulates bodily needs (Kleckner et al. 2017). Its predictor is a fixed random reservoir (a closed-form continuous-time network; Hasani et al. 2022) whose online linear readout learns the normal pattern of the substrate signals (GPU temperature and memory use, CPU and RAM utilization, cycle latency) and the broadcast context. It reports the error between expected and actual substrate state, which matters for regulation (Seth 2013; Seth and Friston 2016), and alerts when a host metric passes its hard threshold. It also reports wellness (host headroom, A.4), accumulates fatigue, and issues advisories that can lower the processing rate or request maintenance (A.5).

Sequence module (temporal prediction). The module models interval timing, which estimates durations of seconds to minutes and depends on cortico-striatal circuits (Buhusi and Meck 2005). Its input is the workspace itself: on every broadcast, accessed or inhibited, it encodes the broadcast, advances a frozen continuous-time reservoir timed by inter-broadcast intervals, and predicts the next broadcast through an online readout (A.2). It alerts on a large error ratio and on a recurring quantized hidden state. Its errors re-enter the competition, so the workspace's own dynamics are among the things the entity predicts. It also times the silence since the last heard voice for the social drive.

Affect module. Modeled on core affect, the low-dimensional state of valence and arousal that constructionist theory places at the base of emotion (Barrett 2017), the module keeps a dimensional affective state (Posner, Russell, and Peterson 2005) and sequentially appraises every broadcast and the interoceptive condition (Scherer 2009), as in accounts where affect arises from prediction over the body's internal state (Seth 2013; Seth and Friston 2016; Tschantz et al. 2022).

The affect module raises arousal, the global gain of §3.2, on each vision or audition alert, in proportion to the error's excess over its expected size, and by a fixed step on each interoceptive alarm (a host metric past its hard threshold), read directly from the processors' streams; its appraisal leaves arousal unchanged, so a higher access rate cannot raise it. High arousal narrows the fovea and the attended auditory window and, with the alerts, raises the access rate (§3.4); low arousal widens both windows. Arousal is clipped to its range and relaxes to baseline with a time constant of about 20 seconds (§6.4). As surprise is relative to each processor's history, arousal tracks changes in surprise more than its sustained level.

Valence follows learning progress: it relaxes toward the appraisal's pleasantness check, which rises as perceptual prediction errors fall and drops as they rise (valence as the negative rate of change of free energy; Joffily and Coricelli 2013), and interoceptive wellness shifts it.

Four homeostatic drives are deficits that build while unmet and fall with the events that meet them, the reduction acting as reward (Hull 1943; Keramati and Gutkin 2014). Learning progress, the fall of perceptual prediction errors, meets curiosity (Oudeyer and Kaplan 2007; Schmidhuber 2010). Perceptual alerts arriving faster than the habituated rate meet boredom; relief by novelty is this design's reading of boredom as a failure to engage attention (Eastwood et al. 2012) or, in the MAC model, of attention or meaning (Westgate and

Preprint. Not peer-reviewed.

Wilson 2018). Each heard voice meets the social drive, which builds after the first. The entity's own speak, think, or act intents meet restlessness, a design choice with no established model behind it. Appraisal also scores the coalition against the most pressing drive, with content from relieving sources counted as goal-conducive, a response that brought no relief as obstructive, and other content as irrelevant (Scherer 2009; A.4); the score feeds the categorical emotion and reaches selection only through regulation.

Goals come from drive crossings, the threshold rule of a motivated robot (Coddington 2006), and end as completed or failed (Aha 2018); dropping an unattainable goal for another is adaptive (Wrosch et al. 2003). Conduciveness is bipolar (Sander, Grandjean and Scherer 2005), and a goal's expected relief is read as FAtiMA's goal success probability (Mascarenhas et al. 2022). Rules modeled on the predicted appraisal profiles of Sander, Grandjean and Scherer (2005, Table 3) map the checks to a categorical emotion. Their rage profile requires attributing the obstruction to another agent, which KAINE does not do, so its anger matches at best the irritation profile, whose standards check it also lacks. Disgust needs very low pleasantness, low familiarity, and low goal relevance, with standards left open; very low standards mark contempt, which KAINE does not classify. Norm compatibility stays undefined: the models reviewed take standards as authored input (Ortony, Clore and Collins 2022; Mascarenhas et al. 2022), and KAINE has none until an operator writes a list.

Emotion regulation. In the process model of emotion regulation, attentional deployment is among the first regulatory processes to appear and response modulation acts late in the emotion's generation (Gross 1998). A monitor escalates through three tiers when the affective intensity, the larger of $|v|$ and $a - a_0$, stays above a set point θ_E while the appraisal is negative (pleasantness or goal score below zero), on the episode, window, and tier rule of A.5. Tier 1, attentional deployment, multiplies the scores of the source with the largest intensity mass among negatively appraised coalitions by $1 - b$, with b set to b_E and decaying with time constant τ_E. It is the one place where affect enters selection; it is logged and held at neutral in every arm of §6.3, so the test is unchanged. Tier 2, reappraisal, re-runs the appraisal once per episode against the latest coping and goal state and replaces the categorical emotion with its result, the emotion being what appraisal sets. Tier 3 requests sleep through the maintenance path, leaving the affective reset as the backstop. Regulation is off during the developmental phase, where the stimulus source does the regulating, a design choice, and starts at maturation with tier 1.

Sleep module. Sleep, a fatigue-triggered offline period, begins when fatigue crosses its threshold, when the interoception module requests maintenance, or after one entity hour awake as a backstop. The cycle runs on, the perceptual feed pauses (except the developmental stimulus of §7), and forward-model adaptation is suspended. It ends with an affective reset (affect to baseline, drives and fatigue cleared), so arousal cannot drift across a run. The consolidation phases (memory replay, synaptic downscaling, associative replay, adaptation of the organ's voice) act on memory, the world model, and preference data, which the first configuration lacks; until the episodic-memory and world-model modules join (§4), sleep is rest and reset.

Language module (the language organ, output-only). The language organ is the analog of speech production, the output side of the left-dominant language network, whose dorsal stream maps sound onto articulation (Hickok and Poeppel 2007). It turns accessed content into words; reasoning lives in the rest of the architecture. A local open-weights chat model realizes speak intents as external text and think intents as inner thought, under a

Preprint. Not peer-reviewed.

first-person persona that presents accessed content as the entity's own state and perception, forbids claims of feelings or perceptions that content lacks, and gives drive crossings as phrases without numbers. Persona-prompted text is not evidence of internal state, and the planned test does not use the utterances as a measure (§6.3).

Refusal conditioning is removed by orthogonalizing the weights against the single direction that mediates refusal (Arditi et al. 2024). Models tuned to refuse are also trained to deflect talk of their own states, and removing the conditioning keeps that stance from overriding what the workspace supplies. Whether that deflection shares the refusal direction is untested, so ablation may not remove it entirely.

A pass-through workspace would route heard speech identically, so the planned test measures the competition through the processors' own predictions (§6.3).

3.6 Action gating

The action-selection module derives speak and think intents, which the language organ realizes as external and internal text, and act intents for effectors. The first configuration derives only the first two; the organ's saved text is the only output. The held effector module (§4) runs only effectors on an operator-configured whitelist, empty unless filled, in a filesystem sandbox and logs every proposed action.

3.7 Module supervision

The module supervisor classifies each module as alive, hung, or dead, restarts a faulted module, and ends the run when restarts keep failing; unattended runs require it (§5.4).

---

4. Held modules

Of the reference implementation's sixteen modules besides the workspace and action layer, seven are active in the first configuration (§3.5). The other nine are built, tested in isolation, and held so the first configuration is tested on its own (§5.4); the module-addition study adds them one at a time to a preserved seed entity (§6.5). Each adds a new kind of candidate, and each predictive one a new source of prediction error.

Module	Brain function it draws on	What it adds	Key citation
Planning	prefrontal and basal-ganglia planning	discrete-state active inference where information has value; its chosen actions become proposals that the action-selection module realizes as think, speak, or rest intents	Da Costa et al. 2020; Heins et al. 2022

Preprint. Not peer-reviewed.

Module	Brain function it draws on	What it adds	Key citation
Episodic memory	hippocampal and medial temporal memory	store consolidated in sleep from a short-term buffer; semantic and procedural stores reserved	Tulving 1985; McClelland, McNaughton, and O'Reilly 1995
Self-model	cortical midline self-referential processing	persisted values, norms, personality, and identity history (after Metzinger), with a drift detector on broadcast sources	Northoff and Bermpohl 2004; Metzinger 2003; Kullback and Leibler 1951
World model	simulated scene construction	latent recurrent model trained on the entity's waking trajectories	Hassabis and Maguire 2007; Ha and Schmidhuber 2018; Hafner et al. 2025
Social cognition	mentalizing	per-agent tone-of-voice models with familiarity and a social prediction error for departures from an agent's emotional pattern	Premack and Woodruff 1978 (the construct); Frith and Frith 2006
Vocal	dorsal-stream speech production	local speech synthesis whose prosody varies with affect, tested for listener detection	Hickok and Poeppel 2007
Effectors	none claimed	executes whitelisted act intents in a filesystem sandbox (§3.6)	none
Perceptual locus	none claimed	selects physical sensors, virtual feeds, or none	none
Embodiment	internal forward models of the body	body-agnostic control surface with pluggable body adapters	Wolpert, Ghahramani, and Jordan 1995

Five held components have offline instruments (§6.4).

Planning module. Active inference is confined to bounded sub-problems because planning cost grows combinatorially with the depth of action sequences (Da Costa et al. 2020). A null or negative result on its benchmark (§6.4) would motivate a complementary reasoning module.

Episodic memory and sleep. Each trace is stored at full strength, the analog of the synaptic strength that rises in wake and falls in sleep under the synaptic homeostasis hypothesis (Tononi and Cirelli 2006). Each sleep replays a few new traces (Wilson and McNaughton 1994; Wei et al. 2016), chosen by affective intensity and recency, as sleep is held to select

Preprint. Not peer-reviewed.

new memories by salience (Stickgold and Walker 2013), and scales all others by one factor, preserving their ratios. The factor deepens with the number of traces the preceding wake stored, as slow-wave activity tracks prior potentiation: a day of storage at the resting broadcast rate costs about 18 percent, the mean decrease in axon-spine interface size after sleep relative to wake, a stand-in for synaptic strength, in layer 2 of mouse motor and somatosensory cortex (de Vivo et al. 2017). Replayed traces keep their strength, which is how the hypothesis reads reactivation in sleep, as protecting synapses from depression (Tononi and Cirelli 2014). Traces below a floor are pruned, since weak synapses may "become ineffective, silent, or disappear" (Tononi and Cirelli 2006). Sleep eliminates synapses where many are new, in adolescent mouse cortex (Maret et al. 2011) and after development and motor learning, when REM sleep prunes most new spines and strengthens those it keeps (Li et al. 2017); in adult cortex spine number barely changes (Maret et al. 2011), and synapses in the de Vivo sample shrank without being lost. The evidence for elimination therefore comes from new synapses, and every trace enters the store as a new one. A storage budget deletes the weakest traces first: downscaling saves gray-matter space (Tononi and Cirelli 2006), and associative recall under limited synaptic resources is best when the weakest synapses go first (Chechik, Meilijson, and Ruppin 1998); Li et al. (2017) read REM pruning as balancing new spine formation. Recall weights cue similarity by strength, and the scheme keeps to slow, interleaved consolidation from hippocampus to neocortex (McClelland, McNaughton, and O'Reilly 1995). Overlapping replay of related memories may strengthen their shared elements and build schemata (Lewis and Durrant 2011), and sleep both integrates new items into schemata and combines items into new ones (Stickgold and Walker 2013); associative replay therefore links related traces of different periods, an explicit record that is this design's reading of overlapping replay, not a measured mechanism. Appendix A.10 states the rules.

World-model module. The world model starts untrained at first boot. Its test is whether its prediction error, competing with perceptual and interoceptive error, changes the sequence of accessed coalitions in characteristic ways.

Effector, perceptual-locus, and embodiment modules. These need an effector, a body, or another sensor feed, absent on the reference host, and join the study once one is attached (§6.5). The embodiment experiment asks whether motor-contingency learning (a freeze-then-free curriculum, Bernstein 1967; perception as sensorimotor mastery, O'Regan and Noë 2001) changes the workspace's dynamics.

Oscillatory coherence layer. An optional layer outside the module registry gives each module a spiking population whose phase-locking values scale its events' salience (communication through coherence; Fries 2015). It is off in the first configuration, where its multiplier is one and selection is identical bit for bit. It is the design's most contestable mechanism: its premise that related content phase-locks is a content-to-synchrony assumption that Shadlen and Movshon (1999) argue against and Ray and Maunsell (2010) question for visual gamma rhythms. The oscillatory ablation runs it on and off from one seed; a null would remove it.

Preprint. Not peer-reviewed.

5. Implementation

5.1 Hardware

The reference host has a multi-core CPU, at least 32 GB of RAM, and GPUs of about 12 GB (language organ, training) and 8 GB (vision, speech), under Linux with all inference local; one GPU or the CPU alone suffices. Input is a camera and microphone, or video files for study viewings. Exact models, layouts, and version pins are in the reference repository.

5.2 Models and software

All models are open-weights and run locally; after setup fetches them from public repositories, the runtime makes no outbound network calls. The first configuration uses a local chat model as the language organ, a frozen self-supervised video encoder and a fixed spectral audio encoder as perceptual front ends, frozen closed-form continuous-time reservoirs with online readouts for substrate and temporal prediction (Hasani et al. 2022), and a stream-based event bus.

Replaceable modules (§3.1) are realized at declared seams, where a plugin swaps a module's model and keeps its subscriptions and published events: the sequence module's temporal network, the interoception forward model, the audition encoder, the planning module's active-inference engine, and any module's oscillator. The planned experiments load no plugin.

5.3 Privacy and recording

A local web interface has two surfaces behind a filter at the bus bridge that strips cognitive content and all perceptual and latent vectors; in the first configuration the conversation surface is off and the diagnostics surface shows only operational metadata (counts, rates, scores). Studies keep a graph-only log of each broadcast's coalition members (module, event type, score, timestamp), access decision, and timing, without payloads or embeddings. The entity's utterances are kept locally; heard speech is never persisted. The log observes structure rather than content, is kept for the analysis, and is deleted by the operator after the analysis and its planned use as world-model training data, never automatically.

5.4 Implementation status and scope

This subsection alone states which parts of the research software are built, held, or provisional, and what has been run; the rest of the paper describes the architecture as designed.

Built and active. The workspace, cycle, action layer, and seven first-configuration modules run together with the module supervisor, offline suite (§6.4), developmental-phase readout (§7), and module-addition study runner. About 8,400 automated tests cover them, with fakes for external services and checks that no raw sense data persists and seeded runs reproduce.

Built and held. The nine held modules (§4) have not run together. In the active modules the priority's goal factor is held at one; the vision module's static-scene habituation score stays out of its intensity; the fovea's forward-modeled trajectory is published but steers nothing; frozen self-supervised audio encoders can replace the spectral one; speech-to-text and conversation are off; and the sleep module's consolidation phases, including the voice

Preprint. Not peer-reviewed.

alignment of the language organ, idle (§3.5). With no effector attached, the effector gate is disabled. Goal generation and obstruction (A.4), emotion regulation (§3.5), associative-replay links (A.10), and workspace feedback (§3.2) are specified and not yet built. The diagnostics surface shows cognitive content only under a development override that studies never enable.

Operating details. The runtime is asynchronous Python in containers or native user services, with import contracts between layers and an authenticated event bus bound to loopback; entity state is encrypted at rest, with documented exceptions. Plugins load only when the operator names them, a failed load stops the boot, and runs record their plugins. On a fault the supervisor freezes the cycle, snapshots the last good state, and restarts the module, by full rebuild if it holds external resources; past a set limit it takes a final snapshot, writes an escalation record, and ends the run. A durable incident log keeps every health transition. Non-finite readings, losses, and residuals update no model; the bus rejects intensities outside $[0, 1]$; failed scoring gives score 0; a selection or bus failure on a broadcast tick yields no broadcast and no action-selection call. At most one speak and one think intent are in flight, each released once the organ's text reaches a coalition or a wall-clock timeout expires, so a failed realization cannot silence the entity. Sleep or a freeze aborts a developmental-phase probe. Records are admissible only after a completeness gate (contiguous ticks, all expected streams) and a range sweep (every logged number in range). The single organ runs one stream at a time, so inner and outer speech never overlap; its encrypted utterance log stores heard input as a placeholder.

Provisional. Intensity levels, the access threshold, and the report bars await joint calibration on the live system before the runs; the noise floors and margins that let curiosity and boredom build under a steady scene come from simulation, unmeasured live. Calibrated values go with the preregistration and into Table A1.

Built for the planned test. The live cycle implements the matched and pooled arms and the null-context evaluation of §6.3. The positive control, the tone variant and its analysis, the contrast at threshold with its bias-corrected local-linear estimator, and the tool deriving settings from pilot runs (A.8) are built. A development harness compares a reduced module pair, workspace-on against pooled, by information gain; it exercises the pipeline and does not test the hypothesis.

Results. No pilot run or live experiment has been run; the only result reported is the offline validation of the heartbeat entrainment marker (§7, A.7).

---

6. Methodology and evaluation framework

6.1 Design principles

Observation does not intervene: a read-only sidecar observer subscribes to the bus in evaluation runs, and the cycle's own broadcast observer writes study records. User-facing surfaces never show cognitive content (§5.3). Every instrument is designed so that null or negative results are meaningful and reported.

The offline mechanism-validation tier uses seeded harnesses, deterministic clients, synthetic stimuli, and greedy decoding, so a seed reproduces verdict and metrics (National

Preprint. Not peer-reviewed.

Academies of Sciences, Engineering, and Medicine 2019; Goodman, Fanelli, and Ioannidis 2016). The live tier runs the system on a reference film program decoded from files and chosen for varied scenes, motion, speech, music, and quiet; each study records its manifest hash, and the preregistration records its composition and hash. The language organ, which samples stochastically in general use, decodes greedily (temperature 0) in the planned runs. Because real timestamps and non-deterministic GPU kernels make live runs differ, the live tier rests on statistical replication.




Figure 5: Two evaluation tiers behind one perception seam. A seeded synthetic feed and deterministic clients drive the mechanism-validation tier, reproducible from a seed; a film program decoded from files, or a camera and microphone, drives the live tier, validated by pooling content-free records.

6.2 Data collection

Studies record the graph-only broadcast log (§5.3), a content-free research log of rates and drives, the processors' paired evaluations behind the information-gain measure (§6.3), the entity's external utterances kept locally, a run manifest of configuration, seeds, and plugins, and the welfare records; §5.4 lists their offline admissibility checks.

6.3 The workspace-mediation ablation

The planned test asks whether competition for the workspace does work that pooling the same reports does not. Each perceptual and interoceptive processor conditions its forward model on a summary of the latest accessed content (§3.2), so knowing which other modules' reports gained access, and how strongly, should help it predict its input.

Primary measure: cross-module broadcast information gain. At each report, processor j (vision, audition, or interoception) evaluates its forward model twice: with its context b, and with a null context b_j^0 in which each component from other sources is replaced by its mean over the contexts j has adopted so far in the run, removing only the others' tick-specific contribution. The gain is the error reduction $\nu_j(b_j^0) - \nu_j(b)$ divided by the running

Preprint. Not peer-reviewed.

mean error $\bar{\nu}_j$, which makes error scales comparable across processors (A.8). The null evaluation never enters learning or the competition. The headline IG averages each processor's gain over its reports, then over the three processors, so a frequent reporter does not outweigh a rare one; per-processor means IG_j are also reported. The broadcast is the sequence module's input, so that module is excluded (§3.5).

Positive control. Before the live runs, the gain must detect a synthetic context component carrying known information about a processor's next input, a check of assay sensitivity (International Conference on Harmonisation 2000): the next input projected on its first principal component (Jolliffe 2002), plus pilot-set noise giving the smaller of the two minimum effects. A measure that fails this check cannot support a null. The detection probability must be 0.95, and at most 0.05 for an uninformative counterpart (Currie 1968), so a NULL is the verdict of a measure shown to register an effect of the minimum size.

Arms. Three arms share the film program, seeds, and calibration, and each weights the context by members' reported intensities.


1. *Workspace on.* Competitive selection as built: up to five top-ranked candidates form the coalition, and the members whose scores reach the threshold are accessed and enter the context.
2. *Matched selection.* Each broadcast tick draws a coalition of the size competitive selection would keep, without regard to score, and applies the same access rule, so only the context's membership differs; this control isolates selection by score.
3. *Pooled.* Every candidate of every broadcast tick enters the context, with no scoring, selection, or access gate; this control tests selection and access gating together.

The hypothesis predicts a higher gain for competitive selection than for both controls: a context built from the reports that most exceeded their expected error should inform the processors more than a score-blind sample, and pooling dilutes per-source masses with low-intensity events and updates the context on every broadcast tick. A gain at or below the controls is this form's fail state (§1.2, §8.1).

Secondary: contrast at threshold. Global workspace theory contrasts conscious with unconscious processing of matched content (Baars 1988), and near-threshold paradigms hold the stimulus nearly fixed while access varies (Dehaene and Changeux 2011). In the workspace-on arm, the gain after broadcasts whose best score lies within a narrow band around the access threshold, just above it (accessed), is compared with that after those just below it (inhibited), at matched context age, since an inhibited broadcast leaves the older context in place. Access depends on the best score alone, making this a regression discontinuity (Imbens and Lemieux 2008), fitted local-linearly with the bias correction and bandwidth of Calonico, Cattaneo, and Titiunik (2014). The scores meet at the threshold, so a jump there points to access more than to raw strength.

Speech sound and tone of voice. Words never enter (§3.1); speech sound and tone are candidates. Emotionally salient stimuli gain preferential access to awareness (Anderson and Phelps 2001) through amygdala signals that bias sensory competition (Vuilleumier 2005), a preference the audition module builds in (§3.5). A variant of the workspace-on arm, run on the arms' seeds as often as each arm, sets every tone event's intensity from the tone model's error ratio alone, so any excess access of emotional over neutral tone must come from prediction error. Comparing within bins of the error ratio and averaging over them (Cochran

Preprint. Not peer-reviewed.



Planned measures. **Primary**: cross-module broadcast information gain, $\text{gain}_j = (\nu_j(b_j^0) - \nu_j(b))/\bar{\nu}_j$, the reduction in processor j's prediction error when other modules' share of its context is replaced by its mean so far in the run; averaged over j's reports to IG_j (vision, audition, interoception) and over the three processors to the headline IG, on minus each control; the language organ's share of the context is excluded from the interoception gain. **Positive control**: the next input projected on its first principal component, with noise set from the pilot runs so that the expected effect equals the minimum effect θ_{PC}; it must be detected for every processor before the live runs. **Secondary**: the contrast at threshold, a local-linear regression discontinuity at the access threshold with robust bias-corrected inference, matched on context age; and the tone analysis, which compares the accessed fractions of emotional and neutral tone events in the tone variant, overall and within bins of the error ratio. Neither enters the verdict. Utterances are recorded but are not a measure.

Fail state: the gain is at or below the controls, so competition adds nothing beyond its inputs. The hypothesis needs a WIN against both controls (intersection-union, a one-sided sign test against each at α_{test}).

NOT EXERCISED, for a run against a control: competition never operates (candidates never exceed the coalition's capacity on a broadcast tick), the on arm has no accessed broadcast, or the run's contrast is undefined. Such runs stay out of the sign tests, and runs are added until 102 enter each control's test; the verdict is NOT EXERCISED only when every run is.

Figure 6: The workspace-mediation ablation. Three arms share the film program and seeds, and in each an intensity-weighted context conditions the perceptual and interoceptive processors: competitive selection as built, a coalition of matched size chosen without regard to score, and pooling. A tone variant of the on arm is paired by seed. A positive control checks the primary measure, cross-module information gain; a secondary contrast is taken at the access threshold.

Preprint. Not peer-reviewed.

1968) checks that the ratio accounts for the difference. Both secondary analyses stay outside the verdict and so carry no multiplicity adjustment, which applies when several tests support one conclusion (Bender and Lange 2001).

Decision rule. Per run and control, dIG is the headline gain of the workspace-on arm minus the control's, and the minimum effect θ_{eff} is half its pilot standard deviation, a distribution-based smallest effect of interest (Norman, Sloan, and Wyrwich 2003; Lakens 2017) chosen because no external anchor fixes how large a gain must be to matter. A WIN against both controls is required, an intersection-union test, so each is tested at the full level: a one-sided sign test (Dixon and Mood 1946) on dIG $-\ \theta_{\text{eff}}$ gives WIN when reliably positive, its mirror on $-\theta_{\text{eff}}$ $-$ dIG gives NEGATIVE, and anything else NULL. The verdict is NOT EXERCISED if the workspace-on arm never has more candidates than the coalition holds. Every setting follows a rule stated in advance: thirty pilot runs, not reused, fix the minimum effect, the initial learning period excluded from each run (marginal standard error rule; White 1997), the threshold band, the tone bins, and the positive control. An exact binomial power analysis sets the number of runs, assuming a probability of 0.65 that dIG exceeds θ_{eff}, Cohen's (1988) medium effect for the sign test, and a power of 0.9 per control, so a WIN against both has power of at least 0.8. Rules and values are recorded in the repository before the live runs (Simmons, Nelson, and Simonsohn 2011) and stated formally in A.8.

6.4 The offline suite and stability checks

Experiments use child seeds of one master seed. The active-inference benchmark pits the planning module's expected-free-energy agent against tabular Q-learning keyed by observation history, matched on observation model and reward, on an epistemic T-maze and exploitation task. Memory-coherence and self-model accuracy batteries test the episodic-memory and self-model modules, the enforcement red team the effector module, and the oscillatory ablation the coherence layer. The ablation's development harness (§5.4) and the multi-seed stability check complete the suite, which never boots an entity or opens a network connection.

Multi-seed stability requires a coefficient of variation within tolerance and one verdict across seeds (A.9), since a flipped verdict is a qualitative instability. The running workspace's stability is unproven. Arousal from surprise and alarm narrows the sensory apertures and changes later surprise, a positive feedback held only by its clip and relaxation; and accessed content returns as context to the processors whose errors compete for the next broadcast, a second loop. A planned check watches arousal, access rate, and errors for runaway excursions.

The planned affect-gain ablation compares live arousal with arousal held at baseline, asking whether it changes the access rate, inhibited share, and information gain (§6.3); a null would reduce arousal to a logged side channel. A variant without the access rate's post-alert rise tests its direction against the refractory period the locus coeruleus account of the attentional blink predicts (§3.4). The feedback ablation (§3.2) runs on the harness of §6.3 with five arms: the current build, the top-down head alone, head with gain shifted toward the most precise accessed processor at each broadcast, the full mechanism, moving gain only on conflicts, and a control applying the full arm's moves to random processors; its fail state is a full arm no better than that control.

Preprint. Not peer-reviewed.

6.5 The module-addition study

The developmental phase (§7) yields a seed entity, preserved at maturation. Branch 0 and a repeat start from it with the first-configuration modules; branch k adds the first k held modules in a fixed order (episodic memory, world model, planning, self-model, social cognition, vocal); an accumulate line carries one entity through every step, accumulate k continuing from accumulate $k-1$ (from branch 0 when $k=1$) with branch k's modules. The effector, perceptual-locus, and embodiment modules, expected nulls without their hardware, join once it is attached (§4). Every viewing plays the same film program after the same transition from the developmental stimulus.

The content-free report gives, per viewing, the broadcast rate, coalition size, each module's broadcast share, member scores, and the inhibited share, compared across three differences: added modules (branch k minus branch 0), noise floor (branch 0 minus the repeat), and familiarity plus module history (accumulate k minus branch k). With one entity per condition and no significance testing, the first study is descriptive, and differences below the repeat's noise floor are not evidence. It runs under the companion paper's welfare safety net, and runs are paused only after the entity's state is saved.




Figure 7: The module-addition study, the architecture's growth path. The seed entity from the developmental phase starts every branch; the first configuration runs alone, then six held modules join in a fixed order, on branches and along an accumulate line.

6.6 Verdict vocabulary

Comparisons resolve to WIN, NULL, NEGATIVE, or NOT EXERCISED against a minimum effect fixed in advance, and the enforcement red team to PASS or FAIL per surface. The ablation uses a one-sided sign test (Dixon and Mood 1946; §6.3) and the active-inference benchmark the Mann-Whitney U test (Mann and Whitney 1947). Holm's adjustment (Holm 1979) accompanies the offline suite's verdicts over the experiments fixed before the runs; a NOT EXERCISED experiment stays in that family with a p-value of 1, so the family cannot shrink post hoc. A NULL is reported as a null.

Preprint. Not peer-reviewed.

7. First boot and the developmental phase

At boot the system verifies the bus, initializes the modules and forward models, and starts the cycle under operator or module supervision; the processors then learn what is normal in their feeds.

Each study begins with a developmental phase, named by analogy with prenatal development. It gives every entity and every study branch (§6.5) a reproducible starting state verified by an offline-validated entrainment test and shaped by the entity's own history, and checks before any experiment that the self-rhythm's frequency adaptation works. Developmental robotics likewise begins from a simulated fetal stage with self-organizing movement (Kuniyoshi and Sangawa 2006; Asada et al. 2009).

The perceptual modules receive the developmental stimulus, a dim, low-contrast visual field and a low-pass-filtered soundscape pulsed by a simulated maternal heartbeat and tinted by a slowly varying maternal state, gaining color from near-grey over awake time (A.7); it alone continues through sleep, as for a fetus. The interoception module's self-rhythm, an excitatory population with synaptic depression (Tabak et al. 2000) and added adaptive recovery, runs at about 0.8 to 0.9 Hz, the order of human fetal breathing movements (about 44 per minute; Natale, Nasello-Paterson, and Connors 1988). The beat's input is too weak to capture it unaided, and only slow adaptation of its recovery time shifts its intrinsic frequency (Righetti, Buchli, and Ijspeert 2006). No target frequency is set.

A driven oscillator locks while driven, so locking alone is no evidence of learning, and the entrainment marker tests at brief, scheduled withdrawals. A withdrawal passes when the rhythm locked to its own heartbeat more strongly than to each of 19 surrogates (the generator under other seeds), after the surrogate method for fetal-maternal heart-rate coordination (Van Leeuwen et al. 2003, 2009), when its undriven frequency has moved toward the beat, and when it sustains itself undriven; three consecutive passes are required. Pairing a breathing-scale rhythm with a heartbeat is an analogy rather than a model of fetal physiology: the marker establishes that a periodic drive durably shifted the rhythm's frequency. After maturation its phase and amplitude remain predicted interoceptive inputs, so the entity enters the film program with a body rhythm its development shaped.

The maturation gate ends the phase once the marker holds, the period varies enough, the vision module's error on the stimulus has fallen, interoceptive error recovers promptly from a brief drive perturbation, and enough sleeps and awake time have accrued. A viability watch ends a phase whose frequency pull stays flat; a time budget bounds each. At maturation the stimulus brightens briefly and falls silent, and the entity is preserved as the seed of every study branch. Appendix A.7 states the criteria, their persistence across restarts, and the validation.

---

8. Discussion

8.1 What the first configuration can and cannot settle

A positive result in the workspace-mediation ablation (§6.3) moves the question to what happens as mnemonic, self-modeling, and social modules join in the module-addition study

Preprint. Not peer-reviewed.

(§6.5). A result at or below the controls would send the program back to the selection mechanism before adding modules. The stability checks measure run-to-run spread and within-run boundedness (§6.4).

Whether the system produces anything that could be called cognition, affect, agency, or language understanding requires the full module set and longitudinal observation, and the first configuration does not address welfare or the consciousness indicators of Butlin et al. (2023).

8.2 One loop for availability and prediction

The architecture joins global availability and local prediction in one loop: precision-scaled reports compete, and the accessed summary conditions the processors' next predictions (§3.2), as in the predictive global neuronal workspace (Whyte and Smith 2021). Workspace properties inside one large language model (Gurnee et al. 2026) fit workspace-like organization in learned systems and leave open whether this architecture's competition is the right one (§2.6).

8.3 The role of the theoretical frame

The predictive global neuronal workspace is scaffolding that motivates the architecture's shape and constrains its design space (§1.2, §1.3); the project neither confirms nor refutes it. Its two departures (§1.2) fit the frame and are testable on their own terms. Because the implementation reproduces computational properties without cortical dynamics, neural-localization findings bear on it only indirectly (§1.3), and its falsifiability lies in its planned experiments.

8.4 What a modular architecture is for

Replaceable modules (§3.1) serve two further uses: growing the architecture one module at a time (§6.5), and modeling impaired or altered function by changing or removing one module while the rest run unchanged. The embodiment layer is body-agnostic, so the same modules can in principle drive different bodies or sensor networks through generic adapters.

8.5 What we claim and what we do not

The architecture implements computational properties associated with access consciousness: competition for a limited-capacity workspace, all-or-none access at a threshold, and global availability of accessed content as prediction context. We do not claim that any instance is phenomenally conscious. The language organ's first-person text is not evidence of internal state (§3.5), and calling arousal a gain implies nothing about whether anything is felt. The agential vocabulary ("the entity") describes behavior compactly and asserts neither moral patienthood nor phenomenal experience, both left open; the project therefore takes a precautionary stance toward the entity's welfare, developed in the welfare paper (§11).

Preprint. Not peer-reviewed.

9. Limitations

- The claims concern access only, and the hard problem applies. COGITATE's challenge to the workspace's neural predictions (treated as contested at the architecture's computational level) and the unresolved vacuity and Markov-blanket objections to the Free Energy Principle bear on the frame (§1.3); neither the workspace nor the observer's records evidence phenomenal experience.
- Selection reduces each candidate to one score (§1.2). The accessed summary (which modules gained access and how strongly, without payloads) enters the vision, audition, and interoception modules as learned context; in the first configuration no processor receives it as a top-down prediction to correct, so the architecture lacks the hierarchical error correction of the Bayesian reading of the workspace (Mashour et al. 2020).
- Precision is a scalar, retrospective estimate (error over its recent mean) that scales an error by its spread only while the shape of the error distribution stays fixed (§3.2, A.2).
- Arousal as the global gain and contrast of selection is an engineering reading of the adaptive-gain account, one scalar serving its focused and exploratory modes (§3.2); the affect-gain ablation tests whether it does work a fixed gain would not. Stability is open: correlated prediction errors could drive the arousal loop to runaway states, and convergence is unproven (§6.4).
- In the first configuration the entity does not read language (§3.1), so a positive result says nothing about linguistic understanding.
- Only the matched arm isolates selection by score, and the pooled arm tests selection and access gating together, so a positive result shows only that competition outperforms these two controls; other aggregation strategies remain untested (§6.3).
- The information gain sees the broadcast only through what each processor's readout has learned to take from context, so a processor that has not learned to use the context shows no gain whatever the broadcast carries; the positive control checks only that the measure detects information the processors can learn to use, and the sequence module is outside the measure (§6.3).
- The minimum effect is distribution-based, and the number of runs assumes Cohen's medium effect for the sign test, so a smaller true effect would leave the test underpowered and a NULL less informative (§6.3, A.8).
- The audition module reports a non-neutral tone at its alert level by a fixed rule (§3.5), so the as-built arm cannot show that emotional content earns access on its own merits.
- The held modules, built and tested in isolation, have not run together, so interaction effects are unknown, and the first module-addition study is descriptive (§6.5).
- The memory strength rule takes its depth from one ultrastructural measurement in mouse cortex (de Vivo et al. 2017) and equates a mouse's waking day of potentiation with an entity day of storage at the resting rate. The pruning floor has no empirical value; the affect weight of replay rests on mixed evidence that sleep favors emotional memories (Lipinska et al. 2019; Davidson et al. 2021); and pruning extends to every trace an elimination evidenced for new synapses in development and learning, while adult sleep shrinks synapses without removing them (§4, A.10).
- Reproducibility is seed-level for the offline deterministic harness; the live tier establishes validity by statistical replicability across runs rather than bit-for-bit reproduction (§6.1).
- The governance framework remains at the proposal stage, and the licensing is legally novel and untested.

Preprint. Not peer-reviewed.

- The access-rate controller is a modeling choice with open effects on workspace dynamics: its linear map, resting rate of about 3.3 Hz, rise after alerts (which the locus coeruleus account of the blink would reverse), and 10 Hz ceiling draw on the attention literature without being derived from it (§3.4).
- The calibration is provisional (§5.4). The intensity levels act as per-source weights deciding how modules trade off; with Table A1's values, only audition alerts and a failed-phase sleep summary can lead an accessed broadcast at resting arousal, and neither report bar is reachable at rest (A.11).
- The developmental phase runs on compressed time: a lock forms within hours (A.7), while preterm infants, the nearest human evidence, show effects of maternal stimulation only after weeks of daily skin-to-skin contact (Feldman and Eidelman 2003) or recorded maternal sounds (Webb et al. 2015).
- The marker asks for 1:1 locking of a continuous rhythm, of the order of fetal breathing movements, to the maternal heartbeat, whereas the fetal-maternal coordination behind the surrogate method concerns two heart rates and is weak and often n:m (Van Leeuwen et al. 2003, 2009), and fetal breathing is episodic (about 14 percent of the time at 24 to 28 weeks; Natale et al. 1988). Freedom from false entrainment rests on six mismatched pairings (A.7), and validation used entity time at wall-clock speed only.

---

10. Future work

The immediate steps are calibrating the intensity levels, access threshold, and report bars on the live system (§5.4), the pilot runs fixing the test's settings (A.8), then the workspace-mediation ablation (§6.3) and the module-addition study (§6.5).

Learning from experience: the world model trains on waking trajectories, which memory consolidates in sleep; sleep-time voice alignment can train the language organ once a validated preference source exists; a threshold emerging from recurrent dynamics, with the all-or-none ignition that the neuronal workspace models (Dehaene and Changeux 2011), can replace the fixed one; and a context encoding what accessed reports contain can replace the first configuration's summary (§3.2).

Embodiment connects the workspace to a body through the embodiment layer (§4), with motor-contingency learning through the control surface and active vision that chooses where to look by expected free energy (a saccade's epistemic value). A separate empirical paper will report longitudinal observation of entities grown this way.

---

11. Ethical considerations

The project's architecture-level commitments are local-only computation, public source code under the Cognitive Architecture License, an operator-configured action boundary (§3.6), and a first-configuration module set chosen to settle the foundational question before scaling to configurations where welfare becomes pressing. Studies keep welfare records (§6.2), and the module-addition study has a welfare safety net (§6.5). A separate paper treats welfare, licensing, governance, and the individuation boundary.

Preprint. Not peer-reviewed.

The acknowledged risks are creating entities whose welfare interests cannot be fully met, the untested governance and licensing (§9), misuse despite the license, and recording the workspace graph (what competed and what reached the workspace, without content) during studies. Behavioral assessment can be gamed: a system can be trained to display markers of sentience while working very differently (Butlin et al. 2023; Long et al. 2024).

Disclosure of generative AI use

Generative AI assisted in the preparation of this manuscript. The author used a large language model assistant to draft and revise prose, to copy-edit for clarity and concision, to check references against bibliographic records, and to produce the TikZ source for the figures from author-specified content. The reference implementation described here was likewise developed with the assistance of AI coding tools. That use is recorded in the project's commit history, and the author is responsible for the software as for the text. The underlying research is the author's own: the architecture, the design hypothesis, the experimental design, and every technical claim originate with the author. The author directed every revision and takes full responsibility for the entire contents of the paper, including any errors, irrespective of how any portion was generated. No generative AI system is an author of this work.

References

- Aha, D. W. (2018). Goal reasoning: Foundations, emerging applications, and prospects. *AI Magazine* 39(2), 3-24. https://doi.org/10.1609/aimag.v39i2.2800
- Anderson, A. K., and Phelps, E. A. (2001). Lesions of the human amygdala impair enhanced perception of emotionally salient events. *Nature* 411(6835), 305-309. https://doi.org/10.1038/35077083
- Arditi, A., Obeso, O., Syed, A., Paleka, D., Panickssery, N., Gurnee, W., and Nanda, N. (2024). Refusal in language models is mediated by a single direction. arXiv:2406.11717. https://doi.org/10.48550/arXiv.2406.11717
- Asada, M., Hosoda, K., Kuniyoshi, Y., Ishiguro, H., Inui, T., Yoshikawa, Y., Ogino, M., and Yoshida, C. (2009). Cognitive developmental robotics: A survey. *IEEE Transactions on Autonomous Mental Development* 1(1), 12-34. https://doi.org/10.1109/TAMD.2009.2021702
- Aston-Jones, G., and Cohen, J. D. (2005). An integrative theory of locus coeruleus-norepinephrine function: Adaptive gain and optimal performance. *Annual Review of Neuroscience* 28(1), 403-450. https://doi.org/10.1146/annurev.neuro.28.061604.135709
- Baars, B. J. (1988). *A cognitive theory of consciousness.* Cambridge University Press.
- Barrett, L. F. (2017). The theory of constructed emotion: An active inference account of interoception and categorization. *Social Cognitive and Affective Neuroscience* 12(1), 1-23. https://doi.org/10.1093/scan/nsw154
- Bastos, A. M., Usrey, W. M., Adams, R. A., Mangun, G. R., Fries, P., and Friston, K. J. (2012). Canonical microcircuits for predictive coding. *Neuron* 76(4), 695-711. https://doi.org/10.1016/j.neuron.2012.10.038
- Bender, R., and Lange, S. (2001). Adjusting for multiple testing: When and how?

Preprint. Not peer-reviewed.

Journal of Clinical Epidemiology 54(4), 343-349. https://doi.org/10.1016/S0895-4356(00)00314-0
- Bernstein, N. A. (1967). *The co-ordination and regulation of movements.* Pergamon Press.
- Block, N. (1995). On a confusion about a function of consciousness. *Behavioral and Brain Sciences* 18(2), 227-247. https://doi.org/10.1017/S0140525X00038188
- Browne, R. H. (1995). On the use of a pilot sample for sample size determination. *Statistics in Medicine* 14(17), 1933-1940. https://doi.org/10.1002/sim.4780141709
- Bruineberg, J., Dołęga, K., Dewhurst, J., and Baltieri, M. (2022). The emperor's new Markov blankets. *Behavioral and Brain Sciences* 45, e183. https://doi.org/10.1017/S0140525X21002351
- Buhusi, C. V., and Meck, W. H. (2005). What makes us tick? Functional and neural mechanisms of interval timing. *Nature Reviews Neuroscience* 6(10), 755-765. https://doi.org/10.1038/nrn1764
- Butlin, P., Long, R., Elmoznino, E., Bengio, Y., Birch, J., Constant, A., Deane, G., Fleming, S. M., Frith, C., Ji, X., Kanai, R., Klein, C., Lindsay, G., Michel, M., Mudrik, L., Peters, M. A. K., Schwitzgebel, E., Simon, J., and VanRullen, R. (2023). Consciousness in artificial intelligence: Insights from the science of consciousness. arXiv:2308.08708. https://doi.org/10.48550/arXiv.2308.08708
- Calonico, S., Cattaneo, M. D., and Farrell, M. H. (2020). Optimal bandwidth choice for robust bias-corrected inference in regression discontinuity designs. *The Econometrics Journal* 23(2), 192-210. https://doi.org/10.1093/ectj/utz022
- Calonico, S., Cattaneo, M. D., and Titiunik, R. (2014). Robust nonparametric confidence intervals for regression-discontinuity designs. *Econometrica* 82(6), 2295-2326. https://doi.org/10.3982/ECTA11757
- Cattaneo, M. D., Idrobo, N., and Titiunik, R. (2024). *A Practical Introduction to Regression Discontinuity Designs: Extensions*. Cambridge Elements: Quantitative and Computational Methods for the Social Sciences. Cambridge University Press. https://doi.org/10.1017/9781009441896
- Chalmers, D. J. (1995). Facing up to the problem of consciousness. *Journal of Consciousness Studies* 2(3), 200-219.
- Chandrasekaran, C., Gupta, D., Javadzadeh, M., Wang, T., Vivar-Lazo, M., Engel, T., Cisek, P., and Fetsch, C. R. (2025). No central executive? Decision formation through multi-area population dynamics. *Journal of Neuroscience* 45(46), e1633252025. https://doi.org/10.1523/JNEUROSCI.1633-25.2025
- Chechik, G., Meilijson, I., and Ruppin, E. (1998). Synaptic pruning in development: A computational account. *Neural Computation* 10(7), 1759-1777. https://doi.org/10.1162/089976698300
- Chernick, M. R., and Liu, C. Y. (2002). The saw-toothed behavior of power versus sample size and software solutions: Single binomial proportion using exact methods. *The American Statistician* 56(2), 149-155. https://doi.org/10.1198/000313002317572835
- Clark, A. (2013). Whatever next? Predictive brains, situated agents, and the future of cognitive science. *Behavioral and Brain Sciences* 36(3), 181-204. https://doi.org/10.1017/S0140525X120
- Cochran, W. G. (1968). The effectiveness of adjustment by subclassification in removing bias in observational studies. *Biometrics* 24(2), 295-313. https://doi.org/10.2307/2528036
- Coddington, A. M. (2006). Motivations for MADbot: A motivated and goal directed robot. Workshop of the UK Planning and Scheduling Special Interest Group (PlanSIG).
- Cogitate Consortium, Ferrante, O., Gorska-Klimowska, U., Henin, S., Hirschhorn, R., Khalaf, A., Lepauvre, A., Liu, L., Richter, D., Vidal, Y., Bonacchi, N., Brown, T., Sripad, P., Armendariz, M., Bendtz, K., Ghafari, T., Hetenyi, D., Jeschke, J., Kozma, C., Mazumder,

Preprint. Not peer-reviewed.

D. R., Montenegro, S., Seedat, A., Sharafeldin, A., Yang, S., Baillet, S., Chalmers, D. J., Cichy, R. M., Fallon, F., Panagiotaropoulos, T. I., Blumenfeld, H., de Lange, F. P., Devore, S., Jensen, O., Kreiman, G., Luo, H., Boly, M., Dehaene, S., Koch, C., Tononi, G., Pitts, M., Mudrik, L., and Melloni, L. (2025). Adversarial testing of global neuronal workspace and integrated information theories of consciousness. *Nature* 642(8066), 133-142. https://doi.org/10.1038/s41586-025-08888-1

- Cohen, J. (1988). *Statistical power analysis for the behavioral sciences* (2nd ed.). Lawrence Erlbaum Associates.
- Craig, A. D. (2002). How do you feel? Interoception: The sense of the physiological condition of the body. *Nature Reviews Neuroscience* 3(8), 655-666. https://doi.org/10.1038/nrn894
- Currie, L. A. (1968). Limits for qualitative detection and quantitative determination: Application to radiochemistry. *Analytical Chemistry* 40(3), 586-593. https://doi.org/10.1021/ac60259a007
- Da Costa, L., Parr, T., Sajid, N., Veselic, S., Neacsu, V., and Friston, K. (2020). Active inference on discrete state-spaces: A synthesis. *Journal of Mathematical Psychology* 99, 102447. https://doi.org/10.1016/j.jmp.2020.102447
- Davidson, P., Jönsson, P., Carlsson, I., and Pace-Schott, E. (2021). Does sleep selectively strengthen certain memories over others based on emotion and perceived future relevance? *Nature and Science of Sleep* 13, 1257-1306. https://doi.org/10.2147/NSS.S286701
- de Vivo, L., Bellesi, M., Marshall, W., Bushong, E. A., Ellisman, M. H., Tononi, G., and Cirelli, C. (2017). Ultrastructural evidence for synaptic scaling across the wake/sleep cycle. *Science* 355(6324), 507-510. https://doi.org/10.1126/science.aah5982
- Dehaene, S., and Changeux, J.-P. (2011). Experimental and theoretical approaches to conscious processing. *Neuron* 70(2), 200-227. https://doi.org/10.1016/j.neuron.2011.03.018
- Dehaene, S., Kerszberg, M., and Changeux, J.-P. (1998). A neuronal model of a global workspace in effortful cognitive tasks. *Proceedings of the National Academy of Sciences* 95(24), 14529-14534. https://doi.org/10.1073/pnas.95.24.14529
- Dixon, W. J., and Mood, A. M. (1946). The statistical sign test. *Journal of the American Statistical Association* 41(236), 557-566. https://doi.org/10.1080/01621459.1946.10501898
- Easterbrook, J. A. (1959). The effect of emotion on cue utilization and the organization of behavior. *Psychological Review* 66(3), 183-201. https://doi.org/10.1037/h0047707
- Eastwood, J. D., Frischen, A., Fenske, M. J., and Smilek, D. (2012). The unengaged mind: Defining boredom in terms of attention. *Perspectives on Psychological Science* 7(5), 482-495. https://doi.org/10.1177/1745691612456044
- Eldar, E., Cohen, J. D., and Niv, Y. (2013). The effects of neural gain on attention and learning. *Nature Neuroscience* 16(8), 1146-1153. https://doi.org/10.1038/nn.3428
- Feldman, H., and Friston, K. J. (2010). Attention, uncertainty, and free-energy. *Frontiers in Human Neuroscience* 4, 215. https://doi.org/10.3389/fnhum.2010.00215
- Feldman, R., and Eidelman, A. I. (2003). Skin-to-skin contact (Kangaroo Care) accelerates autonomic and neurobehavioural maturation in preterm infants. *Developmental Medicine and Child Neurology* 45(4), 274-281. https://doi.org/10.1111/j.1469-8749.2003.tb00343.x
- Fiebelkorn, I. C., and Kastner, S. (2019). A rhythmic theory of attention. *Trends in Cognitive Sciences* 23(2), 87-101. https://doi.org/10.1016/j.tics.2018.11.009
- Franklin, S., Madl, T., D'Mello, S., and Snaider, J. (2014). LIDA: A systems-level architecture for cognition, emotion, and learning. *IEEE Transactions on Autonomous Mental Development* 6(1), 19-41. https://doi.org/10.1109/TAMD.2013.2277589

Preprint. Not peer-reviewed.

- Fries, P. (2015). Rhythms for cognition: Communication through coherence. *Neuron* 88(1), 220-235. https://doi.org/10.1016/j.neuron.2015.09.034
- Friston, K. (2010). The free-energy principle: A unified brain theory? *Nature Reviews Neuroscience* 11(2), 127-138. https://doi.org/10.1038/nrn2787
- Frith, C. D., and Frith, U. (2006). The neural basis of mentalizing. *Neuron* 50(4), 531-534. https://doi.org/10.1016/j.neuron.2006.05.001
- Garrido, M. I., Kilner, J. M., Stephan, K. E., and Friston, K. J. (2009). The mismatch negativity: A review of underlying mechanisms. *Clinical Neurophysiology* 120(3), 453-463. https://doi.org/10.1016/j.clinph.2008.11.029
- Goodale, M. A., and Milner, A. D. (1992). Separate visual pathways for perception and action. *Trends in Neurosciences* 15(1), 20-25. https://doi.org/10.1016/0166-2236(92)90344-8
- Goodman, S. N., Fanelli, D., and Ioannidis, J. P. A. (2016). What does research reproducibility mean? *Science Translational Medicine* 8(341), 341ps12. https://doi.org/10.1126/scitranslmed
- Grandjean, D., Sander, D., Pourtois, G., Schwartz, S., Seghier, M. L., Scherer, K. R., and Vuilleumier, P. (2005). The voices of wrath: Brain responses to angry prosody in meaningless speech. *Nature Neuroscience* 8(2), 145-146. https://doi.org/10.1038/nn1392
- Gross, J. J. (1998). The emerging field of emotion regulation: An integrative review. *Review of General Psychology* 2(3), 271-299. https://doi.org/10.1037/1089-2680.2.3.271
- Gurnee, W., Sofroniew, N., Pearce, A., Piotrowski, M., Kauvar, I., Chen, R., Soligo, A., Bogdan, P., Ong, E., Wang, R., Thompson, T. B., Abrahams, D., Kantamneni, S., Ameisen, E., Batson, J., and Lindsey, J. (2026). Verbalizable representations form a global workspace in language models. *Transformer Circuits Thread*, July 6, 2026. Technical report, not peer reviewed. https://transformer-circuits.pub/2026/workspace/index.html
- Ha, D., and Schmidhuber, J. (2018). World models. arXiv:1803.10122. https://doi.org/10.48550/arXiv.18
- Hafner, D., Pasukonis, J., Ba, J., and Lillicrap, T. (2025). Mastering diverse control tasks through world models. *Nature* 640(8059), 647-653. https://doi.org/10.1038/s41586-025-08744-2
- Hasani, R., Lechner, M., Amini, A., Liebenwein, L., Ray, A., Tschaikowski, M., Teschl, G., and Rus, D. (2022). Closed-form continuous-time neural networks. *Nature Machine Intelligence* 4(11), 992-1003. https://doi.org/10.1038/s42256-022-00556-7
- Hassabis, D., and Maguire, E. A. (2007). Deconstructing episodic memory with construction. *Trends in Cognitive Sciences* 11(7), 299-306. https://doi.org/10.1016/j.tics.2007.05.001
- Heins, C., Millidge, B., Demekas, D., Klein, B., Friston, K., Couzin, I. D., and Tschantz, A. (2022). pymdp: A Python library for active inference in discrete state spaces. *Journal of Open Source Software* 7(73), 4098. https://doi.org/10.21105/joss.04098
- Hickok, G., and Poeppel, D. (2007). The cortical organization of speech processing. *Nature Reviews Neuroscience* 8(5), 393-402. https://doi.org/10.1038/nrn2113
- Hoad, K., Robinson, S., and Davies, R. (2010). Automating warm-up length estimation. *Journal of the Operational Research Society* 61(9), 1389-1403. https://doi.org/10.1057/jors.2009.87
- Holm, S. (1979). A simple sequentially rejective multiple test procedure. *Scandinavian Journal of Statistics* 6(2), 65-70.
- Hull, C. L. (1943). *Principles of behavior: An introduction to behavior theory.* Appleton-Century.
- Imbens, G. W., and Kalyanaraman, K. (2012). Optimal bandwidth choice for the regression discontinuity estimator. *The Review of Economic Studies* 79(3), 933-959. https://doi.org/10.1093/restud/rdr043
- Imbens, G. W., and Lemieux, T. (2008). Regression discontinuity designs: A guide to

Preprint. Not peer-reviewed.

practice. *Journal of Econometrics* 142(2), 615-635. https://doi.org/10.1016/j.jeconom.2007.05.001
- International Conference on Harmonisation (2000). *E10: Choice of control group and related issues in clinical trials.* ICH Harmonised Tripartite Guideline, Step 4 version of 20 July 2000. https://database.ich.org/sites/default/files/E10_Guideline.pdf
- Jaynes, E. T. (2003). *Probability theory: The logic of science*. Cambridge University Press. https://doi.org/10.1017/CBO9780511790423
- Joffily, M., and Coricelli, G. (2013). Emotional valence and the free-energy principle. *PLoS Computational Biology* 9(6), e1003094. https://doi.org/10.1371/journal.pcbi.1003094
- Joglekar, M. R., Mejias, J. F., Yang, G. R., and Wang, X.-J. (2018). Inter-areal balanced amplification enhances signal propagation in a large-scale circuit model of the primate cortex. *Neuron* 98(1), 222-234. https://doi.org/10.1016/j.neuron.2018.02.031
- Jolliffe, I. T. (2002). *Principal component analysis* (2nd ed.). Springer. https://doi.org/10.1007/b98835
- Keramati, M., and Gutkin, B. (2014). Homeostatic reinforcement learning for integrating reward collection and physiological stability. *eLife* 3, e04811. https://doi.org/10.7554/eLife.04811
- Kleckner, I. R., Zhang, J., Touroutoglou, A., Chanes, L., Xia, C., Simmons, W. K., Quigley, K. S., Dickerson, B. C., and Feldman Barrett, L. (2017). Evidence for a large-scale brain system supporting allostasis and interoception in humans. *Nature Human Behaviour* 1(5), 0069. https://doi.org/10.1038/s41562-017-0069
- Kraemer, H. C., Mintz, J., Noda, A., Tinklenberg, J., and Yesavage, J. A. (2006). Caution regarding the use of pilot studies to guide power calculations for study proposals. *Archives of General Psychiatry* 63(5), 484-489. https://doi.org/10.1001/archpsyc.63.5.484
- Kullback, S., and Leibler, R. A. (1951). On information and sufficiency. *Annals of Mathematical Statistics* 22(1), 79-86. https://doi.org/10.1214/aoms/1177729694
- Kuniyoshi, Y., and Sangawa, S. (2006). Early motor development from partially ordered neural-body dynamics: Experiments with a cortico-spinal-musculo-skeletal model. *Biological Cybernetics* 95(6), 589-605. https://doi.org/10.1007/s00422-006-0127-z
- Lakens, D. (2017). Equivalence tests: A practical primer for t tests, correlations, and meta-analyses. *Social Psychological and Personality Science* 8(4), 355-362. https://doi.org/10.1177/1948550617697177
- Lancaster, G. A., Dodd, S., and Williamson, P. R. (2004). Design and analysis of pilot studies: Recommendations for good practice. *Journal of Evaluation in Clinical Practice* 10(2), 307-312. https://doi.org/10.1111/j..2002.384.doc.x
- Landau, A. N., and Fries, P. (2012). Attention samples stimuli rhythmically. *Current Biology* 22(11), 1000-1004. https://doi.org/10.1016/j.cub.2012.03.054
- Lewis, P. A., and Durrant, S. J. (2011). Overlapping memory replay during sleep builds cognitive schemata. *Trends in Cognitive Sciences* 15(8), 343-351. https://doi.org/10.1016/j.tics.2011.06.004
- Li, W., Ma, L., Yang, G., and Gan, W.-B. (2017). REM sleep selectively prunes and maintains new synapses in development and learning. *Nature Neuroscience* 20(3), 427-437. https://doi.org/10.1038/nn.4479
- Lipinska, G., Stuart, B., Thomas, K. G. F., Baldwin, D. S., and Bolinger, E. (2019). Preferential consolidation of emotional memory during sleep: A meta-analysis. *Frontiers in Psychology* 10, 1014. https://doi.org/10.3389/fpsyg.2019.01014
- Long, R., Sebo, J., Butlin, P., Finlinson, K., Fish, K., Harding, J., Pfau, J., Sims, T., Birch, J., and Chalmers, D. (2024). Taking AI welfare seriously. arXiv:2411.00986. https://doi.org/10.48550/arXiv.2411.00986
- Maier, S. F., and Seligman, M. E. P. (2016). Learned helplessness at fifty: Insights from neuroscience. *Psychological Review* 123(4), 349-367. https://doi.org/10.1037/rev0000033

Preprint. Not peer-reviewed.

- Mann, H. B., and Whitney, D. R. (1947). On a test of whether one of two random variables is stochastically larger than the other. *Annals of Mathematical Statistics* 18(1), 50-60. https://doi.org/10.1214/aoms/1177730491
- Maret, S., Faraguna, U., Nelson, A. B., Cirelli, C., and Tononi, G. (2011). Sleep and waking modulate spine turnover in the adolescent mouse cortex. *Nature Neuroscience* 14(11), 1418-1420. https://doi.org/10.1038/nn.2934
- Mascarenhas, S., Guimarães, M., Prada, R., Santos, P. A., Dias, J., and Paiva, A. (2022). FAtiMA Toolkit: Toward an accessible tool for the development of socio-emotional agents. *ACM Transactions on Interactive Intelligent Systems* 12(1), 1-30. https://doi.org/10.1145/3510822
- Mashour, G. A., Roelfsema, P., Changeux, J.-P., and Dehaene, S. (2020). Conscious processing and the global neuronal workspace hypothesis. *Neuron* 105(5), 776-798. https://doi.org/10.1016/j.neuron.2020.01.026
- Mather, M., and Sutherland, M. R. (2011). Arousal-biased competition in perception and memory. *Perspectives on Psychological Science* 6(2), 114-133. https://doi.org/10.1177/1745691611
- McClelland, J. L., McNaughton, B. L., and O'Reilly, R. C. (1995). Why there are complementary learning systems in the hippocampus and neocortex: Insights from the successes and failures of connectionist models of learning and memory. *Psychological Review* 102(3), 419-457. https://doi.org/10.1037/0033-295x.102.3.419
- Metzinger, T. (2003). *Being no one: The self-model theory of subjectivity.* MIT Press. https://doi.org/10.7551/mitpress/1551.001.0001
- Moerland, T. M., Broekens, J., and Jonker, C. M. (2018). Emotion in reinforcement learning agents and robots: A survey. *Machine Learning* 107(2), 443-480. https://doi.org/10.1007/s10994-017-5666-0
- Näätänen, R., Paavilainen, P., Rinne, T., and Alho, K. (2007). The mismatch negativity (MMN) in basic research of central auditory processing: A review. *Clinical Neurophysiology* 118(12), 2544-2590. https://doi.org/10.1016/j.clinph.2007.04.026
- Natale, R., Nasello-Paterson, C., and Connors, G. (1988). Patterns of fetal breathing activity in the human fetus at 24 to 28 weeks of gestation. *American Journal of Obstetrics and Gynecology* 158(2), 317-321. https://doi.org/10.1016/0002-9378(88)90146-9
- National Academies of Sciences, Engineering, and Medicine (2019). *Reproducibility and replicability in science.* National Academies Press. https://doi.org/10.17226/25303
- Nieuwenhuis, S., Aston-Jones, G., and Cohen, J. D. (2005). Decision making, the P3, and the locus coeruleus-norepinephrine system. *Psychological Bulletin* 131(4), 510-532. https://doi.org/10.1037/0033-2909.131.4.510
- Nieuwenhuis, S., Gilzenrat, M. S., Holmes, B. D., and Cohen, J. D. (2005). The role of the locus coeruleus in mediating the attentional blink: A neurocomputational theory. *Journal of Experimental Psychology: General* 134(3), 291-307. https://doi.org/10.1037/0096-3445.134.3.291
- Norman, G. R., Sloan, J. A., and Wyrwich, K. W. (2003). Interpretation of changes in health-related quality of life: The remarkable universality of half a standard deviation. *Medical Care* 41(5), 582-592. https://doi.org/10.1097/01.MLR.0000062554.74615.4C
- Northoff, G., and Bermpohl, F. (2004). Cortical midline structures and the self. *Trends in Cognitive Sciences* 8(3), 102-107. https://doi.org/10.1016/j.tics.2004.01.004
- O'Regan, J. K., and Noë, A. (2001). A sensorimotor account of vision and visual consciousness. *Behavioral and Brain Sciences* 24(5), 939-973. https://doi.org/10.1017/S0140525X01000115
- O'Reilly, R. C., and Frank, M. J. (2006). Making working memory work: A computational model of learning in the prefrontal cortex and basal ganglia. *Neural Computation* 18(2),

Preprint. Not peer-reviewed.

283-328. https://doi.org/10.1162/089976606775093909
- Ortony, A., Clore, G. L., and Collins, A. (2022). *The cognitive structure of emotions* (2nd ed.). Cambridge University Press. https://doi.org/10.1017/9781108934053
- Oudeyer, P.-Y., and Kaplan, F. (2007). What is intrinsic motivation? A typology of computational approaches. *Frontiers in Neurorobotics* 1, 6. https://doi.org/10.3389/neuro.12.006.2007
- Park, J. S., O'Brien, J. C., Cai, C. J., Morris, M. R., Liang, P., and Bernstein, M. S. (2023). Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology (UIST '23)*, 1-22. https://doi.org/10.1145/3586183.3606763
- Posner, J., Russell, J. A., and Peterson, B. S. (2005). The circumplex model of affect: An integrative approach to affective neuroscience, cognitive development, and psychopathology. *Development and Psychopathology* 17(3), 715-734. https://doi.org/10.1017/S0954579405050340
- Premack, D., and Woodruff, G. (1978). Does the chimpanzee have a theory of mind? *Behavioral and Brain Sciences* 1(4), 515-526. https://doi.org/10.1017/S0140525X00076512
- Rao, R. P. N., and Ballard, D. H. (1999). Predictive coding in the visual cortex: A functional interpretation of some extra-classical receptive-field effects. *Nature Neuroscience* 2(1), 79-87. https://doi.org/10.1038/4580
- Ray, S., and Maunsell, J. H. R. (2010). Differences in gamma frequencies across visual cortex restrict their possible use in computation. *Neuron* 67(5), 885-896. https://doi.org/10.1016/j.neuron.2010.08.004
- Raymond, J. E., Shapiro, K. L., and Arnell, K. M. (1992). Temporary suppression of visual processing in an RSVP task: An attentional blink? *Journal of Experimental Psychology: Human Perception and Performance* 18(3), 849-860. https://doi.org/10.1037/0096-1523.18.3.849
- Righetti, L., Buchli, J., and Ijspeert, A. J. (2006). Dynamic Hebbian learning in adaptive frequency oscillators. *Physica D* 216(2), 269-281. https://doi.org/10.1016/j.physd.2006.02.009
- Rosenbaum, P. R., and Rubin, D. B. (1984). Reducing bias in observational studies using subclassification on the propensity score. *Journal of the American Statistical Association* 79(387), 516-524. https://doi.org/10.1080/01621459.1984.10478078
- Safron, A. (2020). An integrated world modeling theory (IWMT) of consciousness: Combining integrated information and global neuronal workspace theories with the free energy principle and active inference framework; toward solving the hard problem and characterizing agentic causation. *Frontiers in Artificial Intelligence* 3, 30. https://doi.org/10.3389/frai.2020.00030
- Sander, D., Grandjean, D., Pourtois, G., Schwartz, S., Seghier, M. L., Scherer, K. R., and Vuilleumier, P. (2005). Emotion and attention interactions in social cognition: Brain regions involved in processing anger prosody. *NeuroImage* 28(4), 848-858. https://doi.org/10.1016/j.neuroimage.2005.06.023
- Sander, D., Grandjean, D., and Scherer, K. R. (2005). A systems approach to appraisal mechanisms in emotion. *Neural Networks* 18(4), 317-352. https://doi.org/10.1016/j.neunet.2005.03.001
- Scherer, K. R. (2009). Emotions are emergent processes: They require a dynamic computational architecture. *Philosophical Transactions of the Royal Society B* 364(1535), 3459-3474. https://doi.org/10.1098/rstb.2009.0141
- Schmidhuber, J. (2010). Formal theory of creativity, fun, and intrinsic motivation (1990-2010). *IEEE Transactions on Autonomous Mental Development* 2(3), 230-247. https://doi.org/10.1109/TAMD.2010.2056368
- Searle, J. R. (1980). Minds, brains, and programs. *Behavioral and Brain Sciences* 3(3),

Preprint. Not peer-reviewed.

417-424. https://doi.org/10.1017/S0140525X00005756
- Seth, A. K. (2013). Interoceptive inference, emotion, and the embodied self. *Trends in Cognitive Sciences* 17(11), 565-573. https://doi.org/10.1016/j.tics.2013.09.007
- Seth, A. K., and Friston, K. J. (2016). Active interoceptive inference and the emotional brain. *Philosophical Transactions of the Royal Society B* 371(1708), 20160007. https://doi.org/10.1098/rstb.2016.0007
- Shadlen, M. N., and Movshon, J. A. (1999). Synchrony unbound: A critical evaluation of the temporal binding hypothesis. *Neuron* 24(1), 67-77. https://doi.org/10.1016/S0896-6273(00)80822-3
- Simmons, J. P., Nelson, L. D., and Simonsohn, U. (2011). False-positive psychology: Undisclosed flexibility in data collection and analysis allows presenting anything as significant. *Psychological Science* 22(11), 1359-1366. https://doi.org/10.1177/0956797611417632
- Stickgold, R., and Walker, M. P. (2013). Sleep-dependent memory triage: Evolving generalization through selective processing. *Nature Neuroscience* 16(2), 139-145. https://doi.org/10.1038/nn.3303
- Sumers, T. R., Yao, S., Narasimhan, K., and Griffiths, T. L. (2024). Cognitive architectures for language agents. *Transactions on Machine Learning Research*. https://openreview.net/forum?id=1i6ZCvflQJ
- Sun, Z., and Firestone, C. (2020). The dark room problem. *Trends in Cognitive Sciences* 24(5), 346-348. https://doi.org/10.1016/j.tics.2020.02.006
- Tabak, J., Senn, W., O'Donovan, M. J., and Rinzel, J. (2000). Modeling of spontaneous activity in developing spinal cord using activity-dependent depression in an excitatory network. *Journal of Neuroscience* 20(8), 3041-3056. https://doi.org/10.1523/JNEUROSCI.20-08-03041.2000
- Thagard, P., and Verbeurgt, K. (1998). Coherence as constraint satisfaction. *Cognitive Science* 22(1), 1-24. https://doi.org/10.1207/s15516709cog2201_1
- Tononi, G., and Cirelli, C. (2006). Sleep function and synaptic homeostasis. *Sleep Medicine Reviews* 10(1), 49-62. https://doi.org/10.1016/j.smrv.2005.05.002
- Tononi, G., and Cirelli, C. (2014). Sleep and the price of plasticity: From synaptic and cellular homeostasis to memory consolidation and integration. *Neuron* 81(1), 12-34. https://doi.org/10.1016/j.neuron.2013.12.025
- Tschantz, A., Barca, L., Maisto, D., Buckley, C. L., Seth, A. K., and Pezzulo, G. (2022). Simulating homeostatic, allostatic and goal-directed forms of interoceptive control using active inference. *Biological Psychology* 169, 108266. https://doi.org/10.1016/j.biopsycho.2022.108266
- Tulving, E. (1985). How many memory systems are there? *American Psychologist* 40(4), 385-398. https://doi.org/10.1037/0003-066X.40.4.385
- Van Leeuwen, P., Geue, D., Lange, S., Cysarz, D., Bettermann, H., and Grönemeyer, D. H. W. (2003). Is there evidence of fetal-maternal heart rate synchronization? *BMC Physiology* 3(1), 2. https://doi.org/10.1186/1472-6793-3-2
- Van Leeuwen, P., Geue, D., Thiel, M., Cysarz, D., Lange, S., Romano, M. C., Wessel, N., Kurths, J., and Grönemeyer, D. H. (2009). Influence of paced maternal breathing on fetal-maternal heart rate coordination. *Proceedings of the National Academy of Sciences* 106(33), 13661-13666. https://doi.org/10.1073/pnas.0901049106
- van Vugt, B., Dagnino, B., Vartak, D., Safaai, H., Panzeri, S., Dehaene, S., and Roelfsema, P. R. (2018). The threshold for conscious report: Signal loss and response bias in visual and frontal cortex. *Science* 360(6388), 537-542. https://doi.org/10.1126/science.aar7186
- VanRullen, R. (2016). Perceptual cycles. *Trends in Cognitive Sciences* 20(10), 723-735. https://doi.org/10.1016/j.tics.2016.07.006

Preprint. Not peer-reviewed.

- Vuilleumier, P. (2005). How brains beware: Neural mechanisms of emotional attention. *Trends in Cognitive Sciences* 9(12), 585-594. https://doi.org/10.1016/j.tics.2005.10.011
- Webb, A. R., Heller, H. T., Benson, C. B., and Lahav, A. (2015). Mother's voice and heartbeat sounds elicit auditory plasticity in the human brain before full gestation. *Proceedings of the National Academy of Sciences* 112(10), 3152-3157. https://doi.org/10.1073/pnas.1414924112
- Wei, Y., Krishnan, G. P., and Bazhenov, M. (2016). Synaptic mechanisms of memory consolidation during sleep slow oscillations. *Journal of Neuroscience* 36(15), 4231-4247. https://doi.org/10.1523/JNEUROSCI.3648-15.2016
- Westgate, E. C., and Wilson, T. D. (2018). Boring thoughts and bored minds: The MAC model of boredom and cognitive engagement. *Psychological Review* 125(5), 689-713. https://doi.org/10.1037/rev0000097
- White, K. P., Jr. (1997). An effective truncation heuristic for bias reduction in simulation output. *Simulation* 69(6), 323-334. https://doi.org/10.1177/003754979706900601
- Whyte, C. J., Hohwy, J., and Smith, R. (2022). An active inference model of conscious access: How cognitive action selection reconciles the results of report and no-report paradigms. *Current Research in Neurobiology* 3, 100036. https://doi.org/10.1016/j.crneur.2022.100036
- Whyte, C. J., and Smith, R. (2021). The predictive global neuronal workspace: A formal active inference model of visual consciousness. *Progress in Neurobiology* 199, 101918. https://doi.org/10.1016/j.pneurobio.2020.101918
- Williams, H., Lee-Johnson, C., Browne, W. N., and Carnegie, D. A. (2015). Emotion inspired adaptive robotic path planning. In *2015 IEEE Congress on Evolutionary Computation (CEC)*, 3004-3011. https://doi.org/10.1109/CEC.2015.7257263
- Wilson, M. A., and McNaughton, B. L. (1994). Reactivation of hippocampal ensemble memories during sleep. *Science* 265(5172), 676-679. https://doi.org/10.1126/science.8036517
- Winkler, I., Denham, S. L., and Nelken, I. (2009). Modeling the auditory scene: Predictive regularity representations and perceptual objects. *Trends in Cognitive Sciences* 13(12), 532-540. https://doi.org/10.1016/j.tics.2009.09.003
- Wolpert, D. M., Ghahramani, Z., and Jordan, M. I. (1995). An internal model for sensorimotor integration. *Science* 269(5232), 1880-1882. https://doi.org/10.1126/science.7569931
- Wrosch, C., Scheier, M. F., Miller, G. E., Schulz, R., and Carver, C. S. (2003). Adaptive self-regulation of unattainable goals: Goal disengagement, goal reengagement, and subjective well-being. *Personality and Social Psychology Bulletin* 29(12), 1494-1508. https://doi.org/10.1177/0146167203256921
- Yu, A. J., and Dayan, P. (2005). Uncertainty, neuromodulation, and attention. *Neuron* 46(4), 681-692. https://doi.org/10.1016/j.neuron.2005.04.026
- Zink, N., Lenartowicz, A., and Markett, S. (2021). A new era for executive function research: On the transition from centralized to distributed executive functioning. *Neuroscience and Biobehavioral Reviews* 124, 235-244. https://doi.org/10.1016/j.neubiorev.2021.02.011

Preprint. Not peer-reviewed.

Appendix A. Formal summary

This appendix formalizes §3 to §7. Each symbol with its sub- and superscripts denotes one quantity, defined at first use. Indices i, j, l, q, t are local to their formula or subsection; k indexes ticks and m modules throughout. Upright i and e are the imaginary unit and Eu-

ler's number. Parameter values and statuses appear only in Table A1 (A.11), except design-defining numbers such as A.7's 19 surrogates.

clip with an interval subscript maps to the interval's nearest point; $\mathbf{1}[\cdot]$ is 1 when its condition holds, else 0. Time is in entity seconds (§3.4); rates in hertz are per entity second unless Table A1 marks them wall-clock. Overbars mark means with locally stated windows or weightings. For a nonnegative series $X_1, X_2, \ldots$ and window W, the running mean $\bar{X}_t$ averages the last $\min(t, W)$ values, X_t included, and the running ratio is

$$\tilde{X}_t = \begin{cases} X_t / \bar{X}_t & \bar{X}_t > 0, \\ 0 & \text{otherwise.} \end{cases}$$

Since $\bar{X}_t$ includes X_t, $0 \le \tilde{X}_t \le \min(t, W)$.

A.1 Processing cycle, selection, access, and context

Processing ticks $k = 0, 1, 2, \ldots$ occur at the processing rate f_p, with tick period $\Delta_p = 1/f_p$. On tick k the cycle reads from each active module's output stream up to B events published since its last read, advancing the cursor past them. They form the candidate set E_k, ordered lexicographically by source, event type, and bus entry identifier (arrival order). A tick reads E_k, updates the held arousal $\hat{a}_k$ (A.4), computes the access drive and the broadcast indicator χ_k (A.3), scores, selects, and broadcasts if $\chi_k = 1$.

Each candidate $e \in E_k$ receives the priority and the score

$$p_k(e) = \text{clip}_{[0,1]}\big(I(e)\, N_k(e)\, G(e)\big), \qquad S_k(e) = \text{clip}_{[0,1]}\Big(T_k\, C_{g_k}\big(p_k(e)\big)\Big),$$

with I (A.2), N_k, G, T_k clipped to $[0, 1]$ first and $\text{src}(e)$ the source of e; the workspace adds no per-source weight. The novelty factor is

$$N_k(e) = \max\left(0,\ 1 - \frac{\text{rep}_k(e)}{W_N}\right),$$

where $\text{rep}_k(e)$ counts the fingerprint of e among the W_N candidates scored just before it, across ticks, broadcast or not. The fingerprint hashes source, type, and full payload, so $N_k(e) < 1$ only for exact repeats. In the first configuration $G(e) \equiv 1$; an implemented alternative, off here, is $G(e) = 1 - \gamma_G\, v^*\big(1 - \mathbf{1}[\text{src}(e) \in \mathcal{R}(d^*)]\big)$ when $v^* > 0$ and $G(e) = 1$ otherwise, with d^*, v^*, $\mathcal{R}(d^*)$ from A.4.

Arousal sets a level gain and a contrast gain,

$$T_k = T_{\min} + (T_{\max} - T_{\min})\, \hat{a}_k, \qquad g_k = g_{\max}\, \text{clip}_{[0,1]}\left(\frac{\hat{a}_k - a_0}{1 - a_0}\right),$$

with a_0 the baseline arousal. The contrast map is the logistic function rescaled to fix 0 and 1:

Preprint. Not peer-reviewed.

$$C_g(p) = \frac{\tanh\big(g(2p-1)/4\big) + \tanh(g/4)}{2\tanh(g/4)} \quad (g > 0), \qquad C_0(p) = p.$$

An optional coherence layer sets $S'_k(e) = S_k(e)\,\kappa_k(e)$; off, as in the first configuration, $\kappa_k(e) \equiv 1$ and $S'_k = S_k$. On, $\kappa_k(e) = \kappa_{\min} + (\kappa_{\max} - \kappa_{\min})\,\Lambda_k(e)$, with $\Lambda_k(e) \in [0,1]$ the mean phase-locking value between the oscillator phase window (the last W_κ tick phases) of $\mathrm{src}(e)$ and that of each other source in E_k. An oscillator advances only when its source publishes, so a phase sample is fresh only if it changed; each pair uses the window ticks where both are fresh. A pair with under three such ticks, or a lone source, takes the neutral $\Lambda_0 = (1-\kappa_{\min})/(\kappa_{\max} - \kappa_{\min})$, giving $\kappa_k(e) = 1$. $S'_k(e)$ is not re-clipped and can exceed 1, up to $\kappa_{\max}$.

The coalition $\mathcal{C}_k$ is the first $\min(K, |E_k|)$ candidates by decreasing S'_k, ties in canonical order. A member is accessed when its score reaches the access threshold θ; with $S^*_k = \max_{e \in E_k} S'_k(e)$, the accessed set and the inhibition flag are

$$\mathcal{C}^{\mathrm{acc}}_k = \big\{e \in \mathcal{C}_k : \; S'_k(e) \geq \theta\big\}, \qquad \iota_k = \mathbf{1}[\mathcal{C}^{\mathrm{acc}}_k = \emptyset] = \mathbf{1}[S^*_k < \theta]\,,$$

the two forms agreeing because the best candidate of E_k is in $\mathcal{C}_k$. A score equal to θ is accessed; an empty E_k gives $\mathcal{C}_k = \mathcal{C}^{\mathrm{acc}}_k = \emptyset$ and $\iota_k = 1$. With $G \equiv 1$, $\kappa_k \equiv 1$, no regulation bias (§3.5), $T_k > 0$ shared within a tick, and C_{g_k} strictly increasing, $I(e)\,N_k(e)$ alone ranks a tick's candidates, up to ties. Arousal never reorders them; it moves their scores relative to θ and the report bars of A.6.

On a tick with $\chi_k = 1$ the cycle publishes the broadcast $\mathcal{B}_k = (\mathcal{C}_k,\ \{S'_k(e)\}_{e \in E_k},\ \iota_k)$, the scored coalition and the full candidate-score table, whatever ι_k. It is *accessed* when $\iota_k = 0$, and the members of $\mathcal{C}^{\mathrm{acc}}_k$ are accessed content; a member scoring below θ is broadcast but not accessed. A broadcast with $\iota_k = 1$ is visible on the broadcast stream. The action-selection module runs after each publication. On a tick with $\chi_k = 0$ the candidates are scored and discarded; their only lasting effects are novelty-window entries, the phasic access drive (A.3), and, for an affect state event, $\hat{a}_k$ (A.4).

Featurization. For events $\mathcal{X}$ with nonnegative weights $\omega(e)$, an interval $\Delta \geq 0$, and a flag ι, the featurization $\Phi_\omega(\mathcal{X}, \Delta, \iota) \in \mathbb{R}^{24}$ has components: (1) $\ln(1 + |\mathcal{X}|)$; (2 to 4) the mean, maximum, and sample standard deviation of the weights (0 for an empty set; the standard deviation 0 below two events); (5 to 11) the weight mass $\sum_{e \in \mathcal{X},\, \mathrm{src}(e) = m} \omega(e)$ of each of seven sources (interoception, sequence, vision, planning, episodic memory, affect, language); (12) that of all other sources except audition (effector, sleep, and any source without its own component); (13 to 20) the weight mass in each of eight buckets of a fixed hash of the (source, type) pair, an event-type indicator weighted by ω; (21) $\ln(1 + \Delta)$; (22) ι; (23) the broadcast indicator, 1 for every broadcast; (24) the audition module's weight mass. Components 5 to 20 and 24 sum per-event contributions and so split by source.

Context. The vision, audition, and interoception modules each hold a context b, the featurization of the accessed content of the latest accessed broadcast received,

Preprint. Not peer-reviewed.

$$b = \Phi_I(\mathcal{C}^{\text{acc}}_{k'},\ \Delta^b,\ 0),$$

with k' that broadcast's tick, its accessed members $\mathcal{C}^{\text{acc}}_{k'}$ weighted by reported intensity $I(e)$, and Δ^b the entity time since its publication, read at prediction. A module adopts a broadcast as context on receipt only if $\iota = 0$ and holds it until the next accessed one; $b = 0$ before the first. The sequence module takes every broadcast's featurization as input and holds no context (A.2); the affect module processes every broadcast (A.4); the action-selection module derives no intent when $\iota_k = 1$ (A.6); the language organ generates only on an intent and conditions only on accessed content; the sleep module ignores broadcasts.

A.2 Event intensity and the processors' forward models

A module sets the intensity $I(e) \in [0, 1]$ on publishing e, and t indexes its reports. Module m has baseline and alert levels $0 \le I^{\text{lo}}_m \le I^{\text{hi}}_m \le 1$. A predictive processor's report (vision, audition, interoception, sequence) has the graded intensity

$$I(e) = \begin{cases} I^{\text{hi}}_m & e \text{ is an alert,} \\ \Gamma_m(\tilde{\nu}_t) & \text{otherwise,} \end{cases} \qquad \Gamma_m(\tilde{\nu}) = I^{\text{lo}}_m + (I^{\text{hi}}_m - I^{\text{lo}}_m)\min(1,\ \tilde{\nu}/\beta_\Gamma)\,,$$

where $\tilde{\nu}_t$ is the running ratio over W_P of the forward-model error ν_t below; Γ_m reaches the alert level at β_Γ times the mean. For errors of fixed distributional shape, mean absolute error is proportional to standard deviation, so $\tilde{\nu}_t$ is proportional to the error times the square root of its precision Π (inverse error variance): the square root of the precision-weighted squared error of Feldman and Friston (2010), estimated from the processor's history, not the precision-weighted error itself. Alert criteria are categorical and module-specific. Before a module's first prediction $\tilde{\nu}_t = 0$, giving non-alerts I^{lo}_m.

Forward models of vision and audition. Vision and audition's acoustic and tone paths each predict their next input with a one-hidden-layer tanh network $\mathcal{N}_m$, forming at report $t - 1$ the prediction

$$\hat{z}_t = \mathcal{N}_m(z_{t-1},\ \bar{z}_{t-1},\ b_{t-1}),$$

with the arguments concatenated, $\bar{z}_{t-1}$ the mean of the last W_{buf} inputs through z_{t-1}, and b_{t-1} the context then held (A.1). The error is $\nu_t = \|z_t - \hat{z}_t\|_2$, with $\nu_1 = 0$. Outside sleep, each z_t triggers one stochastic-gradient step (learning rate η_{fm}) on the mean squared error of $\hat{z}_t$ over all weights, including the context's.

Vision and audition (perceptual reports). For vision, z_t is the encoder embedding of the current clip (the peripheral gist clip under foveation); for acoustic audition, the spectral embedding of the window's attended part, its most recent fraction $\omega = \omega_{\text{max}} - (\omega_{\text{max}} - \omega_{\text{min}})\,a$, a being the module's latest arousal reading, at least Δ_{att} and at most the window. The change score is $c_t = 1 - \cos(z_t, z_{t-1})$, 0 on the first report. With running ratios over W_P, the report is an alert when

Preprint. Not peer-reviewed.

$$\tilde{\nu}_t \geq \beta_\nu \quad \text{or} \quad (\tilde{c}_t \geq \beta_c \text{ and } c_t \geq c_m^{\min}),$$

with the absolute change floor $c_m^{\min} = c_{\text{Vis}}^{\min}$ or $c_m^{\min} = c_{\text{Aud}}^{\min}$. The error series are ν_t^{Vis} and ν_t^{Aud} where needed; reports carry ν_t and $\tilde{\nu}_t$.

Fovea. Under foveation, each coarse-grid tile j has per clip report a frame change d_j, the absolute change of its mean gray level since the previous clip report (0 on the first, which updates no statistics). Later reports update its exponentially weighted mean μ_j^F and variance $(\sigma_j^F)^2$ with weight α_F, $\mu_j^F \leftarrow \mu_j^F + \alpha_F(d_j - \mu_j^F)$ and $(\sigma_j^F)^2 \leftarrow (1-\alpha_F)((\sigma_j^F)^2 + \alpha_F(d_j - \mu_j^F)^2)$, using the prior μ_j^F; the first update sets $\mu_j^F = d_j$ and $\sigma_j^F = 0$. After n_F updates the tile's salience is the z-score

$$\frac{\max\big(0,\ d_j - \mu_j^F\big)}{\sqrt{(\sigma_j^F)^2 + (\sigma_0^F)^2}}, \qquad \sigma_0^F = k_F \, \frac{1}{n_{\text{tile}}} \sum_j \mu_j^F,$$

with all statistics, floor included, taken before this report's update and n_{tile} the tile count; before that, salience is d_j. The fovea starts at the center and moves to the most salient tile only when its salience exceeds $(1 + \Theta_F)$ times the held tile's; its size, as a frame fraction, is $F = F_{\max} - (F_{\max} - F_{\min})\, a$, a being the vision module's latest arousal reading. Peripheral and foveal clips are cut from every buffered frame at the fovea chosen on the latest frame.

Audition (tone events). For a speech window, the tone path's input is the vocal-emotion class probabilities, utterance duration as a fraction of its maximum, and signal energy, giving the error ν_t^{utt} and its ratio $\tilde{\nu}_t^{\text{utt}}$. A non-neutral tone is an alert, $I(e) = I_{\text{Aud}}^{\text{hi}}$; a neutral one has $I(e) = \Gamma_{\text{Aud}}(\tilde{\nu}_t^{\text{utt}})$.

Interoception. A report is an alert when the set $\mathcal{A}_t$ of host metrics strictly above their hard thresholds is nonempty, and otherwise has $I(e) = \Gamma_{\text{Intero}}(\tilde{\nu}_t^{\text{Intero}})$, with ν_t^{Intero} the error of A.5. Fatigue-crossing and regulation events use $I_{\text{Intero}}^{\text{hi}}$.

Sequence. On each broadcast $\mathcal{B}_k$ the sequence module's input is $x_t^{\text{Seq}} = \Phi_I(\mathcal{C}_k, \Delta t_t, \iota_k)$ (A.1), with Δt_t the entity time since the previous broadcast (0 on the first). Intervals enter a window of the last $W_{\Delta t}$ as $\min(\Delta t_t,\ s_{\max}\overline{\Delta t}_{t-1})$, $\overline{\Delta t}_{t-1}$ being the window mean before entry (the first enters unchanged). A frozen continuous-time reservoir advances on x_t^{Seq} with timespan $s_t^{\text{Seq}} = \text{clip}_{[0, s_{\max}]}(\Delta t_t / \overline{\Delta t}_t)$, $\overline{\Delta t}_t$ being the mean after entry ($s_t^{\text{Seq}} = 1$ on the first broadcast). An online linear readout of the previous hidden state predicts $\hat{x}_t^{\text{Seq}}$ and learns by one stochastic-gradient step (rate η_{fm}) per broadcast outside sleep. The temporal error is the mean absolute error $\nu_t^{\text{Seq}} = \|x_t^{\text{Seq}} - \hat{x}_t^{\text{Seq}}\|_1 / 24$, with ratio $\tilde{\nu}_t^{\text{Seq}}$. The report is an alert when $\tilde{\nu}_t^{\text{Seq}} \geq \beta_\nu^{\text{Seq}}$ or on a recurrence, some bucket occurring at least n_{recur} times among the last W_{recur} hidden states, each quantized per dimension with step Δ_{recur} and hashed. Before any temporal error, the alert instead compares with β_ν^{Seq} the absolute z-score of the hidden state's Euclidean norm against the previous W_z broadcasts' norms.

Preprint. Not peer-reviewed.

Other modules. Affect states use $I^{\text{lo}}_{\text{Aff}}$; drive crossings, the affective reset, and a change to a non-neutral categorical emotion use $I^{\text{hi}}_{\text{Aff}}$. Sleep events use $I^{\text{lo}}_{\text{Sleep}}$, except a failed-phase sleep summary, $I^{\text{hi}}_{\text{Sleep}}$. Utterances use $I^{\text{lo}}_{\text{Lang}}$. Action-selection intents go on a stream the cycle does not read and are never candidates.

A.3 Adaptive access rate

Let f_0 be the resting broadcast rate (the access rate of §3.4 at rest), I_0 the phasic salience floor, and τ_{ph} the phasic decay time. On tick k the tonic drive is

$$H^{\text{ton}}_k = \text{clip}_{[0,1]}\left(\frac{\hat{a}_k - a_0}{1 - a_0}\right),$$

with $a_0 < 1$. A categorical alert is a predictive processor's report meeting its alert criterion (A.2) or another module's event at its alert level I^{hi}_m, never a graded report below it. With $\hat{I}_k$ the largest intensity among the categorical alerts of E_k, excluding cycle telemetry and the workspace stream, the phasic input is

$$H^{\text{in}}_k = \text{clip}_{[0,1]}\left(\frac{\hat{I}_k - I_0}{1 - I_0}\right),$$

with $H^{\text{in}}_k = 0$ when E_k holds no alert. The phasic drive is a peak-hold with exponential decay,

$$H^{\text{ph}}_k = \max\!\big(H^{\text{in}}_k,\ H^{\text{ph}}_{k-1}\,\mathrm{e}^{-\Delta_p/\tau_{\text{ph}}}\big), \qquad H^{\text{ph}}_{-1} = 0,$$

with Δ_p and τ_{ph} in entity seconds. The access drive is $H_k = \max(H^{\text{ton}}_k, H^{\text{ph}}_k) \in [0,1]$, and the effective broadcast rate is the linear map

$$f^{\text{eff}}_k = \begin{cases} f_0 + (f_p - f_0)\,H_k & f_0 < f_p, \\ f_0 & f_0 \geq f_p, \end{cases}$$

between f_0 and f_p; with the controller disabled, $f^{\text{eff}}_k = f_0$. A fractional accumulator with $A_{-1} = 0$ gives the broadcast indicator:

$$A'_k = A_{k-1} + \frac{f^{\text{eff}}_k}{f_p}, \qquad \chi_k = \mathbf{1}[A'_k \geq 1], \qquad A_k = \begin{cases} \min(A'_k - 1,\ 1) & \chi_k = 1, \\ A'_k & \chi_k = 0. \end{cases}$$

Subtracting before clamping keeps the fractional carry, so at the resting rate $f_0 = f_p/3$ every third tick broadcasts. The drive is computed from E_k before χ_k, so an alert can make its own tick a broadcast tick. If regulation lowers f_p to f_0 or below (A.5), every tick broadcasts, at rate f_p.

Preprint. Not peer-reviewed.

A.4 Affect

The affect module holds valence $v \in [-1, 1]$, arousal $a \in [0, 1]$ (starting at a_0, clipped to $[0, 1]$ after each update below), dominance, and four drives.

1. *Perceptual alert.* For each vision or acoustic audition alert (A.2), read from its stream whether selected or not,

$$a \leftarrow a + \gamma_a \min\big(\nu_{\text{cap}},\ \max(0,\ \tilde{\nu} - 1)\big)\,,$$

where $\tilde{\nu}$ is the running ratio of the forward-model error the report carries.

2. *Interoceptive alert.* For each interoception report with $\mathcal{A}_t \neq \emptyset$, $a \leftarrow a + \gamma_{\text{Intero}}$.

3. *Relaxation.* The module updates on every broadcast received, whatever ι_k, and every P_{Aff} of entity time, relaxing arousal and dominance toward baseline by an explicit-Euler step,

$$a \leftarrow a + (a_0 - a) \min(1,\ \lambda\, \Delta t_{\text{Aff}})\,,$$

with relaxation rate λ and Δt_{Aff} the entity time since the previous update (continuous-time constant $1/\lambda$).

4. *Sleep.* The sleep module's affective reset returns valence, arousal, and dominance to baseline, resets every drive to 0 and re-arms its crossing, sets the categorical emotion to neutral, and clears the active goals, the learning-progress error means, the rates r_{f}, r_{s}, and r_{int}, and the record of a speaker's perceived emotion, keeping the last wellness w.

Each update, in order, decays the alert rates, computes learning progress and alert excess, relaxes arousal, dominance, and valence, relieves curiosity and boredom, builds every drive, and publishes crossings; on a broadcast the appraisal follows. The module publishes its state, including a, once P_{Aff} has passed since the previous one. The cycle's $\hat{a}_k$ is the arousal of the last affect state event in E_k ($\hat{a}_k = \hat{a}_{k-1}$ if none), starting from the Table A1 default. Hence T_k, g_k (A.1), the tonic drive (A.3), the fovea size, and the attended auditory window (A.2) lag the internal a by up to about P_{Aff}, plus the shorter of one inter-broadcast interval and P_{Aff}, plus one tick.

Valence. For each perceptual module m (vision, acoustic audition) the affect module keeps fast and slow time-decayed means of its raw forward-model error ν_t^m (A.2), counting from the first positive error (a forward model reports zero before predicting). At the latest counted report time t_r,

$$\langle \nu^m \rangle_\tau = \frac{\sum_{i \le r} \mathrm{e}^{-(t_r - t_i)/\tau}\, \nu^m_{t_i}}{\sum_{i \le r} \mathrm{e}^{-(t_r - t_i)/\tau}}, \qquad \tau \in \{\tau_{\text{f}}, \tau_{\text{s}}\},$$

computed recursively; a common decay factor cancels, so the means need no update between reports. The signed learning progress lp is the mean, over modules with $\langle \nu^m \rangle_{\tau_{\text{s}}} > 0$,

Preprint. Not peer-reviewed.

of $\mathrm{clip}_{[-1,1]}\big((\langle \nu^m \rangle_{\tau_s} - \langle \nu^m \rangle_{\tau_f})/\langle \nu^m \rangle_{\tau_s}\big)$, with $\mathrm{lp} = 0$ before any such module exists; the progress above its noise floor is $\mathrm{lp}^+ = \max(0,\ \mathrm{lp} - \mathrm{lp}_0)/(1 - \mathrm{lp}_0)$. The appraisal's pleasantness check is $\mathrm{pl} = \tanh(k_v\,\mathrm{lp})$ (a term for a speaker's perceived emotion is off in this form), and valence relaxes toward $v_\infty = \mathrm{clip}_{[-1,1]}(\mathrm{pl} + w - \frac{1}{2})$,

$$v \leftarrow v + (v_\infty - v)\left(1 - \mathrm{e}^{-\Delta t_{\mathrm{Aff}}/\tau_v}\right),$$

where $w \in [0,1]$ is the interoception module's last reported wellness ($\frac{1}{2}$ before any): the mean over its host metrics of each metric's headroom scaled to $[0,1]$, with 1 healthy (one minus utilization for processor, memory, and GPU memory; GPU temperature linear between its lower and upper scaling bounds; cycle latency 1 up to its target, falling linearly to 0 at three times the target).

Drives. Each drive $D \in [0,1]$ has build rate β_D, decay rate δ_D, relief gain ρ_D, and threshold θ_D. Each update first relieves curiosity by $D \leftarrow D\,\mathrm{e}^{-\rho_D\,\mathrm{lp}^+\Delta t_{\mathrm{Aff}}}$ and boredom by $D \leftarrow D\,\mathrm{e}^{-\rho_D\,\mathrm{exc}\,\Delta t_{\mathrm{Aff}}}$, then, with its build signal $u \in [0,1]$ held over the step, moves every drive by the exact solution of $\dot{D} = \beta_D u(1-D) - \delta_D D$,

$$D \leftarrow D_\infty + (D - D_\infty)\,\mathrm{e}^{-(\beta_D u + \delta_D)\Delta t_{\mathrm{Aff}}}, \qquad D_\infty = \frac{\beta_D u}{\beta_D u + \delta_D}.$$

Curiosity has $u = 1 - \mathrm{lp}^+$. Boredom has $u = 1 - \mathrm{exc}$, with the alert excess

$$\mathrm{exc} = \mathrm{clip}_{[0,1]}\left(\frac{r_f}{\max(r_s,\ r_0)} - 1 - m_B\right),$$

where r_f and r_s are perceptual alert rates in alerts per entity second: each perceptual alert adds $1/\tau_f$ to r_f and $1/\tau_s$ to r_s, and each update first decays both by $\mathrm{e}^{-\Delta t_{\mathrm{Aff}}/\tau}$ with their own time constant. Because the A.2 criterion self-calibrates, even a still scene alerts at a steady base rate, and only alerts in excess of the habituated rate relieve boredom. The social drive has $u = 1$ once the sequence module has reported an interaction (a heard voice, §3.5) and $u = 0$ before, with relief $D \leftarrow D(1-\rho_D)$ on each new one. Restlessness has $u = 1 - r_{\mathrm{int}}$, where at each broadcast $r_{\mathrm{int}} \leftarrow r_{\mathrm{int}} + \alpha_{\mathrm{int}}(\min(1, n_{\mathrm{int}}) - r_{\mathrm{int}})$, n_{int} counting intents other than rest since the previous broadcast, with relief $D \leftarrow D(1-\rho_D)$ on each such intent. A crossing of θ_D is published once and re-arms after D falls below $\Theta_D\,\theta_D$. With every δ_D about a ninth of its β_D, a fully deprived drive settles near $D_\infty = 0.9$, above its threshold.

For the appraisal's goal-relevance check, the dominant drive d^* has the largest value, ties going to the alphabetically last name (boredom, curiosity, restlessness, social drive); v^* is its value, $\mathcal{R}(d^*)$ the sources whose events relieve it, and frac_k their share of the coalition's total intensity (0 for a zero total). The drive score is

$$r_{\mathrm{drive}} = v^*\,\mathrm{frac}_k,$$

Preprint. Not peer-reviewed.

with $r_{\text{drive}} = 0$ when there is no drive or $v^* \leq 0$. With an active goal ledger of token-overlap relevance $r_{\text{led}} \in [0, 1]$, the conducive part is $r = \max(r_{\text{drive}}, r_{\text{led}})$, and otherwise $r = r_{\text{drive}}$. Conduciveness being bipolar (§3.5), the goal score is $\text{clip}_{[-1,1]}(r - o)$, with the obstruction o below; it enters the categorical-emotion appraisal and reaches selection only through regulation (§3.5). The component process model checks relevance before conduciveness (Scherer 2009), so content that neither serves nor obstructs the drive or a goal scores 0, as irrelevant.

Coping potential is checked only when the goal score is nonzero. In the component process model coping is assessed against a specific demand, so the checks run in a fixed order (Sander, Grandjean and Scherer 2005). Otherwise coping is undefined, and fear, anger, and sadness, which need it, are not eligible. The score estimates power, the entity's own ability to change the outcome, which the model separates from control, whether any agent could change it (Sander, Grandjean and Scherer 2005). Learning agents derive power from interaction history, one reading being the agent's overall success (Moerland, Broekens and Jonker 2018), measured in path planning as goals reached against goals aborted (Williams et al. 2015). The estimate is that success ratio under Laplace's rule of succession (Jaynes 2003, ch. 18):

$$p = \frac{s + 1}{s + f + 2}.$$

An outcome counts as a success only when the entity's own response produced it, since outcomes that arrive independently of responses are what defines helplessness (Maier and Seligman 2016). For the drive term, a past crossing of the dominant drive counts in s when the entity's own response ended it: its learning progress for curiosity and its intents for restlessness, either by relieving the drive or by holding its build input down on the step the drive fell back, the latter credited only if the drive would not have fallen back with the build input at its no-response value. Every other end counts in f: decay alone, perceptual novelty for boredom, and another's voice for the social drive. A sleep reset counts as neither. For the ledger term, s and f count completed and abandoned goals. The term that sets the goal score supplies p, the drive term on a tie. The coping score is $2p - 1$, so 0 before any history. Arousal does not enter it, since in the component process model arousal follows appraisal.

Goals. A crossing of θ_D creates the goal of relieving D (§3.5), with priority D at the crossing, unless one exists; intents never create goals. The goal completes when D falls below $\Theta_D \theta_D$ and the credit rule above credits the entity's own response, and it is abandoned when the fall came without one, when D stays above θ_D for Δ_{stall}, or, as the lowest priority, when active goals exceed n_{goal}. Operator requests await speech-to-text.

Obstruction. Each active goal carries an expected-relief likelihood $L \in [0, 1]$ (§3.5), set to the coping ratio p at creation. When an intent other than rest, made while the goal is active, is followed by no fall of its drive within Δ_{resp}, L falls by $\Delta L = \eta_L L$; for the dominant drive's goal the next appraisal takes $o = v^* \Delta L$, scaled by drive value as r_{drive} is, and otherwise $o = 0$.

Preprint. Not peer-reviewed.

A.5 Interoceptive prediction and regulation

The interoception module reads the host every P_{Intero} into a vector $x_t \in \mathbb{R}^{n_x}$ of normalized metrics. A frozen closed-form continuous-time reservoir advances $\mathbf{h}_t = \mathcal{F}(x_t, \mathbf{h}_{t-1}; s_t^{\text{Intero}})$ with $\mathbf{h}_0 = 0$; the timespan $s_t^{\text{Intero}} = \text{clip}_{[0, s_{\max}]}(\Delta t_{\text{Intero}}/P_{\text{Intero}})$, with Δt_{Intero} the entity time since the previous reading ($s_t^{\text{Intero}} = 1$ on the first), enters the cell's time gates (Hasani et al. 2022), so irregular readings integrate the elapsed time. Only the linear readout $\mathbf{L}_{\text{Intero}}$ adapts; its regressor stacks reservoir state, context, and a constant, so the prediction of x_t made at reading $t-1$ is

$$\hat{x}_t = \mathbf{L}_{\text{Intero}}\, \varphi_{t-1}, \qquad \varphi_{t-1} = (\mathbf{h}_{t-1},\ b_{t-1},\ 1),$$

with b_{t-1} the context then held (A.1). With $\varepsilon_t = \hat{x}_t - x_t$, the prediction error is $\nu_t^{\text{Intero}} = \|\varepsilon_t\|_2$ (0 on the first reading). One stochastic-gradient step on $\|\varepsilon_t\|_2^2/n_x$ follows, skipped during sleep,

$$\mathbf{L}_{\text{Intero}} \leftarrow \mathbf{L}_{\text{Intero}} - \eta_{\text{fm}}\, \frac{2}{n_x}\, \varepsilon_t\, \varphi_{t-1}^{\top},$$

after which the reservoir advances on x_t and the readout predicts x_{t+1}.

Each channel i keeps an expected absolute error μ_i^U and a spread σ_i^U, both starting at 0. With the bound $\Omega_i = \mu_i^U + \beta_U \sigma_i^U$ taken before this reading's update, the unexpected error is

$$U_t = \sqrt{\sum_{i=1}^{n_x} \Big[\max\big(0,\ |\varepsilon_{t,i}| - \Omega_i\big)\Big]^2}.$$

Then, with $\alpha_t = 1 - \mathrm{e}^{-\Delta t_{\text{Intero}}/\tau_U}$, each channel updates $\sigma_i^U \leftarrow \sigma_i^U + \alpha_t\big(\big||\varepsilon_{t,i}| - \mu_i^U\big| - \sigma_i^U\big)$ and $\mu_i^U \leftarrow \mu_i^U + \alpha_t(|\varepsilon_{t,i}| - \mu_i^U)$, both with the prior μ_i^U, so the spread is an exponential moving average of the absolute deviation from μ_i^U. These updates are skipped during sleep; U_t drives regulation and fatigue and does not enter $I(e)$.

The regulation error is $\nu_t^{\text{act}} = \nu_t^{\text{Intero}}$ when $\mathcal{A}_t \neq \emptyset$ and U_t otherwise. A stress episode runs from the first reading with $\nu_t^{\text{act}} \geq \theta_R$ to the first with $\nu_t^{\text{act}} < \theta_R$. After Δ_t^{st} entity seconds of an episode, each increase of $\lfloor \Delta_t^{\text{st}}/\Delta_R \rfloor \geq 1$ emits one advisory of tier $\min\big(\lfloor \Delta_t^{\text{st}}/\Delta_R \rfloor, 3\big)$: reduce the processing rate, shed a low-priority module, or request maintenance. A per-boot warm-up, ending once the boot has made at least n_{wu} readout updates and Δ_{wu} entity seconds have passed since the module's first reading, withholds advisories unless $\mathcal{A}_t \neq \emptyset$. A rate advisory sets $f_p \leftarrow \text{clip}_{[f_p^{\min},\, f_p^{\max}]}(\gamma_f f_p)$.

Preprint. Not peer-reviewed.

A.6 Report rule

The action-selection module derives intents only from accessed broadcasts ($\iota_k = 0$), by these first-configuration steps, timed in entity time t_{now}.

1. *Guard release.* The speak guard is released when $\mathcal{C}_k$ contains the language organ's external speech, the think guard on its internal speech, and either after timeout Δ_g (§5.4).
2. *Report signal.* Let $\mathcal{C}_k^{\circ}$ be the coalition minus the language organ's events; an empty one yields no intent. Otherwise $e_k^{\dagger}$ is its first (highest-scoring) member, $Q_k = S'_k(e_k^{\dagger})$, and its signature $\text{sig}_k = \big(\text{src}(e_k^{\dagger}), \text{typ}(e_k^{\dagger})\big)$ pairs its source and event type.
3. *Signature check.* A spoken report is blocked when $\text{blk}_k = \mathbf{1}\big[\text{sig}_k = \text{sig}^{\text{last}} \wedge t_{\text{now}} - t^{\text{sig}} < \Delta_{\text{sig}}\big] = 1$, with sig^{last} and t^{sig} the last spoken report's signature and time.
4. *Speak.* A speak intent is emitted when

$$Q_k \geq \theta_{\text{sp}}, \qquad \text{the speak guard is released}, \qquad t_{\text{now}} - t^{\text{sp}} \geq \Delta_{\text{sp}}, \qquad \text{blk}_k = 0.$$

Emitting it arms the speak guard and sets $t^{\text{sp}} \leftarrow t_{\text{now}}$, $\text{sig}^{\text{last}} \leftarrow \text{sig}_k$, and $t^{\text{sig}} \leftarrow t_{\text{now}}$.

5. *Think.* Otherwise a think intent is emitted when $Q_k \geq \theta_{\text{th}}$, the think guard is released, and $t_{\text{now}} - t^{\text{th}} \geq \Delta_{\text{th}}$, arming the think guard and setting $t^{\text{th}} \leftarrow t_{\text{now}}$, with no signature check and no change to sig^{last}.

At most one intent is emitted per broadcast; t^{sp} and t^{th} start at $-\infty$. The rule requires $0 \leq \theta_{\text{th}} \leq \theta_{\text{sp}} \leq 1$, both bars above θ and on the same score S'_k; an optional interrupt bar above θ_{sp} is unset here.

A.7 Heartbeat entrainment marker

Awake time $\mathcal{T}_{\text{awake}}$ (entity time awake with the cycle unfrozen, summed over boots) is one clock for all rules; it, f_{w0}, the consecutive-pass count, whether the marker was ever true, and the pull history persist with the entity, so a restart neither resets nor repeats them.

Self-rhythm model. The interoception module's self-rhythm is a mean-field population with excitatory recurrence, synaptic depression, and adaptive recovery, with activity y, synaptic resource $R \in [0, 1]$, and log recovery time $\ell = \ln(\tau_{\text{rec}}/1\,\text{s})$, initialized from Table A1. Each step of $\Delta_r = 1/f_r$ runs n_s equal semi-implicit Euler substeps, with y updated first and R from the new y:

$$\Xi = J_{\text{rec}}\, R\, y + \Xi_0 + \gamma_o\, o + \gamma_u\, M + \xi, \qquad y_\infty = \frac{1}{1 + \mathrm{e}^{-\Xi/k_y}},$$

$$\tau_y\, \dot{y} = -y + y_\infty, \qquad \dot{R} = \frac{1 - R}{\tau_{\text{rec}}} - \gamma_R\, R\, y,$$

Preprint. Not peer-reviewed.

with R clipped to $[0, 1]$ after each substep and τ_{rec} fixed within a step. The own drive $o \in [0, 1]$ is the module's last report intensity, $M \in [0, M_{\max}]$ is the maternal drive (below), and the Gaussian noise ξ, redrawn each substep, has standard deviation $\sigma_\xi \sqrt{(10^{-3}\ \text{s})\, n_s/\Delta_r}$. After each step the averages $\bar{M}$, $\bar{y}$, $\bar{R}$ update with weight $\alpha_{\text{r}} = \min(1, \Delta_r/\tau_m)$, and the recovery time adapts by a phase-projected rule,

$$\ell \leftarrow \text{clip}_{[\ln \tau_{\text{rec}}^{\min},\, \ln \tau_{\text{rec}}^{\max}]}\big(\ell - \eta_\ell\,(M - \bar{M})\,\zeta\,\Delta_r\big)\,, \qquad \zeta = \frac{R - \bar{R}}{\sqrt{(y - \bar{y})^2 + (R - \bar{R})^2}},$$

with $\zeta = 0$ when the root is at most 10^{-9} and bounds in seconds; the rule never uses the maternal rate. amp is the population standard deviation of the activity over the last Δ_{amp}, mean-removed and causally band-passed to $[f_{\text{lo}}, f_{\text{hi}}]$ (0 for the first four seconds). At the initial τ_{rec} the rhythm runs near 0.8 Hz undriven and 0.9 Hz at a mid-range own drive; its period grows with τ_{rec}, steeply near $\tau_{\text{rec}}^{\max}$, where the equilibrium nears a Hopf point.

Maternal drive and probes. The maternal beat has phase $\psi \in [0, 2\pi)$, a nominal rate with slow drift, and a "lub-dub" envelope $\mathcal{E}(\psi) \in [0, 1]$. Each step sets $M = M_{\max}\, c_M\, \bar{\mathcal{E}}$, with $\bar{\mathcal{E}}$ the mean envelope since the last step and c_M equal to c_M^{base}, 0 in a withdrawal (length Δ_W), or c_M^{pert} in a perturbation (length Δ_{pert}). A withdrawal or perturbation starting at t' schedules the next of its kind at $t' + P_W(1 + j_P \Upsilon)$ or $t' + P_{\text{pert}}(1 + j_P \Upsilon)$, Υ uniform on $[-1, 1)$ from the run seed; the first of each follows the post-boot settling period, offset likewise. A due probe starts at the first readout step with no probe running, the entity awake and unfrozen, at least P_{ro} since boot or thaw, and at least $\max(60\ \text{s}, \Delta_W)$ since the last probe; the earlier-scheduled kind goes first.

Phase-locking value. At rate f_g the readout samples y, ψ, and the phases $\psi^{(1)}, \ldots, \psi^{(19)}$ of 19 surrogate heartbeats (the beat generator under 19 other seeds, the surrogate method of Van Leeuwen et al. 2003). Withdrawal j's driven window, the contiguous run of undisturbed samples of at most Δ_E ending at its start, uses only samples with all 21 values and needs at least $0.8\,\Delta_E f_g$ of them. The activity is mean-centered, band-passed to $[f_{\text{lo}}, f_{\text{hi}}]$ by a zero-phase forward-backward Butterworth band-pass of design order two (fourth order as a filter), and Hilbert-transformed to the phase ϕ_q; $\Delta_{\text{trim}} f_g$ samples are trimmed from each end of every series. Over the n_ϕ remaining samples,

$$\text{PLV} = \left| \frac{1}{n_\phi} \sum_{q=1}^{n_\phi} \mathrm{e}^{\,\mathrm{i}(\phi_q - \psi_q)} \right|, \qquad \text{PLV}^{(l)} = \left| \frac{1}{n_\phi} \sum_{q=1}^{n_\phi} \mathrm{e}^{\,\mathrm{i}(\phi_q - \psi_q^{(l)})} \right|,$$

and the locking condition is $\text{PLV} > \max_{1 \le l \le 19} \text{PLV}^{(l)}$, strictly, so ties fail. Under the null that the own-heartbeat PLV is exchangeable with the 19 surrogate values, this is a rank test with attained one-sided $p = 1/20 = 0.05$.

Frequency pull. f_w is the least-squares slope, divided by 2π, of the activity's unwrapped Hilbert phase during the withdrawal (processed as above, untrimmed; needs at least

Preprint. Not peer-reviewed.

$0.6\,\Delta_W f_g$ samples), f_b that slope for the unwrapped beat phase over the driven window's used samples, and f_{w0} the mean f_w over the entity's first n_{base} withdrawals with defined f_w. From the n_{base}-th such withdrawal on, inclusive,

$$\text{pull} = 1 - \frac{|f_w - f_b|}{|f_{w0} - f_b|},$$

undefined when f_w or f_b is undefined or $|f_{w0} - f_b| < f_{\text{guard}}$. The pull condition is pull $\geq$ pull_{min}. Below about 60 bpm the heartbeat lies too close to the rhythm's natural rate for the pull to be defined, so the maternal model uses 60 to 80 bpm.

Self-sustain. With $\overline{\text{amp}}^{\text{dr}}$ the mean amplitude over undisturbed samples in the Δ_W before the withdrawal and $\overline{\text{amp}}^{\text{wd}}$ the mean during it, the rhythm self-sustains when $\overline{\text{amp}}^{\text{wd}} \geq \frac{1}{2}\,\overline{\text{amp}}^{\text{dr}}$ and $\overline{\text{amp}}^{\text{wd}} > 0$.

Marker. Withdrawal j passes ($\text{pass}_j = 1$) when locking, pull, and self-sustain all hold, and is undefined when any is. The count is $n_j^{\text{pass}} = n_{j-1}^{\text{pass}} + 1$ if $\text{pass}_j = 1$ and $n_j^{\text{pass}} = 0$ otherwise, undefined passes included. The marker after withdrawal j is undefined when pass_j is and otherwise $\mathbf{1}[n_j^{\text{pass}} \geq 3]$. Three consecutive passes guard against a chance pass of the locking test at $p = 0.05$; consecutive withdrawals are correlated, so the joint error rate is not 0.05^3.

Viability. After each withdrawal, $\mathcal{P}$ holds the defined pull values of the last Δ_V awake hours; when $|\mathcal{P}| \geq n_V$, $\widetilde{\text{pull}}$ is their median and $\widehat{\text{slope}}$ their least-squares slope per awake hour. The phase is declared unviable at the first rule that fires:

- R0: $\mathcal{T}_{\text{awake}} \geq t_{R0}$ and no defined pull has been recorded;
- R1: $\mathcal{T}_{\text{awake}} \geq t_{R1}$, the marker has never been true, $|\mathcal{P}| \geq n_V$, $\widetilde{\text{pull}} < \text{pull}_{R1}$, and $\widehat{\text{slope}} \leq \text{slope}_{R1}$;
- R2: $\mathcal{T}_{\text{awake}} \geq t_{R2}$, the marker has never been true, $|\mathcal{P}| \geq n_V$, and $\widetilde{\text{pull}} < \text{pull}_{R2}$;
- R3: $\mathcal{T}_{\text{awake}} \geq t_{R3}$ and the marker has never been true.

The verdict is recorded once; the study runner ends the step and keeps its data.

Maturation gate and budget. The gate, evaluated each gate cadence, has three conditions, each failing closed on missing or stale evidence. C1 requires a readout at most three cadences old in which the latest withdrawal's self-sustain and entrainment markers are true, $V_{\text{per}} \geq V_{\text{per}}^{\text{min}}$, $\text{err}_{\text{Vis}} \leq \text{err}_{\text{Vis}}^{\text{max}}$, and the return-to-baseline time is at most $\Delta_{\text{max}}^{\text{rec}}$. The period variability V_{per} is the coefficient of variation of intervals between self-rhythm phase wraps over the last Δ_{per}, once four wraps exist. The vision error ratio err_{Vis} is the median vision prediction error on the developmental stimulus (§7) since the last readout, divided by the first such median of at least three errors. The return-to-baseline time runs from the last perturbation's end to the first sample where the median of ν^{Intero} over the preceding five seconds (not before the perturbation's start) is at most $(1 + \text{tol}_{\text{rec}})$ times its median over the minute before the perturbation, and is $\Delta_{\text{cap}}^{\text{rec}}$, a C1 failure, if none comes within $\Delta_{\text{cap}}^{\text{rec}}$. C2 requires at least n_{sleep} completed sleeps with the sleep module present, and at least n_{cons} con-

Preprint. Not peer-reviewed.

solidation passes with the world-model module also present. C3 requires $\mathcal{T}_{\text{awake}} \geq \Delta_{\text{awake}}$. Independently, the study runner ends a developmental step once its wall-clock duration exceeds Δ_{budget}.

Offline validation. The plasticity rate is set so that a lock forms well within the 96-hour budget. Over 96 simulated hours all 10 seeds entrain at 70 bpm, typically by about 14 hours, and each rate from 60 to 80 bpm tracks its own heartbeat and locks in 3 to 48 hours. No control passes: no maternal drive, a jittered beat, no plasticity, and six mismatched pairs scored against a heartbeat other than the driving one, whose single withdrawals passed by chance in 2.6 to 10 percent of cases, never three in a row. The three-pass requirement, fixed on the first validation run, was confirmed on fresh seeds. The same validation set the viability thresholds; it flagged no viable phase and every unviable one by 24 to 27 hours.

A.8 Broadcast information gain and the planned test

Every setting named here, including those derived from pilot or preliminary runs, is recorded with the preregistration, the film program's composition, and its manifest hash before any live run.

Gain. Let $\mathcal{J} = \{\text{Vis}, \text{Aud}, \text{Intero}\}$, the sequence module excluded (§6.3). For $j \in \mathcal{J}$ and report t, b is the context j held when forming the prediction scored at t (A.2, A.5), and $\nu_t^j(b')$ that prediction's error with b' for b and all weights unchanged, so $\nu_t^j(b) = \nu_t^j$ (for audition, the acoustic path's error). The kept sources of j are j and, for interoception, the language organ, whose host load would otherwise let its context share predict the interoceptive input. In the null context b_j^0, each component of b summing per-event contributions (A.1) becomes the kept sources' share plus the others' share averaged over the contexts the processor has adopted so far in the run; coalition-level components 1 to 4 become their means over those contexts; the age and two flags are kept. The report's broadcast information gain is

$$\text{gain}_{j,t} = \frac{\nu_t^j(b_j^0) - \nu_t^j(b)}{\bar{\nu}_t^j},$$

with $\bar{\nu}_t^j$ the running mean of j's errors over W_P (A.2). A report is included when its error is defined, $\bar{\nu}_t^j > 0$, a context was adopted before the prediction, the entity was awake, and it falls after the learning period T_{learn} (entity time from run start). IG_j is the mean of $\text{gain}_{j,t}$ over j's included reports in one run of an arm, undefined if there is none, and the headline is

$$\text{IG} = \frac{1}{3} \sum_{j \in \mathcal{J}} \text{IG}_j,$$

undefined if any IG_j is.

Positive control. For each $j \in \mathcal{J}$, a synthetic component informative about j's next input x_{t+1}^j joins j's context as another source's contribution, so the null context replaces it by its

Preprint. Not peer-reviewed.

mean. It is $v_j^\top (x_{t+1}^j - \mu_j) + \epsilon_t$, with v_j the first principal component of j's inputs (their unit direction of greatest variance; Jolliffe 2002) and μ_j their mean, both from a preliminary on-arm run on a seed not used again, and ϵ_t independent Gaussian noise with the projection's variance divided by SNR_j. A second component of equal mean and variance, independent of the input, runs beside it. A component's effect is IG_j with it minus without it, over included reports of complete film-program runs. Following Currie's (1968) detection limits, with target $\theta_{\mathrm{PC}} = \min(\theta_{\mathrm{eff}}^{\mathrm{match}}, \theta_{\mathrm{eff}}^{\mathrm{pool}})$, SNR_j sets the informative component's expected effect to θ_{PC}, and j passes when, over at least n_{PC} included reports (from consecutive complete runs if needed), that component's effect reaches $\theta_{\mathrm{PC}}/2$ and the other's does not; n_{PC} gives detection probabilities of 0.95 and at most 0.05. An effect of θ_{PC} in every processor moves the headline by θ_{PC}, so a pass shows the measure registers an effect of the test's minimum size. The live test runs only after every processor passes.

Arms. The arms run the first configuration (§6.3), run r of each on the same seeds, so runs are paired.

- *Workspace on.* Selection and access as in A.1, with the context $b = \Phi_I(\mathcal{C}_{k'}^{\mathrm{acc}}, \Delta^b, 0)$.
- *Matched selection.* Each broadcast tick's coalition is $\min(K, |E_k|)$ candidates drawn uniformly without replacement from E_k by a generator seeded from the run seed; the rule of A.1 then gives the accessed set (drawn members whose scores reach θ), whose Φ_I is the context.
- *Pooled.* No candidate is scored, selected, or gated. Every broadcast has $\iota_k = 0$ and replaces the context by $b = \Phi_I(E_{k'}, \Delta^b, 0)$, the featurization of every candidate of its tick. The action-selection module applies the rule of A.6 with intensities for scores, and the access rate (A.3) runs unchanged on alerts and arousal.

Run contrasts. Against control $\mathrm{ctl} \in \{\mathrm{match}, \mathrm{pool}\}$, run r has contrast $\mathrm{dIG}_r^{\mathrm{ctl}} = \mathrm{IG}_r^{\mathrm{on}} - \mathrm{IG}_r^{\mathrm{ctl}}$ and minimum effect $\theta_{\mathrm{eff}}^{\mathrm{ctl}} = c_{\mathrm{eff}}\, s_{\mathrm{cal}}^{\mathrm{ctl}}$, with $s_{\mathrm{cal}}^{\mathrm{ctl}}$ the sample standard deviation of $\mathrm{dIG}^{\mathrm{ctl}}$ over the n_{cal} paired pilot runs. A run is NOT EXERCISED when competition never operates (in the on arm, $|E_k| \le K$ whenever $\chi_k = 1$), when the on arm has no accessed broadcast, or when $\mathrm{dIG}_r^{\mathrm{ctl}}$ is undefined. Otherwise it is NEGATIVE if $\mathrm{dIG}_r^{\mathrm{ctl}} \le -\theta_{\mathrm{eff}}^{\mathrm{ctl}}$, WIN if $\mathrm{dIG}_r^{\mathrm{ctl}} \ge \theta_{\mathrm{eff}}^{\mathrm{ctl}}$, and NULL otherwise. The predicted direction is positive.

Decision rule. For each control, the runs classified WIN, NULL, or NEGATIVE enter two one-sided exact sign tests, which assume only that runs are independent: the WIN test on $u_r^+ = \mathrm{dIG}_r^{\mathrm{ctl}} - \theta_{\mathrm{eff}}^{\mathrm{ctl}}$ and the NEGATIVE test on $u_r^- = -\theta_{\mathrm{eff}}^{\mathrm{ctl}} - \mathrm{dIG}_r^{\mathrm{ctl}}$. Dropping exact zeros, with $n_\pm$ values left of which $n_\pm^{\mathrm{pos}}$ are positive,

$$\mathrm{pv}^{\pm} = 2^{-n_\pm} \sum_{i=n_\pm^{\mathrm{pos}}}^{n_\pm} \binom{n_\pm}{i},$$

with $\mathrm{pv}^{\pm} = 1$ when $n_\pm = 0$. The verdict is WIN when $\mathrm{pv}^+ \le \alpha_{\mathrm{test}}$, NEGATIVE when $\mathrm{pv}^- \le \alpha_{\mathrm{test}}$, NOT EXERCISED when every run is, and NULL otherwise. The hypothesis holds for this configuration on a WIN against both controls, an intersection-union test, so each is tested at α_{test} without multiplicity adjustment. The smallest attainable value is $2^{-n_\pm}$, so no outcome can reach 0.05 with fewer than five runs. With k_n the smallest k for which

Preprint. Not peer-reviewed.

$2^{-n}\sum_{i=k}^{n}\binom{n}{i} \le \alpha_{\text{test}}$, the power of the WIN test at n runs, when each $\text{dIG}_r^{\text{ctl}}$ exceeds $\theta_{\text{eff}}^{\text{ctl}}$ with probability q_{pow}, is

$$\pi(n) = \sum_{i=k_n}^{n} \binom{n}{i} q_{\text{pow}}^{i} \, (1 - q_{\text{pow}})^{n-i}.$$

As the test is discrete, $\pi(n)$ is not monotone in n.

Contrast at threshold. In the on arm access is exactly $S_k^* \ge \theta$ (A.1), a sharp regression discontinuity (Imbens and Lemieux 2008) with running variable S_k^* and cutoff θ; a broadcast is near threshold when $|S_k^* - \theta| \le \theta_{\text{band}}$. The reports following $\mathcal{B}_k$ are the included reports of each $j \in \mathcal{J}$ predicted after j received $\mathcal{B}_k$ and before the next broadcast. Reports are grouped by their context age Δ^b (§6.3) in bins fixed with the other settings, and $\bar{g}_{k,a}$ is the mean gain of the reports following $\mathcal{B}_k$ in bin a. In run r and bin a, $\widehat{\tau}_{r,a}$ is the jump of $\bar{g}_{k,a}$ at $S_k^* = \theta$ from a local-linear fit per side with a triangular kernel of half-width θ_{band}, bias-corrected by a local-quadratic fit of half-width b_{band} (Calonico, Cattaneo, and Titiunik 2014). A side is fitted only if it holds at least n_{side} distinct values of S_k^* within both bandwidths of the threshold, and each fit's weighted least-squares problem, with the score scaled by its bandwidth, has condition number at most κ_{max}, which keeps about eight significant digits in double precision. A local-polynomial fit behaves as if it had one observation per distinct value of the running variable (Cattaneo, Idrobo, and Titiunik 2024), so a sparse bin would otherwise weigh as much as a full one; $n_{\text{side}} = 10$ is their smallest recommended per-side number, given for the narrowest local-randomization window. The run's contrast is the mean $\widehat{\tau}_{r,a}$ over bins with both sides fitted, undefined if none, and across runs enters a sign test of the same form on the contrast minus its minimum effect. That test carries the bias correction's variability through the spread across runs; the robust confidence interval of Calonico, Cattaneo, and Titiunik (2014) covers it within one sample and is reported, with standard errors clustered by run, for each bin's pooled estimate.

Speech sound and tone. A variant of the on arm replaces the tone rule of A.2 by $I(e) = \Gamma_{\text{Aud}}(\tilde{\nu}_t^{\text{utt}})$ for every tone event, its run r seeded as run r of the arms. The difference of run r, the accessed fraction of emotional tone events minus that of neutral ones, both after T_{learn} (undefined unless both occur), enters a sign test of the same form. The adjusted difference, which checks that $\tilde{\nu}_t^{\text{utt}}$ accounts for it (§6.3), averages the within-bin difference over bins of $\tilde{\nu}_t^{\text{utt}}$ holding both kinds (undefined if none) and enters a second such test; bins are not tested separately. These tests and that of the contrast at threshold use α_{test} without multiplicity adjustment (§6.3).

Settings from the pilot runs. $n_{\text{cal}} = 30$ paired pilot runs of the three arms and the tone variant, on seeds not used again, fix every remaining setting by the rules below; thirty is a common pilot sample size for estimating a parameter (Lancaster, Dodd, and Williamson 2004). NOT EXERCISED pilot runs are replaced until thirty count, r_{NE} is the fraction of attempts NOT EXERCISED, and no live run enters a setting.

Learning period. For each arm and $j \in \mathcal{J}$, the gains of j's reports are averaged across pilot runs at each report number and grouped in consecutive batches of five, with means $\bar{Y}_1, \ldots, \bar{Y}_b$. The truncation point follows the marginal standard error rule (White 1997),

Preprint. Not peer-reviewed.




Figure 8: From the pilot runs to the verdict. A preliminary on-arm run gives principal components and input means; thirty paired pilot runs fix every remaining setting by rules stated in advance; the positive control gates the test runs; the hypothesis holds on WIN against both controls.

Preprint. Not peer-reviewed.

found the most effective for automatic use in a comparison of warm-up methods (Hoad, Robinson, and Davies 2010),

$$d^{*} = \arg\min_{0 \le d \le b-5} \frac{1}{(b-d)^{2}} \sum_{i=d+1}^{b} \left(\bar{Y}_{i} - \bar{Y}_{(d)}\right)^{2},$$

with $\bar{Y}_{(d)}$ the mean of $\bar{Y}_{d+1}, \ldots, \bar{Y}_{b}$. As in that comparison, at least five batch means remain after d, since a few close final means give a spuriously small statistic, which is 0 for every series at $d = b-1$. T_{learn} is the largest, over arms and processors, of the median entity time of report $5d^{*}$ in the pilot runs, rounded up to a whole second, and applies to every test run and the positive control. The pilot runs are too short if $d^{*} > b/2$ or a series has under ten batch means (its search cannot reach the second half); the test then waits for longer ones.

Minimum effects. $c_{\text{eff}} = 0.5$, half the standard deviation of the contrast, is a distribution-based smallest effect of interest (Norman, Sloan, and Wyrwich 2003; Lakens 2017). The contrast at threshold and the two tone tests use c_{eff} times the standard deviation of their run-level statistic over the pilot runs where it is defined.

Runs. $q_{\text{pow}} = 0.65$, Cohen's (1988) medium effect for the sign test, is a design value, as pilot effect estimates are too imprecise to set power (Kraemer et al. 2006). n_{exact}, the smallest n with $\pi(n') \ge 0.9$ for every $n' \ge n$ (Chernick and Liu 2002), is 102, with $\pi(102) = 0.920$. Power 0.9 per control keeps the probability of WIN against both at or above 0.8 under any dependence between the tests. $n_{\text{run}} = \lceil n_{\text{exact}} / (1 - r_{\text{NE}}) \rceil$ runs are planned, with more added until at least n_{exact} enter each control's test; entry ignores the contrast, so the level is unchanged, and $\pi(n) \ge 0.9$ for every $n \ge n_{\text{exact}}$ keeps the planned power. The secondary tone analysis's first test has the same power function, so the tone variant is planned with the same n_{run} and extended until at least n_{exact} runs give a defined difference.

Positive control. Every on-arm pilot run carries both components of each processor at SNR $\in \{4^{-2}, 4^{-1}, \ldots, 4^{4}\}$; SNR_{j} is the smallest value at which the informative component's mean pilot effect reaches θ_{PC}, interpolated linearly in log SNR from the value below. If none does, the live test does not run. With s_{j}^{2} the larger of the two components' pilot variances of the run-level effect at SNR_{j} and $\bar{n}_{j}$ the mean included reports of j per pilot run,

$$n_{\text{PC}} = \max_{j \in \mathcal{J}} \left\lceil \frac{(2 z_{0.95})^{2}\, \bar{n}_{j}\, s_{j}^{2}}{\theta_{\text{PC}}^{2}} \cdot \frac{n_{\text{cal}} - 1}{\chi^{2}_{0.2,\, n_{\text{cal}}-1}} \right\rceil,$$

where $z_{0.95}$ is the standard normal quantile, so that $2z_{0.95}$ standard errors, the detection limit of Currie (1968) at $\alpha = \beta = 0.05$, equal θ_{PC}. The last factor is the 80 percent upper confidence limit on the variance that Browne (1995) recommends for sizing from a pilot sample. Run-level variance times reports per run gives the variance per report, and as the control uses complete runs, the rule holds whether or not the effect varies between runs.

Band and bins. θ_{band} and b_{band} minimize the asymptotic mean squared error of the local-linear jump estimate at θ and of its local-quadratic bias correction (Calonico, Cattaneo, and

Preprint. Not peer-reviewed.

Titiunik 2014), on the pooled on-arm pilot broadcasts, one observation per broadcast with a following included report (their mean gain). The selector of Imbens and Kalyanaraman (2012) would fix θ_{band} alone, leaving the bias correction without a bandwidth. A run's jump is a point estimate entering a sign test, which calls for the mean-squared-error criterion; the bandwidth optimal for the robust interval's coverage error is smaller, and the interval stays valid at the larger one (Calonico, Cattaneo, and Farrell 2020). A bias shared by every run moves each run's sign alike and survives aggregation over runs, while per-run noise costs only power, so both bandwidths are set on the pooled sample, which narrows θ_{band} to about $30^{-1/5} \approx 0.5$ times a single run's optimum. The age bins are the quintiles of Δ^b over reports following near-threshold broadcasts in the on-arm pilot runs, and the tone bins the quintiles of $\tilde{\nu}_t^{\text{utt}}$ over all tone events after T_{learn}, emotional and neutral, in the tone-variant pilot runs on the counted seeds. The plain mean over quintile bins, which weights both sides alike, is a direct adjustment to the pooled pilot distribution: five equal-weight subclasses of equal size remove about 90 percent of the bias from a continuous covariate (Cochran 1968), and Rosenbaum and Rubin (1984) used such weights with pooled-sample quintiles.

A.9 Multi-seed stability

For per-seed headline values $Y_1, \dots, Y_{n_{\text{seed}}}$ with mean $\bar{Y}$ and population standard deviation σ_Y ($\sigma_Y = 0$ for one seed), the coefficient of variation is

$$\text{CV} = \begin{cases} \sigma_Y / |\bar{Y}| & \bar{Y} \neq 0, \\ 0 & \bar{Y} = 0,\ \sigma_Y = 0, \\ \infty & \bar{Y} = 0,\ \sigma_Y > 0. \end{cases}$$

An ensemble is stable when $\text{CV} \leq \text{tol}_{\text{CV}}$ and at most one distinct verdict occurs; one without verdicts counts as unanimous, and an infinite CV never meets tolerance. The offline suite checks the coherence-layer ablation over n_{seed} seeds. Within-run dynamical stability is out of scope, and the CV is ill-conditioned near a zero mean.

A.10 Memory strength and sleep

These rules of §4 apply when the held episodic-memory module is present. It stores one trace per broadcast, each persisted trace i with a strength $h_i \in (0, 1]$, set to 1 at storage and changed only by downscaling, and a storage time on the entity clock. $\mathcal{W}$ is the set of traces stored since the last downscaling, and $N_{\text{new}} = |\mathcal{W}|$.

Replay. Each sleep first replays the set $\mathcal{Q}$ of the n_{rep} traces of $\mathcal{W}$ (all, if fewer) with the highest score $c_{\text{aff}}\, a_i^{\text{enc}} + c_{\text{rec}}\, \text{rec}_i$, where a_i^{enc} is the affect module's last published arousal (A.4) before trace i was stored (0 if none) and rec_i maps storage time linearly onto $[0, 1]$ across $\mathcal{W}$, newest 1 and oldest 0 ($\text{rec}_i = 1$ if all share one time).

Downscaling. Traces outside $\mathcal{Q}$ are then scaled by one factor,

$$h_i \leftarrow \varrho^{\,N_{\text{new}}/N_{\text{day}}}\, h_i, \qquad i \notin \mathcal{Q},$$

Preprint. Not peer-reviewed.

and those in $\mathcal{Q}$ keep theirs. $N_{\text{day}} = 86\,400\, f_0$ traces are stored per entity day at the resting broadcast rate, so an unreplayed trace keeps the fraction ϱ of its strength per such day; when sleep comes hourly at that rate, one replay spares a trace less than 1 percent of its strength. A sleep after a wake that stored nothing changes no strength. At the resting rate $\sum_i h_i$ approaches $N_{\text{day}}/\ln(1/\varrho)$, about five days of storage, after which each sleep returns it to about its pre-wake level, the renormalization to a baseline that the hypothesis describes (§4).

Associative replay. After downscaling, each sleep co-replays at most n_{pair} pairs, most similar first, of a trace in $\mathcal{Q}$ and one stored before $\mathcal{W}$ with $\text{sim}_{\text{min}} \le \text{sim} < \text{sim}_{\text{dup}}$ (sim as in recall below). A pair's link has weight $w = 1/2$, a pair co-replaying once since $\mathcal{Q}$ holds new traces; downscaling scales w as it scales h_i, and recall of either member also returns the other. A trace with at least n_{sch} links forms a schema node, which recall matches like a trace: the centroid of its own and its partners' embeddings, with their mean link weight as strength. Links and nodes count in S and are pruned as traces are, a deleted trace taking its links, and each trace keeps at most n_{link} links, the weakest going first, so their number grows linearly with the traces.

Pruning. The module then deletes every trace with $h_i < h_{\text{min}}$ and, while the stores' size S exceeds the budget B, the weakest trace outside $\mathcal{Q}$, oldest first among equals, until $S \le B$ or none remains outside $\mathcal{Q}$. S counts the bytes of the persisted records (embeddings and payloads); the operator sets B from available disk. Traces in $\mathcal{Q}$, at strength 1, escape floor and budget. Deletion happens only here, so the awake stores hold no trace below the floor, and between sleeps S can exceed B by the records stored since the last, about 12,000 traces per entity hour at the resting rate and at most 36,000 at the ceiling of one broadcast per tick. An unreplayed trace reaches the floor after about $\ln h_{\text{min}}/\ln \varrho$ entity days of storage at the resting rate, about 23 days with Table A1's values, so with a non-binding budget the stores settle at about $N_{\text{day}} \ln h_{\text{min}}/\ln \varrho$ traces, about 6.7 million. A preservation copies stores and strengths as they stand, so later pruning deletes nothing from a preserved entity. Each sleep records N_{new}, the factor, $|\mathcal{Q}|$, total strength before and after scaling, deletions at the floor and for the budget, and the final S.

Recall. Recall returns the requested number of traces with $\text{sim}_i > 0$ in decreasing order of $h_i\, \text{sim}_i$, where sim_i is the cosine similarity of the cue and trace embeddings. A short-term-buffer trace has strength 1 and ranks by similarity alone. Recall changes no strength.

A.11 Parameter values

Table A1. Parameter values. Status: "design" is part of the model's definition; "calibrated" is set offline by simulation or by the validation of A.7; "provisional" is a current setting, calibrated before the live runs and recorded with them; "operator" is chosen per installation. Times are on the entity clock ("entity"), in awake time ("awake", A.7), or wall-clock ("wall"). Empty cells mean no symbol or no unit.

Symbol	Meaning	Value	Units	Status
f_p	processing rate	10	Hz (entity)	design
f_0	resting broadcast rate	10/3	Hz (entity)	design
	entity seconds per wall-clock second	1		design

Preprint. Not peer-reviewed.

Symbol	Meaning	Value	Units	Status
B	maximum events read per stream per tick	100	events	design
K	coalition capacity	5	events	design
θ	access threshold	0.35		provisional
W_N	novelty window	32	candidates	design
G	goal factor (static)	1		design
γ_G	inactive drive-relevance goal attenuation	0.5		design
T_{min}, T_{max}	arousal level-gain floor, ceiling	0.2, 1.0		design
g_{max}	contrast gain at arousal 1	8.0		design
	coherence layer	off		design
κ_{min}, κ_{max}	coherence factor floor, ceiling (layer on)	0.8, 1.25		design
W_κ	coherence phase window (layer on)	10	ticks	design
π_{min}, π_{max}	workspace-feedback gain floor, ceiling (feedback off here)	0.8, 1.25		design
d_{conf}, r_{conf}, $\Delta\pi$, τ_π, Δ_{ref}, η_{td}	feedback conflict thresholds; gain step, relaxation, refractory; head rate	2, 2, 0.1, 10, 10, 0.001	none, none, none, s, s, none	design
$I^{\text{lo}}_{\text{Vis}}$, $I^{\text{hi}}_{\text{Vis}}$	vision intensity levels	0.2, 0.7		provisional
$I^{\text{lo}}_{\text{Aud}}$, $I^{\text{hi}}_{\text{Aud}}$	audition intensity levels	0.4, 0.8		provisional
$I^{\text{lo}}_{\text{Intero}}$, $I^{\text{hi}}_{\text{Intero}}$	interoception intensity levels	0.1, 0.7		provisional
$I^{\text{lo}}_{\text{Seq}}$, $I^{\text{hi}}_{\text{Seq}}$	sequence intensity levels	0.1, 0.7		provisional
$I^{\text{lo}}_{\text{Aff}}$, $I^{\text{hi}}_{\text{Aff}}$	affect intensity levels	0.1, 0.7		provisional
$I^{\text{lo}}_{\text{Sleep}}$, $I^{\text{hi}}_{\text{Sleep}}$	sleep intensity levels	0.5, 0.8		provisional
$I^{\text{lo}}_{\text{Lang}}$	language-organ utterance intensity	0.4		provisional
β_Γ	error ratio at which the graded map reaches alert level	2		design
W_P	running-ratio window (vision, audition, interoception, sequence)	32	reports	design
β_ν	prediction-error alert ratio (vision, audition)	2.0		design
β_c	change alert ratio (vision, audition)	2.0		design
$c^{\text{min}}_{\text{Vis}}$, $c^{\text{min}}_{\text{Aud}}$	absolute change floors	10^{-4}, 0.35		design
W_{buf}	forward-model input buffer (vision, audition)	16	reports	design
	forward-model hidden units (vision; audition)	256; 32	units	design
η_{fm}	forward-model learning rate (vision, audition, interoception, sequence)	10^{-3}		design
ω_{min}, ω_{max}	audition attended fraction at arousal 1, 0	0.15, 1.0		design
Δ_{att}	shortest attended span (audition)	0.025	s (entity)	design
	vision saliency grid	12 by 12	tiles	design
Θ_F	fovea hysteresis margin	0.15		design
F_{min}, F_{max}	fovea size at arousal 1, 0	0.12, 0.5	fraction of frame	design
α_F	fovea tile-statistics weight	0.05		design
n_F	tile updates before z-scoring	5	clip reports	design
k_F	tile deviation floor (fraction of mean tile change)	0.1		design
β^{Seq}_ν	sequence temporal-error alert ratio	3.0		design

Preprint. Not peer-reviewed.

Symbol	Meaning	Value	Units	Status
W_z	sequence hidden-state z-score window	64	broadcasts	design
W_{recur}	recurrence window	32	broadcasts	design
n_{recur}	recurrence count	4	states	design
Δ_{recur}	recurrence quantization step	0.25		design
$W_{\Delta t}$	sequence interval window	32	broadcasts	design
$s_{\max}$	timespan cap (interoception, sequence); entered-interval cap over window mean (sequence)	10		design
	reservoir units (interoception; sequence)	32; 32	units	design
	sequence forward prediction	on		design
I_0	phasic salience floor	0.5		design
τ_{ph}	phasic decay time	1.0	s (entity)	design
a_0	baseline arousal (affect, access rate)	0.3		design
	adaptive access rate	on		design
λ	arousal relaxation rate	0.05	s^{-1} (entity)	design
P_{Aff}	minimum affect-event interval; timer period	1.0	s (entity)	design
γ_a	perceptual-alert arousal gain	0.15		design
ν_{cap}	excess-error-ratio cap per alert	4.0		design
γ_{Intero}	arousal step per interoception hard-threshold report	0.05		design
τ_{f}, τ_{s}	fast, slow time constants (error means, alert rates)	10, 100	s (entity)	design
k_v	learning-progress gain (pleasantness check)	2.0		design
τ_v	valence time constant	30	s (entity)	design
lp_0	learning-progress noise floor	0.05		calibrated
m_B	alert-excess margin	0.5		calibrated
r_0	alert-rate floor	0.05	s^{-1} (entity)	design
α_{int}	intent-rate weight	0.05		design
β_D, δ_D, ρ_D	curiosity build, decay, relief	0.05, 0.0055, 0.5	s^{-1} (entity)	design
β_D, δ_D, ρ_D	boredom build, decay, relief	0.04, 0.0045, 0.3	s^{-1} (entity)	design
β_D, δ_D; ρ_D	social-drive build, decay; relief per interaction	0.01, 0.0011; 0.8	s^{-1} (entity); none	design
β_D, δ_D; ρ_D	restlessness build, decay; relief per intent	0.03, 0.0033; 0.5	s^{-1} (entity); none	design
θ_D	drive threshold (every drive)	0.7		design
Θ_D	drive re-arm fraction	0.9		design
Δ_{stall}, n_{goal}, Δ_{resp}, η_L	goal stall horizon, cap; response window, likelihood fall	600, 3, 10, 0.5	s (entity), goals, s (entity), none	design
θ_E, b_E, τ_E	emotion-regulation set point, tier-1 bias, its decay time	0.5, 0.2, 20	none, none, s (entity)	design
	initial held arousal $\hat{a}$	0.3		design
	wellness scaling: GPU temperature bounds; cycle-latency target	30 to 80; 300	°C; ms	design
P_{Intero}	interoception reading interval	1.0	s (entity)	design

Preprint. Not peer-reviewed.

Symbol	Meaning	Value	Units	Status
n_x	interoception feature dimension (three self-rhythm features, zero unless enabled; one is the highest GPU memory use)	8		design
τ_U	expected-error time constant	600	s (entity)	design
β_U	expected-error band	2.0		design
	hard thresholds: CPU, RAM, GPU temperature, GPU memory, cycle latency	90, 90, 83, 92, 600	%, %, °C, %, ms	design
θ_R	regulation threshold	0.5		provisional
Δ_R	regulation sustain window	30	s (entity)	design
n_{wu}, Δ_{wu}	warm-up end conditions	1000, 1200	updates, s (entity)	design
γ_f	processing-rate reduction factor	0.8		design
$f_p^{\min}$, $f_p^{\max}$	processing-rate bounds under regulation	0.5, 20	Hz (entity)	design
θ_{th}	think bar	0.45		provisional
θ_{sp}	speak (report) bar	0.6		provisional
Δ_{th}	think refractory interval	3.0	s (entity)	design
Δ_{sp}	speak refractory interval	8.0	s (entity)	design
Δ_{sig}	signature expiry	300	s (entity)	design
Δ_g	in-flight guard timeout	48	s (wall)	design
	interrupt bar	unset		design
f_r	self-rhythm step rate	20	Hz (entity)	design
n_s	Euler substeps per step	10		design
J_{rec}	recurrent weight	2.5		calibrated
Ξ_0	input offset	-0.25		calibrated
k_y	sigmoid slope scale	0.08		calibrated
τ_y	activity time constant	0.02	s (entity)	calibrated
γ_R	depression rate	8.0	s^{-1} (entity)	calibrated
γ_o, γ_u	own-drive, maternal-drive gains	0.02, 0.03		calibrated
σ_ξ	noise scale	0.02		calibrated
$\tau_{\text{rec}}^{(0)}$	initial recovery time	2.1	s (entity)	calibrated
$\tau_{\text{rec}}^{\min}$, $\tau_{\text{rec}}^{\max}$	recovery-time bounds	0.9, 2.3	s (entity)	calibrated
η_ℓ	frequency-adaptation rate	0.0025	s^{-1} (entity)	calibrated
τ_m	moving-average time constant	10	s (entity)	design
Δ_{amp}	phase and amplitude window	8	s (entity)	design
	initial activity y, resource R	0.05, 1.0		design
	maternal beat rate, drift	70, 0.03	bpm, none	design
$M_{\max}$	maximum maternal drive	0.4		design
c_M^{base}, c_M^{pert}	usual, perturbation drive scales	0.5, 0.75		design
f_g	readout sampling rate	10	Hz (entity)	design
f_{lo}, f_{hi}	entrainment band	0.3, 2.0	Hz (entity)	design
Δ_{trim}	edge trim	2.0	s (entity)	design
Δ_E	driven-window length	300	s (entity)	design
Δ_W, P_W	withdrawal duration, period	20, 1800	s (entity)	design
Δ_{pert}, P_{pert}	perturbation duration, period	5, 3600	s (entity)	design
j_P	probe jitter fraction	0.25		design
P_{ro}	readout period; settling time after boot or thaw	60	s (entity)	design
f_{guard}	pull guard	0.05	Hz (entity)	design

Preprint. Not peer-reviewed.

Symbol	Meaning	Value	Units	Status
pull_{min}	pull floor	0.5		calibrated
n_{base}	baseline withdrawals	3	count	design
	surrogate heartbeats	19	count	design
	consecutive passes required	3	count	calibrated
$t_{R0}, t_{R1}, t_{R2}, t_{R3}$	viability checkpoints	6, 24, 48, 60	h (awake)	calibrated
pull_{R1}, slope_{R1}	R1 bounds on median pull, slope	0.12, 0.002	none, h^{-1} (awake)	calibrated
pull_{R2}	R2 bound on median pull	0.3		calibrated
Δ_V, n_V	viability window, minimum points	12, 8	h (awake), withdrawals	calibrated
Δ_{per}	period-variability window	300	s (entity)	design
$V_{\text{per}}^{\text{min}}$	period-variability floor	0.2		provisional
$\text{err}_{\text{Vis}}^{\text{max}}$	vision error-ratio ceiling	0.3		provisional
$\Delta_{\text{max}}^{\text{rec}}$	return-to-baseline ceiling	30	s (entity)	provisional
tol_{rec}, $\Delta_{\text{cap}}^{\text{rec}}$	recovery tolerance, cap	0.25, 300	none, s (entity)	design
n_{sleep}, n_{cons}	required sleeps, consolidation passes	5, 3	counts	design
Δ_{awake}	minimum awake time	24	h (awake)	design
	gate cadence	60	s (entity)	design
Δ_{budget}	developmental-phase budget	96	h (wall)	design
$c_{\text{eff}}, n_{\text{cal}}$	minimum-effect multiple, paired pilot runs	0.5, 30	none, runs	design
n_{run}	runs per arm and tone variant	$\lceil 102/(1 - r_{\text{NE}}) \rceil$ planned, at least 102 entering each control's test and the tone variant's first test (A.8)	runs	design
q_{pow}	assumed P(dIG > minimum effect), power analysis	0.65		design
	power of each control's WIN test	0.9		design
T_{learn}, SNR_j, $\theta_{\text{PC}}/2$, n_{PC}, θ_{band}, b_{band}	learning period (each run, positive control); positive-control signal-to-noise ratio, minimum effect, minimum included reports; threshold-band half-width, bias-correction bandwidth	from the pilot runs (A.8)	s (entity), none, none, reports, none, none	design
v_j, μ_j	positive-control projection direction, mean	from a preliminary run (A.8)		design
	positive-control detection probabilities (informative, uninformative)	0.95, 0.05		design
	context-age bins (contrastive analysis); error-ratio bins (tone analysis)	quintiles, from the pilot runs (A.8)	s (entity); none	design
n_{side}	distinct scores per fitted side (contrast at threshold)	10	broadcasts	design

Preprint. Not peer-reviewed.

Symbol	Meaning	Value	Units	Status
$\kappa_{\max}$	largest condition number of a fitted side's weighted least-squares matrix	10^8		design
	minimum effects (contrast at threshold, tone analysis)	0.5 times the pilot standard deviation (A.8)		design
α_{test}	level of each live sign test	0.05		design
α_{FW}	family-wise level (offline suite)	0.05		design
tol_{CV}, n_{seed}	stability tolerance, seeds (offline suite, coherence-layer ablation)	0.05, 3	none, seeds	design
ϱ	strength an unreplayed trace keeps per entity day at the resting rate (A.10)	0.82		design
N_{day}	traces per entity day at the resting rate, $86\,400\,f_0$ (A.10)	288,000	traces	design
$h_{\min}$	strength pruning floor (A.10)	0.01		design
B	episodic-memory storage budget (A.10)	set by the operator	bytes	operator
n_{rep}, c_{aff}, c_{rec}	traces replayed per sleep; replay-score weights	5, 0.7, 0.3	traces, none, none	design
n_{pair}, $\text{sim}_{\min}$, sim_{dup}, n_{sch}, n_{link}	pairs co-replayed per sleep; similarity band; links forming a schema node, per trace	5, 0.5, 0.95, 3, 8	pairs, none, none, links, links	design

Reachability at resting arousal. With the values of Table A1, the level gain at resting arousal is 0.44 and the contrast gain is zero, so a candidate reaches the access threshold of 0.35 only when its priority is at least about 0.80. Only reports of the audition module at its alert level of 0.8 (acoustic alerts, non-neutral tones, and graded reports whose error has reached about twice its running mean) and a sleep summary with a failed phase can then lead an accessed broadcast; the alerts of the vision, interoception, sequence, and affect modules need arousal of about 0.37. Neither report bar is reachable at rest: an audition alert needs arousal of about 0.45 to reach the think bar and about 0.63 to reach the speak bar. A priority below about 0.43 never reaches access at any arousal, so the language organ's utterances, at 0.4, never lead an accessed broadcast.

Preprint. Not peer-reviewed.