

Temporal workflow versioning (demo example)

Demo context.

- workflow used is `MoneyTransfer` from [Temporal workflow example](#)
- in `MoneyTransfer` workflow, we do.
 - **withdrawal**. If withdrawal failed, we return error. If withdrawal succeeded, we proceed next
 - **deposit**. If deposit succeeded, workflow completed. If deposit failed, we refund**** for simplicity, both activities will always succeed**
- to demonstrate long running processes, I added.
 - 15s delay for withdrawal
 - 30s delay for deposit

Demo scenario (sequentially).

1. initial version of `MoneyTransfer` workflow without versioning.

workflow initiated → withdrawal is triggered → deposit is triggered → workflow completed

expected.

- withdrawal running on v0 (no versioning)
- deposit running on v0 (no versioning)

example code.

 [chore\(demo\): no versioning · willtpa/money-transfer-project-template-go@657b9ba](#)

in temporal ui.

 [\[workflowversioning\] no versioning](#)

2. change in withdrawal logic (deposit remains the same).

[before] withdrawal delay 15s ... v0 (DefaultVersion)

[after] withdrawal delay 10s ... v1

- created new activity for withdrawal v1 called `WithdrawV1` with delay reduced to 10s
- since this is withdrawal related logic change, I named changeID as "withdrawal-feature"

expected.

- withdrawal running on v1
- deposit running on v0 (no versioning)

example code.

 [chore\(demo\): withdraw v1 · willtpa/money-transfer-project-template-go@c33a292](#)

in temporal ui.

 [\[workflowversioning\]: withdraw v1](#)

3. again, change in withdrawal logic (deposit remains the same).

[before] withdrawal delay 10s ... v1

[after] withdrawal delay 5s ... v2

- created new activity for withdrawal v2 called `WithdrawV2` with delay reduced to 5s
- reuse changeID "withdrawal-feature"

expected.

- withdrawal running on v2
- deposit running on v0 (no versioning)

example code.

 `chore(demo): withdraw v2 · willtpa/money-transfer-project-template-go@156628b`

in temporal ui.

 `[workflowversioning]: withdraw v2`

4. next, change in deposit logic (withdrawal logic remains withdraw v2)

[before] deposit delay 30s ... v0 (DefaultVersion)

[after] deposit delay 20s ... v1

- created new activity for deposit v1 called `DepositV1` with delay reduced to 20s
- since this is deposit related logic change, I named changeID as "deposit-feature"

expected.

- withdrawal running on v2
- deposit running on v1

example code.

 `chore(demo): deposit v1 · willtpa/money-transfer-project-template-go@c16b851`

in temporal ui.

 `[workflowversioning]: deposit v1`

5. since now our `MoneyTransfer` workflow is running using withdrawal v2 & deposit v1, we can remove completely versioning code for withdrawal v0, withdrawal v1, and deposit v0

**** make sure you have no remaining withdrawal v0, withdrawal v1, and deposit v0 running**

expected.

- withdrawal running on v2
- deposit running on v1
- no more versioning for both withdrawal & deposit

example code.

 `chore(demo): running withdraw v2 & deposit v1, remove versionings · willtpa/money-transfer-project-template-go@ab91552`

in temporal ui.

 `[workflowversioning]: running withdraw v2, deposit v1, remove versioning for both`

6. next, change in `MoneyTransfer` workflow, we remove deposit completely.

[before] withdrawal v2 → deposit v1 → complete

[after] withdrawal v2 → complete

- created versioning for the workflow itself
- since this is workflow `MoneyTransfer` related change, I named changeID as "money-transfer-no-deposit"

expected.

workflow initiated → withdrawal (v2) is triggered → workflow completed

example code.

 chore(demo): money transfer without deposit · willtpa/money-transfer-project-template-go@baa6c34

in temporal ui.

 [workflowversioning]: money transfer without deposit