

To,
Mr. Vinay Kumar Sir
Plant location- BIHAR
Office Location- New Delhi

DATE	09-04-2026
QUOTE #	D-10320/2025
VALID UNTIL	09-06-2026

Capacity 5 Ton Per Hr
2 Shifts Per Day
Total Production 100 Ton Per Day
Raw Material: - Parali, Rice-
Husk, Baggase etc.

PROPOSAL FOR YULONG XGJ560+8th 160 KW PELLET MILL & HAMMER MILL GXP75*150

ALL CONTROL PANELS & VFD DRIVES WILL BE PROVIDED BY US WITH THE MACHINES.

YULONG MACHINE PANELS ARE OF CHINT COMPANY.

DUST COLLECTOR BAGS OF HAMMER MILL ARE INCLUDED IN QUOTATION.(YULONG)

PRICE LIST

SR.NO	PRODUCT DESCRIPTION	MAKE IN	QTY/UNIT	PRICE/UNIT	TOTAL AMOUNT
SECTION-A PELLETING SECTION (YULONG)					
1.	PELLET MACHINE 160 KW	YULONG XGJ560+8 TH	3	₹ 31,50,000	₹ 94,50,000
2.	PELLET MACHINE INPUT CONVEYOR - Screw Conveyor, Covered - Make In - Ms - Length- 20 Ft - Width- 2 Ft - Height- 10 Ft	INDIAN	3	₹ 2,50,000	₹ 7,50,000
SECTION-B HAMMER MILL SECTION (YULONG)					
3.	HAMMER MILL(MAIN POWER 160 KW) (TOTAL POWER 216 KW)	YULONG GXP75*150	2	₹ 36,00,000	₹ 72,00,000
4.	HAMMER MACHINE INPUT CONVEYOR - Belt Conveyor - Make In - Ms - Length- 22 Ft - Width- 2 Ft - Height- 10 Ft	INDIAN	2	₹ 2,50,000	₹ 5,00,000
SECTION-C TRIPPLE PASS RIBBON MIXER (INDIAN)					
5.	TRIPPLE PASS RIBBON MIXER	INDIAN	1	₹ 12,00,000	₹ 12,00,000
SECTION-D DOUBLE SHAFT SHREEDER SECTION (INDIAN)					
6.	DOUBLE SHAFT SHREDDER Fully Automatic Advanced Control Panels with VFD, safety Sensor, control, Switchgears, Amp meter, Voltmeter, overload sensor, turndown as per requirements of & control as per requirements. Stairs/ladder, Machine Operational / Maintenance Manual, Machine Tool Kit	INDIAN	1	₹ 40,00,000	₹ 40,00,000
7.	DOUBLE SHAFT SHREDDER INPUT CONVEYOR - Length :- 12 Mtr - Belt Width :- 1 Mtr 3ply:- 8mm	INDIAN	1	₹ 3,00,000	₹ 3,00,000

GATTUWALA GROUP

8.	DOUBLE SHAFT SHREDDER OUTPUT CONVEYOR - Length :- 10 Mtr - Blet Width :- 800 Mm 3ply:-8mm - Chevron	INDIAN	1	₹ 2,00,000	₹ 2,00,000
----	--	--------	---	------------	------------

SECTION-E AUTOFEEDER SECTION (INDIAN)					
9.	AUTOFEEDER MACHINE - Length :- 27 Ft. - Width :- 5.3 Ft. - Height :-10.4 Ft - Make In :- Ms - Sheet Thickness:- 3mm	INDIAN	1	₹ 7,95,000	₹ 7,95,000
10.	AUTOFEEDER MACHINE STAND	INDIAN	1	₹ 2,00,000	₹ 2,00,000
SECTION-F COOLING & INSTALLATION SECTION					
11.	COOLING BELT CONVEYOR 25 FT WITH 3HP MOTOR & GEAR BOX	INDIAN	1	₹ 2,25,000	₹ 2,25,000
12.	SIEVER WITH MOTOR	INDIAN	1	₹ 1,70,000	₹ 1,70,000
13.	INSTALLATION AND TRAINING ERECTION & COMMISSION			₹ 2,00,000	₹ 2,00,000
14.	ELECTRICAL CONTROL CABINET (PUSH START/STOP BUTTON)			₹ 2,50,000	₹ 2,50,000
	TRANSPORTATION				EXTRA
	ONE YEAR WARRANTY AND SERVICE				INCLUDED
	TOTAL				₹ 2,54,40,000
NOTE: THE RATES PROVIDE ARE EXCLUSIVE OF GST. G S T @ 18 % A P P L I C A B L E .					

istara

E N E R G I E S

MODEL	SPECIFICATIONS	PHOTOS
XGJ560+8th-160 KW	- POWER:160KW - VERTICAL RING DIE PELLET MACHINE - MOULD: RING DIE 6-8-10 MM - MAIN MOTOR: 160+2.2+0.55+0.25+0.15+1.5 KW - OUTPUT (KG/H): 2000-2500 KG/H - VOLTAGE: 3 PHASES, 415V, 50HZ - DIMENSION(L*W*H): 2330X1580X1780MM - WEIGHT: 5.3 TON THE COMPOSITION OF THE PELLET MACHINE - THE WOOD PELLET MACHINE IS MAINLY COMPOSED OF FOUR PARTS: PELLET MILL, THE LUBRICATING OIL PUMP, THE DUST REMOVAL AND THE ELECTRIC CONTROL CABINET. - THE POWER IS 160KW, CAPACITY IS 2-2.5 TONS/HR. THE MOTOR IS DIRECTLY CONNECTED TO THE GEAR BOX TO INCREASE THE CONVERSION RATE OF KINETIC ENERGY AND IMPROVE PRODUCTION EFFICIENCY. - PRICE CONTAIN PELLET MACHINE WITH ELECTRIC MOTOR, LUBRICATION PUMP, FAN TO COOL LUBRICATION OIL, CHINESE ELECTRIC CONTROL CABINET WITH SOFT START.	 

TECHNICAL ADVANTAGES OF PELLET MACHINE GEARBOX

THE GEAR BOX ADOPTS THREE-STAGE GEAR DECELERATION, THE CARRYING CAPACITY IS 5 TIMES LARGER THAN THE OLD MODEL, AND THE SERVICE LIFE IS SUPER LONG. THE BEARINGS OF GEAR SHAFTS ARE ADJUSTABLE STRUCTURE. THE BEARING CAN BE ADJUSTED WITHOUT UNLOADING THE MACHINE AFTER LONG-TERM RUNNING OF WEAR. THE GEARBOX COMES WITH A LUBRICATING COOLING SYSTEM, IT CAN COOL DOWN THE LUBRICATING OIL WITHOUT STOPPING THE MACHINE TO ENSURE LONG-TERM OPERATION. THE GEARBOX LUBRICATION SYSTEM IS EQUIPPED WITH FLOW DETECTION AND OVER-PRESSURE PROTECTION, WHICH CAN PREVENT EQUIPMENT FAILURES CAUSED BY POOR LUBRICATION EFFECTIVELY.

NEW FEED SYSTEM

THE EXTERNAL SETTING OF THE MATERIAL DIAL COMPLETELY SOLVES THE PROBLEM THAT THE DIAL MATERIAL SYSTEM IS EASILY CORRODED BY HIGH TEMPERATURE STEAM. IT IS A MAJOR INNOVATION OF THE EIGHTH GENERATION WOOD PELLET MACHINE. IN THE MATERIAL SHIFTING COVER, EXCEPT FOR THE MATERIAL SHIFTING TURNTABLE, OTHER NON-MOVING PARTS IN CONTACT WITH MATERIALS AND STEAM ARE ALL MADE OF STAINLESS STEEL, WHICH SOLVES THE CORROSION PROBLEM OF METAL MATERIALS FUNDAMENTALLY.

NOTE:

THE PROVISION OF LUBRICANTS SUCH AS ELECTRIC CABLES OIL AND GREASE FOR THE PELLET MACHINE IS THE RESPONSIBILITY OF THE BUYER, WHO IS EXPECTED TO HAVE THEM READILY AVAILABLE AT THE TIME OF INSTALLATION.

HAMMER MACHINE



NO	NAME	MODEL	POWER (KW)	TOTAL POWER (KW)	QTY	NOTES
101	HAMMER MILL	GXP75*150	160+5.5	165.5	1	MAIN POWER:165.5 KW CAPACITY: 3-4T/H WOOD CHIPS LENGTH AND WIDTH< 50MM, THICKNESS < 5MM, AND MOISTURE < 20% NO OF BLADE: 126 SIEVE HOLE DIAMETER: Φ14-16
	AIR FAN	CM-8C	45	45		
	CYCLONE	Φ180	/	/		SUITABLE FOR STRAW AND OTHER FIBER MATERIALS, AND MOISTURE SHOULD <20% THE ASSEMBLE PLATFORM OF THE HAMMER MILL MOTOR BASE AND THE ASSEMBLY PLATFORM OF THE ROTOR SPINDLE BEARING SEAT ARE PROCESSED SYNCHRONOUSLY AT ONE TIME TO ENSURE THE HORIZONTAL ACCURACY: THE ROTOR, THE MAIN COMPONENT, HAS UNDERGONE A DYNAMIC BALANCE CHECK BEFORE ASSEMBLY, THUS ENSURING THE SMOOTH OPERATION OF THE MACHINE. THE AIR FAN IS INDEPENDENTLY PRODUCED BY YULONG. THE FAN BLADES ARE WELDED WITH THICKER AND WEAR-RESISTANT MATERIALS.THE DYNAMIC BALANCE IS CHECKED AND THE USE IS STABLE.
	AIR LOCK	700	5.5	5.5		
	PIPE	Φ426*7M	/	/		
	BAGS DUST COLLECTOR	180 HOLES				
	ELECTRIC CONTROL CABINET					
	TOTAL			216		PLC CONTROL WITH TOUCH SCREEN, SOFT START THE MACHINE
	TOTAL POWER(KW)			216		

TRIPPLE PASS RIBBON MIXER

SPECIFICATIONS OF MIXER

- Length 15 ft
- Height 7.8 ft
- Width 2.8 ft
- Motor 8 KW (Crompton)
- Gear Box Elecon

Double Shaft Shredder



Double Shaft Shredder Model GTW- 150 HP

Model No	GTW-150
Material to crushed	Paddy Straw & Sugar Cane leaves
Production capacity	5.0 to 5.5 TPH
Shredding machine type	Double-shaft shredder machine
Input material	Paddy Straw & Sugar Cane leaves
Output material size (95%)	20 mm -40 mm
Inlet-size cutting chamber	900 mm x 500 mm
Liner	C45
CONSTRUCTION OF MACHINE	
Main body	Fabricated MS plate
Feeding hopper	3.5 mm including in-machine
Feeding hopper Size	1800mm x 1200mm
Machine Frame & Stand	C250x75 ISI Mark
Channel Make	Jindal, Sail India, Tata Steel
Body chassis	Mild steel structure Mig welded use of c-type
Motor	
Motor	75 HP+ 75 HP Rpm 1440 (2Nos) 415 V
Motor Make	IE-3 CG
Number of motors	02 no's
Gear Box	
No of Gearbox	02 No's
Gear Box Type	Helical
Gear Box Make	Elecon
Gear oil	VG320 no.
Bearing	
Bearing	FAG
No of Bearing	4 No's

Bearing Chassis	Forged Mild Steel IS2062
Shaft	
Shaft Diameter coupling	300 mm
No's of shaft (roller)	02 no's
Shaft Type	Hexagon
Shaft Material	EN 24
Nut bolt & Seals	
Nut bolt	Pooja Forge / TV's
Safety Seal	Dust Control Seals
Cutter & Spacer	
Cutter thickness	15mm
Spacer	16mm thickness
Cutting Chamber	Universal design
Cutter	Tool steel (60 HRC)
No. of teeth	17
Cleaners	Tool steel
Control Panel	
Panel Type	Fully Automatic
Overload sensor	Inbuilt
Switchgear	Inbuilt
Amp meter	Inbuilt
Voltmeter	Inbuilt
safety Sensor	Inbuilt
PLC	Inbuilt
VFD	Inbuilt
VFDMAKE	SCHNEIDER
Machine Safety	
Safety covers over all movable parts	Yes / Provided
Emergency Stop	Yes / Provided
Auto Reverse Function	Yes / Provided
Overload Function	Yes / Provided

AUTOMATIC FEEDING UNIT



Type		Flat Belt
Quantity		1
Operating Capacity	TPH	up to 6.0
Belt Width	mm	1500
Troughing Angle	Deg	NA
Belt Speed	m/sec	DDE
Inclination	Deg	0
Horizontal Length C/c	m	7.5 Approx.
Lift	m	0
Take up		Screw
No. of feed & Discharge Points	Nos	1
Head Pulley		273 dia x 1500 mm x 12 mm thickness (Rubberised)
Tail Pulley		219 dia x 1500 mm x 10 mm thickness
Impact Idlers		Provided
Carrying Idlers		NA
Return Idlers		Provided
Coupling		EN8 Sleeve Type
Drive Motor		
Motor Type/Class		4 Pole Squirrel Cage type TEFC
Motor Power	HP	1.0 (With VFD)
Gear Box		Planetary
Service Factor		1.4
Belt		
Rating /Nos of PLY		315 / 3
Belt Width	mm	1500
Top Cover	mm	3

Bottom Cover	Mm	1.5
Grade		M24
Safety Switches		
Pull cord Switch		NA
Emergency Stop		Provided
Reverse/Forward Switch		Provided
Belt Scraper / Cleaner		
Type		V-Type, 01 NOS
Structure		
Skirt Board Type		Segmented
Plate MOC / Thk	mm	Front Gate -1.6/MS, Side-3/MS, Back Side - 2/MS
Length of skirt Provided	mm	Throughout the length
Rubber Thk for Skirt Board	mm	6
Height of Skirt Board	mm	1250
Stringer/Short Supports Size		ISMC 100
Support Spacing	mm	DDE
Hood Cover		NA
MS Gantry, Walkways		NA
Discharge Chute		NA
Push Roller		
Motor		1.0 HP
Gear Box		Planetary
Service Factor		1.7

TERMS & CONDITIONS

- **20% advance against the Purchase order.**
- **20% after 15 days**
- **40% at the time of intimation of dispatch from China (With Proof)**
- **20% Before Delivery.**

WARRANTY T & C:

- 1 YEAR WARRANTY FOR GENUINE (VISTARA ENERGIES PRIVATE LIMITED.) MACHINE PART/S ONLY FOR MANUFACTURING DEFECT. TRANSPORTATION AND LABOUR COST FOR THOSE PARTS WOULD BE ON BUYER SIDE.
- FORCE MAJEURE CLAUSE APPLICABLE.
- ANY TYPE OF MISUSE/MISHANDLING/ACCIDENT DOES NOT ENTITLE TO WARRANTY/MAKE ANY SUE.
- AFTER ANY REQUEST FOR PROVIDING SPARE PART/S OR REPAIRING FROM LOCAL MARKET NEAR THE BUYER, VISTARA ENERGIES PRIVATE LIMITED WOULD NOT HOLD THE WARRANTY OF THAT PART/S OR ANY DAMAGE OCCURRING DUE TO THAT PART/S.
- WARRANTY IS NOT APPLICABLE ON REGULAR WEARABLE PARTS LIKE DIES, ROLLER SHELLS, BEARINGS, OIL SEAL, SHAFT, FABRICATED PART ETC.
- ESPECIALLY FOR VERTICAL RING DIE PELLET MACHINE - OUR WARRANTY IS APPLICABLE ON OUR STANDARD PRODUCT MAIN MOTOR AND MAIN GEARBOX ONLY. REST ALL THE PARTS ARE OUTSIDE OF OUR SCOPE OF WARRANTY.
- MOTOR, GEARBOX & PANEL WARRANTY ACCORDING TO THE CONCERN SUPPLIER COMPANY POLICY.
- ANY MODIFICATION OR USE OF PARTS OTHER THAN GENUINE PARTS WITHOUT WRITTEN PERMISSION OF VISTARA, WILL FREE VISTARA FROM WARRANTY. THE PRODUCTION CAPACITY OF THE WHOLE LINE IS CONSIDERED UNDER STANDARD CONDITIONS OF PLACE, POWER SUPPLY, OPERATOR SKILL, RAW MATERIAL TYPE. DURING THE BREAKDOWN PERIOD, VISTARA BEARS NO RESPONSIBILITY FOR ANY LOSS OF PRODUCTION, REVENUE, ETC.
- VISTARA WILL NOT BE LIABLE IF ANY INJURY TAKES PLACE AT THE WORKING SITE DUE TO NEGLECTING THE SAFETY STANDARD OPERATING PROCEDURES.
- IF ANY MANUFACTURING FAULT IS NOTICED DURING THE WARRANTY PERIOD, THEN THE COMPANY WILL REPAIR THE DEFECTIVE PART FREE OF COST, BUT THE CLIENT MUST PAY THE TRANSPORTATION CHARGES OF SUCH PART. THE CLIENT SHOULD INFORM WITHIN 2 WORKING DAYS FROM THE TIME OF THE NOTICEABLE DEFECT.
- IF THE INSTALLATION AND COMMISSIONING OF THE MACHINERY TAKE PLACE WITHOUT THE PRESENCE OF VISTARA STAFF, THEN VISTARA WILL BE FREE FROM ANY TYPE OF PRODUCT LIABILITY AND WARRANTY/OBLIGATIONS
- OUR STAFF WILL GUIDE THE COMMISSIONING PROCESS ONLY, THERE MUST BE 4-6 TRAINED PERSONS STAFF FROM BUYER SIDE FOR WORKING ON INSTALLATION AND OPERATION, OTHERWISE WE ARE NOT BOUND TO INSTALL THE MACHINE.
- BUYER'S TRAINED OPERATOR MUST BE AVAILABLE AT THE TIME OF INSTALLATION AND COMMISSIONING. THAT OPERATOR MUST KNOW ALL THE OPERATING METHODS AND PROBLEM SOLUTIONS THAT OCCURS IN THIS INDUSTRY OFTENLY. ESPECIALLY HE MUST BE SKILLED IN OPERATING AND MAINTAINING THE VERTICAL RING DIE PELLET MACHINE. IF BUYER DOESN'T HAVE ANY PROPER AND SKILLED OPERATOR, THERE WILL BE NO WARRANTY FROM VISTARA FOR ANY MISHANDLING AND FAULT DURING OPERATION.
- VISTARA IS NOT RESPONSIBLE FOR ACCIDENTS HAPPENING AFTER GOODS LOADED TRUCK LEFT VISTARA PREMISES.
- DEFECTS IN ANY OF THE MOTORS - DUE TO HIGH VOLTAGE, LOW PHASE, MISCONNECTIONS, OVERLOADING, SPARKING, ELECTRIC FLUCTUATION ETC. ARE FROM BUYERS SIDE AND VISTARA DOES NOT HOLD ANY GUARANTEE FOR IT

COMPULSORY SCOPE OF WORK FROM BUYER SIDE:

- ELECTRIC CONNECTION TO THE PANEL SPOT MUST BE PROVIDED BEFORE OUR SUPERVISOR COMES THERE.
- OIL AND WATER CONNECTION WITH SUPPLY MUST BE COMPLETE UP TO MACHINE FOUNDATION BEFORE FITTING STARTS.
- ANY TYPE OF FOUNDATION WORK OR CIVIL WORK AT THE SITE MUST BE DONE BY BUYER TIMELY, IF THESE TYPE OF WORK WILL TAKE MORE TIME THEN OUR TEAM'S STAY AT THE SITE WILL BE CHARGEABLE.
- COMPULSORY SHED WITH PROPER FLOORING, OVERHEAD AND UNDER HEAD WATER TANK IS REQUIRED BEFORE STARTING OFFITTING OF ANY MACHINE.
- BRICK WORK OF THE FOUNDATION SHOULD BE COMPLETE. (AS PER THE DRAWING PROVIDED BY US ONLY).
- 3 HELPERS AND 1 MACHINE OPERATOR MUST BE AVAILABLE AT THE SITE AND FOLLOW AS OUR SUPERVISOR'S INSTRUCTIONS IN ORDER TO TRAIN THEM IN FITTING AND OPERATING PROCESS.
- OUR TEAM WILL JUST GUIDE FOR FITTING AND CONNECTIONS, REST ALL TASKS WILL BE DONE BY YOUR LABOR.

BANK DETAILS

COMPANY NAME	VISTARA ENERGIES PRIVATE LIMITED
BANK NAME	YES BANK
A/C NO.	107827000000407
IFSC CODE	YESB0001078
BRANCH	WEST PATEL NAGAR
SIGN & STAMP.	