

```

%===== findTemplate =====
%
% A script to find the location of a template object within a given image
% when some approxiamte location is known.
%
%===== findTemplate =====

%==[1] Perform a little smoothing of the image to aid the gradient descent.
%           It is good to also smooth the template a little bit. The image
%           should be smoothed noticeably, while the template just a bit.
%

% Choose template and image
I = I3;
t = templ;
pos = [620,790]; % Initial guess of position.

tI = imgaussfilt(t,2); % Filter template a little bit.
fI = imgaussfilt(I,5); % Filter image some.

tnsq = sqrt(sumsqr(tI)); % Compute "magnitude" of the template.
% Useful to incorporate into c.

c = 1/(30*tnsq); % Step adjustment factor.

nsteps = 200; % Number of steps in the gradient descent.

I_name = 'I3';
t_name = 'templ';
fprintf('Image: %s\n',I_name);
fprintf('Template: %s\n',t_name);
fprintf('Parameters:\n');
fprintf(' (c=%f,nsteps=%d,pos=[%d,%d])\n',c,nsteps,pos(1),pos(2));

%==[2] Plot the template and the image.

figure(3);
imshow(tI);
title(sprintf('Template:%s', t_name));
hold on;
plot( size(tI,2)/2, size(tI,1)/2, 'r+');
hold off;
% Placed a plus at the template center.

figure(2);
imagesc(I);
colormap('Gray');
title(sprintf('Image:%s',I_name));
hold on;
plot(pos(1), pos(2), 'go');

for ii=1:nsteps
    dpos = gradTempMatch(double(tI), double(fI), pos);
    pos = pos - c.*dpos;
    plot(pos(1), pos(2), 'r. ');
    drawnow;
end

plot(pos(1), pos(2), 'rx');
fprintf('Final Point:[%f,%f]\n',pos(1),pos(2));

```

Image: I3  
Template: templ  
Parameters:  
(c=0.000025,nsteps=200,pos=[620,790])  
Final Point:[676.103055,809.589928]

Template:templ



Image:I3

