



Plan

- Ch1 – Overview of System Design Using SystemC
- Ch2 – Overview of SystemC
- Ch3 – Data Types
- Ch4 – Modules
- Ch5 – Notion of Time
- Ch6 – Concurrency
- Ch7 – Predefined Channels
- Ch8 – Structure
- Ch9 – Communication
- **Ch10 – Custom Channels and Data**
- Ch11 – Transaction Level Modeling



Custom Channels and Data

- **Custom Primitive Channel**
- Custom Data Type
- Custom Hierarchical Channel
- Adaptor / Transactor

Predefined Primitive Channels (Mutexs, FIFOs, Signals)			
Simulation Kernel	Threads & Methods	Channels & Interfaces	Data types Logic, Integers, Fixed point
	Events, Sensitivity & Notification	Modules & Hierarchy	




Review of Interface & Channels

- Interface
 - makes a channel usable with ports
 - enables the separation of communication from processing
- Primitive Channel
 - inherits from `sc_prim_channel` (Chapter 7)
 - no hierarchy, no port
 - no SC_METHODs or SC_THREADS
 - ability to implement the evaluate-update paradigm
 - simple and fast communications
 - built-in channel (`sc_fifo`, `sc_mutex`, `sc_semaphore`, `sc_signal`)
- Hierarchical Channel
 - inherits from `sc_channel`
 - accesses ports
 - contains process(es), hierarchy
 - complex communications buses (PCI, AMBA AXI ...)
- Channels are important
 - suitable channels enable safe communication between processes
 - channels with ports clarify the relationships of communication from processing




Custom Primitive Channel

- Problem : connect an event or interrupt between 2 modules
 - OK for 2 processes ... (Chapter 6 – Concurrency)
 - side effect : we can use `sc_signal<bool>` !



Interrupt Example Define Primitive Channel




Copyright © F. Muller
2005-2010

Custom Channels and Data



Ch10 - 5 -

Interrupt Example Modules



Copyright © F. Muller
2005-2010

Custom Channels and Data



Ch10 - 6 -

Interrupt Example Simulation

test_interrupt.h

```
#include <systemc.h>
#include "processor.h"
#include "peripheral.h"
#include "my_interrupt.h"
#include "my_interrupt_in_if.h"
#include "my_interrupt_out_if.h"
```

```
SC_MODULE(test_interrupt)
{
    my_interrupt* irq;
    processor* processor_i;
    peripheral* peripheral_i;

    SC_HAS_PROCESS(test_interrupt);
    test_interrupt(sc_module_name nm);
};
```

test_interrupt.cpp

```
#include "test_interrupt.h"

test_interrupt::test_interrupt(sc_module_name nm)
{
    irq = new my_interrupt();
    processor_i = new processor("processor_i");
    peripheral_i = new peripheral("peripheral_i");
    processor_i->irq(*irq);
    peripheral_i->irq(*irq);
}
```

my_interrupt

main.cpp

```
#include <systemc.h>
#include "test_interrupt.h"

int sc_main(int argc, char* argv[])
{
    cout << "INFO: Elaborating " << endl;
    test_interrupt interrupt_i("interrupt_i");
    cout << "INFO: Simulating " << endl;
    sc_start();
    cout << "INFO: Post-processing " << endl;

    return 0;
}
```

```
INFO: Elaborating
INFO: Simulating
interrupt_i.peripheral_i : Sending IRQ event at 1 ns
interrupt_i.processor_i : Received IRQ event at 1 ns
interrupt_i.peripheral_i : Sending IRQ event at 6 ns
interrupt_i.processor_i : Received IRQ event at 6 ns
interrupt_i.peripheral_i : Sending IRQ event at 11 ns
interrupt_i.processor_i : Received IRQ event at 11 ns
interrupt_i.peripheral_i : Sending IRQ event at 16 ns
interrupt_i.processor_i : Received IRQ event at 16 ns
interrupt_i.peripheral_i : Sending IRQ event at 21 ns
interrupt_i.processor_i : Received IRQ event at 21 ns
INFO: Post-processing
```





Custom Channels and Data

- Custom Primitive Channel
- Custom Data Type
- Custom Hierarchical Channel
- Adaptor / Transactor


Predefined Primitive Channels (Mutexs, FIFOs, Signals)			
Simulation Kernel	Threads & Methods	Channels & Interfaces	Data types Logic, Integers, Fixed point
	Events, Sensitivity & Notification	Modules & Hierarchy	

PCIX Bus Example Model

- Transmit a packet on the PCI-X Bus



SystemC Model



Copyright © F. Muller
2005-2010



Custom Channels and Data



Ch10 - 9 -

PCIX Bus Example Structure Declaration (Header File)

pcix_trans.h

```

struct pcix_trans
{
    int devnum;
    int addr;
    int attr1;
    int attr2;
    int cmdnd;
    int data[8];
    bool done;

    // Constructors
    pcix_trans()
        : devnum(-1), addr(-1), cmdnd(-1),
          attr1(-1), attr2(-1), done(false)
    {
        for (unsigned i=0; i!=8; i++) data[i] = 0;
    }

    pcix_trans(int _devnum, int _addr,
               int _attr1, int _attr2, int _cmdnd, int* _data,
               int _done)
        : devnum(_devnum), addr(_addr), cmdnd(_cmdnd),
          attr1(_attr1), attr2(_attr2), done(_done)
    {
        for (unsigned i=0; i!=8; i++) data[i] = _data[i];
    }
}

// Required by sc_signal<> and sc_fifo<>
pcix_trans& operator= (const pcix_trans& rhs);

// Required by sc_signal<>
bool operator== (const pcix_trans& rhs) const;
};

// Stream operator to output a PCIX transaction packet to terminal
ostream& operator<<(ostream& file, const pcix_trans& trans);

// Trace a PCIX transaction packet in case it is used in an sc_signal
void sc_trace(sc_trace_file* tf, const pcix_trans& trans, sc_string nm);
    
```

Copyright © F. Muller
2005-2010



Custom Channels and Data



Ch10 - 10 -



PCIX Bus Example Structure Declaration (Body File)



```
/****** Member Functions *****/
// Required by sc_signal<> and sc_fifo<>
pcix_trans& pcix_trans::operator=(const pcix_trans& rhs)
{
    devnum = rhs.devnum;
    addr = rhs.addr;
    attr1 = rhs.attr1;
    attr2 = rhs.attr2;
    cmdnd = rhs.cmdnd;
    for (unsigned i=0; i<8; i++)
        data[i] = rhs.data[i];
    done = rhs.done;
    return *this;
}

// Required by sc_signal<>
bool pcix_trans::operator==(const pcix_trans& rhs) const
{
    return (
        devnum == rhs.devnum && addr == rhs.addr &&
        attr1 == rhs.attr1 && attr2 == rhs.attr2 &&
        cmdnd == rhs.cmdnd && data[0] == rhs.data[0] &&
        data[1] == rhs.data[1] && data[2] == rhs.data[2] &&
        data[3] == rhs.data[3] && data[4] == rhs.data[4] &&
        data[5] == rhs.data[5] && data[6] == rhs.data[6] &&
        data[7] == rhs.data[7] && done == rhs.done
    );
}

/****** Non-Member Functions *****/
// Print a PCIX transaction packet out to a stream (usually just the terminal
// window), in a nice-looking format
ostream& operator<<(ostream& os, const pcix_trans& trans)
{
    os << "[" << endl
        << "cmdnd: " << trans.cmdnd << ", "
        << "attr1:" << trans.attr1 << ", "
        << " " << trans.data[4] << " "
        << " " << endl
        << "done:" << (trans.done?"true":"false") << endl
        << "];"
    return os;
}

// trace function, only required if actually used
void sc_trace(sc_trace_file* tf, const pcix_trans& trans, sc_string nm)
{
    sc_trace(tf, trans.devnum, nm + ".devnum");
    sc_trace(tf, trans.addr, nm + ".addr");
    sc_trace(tf, trans.attr1, nm + ".attr1");
    sc_trace(tf, trans.attr2, nm + ".attr2");
    sc_trace(tf, trans.cmdnd, nm + ".cmdnd");
    sc_trace(tf, trans.data[0], nm + ".data[0]");
    ...
    sc_trace(tf, trans.data[7], nm + ".data[7]");
    sc_trace(tf, trans.done, nm + ".done");
}
```

Copyright © F. Muller
2005-2010



Custom Channels and Data



Ch10 - 11 -



PCIX Bus Example Simulation




```
SC_MODULE(pcix)
{
    sc_signal<pcix_trans> pcix_sig;
    sc_fifo<pcix_trans> pcix_fifo;

    SC_CTOR(pcix)
    {
        SC_THREAD(send_pcix_packet_thread);
        SC_METHOD(receive_pcix_packet_method);
        sensitive << pcix_sig;
        dont_initialize();
    }

    void send_pcix_packet_thread(void);
    void receive_pcix_packet_method(void);
};
```

pci_datatype

Wave of Signal



Elaborating ...
Simulating ...
0 ns New PCIX transaction {
cmdnd: 19169, attr1:6334, attr2:26500,
devnum:41, addr:18467,
data: 11478.26962.0.0.0.0.0.0,
done:false
}
2 ns New PCIX transaction {
cmdnd: 9961, attr1:23281, attr2:16827,
devnum:5705, addr:28145,
data: 2995.4827.32391.3902.0.0.0.0,
done:false
}
4 ns New PCIX transaction {
cmdnd: 19718, attr1:17421, attr2:18716,
devnum:292, addr:12382,
data: 5447.14771.0.0.0.0.0.0,
done:false
}
6 ns New PCIX transaction {
cmdnd: 17035, attr1:25667, attr2:26299,
devnum:1869, addr:19912,
data: 28703.31322.17673.0.0.0.0.0.0,
done:false
}
8 ns New PCIX transaction {
cmdnd: 25547, attr1:28253, attr2:6868,
devnum:15141, addr:7711,
data: 32662.20037.8723.27529.0.0.0.0,
done:false
}
...

Copyright © F. Muller
2005-2010



Custom Channels and Data



Ch10 - 12 -

Custom Channels and Data

- Custom Primitive Channel
- Custom Data Type
- Custom Hierarchical Channel
- Adaptor / Transactor

Predefined Primitive Channels (Mutexs, FIFOs, Signals)			
Simulation Kernel	Threads & Methods	Channels & Interfaces	Data types Logic, Integers, Fixed point
	Events, Sensitivity & Notification	Modules & Hierarchy	


Copyright © F. Muller
2005-2010



Ch10 - 13 -

Hierarchical Channel

- To model complex buses
- inherit from `sc_channel`
 - `sc_channel` is just a `sc_module`
- Body of `sc_channel`
 - Ports
 - Member channel instances (sub-channel)
 - Member data instance
 - Constructor
 - Destructor
 - Process member functions (processes)
 - Helper functions



```
struct generator : public sc_channel, public generator_if
{
    ...
};
```

Copyright © F. Muller
2005-2010




Custom Channels and Data



Ch10 - 14 -

Example : Generator Channel Declaration




Copyright © F. Muller
2005-2010

 Custom Channels and Data



Ch10 - 15 -

Example : Generator Channel Simulation



Copyright © F. Muller
2005-2010

 Custom Channels and Data



Ch10 - 16 -

Custom Channels and Data

- Custom Primitive Channel
- Custom Data Type
- Custom Hierarchical Channel
- **Adaptor / Transactor**

Predefined Primitive Channels (Mutexs, FIFOs, Signals)			
Simulation Kernel	Threads & Methods	Channels & Interfaces	Data types Logic, Integers, Fixed point
	Events, Sensitivity & Notification	Modules & Hierarchy	


Copyright © F. Muller
2005-2010



Ch10 - 17 -

Adaptator

- Custom Primitive Channel (`sc_prim_channel`)
- Translates between modules with different interfaces
- Moving between different abstractions
 - communication at the TLM Level
 - communication at the RTL Level (Pin accurate level)



Copyright © F. Muller
2005-2010


Custom Channels and Data



Ch10 - 18 -

Transactor

- Custom Hierarchical Channel (sc_channel)
- Translates between modules with different interfaces
- Moving between different abstractions
 - testbench at the TLM Level
 - memory IP at the RTL Level (Pin accurate level)



Copyright © F. Muller
2005-2010


Custom Channels and Data



Ch10 - 19 -

Exercise

■ PCIX Bus



Copyright © F. Muller
2005-2010

Custom Channels and Data



Ch10 - 20 -