

20W Embedded Wireless Charging Module

Furniture-integrated wireless charging transmitter with dedicated AC/DC power adapter



Integrated wireless power for furniture and equipment

A compact round charging transmitter supplied with a dedicated AC/DC adapter, designed for installation in desks, tables, counters and other embedded charging applications.

Specification derived only from the supplied image package. The adapter label is used for electrical input/output data; dimensions not provided in the source remain TBD.

1. Functional Description

This Embedded Wireless Charging Module combines a circular wireless-power transmitter with a separate inline AC/DC adapter. The transmitter can be integrated into a furniture or equipment surface to create a dedicated contactless charging point. Multiple cosmetic transmitter styles are shown in the supplied package, including black, white and silver/gray finishes.

2. Key Features

Wireless power transfer	Circular transmitter provides contactless charging to a compatible receiving device.
Dedicated power adapter	Inline AC/DC adapter converts mains input to low-voltage DC for the charging transmitter.
Furniture integration	Compact round form is suited to desks, conference tables, counters and embedded equipment.
Multiple finishes	Black, white and silver/gray product styles are shown.
Cable-integrated architecture	Adapter and transmitter are supplied as a wired charging assembly.
Low-profile transmitter	Flat circular charging head minimizes the visible footprint on the installation surface.

3. Electrical Characteristics

AC input	AC 100-280 V, 50/60 Hz - as legible on the supplied adapter label.
DC adapter output	9 V DC, 2.3 A - as legible on the supplied adapter label.
Adapter output power	Approx. 20.7 W calculated from the stated 9 V x 2.3 A output.
Wireless charging output power	TBD - transmitter-side rated wireless power is not stated in the supplied images.
Adapter model marking	JIECI
Wireless charging protocol	TBD - exact Qi / proprietary protocol version is not stated.
AC connection	Two-wire mains lead shown on the adapter input side.
DC connection	Barrel-style DC connector is shown between the adapter and transmitter assembly.

4. Input / Output Summary

System input	100-280 VAC, 50/60 Hz
Power conversion output	9 VDC, 2.3 A
Available adapter power	20.7 W nominal based on label values
Final power output	Wireless power at the circular transmitter surface; exact delivered wattage TBD
Power path	AC mains -> inline AC/DC adapter -> 9 VDC cable connection -> wireless charging transmitter

5. Mechanical Characteristics

Transmitter form	Round, low-profile charging puck / embedded charging head
Transmitter dimensions	TBD - no dimensioned drawing is included in the supplied package.
Adapter dimensions	TBD
Cable length	TBD
Finish options shown	Black / White / Silver-Gray
Installation method	Embedded or surface-integrated application is suggested by the product form; final mounting method TBD.
Weight	TBD

6. Typical Applications

Conference tables, office desks, executive furniture, hotel furniture, bedside tables, reception counters, kitchen/work surfaces, commercial fixtures and other furniture or equipment requiring an integrated wireless charging point.

PRODUCT VIEWS

产品实拍展示

CHARGER



7. Product Variants

The supplied package shows several transmitter-face designs while using the same general external adapter architecture. Cosmetic options include plain white, plain black, silver/gray and versions with printed wireless-charging symbols. Final model assignment should distinguish cosmetic finish from electrical power configuration.

8. Integration Considerations

Confirm the furniture cutout, mounting depth and allowable surface thickness before installation. Maintain sufficient clearance for the transmitter body, cable routing and adapter ventilation. Avoid placing unintended metallic objects between the transmitter and receiving device. The final installation should comply with the electrical and thermal requirements of the selected wireless-power design.

9. Production-Release Data Required

Before controlled release, confirm transmitter rated wireless output power, supported charging protocol, operating frequency, charging efficiency, foreign-object detection, over-temperature/over-current/over-voltage protection, transmitter dimensions, installation cutout, cable lengths, connector polarity, enclosure materials, operating/storage temperature, ingress rating and applicable safety/EMC certifications.

10. Source Electrical Label



Document status: Preliminary English product specification based on the supplied image package. The AC/DC values above are transcribed from the visible adaptor label; unprovided transmitter specifications remain TBD.