

75 mm Bolt-Mount Wireless Charger

Secure furniture-integrated wireless charging module with USB power lead and anti-theft bolt mounting



Compact wireless charging with secure mechanical retention

A circular wireless charging module designed for through-surface installation. The supplied M6 bolt, nut and backing plate provide a fixed anti-theft mounting arrangement for desks, tables, counters and public-use furniture.

Preliminary specification based only on the two supplied product images. Confirmed dimensions and mounting hardware are preserved from the source; unstated electrical ratings remain TBD.

1. Functional Description

The 75 mm Bolt-Mount Wireless Charger provides a dedicated contactless charging point for compatible devices while allowing the charging module to be mechanically secured to the installation surface. The round charging head sits above the furniture surface, while the lower body passes into the mounting opening. A metal backing plate, nut and M6 x 50 mm bolt secure the assembly from below. Power is supplied through the attached USB Type-A lead shown in the source image.

2. Key Features

Wireless charging	Circular contactless charging surface with wireless-power symbol.
Secure bolt mounting	Source annotation identifies an anti-theft screw/bolt mounting arrangement for firmer retention.
Mounting hardware	Metal backing plate, nut and M6 x 50 mm bolt are shown with the product.
USB power lead	Attached cable terminates in a USB Type-A plug marked 'Fast Charger'.
Furniture integration	Through-surface architecture supports installation in desks, tables, counters and similar fixtures.
Low-profile top	Wide circular flange provides a clean finished appearance above the mounting surface.

3. Electrical Characteristics

Electrical input	USB-powered DC input; exact voltage/current is TBD because no electrical rating is shown.
Input connector	USB Type-A male plug.
Wireless output power	TBD - no verified 5 W / 10 W / 15 W or other wattage is stated.
Wireless charging protocol	TBD - exact Qi version or other protocol is not stated.
Charging efficiency	TBD.
Protection functions	TBD - confirm foreign-object, thermal, overcurrent and overvoltage protection before production release.

4. Mechanical Specifications

Top flange diameter	2.91 in (approximately 73.9 mm) - dimension shown in source.
Lower body diameter	2.36 in (approximately 59.9 mm) - dimension shown in source.
Mounting bolt	M6 x 50 mm.
Retention hardware	Metal backing plate + nut + bolt.
Installation type	Through-surface, bolt-retained / anti-theft mounting.
Overall thickness / depth	TBD - not dimensioned in the supplied source.
Cable length	TBD.
Weight	TBD.
Finish shown	Black charging face with metallic/silver perimeter and housing.

5. Input / Output Summary

Input	Low-voltage DC via attached USB Type-A cable; exact electrical rating TBD.
Primary output	Wireless charging field at the circular top surface.
Mechanical interface	Approx. 60 mm lower body through the mounting opening, retained by M6 hardware.
User interface	Place a compatible receiving device over the marked wireless charging area.

6. Typical Applications

Conference tables, office desks, hotel and hospitality furniture, libraries, lounges, reception counters, public charging furniture, retail fixtures and other installations where the wireless charger should be mechanically secured against casual removal.



ANTI-THEFT BOLT MOUNT

Secure fixed installation

Bolt: M6 x 50 mm

7. Installation Concept

Prepare a mounting opening suitable for the approximately 2.36 in (59.9 mm) lower body. Insert the charger from the top of the surface, position the supplied backing plate below the surface, and secure the assembly using the supplied M6 x 50 mm bolt and nut arrangement. Final hole tolerance, allowable tabletop thickness and tightening torque must be confirmed from the controlled mechanical drawing before production installation.

8. Production-Release Data Required

Before release as a controlled SiCore product specification, confirm USB input voltage/current, rated wireless output power, supported charging protocol, operating frequency, charging efficiency, foreign-object detection, thermal and electrical protection, exact installation cutout tolerance, maximum/minimum surface thickness, tightening torque, cable length, enclosure and backing-plate materials, operating/storage temperature, environmental rating, product weight and applicable FCC/UL/ETL/CSA or other regional certifications.

9. Product Classification

Primary category: Wireless Charging

Product type: Furniture-Integrated Wireless Charging Module

Mechanical architecture: Through-surface anti-theft bolt mount

Confirmed dimensions: 2.91 in top flange / 2.36 in lower body / M6 x 50 mm mounting bolt



Document status: Preliminary English product specification based solely on the supplied two-image package. No unsupported voltage, current or wireless power values have been introduced.