

75 mm Wireless Charging Pad

Compact circular wireless charging module with external QC 3.0-marked power adapter



Compact contactless charging in a 75 mm footprint

A round wireless charging pad supplied as a wired assembly with an external wall adapter. The product is offered in white and black versions in the supplied image set.

Preliminary specification based only on the supplied five product images. Only the visible 75 mm diameter and QC 3.0 adapter marking are treated as confirmed; unstated electrical values remain TBD.

1. Functional Description

The 75 mm Wireless Charging Pad provides a dedicated contactless charging surface for compatible receiving devices. The circular transmitter is connected by a fixed cable to an external AC/DC wall adapter. The product images show both white and black charging-pad versions, a US two-blade wall adapter, and a ventilated rear housing on the charging transmitter.

2. Key Features

Wireless charging surface	Circular top surface marked with the wireless charging symbol and 'Wireless Charging' text.
Compact diameter	75 mm outside diameter is explicitly dimensioned in the supplied source.
External power adapter	Charging pad is supplied with a separate wall adapter.
QC 3.0 marking	Quick Charge 3.0 / QC 3.0 marking is visible on the supplied adapter imagery.
Color options	White and Black versions are shown.
Ventilated rear housing	Rear face includes multiple ventilation openings around the center region.
Integrated cable	A long attached cable connects the charging pad to the power adapter assembly.

3. Electrical Characteristics

AC input	TBD - the adapter rating text is not sufficiently legible in the supplied images.
Adapter DC output	TBD - exact QC 3.0 voltage/current profiles are not reliably readable.
Charging-pad input	TBD.
Wireless output power	TBD - no verified 5 W / 10 W / 15 W or other wireless wattage is stated in the supplied package.
Adapter technology marking	QC 3.0 / Quick Charge 3.0 marking visible.
Wireless charging standard	TBD - exact Qi generation or other protocol is not stated.
Protection functions	TBD.

4. Input / Output Summary

System input	AC mains through the external wall adapter.
Power conversion	External AC/DC adapter with QC 3.0 marking.
Transmitter input	Low-voltage DC delivered through the attached cable; exact electrical profile TBD.
Primary output	Wireless power through the 75 mm circular transmitter surface.
Receiving device	Compatible wireless-charging device.

5. Mechanical Characteristics

Outside diameter	75 mm - confirmed by source dimension graphic.
Thickness	TBD.
Product form	Circular low-profile charging pad / transmitter.
Top finish	Smooth charging face with molded/embossed wireless charging graphic.
Rear construction	Circular rear cover with ventilation perforations and visible fasteners.
Colors shown	White / Black.
Cable length	TBD.
Weight	TBD.
Installation method	TBD - source images show the module in use but do not provide a controlled mounting drawing.

6. Typical Applications

Desks, conference tables, bedside furniture, hospitality furniture, counters, workspaces and other equipment or surfaces requiring a compact wireless charging point. Final mounting suitability should be verified against the production mechanical design.



7. Application View



8. Product Architecture

The product uses an external-adapter architecture: AC mains is converted to low-voltage DC by the wall adapter, the DC power is carried through the attached cable, and the circular transmitter converts that electrical input into a wireless charging field at the top surface.

9. Production-Release Data Required

Before release as a controlled SiCore product specification, confirm the adapter AC input range and frequency, QC 3.0 output profiles, transmitter input voltage/current, rated wireless output power, supported wireless charging standard, operating frequency, charging efficiency, foreign-object detection, thermal/overcurrent/overvoltage protection, exact thickness, cable length, connector architecture, enclosure materials, operating/storage temperature, mounting method, product weight and applicable UL/ETL/CSA/FCC or other regional certifications.

10. Product Classification

Primary category: Wireless Charging

Product type: Compact Wireless Charging Pad / Transmitter

Confirmed mechanical size: 75 mm diameter

Power architecture: External QC 3.0-marked wall adapter + wired charging transmitter

Document status: Preliminary English product specification based solely on the supplied image package. No unsupported voltage, current, wireless wattage or dimensional values have been introduced.