

57W 12V-to-19V IP68 DC-DC Converter

EV60-T1219 | 9-16V DC Input | 19V / 3A Regulated Output



Product Overview

Compact sealed DC-DC step-up converter designed to convert a nominal 12 V DC supply (supported input range 9-16 V DC) to a regulated 19 V DC output. The supplied product material specifies a maximum output current of 3 A, 57 W output power, conversion efficiency of at least 93%, IP68 ingress protection, and an operating temperature range of -20 to 80 deg C.

Key Features

- 9-16 V DC input range for nominal 12 V systems
- 19 V DC regulated output with +/-0.15 V tolerance
- 3 A maximum output current and 57 W output power
- Conversion efficiency >=93%
- IP68 ingress protection
- Operating temperature: -20 to 80 deg C
- 58 x 39.5 x 21.8 mm compact enclosure
- 21 cm pre-wired cables and 3.9 mm mounting holes

Electrical & Mechanical Specifications

Parameter	Specification
Model	EV60-T1219
Product Type	12V to 19V DC-DC Converter
Input Voltage	DC 9-16 V
Nominal Input	12 V DC
Output Voltage	DC 19 V +/- 0.15 V
Output Current	3 A max.
Output Power	57 W
Conversion Efficiency	>= 93%
Operating Temperature	-20 to 80 deg C
Ingress Protection Rating	IP68
Product Weight	99 g
Dimensions (L x W x H)	58 x 39.5 x 21.8 mm
Cable Length	21 cm
Mounting Hole Diameter	3.9 mm

Mechanical Configuration



The supplied mechanical image specifies a 58 mm x 39.5 mm x 21.8 mm enclosure, 21 cm cable length, and 3.9 mm mounting-hole diameter.

Typical Applications

- 12 V vehicle electrical systems requiring a regulated 19 V rail
- Mobile and battery-powered electronics
- Industrial embedded equipment
- Outdoor or environmentally exposed DC power conversion
- 19 V auxiliary power for compatible electronic equipment

Integration Notes

Operate the converter only within the specified 9-16 V DC input range and within the stated 3 A / 57 W output rating. Confirm connector dimensions, polarity, load transient behavior, ripple/noise requirements, and thermal performance in the final system before production use.

Source-control note: This datasheet is based only on the three supplied product images. No webpage/HTML files were included. Protection functions other than the stated IP68 rating, certification status, ripple/noise, standby current, and detailed connector dimensions were not provided and are therefore not claimed.