

Gaming Mouse Wireless Charging Dock

Purpose-built desktop charging cradle with guided mouse positioning and illuminated status accents



Drop-in charging for compatible performance mice

A contoured desktop charging dock that mechanically locates a compatible mouse over a dedicated charging interface while providing a stable resting position between uses.

Preliminary specification based solely on the supplied eight product photographs. No electrical rating, power level, dimensions, protocol or compatibility list is visible in the source; these items remain TBD.

1. Functional Description

The Gaming Mouse Wireless Charging Dock is a desktop cradle designed to hold and charge a compatible computer mouse when it is placed in the dock. The enclosure uses a contoured guide geometry to position the mouse consistently over the charging area. Supplied images show several interchangeable or prototype-colored charging inserts and an illuminated perimeter/status area, indicating a design intended for convenient repeatable docking in gaming, workstation and peripheral-charging applications.

2. Key Features

Guided docking	Contoured cradle supports repeatable mouse placement and mechanical alignment.
Dedicated charging interface	Central charging insert/interface is positioned directly beneath the mouse when docked.
Desktop cradle	Angled body supports the mouse in a stable parked position.
Status / accent illumination	Green, blue and red illumination is visible in different supplied product views; exact signaling logic is TBD.
Cable-powered base	A wired power connection is visible at the rear/side of the dock.
Serviceable / modular structure	Open product views show a removable central insert and internal guide structure.
Compact peripheral integration	Designed as a dedicated charging location without requiring a large charging mat.

3. Electrical Characteristics

Electrical input	TBD - input voltage/current are not shown in the supplied photographs.
Charging output	TBD - charging power is not stated.
Charging method	Dedicated close-coupled charging interface is evident; exact inductive/magnetic/contact protocol requires engineering confirmation.
Power connector	Wired input is visible; exact connector type and cable specification are TBD.
Status indication	Illuminated base/interface is visible; LED color meanings and control behavior are TBD.
Protection functions	TBD - confirm overcurrent, overvoltage, overtemperature, short-circuit and foreign-object behavior as applicable.

4. Mechanical Characteristics

Product form	Angled desktop cradle with contoured mouse-support geometry.
Docking cavity	Open-top guide structure shaped to locate a compatible mouse.
Central interface	Circular removable/replaceable charging insert visible in product views.
Housing finish	Black housing; colored insert/accent variants shown in green, blue and orange/red.
Overall dimensions	TBD - no dimensioned drawing or reliable scale is included.
Cable length	TBD.
Weight	TBD.
Retention / alignment	Passive mechanical guidance from the cradle geometry; magnetic assistance, if any, is TBD.

5. Input / Output Summary

Input	Low-voltage wired input to the charging dock; exact electrical rating TBD.
Primary output	Charging energy transferred from the dock interface to a compatible mouse.
Mechanical input	User places the mouse into the shaped cradle.
User feedback	Visible illumination around the charging/docking region; exact status definitions TBD.

6. Typical Applications

Gaming desktops, professional workstations, esports environments, computer-peripheral charging stations, shared desks and other applications requiring a dedicated park-and-charge location for a compatible wireless mouse.

PRODUCT VIEWS



7. Docking Architecture

The product combines mechanical guidance and a dedicated charging zone. The cradle geometry first positions the mouse body, while the central interface aligns with the corresponding receiver area on the mouse. This arrangement is intended to make charging repeatable without manually connecting a cable to the mouse each time. The exact energy-transfer technology cannot be confirmed from the photographs alone and should be defined from the electrical design before release.

8. Product Differentiators

Purpose-built geometry	Unlike a flat charging pad, the dock physically supports and locates the mouse.
Repeatable alignment	The shaped cradle reduces placement variability at the charging interface.
Small desktop footprint	Provides a dedicated charging location without occupying the area of a full-size mouse mat.
Visual feedback potential	Integrated illumination can support charging, ready, fault or decorative status functions once final firmware/electronics behavior is defined.
Modular interface potential	The visible central insert suggests a design that can support serviceability or variant-specific charging interfaces; final implementation must be confirmed.

9. Production-Release Data Required

Before release as a controlled SiCore specification, confirm input voltage/current and connector, charging method and protocol, rated output power, compatible mouse/receiver interface, charging time, alignment tolerance, LED status definitions, cable length, overall dimensions, enclosure and insert materials, operating/storage temperature, mechanical life, protection functions, EMC requirements and applicable FCC/UL/ETL/CSA or other certifications.

10. Product Classification

Primary category: Docking / Charging

Product type: Gaming Mouse Charging Dock

Alignment method: Passive mechanical guidance

Charging interface: Dedicated close-coupled interface - exact electrical technology TBD

Target environment: Desktop / Gaming / Workstation peripherals

Document status: Preliminary English product specification based solely on supplied product photography. No unsupported voltage, current, charging power, dimensions or protocol values have been introduced.