

Multifunction Conference Table Power Hub

Integrated AC power, USB charging, data connectivity and wireless charging for modern workspaces



All-in-one desktop connectivity

A recessed table module combining universal AC outlets, USB charging, network, HDMI and a dedicated wireless charging surface in a clean sliding-cover enclosure.

Preliminary specification prepared from the supplied product image. Values not visible or verifiable in the source are identified as TBD rather than estimated.

1. Functional Description

The Multifunction Conference Table Power Hub is a recessed connectivity module designed for conference tables, executive desks, collaborative workspaces and integrated furniture. It consolidates mains power, low-voltage USB charging, wired network access, HDMI connectivity and wireless device charging into a single low-profile station. Sliding metal covers help preserve a clean tabletop appearance when interfaces are not in use.

2. Key Features

Integrated AC power	Universal-style AC receptacles are provided for laptop adapters and other compatible equipment.
USB charging	Integrated USB charging interface is labeled 5 V DC, 2 A.
Wireless charging	Dedicated top charging area is visibly identified by a wireless-power symbol.
Network connectivity	RJ45 network port labeled NET.
Video connectivity	HDMI interface for display / presentation connection.
Furniture integration	Low-profile recessed construction with sliding covers for conference-table or desktop installation.
Finish	Black central interface panel with metallic sliding cover surfaces, as shown in the supplied image.

3. Electrical Characteristics

AC input / outlet rating	110-240 V AC, 50/60 Hz, 10 A - marking visible on the supplied product image.
USB output	5 V DC, 2 A - marking visible on the supplied product image.
USB output power	10 W nominal maximum based on the visible 5 V / 2 A marking.
Wireless charging output	TBD - charging power is not stated in the supplied source.
AC outlet count	Product imagery shows two AC receptacles on the extended configuration and one receptacle on the compact configuration.
Network	RJ45 physical interface; Ethernet category / speed TBD.
HDMI	HDMI physical interface; supported HDMI version / resolution TBD.
Total system power	TBD - depends on final AC outlet configuration, internal wiring rating and wireless charging specification.

4. Interface Configuration

AC receptacle	Universal-style mains outlet
USB	USB charging ports; source marking indicates 5 V / 2 A
Wireless charging surface	Integrated charging pad on the left-side sliding section in the extended configuration
NET	RJ45 network connection
HDMI	HDMI audio/video connection

5. Mechanical Specifications

Product form	Recessed / built-in conference-table power and connectivity module
Enclosure geometry	Rectangular low-profile interface body with sliding top covers
Overall dimensions	TBD - no dimensional drawing or scale is included in the supplied source.
Table cutout dimensions	TBD - required for installation release.
Mounting depth	TBD.
Weight	TBD.
Visible materials / finish	Metallic sliding covers with black interface panel; exact alloy and coating TBD.

6. Typical Applications

Conference tables, executive desks, meeting rooms, training rooms, collaborative workstations, hotel/business-center furniture, AV presentation stations and other integrated furniture requiring convenient access to power, charging, network and display connections.

7. Information Required for Production Release

Before this datasheet is released as a controlled production specification, confirm the overall dimensions, table cutout, mounting depth, wireless charging wattage and standard, USB connector type and port count, AC receptacle count by model, total current rating, internal protection, cable length, Ethernet category/speed, HDMI version, operating temperature, enclosure material, applicable safety certifications and final model number.



Document status: Preliminary product specification derived from supplied imagery. TBD items must be confirmed against engineering drawings, electrical design data or the production unit.