

Information générale du routeur :

The screenshot shows the Cisco RV215W Wireless-N VPN Firewall Dashboard. The left sidebar contains navigation links: Getting Started, Status (selected), Dashboard, System Summary, Wireless Statistics, VPN Status, IPSec Connection Status, View Logs, Connected Devices, Port Statistics, Guest Net Status, Mobile Network, Networking, Wireless, Firewall, VPN, QoS, and Administration. The main content area is titled 'Dashboard' and includes a 'Show Panel View' button. It displays the following information:

- Device Information:** System Name: routerAB284F, Firmware Version: 1.1.0.5, Serial Number: CCO19190S5N.
- Resource Utilization:** CPU: 3%, Memory: 61% (39/64 MB), Current Time: 01/11/2010 04:14 AM, System Up Time: 10 Days, 4 Hours, 14 Minutes, 36 Seconds.
- Syslog Summary:** Emergency: Logging Disabled, Alert: Logging Disabled, Critical: Logging Disabled, Error: Logging Disabled, Warning: Logging Disabled.
- LAN (Local Network) Interface:** MAC Address: 10:BD:18:AB:28:4F, IPv4 Address: 192.168.1.1, IPv6 Address: FEC0:0000:0000:0000:0000:0000:0001:64, DHCP Server: Enabled, DHCPv6 Server: Disabled.
- WAN (Ethernet) Information:** IPv4 Address: 192.168.184.134, IPv6 Address: FE80:0000:0000:0000:12BD:18FF:FEAB:284F/64, State: Up.
- Wireless Networks:** router_Drone: Active, ciscosb2: Disabled, ciscosb3: Disabled, ciscosb4: Disabled.
- VPN:** QuickVPN Users: 0/0, PPTP Users: 0/0.

Paramétrage du routeur déjà en place depuis l'année dernière :

The screenshot shows the 'Basic Settings' page of the Cisco RV215W Wireless-N VPN Firewall. The left sidebar is the same as the dashboard, but the 'Firewall' section is expanded, showing 'Basic Settings' (selected), Schedule Management, Service Management, Access Rules, Internet Access Policy, Single Port Forwarding, Port Range Forwarding, and Port Range Triggering. The main content area is titled 'Basic Settings' and contains the following configuration options:

- Firewall:** ☒ Enable
- DoS Protection:** ☒ Enable
- Block WAN Request:** ☒ Enable
- Web Access:** ☒ HTTP ☒ HTTPS
- Remote Management:** ☐ Enable
- Remote Access:** ☐ HTTP ☒ HTTPS
- Remote Upgrade:** ☐ Enable
- Allowed Remote IP Address:** ☒ Any IP Address, ☐ 0 . 0 . 0 . 0 - 0
- Remote Management Port:** 443 (Range: 1 - 65535, Default: 443)
- IPv4 Multicast Passthrough:(IGMP Proxy)** ☒ Enable
- IPv6 Multicast Passthrough:(IGMP Proxy)** ☐ Enable
- UPnP** ☒ Enable
- Allow Users to Configure** ☒ Enable
- Allow Users to Disable Internet Access** ☐ Enable
- Block Java:** ☐ ☒ Auto ☐ Manual Port:
- Block Cookies:** ☐ ☒ Auto ☐ Manual Port:
- Block ActiveX:** ☐ ☒ Auto ☐ Manual Port:
- Block Proxy:** ☐ ☒ Auto ☐ Manual Port:

At the bottom, there are 'Save' and 'Cancel' buttons.

Password pour se connecter au routeur :

Small Business
cisco RV215W Wireless-N VPN Firewall

Basic Settings

Radio: ☒ Enable

Wireless Network Mode: B/G/N-Mixed

Wireless Band Selection: 20MHz 20/40MHz

Wireless Channel: 6-2.437 GHz

AP Management VLAN: 1

U-APSD (WMM Power Save): ☐ Enable

	Enable SSID	SSID Name	SSID Broadcast	Security Mode	MAC Filter	Guest Network	VLAN	Wireless Isolation with SSID	WMM	WPS
<input type="checkbox"/>	<input checked="" type="checkbox"/> ON	routeur_Drone	<input checked="" type="checkbox"/>	WPA2-Personal	Disabled	<input type="checkbox"/>	1	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/> OFF	ciscosb2	<input checked="" type="checkbox"/>	Disabled	Disabled	<input type="checkbox"/>	1	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/> OFF	ciscosb3	<input checked="" type="checkbox"/>	Disabled	Disabled	<input type="checkbox"/>	1	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/> OFF	ciscosb4	<input checked="" type="checkbox"/>	Disabled	Disabled	<input type="checkbox"/>	1	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

Edit Edit Security Mode Edit MAC Filtering Time of Day Access Edit Guest Net Edit WPS

Save Cancel

Small Business
cisco RV215W Wireless-N VPN Firewall

Security Settings

Select SSID: routeur_Drone

Security Mode: WPA2-Personal

Encryption: AES

Security Key: TRexTeam Weak

Unmask Password: ☒

Key Renewal: 3600 Seconds (Range: 600 - 7200, Default: 3600)

Save Cancel Back