



# **P4<sub>16</sub> Language Specification**

**The P4 Language Consortium**

**Version v1.2.5, 2026-02-23**

# Contents

|                                                                            |    |
|----------------------------------------------------------------------------|----|
| 1. Scope                                                                   | 15 |
| 2. Terms, definitions, and symbols                                         | 15 |
| 3. Overview                                                                | 16 |
| 3.1. Benefits of P4                                                        | 18 |
| 3.2. P4 language evolution: comparison to previous versions (P4 v1.0/v1.1) | 19 |
| 4. Architecture Model                                                      | 20 |
| 4.1. Standard architectures                                                | 21 |
| 4.2. Data plane interfaces                                                 | 21 |
| 4.3. Extern objects and functions                                          | 21 |
| 5. Example: A very simple switch                                           | 22 |
| 5.1. Very Simple Switch Architecture                                       | 23 |
| 5.2. Very Simple Switch Architecture Description                           | 25 |
| 5.2.1. Arbiter block.                                                      | 25 |
| 5.2.2. Parser runtime block                                                | 25 |
| 5.2.3. Demux block                                                         | 26 |
| 5.2.4. Available extern blocks.                                            | 26 |
| 5.3. A complete Very Simple Switch program.                                | 26 |
| 6. P4 language definition                                                  | 30 |
| 6.1. Syntax and semantics                                                  | 30 |
| 6.1.1. Grammar                                                             | 31 |
| 6.1.2. Semantics and the P4 abstract machines                              | 31 |
| 6.1.2.1. Pseudo-code snippets                                              | 31 |
| 6.1.2.2. Prose algorithms                                                  | 31 |
| 6.1.2.2.1. Prose algorithm shorthands                                      | 32 |
| 6.2. Lexical constructs.                                                   | 33 |
| 6.2.1. Identifiers                                                         | 33 |
| 6.2.2. Literal constants                                                   | 34 |
| 6.2.2.1. Boolean literals.                                                 | 34 |
| 6.2.2.2. Integer literals.                                                 | 34 |
| 6.2.2.3. String literals.                                                  | 35 |
| 6.2.3. Comments                                                            | 35 |
| 6.2.4. Optional trailing commas                                            | 36 |
| 6.3. Scoping                                                               | 36 |
| 6.3.1. Name resolution                                                     | 37 |
| 6.3.2. Name visibility                                                     | 38 |
| 6.4. Stateful elements.                                                    | 38 |
| 6.5. Call convention: copy-in/copy-out.                                    | 38 |
| 6.5.1. Justification.                                                      | 41 |
| 6.5.2. Optional parameters                                                 | 42 |
| 6.6. Overloading.                                                          | 42 |
| 6.7. Naming conventions                                                    | 43 |
| 7. The P4 Abstract Machine                                                 | 43 |
| 7.1. Preprocessing.                                                        | 44 |
| 7.2. Type checking.                                                        | 44 |
| 7.2.1. P4 Intermediate Representation                                      | 45 |
| 7.2.2. Typing a P4 program                                                 | 46 |
| 7.2.3. Typing context.                                                     | 47 |
| 7.3. Instantiation                                                         | 48 |

|                                                                   |    |
|-------------------------------------------------------------------|----|
| 7.3.1. Control-plane names .....                                  | 50 |
| 7.3.1.1. Computing control-plane names. ....                      | 50 |
| 7.3.1.1.1. Value sets .....                                       | 50 |
| 7.3.1.1.2. Tables .....                                           | 50 |
| 7.3.1.1.3. Keys .....                                             | 51 |
| 7.3.1.1.4. Actions. ....                                          | 51 |
| 7.3.1.1.5. Instances. ....                                        | 52 |
| 7.3.1.2. Annotations controlling naming .....                     | 53 |
| 7.3.1.3. Recommendations. ....                                    | 53 |
| 7.3.2. Instantiating a P4 program .....                           | 54 |
| 7.3.3. Instantiation context .....                                | 54 |
| 7.4. Runtime evaluation .....                                     | 56 |
| 7.4.1. Evaluating a P4 program .....                              | 56 |
| 7.4.2. Evaluation context .....                                   | 57 |
| 7.4.3. The parser abstract machine .....                          | 57 |
| 7.4.4. The match-action pipeline abstract machine .....           | 57 |
| 7.4.5. Concurrency model .....                                    | 57 |
| 7.5. Compile-time known and local compile-time known values. .... | 59 |
| 8. P4 types and values .....                                      | 60 |
| 8.1. Semantics of types. ....                                     | 61 |
| 8.1.1. Type checking surface types .....                          | 61 |
| 8.1.2. Well-formedness .....                                      | 61 |
| 8.2. Base types and values. ....                                  | 61 |
| 8.2.1. Well-formedness .....                                      | 62 |
| 8.2.2. The void type .....                                        | 62 |
| 8.2.2.1. Type checking .....                                      | 63 |
| 8.2.3. Booleans .....                                             | 63 |
| 8.2.3.1. Operations. ....                                         | 63 |
| 8.2.3.2. Type checking .....                                      | 64 |
| 8.2.4. Errors .....                                               | 64 |
| 8.2.4.1. Operations. ....                                         | 64 |
| 8.2.4.2. Type checking .....                                      | 65 |
| 8.2.5. Match kinds .....                                          | 65 |
| 8.2.5.1. Operations. ....                                         | 65 |
| 8.2.5.2. Type checking .....                                      | 66 |
| 8.2.6. Strings .....                                              | 66 |
| 8.2.6.1. Operations. ....                                         | 66 |
| 8.2.6.2. Type checking .....                                      | 66 |
| 8.2.7. Integers (signed and unsigned). ....                       | 66 |
| 8.2.7.1. Portability .....                                        | 67 |
| 8.2.7.2. Integer literals. ....                                   | 67 |
| 8.2.7.3. Illegal arithmetic expressions. ....                     | 68 |
| 8.2.7.4. Arbitrary-precision integers .....                       | 69 |
| 8.2.7.4.1. Operations .....                                       | 69 |
| 8.2.7.4.2. Type checking. ....                                    | 70 |
| 8.2.7.5. Fixed-width unsigned integers (bit-strings) .....        | 70 |
| 8.2.7.5.1. Operations .....                                       | 71 |
| 8.2.7.5.2. Type checking. ....                                    | 72 |
| 8.2.7.6. Fixed-width signed integers .....                        | 73 |
| 8.2.7.6.1. Operations .....                                       | 73 |

|                                                                     |     |
|---------------------------------------------------------------------|-----|
| 8.2.7.6.2. Type checking . . . . .                                  | 74  |
| 8.2.7.7. Dynamically-sized bit-strings . . . . .                    | 75  |
| 8.2.7.7.1. Operations . . . . .                                     | 75  |
| 8.2.7.7.2. Type checking . . . . .                                  | 76  |
| 8.3. Named types . . . . .                                          | 76  |
| 8.3.1. Type definitions (type constructors) . . . . .               | 78  |
| 8.3.2. Type resolution . . . . .                                    | 78  |
| 8.3.3. Type specialization . . . . .                                | 79  |
| 8.3.4. Type names . . . . .                                         | 79  |
| 8.3.4.1. Operations . . . . .                                       | 80  |
| 8.3.4.2. Type checking . . . . .                                    | 80  |
| 8.3.5. Specialized types . . . . .                                  | 81  |
| 8.3.5.1. Type checking . . . . .                                    | 81  |
| 8.4. Data types and values . . . . .                                | 81  |
| 8.4.1. Lists . . . . .                                              | 82  |
| 8.4.1.1. Operations . . . . .                                       | 82  |
| 8.4.1.2. Type checking . . . . .                                    | 83  |
| 8.4.1.3. Well-formedness . . . . .                                  | 83  |
| 8.4.2. Tuples . . . . .                                             | 83  |
| 8.4.2.1. Operations . . . . .                                       | 83  |
| 8.4.2.2. Type checking . . . . .                                    | 84  |
| 8.4.2.3. Well-formedness . . . . .                                  | 84  |
| 8.4.3. Header stacks . . . . .                                      | 84  |
| 8.4.3.1. Operations . . . . .                                       | 85  |
| 8.4.3.2. Type checking . . . . .                                    | 86  |
| 8.4.3.3. Well-formedness . . . . .                                  | 87  |
| 8.4.4. Arrays . . . . .                                             | 87  |
| 8.4.5. Structs . . . . .                                            | 87  |
| 8.4.5.1. Operations . . . . .                                       | 88  |
| 8.4.5.2. Type checking . . . . .                                    | 88  |
| 8.4.5.3. Well-formedness . . . . .                                  | 88  |
| 8.4.6. Headers . . . . .                                            | 89  |
| 8.4.6.1. Operations . . . . .                                       | 91  |
| 8.4.6.2. Type checking . . . . .                                    | 91  |
| 8.4.6.3. Well-formedness . . . . .                                  | 91  |
| 8.4.7. Header unions . . . . .                                      | 91  |
| 8.4.7.1. Operations . . . . .                                       | 92  |
| 8.4.7.2. Type checking . . . . .                                    | 95  |
| 8.4.7.3. Well-formedness . . . . .                                  | 96  |
| 8.4.8. Enums . . . . .                                              | 96  |
| 8.4.8.1. Enum type declaration without an underlying type . . . . . | 96  |
| 8.4.8.2. Enum type declaration with an underlying type . . . . .    | 97  |
| 8.4.8.3. Operations . . . . .                                       | 97  |
| 8.4.8.4. Type checking . . . . .                                    | 100 |
| 8.4.8.5. Well-formedness . . . . .                                  | 101 |
| 8.5. Object types and values . . . . .                              | 101 |
| 8.5.1. Extern object types . . . . .                                | 101 |
| 8.5.1.1. Type checking . . . . .                                    | 102 |
| 8.5.1.2. Well-formedness . . . . .                                  | 102 |
| 8.5.2. Parser object types . . . . .                                | 102 |



|                                                             |     |
|-------------------------------------------------------------|-----|
| 8.5.2.1. Type checking . . . . .                            | 103 |
| 8.5.2.2. Well-formedness . . . . .                          | 103 |
| 8.5.3. Control object types . . . . .                       | 103 |
| 8.5.3.1. Type checking . . . . .                            | 104 |
| 8.5.3.2. Well-formedness . . . . .                          | 104 |
| 8.5.4. Package object types . . . . .                       | 104 |
| 8.5.4.1. Type checking . . . . .                            | 104 |
| 8.5.4.2. Well-formedness . . . . .                          | 105 |
| 8.5.5. Table object types . . . . .                         | 105 |
| 8.5.5.1. Well-formedness . . . . .                          | 105 |
| 8.5.6. Object reference values . . . . .                    | 105 |
| 8.5.7. <b>typedef</b> declaration . . . . .                 | 106 |
| 8.5.7.1. Type checking . . . . .                            | 106 |
| 8.5.7.2. Well-formedness . . . . .                          | 106 |
| 8.5.8. <b>type</b> declaration . . . . .                    | 107 |
| 8.5.8.1. Operations . . . . .                               | 107 |
| 8.5.8.2. Type checking . . . . .                            | 107 |
| 8.5.8.3. Well-formedness . . . . .                          | 108 |
| 8.6. Synthesized types and values . . . . .                 | 108 |
| 8.6.1. Default . . . . .                                    | 108 |
| 8.6.1.1. Operations . . . . .                               | 108 |
| 8.6.1.2. Well-formedness . . . . .                          | 109 |
| 8.6.2. Invalid headers . . . . .                            | 109 |
| 8.6.2.1. Operations . . . . .                               | 109 |
| 8.6.2.2. Well-formedness . . . . .                          | 110 |
| 8.6.3. Sequences . . . . .                                  | 110 |
| 8.6.3.1. Operations . . . . .                               | 110 |
| 8.6.3.2. Well-formedness . . . . .                          | 111 |
| 8.6.4. Records . . . . .                                    | 111 |
| 8.6.4.1. Operations . . . . .                               | 112 |
| 8.6.4.2. Well-formedness . . . . .                          | 112 |
| 8.6.5. Sets . . . . .                                       | 113 |
| 8.6.5.1. Operations . . . . .                               | 113 |
| 8.6.5.1.1. Singleton sets . . . . .                         | 114 |
| 8.6.5.1.2. The universal set . . . . .                      | 114 |
| 8.6.5.1.3. Masks . . . . .                                  | 114 |
| 8.6.5.1.4. Ranges . . . . .                                 | 115 |
| 8.6.5.1.5. Products . . . . .                               | 115 |
| 8.6.5.2. Well-formedness . . . . .                          | 115 |
| 8.6.6. Table metadata . . . . .                             | 115 |
| 8.6.6.1. Operations . . . . .                               | 116 |
| 8.6.6.2. Well-formedness . . . . .                          | 116 |
| 8.7. Unrolling . . . . .                                    | 116 |
| 9. P4 callables . . . . .                                   | 117 |
| 9.1. Parameters . . . . .                                   | 118 |
| 9.1.1. Type checking . . . . .                              | 119 |
| 9.1.2. Well-formedness . . . . .                            | 120 |
| 9.2. Callable definitions (callable constructors) . . . . . | 121 |
| 9.2.1. Well-formedness . . . . .                            | 122 |
| 9.3. Actions . . . . .                                      | 122 |

|                                           |     |
|-------------------------------------------|-----|
| 9.3.1. Well-formedness . . . . .          | 123 |
| 9.4. Functions . . . . .                  | 124 |
| 9.4.1. User-defined functions . . . . .   | 124 |
| 9.4.1.1. Well-formedness . . . . .        | 125 |
| 9.4.2. Extern functions . . . . .         | 125 |
| 9.4.2.1. Well-formedness . . . . .        | 126 |
| 9.5. Methods . . . . .                    | 126 |
| 9.5.1. Extern methods . . . . .           | 127 |
| 9.5.1.1. Well-formedness . . . . .        | 128 |
| 9.5.2. Parser apply methods . . . . .     | 129 |
| 9.5.2.1. Well-formedness . . . . .        | 129 |
| 9.5.3. Control apply methods . . . . .    | 129 |
| 9.5.3.1. Well-formedness . . . . .        | 130 |
| 9.5.4. Table apply methods . . . . .      | 130 |
| 9.5.4.1. Well-formedness . . . . .        | 131 |
| 9.5.5. Built-in methods . . . . .         | 131 |
| 10. P4 objects and constructors . . . . . | 131 |
| 10.1. Objects . . . . .                   | 131 |
| 10.1.1. Fully-qualified names . . . . .   | 131 |
| 10.2. Constructors . . . . .              | 132 |
| 10.2.1. Constructor parameters . . . . .  | 132 |
| 10.2.1.1. Well-formedness . . . . .       | 133 |
| 10.2.2. Constructor definitions . . . . . | 134 |
| 10.2.2.1. Well-formedness . . . . .       | 134 |
| 10.3. Extern objects . . . . .            | 134 |
| 10.3.1. Well-formedness . . . . .         | 135 |
| 10.3.2. Instantiation . . . . .           | 136 |
| 10.4. Parser objects . . . . .            | 137 |
| 10.4.1. Well-formedness . . . . .         | 138 |
| 10.4.2. Instantiation . . . . .           | 138 |
| 10.5. Control objects . . . . .           | 139 |
| 10.5.1. Well-formedness . . . . .         | 140 |
| 10.5.2. Instantiation . . . . .           | 141 |
| 10.6. Table objects . . . . .             | 141 |
| 10.6.1. Well-formedness . . . . .         | 143 |
| 10.7. Parser value set objects . . . . .  | 143 |
| 10.8. Package objects . . . . .           | 144 |
| 10.8.1. Well-formedness . . . . .         | 145 |
| 10.8.2. Instantiation . . . . .           | 145 |
| 11. Declarations . . . . .                | 146 |
| 11.1. Semantics of declarations . . . . . | 147 |
| 11.1.1. Type checking . . . . .           | 147 |
| 11.1.2. Compile-time evaluation . . . . . | 148 |
| 11.1.3. Runtime evaluation . . . . .      | 149 |
| 11.2. Variable declarations . . . . .     | 149 |
| 11.2.1. Type checking . . . . .           | 150 |
| 11.2.2. Runtime evaluation . . . . .      | 151 |
| 11.3. Constant declarations . . . . .     | 152 |
| 11.3.1. Type checking . . . . .           | 153 |
| 11.3.2. Compile-time evaluation . . . . . | 154 |

|                                                                  |     |
|------------------------------------------------------------------|-----|
| 11.3.3. Runtime evaluation .....                                 | 154 |
| 11.4. Instantiations .....                                       | 154 |
| 11.4.1. Objects with abstract methods .....                      | 155 |
| 11.4.1.1. Type checking.....                                     | 156 |
| 11.4.1.2. Compile-time evaluation.....                           | 158 |
| 11.4.2. Type checking .....                                      | 158 |
| 11.4.3. Compile-time evaluation .....                            | 161 |
| 11.5. Function declarations .....                                | 163 |
| 11.5.1. Type checking .....                                      | 163 |
| 11.5.2. Compile-time evaluation .....                            | 164 |
| 11.6. Action declarations .....                                  | 165 |
| 11.6.1. Type checking .....                                      | 165 |
| 11.6.2. Compile-time evaluation .....                            | 166 |
| 11.7. Error declarations .....                                   | 167 |
| 11.7.1. Type checking .....                                      | 167 |
| 11.7.2. Compile-time evaluation .....                            | 167 |
| 11.8. Match kind declarations .....                              | 168 |
| 11.8.1. Type checking .....                                      | 168 |
| 11.8.2. Compile-time evaluation .....                            | 169 |
| 11.9. Extern function declarations .....                         | 169 |
| 11.9.1. Type checking .....                                      | 169 |
| 11.9.2. Compile-time evaluation .....                            | 170 |
| 11.10. Extern object declarations .....                          | 170 |
| 11.10.1. Extern methods .....                                    | 171 |
| 11.10.1.1. Type checking.....                                    | 171 |
| 11.10.2. Extern constructors .....                               | 172 |
| 11.10.2.1. Type checking.....                                    | 172 |
| 11.10.3. Type checking .....                                     | 173 |
| 11.10.4. Compile-time evaluation .....                           | 175 |
| 11.11. Parser declarations .....                                 | 176 |
| 11.11.1. Type checking .....                                     | 176 |
| 11.11.2. Compile-time evaluation .....                           | 178 |
| 11.12. Control declarations .....                                | 178 |
| 11.12.1. Type checking .....                                     | 178 |
| 11.12.2. Compile-time evaluation .....                           | 180 |
| 11.13. Enum type declaration .....                               | 180 |
| 11.13.1. Enum type declarations without an underlying type ..... | 181 |
| 11.13.1.1. Type checking.....                                    | 181 |
| 11.13.1.2. Compile-time evaluation .....                         | 181 |
| 11.13.2. Enum type declarations with an underlying type .....    | 182 |
| 11.13.2.1. Type checking.....                                    | 182 |
| 11.13.2.2. Compile-time evaluation .....                         | 183 |
| 11.14. Struct type declaration .....                             | 184 |
| 11.14.1. Type checking .....                                     | 184 |
| 11.14.2. Compile-time evaluation .....                           | 185 |
| 11.15. Header type declaration.....                              | 185 |
| 11.15.1. Type checking .....                                     | 186 |
| 11.15.2. Compile-time evaluation.....                            | 187 |
| 11.16. Header union type declaration .....                       | 187 |
| 11.16.1. Type checking .....                                     | 187 |

|                                                     |     |
|-----------------------------------------------------|-----|
| 11.16.2. Compile-time evaluation . . . . .          | 188 |
| 11.17. Typedef declaration . . . . .                | 189 |
| 11.17.1. <code>typedef</code> declaration . . . . . | 189 |
| 11.17.1.1. Type checking. . . . .                   | 189 |
| 11.17.1.2. Compile-time evaluation . . . . .        | 190 |
| 11.17.2. New type declaration. . . . .              | 191 |
| 11.17.2.1. Type checking. . . . .                   | 191 |
| 11.17.2.2. Compile-time evaluation . . . . .        | 192 |
| 11.18. Parser type declaration . . . . .            | 192 |
| 11.18.1. Type checking . . . . .                    | 192 |
| 11.18.2. Compile-time evaluation . . . . .          | 193 |
| 11.19. Control type declaration. . . . .            | 193 |
| 11.19.1. Type checking . . . . .                    | 193 |
| 11.19.2. Compile-time evaluation . . . . .          | 194 |
| 11.20. Package type declaration . . . . .           | 194 |
| 11.20.1. Type checking . . . . .                    | 194 |
| 11.20.2. Compile-time evaluation . . . . .          | 195 |
| 12. L-values . . . . .                              | 196 |
| 12.1. Semantics of l-values . . . . .               | 196 |
| 12.1.1. Type checking . . . . .                     | 196 |
| 12.1.2. Runtime evaluation . . . . .                | 197 |
| 12.1.2.1. Creation. . . . .                         | 197 |
| 12.1.2.2. Read . . . . .                            | 197 |
| 12.1.2.3. Write. . . . .                            | 197 |
| 12.2. Identifiers . . . . .                         | 198 |
| 12.2.1. Type checking . . . . .                     | 198 |
| 12.2.2. Creation . . . . .                          | 198 |
| 12.2.3. Read . . . . .                              | 198 |
| 12.2.4. Write . . . . .                             | 198 |
| 12.3. Member accesses . . . . .                     | 199 |
| 12.3.1. Type checking . . . . .                     | 199 |
| 12.3.2. Creation . . . . .                          | 199 |
| 12.3.3. Read . . . . .                              | 200 |
| 12.3.4. Write . . . . .                             | 201 |
| 12.4. Index accesses . . . . .                      | 202 |
| 12.4.1. Type checking . . . . .                     | 202 |
| 12.4.2. Creation . . . . .                          | 203 |
| 12.4.3. Read . . . . .                              | 204 |
| 12.4.4. Write . . . . .                             | 204 |
| 12.5. Bit-slice accesses . . . . .                  | 205 |
| 12.5.1. Type checking . . . . .                     | 205 |
| 12.5.2. Creation . . . . .                          | 206 |
| 12.5.3. Read . . . . .                              | 206 |
| 12.5.4. Write . . . . .                             | 207 |
| 12.6. Parenthesized l-values . . . . .              | 207 |
| 12.6.1. Type checking . . . . .                     | 207 |
| 12.6.2. Creation . . . . .                          | 207 |
| 13. Statements . . . . .                            | 207 |
| 13.1. Semantics of statements . . . . .             | 208 |
| 13.1.1. Type checking . . . . .                     | 208 |

|                                                   |     |
|---------------------------------------------------|-----|
| 13.1.2. Compile-time evaluation . . . . .         | 209 |
| 13.1.3. Runtime evaluation . . . . .              | 209 |
| 13.2. Empty statements . . . . .                  | 210 |
| 13.2.1. Type checking . . . . .                   | 210 |
| 13.2.2. Compile-time evaluation . . . . .         | 210 |
| 13.2.3. Runtime evaluation . . . . .              | 210 |
| 13.3. Assignment statements . . . . .             | 211 |
| 13.3.1. Type checking . . . . .                   | 211 |
| 13.3.2. Compile-time evaluation . . . . .         | 212 |
| 13.3.3. Runtime evaluation . . . . .              | 212 |
| 13.4. Call statements . . . . .                   | 213 |
| 13.4.1. Type checking . . . . .                   | 213 |
| 13.4.2. Compile-time evaluation . . . . .         | 215 |
| 13.4.3. Runtime evaluation . . . . .              | 215 |
| 13.5. Direct type invocation . . . . .            | 215 |
| 13.5.1. Type checking . . . . .                   | 216 |
| 13.5.2. Compile-time evaluation . . . . .         | 217 |
| 13.6. Return statements . . . . .                 | 218 |
| 13.6.1. Type checking . . . . .                   | 219 |
| 13.6.2. Compile-time evaluation . . . . .         | 219 |
| 13.6.3. Runtime evaluation . . . . .              | 220 |
| 13.7. Exit statements . . . . .                   | 220 |
| 13.7.1. Type checking . . . . .                   | 221 |
| 13.7.2. Compile-time evaluation . . . . .         | 221 |
| 13.7.3. Runtime evaluation . . . . .              | 221 |
| 13.8. Block statements . . . . .                  | 221 |
| 13.8.1. Type checking . . . . .                   | 222 |
| 13.8.2. Compile-time evaluation . . . . .         | 224 |
| 13.8.3. Runtime evaluation . . . . .              | 225 |
| 13.9. Conditional statements . . . . .            | 226 |
| 13.9.1. Type checking . . . . .                   | 227 |
| 13.9.2. Compile-time evaluation . . . . .         | 227 |
| 13.9.3. Runtime evaluation . . . . .              | 228 |
| 13.10. For statements . . . . .                   | 229 |
| 13.10.1. 3-clause <b>for</b> statements . . . . . | 230 |
| 13.10.1.1. Type checking . . . . .                | 230 |
| 13.10.1.2. Compile-time evaluation . . . . .      | 233 |
| 13.10.1.3. Runtime evaluation . . . . .           | 233 |
| 13.10.2. <b>for-in</b> statements . . . . .       | 237 |
| 13.10.2.1. Type checking . . . . .                | 237 |
| 13.10.2.2. Compile-time evaluation . . . . .      | 239 |
| 13.10.2.3. Runtime evaluation . . . . .           | 239 |
| 13.11. Break statements . . . . .                 | 242 |
| 13.11.1. Type checking . . . . .                  | 242 |
| 13.11.2. Compile-time evaluation . . . . .        | 242 |
| 13.11.3. Runtime evaluation . . . . .             | 242 |
| 13.12. Continue statements . . . . .              | 242 |
| 13.12.1. Type checking . . . . .                  | 243 |
| 13.12.2. Compile-time evaluation . . . . .        | 243 |
| 13.12.3. Runtime evaluation . . . . .             | 243 |

|                                                                   |     |
|-------------------------------------------------------------------|-----|
| 13.13. Switch statements . . . . .                                | 243 |
| 13.13.1. Notes common to all switch statements . . . . .          | 244 |
| 13.13.2. Switch statement on match-action table result. . . . .   | 244 |
| 13.13.2.1. Type checking. . . . .                                 | 244 |
| 13.13.2.2. Compile-time evaluation . . . . .                      | 246 |
| 13.13.2.3. Runtime evaluation . . . . .                           | 247 |
| 13.13.3. Switch statement on numeric or enumerated type . . . . . | 249 |
| 13.13.3.1. Type checking. . . . .                                 | 249 |
| 13.13.3.2. Compile-time evaluation . . . . .                      | 251 |
| 13.13.3.3. Runtime evaluation . . . . .                           | 251 |
| 14. Expressions . . . . .                                         | 254 |
| 14.1. Semantics of expressions. . . . .                           | 255 |
| 14.1.1. Type checking . . . . .                                   | 255 |
| 14.1.2. Local compile-time evaluation . . . . .                   | 256 |
| 14.1.3. Compile-time evaluation . . . . .                         | 256 |
| 14.1.4. Runtime evaluation . . . . .                              | 257 |
| 14.2. Literal expressions . . . . .                               | 258 |
| 14.2.1. Type checking . . . . .                                   | 259 |
| 14.2.2. Local compile-time evaluation . . . . .                   | 259 |
| 14.2.3. Compile-time evaluation . . . . .                         | 260 |
| 14.2.4. Runtime evaluation . . . . .                              | 260 |
| 14.3. Reference expressions . . . . .                             | 261 |
| 14.3.1. Type checking . . . . .                                   | 261 |
| 14.3.2. Local compile-time evaluation . . . . .                   | 262 |
| 14.3.3. Compile-time evaluation . . . . .                         | 262 |
| 14.3.4. Runtime evaluation . . . . .                              | 263 |
| 14.4. Default expressions. . . . .                                | 264 |
| 14.4.1. Type checking . . . . .                                   | 264 |
| 14.4.2. Local compile-time evaluation . . . . .                   | 264 |
| 14.4.3. Compile-time evaluation . . . . .                         | 264 |
| 14.4.4. Runtime evaluation . . . . .                              | 265 |
| 14.5. Unary expressions. . . . .                                  | 265 |
| 14.5.1. Type checking . . . . .                                   | 265 |
| 14.5.1.1. Negation . . . . .                                      | 265 |
| 14.5.1.2. Bitwise complement . . . . .                            | 265 |
| 14.5.1.3. Plus and minus. . . . .                                 | 266 |
| 14.5.2. Local compile-time evaluation . . . . .                   | 266 |
| 14.5.3. Compile-time evaluation . . . . .                         | 266 |
| 14.5.4. Runtime evaluation . . . . .                              | 267 |
| 14.6. Binary expressions . . . . .                                | 267 |
| 14.6.1. Type checking . . . . .                                   | 267 |
| 14.6.1.1. Plus, minus, and multiplication . . . . .               | 268 |
| 14.6.1.2. Saturating plus and minus . . . . .                     | 268 |
| 14.6.1.3. Division and modulo . . . . .                           | 269 |
| 14.6.1.4. Shift left and right . . . . .                          | 269 |
| 14.6.1.5. Equality and inequality . . . . .                       | 270 |
| 14.6.1.6. Comparison . . . . .                                    | 271 |
| 14.6.1.7. Bitwise and, xor, and or . . . . .                      | 271 |
| 14.6.1.8. Concatenation . . . . .                                 | 271 |
| 14.6.1.9. Logical and, and or . . . . .                           | 272 |

|                                              |     |
|----------------------------------------------|-----|
| 14.6.2. Local compile-time evaluation .....  | 272 |
| 14.6.3. Compile-time evaluation .....        | 273 |
| 14.6.4. Runtime evaluation .....             | 274 |
| 14.7. Ternary expressions .....              | 275 |
| 14.7.1. Type checking .....                  | 276 |
| 14.7.2. Local compile-time evaluation .....  | 276 |
| 14.7.3. Compile-time evaluation .....        | 277 |
| 14.7.4. Runtime evaluation .....             | 277 |
| 14.8. Cast expressions .....                 | 278 |
| 14.8.1. Type checking .....                  | 278 |
| 14.8.2. Local compile-time evaluation .....  | 278 |
| 14.8.3. Compile-time evaluation .....        | 279 |
| 14.8.4. Runtime evaluation .....             | 279 |
| 14.9. Invalid header expressions .....       | 279 |
| 14.9.1. Type checking .....                  | 279 |
| 14.9.2. Local compile-time evaluation .....  | 280 |
| 14.9.3. Compile-time evaluation .....        | 280 |
| 14.9.4. Runtime evaluation .....             | 280 |
| 14.10. Sequence expressions .....            | 280 |
| 14.10.1. Type checking .....                 | 281 |
| 14.10.2. Local compile-time evaluation ..... | 282 |
| 14.10.3. Compile-time evaluation .....       | 283 |
| 14.10.4. Runtime evaluation .....            | 283 |
| 14.11. Record expressions .....              | 284 |
| 14.11.1. Type checking .....                 | 284 |
| 14.11.2. Local compile-time evaluation ..... | 286 |
| 14.11.3. Compile-time evaluation .....       | 286 |
| 14.11.4. Runtime evaluation .....            | 287 |
| 14.12. Error access expression .....         | 287 |
| 14.12.1. Type checking .....                 | 288 |
| 14.12.2. Local compile-time evaluation ..... | 288 |
| 14.12.3. Compile-time evaluation .....       | 288 |
| 14.12.4. Runtime evaluation .....            | 288 |
| 14.13. Member access expressions .....       | 289 |
| 14.13.1. Type checking .....                 | 289 |
| 14.13.2. Local compile-time evaluation ..... | 291 |
| 14.13.3. Compile-time evaluation .....       | 292 |
| 14.13.4. Runtime evaluation .....            | 293 |
| 14.14. Index access expressions .....        | 295 |
| 14.14.1. Type checking .....                 | 296 |
| 14.14.2. Local compile-time evaluation ..... | 297 |
| 14.14.3. Compile-time evaluation .....       | 297 |
| 14.14.4. Runtime evaluation .....            | 298 |
| 14.15. Bitslice access expressions .....     | 299 |
| 14.15.1. Type checking .....                 | 299 |
| 14.15.2. Local compile-time evaluation ..... | 300 |
| 14.15.3. Compile-time evaluation .....       | 300 |
| 14.15.4. Runtime evaluation .....            | 301 |
| 14.16. Call expressions .....                | 301 |
| 14.16.1. Type checking .....                 | 302 |

|                                                          |     |
|----------------------------------------------------------|-----|
| 14.16.2. Local compile-time evaluation . . . . .         | 304 |
| 14.16.3. Compile-time evaluation . . . . .               | 306 |
| 14.16.4. Runtime evaluation . . . . .                    | 307 |
| 14.17. Parenthesized expressions . . . . .               | 308 |
| 14.17.1. Type checking . . . . .                         | 308 |
| 14.17.2. Local compile-time evaluation . . . . .         | 309 |
| 14.17.3. Compile-time evaluation . . . . .               | 309 |
| 14.17.4. Runtime evaluation . . . . .                    | 309 |
| 15. Abstract parser machine . . . . .                    | 309 |
| 15.1. Parser state machine . . . . .                     | 310 |
| 15.1.1. Sub-parsers . . . . .                            | 310 |
| 15.1.2. Runtime evaluation of a parser . . . . .         | 312 |
| 15.1.3. Parser state transitions . . . . .               | 313 |
| 15.2. Parser local declarations . . . . .                | 314 |
| 15.2.1. Semantics of parser local declarations . . . . . | 314 |
| 15.2.1.1. Type checking . . . . .                        | 314 |
| 15.2.1.2. Compile-time evaluation . . . . .              | 315 |
| 15.2.1.3. Runtime evaluation . . . . .                   | 316 |
| 15.2.2. Constant declarations . . . . .                  | 317 |
| 15.2.2.1. Type checking . . . . .                        | 317 |
| 15.2.2.2. Compile-time evaluation . . . . .              | 317 |
| 15.2.2.3. Runtime evaluation . . . . .                   | 317 |
| 15.2.3. Instantiations . . . . .                         | 318 |
| 15.2.3.1. Type checking . . . . .                        | 318 |
| 15.2.3.2. Compile-time evaluation . . . . .              | 318 |
| 15.2.4. Variable declarations . . . . .                  | 318 |
| 15.2.4.1. Type checking . . . . .                        | 318 |
| 15.2.4.2. Compile-time evaluation . . . . .              | 318 |
| 15.2.4.3. Runtime evaluation . . . . .                   | 318 |
| 15.2.5. Parser value set declarations . . . . .          | 319 |
| 15.2.5.1. Type checking . . . . .                        | 319 |
| 15.2.5.2. Compile-time evaluation . . . . .              | 319 |
| 15.3. Parser states . . . . .                            | 320 |
| 15.3.1. Type checking . . . . .                          | 320 |
| 15.3.2. Compile-time evaluation . . . . .                | 322 |
| 15.3.3. Runtime evaluation . . . . .                     | 323 |
| 15.4. Parser statements . . . . .                        | 323 |
| 15.4.1. Semantics of parser statements . . . . .         | 324 |
| 15.4.1.1. Type checking . . . . .                        | 324 |
| 15.4.1.2. Compile-time evaluation . . . . .              | 325 |
| 15.4.1.3. Runtime evaluation . . . . .                   | 326 |
| 15.4.2. Constant declaration . . . . .                   | 327 |
| 15.4.2.1. Type checking . . . . .                        | 327 |
| 15.4.2.2. Compile-time evaluation . . . . .              | 327 |
| 15.4.2.3. Runtime evaluation . . . . .                   | 327 |
| 15.4.3. Variable declaration . . . . .                   | 328 |
| 15.4.3.1. Type checking . . . . .                        | 328 |
| 15.4.3.2. Compile-time evaluation . . . . .              | 328 |
| 15.4.3.3. Runtime evaluation . . . . .                   | 328 |
| 15.4.4. Empty statement . . . . .                        | 328 |



|                                                          |     |
|----------------------------------------------------------|-----|
| 15.4.4.1. Type checking . . . . .                        | 328 |
| 15.4.4.2. Compile-time evaluation. . . . .               | 329 |
| 15.4.4.3. Runtime evaluation . . . . .                   | 329 |
| 15.4.5. Assignment statement. . . . .                    | 329 |
| 15.4.5.1. Type checking . . . . .                        | 329 |
| 15.4.5.2. Compile-time evaluation. . . . .               | 329 |
| 15.4.5.3. Runtime evaluation . . . . .                   | 330 |
| 15.4.6. Call statement . . . . .                         | 330 |
| 15.4.6.1. Type checking . . . . .                        | 330 |
| 15.4.6.2. Compile-time evaluation. . . . .               | 330 |
| 15.4.6.3. Runtime evaluation . . . . .                   | 331 |
| 15.4.7. Direct type invocation . . . . .                 | 331 |
| 15.4.7.1. Type checking . . . . .                        | 331 |
| 15.4.7.2. Compile-time evaluation. . . . .               | 331 |
| 15.4.8. Block statement . . . . .                        | 332 |
| 15.4.8.1. Type checking . . . . .                        | 332 |
| 15.4.8.2. Compile-time evaluation. . . . .               | 332 |
| 15.4.8.3. Runtime evaluation . . . . .                   | 332 |
| 15.4.9. Conditional statement . . . . .                  | 333 |
| 15.4.9.1. Type checking . . . . .                        | 333 |
| 15.4.9.2. Compile-time evaluation. . . . .               | 334 |
| 15.4.9.3. Runtime evaluation . . . . .                   | 334 |
| 15.5. Parser transition statements . . . . .             | 335 |
| 15.5.1. Type checking . . . . .                          | 336 |
| 15.5.2. Runtime evaluation . . . . .                     | 336 |
| 15.6. Parser select expression. . . . .                  | 337 |
| 15.6.1. Type checking . . . . .                          | 339 |
| 15.6.2. Runtime evaluation . . . . .                     | 342 |
| 15.7. <i>verify</i> . . . . .                            | 344 |
| 15.8. Packet data extraction . . . . .                   | 345 |
| 15.8.1. Fixed-width extraction . . . . .                 | 345 |
| 15.8.2. Variable-width extraction . . . . .              | 346 |
| 15.8.3. Lookahead . . . . .                              | 347 |
| 15.8.4. Skipping bits . . . . .                          | 348 |
| 16. Abstract control machine . . . . .                   | 349 |
| 16.1. Match-action pipeline machine . . . . .            | 349 |
| 16.1.1. Sub-controls . . . . .                           | 349 |
| 16.1.2. Runtime evaluation of a control. . . . .         | 350 |
| 16.2. Control local declarations . . . . .               | 351 |
| 16.2.1. Semantics of parser local declarations . . . . . | 351 |
| 16.2.1.1. Type checking . . . . .                        | 351 |
| 16.2.1.2. Compile-time evaluation. . . . .               | 352 |
| 16.2.1.3. Runtime evaluation . . . . .                   | 353 |
| 16.2.2. Constant declarations . . . . .                  | 354 |
| 16.2.2.1. Type checking . . . . .                        | 354 |
| 16.2.2.2. Compile-time evaluation. . . . .               | 355 |
| 16.2.2.3. Runtime evaluation . . . . .                   | 355 |
| 16.2.3. Instantiations. . . . .                          | 355 |
| 16.2.3.1. Type checking . . . . .                        | 355 |
| 16.2.3.2. Compile-time evaluation. . . . .               | 355 |

|                                                              |     |
|--------------------------------------------------------------|-----|
| 16.2.4. Variable declarations . . . . .                      | 355 |
| 16.2.4.1. Type checking . . . . .                            | 355 |
| 16.2.4.2. Compile-time evaluation . . . . .                  | 356 |
| 16.2.4.3. Runtime evaluation . . . . .                       | 356 |
| 16.2.5. Action declarations . . . . .                        | 356 |
| 16.2.5.1. Type checking . . . . .                            | 356 |
| 16.2.5.2. Compile-time evaluation . . . . .                  | 356 |
| 16.3. Match-action tables . . . . .                          | 357 |
| 16.3.1. Semantics of match-action table properties . . . . . | 357 |
| 16.3.1.1. Type checking . . . . .                            | 357 |
| 16.3.1.2. Compile-time evaluation . . . . .                  | 358 |
| 16.3.2. Table keys . . . . .                                 | 359 |
| 16.3.2.1. Type checking . . . . .                            | 360 |
| 16.3.2.2. Compile-time evaluation . . . . .                  | 362 |
| 16.3.2.3. Runtime evaluation . . . . .                       | 362 |
| 16.3.3. Table actions . . . . .                              | 364 |
| 16.3.3.1. Type checking . . . . .                            | 365 |
| 16.3.3.2. Compile-time evaluation . . . . .                  | 367 |
| 16.3.4. Table default actions . . . . .                      | 368 |
| 16.3.4.1. Type checking . . . . .                            | 368 |
| 16.3.4.2. Compile-time evaluation . . . . .                  | 370 |
| 16.3.5. Table entries . . . . .                              | 370 |
| 16.3.6. Table custom properties . . . . .                    | 371 |
| 16.3.7. Match-action table invocation . . . . .              | 371 |
| 17. Casting . . . . .                                        | 371 |
| 17.1. Explicit casts . . . . .                               | 371 |
| 17.2. Implicit casts . . . . .                               | 378 |
| 17.3. Cast insertion . . . . .                               | 385 |
| 17.3.1. Casts to match expected type . . . . .               | 385 |
| 17.3.2. Casts to ensure type equality . . . . .              | 385 |
| 17.4. Performing casts . . . . .                             | 386 |
| 18. Calls . . . . .                                          | 395 |
| 18.1. Call targets . . . . .                                 | 395 |
| 18.2. Overload resolution . . . . .                          | 398 |
| 18.2.1. Positional arguments . . . . .                       | 399 |
| 18.2.2. Named arguments . . . . .                            | 400 |
| 18.3. Callee resolution . . . . .                            | 400 |
| 18.3.1. Resolving constructors . . . . .                     | 401 |
| 18.3.2. Resolving callables . . . . .                        | 403 |
| 18.3.2.1. Actions . . . . .                                  | 403 |
| 18.3.2.2. Functions . . . . .                                | 404 |
| 18.3.2.3. Built-in methods . . . . .                         | 405 |
| 18.3.2.4. Extern methods . . . . .                           | 408 |
| 18.3.2.5. Parser apply methods . . . . .                     | 410 |
| 18.3.2.6. Control apply methods . . . . .                    | 411 |
| 18.3.2.7. Table apply methods . . . . .                      | 413 |
| 18.4. Call convention . . . . .                              | 414 |
| 18.5. Runtime evaluation of constructor calls . . . . .      | 414 |
| 18.6. Runtime evaluation of callable calls . . . . .         | 414 |
| 18.6.1. Actions . . . . .                                    | 414 |

|                                                                                 |     |
|---------------------------------------------------------------------------------|-----|
| 18.6.2. Functions .....                                                         | 415 |
| 18.6.3. Built-in methods .....                                                  | 415 |
| 18.6.4. Extern methods .....                                                    | 415 |
| 18.6.5. Parser apply methods .....                                              | 415 |
| 18.6.6. Control apply methods .....                                             | 415 |
| 18.6.7. Table apply methods .....                                               | 416 |
| 19. Operations .....                                                            | 416 |
| 19.1. Unary operations .....                                                    | 416 |
| 19.2. Binary operations .....                                                   | 417 |
| 19.3. Default values .....                                                      | 437 |
| 20. Annotations .....                                                           | 439 |
| 20.1. Bodies of Unstructured Annotations .....                                  | 440 |
| 20.1.1. Structured Annotation Examples .....                                    | 441 |
| 20.2. Predefined annotations .....                                              | 443 |
| 20.2.1. Optional parameter annotations .....                                    | 443 |
| 20.2.2. Annotations on the table action list .....                              | 443 |
| 20.2.3. Control-plane API annotations .....                                     | 443 |
| 20.2.3.1. Restrictions .....                                                    | 444 |
| 20.2.4. Concurrency control annotations .....                                   | 444 |
| 20.2.5. Branch prediction annotations .....                                     | 444 |
| 20.2.6. Value set annotations .....                                             | 444 |
| 20.2.7. Extern function/method annotations .....                                | 445 |
| 20.2.8. Deprecated annotation .....                                             | 445 |
| 20.2.9. No warnings annotation .....                                            | 445 |
| Appendix A: Revision History .....                                              | 446 |
| A.1. Summary of changes made in unreleased version .....                        | 446 |
| A.2. Summary of changes made in version 1.2.5, released October 11, 2024 .....  | 446 |
| A.3. Summary of changes made in version 1.2.4, released May 15, 2023 .....      | 446 |
| A.4. Summary of changes made in version 1.2.3, released July 11, 2022 .....     | 447 |
| A.5. Summary of changes made in version 1.2.2, released May 17, 2021 .....      | 448 |
| A.6. Summary of changes made in version 1.2.1, released June 11, 2020 .....     | 448 |
| A.7. Summary of changes made in version 1.2.0, released October 14, 2019 .....  | 449 |
| A.8. Summary of changes made in version 1.1.0, released November 26, 2017 ..... | 449 |
| A.9. Initial version 1.0.0, released May 17, 2017 .....                         | 450 |
| Appendix B: P4 reserved keywords .....                                          | 450 |
| Appendix C: P4 reserved annotations .....                                       | 450 |
| Appendix D: P4 core library .....                                               | 451 |
| Appendix E: P4 grammar .....                                                    | 452 |

## *Abstract*

P4 is a language for programming the data plane of network devices. This document provides a precise definition of the P4<sub>16</sub> language, which is the 2016 revision of the P4 language (<http://p4.org>). The target audience for this document includes developers who want to write compilers, simulators, IDEs, and debuggers for P4 programs. This document may also be of interest to P4 programmers who are interested in understanding the syntax and semantics of the language at a deeper level.

# 1. Scope

This specification document defines the structure and interpretation of programs in the P4<sub>16</sub> language. It defines the syntax, semantic rules, and requirements for conformant implementations of the language.

It does not define:

- Mechanisms by which P4 programs are compiled, loaded, and executed on packet-processing systems,
- Mechanisms by which data are received by one packet-processing system and delivered to another system,
- Mechanisms by which the control plane manages the match-action tables and other stateful objects defined by P4 programs,
- The size or complexity of P4 programs,
- The minimal requirements of packet-processing systems that are capable of providing a conformant implementation.

It is understood that some implementations may be unable to implement the behavior defined here in all cases, or may provide options to eliminate some safety guarantees in exchange for better performance or handling larger programs. They should document where they deviate from this specification.

# 2. Terms, definitions, and symbols

Throughout this document, the following terms will be used:

- **Architecture:** A set of P4-programmable components and the data plane interfaces between them.
- **Control plane:** A class of algorithms and the corresponding input and output data that are concerned with the provisioning and configuration of the data plane.
- **Data plane:** A class of algorithms that describe transformations on packets by packet-processing systems.
- **Metadata:** Intermediate data generated during execution of a P4 program.
- **Packet:** A network packet is a formatted unit of data carried by a packet-switched network.
- **Packet header:** Formatted data at the beginning of a packet. A given packet may contain a sequence of packet headers representing different network protocols.
- **Packet payload:** Packet data that follows the packet headers.
- **Packet-processing system:** A data-processing system designed for processing network packets. In general, packet-processing systems implement control plane and data plane algorithms.
- **Target:** A packet-processing system capable of executing a P4 program.

All terms defined explicitly in this document should not be understood to refer implicitly to similar terms defined elsewhere. Conversely, any terms not defined explicitly in this document should be interpreted

according to generally recognizable sources—e.g., IETF RFCs.

### 3. Overview




Figure 1. Traditional switches vs. programmable switches.

P4 is a language for expressing how packets are processed by the data plane of a programmable forwarding element such as a hardware or software switch, network interface card, router, or network appliance. The name P4 comes from the original paper that introduced the language, "Programming Protocol-independent Packet Processors," <https://arxiv.org/pdf/1312.1719.pdf>. While P4 was initially designed for programming switches, its scope has been broadened to cover a large variety of devices. In the rest of this document we use the generic term *target* for all such devices.

Many targets implement both a control plane and a data plane. P4 is designed to specify only the data plane functionality of the target. P4 programs also partially define the interface by which the control plane and the data-plane communicate, but P4 cannot be used to describe the control-plane functionality of the target. In the rest of this document, when we talk about P4 as "programming a target", we mean "programming the data plane of a target".

As a concrete example of a target, Figure 1 illustrates the difference between a traditional fixed-function switch and a P4-programmable switch. In a traditional switch the manufacturer defines the data-plane functionality. The control-plane controls the data plane by managing entries in tables (e.g. routing tables), configuring specialized objects (e.g. meters), and by processing control-packets (e.g. routing protocol packets) or asynchronous events, such as link state changes or learning notifications.

A P4-programmable switch differs from a traditional switch in two essential ways:

- The data plane functionality is not fixed in advance but is defined by a P4 program. The data plane is configured at initialization time to implement the functionality described by the P4 program (shown by the long red arrow) and has no built-in knowledge of existing network protocols.
- The control plane communicates with the data plane using the same channels as in a fixed-function device, but the set of tables and other objects in the data plane are no longer fixed, since they are defined by a P4 program. The P4 compiler generates the API that the control plane uses to

communicate with the data plane.

Hence, P4 can be said to be protocol independent, but it enables programmers to express a rich set of protocols and other data plane behaviors.




Figure 2. Programming a target with P4.

The core abstractions provided by the P4 language are:

- **Header types** describe the format (the set of fields and their sizes) of each header within a packet.
- **Parsers** describe the permitted sequences of headers within received packets, how to identify those header sequences, and the headers and fields to extract from packets.
- **Tables** associate user-defined keys with actions. P4 tables generalize traditional switch tables; they can be used to implement routing tables, flow lookup tables, access-control lists, and other user-defined table types, including complex multi-variable decisions.
- **Actions** are code fragments that describe how packet header fields and metadata are manipulated. Actions can include data, which is supplied by the control-plane at runtime.
- **Match-action units** perform the following sequence of operations:
  - Construct lookup keys from packet fields or computed metadata,
  - Perform table lookup using the constructed key, choosing an action (including the associated data) to execute, and
  - Finally, execute the selected action.
- **Control flow** expresses an imperative program that describes packet-processing on a target, including the data-dependent sequence of match-action unit invocations. Deparsing (packet reassembly) can also be performed using a control flow.
- **Extern objects** are architecture-specific constructs that can be manipulated by P4 programs through well-defined APIs, but whose internal behavior is hard-wired (e.g., checksum units) and hence not programmable using P4.
- **User-defined metadata**: user-defined data structures associated with each packet.
- **Intrinsic metadata**: metadata provided by the architecture associated with each packet—e.g., the input port where a packet has been received.

Figure 2 shows a typical tool workflow when programming a target using P4.

Target manufacturers provide the hardware or software implementation framework, an architecture definition, and a P4 compiler for that target. P4 programmers write programs for a specific architecture, which defines a set of P4-programmable components on the target as well as their external data plane

interfaces.

Compiling a set of P4 programs produces two artifacts:

- a data plane configuration that implements the forwarding logic described in the input program and
- an API for managing the state of the data plane objects from the control plane

P4 is a domain-specific language that is designed to be implementable on a large variety of targets including programmable network interface cards, FPGAs, software switches, and hardware ASICs. As such, the language is restricted to constructs that can be efficiently implemented on all of these platforms.

Assuming a fixed cost for table lookup operations and interactions with extern objects, all P4 programs (i.e., parsers and controls) execute a constant number of operations for each byte of an input packet received and analyzed. Although parsers may contain loops, provided some header is extracted on each cycle, the packet itself provides a bound on the total execution of the parser. In other words, under these assumptions, the computational complexity of a P4 program is linear in the total size of all headers, and never depends on the size of the state accumulated while processing data (e.g., the number of flows, or the total number of packets processed). These guarantees are necessary (but not sufficient) for enabling fast packet processing across a variety of targets.

*P4 conformance* of a target is defined as follows: if a specific target  $T$  supports only a subset of the P4 programming language, say  $P4^T$ , programs written in  $P4^T$  executed on the target should provide the exact same behavior as is described in this document. Note that P4 conformant targets can provide arbitrary P4 language extensions and `extern` elements.

## 3.1. Benefits of P4

Compared to state-of-the-art packet-processing systems (e.g., based on writing microcode on top of custom hardware), P4 provides a number of significant advantages:

- **Flexibility:** P4 makes many packet-forwarding policies expressible as programs, in contrast to traditional switches, which expose fixed-function forwarding engines to their users.
- **Expressiveness:** P4 can express sophisticated, hardware-independent packet processing algorithms using solely general-purpose operations and table look-ups. Such programs are portable across hardware targets that implement the same architectures (assuming sufficient resources are available).
- **Resource mapping and management:** P4 programs describe storage resources abstractly (e.g., IPv4 source address); compilers map such user-defined fields to available hardware resources and manage low-level details such as allocation and scheduling.
- **Software engineering:** P4 programs provide important benefits such as type checking, information hiding, and software reuse.
- **Component libraries:** Component libraries supplied by manufacturers can be used to wrap hardware-specific functions into portable high-level P4 constructs.
- **Decoupling hardware and software evolution:** Target manufacturers may use abstract architectures to further decouple the evolution of low-level architectural details from high-level processing.
- **Debugging:** Manufacturers can provide software models of an architecture to aid in the development and debugging of P4 programs.



## 3.2. P4 language evolution: comparison to previous versions (P4 v1.0/v1.1)




Figure 3. Evolution of the language between versions  $P4_{14}$  (versions 1.0 and 1.1) and  $P4_{16}$ .

Compared to  $P4_{14}$ , the earlier version of the language,  $P4_{16}$  makes a number of significant, backwards-incompatible changes to the syntax and semantics of the language. The evolution from the previous version ( $P4_{14}$ ) to the current one ( $P4_{16}$ ) is depicted in Figure 3. In particular, a large number of language features have been eliminated from the language and moved into libraries including counters, checksum units, meters, etc.

Hence, the language has been transformed from a complex language (more than 70 keywords) into a relatively small core language (less than 40 keywords, shown in Appendix B) accompanied by a library of fundamental constructs that are needed for writing most P4.

The v1.1 version of P4 introduced a language construct called `extern` that can be used to describe library elements. Many constructs defined in the v1.1 language specification will thus be transformed into such library elements (including constructs that have been eliminated from the language, such as counters and meters). Some of these `extern` objects are expected to be standardized, and they will be in the scope of a future document describing a standard library of P4 elements. In this document we provide several examples of `extern` constructs.  $P4_{16}$  also introduces and repurposes some v1.1 language constructs for describing the programmable parts of an architecture. These language constructs are: `parser`, `state`, `control`, and `package`.

One important goal of the  $P4_{16}$  language revision is to provide a **stable** language definition. In other words, we strive to ensure that all programs written in  $P4_{16}$  will remain syntactically correct and behave identically when treated as programs for future versions of the language. Moreover, if some future version of the language requires breaking backwards compatibility, we will seek to provide an easy path for migrating  $P4_{16}$  programs to the new version.



## 4. Architecture Model




Figure 4. P4 program interfaces.

The *P4 architecture* identifies the P4-programmable blocks (e.g., parser, ingress control flow, egress control flow, deparser, etc.) and their data plane interfaces.

The P4 architecture can be thought of as a contract between the program and the target. Each manufacturer must therefore provide both a P4 compiler as well as an accompanying architecture definition for their target. (We expect that P4 compilers can share a common front-end that handles all architectures). The architecture definition does not have to expose the entire programmable surface of the data plane—a manufacturer may even choose to provide multiple definitions for the same hardware device, each with different capabilities (e.g., with or without multicast support).

Figure 4 illustrates the data plane interfaces between P4-programmable blocks. It shows a target that has two programmable blocks (#1 and #2). Each block is programmed through a separate fragment of P4 code. The target interfaces with the P4 program through a set of control registers or signals. Input controls provide information to P4 programs (e.g., the input port that a packet was received from), while output controls can be written to by P4 programs to influence the target behavior (e.g., the output port where a packet has to be directed). Control registers/signals are represented in P4 as *intrinsic metadata*. P4 programs can also store and manipulate data pertaining to each packet as *user-defined metadata*.

The behavior of a P4 program can be fully described in terms of transformations that map vectors of bits to vectors of bits. To actually process a packet, the architecture model interprets the bits that the P4 program writes to intrinsic metadata. For example, to cause a packet to be forwarded on a specific output port, a P4 program may need to write the index of an output port into a dedicated control register. Similarly, to cause a packet to be dropped, a P4 program may need to set a "drop" bit into another dedicated control register. Note that the details of how intrinsic metadata are interpreted is architecture-specific.




Figure 5. P4 program invoking the services of a fixed-function object.

P4 programs can invoke services implemented by extern objects and functions provided by the architecture. Figure 5 depicts a P4 program invoking the services of a built-in checksum computation unit on a target. The implementation of the checksum unit is not specified in P4, but its interface is. In general, the interface for an extern object describes each operation it provides, as well as their parameter and return types.

In general, P4 programs are not expected to be portable across different architectures. For example, executing a P4 program that broadcasts packets by writing into a custom control register will not function correctly on a target that does not have the control register. However, P4 programs written for a given architecture should be portable across all targets that faithfully implement the corresponding model, provided there are sufficient resources.

## 4.1. Standard architectures

We expect that the P4 community will evolve a small set of standard architecture models pertaining to specific verticals. Wide adoption of such standard architectures will promote portability of P4 programs across different targets. However, defining these standard architectures is outside of the scope of this document.

## 4.2. Data plane interfaces

To describe a functional block that can be programmed in P4, the architecture includes a type declaration that specifies the interfaces between the block and the other components in the architecture. For example, the architecture might contain a declaration such as the following:

```
control MatchActionPipe<H>(in bit<4> inputPort,
                           inout H parsedHeaders,
                           out bit<4> outputPort);
```

This type declaration describes a block named `MatchActionPipe` that can be programmed using a data-dependent sequence of match-action unit invocations and other imperative constructs (indicated by the `control` keyword). The interface between the `MatchActionPipe` block and the other components of the architecture can be read off from this declaration:

- The first parameter is a 4-bit value named `inputPort`. The direction `in` indicates that this parameter is an input that cannot be modified.
- The second parameter is an object of type `H` named `parsedHeaders`, where `H` is a type variable representing the headers that will be defined later by the P4 programmer. The direction `inout` indicates that this parameter is both an input and an output.
- The third parameter is a 4-bit value named `outputPort`. The direction `out` indicates that this parameter is an output whose value is undefined initially but can be modified.

## 4.3. Extern objects and functions

P4 programs can also interact with objects and functions provided by the architecture. Such objects are

described using the `extern` construct, which describes the interfaces that such objects expose to the data-plane.

An `extern` object describes a set of methods that are implemented by an object, but not the implementation of these methods (i.e., it is similar to an abstract class in an object-oriented language). For example, the following construct could be used to describe the operations offered by an incremental checksum unit:

```
extern Checksum16 {  
    Checksum16();           // constructor  
    void clear();           // prepare unit for computation  
    void update<T>(in T data); // add data to checksum  
    void remove<T>(in T data); // remove data from existing checksum  
    bit<16> get();          // get the checksum for the data added since last clear  
}
```

## 5. Example: A very simple switch

As an example to illustrate the features of architectures, consider implementing a very simple switch in P4. We will first describe the architecture of the switch and then write a complete P4 program that specifies the data plane behavior of the switch. This example demonstrates many important features of the P4 programming language.




Figure 6. The Very Simple Switch (VSS) architecture.

We call our architecture the "Very Simple Switch" (VSS). Figure 6 is a diagram of this architecture. There is nothing inherently special about VSS—it is just a pedagogical example that illustrates how programmable switches can be described and programmed in P4. VSS has a number of fixed-function blocks (shown in cyan in our example), whose behavior is described in Section 5.2. The white blocks are programmable using P4.

VSS receives packets through one of 8 input Ethernet ports, through a recirculation channel, or from a port connected directly to the CPU. VSS has one single parser, feeding into a single match-action pipeline, which feeds into a single deparser. After exiting the deparser, packets are emitted through one of 8 output Ethernet ports or one of 3 "special" ports:

- Packets sent to the "CPU port" are sent to the control plane
- Packets sent to the "Drop port" are discarded

- Packets sent to the "Recirculate port" are re-injected in the switch through a special input port

The white blocks in the figure are programmable, and the user must provide a corresponding P4 program to specify the behavior of each such block. The red arrows indicate the flow of user-defined data. The cyan blocks are fixed-function components. The green arrows are data plane interfaces used to convey information between the fixed-function blocks and the programmable blocks—exposed in the P4 program as intrinsic metadata.

## 5.1. Very Simple Switch Architecture

The following P4 program provides a declaration of VSS in P4, as it would be provided by the VSS manufacturer. The declaration contains several type declarations, constants, and finally declarations for the three programmable blocks; the code uses syntax highlighting. The programmable blocks are described by their types; the implementation of these blocks has to be provided by the switch programmer.

```
// File "very_simple_switch_model.p4"
// Very Simple Switch P4 declaration
// core library needed for packet_in and packet_out definitions
# include <core.p4>
/* Various constants and structure declarations */
/* ports are represented using 4-bit values */
typedef bit<4> PortId;
/* only 8 ports are "real" */
const PortId REAL_PORT_COUNT = 4w8; // 4w8 is the number 8 in 4 bits
/* metadata accompanying an input packet */
struct InControl {
    PortId inputPort;
}
/* special input port values */
const PortId RECIRCULATE_IN_PORT = 0xD;
const PortId CPU_IN_PORT = 0xE;
/* metadata that must be computed for outgoing packets */
struct OutControl {
    PortId outputPort;
}
/* special output port values for outgoing packet */
const PortId DROP_PORT = 0xF;
const PortId CPU_OUT_PORT = 0xE;
const PortId RECIRCULATE_OUT_PORT = 0xD;
/* Prototypes for all programmable blocks */
/**
 * Programmable parser.
 * @param <H> type of headers; defined by user
 * @param b input packet
 * @param parsedHeaders headers constructed by parser
 */
parser Parser<H>(packet_in b,
                 out H parsedHeaders);
/**
 * Match-action pipeline
 * @param <H> type of input and output headers
 * @param headers headers received from the parser and sent to the deparser
 * @param parseError error that may have surfaced during parsing
 * @param inCtrl information from architecture, accompanying input packet
 * @param outCtrl information for architecture, accompanying output packet
 */
control Pipe<H>(inout H headers,
                in error parseError, // parser error
                in InControl inCtrl, // input port
                out OutControl outCtrl); // output port
/**
 * VSS deparser.
 * @param <H> type of headers; defined by user
 */
```

```

* @param b output packet
* @param outputHeaders headers for output packet
*/
control Deparser<H>(inout H outputHeaders,
                    packet_out b);
/**
* Top-level package declaration - must be instantiated by user.
* The arguments to the package indicate blocks that
* must be instantiated by the user.
* @param <H> user-defined type of the headers processed.
*/
package VSS<H>(Parser<H> p,
               Pipe<H> map,
               Deparser<H> d);
// Architecture-specific objects that can be instantiated
// Checksum unit
extern Checksum16 {
    Checksum16(); // constructor
    void clear(); // prepare unit for computation
    void update<T>(in T data); // add data to checksum
    void remove<T>(in T data); // remove data from existing checksum
    bit<16> get(); // get the checksum for the data added since last clear
}

```

Let us describe some of these elements:

- The included file `core.p4` is described in more detail in [Appendix D](#). It defines some standard data-types and error codes.
- `bit<4>` is the type of bit-strings with 4 bits.
- The syntax `4w0xF` indicates the value 15 represented using 4 bits. An alternative notation is `4w15`. In many circumstances the width modifier can be omitted, writing just `15`.
- `error` is a built-in P4 type for holding error codes
- Next follows the declaration of a parser:

```

parser Parser<H>(packet_in b, out H parsedHeaders);

```

This declaration describes the interface for a parser, but not yet its implementation, which will be provided by the programmer. The parser reads its input from a `packet_in`, which is a pre-defined P4 extern object that represents an incoming packet, declared in the `core.p4` library. The parser writes its output (the `out` keyword) into the `parsedHeaders` argument. The type of this argument is `H`, yet unknown—it will also be provided by the programmer.

- The declaration

```

control Pipe<H>(inout H headers,
                in error parseError,
                in InControl inCtrl,
                out OutControl outCtrl);

```

describes the interface of a Match-Action pipeline named `Pipe`.

The pipeline receives three inputs: the headers `headers`, a parser error `parseError`, and the `inCtrl` control data. [Figure 6](#) indicates the different sources of these pieces of information. The pipeline writes its outputs into `outCtrl`, and it must update in place the headers to be consumed by the deparser.

- The top-level package is called `VSS`; in order to program a VSS, the user will have to instantiate a package of this type (shown in the next section). The top-level package declaration also depends on a

type variable `H`:

```
package VSS<H>
```

A type variable indicates a type yet unknown that must be provided by the user at a later time. In this case `H` is the type of the set of headers that the user program will be processing; the parser will produce the parsed representation of these headers, and the match-action pipeline will update the input headers in place to produce the output headers.

- The `package VSS` declaration has three complex parameters, of types `Parser`, `Pipe`, and `Deparser` respectively; which are exactly the declarations we have just described. In order to program the target one has to supply values for these parameters.
- In this program the `inCtrl` and `outCtrl` structures represent control registers. The content of the headers structure is stored in general-purpose registers.
- The `extern Checksum16` declaration describes an extern object whose services can be invoked to compute checksums.

## 5.2. Very Simple Switch Architecture Description

In order to fully understand VSS's behavior and write meaningful P4 programs for it, and for implementing a control plane, we also need a full behavioral description of the fixed-function blocks. This section can be seen as a simple example illustrating all the details that have to be handled when writing an architecture description. The P4 language is not intended to cover the description of all such functional blocks—the language can only describe the interfaces between programmable blocks and the architecture. For the current program, this interface is given by the `Parser`, `Pipe`, and `Deparser` declarations. In practice we expect that the complete description of the architecture will be provided as an executable program and/or diagrams and text; in this document we will provide informal descriptions in English.

### 5.2.1. Arbiter block

The input arbiter block performs the following functions:

- It receives packets from one of the physical input Ethernet ports, from the control plane, or from the input recirculation port.
- For packets received from Ethernet ports, the block computes the Ethernet trailer checksum and verifies it. If the checksum does not match, the packet is discarded. If the checksum does match, it is removed from the packet payload.
- Receiving a packet involves running an arbitration algorithm if multiple packets are available.
- If the arbiter block is busy processing a previous packet and no queue space is available, input ports may drop arriving packets, without indicating the fact that the packets were dropped in any way.
- After receiving a packet, the arbiter block sets the `inCtrl.inputPort` value that is an input to the match-action pipeline with the identity of the input port where the packet originated. Physical Ethernet ports are numbered 0 to 7, while the input recirculation port has a number 13 and the CPU port has the number 14.

### 5.2.2. Parser runtime block

The parser runtime block works in concert with the parser. It provides an error code to the match-action pipeline, based on the parser actions, and it provides information about the packet payload (e.g., the size of the remaining payload data) to the demux block. As soon as a packet's processing is completed by the parser, the match-action pipeline is invoked with the associated metadata as inputs (packet headers and user-defined metadata).

### 5.2.3. Demux block

The core functionality of the demux block is to receive the headers for the outgoing packet from the deparser and the packet payload from the parser, to assemble them into a new packet and to send the result to the correct output port. The output port is specified by the value of `outCtrl.outputPort`, which is set by the match-action pipeline.

- Sending the packet to the drop port causes the packet to disappear.
- Sending the packet to an output Ethernet port numbered between 0 and 7 causes it to be emitted on the corresponding physical interface. The packet may be placed in a queue if the output interface is already busy emitting another packet. When the packet is emitted, the physical interface computes a correct Ethernet checksum trailer and appends it to the packet.
- Sending a packet to the output CPU port causes the packet to be transferred to the control plane. In this case, the packet that is sent to the CPU is the **original input packet**, and not the packet received from the deparser—the latter packet is discarded.
- Sending the packet to the output recirculation port causes it to appear at the input recirculation port. Recirculation is useful when packet processing cannot be completed in a single pass.
- If the `outputPort` has an illegal value (e.g., 9), the packet is dropped.
- Finally, if the demux unit is busy processing a previous packet and there is no capacity to queue the packet coming from the deparser, **the demux unit may drop the packet**, irrespective of the output port indicated.

Please note that some of the behaviors of the demux block may be unexpected—we have highlighted them in bold. We are not specifying here several important behaviors related to queue size, arbitration, and timing, which also influence the packet processing.

The arrow shown from the parser runtime to the demux block represents an additional information flow from the parser to the demux: the packet being processed as well as the offset within the packet where parsing ended (i.e., the start of the packet payload).

### 5.2.4. Available extern blocks

The VSS architecture provides an incremental checksum extern block, called `Checksum16`. The checksum unit has a constructor and four methods:

- `clear()`: prepares the unit for a new computation
- `update<T>(in T data)`: add some data to be checksummed. The data must be either a bit-string, a header-typed value, or a `struct` containing such values. The fields in the header/struct are concatenated in the order they appear in the type declaration.
- `get()`: returns the 16-bit one's complement checksum. When this function is invoked the checksum must have received an integral number of bytes of data.
- `remove<T>(in T data)`: assuming that `data` was used for computing the current checksum, `data` is removed from the checksum.

## 5.3. A complete Very Simple Switch program

Here we provide a complete P4 program that implements basic forwarding for IPv4 packets on the VSS architecture. This program does not utilize all of the features provided by the architecture—e.g., recirculation—but it does use preprocessor `#include` directives (see [\[sec-preprocessor\]](#)).






Figure 7. Diagram of the match-action pipeline expressed by the VSS P4 program.

The parser attempts to recognize an Ethernet header followed by an IPv4 header. If either of these headers are missing, parsing terminates with an error. Otherwise it extracts the information from these headers into a `Parsed_packet` structure. The match-action pipeline is shown in Figure 7; it comprises four match-action units (represented by the P4 `table` keyword):

- If any parser error has occurred, the packet is dropped (i.e., by assigning
- `outputPort` to `DROP_PORT`)
- The first table uses the IPv4 destination address to determine the
- `outputPort` and the IPv4 address of the next hop. If this lookup fails, the packet is dropped. The table also decrements the IPv4 `ttl` value.
- The second table checks the `ttl` value: if the `ttl` becomes 0, the packet is sent to the control plane through the CPU port.
- The third table uses the IPv4 address of the next hop (which was computed by the first table) to determine the Ethernet address of the next hop.
- Finally, the last table uses the `outputPort` to identify the source Ethernet address of the current switch, which is set in the outgoing packet.

The deparser constructs the outgoing packet by reassembling the Ethernet and IPv4 headers as computed by the pipeline.

```

// Include P4 core library
# include <core.p4>

// Include very simple switch architecture declarations
# include "very_simple_switch_model.p4"

// This program processes packets comprising an Ethernet and an IPv4
// header, and it forwards packets using the destination IP address

typedef bit<48>  EthernetAddress;
typedef bit<32>  IPv4Address;

// Standard Ethernet header
header Ethernet_h {
    EthernetAddress dstAddr;
    EthernetAddress srcAddr;
    bit<16>         etherType;
}

// IPv4 header (without options)
header IPv4_h {

```



```

    bit<4>      version;
    bit<4>      ihl;
    bit<8>      diffserv;
    bit<16>     totalLen;
    bit<16>     identification;
    bit<3>      flags;
    bit<13>     fragOffset;
    bit<8>      ttl;
    bit<8>      protocol;
    bit<16>     hdrChecksum;
    IPv4Address srcAddr;
    IPv4Address dstAddr;
}

// Structure of parsed headers
struct Parsed_packet {
    Ethernet_h ethernet;
    IPv4_h      ip;
}

// Parser section

// User-defined errors that may be signaled during parsing
error {
    IPv4OptionsNotSupported,
    IPv4IncorrectVersion,
    IPv4ChecksumError
}

parser TopParser(packet_in b, out Parsed_packet p) {
    Checksum16() ck; // instantiate checksum unit

    state start {
        b.extract(p.ethernet);
        transition select(p.ethernet.etherType) {
            0x0800: parse_ipv4;
            // no default rule: all other packets rejected
        }
    }

    state parse_ipv4 {
        b.extract(p.ip);
        verify(p.ip.version == 4w4, error.IPv4IncorrectVersion);
        verify(p.ip.ihl == 4w5, error.IPv4OptionsNotSupported);
        ck.clear();
        ck.update(p.ip);
        // Verify that packet checksum is zero
        verify(ck.get() == 16w0, error.IPv4ChecksumError);
        transition accept;
    }
}

// Match-action pipeline section

control TopPipe(inout Parsed_packet headers,
                in error parseError, // parser error
                in InControl inCtrl, // input port
                out OutControl outCtrl) {
    IPv4Address nextHop; // local variable

    /**
     * Indicates that a packet is dropped by setting the
     * output port to the DROP_PORT
     */
    action Drop_action() {
        outCtrl.outputPort = DROP_PORT;
    }

    /**

```

```

* Set the next hop and the output port.
* Decrements ipv4 ttl field.
* @param ipv4_dest ipv4 address of next hop
* @param port output port
*/
action Set_nhop(IPv4Address ipv4_dest, PortId port) {
    nextHop = ipv4_dest;
    headers.ip.ttl = headers.ip.ttl - 1;
    outCtrl.outputPort = port;
}

/**
* Computes address of next IPv4 hop and output port
* based on the IPv4 destination of the current packet.
* Decrements packet IPv4 TTL.
* @param nextHop IPv4 address of next hop
*/
table ipv4_match {
    key = { headers.ip.dstAddr: lpm; } // longest-prefix match
    actions = {
        Drop_action;
        Set_nhop;
    }
    size = 1024;
    default_action = Drop_action;
}

/**
* Send the packet to the CPU port
*/
action Send_to_cpu() {
    outCtrl.outputPort = CPU_OUT_PORT;
}

/**
* Check packet TTL and send to CPU if expired.
*/
table check_ttl {
    key = { headers.ip.ttl: exact; }
    actions = { Send_to_cpu; NoAction; }
    const default_action = NoAction; // defined in core.p4
}

/**
* Set the destination MAC address of the packet
* @param dmac destination MAC address.
*/
action Set_dmac(EthernetAddress dmac) {
    headers.ethernet.dstAddr = dmac;
}

/**
* Set the destination Ethernet address of the packet
* based on the next hop IP address.
* @param nextHop IPv4 address of next hop.
*/
table dmac {
    key = { nextHop: exact; }
    actions = {
        Drop_action;
        Set_dmac;
    }
    size = 1024;
    default_action = Drop_action;
}

/**
* Set the source MAC address.
* @param smac: source MAC address to use

```

```

    */
    action Set_smac(EthernetAddress smac) {
        headers.ethernet.srcAddr = smac;
    }

    /**
     * Set the source mac address based on the output port.
     */
    table smac {
        key = { outCtrl.outputPort: exact; }
        actions = {
            Drop_action;
            Set_smac;
        }
        size = 16;
        default_action = Drop_action;
    }

    apply {
        if (parseError != error.NoError) {
            Drop_action(); // invoke drop directly
            return;
        }

        ipv4_match.apply(); // Match result will go into nextHop
        if (outCtrl.outputPort == DROP_PORT) return;

        check_ttl.apply();
        if (outCtrl.outputPort == CPU_OUT_PORT) return;

        dmac.apply();
        if (outCtrl.outputPort == DROP_PORT) return;

        smac.apply();
    }
}

// deparser section
control TopDeparser(inout Parsed_packet p, packet_out b) {
    Checksum16() ck;
    apply {
        b.emit(p.ethernet);
        if (p.ip.isValid()) {
            ck.clear(); // prepare checksum unit
            p.ip.hdrChecksum = 16w0; // clear checksum
            ck.update(p.ip); // compute new checksum.
            p.ip.hdrChecksum = ck.get();
        }
        b.emit(p.ip);
    }
}

// Instantiate the top-level VSS package
VSS(TopParser(),
    TopPipe(),
    TopDeparser()) main;

```

## 6. P4 language definition

This section provides a high-level overview of the P4 programming language, focusing on its syntax, semantics, lexical constructs, scoping rules, calling conventions, and naming conventions.

[Chapter 7](#) introduces the P4 abstract machine, which serves as the model for describing the behavior of P4 programs. [Chapter 8](#) through [Chapter 16](#) define the P4 syntax and semantics in detail.

## 6.1. Syntax and semantics

### 6.1.1. Grammar

The complete grammar of P4<sub>16</sub> is given in [Appendix E](#), using Yacc/Bison grammar description language. This text is based on the same grammar. We adopt several standard conventions when we provide excerpts from the grammar:

- **UPPERCASE** symbols denote terminals in the grammar.
- Excerpts from the grammar are given in BNF notation as follows:

```
p4program
: /* empty */
| p4program declaration
| p4program ;
;
```

### 6.1.2. Semantics and the P4 abstract machines

We describe the semantics of P4 in terms of abstract machines executing traditional imperative code.

P4 compilers are free to reorganize the code they generate in any way as long as the externally visible behaviors of the P4 programs are preserved as described by this specification where externally visible behavior is defined as:

- The input/output behavior of all P4 blocks, and
- The state maintained by extern blocks.

Throughout this specification, the P4 semantics is described using a combination of:

- P4 code snippets
- Pseudo-code snippets
- Prose algorithms

#### 6.1.2.1. Pseudo-code snippets

Pseudo-code (mostly used for describing the semantics of various P4 constructs) are shown with fixed-size fonts as in the following example:

```
ParserModel.verify(bool condition, error err) {
    if (condition == false) {
        ParserModel.parserError = err;
        goto reject;
    }
}
```

#### 6.1.2.2. Prose algorithms

The semantics of P4 constructs are also described using prose algorithms. For example, below is the signature of an algorithm used to describe type checking of P4 expressions.

[Expr\\_ok](#):

- Typing `expression`, under cursor `cursor` and context `typingContext`:
- Result in `typedExpressionIR`.

Detailed discussion of what `cursor`, `typingContext`, and `typedExpressionIR` mean is given in [Section 7.2](#). For now, it suffices to know that `Expr_ok` takes an `expression`, a `cursor`, and a `typingContext` as inputs and results in a `typedExpressionIR`.

An algorithm is defined in terms of case-analysis, where each case corresponds to a variant of a P4 construct. For example, the following algorithm defines how to type check logical not expressions.

Typing `! expression`, under cursor `p` and context `TC`:

1. Let `typedExpressionIR` be
  - the result of typing `expression`, under cursor `p` and context `TC`.
2. Let `typedExpressionIRreduced` be `!` the result of reducing serializable enums in `typedExpressionIR` until `$compat_lnot` is satisfied.
3. Let `typeIRreduced` be the type of `typedExpressionIRreduced`.
4. Let `ctkreduced` be the compile-time known-ness of `typedExpressionIRreduced`.
5. Let `expressionNoteIR` be a pair of type `typeIRreduced` and compile-time known-ness `ctkreduced`.
6. Result in `! typedExpressionIRreduced` annotated with `expressionNoteIR`.

The shorthand `!` in step 2 is explained in [Section 6.1.2.2.1](#) and `$compat_lnot` is a helper function used to check compatibility of the operand with logical not expressions. And the following algorithm defines type checking of bitwise negation expressions.

Typing `~ expression`, under cursor `p` and context `TC`:

1. Let `typedExpressionIR` be
  - the result of typing `expression`, under cursor `p` and context `TC`.
2. Let `typedExpressionIRreduced` be `!` the result of reducing serializable enums in `typedExpressionIR` until `$compat_bnot` is satisfied.
3. Let `typeIRreduced` be the type of `typedExpressionIRreduced`.
4. Let `ctkreduced` be the compile-time known-ness of `typedExpressionIRreduced`.
5. Let `expressionNoteIR` be a pair of type `typeIRreduced` and compile-time known-ness `ctkreduced`.
6. Result in `~ typedExpressionIRreduced` annotated with `expressionNoteIR`.

And so on for other variants of P4 expressions. These prose algorithms are presented throughout this specification.

#### 6.1.2.2.1. Prose algorithm shorthands

To make the prose algorithms concise, we often use the shorthand `!`. Some algorithms result in an optional result to indicate possible failure. The following example algorithm computes modulo of two natural numbers (including zero).

`na mod nb`

1. If  $n_b$  is not equal to 0:
  - a. Return  $n_a \setminus n_b$ .
2. If  $n_b$  is equal to 0:
  - a. Return  $\cdot$ .

Because the divisor may be zero, the result is optional. Now consider the case when the algorithm is called.

$n \bmod \text{forty-two}$

1. Let  $n_{\text{result}}$  be  $! n \bmod 42$ .
2. Return  $n_{\text{result}}$ .

Here,  $!$  indicates unwrapping of the optional result. This shortened form is equivalent to first getting the optional result, checking that it is not `None`, and then unwrapping it.

## 6.2. Lexical constructs

All P4 keywords use only ASCII characters. All P4 identifiers must use only ASCII characters. P4 compilers should handle correctly strings containing 8-bit characters in comments and string literals. P4 is case-sensitive. Whitespace characters, including newlines are treated as token separators. Indentation is free-form; however, P4 has C-like block constructs, and all our examples use C-style indentation. Tab characters are treated as spaces.

The lexer recognizes the following kinds of terminals:

- **IDENTIFIER**: start with a letter or underscore, and contain letters, digits and underscores
- **TYPE\_IDENTIFIER**: identifier that denotes a type name
- **INTEGER**: integer literals
- **DONTCARE**: a single underscore
- Keywords such as **RETURN**. By convention, each keyword terminal corresponds to a language keyword with the same spelling but using lowercase. For example, the **RETURN** terminal corresponds to the `return` keyword.

### 6.2.1. Identifiers

P4 identifiers may contain only letters, numbers, and the underscore character `_`, and must start with a letter or underscore. The special identifier consisting of a single underscore `_` is reserved to indicate a "don't care" value; its type may vary depending on the context. Certain keywords (e.g., `apply`) can be used as identifiers if the context makes it unambiguous.

```

identifier
: `ID text
;

nonTypeName
: identifier
| APPLY
| KEY
| ACTIONS
| STATE

```

```

| ENTRIES
| TYPE
| PRIORITY
;

typeIdentifier
: `TID text
;

typeName = typeIdentifier

name
: nonTypeName
| typeName
| LIST
;

```

## 6.2.2. Literal constants

### 6.2.2.1. Boolean literals

```

booleanLiteral
: TRUE
| FALSE
;

```

There are two Boolean literal constants: `true` and `false`.

### 6.2.2.2. Integer literals

```

integerLiteral
: D int
| nat W int
| nat S int
;

```

Integer literals are non-negative arbitrary-precision integers. By default, literals are represented in base 10. The following prefixes must be employed to specify the base explicitly:

- `0x` or `0X` indicates base 16 (hexadecimal)
- `0o` or `0O` indicates base 8 (octal)
- `0d` or `0D` indicates base 10 (decimal)
- `0b` or `0B` indicates base 2

The width of a numeric literal in bits can be specified by an unsigned number prefix consisting of a number of bits and a signedness indicator:

- `w` indicates unsigned numbers
- `s` indicates signed numbers

Note that a leading zero by itself does not indicate an octal (base 8) constant. The underscore character is considered a digit within number literals but is ignored when computing the value of the parsed number. This allows long constant numbers to be more easily read by grouping digits together. The underscore cannot be used in the width specification or as the first character of an integer literal. No comments or whitespaces are allowed within a literal. Here are some examples of numeric literals:

```

32w255      // a 32-bit unsigned number with value 255
32w0d255    // same value as above
32w0xFF     // same value as above
32s0xFF     // a 32-bit signed number with value 255
8w0b10101010 // an 8-bit unsigned number with value 0xAA
8w0b_1010_1010 // same value as above
8w170      // same value as above
8s0b1010_1010 // an 8-bit signed number with value -86
16w0377    // 16-bit unsigned number with value 377 (not 255!)
16w0o377    // 16-bit unsigned number with value 255 (base 8)

```

### 6.2.2.3. String literals

```

stringLiteral
: " text "
;

```

String literals are specified as an arbitrary sequence of 8-bit characters, enclosed within double quote characters " (ASCII code 34). Strings start with a double quote character and extend to the first double quote sign which is not immediately preceded by an odd number of backslash characters (ASCII code 92). P4 does not make any validity checks on strings (i.e., it does not check that strings represent legal UTF-8 encodings).

Since P4 does not allow strings to exist at runtime, string literals are generally passed unchanged through the P4 compiler to other third-party tools or compiler-backends. The compiler can, however, perform compile-time concatenation (constant-folding) of concatenation expressions into single literal. When such concatenation is performed, the binary representation of the string literals (excluding the quotes) is concatenated in the order they appear in the source code. There are no escape sequences that would be treated specially when strings are concatenated.

The backends and other tools can define their own handling of escape sequences (e.g., how to specify Unicode characters, or handle unprintable ASCII characters).

Here are 3 examples of string literals:

```

"simple string"
"string \" with \" embedded \" quotes"
"string with embedded
line terminator"

```

Here is an example of concatenation expression and an equivalent string literal:

```

"one string \" with a quote inside;" ++ (" " ++ "another string")
// can be constant folded to
"one string \" with a quote inside; another string"

```

### 6.2.3. Comments

P4 supports several kinds of comments:

- Single-line comments, introduced by `//` and spanning to the end of line,
- Multi-line comments, enclosed between `/*` and `*/`
- Nested multi-line comments are not supported.
- Javadoc-style comments, starting with `/**` and ending with `*/`



Use of Javadoc-style comments is strongly encouraged for the tables and actions that are used to synthesize the interface with the control-plane.

P4 treats comments as token separators and no comments are allowed within a token---e.g. `bi/**/t` is parsed as two tokens, `bi` and `t`, and not as a single token `bit`.

### 6.2.4. Optional trailing commas

The P4 grammar allows several kinds of comma-separated lists to end in an optional comma.

```
trailingCommaOpt
: /* empty */
| ,
;
```

For example, the following declarations are both legal, and have the same meaning:

```
enum E {
    a, b, c
}

enum E {
    a, b, c,
}
```

This is particularly useful in combination with preprocessor directives:

```
enum E {
#ifdef SUPPORT_A
    a,
#endif
    b,
    c,
}
```

## 6.3. Scoping

Scopes are used to organize P4 programs into nested namespaces. There are three kinds of scopes in P4, from outermost to innermost: the top-level scope (global namespace), the scope within a `parser`, `control`, or `extern` declaration (block namespace), and the scope within a block statement (local namespace). Local namespaces can be nested within other local namespaces.

```
// top-level (global) scope
const bit<8> GLOBAL = 255;

control c() {
    // block scope within a control
    bit<8> block = GLOBAL;

    apply {
        // local scope
        bit<8> local = block;
    }
}

bit<8> f() {
    // local scope
```

```

bit<8> local = GLOBAL;
{
    // nested local scope
    bit<8> local_nested = local;
}
return local;
}

```

Cursors are used to track scopes while defining the semantic rules of P4.

```

cursor
: GLOBAL
| BLOCK
| LOCAL
;

```

### 6.3.1. Name resolution

P4 namespaces are organized in a hierarchical fashion.

```

prefixedNonTypeName
: nonTypeName
| `ID . nonTypeName
;

prefixedTypeName
: typeName
| `TID . typeName
;

```

Identifiers prefixed with a dot are always resolved in the top-level namespace.

```

const bit<32> x = 2;
control c() {
    int<32> x = 0;
    apply {
        x = x + (int<32>).x; // x is the int<32> local variable,
                           // .x is the top-level bit<32> variable
    }
}

```

References to resolve an identifier are attempted inside-out, starting with the current scope and proceeding to all lexically enclosing scopes. The compiler may provide a warning if multiple resolutions are possible for the same name (name shadowing).

```

const bit<4> x = 1;
control c() {
    const bit<8> x = 8; // x declaration shadows global x
    const bit<4> y = .x; // reference to top-level x
    const bit<8> z = x; // reference to c's local x
    apply {}
}

```

The order of declarations is important; with the exception of parser states, all uses of a symbol must follow the symbol's declaration. (This is a departure from P4<sub>14</sub>, which allows declarations in any order. This requirement significantly simplifies the implementation of compilers for P4, allowing compilers to use additional information about declared identifiers to resolve ambiguities.)

See [Section 14.3](#) for how variable references are resolved with respect to scopes.

### 6.3.2. Name visibility

Identifiers defined in the top-level namespace are globally visible. Declarations within a `parser` or `control` are private and cannot be referred to from outside of the enclosing `parser` or `control`.

## 6.4. Stateful elements

Most P4 constructs are stateless: given some inputs they produce a result that solely depends on these inputs. There are only two stateful constructs that may retain information across packets:

- `tables`: Tables are read-only for the data plane, but their entries can be modified by the control-plane,
- `extern` objects: many objects have state that can be read and written by the control plane and data plane. All constructs from the P4<sub>14</sub> language version that encapsulate state (e.g., counters, meters, registers) are represented using `extern` objects in P4<sub>16</sub>.

In P4 all stateful elements must be explicitly allocated at compilation-time through the process called "instantiation".

In addition, `parsers`, `control` blocks, and `packages` may contain stateful element instantiations. Thus, they are also treated as stateful elements, even if they appear to contain no state, and must be instantiated before they can be used. However, although they are stateful, `tables` do not need to be instantiated explicitly—declaring a `table` also creates an instance of it. This convention is designed to support the common case, since most tables are used just once. To have finer-grained control over when a `table` is instantiated, a programmer can declare it within a `control`.

Recall the example in [Section 5.3](#): `TopParser`, `TopPipe`, `TopDeparser`, `Checksum16`, and `Switch` are types. There are two instances of `Checksum16`, one in `TopParser` and one in `TopDeparser`, both called `ck`. The `TopParser`, `TopDeparser`, `TopPipe`, and `Switch` are instantiated at the end of the program, in the declaration of the `main` instance object, which is an instance of the `Switch` type (a `package`).

## 6.5. Call convention: copy-in/copy-out

P4 provides multiple constructs for writing modular programs: `extern` methods, `parsers`, `controls`, `actions`. All these constructs behave similarly to procedures in standard general-purpose programming languages:

- They have named and typed parameters.
- They introduce a new local scope for parameters and local variables.
- They allow arguments to be passed by binding them to their parameters.

```
parameterList
: /* empty */
| nonEmptyParameterList
;

nonEmptyParameterList
: parameter
| nonEmptyParameterList , parameter
;

parameter
: annotationList direction type name initializerOpt
;
```

```

direction
: /* empty */
| IN
| OUT
| INOUT
;

```

Invocations are executed using copy-in/copy-out semantics.

Each parameter may be labeled with a direction:

- **in** parameters are read-only. It is an error to use an **in** parameter on the left-hand side of an assignment or to pass it to a callee as a non-**in** argument. **in** parameters are initialized by copying the value of the corresponding argument when the invocation is executed.
- **out** parameters are, with a few exceptions listed below, uninitialized and are treated as l-values (See [Chapter 12](#)) within the body of the method or function. An argument passed as an **out** parameter must be an l-value; after the execution of the call, the value of the parameter is copied to the corresponding storage location for that l-value.
- **inout** parameters behave like a combination of **in** and **out** parameters simultaneously: On entry the value of the arguments is copied to the parameters. On return the value of the parameters is copied back to the arguments. In consequence, an argument passed as an **inout** parameter must be an l-value.
- The meaning of parameters with no direction depends upon the kind of entity the parameter is for:
  - For anything other than an action, e.g. a control, parser, or function, a directionless parameter means that the value supplied as an argument in a call must be a compile-time known value (see [Section 7.5](#)).
  - For an action, a directionless parameter indicates that it is "action data". See [Section 9.3](#) for the meaning of action data, but its meaning includes the following possibilities:
    - The parameter's value is provided in the P4 program. In this case, the parameter behaves as if the direction were **in**. Such an argument expression need not be a compile-time known value.
    - The parameter's value is provided by the control plane software when an entry is added to a table that uses that action. See [Section 9.3](#).
  - A directionless parameter of an extern object type is passed by reference.

Direction **out** parameters are always initialized at the beginning of execution of the portion of the program that has the **out** parameters, e.g. **control**, **parser**, **action**, function, etc. This initialization is not performed for parameters with any direction that is not **out**.

- If a direction **out** parameter is of type **header** or **header\_union**, it is set to "invalid".
- If a direction **out** parameter is of type **header stack**, all elements of the header stack are set to "invalid", and its **nextIndex** field is initialized to 0 (see [Section 8.4.3](#)).
- If a direction **out** parameter is a compound type, e.g. a struct or tuple, other than one of the types listed above, then apply these rules recursively to its members.
- If a direction **out** parameter has any other type, e.g. **bit<W>**, an implementation need not initialize it to any predictable value.

For example, if a direction **out** parameter has type **s2\_t** named **p**:

```

header h1_t {
    bit<8> f1;
    bit<8> f2;
}
struct s1_t {

```

```

    h1_t h1a;
    bit<3> a;
    bit<7> b;
}
struct s2_t {
    h1_t h1b;
    s1_t s1;
    bit<5> c;
}

```

then at the beginning of execution of the part of the program that has the `out` parameter `p`, it must be initialized so that `p.h1b` and `p.s1.h1a` are invalid. No other parts of `p` are required to be initialized.

Arguments are evaluated from left to right prior to the invocation of the function itself. The order of evaluation is important when the expression supplied for an argument can have side-effects. Consider the following example:

```

extern void f(inout bit x, in bit y);
extern bit g(inout bit z);
bit a;
f(a, g(a));

```

Note that the evaluation of `g` may mutate its argument `a`, so the compiler has to ensure that the value passed to `f` for its first parameter is not changed by the evaluation of the second argument. The semantics for evaluating a function call is given by the following algorithm (implementations can be different as long as they provide the same result):

1. Arguments are evaluated from left to right as they appear in the function call expression.
2. If a parameter has a default value and no corresponding argument is supplied, the default value is used as an argument.
3. For each `out` and `inout` argument the corresponding l-value is saved (so it cannot be changed by the evaluation of the following arguments). This is important if the argument contains indexing operations into a header stack.
4. The value of each argument is saved into a temporary.
5. The function is invoked with the temporaries as arguments. We are guaranteed that the temporaries that are passed as arguments are never aliased to each other, so this "generated" function call can be implemented using call-by-reference if supported by the architecture.
6. On function return, the temporaries that correspond to `out` or `inout` arguments are copied in order from left to right into the l-values saved in Step 3.

According to this algorithm, the previous function call is equivalent to the following sequence of statements:

```

bit tmp1 = a;    // evaluate a; save result
bit tmp2 = g(a); // evaluate g(a); save result; modifies a
f(tmp1, tmp2);   // evaluate f; modifies tmp1
a = tmp1;        // copy inout result back into a

```

To see why Step 3 in the above algorithm is important, consider the following example:

```

header H { bit z; }
H[2] s;
f(s[a].z, g(a));

```

The evaluation of this call is equivalent to the following sequence of statements:

```

bit tmp1 = a;           // save the value of a
bit tmp2 = s[tmp1].z;   // evaluate first argument
bit tmp3 = g(a);        // evaluate second argument; modifies a
f(tmp2, tmp3);          // evaluate f; modifies tmp2
s[tmp1].z = tmp2;       // copy inout result back; dest is not s[a].z

```

When used as arguments, `extern` objects can only be passed as directionless parameters—e.g., see the packet argument in the very simple switch example.

### 6.5.1. Justification

The main reason for using copy-in/copy-out semantics (instead of the more common call-by-reference semantics) is for controlling the side-effects of `extern` functions and methods. `extern` methods and functions are the main mechanism by which a P4 program communicates with its environment. With copy-in/copy-out semantics `extern` functions cannot hold references to P4 program objects; this enables the compiler to limit the side-effects that `extern` functions may have on the P4 program both in space (they can only affect `out` parameters) and in time (side-effects can only occur at function call time).

In general, `extern` functions are arbitrarily powerful: they can store information in global storage, spawn separate threads, "collude" with each other to share information—but they cannot access any variable in a P4 program. With copy-in/copy-out semantics the compiler can still reason about P4 programs that invoke `extern` functions.

There are additional benefits of using copy-in copy-out semantics:

- It enables P4 to be compiled for architectures that do not support references (e.g., where all data is allocated to named registers. Such architectures may require indices into header stacks that appear in a program to be compile-time known values.)
- It simplifies some compiler analyses, since function parameters can never alias to each other within the function body.

Following is a summary of the constraints imposed by the parameter directions:

- When used as arguments, `extern` objects can only be passed as directionless parameters.
- All constructor parameters are evaluated at compilation-time, and in consequence they must all be directionless (they cannot be `in`, `out`, or `inout`); this applies to `package`, `control`, `parser`, and `extern` objects. Expressions for these parameters must be supplied at compile-time, and they must evaluate to compile-time known values. See [Section 10.2.1](#) for further details.
- For actions all directionless parameters must be at the end of the parameter list. When an action appears in a `table`'s `actions` list, only the parameters with a direction must be bound. See [Section 9.3](#) for further details.
- Actions can also be explicitly invoked using function call syntax, either from a control block or from another action. In this case, values for all action parameters must be supplied explicitly, including values for the directionless parameters. The directionless parameters in this case behave like `in` parameters. See [Section 18.6.1](#) for further details.
- Default expressions are only allowed for `in` or directionless parameters, and the expressions supplied as defaults must be compile-time known values.
- If parameters with default values do not appear at the end of the list of parameters, invocations that use the default values must use named arguments, as in the following example:

```

extern void f(in bit a, in bit<3> b = 2, in bit<5> c);

void g() {
    f(a = 1, b = 2, c = 3); // ok
    f(a = 1, c = 3);       // ok, equivalent to the previous call, b uses default value
}

```

```
f(1, 2, 3);      // ok, equivalent to the previous call
// f(1, 3); // illegal, since the parameter b is not the last in the list
}
```

## 6.5.2. Optional parameters

A parameter that is annotated with the `@optional` annotation is optional: the user may omit the value for that parameter in an invocation. Optional parameters can only appear for arguments of: packages, parser types, control types, extern functions, extern methods, and extern object constructors. Optional parameters cannot have default values. If a procedure-like construct has both optional parameters and default values then it can only be called using named arguments. It is recommended, but not mandatory, for all optional parameters to be at the end of a parameter list.

The implementation of such objects is not expressed in P4, so the meaning and implementation of optional parameters should be specified by the target architecture. For example, we can imagine a two-stage switch architecture where the second stage is optional. This could be declared as a package with an optional parameter:

```
package pipeline(/* parameters omitted */);
package switch(pipeline first, @optional pipeline second);

pipeline(/* arguments omitted */) ingress;
switch(ingress) main; // a switch with a single-stage pipeline
```

Here the target architecture could implement the elided optional argument using an empty pipeline.

The following example shows optional parameters and parameters with default values.

```
extern void h(in bit<32> a, in bool b = true); // default value

// function calls
h(10); // same as h(10, true);
h(a = 10); // same as h(10, true);
h(a = 10, b = true);

struct Empty {}
control nothing(inout Empty h, inout Empty m) {
    apply {}
}

parser parserProto<H, M>(packet_in p, out H h, inout M m);
control controlProto<H, M>(inout H h, inout M m);

package pack<HP, MP, HC, MC>(
    @optional parserProto<HP, MP> _parser, // optional parameter
    controlProto<HC, MC> _control = nothing()); // default
parameter value

pack() main; // No value for _parser, _control is an instance of nothing()
```

## 6.6. Overloading

Functions, methods, and constructors are the only P4 constructs that support overloading: there can exist multiple methods with the same name in the same scope. When overloading is used, the compiler must be able to disambiguate at compile-time which method, function, or constructor is being called, either by the number of arguments or by the names of the arguments, when calls are specifying argument names. Argument type information is not used in disambiguating calls.

Notice that overloading of abstract methods, parsers, controls, or packages is not allowed:

```
parser p(packet_in p, out bit<32> value) {  
    ...  
}  
  
// The following will cause an error about a duplicate declaration  
//parser p(packet_in p, out Headers headers) {  
//    ...  
//}
```

See [Section 18.2](#) for details on how overload is resolved.

## 6.7. Naming conventions

P4 provides a rich assortment of types. Base types include bit-strings, numbers, and errors. There are also built-in types for representing constructs such as parsers, pipelines, actions, and tables. Users can construct new types based on these: structures, enumerations, headers, header stacks, header unions, etc.

In this document we adopt the following conventions:

- Built-in types are written with lowercase characters—e.g., `int<20>`,
- User-defined types are capitalized—e.g., `IPv4Address`,
- Type variables are always uppercase—e.g., `parser P<H, IH>()`,
- Variables are uncapitalized-- e.g., `ipv4header`,
- Constants are written with uppercase characters—e.g., `CPU_PORT`, and
- Errors and enumerations are written in camel-case-- e.g. `PacketTooShort`.

## 7. The P4 Abstract Machine

A  $P4_{16}$  program is a list of declarations:

```
p4program  
: /* empty */  
| p4program declaration  
| p4program ;  
;
```

An empty declarations is indicated with a single semicolon. (Allowing empty declarations accommodates the habits of C/C++ and Java programmers—e.g., certain constructs, like `struct`, do not require a terminating semicolon).

The evaluation of a P4 program is done in four stages:

- **preprocessing:** at compile time, the P4 program is preprocessed to handle directives such as `#include` and `#define`.
- **type checking:** at compile time, the P4 program is type checked according to the P4 type system.
- **instantiation:** at compile time, all stateful blocks in the P4 program are instantiated.
- **runtime evaluation:** at runtime, each P4 functional block is executed to completion, in isolation, when it receives control from the architecture.



The preprocessing stage is described in [Section 7.1](#).

The type system is described in [Section 7.2](#). In addition to checking the types, the type system also converts an input P4 program into an intermediate representation ( $P4_{IR}$ ).  $P4_{IR}$  is an extension of the surface syntax of P4, e.g., the types of all expressions are made explicit, implicit type casts are inserted, and omitted type arguments are inferred.  $P4_{IR}$  is described in [Section 7.2.1](#).

The instantiation stage is described in [Section 7.3](#). It traverses the type checked  $P4_{IR}$  program, and recursively instantiates all stateful blocks. The result of the instantiation stage is a global store that holds all instantiated stateful blocks.

The runtime evaluation stage is described in [Section 7.4](#). It describes how each P4 block, represented as stateful objects within the global store, is executed to completion. These blocks are orchestrated by the architecture to compose the overall packet processing pipeline.

## 7.1. Preprocessing

To aid the composition of programs from multiple source files, P4 compilers should support the following subset of the C preprocessor functionality:

- `#define` for defining macros (without arguments)
- `#undef`
- `#if #else #endif #ifdef #ifndef #elif`
- `#include`

The preprocessor should also remove the sequence backslash newline (ASCII codes 92, 10) to facilitate splitting content across multiple lines when convenient for formatting.

Additional C preprocessor capabilities may be supported, but are not guaranteed---e.g., macros with arguments. Similar to C, `#include` can specify a file name either within double quotes or within `<>`.

```
# include <system_file>
# include "user_file"
```

The difference between the two forms is the order in which the preprocessor searches for header files when the path is incompletely specified.

P4 compilers should correctly handle `#line` directives that may be generated during preprocessing. This functionality allows P4 programs to be built from multiple source files, potentially produced by different programmers at different times:

- the P4 core library, defined in this document,
- the architecture, defining data plane interfaces and extern blocks,
- user-defined libraries of useful components (e.g. standard protocol header definitions), and
- the P4 programs that specify the behavior of each programmable block.

The P4 language specification defines a core library that includes several common programming constructs. A description of the core library is provided in [Appendix D](#). All P4 programs must include the core library. Including the core library is done with

```
# include <core.p4>
```

## 7.2. Type checking

P4<sub>16</sub> is a statically-typed language. Programs that do not pass the type checker are considered invalid and rejected by the compiler. P4 provides a number of base types as well as type operators that construct derived types.

### 7.2.1. P4 Intermediate Representation

P4<sub>IR</sub> is an intermediate representation for P4 programs. P4<sub>IR</sub> extends the surface syntax of P4<sub>16</sub> with additional information obtained during type checking. They include:

- All expressions are annotated with their types.
- Implicit casts are made explicit.
- Omitted type arguments are inferred and made explicit.

P4<sub>IR</sub> is designed to stay as close as possible to the surface syntax of P4<sub>16</sub>. This makes it easy to relate P4<sub>IR</sub> programs to their source P4<sub>16</sub> programs.

Take expressions as an example.

```
expression
: literalExpression
| referenceExpression
| defaultExpression
| unaryExpression
| binaryExpression
| ternaryExpression
| castExpression
| dataExpression
| accessExpression
| callExpression
| parenthesizedExpression
;

expressionIR
: literalExpressionIR
| referenceExpressionIR
| defaultExpressionIR
| unaryExpressionIR
| binaryExpressionIR
| ternaryExpressionIR
| castExpressionIR
| dataExpressionIR
| accessExpressionIR
| callExpressionIR
| parenthesizedExpressionIR
;

expressionNoteIR
: `( typeIR ctk )
;

typedExpressionIR
: expressionIR # expressionNoteIR
;
```

`typedExpressionIR` is an intermediate representation of `expression` that is annotated with type information, `expressionNoteIR`. Nevertheless, the structure of the grammar mostly stays the same.

`binaryExpression`

```

: expression binop expression
;

binaryExpressionIR
: typedExpressionIR binop typedExpressionIR
;

```

`binaryExpressionIR` is an intermediate representation of `binaryExpression`. The only difference is that the operands are now of type `typedExpressionIR`.

## 7.2.2. Typing a P4 program

For a well-typed  $P4_{16}$  program, `p4program`, a type checker produces a  $P4_{IR}$  program, `p4programIR`:

```

p4programIR
: declarationIR* ;
;

```

`Program_ok` type checks a `p4program` and produces a `p4programIR`.

**Program\_ok:**

- Typing `p4program`:
- Result in typed P4 program `p4programIR`.

Below is a prose algorithm that implements `Program_ok`. Details of what each meta-variable means are provided in the subsequent sections.

**Typing `p4program`:**

1. Let `declaration*` be the list of declarations in `p4program`.
2. Let `TC0` be an empty typing context.
3. Let context `TC1` and `declarationIR*` be
  - the result of typing `declaration*` under context `TC0`.
4. Result in typed P4 program `declarationIR*` ;.

The following helper function is used to collect declarations in a `p4program`:

**The list of declarations in `p4program`**

1. If `p4program` is ``EMPTY'`:
  - a. Return `.`.
2. Else if let `p4program' declaration` be `p4program`:
  - a. Let `declaration*` be the list of declarations in `p4program'`.
  - b. Return `declaration*` concatenated with `declaration`.
3. Else:

- a. Let `p4program'`; be `p4program`.
- b. Return the list of declarations in `p4program'`.

### 7.2.3. Typing context

```
globalTypingLayer = {
  CONSTRUCTOR constructorTypeDefEnv,
  TYPE typeDefEnv,
  CALLABLE callableTypeDefEnv,
  FRAME typeFrame
}

blockTypingLayer = {
  KIND blockKind,
  TYPE typeDefEnv,
  CALLABLE callableTypeDefEnv,
  FRAME typeFrame
}

localTypingLayer = {
  KIND localKind,
  TYPE typeDefEnv,
  FRAMES typeFrame*
}

typingContext = {
  GLOBAL globalTypingLayer,
  BLOCK blockTypingLayer,
  LOCAL localTypingLayer
}
```

A typing context is used to keep track of the types of all named declarations in scope at a given program point. It consists of three layers:

- A global typing layer, which contains all declarations at the top level of a  $P4_{16}$  program.
- A block typing layer, which contains all declarations in the current block scope.
- A local typing layer, which contains all declarations in the current local scope.

Each layer contains mappings from names to types.

```
varTypeIR
: direction typeIR ctk value?
;

typeFrame = map<id, varTypeIR>
```

`typeFrame` is a map from variable names to their types, `varTypeIR`. In addition to the type of the variable, `varTypeIR` also contains the direction of the variable (`direction`), whether it is a compile-time constant (`ctk`), and whether it is associated with a compile-time known value (`value?`).

The compile-time known-ness is discussed in [Section 7.5](#).

Notice that `localTypingLayer` contains multiple `typeFrames`. This is because a local scope can be nested with block statements.

```
typeDefIR
: nameTypeDefIR
```

```

| aliasTypeDefIR
| dataTypeDefIR
| objectTypeDefIR
;

typeDefEnv = map<typeId, typeDefIR>

```

`typeDefEnv` is a map from type names to their type definitions, `typeDefIR`. `typeDefIR` is a type constructor, derived from user-defined type declarations.

```

callableTypeDefIR
: actionTypeDefIR
| functionTypeDefIR
| methodTypeDefIR
;

callableTypeDefEnv = map<callableId, callableTypeDefIR>

```

Functions, methods, and actions can be defined in  $P_{4_{16}}$ . These are collectively called callables. `callableTypeDefEnv` is a map from callable names to their type definitions, `callableTypeDefIR`.

```

constructorTypeDefIR
: CONSTRUCTOR `< typeParameterIR* , typeParameterIR* >
  `( constructorParameterIR* ) : typeIR
;

constructorTypeDefEnv = map<constructorId, constructorTypeDefIR>

```

Stateful objects can be defined in  $P_{4_{16}}$ , which are instantiated using constructors. `constructorTypeDefEnv` is a map from constructor names to their type definitions, `constructorTypeDefIR`.

## 7.3. Instantiation

Instantiation of a program proceeds in order of declarations, starting in the top-level namespace:

- All declarations (e.g., `parsers`, `controls`, types, constants) evaluate to themselves.
- Each `table` evaluates to a table instance.
- Constructor invocations evaluate to stateful objects of the corresponding type. For this purpose, all constructor arguments are evaluated recursively and bound to the constructor parameters. Constructor arguments must be compile-time known values. The order of evaluation of the constructor arguments should be unimportant --- all evaluation orders should produce the same results.
- Instantiations evaluate to named stateful objects.
- The instantiation of a `parser` or `control` block recursively evaluates all stateful instantiations declared in the block.
- The result of the program's evaluation is the value of the top-level `main` variable.

Note that all stateful values are instantiated at compilation time.

As an example, consider the following program fragment:

```

// architecture declaration
parser P(/* parameters omitted */);
control C(/* parameters omitted */);

```

```

control D(/* parameters omitted */);

package Switch(P prs, C ctrl, D dep);

extern Checksum16 { /* body omitted */}

// user code
Checksum16() ck16; // checksum unit instance

parser TopParser(/* parameters omitted */)(Checksum16 unit) { /* body omitted */}
control Pipe(/* parameters omitted */) { /* body omitted */}
control TopDeparser(/* parameters omitted */)(Checksum16 unit) { /* body omitted */}

Switch(TopParser(ck16),
      Pipe(),
      TopDeparser(ck16)) main;

```

The evaluation of this program proceeds as follows:

1. The declarations of **P**, **C**, **D**, **Switch**, and **Checksum16** all evaluate to themselves.
2. The **Checksum16()** **ck16** instantiation is evaluated and it produces an object named **ck16** with type **Checksum16**.
3. The declarations for **TopParser**, **Pipe**, and **TopDeparser** evaluate as themselves.
4. The **main** variable instantiation is evaluated:
  - a. The arguments to the constructor are evaluated recursively.
  - b. **TopParser(ck16)** is a constructor invocation.
    - i. Its argument is evaluated recursively; it evaluates to the **ck16** object.
  - c. The constructor itself is evaluated, leading to the instantiation of an object of type **TopParser**.
  - d. Similarly, **Pipe()** and **TopDeparser(ck16)** are evaluated as constructor calls.
  - e. All the arguments of the **Switch** package constructor have been evaluated (they are an instance of **TopParser**, an instance of **Pipe**, and an instance of **TopDeparser**). Their signatures are matched with the **Switch** declaration.
  - f. Finally, the **Switch** constructor can be evaluated. The result is an instance of the **Switch** package (that contains a **TopParser** named **prs** the first parameter of the **Switch**; a **Pipe** named **ctrl**; and a **TopDeparser** named **dep**).
5. The result of the program evaluation is the value of the **main** variable, which is the above instance of the **Switch** package.

**Figure 8** shows the result of the evaluation in a graphical form. The result is always a graph of instances. There is only one instance of **Checksum16**, called **ck16**, shared between the **TopParser** and **TopDeparser**. Whether this is possible is architecture-dependent. Specific target compilers may require distinct checksum units to be used in distinct blocks.




Figure 8. Evaluation result.

### 7.3.1. Control-plane names

Every controllable entity exposed in a P4 program must be assigned a unique, fully-qualified name, which the control plane may use to interact with that entity. The following entities are controllable.

- value sets
- tables
- keys
- actions
- extern instances

A fully qualified name consists of the local name of a controllable entity prepended with the fully qualified name of its enclosing namespace. Hence, the following program constructs, which enclose controllable entities, must themselves have unique, fully-qualified names.

- control instances
- parser instances

Evaluation may create multiple instances from one type, each of which must have a unique, fully-qualified name.

#### 7.3.1.1. Computing control-plane names

The fully-qualified name of a construct is derived by concatenating the fully-qualified name of its enclosing construct with its local name. Constructs with no enclosing namespace, i.e. those defined at the global scope, have the same local and fully-qualified names. The local names of controllable entities and enclosing constructs are derived from the syntax of a P4 program as follows.

##### 7.3.1.1.1. Value sets

For each `value_set` construct, its syntactic name becomes the local name of the value set. For example:

```
struct vsk_t {
    @match(ternary)
    bit<16> port;
}
value_set<vsk_t>(4) pvs;
```

This `value_set`'s local name is `pvs`.

#### 7.3.1.1.2. Tables

For each **table** construct, its syntactic name becomes the local name of the table. For example:

```
control c(/* parameters omitted */)() {  
  table t { /* body omitted */ }  
}
```

This table's local name is **t**.

#### 7.3.1.1.3. Keys

Syntactically, table keys are expressions. For simple expressions, the local key name can be generated from the expression itself; the algorithm by which a compiler derives control-plane names for complex key expressions is target-dependent.

The spec suggests, but does not mandate, the following algorithm for generating names for some kinds of key expressions:

| Kind                               | Example                         | Name              |
|------------------------------------|---------------------------------|-------------------|
| The <code>isValid()</code> method. | <code>h.isValid()</code>        | "h.isValid()"     |
| Array accesses.                    | <code>header_stack[1]</code>    | "header_stack[1]" |
| Constants.                         | <code>1</code>                  | "1"               |
| Field projections.                 | <code>data.f1</code>            | "data.f1"         |
| Slices.                            | <code>f1[3:0]</code>            | "f1[3:0]"         |
| Masks.                             | <code>h.src &amp; 0xFFFF</code> | "h.src & 0xFFFF"  |

In the following example, the previous algorithm would derive for table **t** two keys with names `data.f1` and `hdrs[3].f2`.

```
table t {  
  keys = {  
    data.f1 : exact;  
    hdrs[3].f2 : exact;  
  }  
  actions = { /* body omitted */ }  
}
```

If a compiler cannot generate a name for a key it *requires* the key expression to be annotated with a `@name` annotation (Section 20.2.3), as in the following example:

```
table t {  
  keys = {  
    data.f1 + 1 : exact @name("f1_mask");  
  }  
  actions = { /* body omitted */ }  
}
```

Here, the `@name("f1_mask")` annotation assigns the local name "f1\_mask" to this key.

#### 7.3.1.1.4. Actions

For each **action** construct, its syntactic name is the local name of the action. For example:



```
control c(/* parameters omitted */)() {
  action a(...) { /* body omitted */ }
}
```

This action's local name is **a**.

#### 7.3.1.1.5. Instances

The local names of **extern**, **parser**, and **control** instances are derived based on how the instance is used. If the instance is bound to a name, that name becomes its local control plane name. For example, if **control C** is declared as,

```
control C(/* parameters omitted */)() { /* body omitted */ }
```

and instantiated as,

```
C() c_inst;
```

then the local name of the instance is **c\_inst**.

Alternatively, if the instance is created as an actual argument, then its local name is the name of the formal parameter to which it will be bound. For example, if **extern E** and **control C** are declared as,

```
extern E { /* body omitted */ }
control C(/* parameters omitted */)(E e_in) { /* body omitted */ }
```

and instantiated as,

```
C(E()) c_inst;
```

then the local name of the extern instance is **e\_in**.

If the construct being instantiated is passed as an argument to a package, the instance name is derived from the user-supplied type definition when possible. In the following example, the local name of the instance of **MyC** is **c**, and the local name of the **extern** is **e2**, not **e1**.

```
extern E { /* body omitted */ }
control ArchC(E e1);
package Arch(ArchC c);

control MyC(E e2)() { /* body omitted */ }
Arch(MyC()) main;
```

Note that in this example, the architecture will supply an instance of the extern when it applies the instance of **MyC** passed to the **Arch** package. The fully-qualified name of that instance is **main.c.e2**.

Next, consider a larger example that demonstrates name generation when there are multiple instances.

```
control Callee() {
  table t { /* body omitted */ }
  apply { t.apply(); }
}
control Caller() {
```

```

Callee() c1;
Callee() c2;
apply {
  c1.apply();
  c2.apply();
}
}
control Simple();
package Top(Simple s);
Top(Caller()) main;

```

The compile-time evaluation of this program produces the structure in [Figure 9](#). Notice that there are two instances of the `table t`. These instances must both be exposed to the control plane. To name an object in this hierarchy, one uses a path composed of the names of containing instances. In this case, the two tables have names `s.c1.t` and `s.c2.t`, where `s` is the name of the argument to the package instantiation, which is derived from the name of its corresponding formal parameter.




Figure 9. Evaluating a program that has several instantiations of the same component.

### 7.3.1.2. Annotations controlling naming

Control plane-related annotations ([Section 20.2.3](#)) can alter the names exposed to the control plane in the following ways.

- The `@hidden` annotation hides a controllable entity from the control plane. This is the only case in which a controllable entity is not required to have a unique, fully-qualified name.
- The `@name` annotation may be used to change the local name of a controllable entity.

Programs that yield the same fully-qualified name for two different controllable entities are invalid.

### 7.3.1.3. Recommendations

The control plane may refer to a controllable entity by a postfix of its fully qualified name when it is unambiguous in the context in which it is used. Consider the following example.

```

control c(/* parameters omitted */>() {
  action a (/* parameters omitted */) { /* body omitted */ }
  table t {
    keys = { /* body omitted */ }
    actions = { a; } }
}
c() c_inst;

```

Control plane software may refer to action `c_inst.a` as `a` when inserting rules into table `c_inst.t`, because it is clear from the definition of the table which action `a` refers to.

Not all unambiguous postfix shortcuts are recommended. For instance, consider the last example in [Section 7.3.1.1.5](#). One might be tempted to refer to `s.c1` simply as `c1`, as no other instance named `c1` appears in the program. However, this leads to a brittle program since future modifications can never introduce an instance named `c1`, or include libraries of P4 code that contain instances with that name.

## 7.3.2. Instantiating a P4 program

```
objectId = nameIR*

object
: externObject
| parserObject
| controlObject
| packageObject
| tableObject
| valueSetObject
;
```

The stateful elements of a P4 program are represented as `objects`. These objects are identified by their fully-qualified names (`objectId`).

```
store = map<objectId, object>
```

A  $P4_{16}$  program is first type checked to yield a  $P4_{IR}$  program, and is then instantiated to create a `store`, which maps `objectIds` to `objects`.

### Program\_inst:

- Loading `p4program`:
- Result in global instantiation layer `globalInstLayer` and store `store`.

### Loading `p4program`:

1. Let typed P4 program `declarationIR*`; be
  - the result of `typing p4program`.
2. Let `IC0` be an empty instantiation context.
3. Let `STO0` be an empty store.
4. Let context `IC1` and store `STO1` be
  - the result of `loading declarationIR*, under context IC0, and store STO0`.
5. Result in global instantiation layer `IC1.GLOBAL` and store `STO1`.

## 7.3.3. Instantiation context

```
globalInstLayer = {
  CONSTRUCTOR constructorDefEnv,
```

```

TYPE typeDefEnv,
CALLABLE callableDefEnv,
FRAME frame
}

blockInstLayer = {
  TYPE theta,
  CALLABLE callableDefEnv,
  STATE stateEnv,
  FRAME frame
}

localInstLayer = {
  TYPE theta,
  FRAMES frame*
}

instContext = {
  PATH objectId,
  GLOBAL globalInstLayer,
  BLOCK blockInstLayer,
  LOCAL localInstLayer
}

```

An instantiation context is used to keep track of the types and compile-time known values of all named declarations in scope at a given program point.

- A global instantiation layer, which contains all declarations at the top level of a P4 program.
- A block instantiation layer, which contains all declarations in the current block scope.
- A local instantiation layer, which contains all declarations in the current local scope.

```

value
: baseValue
| dataValue
| objectReferenceValue
| synthesizedValue
;

frame = map<id, value>

```

`frame` is a map from variable names to their compile-time known values, `value`. The compile-time knownness is discussed in [Section 7.5](#).

```

typeDefIR
: nameTypeDefIR
| aliasTypeDefIR
| dataTypeDefIR
| objectTypeDefIR
;

typeDefEnv = map<typeId, typeDefIR>

```

`typeDefEnv` is a map from type names to their type definitions, `typeDefIR`. `typeDefIR` is a type constructor, derived from user-defined type declarations.

```

callableDef
: actionDef
| functionDef
| methodDef
;

```

```
callableDefEnv = map<callableId, callableDef>
```

`callableDefEnv` is a map from callable names to their definitions, `callableDef`.

```
constructorDef
: externObjectConstructorDef
| parserObjectConstructorDef
| controlObjectConstructorDef
| packageObjectConstructorDef
;

constructorDefEnv = map<callableId, constructorDef>
```

Stateful objects are instantiated using constructors. `constructorDefEnv` is a map from constructor names to their definitions, `constructorDef`.

## 7.4. Runtime evaluation

The runtime evaluation of a P4 program is orchestrated by the architecture model. Each architecture model needs to specify the order and the conditions under which the various P4 component programs are dynamically executed. For example, in the Simple Switch example from [Section 5.1](#) the execution flow goes `Parser` `Pipe` `Deparser`.

Once a P4 execution block is invoked its execution proceeds until termination according to the semantics defined in this document. P4 execution blocks are represented as objects in the global store, which is statically allocated during instantiation.

### 7.4.1. Evaluating a P4 program

P4 program evaluation proceeds by invoking the objects in the global store. A call to a programmable block invokes the corresponding abstract machine:

#### `Call_eval`:

- Calling `callee < typeArgumentListIR > ( argumentListIR )`, under cursor `cursor`, context `evalContext`, and state `arch`:
- Result in context `evalContext`, state `arch`, and call result `callResult`.

A call to an extern function invokes the corresponding extern function:

#### `ExternFunctionCall_eval`:

- Calling an extern function `nameIR ( nameIR* )`, under context `evalContext`, and state `arch`:
- Result in context `evalContext`, state `arch`, and call result `callResult`.

A call to an extern method invokes the corresponding extern method:

#### `ExternMethodCall_eval`:

- Calling an extern method `nameIR ( nameIR* )` on object `objectId`, under context `evalContext`, and state

arch:

- Result in context `evalContext`, state `arch`, and call result `callResult`.

### 7.4.2. Evaluation context

```
globalEvalLayer = globalInstLayer

blockEvalLayer = blockInstLayer

localEvalLayer = localInstLayer

evalContext = {
  GLOBAL globalEvalLayer,
  BLOCK blockEvalLayer,
  LOCAL localEvalLayer
}
```

An evaluation context is used to keep track of the types and compile-time known values of all named declarations in scope at a given program point.

- A global evaluation layer, which contains all declarations at the top level of a P4 program.
- A block evaluation layer, which contains all declarations in the current block scope.
- A local evaluation layer, which contains all declarations in the current local scope.

The layers are the same as in the instantiation context, except that the `frame` is a map from variable names to their current runtime values.

The following sections describe the abstract machines that define the dynamic semantics of the programmable blocks in a P4 target.

### 7.4.3. The parser abstract machine

A parser starts execution in the `start` state and ends execution when one of the `reject` or `accept` states has been reached.

An architecture must specify the behavior when the `accept` and `reject` states are reached. For example, an architecture may specify that all packets reaching the `reject` state are dropped without further processing. Alternatively, it may specify that such packets are passed to the next block after the parser, with intrinsic metadata indicating that the parser reached the `reject` state, along with the error recorded.

### 7.4.4. The match-action pipeline abstract machine

We can describe the computational model of a match-action pipeline, embodied by a control block: the body of the control block is executed, similarly to the execution of a traditional imperative program:

- At runtime, statements within a block are executed in the order they appear in the control block.
- Execution of the `return` statement causes the immediate termination of the execution of the current `control` block and a return to the caller.
- Execution of the `exit` statement causes the immediate termination of the execution of the current `control` block and of all the enclosing caller `control` blocks.
- Applying a `table` executes the corresponding match-action unit.

## 7.4.5. Concurrency model

A typical packet processing system needs to execute multiple simultaneous logical "threads." At the very least there is a thread executing the control plane, which can modify the contents of the tables. Architecture specifications should describe in detail the interactions between the control-plane and the data-plane. The data plane can exchange information with the control plane through `extern` function and method calls. Moreover, high-throughput packet-processing systems may be processing multiple packets simultaneously, e.g., in a pipelined fashion, or concurrently parsing a first packet while performing match-action operations on a second packet. This section specifies the semantics of P4 programs with respect to such concurrent executions.

Each top-level `parser` or `control` block is executed as a separate thread when invoked by the architecture. All the parameters of the block and all local variables are thread-local—i.e., each thread has a private copy of these resources. This applies to the `packet_in` and `packet_out` parameters of parsers and deparsers.

As long as a P4 block uses only thread-local storage (e.g., metadata, packet headers, local variables), its behavior in the presence of concurrency is identical with the behavior in isolation, since any interleaving of statements from different threads must produce the same output.

In contrast, `extern` blocks instantiated by a P4 program are global, shared across all threads. If `extern` blocks mediate access to state (e.g., counters, registers)—i.e., the methods of the `extern` block read and write state, these stateful operations are subject to data races. P4 mandates that execution of a method call on an `extern` instance is atomic.

To allow users to express atomic execution of larger code blocks, P4 provides an `@atomic` annotation, which can be applied to block statements, parser states, control blocks, or whole parsers.

Consider the following example:

```
extern Register { /* body omitted */ }
control Ingress() {
  Register() r;
  table flowlet { /* read state of r in an action */ }
  table new_flowlet { /* write state of r in an action */ }
  apply {
    @atomic {
      flowlet.apply();
      if (ingress_metadata.flow_ipg > FLOWLET_INACTIVE_TIMEOUT)
        new_flowlet.apply();
    }
  }
}
```

This program accesses an `extern` object `r` of type `Register` in actions invoked from tables `flowlet` (reading) and `new_flowlet` (writing). Without the `@atomic` annotation these two operations would not execute atomically: a second packet may read the state of `r` before the first packet had a chance to update it.

Note that even within an `action` definition, if the action does something like reading a register, modifying it, and writing it back, in a way that only the modified value should be visible to the next packet, then, to guarantee correct execution in all cases, that portion of the action definition should be enclosed within a block annotated with `@atomic`.

A compiler backend must reject a program containing `@atomic` blocks if it cannot implement the atomic execution of the instruction sequence. In such cases, the compiler should provide reasonable diagnostics.

The P4 semantics described throughout this document assumes a sequential execution model. Thus, it does not describe the interactions between multiple threads accessing shared state. The purpose of this document is to clearly define the semantics of P4 constructs in isolation. The exact concurrency model, including the interactions between multiple threads, is target-dependent and beyond the scope of this document.

## 7.5. Compile-time known and local compile-time known values

Certain expressions in a P4 program have the property that their value can be determined at compile time. Moreover, for some of these expressions, their value can be determined only using information in the current scope. We call these *compile-time known values* and *local compile-time known values* respectively.

The following are local compile-time known values:

- Integer literals, Boolean literals, and string literals.
- Identifiers declared as constants using the `const` keyword.
- Identifiers declared in an `error`, `enum`, or `match_kind` declaration.
- The `default` identifier.
- The `size` field of a value with type header stack.
- The `_` identifier when used as a `select` expression label.
- The expression `{#}` representing an invalid header or header union value.
- Identifiers that represent declared types, actions, functions, tables, parsers, controls, or packages.
- Tuple expression where all components are local compile-time known values.
- Structure-valued expressions, where all fields are local compile-time known values.
- Expressions evaluating to a list type, where all elements are local compile-time known values.
- Legal casts applied to local compile-time known values.
- Indexing a local compile-time known stack or tuple value with a local compile-time known index.
- Accessing a field of a local compile-time known struct, header, or header union value.
- The following expressions `(+, -, |+, |-|, *, /, %, !, &, |, ^, &&, ||, <<, >>, ~, >, <, ==, !=, <=, >=, ++, [:, ?:)` when their operands are all local compile-time known values.
- Expressions of the form `e.minSizeInBits()`, `e.minSizeInBytes()`, `e.maxSizeInBits()` and `e.maxSizeInBytes()` where the type of `e` is not generic.

The following are compile-time known values:

- All local compile-time known values.
- Constructor parameters (i.e., the declared parameters for a `parser`, `control`, etc.)
- Tuple expression where all components are compile-time known values.
- Structure-valued expressions, where all fields are compile-time known values.
- Expressions evaluating to a list type, where all elements are compile-time known values.
- Legal casts applied to compile-time known values.
- Indexing a compile-time known stack or tuple value with a compile-time known index.
- Accessing a field of a compile-time known struct, header, or header union value.
- The following expressions `(+, -, |+, |-|, *, /, %, !, &, |, ^, &&, ||, <<, >>, ~, >, <, ==, !=, <=, >=, ++, [:, ?:)` when their operands are all compile-time known values.
- Expressions of the form `e.minSizeInBits()`, `e.minSizeInBytes()`, `e.maxSizeInBits()` and `e.maxSizeInBytes()` where the type of `e` is generic.

Intuitively, the main difference between *compile-time known values* and *local compile-time known*



*values* is that the former also contains constructor parameters. The distinction is important when it comes to defining the meaning of features like types. For example, in the type `bit<e>`, the expression `e` must be a local compile-time known value. Suppose instead that `e` were a constructor parameter—i.e., merely a compile-time known value. In this situation, it would be impossible to resolve `bit<e>` to a concrete type using purely local information—we would have to wait until the constructor was instantiated and the value of `e` known.

Local compile-time known values can be identified in the type checking phase. Compile-time known values can be identified after type checking, during the instantiation phase. Once the constructor parameters are bound to actual arguments and type parameters are bound to actual types, compile-time known values can be evaluated to concrete values.

`ctk` is a marker used in  $P4_{IR}$  to indicate whether an expression is local compile-time known, compile-time known, or neither.

```
ctk
: LCTK
| CTK
| DYN
;
```

`typedExpressionIRs` in  $P4_{IR}$ , produced by typing `expressions` in  $P4_{16}$ , annotated with their type `typeIR` and a `ctk` marker indicating the compile-time known status.

```
expressionNoteIR
: `( typeIR ctk )
;

typedExpressionIR
: expressionIR # expressionNoteIR
;
```

## 8. P4 types and values

$P4_{16}$  is a statically-typed language. Programs that do not pass the type checker are considered invalid and rejected by the compiler. P4 provides a number of base types as well as type operators that construct derived types.

The syntax for P4 types is as follows:

```
type
: baseType
| namedType
| headerStackType
| listType
| tupleType
;

typeOrVoid
: type
| VOID
| identifier
;
```

These types are represented in  $P4_{IR}$  as follows:

```

typeIR
: baseTypeIR
| nameTypeIR
| aliasTypeIR
| dataTypeIR
| objectTypeIR
| synthesizedTypeIR
;

```

The types represent the kinds of values that can be used in P4 programs. The runtime representation of P4 values is as follows:

```

value
: baseValue
| dataValue
| objectReferenceValue
| synthesizedValue
;

```

## 8.1. Semantics of types

### 8.1.1. Type checking surface types

`typeIR` is constructed from type checking the surface syntax of P4 types (`type`) with the following relation:

`Type_ok`:

- Typing `typeOrVoid`, under cursor `cursor` and context `typingContext`:
- Result in `typeIR` and a set of fresh type variables `typed*`.

### 8.1.2. Well-formedness

The P4 type system also imposes well-formedness constraints on types, which enforce additional restrictions on the structure of types, such as type nesting.

`Type_wf`:

- `typeIR` is a well-formed type, with bound type variables `B`

## 8.2. Base types and values

P4 supports the following built-in base types:

- `bool`, which represents Boolean values
- The `error` type, which is used to convey errors in a target-independent, compiler-managed way.
- The `match_kind` type, which is used for describing the implementation of table lookups,
- The `string` type, which can be used with compile-time known values of type string.
- `int`, which represents arbitrary-sized integer values

- Fixed-width signed integers represented using two's complement `int<>`
- Bit-strings of fixed width, denoted by `bit<>`
- Bit-strings of dynamically-computed width with a fixed maximum width `varbit<>`

```
baseType
: BOOL
| ERROR
| MATCH_KIND
| STRING
| INT
| INT `< int >
| INT `< `( expression ) >
| BIT
| BIT `< int >
| BIT `< `( expression ) >
| VARBIT `< int >
| VARBIT `< `( expression ) >
;
```

In addition, P4 supports void types:

```
typeOrVoid
: type
| VOID
| identifier
;
```

- The `void` type, which has no values and can be used only in a few restricted circumstances.

In P4<sub>IR</sub>, base types and values are represented as:

```
baseTypeIR
: voidTypeIR
| boolTypeIR
| errorTypeIR
| matchKindTypeIR
| stringTypeIR
| integerTypeIR
;

baseValue
: boolValue
| errorValue
| matchKindValue
| stringValue
| integerValue
;
```

### 8.2.1. Well-formedness

The well-formedness rules for base types are as follows:

`baseTypeIR` is a well-formed type, with bound type variables `B` when:

1. The relation holds.

## 8.2.2. The void type

```
voidTypeIR
: VOID
;
```

The void type is written `void`. It contains no values. It is not included in the production rule `baseType` as it can only appear in few restricted places in P4 programs.

There is no value of type `void`.

### 8.2.2.1. Type checking

Typing `VOID`, under cursor `p` and context `TC`:

1. Result in `VOID` and a set of fresh type variables `.`.

## 8.2.3. Booleans

```
boolTypeIR
: BOOL
;

boolValue
: `B bool
;
```

The Boolean type `bool` contains just two values, `false` and `true`. Boolean values are not integers or bit-strings.

### 8.2.3.1. Operations

The following operations are provided on Boolean expressions:

- And, denoted by `&&`
- Or, denoted by `||`
- Negation, denoted by `!`
- Equality and inequality tests, denoted by `==` and `!=` respectively.

The precedence of these operators is similar to C and uses short-circuited evaluation where relevant.

Additionally, the size of a boolean can be determined at compile-time (`[sec-minsizeinbits]`).

P4 does not implicitly cast from bit-strings to Booleans or vice versa. As a consequence, a program that is valid in a language like C such as,

```
if (x) /* body omitted */
```

(where `x` has an integer type) must instead be written in P4 as:

```
if (x != 0) /* body omitted */
```

See the discussion on arbitrary-precision types and implicit casts in [Section 17.2](#) for details on how the 0 in this expression is evaluated.

### 8.2.3.2. Type checking

Typing `BOOL`, under cursor `p` and context `TC`:

1. Result in `BOOL` and a set of fresh type variables `.`

### 8.2.4. Errors

```
errorTypeIR
: ERROR
;

errorValue
: ERROR . nameIR
;
```

The error type contains opaque distinct values that can be used to signal errors. It is written as `error`. New elements of the error type are defined with the following syntax:

```
errorDeclaration
: ERROR `{ nameList }
;
```

All elements of the `error` type are inserted into the `error` namespace, irrespective of the place where an error is defined. `error` is similar to an enumeration (`enum`) type in other languages. A program can contain multiple `error` declarations, which the compiler will merge together. It is an error to declare the same identifier multiple times.

Error declaration is described in detail in [Section 11.7](#).

For example, the following declaration creates two elements of the `error` type (these errors are declared in the P4 core library):

```
error { ParseError, PacketTooShort }
```

The underlying representation of errors is target-dependent.

See [Section 11.7](#) for the semantics of error declarations and [Section 14.12](#) for accessing error values.

#### 8.2.4.1. Operations

Symbolic names declared by an `error` declaration belong to the `error` namespace. The `error` type only supports equality (`==`) and inequality (`!=`) comparisons. The result of such a comparison is a Boolean value.

For example, the following operation tests for the occurrence of an error:

```
error errorFromParser;

if (errorFromParser != error.NoError) { /* code omitted */ }
```

#### 8.2.4.2. Type checking

Typing `ERROR`, under cursor `p` and context `TC`:

1. Result in `ERROR` and a set of fresh type variables `.`

#### 8.2.5. Match kinds

```
matchKindTypeIR
: MATCH_KIND
;

matchKindValue
: MATCH_KIND . nameIR
;
```

The `match_kind` type is very similar to the `error` type and is used to declare a set of distinct names that may be used in a table's key property (described in [\[sec-table-props\]](#)). All identifiers are inserted into the top-level namespace. It is an error to declare the same `match_kind` identifier multiple times.

```
matchKindDeclaration
: MATCH_KIND `{ nameList trailingCommaOpt }
;
```

The P4 core library contains the following `match_kind` declaration:

```
match_kind {
    exact,
    ternary,
    lpm
}
```

Architectures may support additional `match_kinds`. The declaration of new `match_kinds` can only occur within model description files; P4 programmers cannot declare new match kinds.

Match kind declaration is described in detail in [Section 11.8](#).

##### 8.2.5.1. Operations

Values of type `match_kind` are similar to `enum` values. They support only assignment and comparisons for equality and inequality.

```
match_kind { fuzzy }
const bool same = exact == fuzzy; // always 'false'
```

### 8.2.5.2. Type checking

Typing `MATCH_KIND`, under cursor `p` and context `TC`:

1. Result in `MATCH_KIND` and a set of fresh type variables `·`.

### 8.2.6. Strings

```
stringTypeIR
  : STRING
  ;

stringValue = stringLiteral
```

The type `string` represents strings. The values of type `string` are either string literals, or concatenations of multiple `string`-typed expressions.

One cannot declare variables with a `string` type. Parameters with type `string` can be only directionless (see Section [Section 18.4](#)). P4 does not support string manipulation in the dataplane; the `string` type is only allowed for describing compile-time known values (i.e., string literals, as discussed in Section [Section 6.2.2.3](#)). Even so, the string type is useful, for example, in giving the type signature for extern functions such as the following:

```
extern void log(string message);
```

As another example, the following annotation indicates that the specified name should be used for a given table in the generated control-plane API:

```
@name("acl") table t1 { /* body omitted */ }
```

#### 8.2.6.1. Operations

The only operation allowed on strings is concatenation, denoted by `++`. For string concatenation, both operands must be strings and the result is also a string. String concatenation can only be performed at compile time.

```
extern void log(string message);

void foo(int<8> v) {
  // ...
  log("my log message " ++
      "continuation of the log message");
}
```

### 8.2.6.2. Type checking

Typing `STRING`, under cursor `p` and context `TC`:

1. Result in `STRING` and a set of fresh type variables `·`.

## 8.2.7. Integers (signed and unsigned)

```
integerTypeIR
  : intTypeIR
  | fixedIntTypeIR
  | fixedBitTypeIR
  | varBitTypeIR
  ;

integerLiteral
  : D int
  | nat W int
  | nat S int
  ;

integerValue
  : integerLiteral
  | nat . nat V int
  ;
```

P4 supports arbitrary-size integer values. The typing rules for the integer types are chosen according to the following principles:

- **Inspired by C:** Typing of integers is modeled after the well-defined parts of C, expanded to cope with arbitrary fixed-width integers. In particular, the type of the result of an expression only depends on the expression operands, and not on how the result of the expression is consumed.
- **No undefined behaviors:** P4 attempts to avoid many of C’s behaviors, which include the size of an integer (int), the results produced on overflow, and the results produced for some input combinations (e.g., shifts with negative amounts, overflows on signed numbers, etc.). P4 computations on integer types have no undefined behaviors.
- **Least surprise:** The P4 typing rules are chosen to behave as closely as possible to traditional well-behaved C programs.
- **Forbid rather than surprise:** Rather than provide surprising or undefined results (e.g., in C comparisons between signed and unsigned integers), we have chosen to forbid expressions with ambiguous interpretations. For example, P4 does not allow binary operations that combine signed and unsigned integers.

The priority of arithmetic operations is identical to C—e.g., multiplication binds tighter than addition.

### 8.2.7.1. Portability

No P4 target can support all possible types and operations. For example, the type `bit<23132312>` is legal in P4, but it is highly unlikely to be supported on any target in practice. Hence, each target can impose restrictions on the types it can support. Such restrictions may include:

- The maximum width supported
- Alignment and padding constraints (e.g., arithmetic may only be supported on widths which are an integral number of bytes).
- Constraints on some operands (e.g., some architectures may only support multiplications by small values, or shifts with small values).

The documentation supplied with a target should clearly specify restrictions, and target-specific compilers should provide clear error messages when such restrictions are encountered. An architecture may reject a well-typed P4 program and still be conformant to the P4 spec. However, if an architecture accepts a P4 program as valid, the runtime program behavior should match this specification.



### 8.2.7.2. Integer literals

The types of integer literals are as follows:

- An integer with no type prefix has type `int`.
- A non-negative integer prefixed with an integer width `W` and the character `w` has type `bit<W>`.
- An integer prefixed with an integer width `W` and the character `s` has type `int<W>`.

The table below shows several examples of integer literals and their types. For additional examples of literals see [Section 6.2.2](#).

| Literal           | Interpretation                                                                  |
|-------------------|---------------------------------------------------------------------------------|
| <code>10</code>   | Type is <code>int</code> , value is 10                                          |
| <code>8w10</code> | Type is <code>bit&lt;8&gt;</code> , value is 10                                 |
| <code>8s10</code> | Type is <code>int&lt;8&gt;</code> , value is 10                                 |
| <code>2s3</code>  | Type is <code>int&lt;2&gt;</code> , value is -1 (last 2 bits), overflow warning |
| <code>1w10</code> | Type is <code>bit&lt;1&gt;</code> , value is 0 (last bit), overflow warning     |
| <code>1s1</code>  | Type is <code>int&lt;1&gt;</code> , value is -1, overflow warning               |

### 8.2.7.3. Illegal arithmetic expressions

Many arithmetic expressions that would be allowed in other languages are illegal in P4. To illustrate, consider the following declarations:

```
bit<8> x;  
bit<16> y;  
int<8> z;
```

The table below shows several expressions which are illegal because they do not obey the P4 typing rules. For each expression we provide several ways that the expression could be manually rewritten into a legal expression. Note that for some expression there are several legal alternatives, which may produce different results! The compiler cannot guess the user intent, so P4 requires the user to disambiguate.

| Expression                   | Why it is illegal                 | Alternatives                                                                                                                                                                                            |
|------------------------------|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x + y</code>           | Different widths                  | <code>(bit&lt;16&gt;)x + y</code><br><code>x + (bit&lt;8&gt;)y</code>                                                                                                                                   |
| <code>x + z</code>           | Different signedness              | <code>(int&lt;8&gt;)x + z</code><br><code>x + (bit&lt;8&gt;)z</code>                                                                                                                                    |
| <code>(int&lt;8&gt;)y</code> | Cannot change both sign and width | <code>(int&lt;8&gt;)(bit&lt;8&gt;)y</code><br><code>(int&lt;8&gt;)(int&lt;16&gt;)y</code>                                                                                                               |
| <code>y + z</code>           | Different widths and signs        | <code>(int&lt;8&gt;)(bit&lt;8&gt;)y + z</code><br><code>y + (bit&lt;16&gt;)(bit&lt;8&gt;)z</code><br><code>(bit&lt;8&gt;)y + (bit&lt;8&gt;)z</code><br><code>(int&lt;16&gt;)y + (int&lt;16&gt;)z</code> |
| <code>x &lt;&lt; z</code>    | RHS of shift cannot be signed     | <code>x &lt;&lt; (bit&lt;8&gt;)z</code>                                                                                                                                                                 |
| <code>x &lt; z</code>        | Different signs                   | <code>x &lt; (bit&lt;8&gt;)z</code>                                                                                                                                                                     |

| Expression                | Why it is illegal                                 | Alternatives                        |
|---------------------------|---------------------------------------------------|-------------------------------------|
|                           |                                                   | <code>(int&lt;8&gt;)x &lt; z</code> |
| <code>1 &lt;&lt; x</code> | Either LHS should have a fixed width (bit shift), | <code>32w1 &lt;&lt; x</code>        |
|                           | Or RHS must be compile-time known (int shift)     | None                                |
| <code>~1</code>           | Bitwise operation on int                          | <code>~32w1</code>                  |
| <code>5 &amp; -3</code>   | Bitwise operation on int                          | <code>32w5 &amp; -3</code>          |

#### 8.2.7.4. Arbitrary-precision integers

The arbitrary-precision data type describes integers with an unlimited precision. This type is written as `int`.

This type is reserved for integer literals and expressions that involve only literals. No P4 runtime value can have an `int` type; at compile time the compiler will convert all `int` values that have a runtime component to fixed-width types, according to the rules described below.

The following example shows three constant definitions whose values are arbitrary-precision integers.

```
const int a = 5;
const int b = 2 * a;
const int c = b - a + 3;
```

Parameters with type `int` are not supported for actions. Parameters with type `int` for other callable entities of a program, e.g. controls, parsers, or functions, must be directionless, indicating that all calls must provide a compile-time known value as an argument for such a parameter. See [Section 18.4](#) for more details on directionless parameters.

##### 8.2.7.4.1. Operations

The type `int` denotes arbitrary-precision integers. In P4, all expressions of type `int` must be compile-time known values. The type `int` supports the following operations:

- Negation, denoted by unary `-`.
- Unary plus, denoted by `+`. This operation behaves like a no-op.
- Addition, denoted by `+`.
- Subtraction, denoted by `-`.
- Comparison for equality and inequality, denoted by `==` and `!=` respectively. These operations produce a Boolean result.
- Numeric comparisons `<`, `<=`, `>`, and `>=`. These operations produce a Boolean result.
- Multiplication, denoted by `*`.
- Truncating integer division between positive values, denoted by `/`.
- Modulo between positive values, denoted by `%`.
- Arithmetic shift left and right denoted by `<<` and `>>`. These operations produce an `int` result. The right operand must be either an unsigned value of type `bit<S>` or a compile-time known value that is a non-negative integer.
- Bit slices, denoted by `[H:L]`, where `H` and `L` must be expressions that evaluate to non-negative, local compile-time known values, and `H >= L` must be true. The types of `H` and `L` (which do not need to be identical) must be one of the following:

- `int` - an arbitrary-precision integer ([[sec-arbitrary-precision-integers](#)])
- `bit<W>` - a `W`-bit unsigned integer where `W >= 0` ([[sec-unsigned-integers](#)])
- `int<W>` - a `W`-bit signed integer where `W >= 1` ([[sec-signed-integers](#)])
- a serializable `enum` with an underlying type that is `bit<W>` or `int<W>` ([[sec-enum-types](#)]).

The result is an unsigned bit-string of width `H - L + 1`, including the bits numbered from `L` (which becomes the least significant bit of the result) to `H` (the most significant bit of the result) from the source operand. The conditions `0 <= L <= H` are checked statically. If necessary, the source integer value that is sliced is automatically extended to have a width with `H` bits. Note that both endpoints of the extraction are inclusive. The bounds are required to be values that are known at compile time so that the width of the result can be computed at compile time. A slice of a negative or positive value is always a positive value.

Each operand that participates in any of these operation must have type `int` (except shifts). Binary operations cannot be used to combine values of type `int` with values of a fixed-width type (except shifts). However, the compiler automatically inserts casts from `int` to fixed-width types in certain situations—see [Chapter 17](#).

All computations on `int` values are carried out without loss of information. For example, multiplying two 1024-bit values may produce a 2048-bit value (note that concrete representation of `int` values is not specified). `int` values can be cast to `bit<w>` and `int<w>` values. Casting an `int` value to a fixed-width type will preserve the least-significant bits. If truncation causes significant bits to be lost, the compiler should emit a warning.

Note: bitwise-operations (`|`, `&`, `^`, `~`) are not defined on expressions of type `int`. In addition, it is illegal to apply division and modulo to negative values. Saturating arithmetic is not supported for arbitrary-precision integers.

#### 8.2.7.4.2. Type checking

Typing `INT`, under cursor `p` and context `TC`:

1. Result in `INT` and a set of fresh type variables `.`

#### 8.2.7.5. Fixed-width unsigned integers (bit-strings)

An unsigned integer (which we also call a "bit-string") has an arbitrary width, expressed in bits. A bit-string of width `W` is declared as: `bit<W>`. `W` must be an expression that evaluates to a local compile-time known value (see [Section 7.5](#)) that is a non-negative integer. When using an expression for the size, the expression must be parenthesized. Bitstrings with width 0 are allowed; they have no actual bits, and can only have the value 0. See [[sec-uninitialized-values-and-writing-invalid-headers](#)] for additional details. Note that `bit<W>` type refers to both cases of `bit<W>` and `bit<(expression)>` where the width is a local compile-time known value.

```
const bit<32> x = 10;    // 32-bit constant with value 10.
const bit<(x + 2)> y = 15; // 12-bit constant with value 15.
                        // expression for width must use ()
```

Bits within a bit-string are numbered from 0 to `W-1`. Bit 0 is the least significant, and bit `W-1` is the most significant.

For example, the type `bit<128>` denotes the type of bit-string values with 128 bits numbered from 0 to 127, where bit 127 is the most significant.

The type `bit` is a shorthand for `bit<1>`.

P4 architectures may impose additional constraints on bit types: for example, they may limit the maximum size, or they may only support some arithmetic operations on certain sizes (e.g., 16-, 32-, and 64-bit values).

#### 8.2.7.5.1. Operations

This section discusses all operations that can be performed on expressions of type `bit<W>` for some width `W`, also known as bit-strings.

Arithmetic operations "wrap around", similar to C operations on unsigned values (i.e., representing a large value on `W` bits will only keep the least-significant `W` bits of the value). In particular, P4 does not have arithmetic exceptions—the result of an arithmetic operation is defined for all possible inputs.

P4 target architectures may optionally support saturating arithmetic. All saturating operations are limited to a fixed range between a minimum and maximum value. Saturating arithmetic has advantages, in particular when used as counters. The result of a saturating counter max-ing out is much closer to the real result than a counter that overflows and wraps around. According to Wikipedia [Saturating Arithmetic](#) is as numerically close to the true answer as possible; for 8-bit binary signed arithmetic, when the correct answer is 130, it is considerably less surprising to get an answer of 127 from saturating arithmetic than to get an answer of  $-126$  from modular arithmetic. Likewise, for 8-bit binary unsigned arithmetic, when the correct answer is 258, it is less surprising to get an answer of 255 from saturating arithmetic than to get an answer of 2 from modular arithmetic. At this time, P4 defines saturating operations only for addition and subtraction. For an unsigned integer with bit-width of `W`, the minimum value is 0 and the maximum value is  $2^W-1$ . The precedence of saturating addition and subtraction operations is the same as for modular arithmetic addition and subtraction.

All binary operations except shifts and concatenation require both operands to have the same exact type and width; supplying operands with different widths produces an error at compile time. No implicit casts are inserted by the compiler to equalize the widths. There are no other binary operations that accept signed and unsigned values simultaneously besides shifts and concatenation. The following operations are provided on bit-string expressions:

- Test for equality between bit-strings of the same width, designated by `==`. The result is a Boolean value.
- Test for inequality between bit-strings of the same width, designated by `!=`. The result is a Boolean value.
- Unsigned comparisons `<`, `>`, `<=`, `>=`. Both operands must have the same width and the result is a Boolean value.

Each of the following operations produces a bit-string result when applied to bit-strings of the same width:

- Negation, denoted by unary `-`. The result is computed by subtracting the value from  $2^W$ . The result is unsigned and has the same width as the input. The semantics is the same as the C negation of unsigned numbers.
- Unary plus, denoted by `+`. This operation behaves like a no-op.
- Addition, denoted by `+`. This operation is associative. The result is computed by truncating the result of the addition to the width of the output (similar to C).
- Subtraction, denoted by `-`. The result is unsigned, and has the same type as the operands. It is computed by adding the negation of the second operand (similar to C).
- Multiplication, denoted by `*`. The result has the same width as the operands and is computed by truncating the result to the output's width. P4 architectures may impose additional restrictions—e.g., they may only allow multiplication by a non-negative integer power of two.

- Bitwise "and" between two bit-strings of the same width, denoted by `&`.
- Bitwise "or" between two bit-strings of the same width, denoted by `|`.
- Bitwise "complement" of a single bit-string, denoted by `~`.
- Bitwise "xor" of two bit-strings of the same width, denoted by `^`.
- Saturating addition, denoted by `|+|`.
- Saturating subtraction, denoted by `|-|`.

Bit-strings also support the following operations:

- Logical shift left and right by a non-negative integer value (which need not be a compile-time known value), denoted by `<<` and `>>` respectively. In a shift, the left operand is unsigned, and right operand must be either an expression of type `bit<S>` or a non-negative integer value that is known at compile time. The result has the same type as the left operand. Shifting by an amount greater than or equal to the width of the input produces a result where all bits are zero.
- Extraction of a set of contiguous bits, also known as a slice, denoted by `[H:L]`, where `H` and `L` must be expressions that evaluate to non-negative, local compile-time known values, and `H >= L`. The types of `H` and `L` (which do not need to be identical) must be numeric (`[sec-numeric-values]`). The result is a bit-string of width `H - L + 1`, including the bits numbered from `L` (which becomes the least significant bit of the result) to `H` (the most significant bit of the result) from the source operand. The conditions `0 <= L <= H < W` are checked statically (where `W` is the length of the source bit-string). Note that both endpoints of the extraction are inclusive. The bounds are required to be local compile-time known values so that the width of the result can be computed at compile time. Slices are also l-values, which means that P4 supports assigning to a slice: `e[H:L] = x`. The effect of this statement is to set bits `H` through `L` (inclusive of both) of `e` to the bit-pattern represented by `x`, and leaves all other bits of `e` unchanged. A slice of an unsigned integer is an unsigned integer.
- Concatenation of bit-strings and/or fixed-width signed integers, denoted by `++`. The two operands must be either `bit<W>` or `int<W>`, and they can be of different signedness and width. The result has the same signedness as the left operand and the width equal to the sum of the two operands' width. In concatenation, the left operand is placed as the most significant bits.

Additionally, the size of a bit-string can be determined at compile-time (`[sec-minsizeinbits]`).

#### 8.2.7.5.2. Type checking

Typing `baseType`, under cursor `p` and context `TC`:

1. If `baseType` is `BIT`:
  - a. Result in `BIT < 1 >` and a set of fresh type variables `·`.
2. Else if let `BIT < int >` be `baseType`:
  - a. Check that `int` has type `nat`.
  - b. Let `n` be `int`.
  - c. Result in `BIT < n >` and a set of fresh type variables `·`.
3. Else if let `BIT < ( expression ) >` be `baseType`:
  - a. Let `typedExpressionIR` be
    - the result of typing `expression`, under cursor `p` and context `TC`.
  - b. Check that the compile-time known-ness of `typedExpressionIR` is `LCTK`.
  - c. Let `value` be

- the result of local compile-time evaluation of `typedExpressionIR`, under cursor `p` and context `TC`.
- d. Check that `value` has type `integerValue`.
  - e. Let `integerValue` be `value`.
  - f. Let `n` be ! the natural number representation of `integerValue`.
  - g. Result in `BIT < n >` and a set of fresh type variables `.`.

#### 8.2.7.6. Fixed-width signed integers

Signed integers are represented using two's complement. An integer with `W` bits is declared as: `int<W>`. `W` must be an expression that evaluates to a local compile-time known (see Section 7.5) value that is a non-negative integer. Note that `int<W>` type refers to both cases of `int<W>` and `int<(expression)>` where the width is a local compile-time known value.

Bits within an integer are numbered from 0 to `W-1`. Bit 0 is the least significant, and bit `W-1` is the sign bit.

For example, the type `int<64>` describes the type of integers represented using exactly 64 bits with bits numbered from 0 to 63, where bit 63 is the most significant (sign) bit.

P4 architectures may impose additional constraints on signed types: for example, they may limit the maximum size, or they may only support some arithmetic operations on certain sizes (e.g., 16-, 32-, and 64-bit values).

A signed integer with width 1 can only have two legal values: 0 and -1.

##### 8.2.7.6.1. Operations

This section discusses all operations that can be performed on expressions of type `int<W>` for some `W`. Recall that the `int<W>` denotes signed `W`-bit integers, represented using two's complement.

In general, P4 arithmetic operations do not detect "underflow" or "overflow": operations simply "wrap around", similar to C operations on unsigned values. Hence, attempting to represent large values using `W` bits will only keep the least-significant `W` bits of the value.

P4 supports saturating arithmetic (addition and subtraction) for signed integers. Targets may optionally reject programs using saturating arithmetic. For a signed integer with bit-width of `W`, the minimum value is  $-2^{(W-1)}$  and the maximum value is  $2^{(W-1)}-1$ .

P4 also does not support arithmetic exceptions. The runtime result of an arithmetic operation is defined for all combinations of input arguments.

All binary operations except shifts and concatenation require both operands to have the same exact type (signedness) and width and supplying operands with different widths or signedness produces a compile-time error. No implicit casts are inserted by the compiler to equalize the types. Except for shifts and concatenation, P4 does not have any binary operations that operate simultaneously on signed and unsigned values.

Note that bitwise operations on signed integers are well-defined, since the representation is mandated to be two's complement.

The `int<W>` datatype supports the following operations; all binary operations require both operands to have the exact same type. The result always has the same width as the left operand.

- Negation, denoted by unary `-`.

- Unary plus, denoted by `+`. This operation behaves like a no-op.
- Addition, denoted by `+`.
- Subtraction, denoted by `-`.
- Comparison for equality and inequality, denoted `==` and `!=` respectively. These operations produce a Boolean result.
- Numeric comparisons, denoted by `<`, `<=`, `>`, and `>=`. These operations produce a Boolean result.
- Multiplication, denoted by `*`. Result has the same width as the operands. P4 architectures may impose additional restrictions—e.g., they may only allow multiplication by a power of two.
- Bitwise "and" between two bit-strings of the same width, denoted by `&`.
- Bitwise "or" between two bit-strings of the same width, denoted by `|`.
- Bitwise "complement" of a single bit-string, denoted by `~`.
- Bitwise "xor" of two bit-strings of the same width, denoted by `^`.
- Saturating addition, denoted by `|+|`.
- Saturating subtraction, denoted by `|-|`.

The `int<W>` datatype also support the following operations:

- Arithmetic shift left and right denoted by `<<` and `>>`. The left operand is signed and the right operand must be either an unsigned number of type `bit<S>` or a compile-time known value that is a non-negative integer. The result has the same type as the left operand. Shifting left produces the exact same bit pattern as a shift left of an unsigned value. Shift left can thus overflow, when it leads to a change of the sign bit. Shifting by an amount greater than the width of the input produces a "correct" result:
  - all result bits are zero when shifting left
  - all result bits are zero when shifting a non-negative value right
  - all result bits are one when shifting a negative value right
- Extraction of a set of contiguous bits, also known as a slice, denoted by `[H:L]`, where `H` and `L` must be expressions that evaluate to non-negative, local compile-time known values, and `H >= L` must be true. The types of `H` and `L` (which do not need to be identical) must be numeric ([\[sec-numeric-values\]](#)). The result is an unsigned bit-string of width `H - L + 1`, including the bits numbered from `L` (which becomes the least significant bit of the result) to `H` (the most significant bit of the result) from the source operand. The conditions `0 <= L <= H < W` are checked statically (where `W` is the length of the source bit-string). Note that both endpoints of the extraction are inclusive. The bounds are required to be values that are known at compile time so that the width of the result can be computed at compile time. Slices are also l-values, which means that P4 supports assigning to a slice: `e[H:L] = x`. The effect of this statement is to set bits `H` through `L` of `e` to the bit-pattern represented by `x`, and leaves all other bits of `e` unchanged. A slice of a signed integer is treated as an unsigned integer.
- Concatenation of bit-strings and/or fixed-width signed integers, denoted by `++`. The two operands must be either `bit<W>` or `int<W>`, and they can be of different signedness and width. The result has the same signedness as the left operand and the width equal to the sum of the two operands' width. In concatenation, the left operand is placed as the most significant bits.

Additionally, the size of a fixed-width signed integer can be determined at compile-time ([\[sec-minsizeinbits\]](#)).

#### 8.2.7.6.2. Type checking

Typing `baseType`, under cursor `p` and context `TC`:



1. If let  $\text{INT} < \text{int} >$  be  $\text{baseType}$ :
  - a. Check that  $\text{int}$  has type  $\text{nat}$ .
  - b. Let  $n$  be  $\text{int}$ .
  - c. Result in  $\text{INT} < n >$  and a set of fresh type variables  $\cdot$ .
2. Else if let  $\text{INT} < (\text{expression}) >$  be  $\text{baseType}$ :
  - a. Let  $\text{typedExpressionIR}$  be
    - the result of **typing**  $\text{expression}$ , under cursor  $p$  and context  $\text{TC}$ .
  - b. Check that **the compile-time known-ness of**  $\text{typedExpressionIR}$  is  $\text{LCTK}$ .
  - c. Let  $\text{value}$  be
    - the result of **local compile-time evaluation of**  $\text{typedExpressionIR}$ , under cursor  $p$  and context  $\text{TC}$ .
  - d. Check that  $\text{value}$  has type  $\text{integerValue}$ .
  - e. Let  $\text{integerValue}$  be  $\text{value}$ .
  - f. Let  $n$  be **! the natural number representation of**  $\text{integerValue}$ .
  - g. Result in  $\text{INT} < n >$  and a set of fresh type variables  $\cdot$ .

### 8.2.7.7. Dynamically-sized bit-strings

Some network protocols use fields whose size is only known at runtime (e.g., IPv4 options). To support restricted manipulations of such values, P4 provides a special bit-string type whose size is set at runtime, called a **varbit**.

The type  $\text{varbit} < W >$  denotes a bit-string with a width of at most  $W$  bits, where  $W$  is a local compile-time known value (see Section 7.5) that is a non-negative integer. For example, the type  $\text{varbit} < 120 >$  denotes the type of bit-string values that may have between 0 and 120 bits. Most operations that are applicable to fixed-size bit-strings (unsigned numbers) **cannot** be performed on dynamically sized bit-strings. Note that  $\text{varbit} < W >$  type refers to both cases of  $\text{varbit} < W >$  and  $\text{varbit} < (\text{expression}) >$  where the width is a local compile-time known value.

P4 architectures may impose additional constraints on varbit types: for example, they may limit the maximum size, or they may require **varbit** values to always contain an integer number of bytes at runtime.

#### 8.2.7.7.1. Operations

To support parsing headers with variable-length fields, P4 offers a type **varbit**. Each occurrence of the type **varbit** has a statically-declared maximum width, as well as a dynamic width, which must not exceed the static bound. Prior to initialization a variable-size bit-string has an unknown dynamic width.

Variable-length bit-strings support a limited set of operations:

- Assignment to another variable-sized bit-string. The target of the assignment must have the same static width as the source. When executed, the assignment sets the dynamic width of the target to the dynamic width of the source.
- Comparison for equality or inequality with another **varbit** field. Two **varbit** fields can be compared only if they have the same type. Two varbits are equal if they have the same dynamic width and all the bits up to the dynamic width are the same.

The following operations are *not* supported directly on a value of type **varbit**, but instead on any type for which **extract** and **emit** operations are supported (e.g. a value with type header) that may contain a field of



type `varbit`. They are mentioned here only to ease finding this information in a section dedicated to type `varbit`.

- Parser extraction into a header containing a variable-sized bit-string using the two-argument `extract` method of a `packet_in` extern object (see [\[sec-packet-extract-two\]](#)). This operation sets the dynamic width of the field.
- The `emit` method of a `packet_out` extern object can be performed on a header and a few other types (see [\[sec-deparse\]](#)) that contain a field with type `varbit`. Such an `emit` method call inserts a variable-sized bit-string with a known dynamic width into the packet being constructed.

Additionally, the maximum size of a variable-length bit-string can be determined at compile-time ([\[sec-minsizeinbits\]](#)).

#### 8.2.7.7.2. Type checking

Typing `baseType`, under cursor `p` and context `TC`:

1. If let `VARBIT < int >` be `baseType`:
  - a. Check that `int` has type `nat`.
  - b. Let `n` be `int`.
  - c. Result in `VARBIT < n >` and a set of fresh type variables `.`
2. Else if let `VARBIT < ( expression ) >` be `baseType`:
  - a. Let `typedExpressionIR` be
    - the result of typing `expression`, under cursor `p` and context `TC`.
  - b. Check that the compile-time known-ness of `typedExpressionIR` is `LCTK`.
  - c. Let `value` be
    - the result of local compile-time evaluation of `typedExpressionIR`, under cursor `p` and context `TC`.
  - d. Check that `value` has type `integerValue`.
  - e. Let `integerValue` be `value`.
  - f. Let `n` be ! the natural number representation of `integerValue`.
  - g. Result in `VARBIT < n >` and a set of fresh type variables `.`

## 8.3. Named types

```
prefixedTypeName
: typeName
| `TID . typeName
;

specializedType
: prefixedTypeName `< typeArgumentList >
;

namedType
: prefixedTypeName
| specializedType
;
```

Named types are types that reference another type by name. User-defined types can be introduced with their names. For example, the following declares a new struct type `S`:

```
struct S {
    bit<32> x;
    bit<32> y;
}
```

This type can then be referenced by its name, as can be seen in the parameter type of the following example:

```
void f(S s) {}
```

Here, `S` is a named type (`typeName`) that refers to the struct type defined earlier.

Types such as struct, header, and header union types can be generic. In order to use such a generic type it must be specialized with appropriate type arguments. For example,

```
// generic structure type
struct S<T> {
    T field;
    bool valid;
}

struct G<T> {
    S<T> s;
}

// specialize S by replacing 'T' with 'bit<32>'
const S<bit<32>> s = { field = 32w0, valid = false };
// Specialize G by replacing 'T' with 'bit<32>'
const G<bit<32>> g = { s = { field = 0, valid = false } };

// generic header type
header H<T> {
    T field;
}

// Specialize H by replacing 'T' with 'bit<8>'
const H<bit<8>> h = { field = 1 };
// Header stack produced from a specialization of a generic header type
H<bit<8>>[10] stack;

// Generic header union
header_union HU<T> {
    H<bit<32>> h32;
    H<bit<8>> h8;
    H<T> ht;
}

// Header union with a type obtained by specializing a generic header union type
HU<bit> hu;
```

To handle named types used as return types, the following production is also used:

```
identifier
: `ID text
;

typeOrVoid
: type
```

```
| VOID
| identifier
;
```

### 8.3.1. Type definitions (type constructors)

```
typeDeclaration
: derivedTypeDeclaration
| typedefDeclaration
| parserTypeDeclaration
| controlTypeDeclaration
| packageTypeDeclaration
;
```

`typeDeclaration` introduces a user-defined type definition. These can be referenced by name. Generic type definitions can be specialized with type arguments to produce a type instance.

The internal representation of type definitions is as follows:

```
nameTypeDefIR = nameTypeIR

aliasTypeDefIR = aliasTypeIR

dataTypeDefIR
: structTypeDefIR
| headerTypeDefIR
| headerUnionTypeDefIR
| enumTypeDefIR
;

objectTypeDefIR
: externObjectTypeDefIR
| parserObjectTypeDefIR
| controlObjectTypeDefIR
| packageObjectTypeDefIR
| tableObjectTypeDefIR
;

typeDefIR
: nameTypeDefIR
| aliasTypeDefIR
| dataTypeDefIR
| objectTypeDefIR
;
```

For example, `structTypeDeclaration` introduces a struct type definition, `structTypeDefIR`:

```
structTypeDefIR
: STRUCT typeId `< typeParameterIR* > `{ fieldTypeIR* }
;

structTypeDeclaration
: annotationList STRUCT name typeParameterListOpt `{ typeFieldList }
;
```

Some type definitions like struct and header type definitions can be polymorphic, meaning they can have type variables as parameters. On the other hand, type definitions such as enum and type alias definitions can only be monomorphic. Below table summarizes which kinds of type definitions can be polymorphic:

### 8.3.2. Type resolution

Notice that P4 has struct types, but the surface syntax does not have an explicit construct for struct types. Instead, struct types are always referenced by name. To easily handle named types in  $P4_{IR}$ , the internal representation of types contain representations for the referred types.

```
structTypeIR
: STRUCT typeId `< typeArgumentIR* > `{ fieldTypeIR* }
;
```

For example, a struct type is represented as `structTypeIR` in  $P4_{IR}$ . Thus, after type checking, a named type in  $P4_{16}$  is resolved to its referred type in  $P4_{IR}$ . For named types referring to monomorphic type definitions, the resolved type is simply the type defined by the type definition.

```
enum E_t { A, B, C; }
void f(E_t e) {}
```

In the above example, the named type `E_t` is resolved to the enum type `enumTypeIR`.

```
struct S<T> { T t; }
void f(S<bit<32>> s) {}
```

In the above example, the named type `S<bit<32>>` is resolved to a `structTypeIR`, where it specializes a `structTypeDefIR` with the type argument `bit<32>`. Type specialization is discussed in detail in the next section.

### 8.3.3. Type specialization

`typeDefIRbase` specialized by `typeArgumentIR*`

1. Let  $(typeParameterIR_{expl}^*, typeParameterIR_{impl}^*)$  be the type parameters of `typeDefIRbase`.
2. Let `typeParameterIR*` be `typeParameterIRexpl*` concatenated with `typeParameterIRimpl*`.
3. Check that the length of `typeParameterIR*` is equal to the length of `typeArgumentIR*`.
4. Let `theta` be  $\{ (typeParameterIR : typeArgumentIR) \}$ .
5. Let `typeIRbase` be the underlying type of `typeDefIRbase`.
6. Let `typeIRspec` be `typeIRbase` substituted by `theta`.
7. Return `typeIRspec`.

### 8.3.4. Type names

```
prefixedTypeName
: typeName
| `TID . typeName
;

identifier
: `ID text
;
```

A `prefixedTypeName` and `identifier` may refer to either a monomorphic type definition or a polymorphic type

definition without type arguments. The names can be prefixed by a dot (.) to refer to the top-level namespace.

On type checking, the referenced type definition is looked up by name. If the referenced type definition is monomorphic, then the resolved type is simply the type defined by the type definition. If the referenced type definition is polymorphic (but without type arguments), then the resolved type is a specialized type with no type arguments.

In some cases, the reference may be a type parameter. In other words, the type is indeed a variable type, not a concrete type until it is bound to a type argument. These are internally represented as:

```
nameTypeDefIR = nameTypeIR
```

#### 8.3.4.1. Operations

Because functions and methods can be generic, they offer the possibility of declaring values with types that are type variables:

```
void f<T>() {  
  T x; // the type of x is T, a type variable  
}
```

The type of such objects is not known until the function is specialized with specific type arguments.

Currently the only operations that are available for such values are assignment (explicit through =, or implicit, through argument passing). This behavior is similar to languages such as Java, and different from languages such as C++.

A future version of P4 may introduce a notion of *type constraints* which would enable more operations on such values. Because of this limitation, such values are currently of limited utility.

#### 8.3.4.2. Type checking

Typing `typeOrVoid`, under cursor `p` and context `TC`:

1. If let `ID typeId` be `typeOrVoid`:
  - a. Let `typeIR` and a set of fresh type variables `typeIdfresh*` be
    - the result of typing `TID typeId`, under cursor `p` and context `TC`.
  - b. Result in `typeIR` and a set of fresh type variables `typeIdfresh*`.
2. Else if let `prefixedTypeName` be `typeOrVoid`:
  - a. Let `prefixedNameIR` be the prefixed name of `prefixedTypeName`.
  - b. Let `typeDefIR'` be ! the type definition of `prefixedNameIR` from the `p` layer of `TC`.
  - c. If `typeDefIR'` is monomorphic:
    - i. Let `typeIR` be the underlying type of `typeDefIR'`.
    - ii. Result in `typeIR` and a set of fresh type variables `.`.
  - d. Else:
    - i. Let `typeIR` be `typeDefIR'` specialized by `.`.
    - ii. Result in `typeIR` and a set of fresh type variables `.`.

### 8.3.5. Specialized types

A generic type may be specialized by specifying arguments for its type variables. In cases where the compiler can infer type arguments, type specialization is not necessary. When a type is specialized, all its type variables must be bound.

```
specializedType
: prefixedTypeName `< typeArgumentList >
;
```

For example, the following extern declaration describes a generic block of registers, where the type of the elements stored in each register is an arbitrary `T`.

```
extern Register<T> {
  Register(bit<32> size);
  T read(bit<32> index);
  void write(bit<32> index, T value);
}
```

The type `T` has to be specified when instantiating a set of registers, by specializing the `Register` type:

```
Register<bit<32>>(128) registerBank;
```

The instantiation of `registerBank` is made using the `Register` type specialized with the `bit<32>` bound to the `T` type argument.

#### 8.3.5.1. Type checking

**Typing** `prefixedTypeName < typeArgumentList >`, under cursor `p` and context `TC`:

1. Let `prefixedNameIR` be the prefixed name of `prefixedTypeName`.
2. Let `typeDefIR'` be ! the type definition of `prefixedNameIR` from the `p` layer of `TC`.
3. Check that `typeDefIR'` is polymorphic.
4. Let `typeIRarg*` and a set of fresh type variables `typeIDfresh*` be
  - the result of **typing** `typeArgumentList`, under cursor `p` and context `TC`.
5. Let `typeIR` be `typeDefIR'` specialized by `typeIRarg*`.
6. Result in `typeIR` and a set of fresh type variables `typeIDfresh*`.

## 8.4. Data types and values

```
dataTypeIR
: listTypeIR
| tupleTypeIR
| headerStackTypeIR
| structTypeIR
| headerTypeIR
| headerUnionTypeIR
| enumTypeIR
;
```

```

dataValue
: listValue
| tupleValue
| headerStackValue
| structValue
| headerValue
| headerUnionValue
| enumValue
;

```

Data types represent the types that aggregate other types, including lists, tuples, header stacks, structs, headers, header unions, and enums.

### 8.4.1. Lists

A list holds zero or more values, where every element must have the same type. The type of a list where all elements have type  $T$  is written as

```
list<T>
```

```

listType
: LIST `< typeArgument >
;

```

Internally, list types and values are represented as follows:

```

listTypeIR
: LIST `< typeIR >
;

listValue
: LIST `[ value* ]
;

```

#### 8.4.1.1. Operations

The value of a list is written using curly braces, with each element separated by a comma. The left curly brace is preceded by a `(list<T>)` where  $T$  is the list element type. Such a value can be passed as an argument, e.g. to extern constructor functions.

```

struct pair_t {
    bit<16> a;
    bit<32> b;
}

extern E {
    E(list<pair_t> data);
    void run();
}

control c() {
    E((list<pair_t>) {{2, 3}, {4, 5}}) e;
    apply {
        e.run();
    }
}

```

Additionally, the size of a list can be determined at compile-time ([[sec-minsizeinbits](#)]).

#### 8.4.1.2. Type checking

Typing  $LIST < typeArgument >$ , under cursor  $p$  and context  $TC$ :

1. Let  $typeIR_{arg}$  and a set of fresh type variables  $typeId_{fresh}^*$  be
  - the result of typing  $typeArgument$ , under cursor  $p$  and context  $TC$ .
2. Result in  $LIST < typeIR_{arg} >$  and a set of fresh type variables  $typeId_{fresh}^*$ .

#### 8.4.1.3. Well-formedness

$LIST < typeIR' >$  is a well-formed type, with bound type variables  $B$  when:

1. Check that  $typeIR'$  can be nested in a list type.
2. Check that  $typeIR'$  is a well-formed type, with bound type variables  $B$ .
3. The relation holds.

### 8.4.2. Tuples

A tuple is similar to a *struct*, in that it holds multiple values. The type of tuples with  $n$  component types  $T_1, \dots, T_n$  is written as

```
tuple<T1, /* more fields omitted */, Tn>
```

The type  $tuple<>$  is a tuple type with no components.

```
tupleType
: TUPLE `< typeArgumentList >
;
```

Internally, tuple types and values are represented as follows:

```
tupleTypeIR
: TUPLE `< typeIR* >
;

tupleValue
: TUPLE `( value* )
;
```

#### 8.4.2.1. Operations

The fields of a tuple can be accessed using array index syntax  $x[0]$ ,  $x[1]$ . The indexes **must** be local compile-time known values, to enable the type-checker to identify the field types statically.

Tuples can be compared for equality using  $==$  and  $!=$ ; two tuples are equal if and only if all their fields are respectively equal.



Currently tuple fields are not left-values, even if the tuple itself is. (i.e., a tuple can only be assigned monolithically, and the field values cannot be changed individually.) This restriction may be lifted in a future version of the language.

#### 8.4.2.2. Type checking

**Typing**  $TUPLE < typeArgumentList >$ , under cursor  $p$  and context  $TC$ :

1. Let  $typeIR_{arg}^*$  and a set of fresh type variables  $typeID_{fresh}^*$  be
  - the result of **typing**  $typeArgumentList$ , under cursor  $p$  and context  $TC$ .
2. Result in  $TUPLE < typeIR_{arg}^* >$  and a set of fresh type variables  $typeID_{fresh}^*$ .

#### 8.4.2.3. Well-formedness

$TUPLE < typeIR^* >$  is a well-formed type, with bound type variables  $B$  when:

1. Check that  $typeIR'$  can be nested in a tuple type, for all  $typeIR'$  in  $typeIR^*$ .
2. Check that  $typeIR'$  is a well-formed type, with bound type variables  $B$ , for all  $typeIR'$  in  $typeIR^*$ .
3. The relation holds.

#### 8.4.3. Header stacks

A header stack represents an array of headers or header unions. A header stack type is defined as:

```
headerStackType
  : namedType `[ expression ]
  ;
```

where `namedType` refers to a header or header union type. For a header stack `hs[n]`, the term `n` is the maximum defined size, and must be a local compile-time known value that is a positive integer. Nested header stacks are not supported.

Internally, header stack types and values are represented as follows:

```
headerStackTypeIR
  : typeIR `[ nat ]
  ;

headerStackValue
  : HEADER_STACK `[ value* `( nat ; nat ) ]
  ;
```

At runtime a stack contains `n` values with type `namedType`, only some of which may be valid. The valid elements of a header stack need not be contiguous.

For example, the following declarations,

```
header Mpls_h {
  bit<20> label;
  bit<3> tc;
```

```

    bit    bos;
    bit<8> ttl;
}
Mpls_h[10] mpls;

```

introduce a header stack called `mpls` containing ten entries, each of type `Mpls_h`.

### 8.4.3.1. Operations

P4 provides a set of computations for manipulating header stacks. A header stack `hs` of type `h[n]` can be understood in terms of the following pseudocode:

```

// type declaration
struct hs_t {
    bit<32> nextIndex;
    bit<32> size;
    h[n] data; // Ordinary array
}

// instance declaration and initialization
hs_t hs;
hs.nextIndex = 0;
hs.size = n;

```

Intuitively, a header stack can be thought of as a struct containing an ordinary array of headers `hs` and a counter `nextIndex` that can be used to simplify the construction of parsers for header stacks, as discussed below. The `nextIndex` counter is initialized to 0.

Given a header stack value `hs` of size `n`, the following expressions are legal:

- `hs[index]`: produces a reference to the header at the specified position within the stack; if `hs` is an l-value, the result is also an l-value. The header may be invalid. Some implementations may impose the constraint that the index expression must be a compile-time known value. A P4 compiler must give an error if an index that is a compile-time known value is out of range.

Accessing a header stack `hs` with an index less than 0 or greater than or equal to `hs.size` results in an undefined value. See [\[sec-uninitialized-values-and-writing-invalid-headers\]](#) for more details.

The `index` is an expression that must be of numeric types ([\[sec-numeric-values\]](#)).

- `hs.size`: produces a 32-bit unsigned integer that returns the size of the header stack (a local compile-time known value).
- assignment from a header stack `hs` into another stack requires the stacks to have the same types and sizes. All components of `hs` are copied, including its elements and their validity bits, as well as `nextIndex`.

To help programmers write parsers for header stacks, P4 also offers computations that automatically advance through the stack as elements are parsed:

- `hs.next`: produces a reference to the element with index `hs.nextIndex` in the stack. May only be used in a `parser`. If the stack's `nextIndex` counter is greater than or equal to `size`, then evaluating this expression results in a transition to `reject` and sets the error to `error.StackOutOfBounds`. If `hs` is an l-value, then `hs.next` is also an l-value.
- `hs.last`: produces a reference to the element with index `hs.nextIndex - 1` in the stack, if such an element exists. May only be used in a `parser`. If the `nextIndex` counter is less than 1, or greater than `size`, then evaluating this expression results in a transition to `reject` and sets the error to `error.StackOutOfBounds`. Unlike `hs.next`, the resulting reference is never an l-value.

- `hs.lastIndex`: produces a 32-bit unsigned integer that encodes the index `hs.nextIndex - 1`. May only be used in a `parser`. If the `nextIndex` counter is 0, then evaluating this expression produces an undefined value.

Finally, P4 offers the following computations that can be used to manipulate the elements at the front and back of the stack:

- `hs.push_front(int count)`: shifts `hs` "right" by `count`. The first `count` elements become invalid. The last `count` elements in the stack are discarded. The `hs.nextIndex` counter is incremented by `count`. The `count` argument must be a compile-time known value that is a positive integer. The return type is `void`.
- `hs.pop_front(int count)`: shifts `hs` "left" by `count` (i.e., element with index `count` is copied in stack at index 0). The last `count` elements become invalid. The `hs.nextIndex` counter is decremented by `count`. The `count` argument must be a compile-time known value that is a positive integer. The return type is `void`.

The following pseudocode defines the behavior of `push_front` and `pop_front`:

```
void push_front(int count) {
    for (int i = this.size-1; i >= 0; i -= 1) {
        if (i >= count) {
            this[i] = this[i-count];
        } else {
            this[i].setInvalid();
        }
    }
    this.nextIndex = this.nextIndex + count;
    if (this.nextIndex > this.size) this.nextIndex = this.size;
    // Note: this.last, this.next, and this.lastIndex adjust with this.nextIndex
}

void pop_front(int count) {
    for (int i = 0; i < this.size; i++) {
        if (i+count < this.size) {
            this[i] = this[i+count];
        } else {
            this[i].setInvalid();
        }
    }
    if (this.nextIndex >= count) {
        this.nextIndex = this.nextIndex - count;
    } else {
        this.nextIndex = 0;
    }
    // Note: this.last, this.next, and this.lastIndex adjust with this.nextIndex
}
```

Similar to structs and headers, the size of a header stack is a compile-time known value (Section [\[section: minsizeinbits\]](#)).

Two header stacks can be compared for equality (`==`) or inequality (`!=`) only if they have the same element type and the same length. Two stacks are equal if and only if all their corresponding elements are equal. Note that the `nextIndex` value is not used in the equality comparison.

#### 8.4.3.2. Type checking

**Typing** `namedType [ expressionsize ], under cursor p and context TC`:

1. Let `typeIRbase` and a set of fresh type variables `typeIdfresh*` be
  - the result of **typing** `namedType`, **under cursor p and context TC**.
2. Let `typedExpressionIRsize` be

- the result of **typing**  $\text{expression}_{\text{size}}$ , under cursor  $p$  and context  $TC$ .
3. Check that **the compile-time known-ness** of  $\text{typedExpressionIR}_{\text{size}}$  is LCTK.
  4. Let  $\text{value}$  be
    - the result of **local compile-time evaluation** of  $\text{typedExpressionIR}_{\text{size}}$ , under cursor  $p$  and context  $TC$ .
  5. Check that  $\text{value}$  has type  $\text{integerValue}$ .
  6. Let  $\text{integerValue}_{\text{size}}$  be  $\text{value}$ .
  7. Let  $n_{\text{size}}$  be **! the natural number representation of**  $\text{integerValue}_{\text{size}}$ .
  8. Check that  $n_{\text{size}}$  is greater than 0.
  9. Result in  $\text{typeIR}_{\text{base}} [ n_{\text{size}} ]$  and a set of fresh type variables  $\text{typeId}_{\text{fresh}}^*$ .

#### 8.4.3.3. Well-formedness

$\text{typeIR}' [ \text{nat} ]$  is a well-formed type, with bound type variables  $B$  when:

1. Check that  $\text{typeIR}'$  can be nested in a header stack type.
2. Check that  $\text{typeIR}'$  is a well-formed type, with bound type variables  $B$ .
3. The relation holds.

#### 8.4.4. Arrays

#### 8.4.5. Structs

P4 **struct** types are defined with the following syntax:

```
typeField
: annotationList type name ;
;

structTypeDeclaration
: annotationList STRUCT name typeParameterListOpt `{ typeFieldList }
;
;
```

This declaration introduces a new struct type definition with the specified name in the current scope. Field names have to be distinct. An empty struct (with no fields) is legal.

```
structTypeDefIR
: STRUCT typeId `< typeParameterIR* > `{ fieldTypeIR* }
;
;
```

For example, the structure **Parsed\_headers** below contains the headers recognized by a simple parser:

```
header Tcp_h { /* fields omitted */ }
header Udp_h { /* fields omitted */ }
struct Parsed_headers {
    Ethernet_h ethernet;
    Ip_h       ip;
    Tcp_h      tcp;
}
```

```

    Udp_h      udp;
}

```

Struct types can be used by referring to their names. Generic struct types can be used by specializing their type parameters with type arguments. Internally, struct types and values are represented as follows:

```

fieldTypeIR
: annotationList typeIR nameIR ;
;

structTypeIR
: STRUCT typeId `< typeArgumentIR* > `{ fieldTypeIR* }
;

fieldValue
: value nameIR ;
;

structValue
: STRUCT typeId `{ fieldValue* }
;

```

### 8.4.5.1. Operations

The only operation defined on expressions whose type is a **struct** is field access, written using dot (".") notation—e.g., `s.field`. If `s` is an l-value, then `s.field` is also an l-value. P4 also allows copying **structs** using assignment when the source and target of the assignment have the same type. Finally, **structs** can be initialized with a sequence expression, as discussed in [Section 8.6.3](#), or with a record expression, as described in [Section 8.6.4](#). Both of these cases must initialize all fields of the structure. The size of a struct can be determined at compile-time ([\[sec-minsizeinbits\]](#)).

Two structs can be compared for equality (==) or inequality (!=) only if they have the same type and all of their fields can be recursively compared for equality. Two structures are equal if and only if all their corresponding fields are equal.

The following example shows a structure initialized in several different ways:

```

struct S {
    bit<32> a;
    bit<32> b;
}
const S x = { 10, 20 };           // sequence expression
const S x = { a = 10, b = 20 };   // record expression
const S x = (S) { a = 10, b = 20 }; // record expression

```

See [\[sec-uninitialized-values-and-writing-invalid-headers\]](#) for a description of the behavior if **struct** fields are read without being initialized.

### 8.4.5.2. Type checking

Struct types are introduced by **struct** declarations. Its typing rule is explained in [Section 11.14](#). Struct types are then used by referencing their names. Thus struct types can be obtained from named types, as illustrated in [Section 8.3](#).

### 8.4.5.3. Well-formedness

`STRUCT typeId < typeArgumentIR* > { ( annotationList typeIRfield nameIRfield ; )* }` is a well-formed type, with bound

type variables  $B$  when:

1. Check that the elements of  $\text{nameIR}_{\text{field}}^*$  are distinct.
2. Check that  $\text{typeIR}_{\text{field}}$  can be nested in a struct type, for all  $\text{typeIR}_{\text{field}}$  in  $\text{typeIR}_{\text{field}}^*$ .
3. Check that  $\text{typeIR}_{\text{field}}$  is a well-formed type, with bound type variables  $B$ , for all  $\text{typeIR}_{\text{field}}$  in  $\text{typeIR}_{\text{field}}^*$ .
4. The relation holds.

### 8.4.6. Headers

The declaration of a header type is given by the following syntax:

```
typeField
: annotationList type name ;
;

headerTypeDeclaration
: annotationList HEADER name typeParameterListOpt `{ typeFieldList }
;
```

where each `type` is restricted to a bit-string type (fixed or variable), a fixed-width signed integer type, a boolean type, or a struct that itself contains other struct fields, nested arbitrarily, as long as all of the "leaf" types are `bit<W>`, `int<W>`, a serializable `enum`, or a `bool`. If a `bool` is used inside a P4 header, all implementations encode the `bool` as a one bit long field, with the value 1 representing `true` and 0 representing `false`. Field names have to be distinct.

A header declaration introduces a new identifier in the current scope; the type definition can be referred to using this identifier.

```
headerTypeDefIR
: HEADER typeId `typeParameterIR* > `{ fieldTypeIR* }
;
```

A header is similar to a `struct` in C, containing all the specified fields. However, in addition, a header also contains a hidden Boolean "validity" field. When the "validity" bit is `true` we say that the "header is valid". When a local variable with a header type is declared, its "validity" bit is automatically set to `false`. The "validity" bit can be manipulated by using the header methods `isValid()`, `setValid()`, and `setInvalid()`.

Header types may be empty:

```
header Empty_h { }
```

Note that an empty header still contains a validity bit.

When a struct is inside of a header, the order of the fields for the purposes of `extract` and `emit` calls is the order of the fields as defined in the source code. An example of a header including a struct is included below.

```
struct ipv6_addr {
    bit<32> Addr0;
    bit<32> Addr1;
    bit<32> Addr2;
    bit<32> Addr3;
}
```

```
header ipv6_t {
    bit<4>    version;
    bit<8>    trafficClass;
    bit<20>   flowLabel;
    bit<16>   payloadLen;
    bit<8>    nextHdr;
    bit<8>    hopLimit;
    ipv6_addr src;
    ipv6_addr dst;
}
```

Headers that do not contain any `varbit` field are *fixed size*. Headers containing `varbit` fields have *variable size*. The size (in bits) of a fixed-size header is simply the sum of the sizes of all component fields (without counting the validity bit). There is no padding or alignment of the header fields. Targets may impose additional constraints on header types—e.g., restricting headers to sizes that are an integer number of bytes.

For example, the following declaration describes a typical Ethernet header:

```
header Ethernet_h {
    bit<48> dstAddr;
    bit<48> srcAddr;
    bit<16> etherType;
}
```

The following variable declaration uses the newly introduced type `Ethernet_h`:

```
Ethernet_h ethernetHeader;
```

P4's parser language provides an `extract` method that can be used to "fill in" the fields of a header from a network packet, as described in [\[sec-packet-data-extraction\]](#). The successful execution of an `extract` operation also sets the validity bit of the extracted header to `true`.

Here is an example of an IPv4 header with variable-sized options:

```
header IPv4_h {
    bit<4>    version;
    bit<4>    ihl;
    bit<8>    diffserv;
    bit<16>   totalLen;
    bit<16>   identification;
    bit<3>    flags;
    bit<13>   fragOffset;
    bit<8>    ttl;
    bit<8>    protocol;
    bit<16>   hdrChecksum;
    bit<32>   srcAddr;
    bit<32>   dstAddr;
    varbit<320> options;
}
```

As demonstrated by a code example in [\[sec-packet-extract-two\]](#), another way to support headers that contain variable-length fields is to define two headers—one fixed length, one containing a `varbit` field—and extract each part in separate parsing steps.

Notice that the names `isValid`, `setValid`, `minSizeInBits`, etc. are all valid header field names.

Internally, header types and values are represented as follows:

```

headerTypeIR
  : HEADER typeId `< typeArgumentIR* > `{ fieldTypeIR* }
  ;

headerValue
  : HEADER typeId `{ bool ; fieldValue* }
  ;

```

#### 8.4.6.1. Operations

Headers provide the same operations as `structs`. Assignment between headers also copies the "validity" header bit.

In addition, headers support the following methods:

- The method `isValid()` returns the value of the "validity" bit of the header.
- The method `setValid()` sets the header's validity bit to "true". It can only be applied to an l-value.
- The method `setInvalid()` sets the header's validity bit to "false". It can only be applied to an l-value.

Similar to a `struct`, a header object can be initialized with a sequence expression (see [Section 8.6.3](#))—the sequence elements are assigned to the header fields in the order they appear—or with a record expression (see [Section 8.6.4](#)). When initialized the header automatically becomes valid:

```

header H { bit<32> x; bit<32> y; }
H h;
h = { 10, 12 }; // This also makes the header h valid
h = { y = 12, x = 10 }; // Same effect as above

```

Two headers can be compared for equality (`==`) or inequality (`!=`) only if they have the same type. Two headers are equal if and only if they are both invalid, or they are both valid and all their corresponding fields are equal. Furthermore, the size of a header can be determined at compile-time (`[sec-minsizeinbits]`).

See [\[sec-uninitialized-values-and-writing-invalid-headers\]](#) for a description of the behavior if header fields are read without being initialized, or header fields are written to a currently invalid header.

#### 8.4.6.2. Type checking

Header types are introduced by `header` declarations. Its typing rule is explained in [Section 11.15](#). Header types are then used by referencing their names. Thus header types can be obtained from named types, as illustrated in [Section 8.3](#).

#### 8.4.6.3. Well-formedness

`HEADER typeId < typeArgumentIR* > { ( annotationList typeIRfield nameIRfield ; )* }` is a well-formed type, with bound type variables `B` when:

1. Check that the elements of `nameIRfield*` are distinct.
2. Check that `typeIRfield` can be used in a header type, for all `typeIRfield` in `typeIRfield*`.
3. Check that `typeIRfield` is a well-formed type, with bound type variables `B`, for all `typeIRfield` in `typeIRfield*`.
4. The relation holds.



### 8.4.7. Header unions

A header union represents an alternative containing at most one of several different headers. Header unions can be used to represent "options" in protocols like TCP and IP. They also provide hints to P4 compilers that only one alternative will be present, allowing them to conserve storage resources.

A header union is defined as:

```
typeField
: annotationList type name ;
;

headerUnionTypeDeclaration
: annotationList HEADER_UNION name typeParameterListOpt `{ typeFieldList }
;
```

This declaration introduces a new type definition with the specified name in the current scope.

```
headerUnionTypeDefIR
: HEADER_UNION typeId `< typeParameterIR* > `{ fieldTypeIR* }
;
```

Each element of the list of fields used to declare a header union must be of header type. An empty list of fields is legal. Field names have to be distinct.

As an example, the type `Ip_h` below represents the union of an IPv4 and IPv6 headers:

```
header_union Ip_h {
  IPv4_h v4;
  IPv6_h v6;
}
```

A header union is not considered a type with fixed length.

Internally, header union types and values are represented as follows:

```
headerUnionTypeIR
: HEADER_UNION typeId `< typeArgumentIR* > `{ fieldTypeIR* }
;

headerUnionValue
: HEADER_UNION typeId `{ fieldValue* }
;
```

#### 8.4.7.1. Operations

A variable declared with a union type is initially invalid. For example:

```
header H1 {
  bit<8> f;
}
header H2 {
  bit<16> g;
}
header_union U {
  H1 h1;
  H2 h2;
}
```

```

}

U u; // u invalid

```

This also implies that each of the headers `h1` through `hn` contained in a header union are also initially invalid. Unlike headers, a union cannot be initialized. However, the validity of a header union can be updated by assigning a valid header to one of its elements:

```

U u;
H1 my_h1 = { 8w0 }; // my_h1 is valid
u.h1 = my_h1;      // u and u.h1 are both valid

```

We can also assign a sequence to an element of a header union,

```

U u;
u.h2 = { 16w1 };    // u and u.h2 are both valid

```

or set their validity bits directly.

```

U u;
u.h1.setValid();    // u and u.h1 are both valid
H1 my_h1 = u.h1;    // my_h1 is now valid, but contains an undefined value

```

Note that reading an uninitialized header produces an undefined value, even if the header is itself valid.

If `u` is an expression whose type is a header union `U` with fields ranged over by `hi`, then the expression `u.hi` evaluates to a header, and thus it can be used wherever a header expression is allowed. If `u` is a left-value, then `u.hi` is also a left-value.

The following operations:

- `u.hi.setValid()`: sets the valid bit for header `hi` to `true` and sets the valid bit for all other headers to `false`, which implies that it is unspecified what value reading any member header of `u` will return.
- `u.hi.setInvalid()`: if the valid bit for any member header of `u` is `true` then sets it to `false`, which implies that it is unspecified what value reading any member header of `u` will return.

The assignment to a union field:

```

u.hi = e;

```

has the following meaning:

- if `e` is valid, then it is equivalent to:

```

u.hi.setValid();
u.hi = e;

```

- if `e` is invalid, then it is equivalent to:

```

u.hi.setInvalid();

```

Assignments between variables of the same type of header union are permitted. The assignment `u1 = u2`

copies the full state of header union `u2` to `u1`. If `u2` is valid, then there is some header `u2.hi` that is valid. The assignment behaves the same as `u1.hi = u2.hi`. If `u2` is not valid, then `u1` becomes invalid (i.e. if any header of `u1` was valid, it becomes invalid).

`u.isValid()` returns true if any member of the header union `u` is valid, otherwise it returns false. `setValid()` and `setInvalid()` methods are not defined for header unions.

Supplying an expression with a union type to `emit` simply emits the single header that is valid, if any.

The following example shows how we can use header unions to represent IPv4 and IPv6 headers uniformly:

```
header_union IP {
    IPv4 ipv4;
    IPv6 ipv6;
}

struct Parsed_packet {
    Ethernet ethernet;
    IP ip;
}

parser top(packet_in b, out Parsed_packet p) {
    state start {
        b.extract(p.ethernet);
        transition select(p.ethernet.etherType) {
            16w0x0800 : parse_ipv4;
            16w0x86DD : parse_ipv6;
        }
    }
    state parse_ipv4 {
        b.extract(p.ip.ipv4);
        transition accept;
    }
    state parse_ipv6 {
        b.extract(p.ip.ipv6);
        transition accept;
    }
}
```

As another example, we can also use unions to parse (selected) TCP options:

```
header Tcp_option_end_h {
    bit<8> kind;
}
header Tcp_option_nop_h {
    bit<8> kind;
}
header Tcp_option_ss_h {
    bit<8> kind;
    bit<32> maxSegmentSize;
}
header Tcp_option_s_h {
    bit<8> kind;
    bit<24> scale;
}
header Tcp_option_sack_h {
    bit<8> kind;
    bit<8> length;
    varbit<256> sack;
}
header_union Tcp_option_h {
    Tcp_option_end_h end;
    Tcp_option_nop_h nop;
}
```

```

    Tcp_option_ss_h    ss;
    Tcp_option_s_h     s;
    Tcp_option_sack_h  sack;
}

typedef Tcp_option_h[10] Tcp_option_stack;

struct Tcp_option_sack_top {
    bit<8> kind;
    bit<8> length;
}

parser Tcp_option_parser(packet_in b, out Tcp_option_stack vec) {
    state start {
        transition select(b.lookahead<bit<8>>()) {
            8w0x0 : parse_tcp_option_end;
            8w0x1 : parse_tcp_option_nop;
            8w0x2 : parse_tcp_option_ss;
            8w0x3 : parse_tcp_option_s;
            8w0x5 : parse_tcp_option_sack;
        }
    }
    state parse_tcp_option_end {
        b.extract(vec.next.end);
        transition accept;
    }
    state parse_tcp_option_nop {
        b.extract(vec.next.nop);
        transition start;
    }
    state parse_tcp_option_ss {
        b.extract(vec.next.ss);
        transition start;
    }
    state parse_tcp_option_s {
        b.extract(vec.next.s);
        transition start;
    }
    state parse_tcp_option_sack {
        bit<8> n = b.lookahead<Tcp_option_sack_top>().length;
        // n is the total length of the TCP SACK option in bytes.
        // The length of the varbit field 'sack' of the
        // Tcp_option_sack_h header is thus n-2 bytes.
        b.extract(vec.next.sack, (bit<32>) (8 * n - 16));
        transition start;
    }
}
}

```

Similar to headers, the size of a header union is a local compile-time known value (Section [\[section: minsizeinbits\]](#)).

Two header unions can be compared for equality (==) or inequality (!=) if they have the same type. The unions are equal if and only if all their corresponding fields are equal (i.e., either all fields are invalid in both unions, or in both unions the same field is valid, and the values of the valid fields are equal as headers).

#### 8.4.7.2. Type checking

Header union types are introduced by `header_union` declarations. Its typing rule is explained in [Section 11.16](#). Header union types are then used by referencing their names. Thus header union types can be obtained from named types, as illustrated in [Section 8.3](#).

### 8.4.7.3. Well-formedness

`HEADER_UNION typeId < typeArgumentIR* > { ( annotationList typeIRfield nameIRfield ; )* }` is a well-formed type, with bound type variables `B` when:

1. Check that the elements of `nameIRfield*` are distinct.
2. Check that `typeIRfield` can be used in a header union type, for all `typeIRfield` in `typeIRfield*`.
3. Check that `typeIRfield` is a well-formed type, with bound type variables `B`, for all `typeIRfield` in `typeIRfield*`.
4. The relation holds.

### 8.4.8. Enums

An enumeration type is defined using the following syntax:

```
namedExpression
  : name = expression
  ;

namedExpressionList
  : namedExpression
  | namedExpressionList , namedExpression
  ;

enumTypeDeclaration
  : annotationList ENUM name `{ nameList trailingCommaOpt }
  | annotationList ENUM type name `{ namedExpressionList trailingCommaOpt }
  ;
```

An `enum` declaration introduces a new enum type definition:

```
enumTypeDefIR = enumTypeIR
```

Enums cannot be parameterized over type parameters, thus is always monomorphic.

Enums can be declared in two different ways, depending on whether or not an underlying representation type is provided. The two forms are described below.

Internally, enum types and values are represented as follows:

```
valueFieldIR
  : nameIR = value ;
  ;

enumTypeIR
  : simpleEnumTypeIR
  | serializableEnumTypeIR
  ;

enumValue
  : typeId . nameIR
  | typeId . nameIR . value
  ;
```

#### 8.4.8.1. Enum type declaration without an underlying type

For example, the declaration

```
enum Suits { Clubs, Diamonds, Hearths, Spades }
```

introduces a new enumeration type, which contains four elements—e.g., `Suits.Clubs`. An `enum` declaration introduces a new identifier in the current scope for naming the created type along with its distinct elements. The underlying representation of the `Suits` enum is not specified, so their "size" in bits is not specified (it is target-specific).

#### 8.4.8.2. Enum type declaration with an underlying type

It is also possible to specify an `enum` with an underlying representation. These are sometimes called serializable `enums`, because headers are allowed to have fields with such `enum` types. This requires the programmer provide both the fixed-width unsigned (or signed) integer type and an associated integer value for each symbolic entry in the enumeration.

For example, the declaration

```
enum bit<16> EtherType {  
    VLAN      = 0x8100,  
    QINQ      = 0x9100,  
    MPLS      = 0x8847,  
    IPV4      = 0x0800,  
    IPV6      = 0x86dd  
}
```

introduces a new enumeration type, which contains five elements—e.g., `EtherType.IPV4`. This `enum` declaration specifies the fixed-width unsigned integer representation for each entry in the `enum` and provides an underlying type: `bit<16>`. This kind of `enum` declaration can be thought of as declaring a new `bit<16>` type, where variables or fields of this type are expected to be unsigned 16-bit integer values, and the mapping of symbolic to numeric values defined by the `enum` are also defined as a part of this declaration. In this way, an `enum` with an underlying type can be thought of as being a type derived from the underlying type carrying equality, assignment, and casts to/from the underlying type.

Compiler implementations are expected to raise an error if the fixed-width integer representation for an enumeration entry falls outside the representation range of the underlying type.

For example, the declaration

```
enum bit<8> FailingExample {  
    first      = 1,  
    second     = 2,  
    third      = 3,  
    unrepresentable = 300  
}
```

would raise an error because `300`, the value associated with `FailingExample.unrepresentable` cannot be represented as a `bit<8>` value.

The initializer `expression` must be a local compile-time known value.

Annotations, represented by the non-terminal `annotationList`, are described in [\[sec-annotations\]](#).

#### 8.4.8.3. Operations

Symbolic names declared by an `enum` belong to the namespace introduced by the `enum` declaration

rather than the top-level namespace.

```
enum X { v1, v2, v3 }
X.v1 // reference to v1
v1   // error - v1 is not in the top-level namespace
```

Similar to errors, `enum` expressions without a specified underlying type only support equality (`==`) and inequality (`!=`) comparisons. Expressions whose type is an `enum` without a specified underlying type cannot be cast to or from any other type.

An `enum` may also specify an underlying type, such as the following:

```
enum bit<8> E {
    e1 = 0,
    e2 = 1,
    e3 = 2
}
```

More than one symbolic value in an `enum` may map to the same fixed-width integer value.

```
enum bit<8> NonUnique {
    b1 = 0,
    b2 = 1, // Note, both b2 and b3 map to the same value.
    b3 = 1,
    b4 = 2
}
```

An `enum` with an underlying type also supports explicit casts to and from the underlying type. For instance, the following code:

```
bit<8> x;
E a = E.e2;
E b;

x = (bit<8>) a; // sets x to 1
b = (E) x;      // sets b to E.e2
```

casts `a` (which was initialized with `E.e2`) to a `bit<8>`, using the specified fixed-width unsigned integer representation for `E.e2`, i.e. `1`. The variable `b` is then set to the symbolic value `E.e2`, which corresponds to the fixed-width unsigned integer value `1`.

Because it is always safe to cast from an `enum` to its underlying fixed-width integer type, implicit casting from an `enum` to its fixed-width (signed or unsigned) integer type is also supported (see [Section 17.2](#)):

```
bit<8> x = E.e2; // sets x to 1 (E.e2 is automatically casted to bit<8>)

E a = E.e2
bit<8> y = a << 3; // sets y to 8 (a is automatically casted to bit<8> and then shifted)
```

Implicit casting from an underlying fixed-width type to an `enum` is **not** supported.

```
enum bit<8> E1 {
    e1 = 0, e2 = 1, e3 = 2
}

enum bit<8> E2 {
```

```

    e1 = 10, e2 = 11, e3 = 12
}
E1 a = E1.e1;
E2 b = E2.e2;

a = b;          // Error: b is automatically casted to bit<8>,
                // but bit<8> cannot be automatically casted to E1

a = (E1) b; // OK

a = E1.e1 + 1; // Error: E.e1 is automatically casted to bit<8>,
                // and the right-hand expression has
                // the type bit<8>, which cannot be casted to E automatically.

a = (E1)(E1.e1 + 1); // Final explicit casting makes the assignment legal

a = E1.e1 + E1.e2; // Error: both arguments to the addition are automatically
                // casted to bit<8>. Thus the addition itself is legal, but
                // the assignment is not

a = (E1)(E2.e1 + E2.e2); // Final explicit casting makes the assignment legal

```

A reasonable compiler might generate a warning in cases that involve multiple automatic casts.

```

E1    a = E1.e1;
E2    b = E2.e2;
bit<8> c;

if (a > b) { // Potential warning: two automatic and different casts to bit<8>.
    // code omitted
}

c = a + b; // Legal, but a warning would be reasonable

```

Note that while it is always safe to cast from an `enum` to its fixed-width unsigned integer type, and vice versa, there may be cases where casting a fixed-width unsigned integer value to its related `enum` type produces an unnamed value.

```

bit<8> x = 5;
E e = (E) x; // sets e to an unnamed value

```

sets `e` to an unnamed value, since there is no symbol corresponding to the fixed-width unsigned integer value 5.

For example, in the following code, the `else` clause of the `if/else if/else` block can be reached even though the matches on `x` are complete with respect to the symbols defined in `MyPartialEnum_t`:

```

enum bit<2> MyPartialEnum_t {
    VALUE_A = 2w0,
    VALUE_B = 2w1,
    VALUE_C = 2w2
}

bit<2> y = < some value >;
MyPartialEnum_t x = (MyPartialEnum_t)y;

if (x == MyPartialEnum_t.VALUE_A) {
    // some code here
} else if (x == MyPartialEnum_t.VALUE_B) {
    // some code here
} else if (x == MyPartialEnum_t.VALUE_C) {
    // some code here
}

```



```

} else {
    // A P4 compiler MUST ASSUME that this branch can be executed
    // some code here
}

```

Additionally, if an enumeration is used as a field of a header, we would expect the **transition select** to match **default** when the parsed integer value does not match one of the symbolic values of **EtherType** in the following example:

```

enum bit<16> EtherType {
    VLAN      = 0x8100,
    IPV4      = 0x0800,
    IPV6      = 0x86dd
}

header ethernet {
    // Some fields omitted
    EtherType etherType;
}

parser my_parser(/* parameters omitted */) {
    state parse_ethernet {
        packet.extract(hdr.ethernet);
        transition select(hdr.ethernet.etherType) {
            EtherType.VLAN : parse_vlan;
            EtherType.IPV4 : parse_ipv4;
            EtherType.IPV6 : parse_ipv6;
            default: reject;
        }
    }
}

```

Any variable with an **enum** type that contains an unnamed value (whether as the result of a cast to an **enum** with an underlying type, parse into the field of an **enum** with an underlying type, or simply the declaration of any **enum** without a specified initial value) will not be equal to any of the values defined for that type. Such an unnamed value should still lead to predictable behavior in cases where any legal value would match, e.g. it should match in any of these situations:

- If used in a **select** expression, it should match **default** or **\_** in a key set expression.
- If used as a key with **match\_kind ternary** in a table, it should match a table entry where the field has all bit positions "don't care".
- If used as a key with **match\_kind lpm** in a table, it should match a table entry where the field has a prefix length of 0.

Note that if an **enum** value lacking an underlying type appears in the control-plane API, the compiler must select a suitable serialization data type and representation. For **enum** values with an underlying type and representations, the compiler should use the specified underlying type as the serialization data type and representation.

Additionally, the size of a serializable enum can be determined at compile-time. However, the size of an enum without an underlying type cannot be determined at compile-time ([\[sec-minsizeinbits\]](#)).

#### 8.4.8.4. Type checking

Enum types are introduced by **enum** declarations. Its typing rule is explained in [Section 11.13](#). Enum types are then used by referencing their names. Thus enum types can be obtained from named types, as illustrated in [Section 8.3](#).

#### 8.4.8.5. Well-formedness

`typeIR` is a well-formed type, with bound type variables `B` when:

1. If let `ENUM _ { nameIRfield }*` be `typeIR`:
  - a. Check that the elements of `nameIRfield*` are distinct.
  - b. The relation holds.
2. Else if let `ENUM _ < typeIR' > { ( nameIRfield = _ ; )* }` be `typeIR`:
  - a. Check that the elements of `nameIRfield*` are distinct.
  - b. Check that `typeIR'` can be used in a serializable enum type.
  - c. Check that `typeIR'` is a well-formed type, with bound type variables `B`.
  - d. The relation holds.

## 8.5. Object types and values

```
objectTypeIR
: externObjectTypeIR
| parserObjectTypeIR
| controlObjectTypeIR
| packageObjectTypeIR
| tableObjectTypeIR
;

objectReferenceValue
: REF objectId
;
```

Stateful objects are represented using `objectTypeIR`. At runtime, these objects are passed along directionless parameters as references (`objectReferenceValue`).

The types `parser`, `control`, and `package` cannot be used as types of arguments for actions, functions, methods, parsers, controls, or tables. They *can* be used as types for the arguments passed to constructors.

### 8.5.1. Extern object types

An extern object declaration declares an object and all methods that can be invoked to perform computations and to alter the state of the object. Extern declarations may only appear as allowed by the architecture model and may be specific to a target.

```
externConstructorPrototype
: annotationList typeIdIdentifier `( parameterList ) ;
;

externMethodPrototype
: annotationList functionPrototype ;
| annotationList ABSTRACT functionPrototype ;
;

externConstructorOrMethodPrototype
: externConstructorPrototype
| externMethodPrototype
;
```

```
externObjectDeclaration
: annotationList EXTERN nonTypeName typeParameterListOpt
  `{ externConstructorOrMethodPrototypeList }
;
```

For example, the P4 core library introduces two extern objects `packet_in` and `packet_out` used for manipulating packets (see [\[sec-packet-data-extraction\]](#) and [\[sec-deparse\]](#)). Here is an example showing how the methods of these objects can be invoked on a packet:

```
extern packet_out {
  void emit<T>(in T hdr);
}
control d(packet_out b, in Hdr h) {
  apply {
    b.emit(h.ipv4);      // write ipv4 header into output packet
                        // by calling emit method
  }
}
```

An extern object declaration introduces a new extern object type definition.

```
externObjectTypeDefIR
: EXTERN typeId `< typeParameterIR* , typeParameterIR* >
  externMethodTypeDefEnv
;
```

Extern object types can be referred to using their name. Internally, extern object types are represented as:

```
externObjectTypeIR
: EXTERN typeId `< typeArgumentIR* > externMethodTypeDefEnv
;
```

### 8.5.1.1. Type checking

Extern object types are introduced by `extern` declarations. Its typing rule is explained in [\[sem-extern-object-declaration\]](#). Extern object types are then used by referencing their names. Thus extern object types can be obtained from named types, as illustrated in [Section 8.3](#).

### 8.5.1.2. Well-formedness

`EXTERN typeId < typeArgumentIR* > { ( callableId : externMethodTypeDefIR )* }` is a well-formed type, with bound type variables `B` when:

1. Check that `externMethodTypeDefIR` is a well-formed callable type definition, with bound type variables `B`, for all `externMethodTypeDefIR` in `externMethodTypeDefIR*`.
2. The relation holds.

## 8.5.2. Parser object types

A parser type declaration describes the signature of a parser. A parser should have at least one argument of type `packet_in`, representing the received packet that is processed.

```
parserTypeDeclaration
: annotationList PARSE name typeParameterListOpt `( parameterList ) ;
```

```
;
```

For example, the following is a type declaration of a parser type named `P` that is parameterized on a type variable `H`. That parser receives as input a `packet_in` value `b` and produces two values:

- A value with a user-defined type `H`
- A value with a predefined type `Counters`

```
struct Counters { /* Fields omitted */ }  
parser P<H>(packet_in b,  
           out H packetHeaders,  
           out Counters counters);
```

A parser type declaration introduces a new parser object type definition.

```
parserObjectTypeDefIR  
  : PARSER typeId `< typeParameterIR* , typeParameterIR* > `( parameterIR* )  
  ;
```

Parser types can be referred to using their name and type arguments. Internally, parser types are represented as:

```
parserObjectTypeInfoR  
  : PARSER typeId `< typeArgumentIR* > `( parameterIR* )  
  ;
```

### 8.5.2.1. Type checking

Parser object types are introduced by parser type declarations. Its typing rule is explained in [Section 11.18](#). Parser object types are then used by referencing their names. Thus parser object types can be obtained from named types, as illustrated in [Section 8.3](#).

### 8.5.2.2. Well-formedness

`PARSER typeId < typeArgumentIR* > ( parameterIR* )` is a well-formed type, with bound type variables `B` when:

1. Check that `parameterIR` is a well-formed parameter type, with bound type variables `B`, for all `parameterIR` in `parameterIR*`.
2. The relation holds.

### 8.5.3. Control object types

A control type declaration describes the signature of a control block.

```
controlTypeDeclaration  
  : annotationList CONTROL name typeParameterListOpt `( parameterList ) ;  
  ;
```

Control type declarations are similar to parser type declarations.

A control type declaration introduces a new control object type definition.

```
controlObjectTypeDefIR
: CONTROL typeId < typeParameterIR* , typeParameterIR* > `( parameterIR* )
;
```

Control types can be referred to using their name and type arguments. Internally, control types are represented as:

```
controlObjectTypeIR
: CONTROL typeId < typeArgumentIR* > `( parameterIR* )
;
```

### 8.5.3.1. Type checking

Control object types are introduced by control type declarations. Its typing rule is explained in [Section 11.19](#). Control object types are then used by referencing their names. Thus control object types can be obtained from named types, as illustrated in [Section 8.3](#).

### 8.5.3.2. Well-formedness

**CONTROL typeId < typeArgumentIR\* > ( parameterIR\* )** is a well-formed type, with bound type variables **B** when:

1. Check that **parameterIR** is a well-formed parameter type, with bound type variables **B**, for all **parameterIR** in **parameterIR\***.
2. The relation holds.

## 8.5.4. Package object types

A package type describes the signature of a package.

```
packageTypeDeclaration
: annotationList PACKAGE name typeParameterListOpt `( parameterList ) ;
;
```

This introduces a new package object type definition.

```
packageObjectTypeDefIR
: PACKAGE typeId < typeParameterIR* , typeParameterIR* > `{ typeIR* }
;
```

Package types can be referred to using their name and type arguments. Internally, package types are represented as:

```
packageObjectTypeIR
: PACKAGE typeId < typeArgumentIR* > `{ typeIR* }
;
```

### 8.5.4.1. Type checking

Package object types are introduced by **package** declarations. Its typing rule is explained in [Section 11.20](#). Package object types are then used by referencing their names. Thus package object types can be obtained from named types, as illustrated in [Section 8.3](#).

#### 8.5.4.2. Well-formedness

**PACKAGE** typeId < typeArgumentIR\* > { typeIR\* } is a well-formed type, with bound type variables B when:

1. Check that typeIR' is a well-formed type, with bound type variables B, for all typeIR' in typeIR\*.
2. The relation holds.

#### 8.5.5. Table object types

A **table** declaration introduces a table instance and a table type definition.

```
tableDeclaration
  : annotationList TABLE name `{ tablePropertyList }
  ;

tableObjectTypeDefIR = tableObjectTypeIR
```

Internally, table types are represented as:

```
tableObjectTypeIR
  : TABLE typeId `{ tableMetadataStructTypeIR }
  ;
```

Table metadata types are introduced in [\[sec-table-metadata-type-and-value\]](#).

##### 8.5.5.1. Well-formedness

**TABLE** typeId { tableMetadataStructTypeIR } is a well-formed type, with bound type variables B when:

1. Check that tableMetadataStructTypeIR is a well-formed type, with bound type variables B.
2. The relation holds.

#### 8.5.6. Object reference values

P4 objects are stateful, thus their values are references to the actual objects allocated in the global store.

```
objectId = nameIR*

objectReferenceValue
  : REF objectId
  ;
```

Objects are referred to by their fully-qualified names from the top-level scope. === Alias types

A **typedef** or **type** declaration can be used to give an alias to a type.

```

typedef
  : type
  | derivedTypeDeclaration
  ;

typedefDeclaration
  : annotationList TYPEDEF typedef name ;
  | annotationList TYPE type name ;
  ;

```

Internally, the alias is represented as:

```

aliasTypeIR
  : typedefTypeIR
  | newTypeIR
  ;

```

### 8.5.7. typedef declaration

```

typedef bit<32> u32;
typedef struct Point { int<32> x; int<32> y; } Pt;
typedef Empty_h[32] HeaderStack;

```

The two types are treated as synonyms, and all operations that can be executed using the original type can be also executed using the newly created type.

If `typedef` is used with a generic type the type must be specialized with the suitable number of type arguments:

```

struct S<T> {
  T field;
}

// typedef S X; -- illegal: S does not have type arguments
typedef S<bit<32>> X; // -- legal

```

Internally, the alias is represented as:

```

typedefTypeIR
  : TYPEDEF typeId typeIR
  ;

```

#### 8.5.7.1. Type checking

`typedefs` are introduced by `typedef` declarations. Its typing rule is explained in [Section 11.17.1](#). `typedefs` are then used by referencing their names. Thus `typedef` types can be obtained from named types, as illustrated in [Section 8.3](#).

#### 8.5.7.2. Well-formedness

`TYPEDEF typeId typeIR` is a well-formed type, with bound type variables `B` when:

1. Check that `typeIR` can be used in a `typedef`.

2. Check that `typeIR` is a well-formed type, with bound type variables `B`.
3. The relation holds.

### 8.5.8. type declaration

Similarly to `typedef`, the keyword `type` can be used to introduce a new type.

```
type bit<32> U32;  
U32 x = (U32)0;
```

While similar to `typedef`, the `type` keyword introduces a new type which is not a synonym with the original type: values of the original type and the newly introduced type cannot be mixed in expressions.

Currently the types that can be created by the `type` keyword are restricted to one of: `bit<>`, `int<>`, `bool`, or types defined using `type` from such types.

One important use of such types is in describing P4 values that need to be exchanged with the control plane through communication channels (e.g., through the control-plane API or through network packets sent to the control plane). For example, a P4 architecture may define a type for the switch ports:

```
type bit<9> PortId_t;
```

This declaration will prevent `PortId_t` values from being used in arithmetic expressions without casts. Moreover, this declaration may enable special manipulation of such values by software that lies outside of the datapath (e.g., a target-specific toolchain could include software that automatically converts values of type `PortId_t` to a different representation when exchanged with the control-plane software).

Internally, the alias is represented as:

```
newTypeIR  
  : TYPE typeId typeIR  
  ;
```

#### 8.5.8.1. Operations

Values with a type introduced by the `type` keyword provide only a few operations:

- assignment to left-values of the same type
- comparisons for equality and inequality if the original type supported such comparisons
- casts to and from the original type

```
type bit<32> U32;  
U32 x = (U32)0; // cast needed  
U32 y = (U32) ((bit<32>)x + 1); // casts needed for arithmetic  
bit<32> z = 1;  
bool b0 = x == (U32)z; // cast needed  
bool b1 = (bit<32>)x == z; // cast needed  
bool b2 = x == y; // no cast needed
```

#### 8.5.8.2. Type checking

types are introduced by `type` declarations. Its typing rule is explained in [Section 11.17.2](#). types are then used



by referencing their names. Thus **type** types can be obtained from named types, as illustrated in [Section 8.3](#).

### 8.5.8.3. Well-formedness

**TYPE typeIR' is a well-formed type, with bound type variables B when:**

1. Check that **typeIR'** can be used in a new type.
2. Check that **typeIR'** is a well-formed type, with bound type variables B.
3. The relation holds.

## 8.6. Synthesized types and values

For the purposes of type-checking the P4 compiler can synthesize some type representations which cannot be directly expressed by users.

These types and values are represented as:

```
synthesizedTypeIR
: defaultTypeIR
| invalidHeaderTypeIR
| sequenceTypeIR
| recordTypeIR
| setTypeIR
| tableMetadataTypeIR
;

synthesizedValue
: defaultValue
| invalidHeaderValue
| sequenceValue
| recordValue
| setValue
| tableMetadataValue
;
```

### 8.6.1. Default

A left-value can be initialized automatically with a default value of the suitable type using:

```
defaultExpression
: ...
;
```

Internally, the type and value of **...** itself are represented as:

```
defaultTypeIR
: DEFAULT
;

defaultValue
: DEFAULT
;
```

### 8.6.1.1. Operations

For example:

```
struct S {
    bit<32> b32;
    bool b;
}

enum int<8> N0 {
    one = 1,
    zero = 0,
    two = 2
}

enum N1 {
    A, B, C, F
}

S s0 = ...; // initialize s0 with the default value { 0, false }
N0 n0 = ...; // initialize n0 with the default value 0
N1 n1 = ...; // initialize n1 with the default value N1.A
```

See [Section 14.4](#) for semantics of default initialization.

### 8.6.1.2. Well-formedness

**DEFAULT** is a well-formed type, with bound type variables **B** when:

1. The relation holds.

## 8.6.2. Invalid headers

The expression `{#}` represents an invalid header of some type, but it can be any header or header union type. A P4 compiler may require an explicit cast on this expression in cases where it cannot determine the particular header or header union type from the context.

```
invalidHeaderExpression
: {#}
;
```

Note that the `#` character cannot be misinterpreted as a preprocessor directive, since it cannot be the first character on a line when it occurs in the single lexical token `{#}`, which may not have whitespace or any other characters between those shown.

Internally, the type and value of `{#}` itself are represented as:

```
invalidHeaderTypeIR
: HEADER_INVALID
;

invalidHeaderValue
: {#}
;
```

### 8.6.2.1. Operations

For example:

```
header H { bit<32> x; bit<32> y; }
H h;
h = {#}; // This makes the header h become invalid
```

### 8.6.2.2. Well-formedness

`HEADER_INVALID` is a well-formed type, with bound type variables `B` when:

1. The relation holds.

### 8.6.3. Sequences

A sequence expression is written using curly braces, with each element separated by a comma:

```
sequenceElementExpression = expressionList

sequenceOrRecordElementExpression
: sequenceElementExpression
| recordElementExpression
;

sequenceOrRecordExpression
: `{ sequenceOrRecordElementExpression trailingCommaOpt }
```

The type of a sequence expression is a sequence type. Its value is a sequence value.

```
sequenceTypeIR
: SEQ `< typeIR* >
| SEQ `< typeIR* , ... >
;

sequenceValue
: SEQ `( value* )
| SEQ `( value* , ... )
;
```

#### 8.6.3.1. Operations

Sequence expressions can be assigned to expressions of type `tuple`, `struct` or `header`, and can also be passed as arguments to methods. Sequences may be nested.

For instance, sequences can be assigned to other tuples with the same type:

```
tuple<bit<32>, bool> x = { 10, false };
```

The following program fragment uses a sequence expression to pass several header fields simultaneously to a learning provider:

```
extern LearningProvider<T> {
    LearningProvider();
    void learn(in T data);
```

```

}

LearningProvider<tuple<bit<48>, bit<32>>>() lp;

lp.learn( { hdr.ethernet.srcAddr, hdr.ipv4.src } );

```

A sequence may be used to initialize a structure if the tuple has the same number of elements as fields in the structure. The effect of such an initializer is to assign the  $n^{\text{th}}$  element of the tuple to the  $n^{\text{th}}$  field in the structure:

```

struct S {
    bit<32> a;
    bit<32> b;
}
const S x = { 10, 20 }; // a = 10, b = 20

```

Sequence expressions that have `...` as their last element are allowed to give values to only a subset of the fields of the struct or header type to which it evaluates. Any field names not given a value explicitly will be given their default value (see [\[sec-initializing-with-default-values\]](#)).

### 8.6.3.2. Well-formedness

`sequenceTypeIR` is a well-formed type, with bound type variables `B` when:

1. If let `SEQ < typeIR* >` be `sequenceTypeIR`:
  - a. Check that `typeIR'` is a well-formed type, with bound type variables `B`, for all `typeIR'` in `typeIR*`.
  - b. The relation holds.
2. Else:
  - a. Let `SEQ < typeIR*, ... >` be `sequenceTypeIR`.
  - b. Check that `typeIR'` is a well-formed type, with bound type variables `B`, for all `typeIR'` in `typeIR*`.
  - c. The relation holds.

### 8.6.4. Records

One can write record expressions that evaluate to a structure or header. The syntax of these expressions is given by:

```

recordElementExpression
: name = expression
| name = expression , ...
| name = expression , namedExpressionList
| name = expression , namedExpressionList , ...
;

sequenceOrRecordElementExpression
: sequenceElementExpression
| recordElementExpression
;

sequenceOrRecordExpression
: `{ sequenceOrRecordElementExpression trailingCommaOpt }
;

```

Internally, the type and value of a record expression are represented as:

```
recordTypeIR
: RECORD `{ fieldTypeIR* }
| RECORD `{ fieldTypeIR* , ... }
;

recordValue
: RECORD `{ fieldValue* }
| RECORD `{ fieldValue* , ... }
;
```

#### 8.6.4.1. Operations

The following example shows a structure-valued expression used in an equality comparison expression:

```
struct S {
    bit<32> a;
    bit<32> b;
}

void f() {
    S s;

    // Compare s with a record expression
    bool b = s == (S) { a = 1, b = 2 };
}
```

Record expressions can be used in the right-hand side of assignments, in comparisons, in field selection expressions, and as arguments to functions, method or actions. Record expressions are not left values.

Record expressions that do not have `...` as their last element must provide a value for every member of the struct or header type to which it evaluates, by mentioning each field name exactly once.

Record expressions that have `...` as their last element are allowed to give values to only a subset of the fields of the struct or header type to which it evaluates. Any field names not given a value explicitly will be given their default values (see [\[sec-initializing-with-default-values\]](#)).

The order of the fields of the `struct` or `header` type does not need to match the order of the values of the structure-valued expression.

It is a compile-time error if a field name appears more than once in the same structure-valued expression.

#### 8.6.4.2. Well-formedness

`recordTypeIR` is a well-formed type, with bound type variables `B` when:

1. If let `RECORD { ( _ typeIRfield nameIRfield ; ) * }` be `recordTypeIR`:
  - a. Check that the elements of `nameIRfield *` are distinct.
  - b. Check that `typeIRfield` is a well-formed type, with bound type variables `B`, for all `typeIRfield` in `typeIRfield *`.
  - c. The relation holds.
2. Else:
  - a. Let `RECORD { ( _ typeIRfield nameIRfield ; ) * , ... }` be `recordTypeIR`.

- b. Check that the elements of  $\text{nameIR}_{\text{field}}^*$  are distinct.
- c. Check that  $\text{typeIR}_{\text{field}}$  is a well-formed type, with bound type variables  $B$ , for all  $\text{typeIR}_{\text{field}}$  in  $\text{typeIR}_{\text{field}}^*$ .
- d. The relation holds.

## 8.6.5. Sets

```
setTypeIR
: SET `< typeIR >
;
```

The set type describes *sets* of values of some type  $T$ . Set types can only appear in restricted contexts in P4 programs. For example, the range expression `8w5 .. 8w8` describes a set containing the 8-bit numbers 5, 6, 7, and 8, so its type is `set<bit<8>>;`. This expression can be used as a label in a `select` expression (see [\[sec-select\]](#)), matching any value in this range. Set types cannot be named or declared by P4 programmers, they are only synthesized by the compiler internally and used for type-checking.

Set values are represented as:

```
setValue
: SET `{ value }
| SET `{ value* `( nat ) }
| SET `{ value &&& value }
| SET `{ value .. value }
| SET `{ ... }
;
```

### 8.6.5.1. Operations

Some P4 expressions denote sets of values. These expressions can appear only in a few contexts—parsers and table entries. For example, the `select` expression ([\[sec-select\]](#)) has the following structure:

```
select (expression) {
  set1: state1;
  set2: state2;
  // More labels omitted
}
```

Here the expressions `set1`, `set2`, etc. evaluate to sets of values and the `select` expression tests whether `expression` belongs to the sets used as labels.

```
keysetExpression
: simpleKeysetExpression
| tupleKeysetExpression
;

tupleKeysetExpression
: `( expression &&& expression )
| `( expression .. expression )
| `( DEFAULT )
| `( _ )
| `( simpleKeysetExpression , simpleKeysetExpressionList )
;

simpleKeysetExpressionList
: simpleKeysetExpression
```

```

| simpleKeysetExpressionList , simpleKeysetExpression
;

simpleKeysetExpression
: expression
| expression &&& expression
| expression .. expression
| DEFAULT
| _
;

```

The mask (&&&) and range (..) operators have the same precedence; the just above the ?: operator.

#### 8.6.5.1.1. Singleton sets

In a set context, expressions denote singleton sets. For example, in the following program fragment,

```

select (hdr.ipv4.version) {
  4: continue;
}

```

The label 4 denotes the singleton set containing the int value 4.

#### 8.6.5.1.2. The universal set

In a set context, the expressions default or \_ denote the universal set, which contains all possible values of a given type:

```

select (hdr.ipv4.version) {
  4: continue;
  _: reject;
}

```

#### 8.6.5.1.3. Masks

The infix operator &&& takes two arguments of the same numeric type ([sec-numeric-values]), and creates a value of the same type. The right value is used as a "mask", where each bit set to 0 in the mask indicates a "don't care" bit. More formally, the set denoted by  $a \ \&\&\ b$  is defined as follows:

$$a \ \&\&\ b = \{ c \text{ where } a \ \& \ b = c \ \& \ b \}$$

For example:

```
8w0x0A &&& 8w0x0F
```

denotes a set that contains 16 different bit<8> values, whose bit-pattern is XXXX1010, where the value of an X can be any bit. Note that there may be multiple ways to express a keyset using a mask operator—e.g., 8w0xFA &&& 8w0x0F denotes the same keyset as in the example above.

Similar to other binary operations, the mask operator allows the compiler to automatically insert casts to unify the argument types in certain situations (Section 17.2).

P4 architectures may impose additional restrictions on the expressions on the left and right-hand side of a mask operator: for example, they may require that either or both sub-expressions be compile-time known values.

#### 8.6.5.1.4. Ranges

The infix operator `..` takes two arguments of the same numeric type `T` ([\[sec-numeric-values\]](#)), and creates a value of the type `set<T>`. The set contains all values numerically between the first and the second, inclusively. For example:

```
4s5 .. 4s8
```

denotes a set of 4 consecutive `int<4>` values `4s5`, `4s6`, `4s7`, and `4s8`.

Similar to other binary operations, the range operator allows the compiler to automatically insert casts to unify the argument types in certain situations ([\[sec-implicit-casts\]](#)).

A range where the second value is smaller than the first one represents an empty set.

#### 8.6.5.1.5. Products

Multiple sets can be combined using Cartesian product:

```
select(hdr.ipv4.ihl, hdr.ipv4.protocol) {  
  (4w0x5, 8w0x1): parse_icmp;  
  (4w0x5, 8w0x6): parse_tcp;  
  (4w0x5, 8w0x11): parse_udp;  
  (_, _): accept; }
```

The type of a product of sets is a set of sequences or tuples.

#### 8.6.5.2. Well-formedness

`SET < typeIR' >` is a well-formed type, with bound type variables `B` when:

1. Check that `typeIR'` can be used in a set type.
2. Check that `typeIR'` is a well-formed type, with bound type variables `B`.
3. The relation holds.

#### 8.6.6. Table metadata

A `table` can be invoked by calling its `apply` method. Calling an `apply` method on a table instance returns a value with a table metadata `struct` type with three fields. This structure is synthesized by the compiler automatically. For each `table T`, the compiler synthesizes a table metadata `enum` and a `struct`, shown in pseudo-P4:

```
enum action_list(T) {  
  // one field for each action in the actions list of table T  
}  
struct apply_result(T) {  
  bool hit;  
  bool miss;  
  action_list(T) action_run;  
}
```



### 8.6.6.1. Operations

The evaluation of the `apply` method sets the `hit` field to `true` and the field `miss` to `false` if a match is found in the lookup-table; if a match is not found `hit` is set to `false` and `miss` to `true`. These bits can be used to drive the execution of the control-flow in the control block that invoked the table:

```
if (ipv4_match.apply().hit) {
    // there was a hit
} else {
    // there was a miss
}

if (ipv4_host.apply().miss) {
    ipv4_lpm.apply(); // Look up the route only if host table missed
}
```

The `action_run` field indicates which kind of action was executed (irrespective of whether it was a hit or a miss). It can be used in a switch statement:

```
switch (dmac.apply().action_run) {
    Drop_action: { return; }
}
```

Internally, the type and value of table metadata are represented as:

```
tableMetadataTypeIR
: tableMetadataEnumTypeIR
| tableMetadataStructTypeIR
;

tableMetadataValue
: tableMetadataEnumValue
| tableMetadataStructValue
;
```

### 8.6.6.2. Well-formedness

`typeIR` is a well-formed type, with bound type variables `B` when:

1. If let `TABLE_ENUM _ { nameIR* }` be `typeIR`:
  - a. Check that the elements of `nameIR*` are distinct.
  - b. The relation holds.
2. Else if let `TABLE_STRUCT _ { HIT _ ; MISS _ ; ACTION_RUN tableMetadataEnumTypeIR ; }` be `typeIR`:
  - a. Check that `tableMetadataEnumTypeIR` is a well-formed type, with bound type variables `B`.
  - b. The relation holds.

## 8.7. Unrolling

`typedefs`, described in [Section 8.5.7](#), introduce indirection in types.

```
struct S {
```

```

    bit<8> t;
    int<8> u;
}

typedef S A;

```

The type `A` is an alias of the struct type `S`. Nevertheless, the underlying type of `A` is a `structTypeIR` with two fields, `t` and `u`, of types `int<8>` and `bit<8>` respectively. It is useful to be able to work with the underlying type of `A`, when dealing with type checking, type equivalence, and other type-based analyses.

Unrolling is the process of recursively expanding all `typedefs` until a type is fully expanded to its underlying type.

`typeIR with typedefs unrolled`

1. If let `TYPEDEF _ typeIR'` be `typeIR`:
  - a. Return `typeIR' with typedefs unrolled`.
2. Otherwise:
  - a. Return `typeIR`.

## 9. P4 callables

$P4_{16}$  includes four entities that can be invoked: actions, functions, methods, and object constructors. Object constructors are explained in [\[sec-def-object\]](#). The other three callable entities are collectively referred to as *callables*.

Callable types are created by the P4 compiler internally to represent the types of actions, functions, and methods during type-checking. We also call the type of a callable its signature. Libraries can contain callable declarations.

For example, consider the following declarations:

```

extern void random(in bit<5> logRange, out bit<32> value);

bit<32> add(in bit<32> left, in bit<32> right) {
    return left + right;
}

```

These declarations describe two callables:

- `random`, which has an extern function type, representing the following information:
  - the result type is `void`
  - the function has two inputs
  - the first formal parameter has direction `in`, type `bit<5>`, and name `logRange`
  - the second formal parameter has direction `out`, type `bit<32>`, and name `value`
- `add`, also has a function type, representing the following information:
  - the result type is `bit<32>`
  - the function has two inputs
  - both inputs have direction `in` and type `bit<32>`

Specifically, during type checking, callable declarations introduce a type constructor for the callable type:

```
callableTypeDefIR
: actionTypeDefIR
| functionTypeDefIR
| methodTypeDefIR
;
```

These callable type definitions are used to construct callable types via specialization:

```
callableTypeIR
: actionTypeIR
| functionTypeIR
| methodTypeIR
;
```

The well-formedness rules for callable types are checked by:

**CallableType\_wf:**

- **callableTypeIR** is a well-formed callable type, with bound type variables **B**

The runtime representation of a callable is given by:

```
callableDef
: actionDef
| functionDef
| methodDef
;
```

## 9.1. Parameters

```
direction
: /* empty */
| IN
| OUT
| INOUT
;

parameter
: annotationList direction type name initializerOpt
;
```

Callables can have parameters. Each parameter has a direction, a type, a name, and an optional default value.

A parameter is internally represented as:

```
parameterIR
: annotationList direction typeIR id parameterInitializerOptIR
;
```

The high-level overview of parameters with respect to the copy in/copy out calling convention is

described in [Section 6.5](#). Below are the formal typing and well-formedness rules for parameters that implement the restrictions described there.

### 9.1.1. Type checking

**Parameter\_ok:**

- Typing `parameter`, under cursor `cursor` and context `typingContext`:
- Result in context `typingContext`,
  - `parameterIR`, and a set of fresh type variables `typeId*`.

Typing a parameter produces a `parameterIR` if it is well-typed. A parameter is well-typed when its type is well-formed and its default value (if any) has the same type as the parameter type.

**Typing** `annotationList direction type name initializerOpt`, under cursor `p` and context `TC0`:

1. If `initializerOpt` is `EMPTY`:
  - a. Let `typeIR` and a set of fresh type variables `typeIdfresh*` be
    - the result of **typing** `type`, under cursor `p` and context `TC0`.
  - b. Let `bound` be **bound type variables from the `p` layer of `TC0`**.
  - c. Let `B` be **the union of the sets `bound` and `{ typeIdfresh* }`**.
  - d. Check that `typeIR` is a well-formed type, with bound type variables `B`.
  - e. Let `nameIR` be **the name of `name`**.
  - f. Let `parameterIR` be `annotationList direction typeIR nameIR`.
  - g. Let `TC1` be `parameterIR` added to the `p` layer of `TC0`.
  - h. Result in context `TC1`,
    - `parameterIR`, and a set of fresh type variables `typeIdfresh*`.
2. Else:
  - a. Let `= expressioninit` be `initializerOpt`.
  - b. Let `typeIR` and a set of fresh type variables `typeIdfresh*` be
    - the result of **typing** `type`, under cursor `p` and context `TC0`.
  - c. Let `bound` be **bound type variables from the `p` layer of `TC0`**.
  - d. Let `B` be **the union of the sets `bound` and `{ typeIdfresh* }`**.
  - e. Check that `typeIR` is a well-formed type, with bound type variables `B`.
  - f. Let `typedExpressionIRinit` be
    - the result of **typing** `expressioninit`, under cursor `p` and context `TC0`.
  - g. Let `typeIRinit` be **the type of `typedExpressionIRinit`**.
  - h. If **the compile-time known-ness of `typedExpressionIRinit` is `CTK`**:
    - i. Let `typedExpressionIRinit_cast` be **! typedExpressionIR<sub>init</sub> implicitly cast to `typeIR`**.
    - ii. Let `nameIR` be **the name of `name`**.
    - iii. Let `parameterInitializerIR` be `= typedExpressionIRinit_cast`.

- iv. Let `parameterIR` be `annotationList direction typeIR nameIR parameterInitializerIR`.
- v. Let `TC1` be `parameterIR added to the p layer of TC0`.
- vi. Result in context `TC1`,
  - `parameterIR`, and a set of fresh type variables `typedfresh*`.
- i. Else if `the compile-time known-ness of typedExpressionIRinit` is LTK:
  - i. Let `typedExpressionIRinit_cast` be `! typedExpressionIRinit implicitly cast to typeIR`.
  - ii. Let `nameIR` be `the name of name`.
  - iii. Let `valueinit` be
    - the result of `local compile-time evaluation of typedExpressionIRinit_cast`, under cursor `p` and context `TC0`.
  - iv. Let `parameterInitializerIR` be ``VALUE valueinit``.
  - v. Let `parameterIR` be `annotationList direction typeIR nameIR parameterInitializerIR`.
  - vi. Let `TC1` be `parameterIR added to the p layer of TC0`.
  - vii. Result in context `TC1`,
    - `parameterIR`, and a set of fresh type variables `typedfresh*`.

### 9.1.2. Well-formedness

#### ParameterType\_wf:

- `annotationList direction typeIR id parameterInitializerIR2` is a well-formed parameter type, with bound type variables `B`

A parameter type is well-formed when its type is well-formed. Also, the type should not be a synthesized type. Types that can only be local compile-time known or compile-time known (e.g., `int` type) must be directionless. A default value can be specified for `in` or directionless parameters only.

`annotationList direction typeIR id parameterInitializerIR2` is a well-formed parameter type, with bound type variables `B` when:

1. If `parameterInitializerIR2` is none:
  - a. Check that `typeIR` is a well-formed type, with bound type variables `B`.
  - b. Let `typeIRunroll` be `typeIR with typedefs unrolled`.
  - c. Check that `typeIRunroll` does not have type `synthesizedTypeIR`.
  - d. Check that if `typeIRunroll` is equal to `INT` or `typeIRunroll` has type `stringTypeIR` or `typeIRunroll` has type `objectTypeIR`, then `direction` is equal to ``EMPTY`.
  - e. The relation holds.
2. Else:
  - a. Check that `typeIR` is a well-formed type, with bound type variables `B`.
  - b. Let `typeIRunroll` be `typeIR with typedefs unrolled`.
  - c. Check that `typeIRunroll` does not have type `synthesizedTypeIR`.
  - d. Check that if `typeIRunroll` is equal to `INT` or `typeIRunroll` has type `stringTypeIR` or `typeIRunroll` has type

`objectTypeIR`, then `direction` is equal to ``EMPTY`.

- e. Check that `direction` is equal to `IN` or `direction` is equal to ``EMPTY`.
- f. Check that `~$optional_annotation_of_parameterIR'(annotationList)`.
- g. The relation holds.

## 9.2. Callable definitions (callable constructors)

Similar to how type declarations introduce type definitions (see [Section 8.3.1](#)), callable declarations introduce callable definitions. These are constructors for callable types, that are parameterized by type parameters (if any).

```
actionTypeDefIR = actionTypeIR

functionTypeDefIR
  : definedFunctionTypeDefIR
  | externFunctionTypeDefIR
  ;

methodTypeDefIR
  : externMethodTypeDefIR
  | parserApplyMethodTypeDefIR
  | controlApplyMethodTypeDefIR
  | tableApplyMethodTypeDefIR
  ;

callableTypeDefIR
  : actionTypeDefIR
  | functionTypeDefIR
  | methodTypeDefIR
  ;
```

When specialized with concrete type arguments, callable type definitions yield callable types:

```
actionTypeIR
  : annotationList ACTION nameIR `( parameterIR* )
  ;

functionTypeIR
  : definedFunctionTypeIR
  | externFunctionTypeIR
  ;

methodTypeIR
  : builtinMethodTypeIR
  | externMethodTypeIR
  | parserApplyMethodTypeIR
  | controlApplyMethodTypeIR
  | tableApplyMethodTypeIR
  ;

callableTypeIR
  : actionTypeIR
  | functionTypeIR
  | methodTypeIR
  ;
```

For example, a function declaration introduces a function type definition:

```
T identity<T>(in T t) { return t; }
```

`identity` is a generic function type definition that falls into:

```
definedFunctionTypeDefIR
: FUNCTION nameIR `< typeParameterIR* , typeParameterIR* > `( parameterIR* )
: typeIR
;
```

Notice that `definedFunctionTypeDefIR` does *not* include the function body. Because callable type definitions are used during type checking, the body of the callable is not part of the type definition. After specialization with proper type argument(s), it yields a function type:

```
definedFunctionTypeIR
: FUNCTION nameIR `( parameterIR* ) : typeIR
;
```

### 9.2.1. Well-formedness

`$(relation: CallableTypeDef_wf)`

`$(rulegroup: CallableTypeDef_wf) $(ruleprose: CallableTypeDef_wf)`

## 9.3. Actions




Figure 10. Actions contain code and data. The code is in the P4 program, while the data is provided in the table entries, typically populated by the control plane. Other parameters are bound by the data plane.

Actions are code fragments that can read and write the data being processed. Actions may contain data values that can be written by the control plane and read by the data plane. Actions are the main construct by which the control plane can dynamically influence the behavior of the data plane. [Figure 10](#) shows the abstract model of an `action`.

```
actionDeclaration
: annotationList ACTION name `( parameterList ) blockStatement
;
```

Syntactically actions resemble functions with no return value. Actions may be declared within a control block; in this case they can only be used within instances of that control block.

The following example shows an action declaration:

```
action Forward_a(out bit<9> outputPort, bit<9> port) {
    outputPort = port;
```

```
}
```

Action parameters may not have `extern` types. Action parameters that have no direction (e.g., `port` in the previous example) indicate "action data." All such parameters must appear at the end of the parameter list. When used in a match-action table (see [\[sec-table-action-list\]](#)), these parameters will be provided by the table entries (e.g., as specified by the control plane, the `default_action` table property, or the `entries` table property).

The body of an action consists of a sequence of statements and declarations. No `table`, `control`, or `parser` applications can appear within actions.

Some targets may impose additional restrictions on action bodies—e.g., only allowing straight-line code, with no conditional statements or expressions.

Actions can be executed in two ways:

- Implicitly: by tables during match-action processing.
- Explicitly: either from a `control` block or from another `action`. In either case, the values for all action parameters must be supplied explicitly, including values for the directionless parameters. In this case, the directionless parameters behave like `in` parameters.

Actions are introduced by `action` declarations. Its typing and instantiation rules are explained in [Section 11.6](#). It introduces an action type definition:

```
actionTypeDefIR = actionTypeIR
```

Because actions cannot be generic, the action type is the same as the action type definition:

```
actionTypeIR
: annotationList ACTION nameIR `( parameterIR* )
;
```

The runtime representation of an action is as follows:

```
actionDef
: ACTION nameIR `( parameterListIR ) blockStatementIR
;
```

### 9.3.1. Well-formedness

`annotationList ACTION nameIR ( parameterIR* )` is a well-formed callable type, with bound type variables `B` when:

1. Check that `parameterIR` is a well-formed parameter type, with bound type variables `B`, for all `parameterIR` in `parameterIR*`.
2. Check that `parameterIR` is not an optional parameter, for all `parameterIR` in `parameterIR*`.
3. Let `direction*` be the list of `direction` and `typeIR*` be the list of `typeIR`, obtained by repeating:

- Let `direction` and `typeIR` be the direction and the type of `parameterIR`.

for each `parameterIR` in `parameterIR*`



4. Check that **directionless parameters in  $\text{direction}^*$  only appear at the end.**
5. Check that  **$\text{typeIR}$  can be used in an action type**, for all  $\text{typeIR}$  in  $\text{typeIR}^*$ .
6. The relation holds.

## 9.4. Functions

Two kinds of functions are supported in P4: user-defined functions and extern functions. The former are functions whose implementation is provided in P4 source code, while the latter are functions whose implementation is provided externally by the target architecture.

The internal representation of functions is as follows:

```
functionTypeDefIR
  : definedFunctionTypeDefIR
  | externFunctionTypeDefIR
  ;

functionTypeIR
  : definedFunctionTypeIR
  | externFunctionTypeIR
  ;

functionDef
  : definedFunctionDef
  | externFunctionDef
  ;
```

### 9.4.1. User-defined functions

Functions can only be declared at the top level and all parameters must have a direction. P4 functions are modeled after functions as found in most other programming languages, but the language does not permit recursive functions.

```
functionPrototype
  : typeOrVoid name typeParameterListOpt `( parameterList )
  ;

functionDeclaration
  : annotationList functionPrototype blockStatement
  ;
```

Here is an example of a function that returns the maximum of two 32-bit values:

```
bit<32> max(in bit<32> left, in bit<32> right) {
  return (left > right) ? left : right;
}
```

A function returns a value using the **return** statement. A function with a return type of **void** can simply use the **return** statement with no arguments. A function with a non-void return type must return a value of the suitable type on all possible execution paths.

The typing and instantiation rules for **function** declarations is explained in [Section 11.5](#). This introduces a function type definition, which can be specialized to a function type.

```

definedFunctionTypeDefIR
  : FUNCTION nameIR `< typeParameterIR* , typeParameterIR* > `( parameterIR* )
  : typeIR
  ;

definedFunctionTypeIR
  : FUNCTION nameIR `( parameterIR* ) : typeIR
  ;

```

Also, the runtime representation of a defined function is as follows:

```

definedFunctionDef
  : FUNCTION nameIR `< typeParameterListIR > `( parameterListIR )
  blockStatementIR
  ;

```

#### 9.4.1.1. Well-formedness

`FUNCTION nameIR ( parameterIR* ) : typeIRret` is a well-formed callable type, with bound type variables `B` when:

1. Check that `parameterIR` is a well-formed parameter type, with bound type variables `B`, for all `parameterIR` in `parameterIR*`.
2. Check that `parameterIR` is not an optional parameter, for all `parameterIR` in `parameterIR*`.
3. Let `typeIR*` be the list of `typeIR`, obtained by repeating:
  - Let `typeIR` be the type of `parameterIR`.
 for each `parameterIR` in `parameterIR*`
4. Check that `typeIR` can be used in a defined function type, for all `typeIR` in `typeIR*`.
5. Check that `typeIRret` is a well-formed return type, with bound type variables `B`.
6. The relation holds.

#### 9.4.2. Extern functions

An extern function declaration describes the name and type signature of the function, but not its implementation.

```

externDeclaration
  : externFunctionDeclaration
  | externObjectDeclaration
  ;

```

`extern` declarations introduce extern function type definitions, which can be specialized to extern function types.

```

externFunctionTypeDefIR
  : EXTERN_FUNCTION nameIR `< typeParameterIR* , typeParameterIR* >
  `( parameterIR* ) : typeIR
  ;

```

```
externFunctionTypeIR
: EXTERN_FUNCTION nameIR `( parameterIR* ) : typeIR
;
```

Also, the runtime representation of an extern function is as follows:

```
externFunctionDef
: EXTERN_FUNCTION nameIR `< typeParameterListIR > `( parameterListIR )
;
```

See [Section 11.9](#) for the typing and instantiation rules for `extern` function declarations.

#### 9.4.2.1. Well-formedness

`EXTERN_FUNCTION nameIR ( parameterIR* ) : typeIRret` is a well-formed callable type, with bound type variables `B` when:

1. Check that `parameterIR` is a well-formed parameter type, with bound type variables `B`, for all `parameterIR` in `parameterIR*`.
2. Let `typeIR*` be the list of `typeIR`, obtained by repeating:
  - Let `typeIR` be the type of `parameterIR`.
for each `parameterIR` in `parameterIR*`
3. Check that `typeIR` can be used in an extern function type, for all `typeIR` in `typeIR*`.
4. Check that `typeIRret` is a well-formed return type, with bound type variables `B`.
5. The relation holds.

## 9.5. Methods

Objects in P4 can have methods associated with them. Specifically, `extern` objects have methods declared in their definitions. `parser`, `control`, and `table` objects have built-in `apply` methods.

Further, P4 allows built-in methods for certain types, such as `isValid()` and `setValid()` methods for header types.

The internal representation of methods is defined as follows:

```
methodTypeDefIR
: externMethodTypeDefIR
| parserApplyMethodTypeDefIR
| controlApplyMethodTypeDefIR
| tableApplyMethodTypeDefIR
;

methodTypeIR
: builtinMethodTypeIR
| externMethodTypeIR
| parserApplyMethodTypeIR
| controlApplyMethodTypeIR
| tableApplyMethodTypeIR
;
```

```

methodDef
: externMethodDef
| parserApplyMethodDef
| controlApplyMethodDef
| tableApplyMethodDef
;

```

### 9.5.1. Extern methods

An extern object declaration declares an object and all methods that can be invoked to perform computations and to alter the state of the object.

```

externConstructorPrototype
: annotationList typeIdIdentifier `( parameterList ) ;
;

externMethodPrototype
: annotationList functionPrototype ;
| annotationList ABSTRACT functionPrototype ;
;

externConstructorOrMethodPrototype
: externConstructorPrototype
| externMethodPrototype
;

externObjectDeclaration
: annotationList EXTERN nonTypeName typeParameterListOpt
  `{ externConstructorOrMethodPrototypeList }
;

```

For example, the P4 core library introduces two extern objects `packet_in` and `packet_out` used for manipulating packets (see [\[sec-packet-data-extraction\]](#) and [\[sec-deparse\]](#)). Here is an example showing how the methods of these objects can be invoked on a packet:

```

extern packet_out {
    void emit<T>(in T hdr);
}
control d(packet_out b, in Hdr h) {
    apply {
        b.emit(h.ipv4);          // write ipv4 header into output packet
    }                          // by calling emit method
}

```

Internally, extern methods are represented as follows:

```

externMethodTypeDefIR
: EXTERN_METHOD nameIR `< typeParameterIR* , typeParameterIR* >
  `( parameterIR* ) : typeIR
| EXTERN_METHOD ABSTRACT nameIR `< typeParameterIR* , typeParameterIR* >
  `( parameterIR* ) : typeIR
;

externMethodTypeIR
: EXTERN_METHOD nameIR `( parameterIR* ) : typeIR
| EXTERN_METHOD ABSTRACT nameIR `( parameterIR* ) : typeIR
;

externMethodDef
: EXTERN_METHOD nameIR `< typeParameterListIR > `( parameterListIR )
  blockStatementIR?

```

```
| EXTERN_METHOD ABSTRACT nameIR `< typeParameterListIR > `( parameterListIR )
;
```

Typical extern object methods are implemented by the target architecture. P4 programmers can only call such methods.

Some types of extern objects may provide methods that can be implemented by the P4 programmers. Such methods are described with the **abstract** keyword prior to the method definition. Here is an example:

```
extern Balancer {
  Balancer();
  // get the number of active flows
  bit<32> getFlowCount();
  // return port index used for load-balancing
  // @param address: IPv4 source address of flow
  abstract bit<4> on_new_flow(in bit<32> address);
}
```

When such an object is instantiated the user has to supply an implementation of all the **abstract** methods (see [\[sec-instantion-abstract-method\]](#)).

### 9.5.1.1. Well-formedness

**externMethodTypeIR** is a well-formed callable type, with bound type variables **B** when:

1. If let **EXTERN\_METHOD \_ ( parameterIR<sup>\*</sup> ) : typeIR<sub>ret</sub>** be **externMethodTypeIR**:
  - a. Check that **parameterIR** is a well-formed parameter type, with bound type variables **B**, for all **parameterIR** in **parameterIR<sup>\*</sup>**.
  - b. Let **typeIR<sup>\*</sup>** be the list of **typeIR**, obtained by repeating:
    - Let **typeIR** be the type of **parameterIR**.
 for each **parameterIR** in **parameterIR<sup>\*</sup>**
  - c. Check that **typeIR** can be used in an extern method type, for all **typeIR** in **typeIR<sup>\*</sup>**.
  - d. Check that **typeIR<sub>ret</sub>** is a well-formed return type, with bound type variables **B**.
  - e. The relation holds.
2. Else:
  - a. Let **EXTERN\_METHOD ABSTRACT \_ ( parameterIR<sup>\*</sup> ) : typeIR<sub>ret</sub>** be **externMethodTypeIR**.
  - b. Check that **parameterIR** is a well-formed parameter type, with bound type variables **B**, for all **parameterIR** in **parameterIR<sup>\*</sup>**.
  - c. Check that **parameterIR** is not an optional parameter, for all **parameterIR** in **parameterIR<sup>\*</sup>**.
  - d. Let **typeIR<sup>\*</sup>** be the list of **typeIR**, obtained by repeating:
    - Let **typeIR** be the type of **parameterIR**.
 for each **parameterIR** in **parameterIR<sup>\*</sup>**
  - e. Check that **typeIR** can be used in an extern method type, for all **typeIR** in **typeIR<sup>\*</sup>**.
  - f. Check that **typeIR<sub>ret</sub>** is a well-formed return type, with bound type variables **B**.
  - g. The relation holds.

## 9.5.2. Parser apply methods

P4 allows parsers to invoke the services of other parsers, similar to subroutines. To invoke the services of another parser, the sub-parser must be first instantiated; the services of an instance are invoked by calling it using its `apply` method.

The following example shows a sub-parser invocation:

```
parser callee(packet_in packet, out IPv4 ipv4) { /* body omitted */ }
parser caller(packet_in packet, out Headers h) {
  callee() subparser; // instance of callee
  state subroutine {
    subparser.apply(packet, h.ipv4); // invoke sub-parser
    transition accept; // accept if sub-parser ends in accept state
  }
}
```

A parser apply method type definition is implicitly introduced by a `parser` declaration. Its semantics is explained in [Section 11.11](#). A parser apply method is represented internally as follows:

```
parserApplyMethodTypeDefIR = parserApplyMethodTypeIR

parserApplyMethodTypeIR
: PARSE_APPLY `( parameterIR* )
;

parserApplyMethodDef
: PARSE_APPLY `( parameterListIR )
  `{ parserLocalDeclarationListIR ; stateEnv }
;
```

### 9.5.2.1. Well-formedness

`PARSE_APPLY ( parameterIR* )` is a well-formed callable type, with bound type variables **B** when:

1. Check that `parameterIR` is a well-formed parameter type, with bound type variables **B**, for all `parameterIR` in `parameterIR*`.
2. Check that `parameterIR` is not an optional parameter, for all `parameterIR` in `parameterIR*`.
3. Let `typeIR*` be the list of `typeIR`, obtained by repeating:
  - Let `typeIR` be the type of `parameterIR`.for each `parameterIR` in `parameterIR*`
4. Check that `typeIR` can be used in a parser apply method type, for all `typeIR` in `typeIR*`.
5. The relation holds.

## 9.5.3. Control apply methods

P4 allows controls to invoke the services of other controls, similar to subroutines. To invoke the services of another control, it must be first instantiated; the services of an instance are invoked by calling it using its `apply` method.

The following example shows a control invocation:

```

control Callee(inout IPv4 ipv4) { /* body omitted */ }
control Caller(inout Headers h) {
  Callee() instance; // instance of callee
  apply {
    instance.apply(h.ipv4); // invoke control
  }
}

```

A control apply method type definition is implicitly introduced by a **control** declaration. Its semantics is explained in [Section 11.12](#). A control apply method is represented internally as follows:

```

controlApplyMethodTypeDefIR = controlApplyMethodTypeIR

controlApplyMethodTypeIR
  : CONTROL_APPLY `( parameterIR* )
  ;

controlApplyMethodDef
  : CONTROL_APPLY `( parameterListIR )
    `{ controlLocalDeclarationListIR ; actionDefEnv ; controlBodyIR }
  ;

```

### 9.5.3.1. Well-formedness

**CONTROL\_APPLY ( parameterIR\* )** is a well-formed callable type, with bound type variables **B** when:

1. Check that **parameterIR** is a well-formed parameter type, with bound type variables **B**, for all **parameterIR** in **parameterIR\***.
2. Check that **parameterIR** is not an optional parameter, for all **parameterIR** in **parameterIR\***.
3. Let **typeIR\*** be the list of **typeIR**, obtained by repeating:
  - Let **typeIR** be the type of **parameterIR**.
 for each **parameterIR** in **parameterIR\***
4. Check that **typeIR** can be used in a control apply method type, for all **typeIR** in **typeIR\***.
5. The relation holds.

### 9.5.4. Table apply methods

A **table** can be invoked by calling its **apply** method. Calling an apply method on a table instance returns a synthesized table metadata structure, explained in [Section 8.6.6](#).

A table apply method definition is introduced by a **table** declaration. Its semantics rule is explained in [\[sec-table-declaration\]](#). A table declaration may not be generic. Thus, the table apply method type definition does not have type parameters, and is same as the table apply method type. A table apply method is represented internally as follows:

```

tableApplyMethodTypeDefIR = tableApplyMethodTypeIR

tableApplyMethodTypeIR
  : TABLE_APPLY : tableMetadataStructTypeIR
  ;

```

```

tableApplyMethodDef
: TABLE_APPLY `{ tablePropertyListIR }
;

```

#### 9.5.4.1. Well-formedness

`TABLE_APPLY` : `tableMetadataStructTypeIR` is a well-formed callable type, with bound type variables `B` when:

1. The relation holds.

#### 9.5.5. Built-in methods

Built-in methods are methods associated with certain types defined by the P4 language. Thus, they do not have method type definitions, and only have method types. The internal representations are:

```

builtinMethodTypeIR
: BUILTIN_METHOD nameIR `( parameterIR* ) : typeIR
;

```

## 10. P4 objects and constructors

### 10.1. Objects

`tables`, `value_sets`, and `extern` objects are stateful entities in P4 programs. These objects should be instantiated statically prior to program execution. `parsers`, `controls`, and `packages` may contain stateful objects, thus they must also be instantiated.

The runtime representation of these objects is defined as follows:

```

object
: externObject
| parserObject
| controlObject
| packageObject
| tableObject
| valueSetObject
;

```

The instantiation phase (described in [Section 7.3](#)) creates objects in the source P4 program, and allocates them in the global store. At runtime (described in [Section 7.4](#)), these objects interact, as defined by the target architecture, to process packets.

#### 10.1.1. Fully-qualified names

Instantiation may create multiple instances of a type, each of which must have a unique, fully-qualified name. Thus, objects are identified by their full-qualified names (`objectId`). [Section 7.3.1](#) describes how a fully-qualified name is constructed.

```

objectId = nameIR*

```



## 10.2. Constructors

Objects can be instantiated in three ways:

- Using instantiations, described in [Section 11.4](#).
- Using constructor call expressions, described in [\[sec-constructor-call-expression\]](#).
- Using direct type invocation statements, described in [Section 13.5](#).

Instantiations and constructor call expressions invoke constructors, which creates an object as a result. Direct application statements are syntactic sugar for instantiations of `parser` and `control` objects.

Constructor invocation is similar to callable invocation; constructors can also be overloaded, and called using named arguments.

The following example shows a constructor invocation for setting the target-dependent implementation property of a table:

```
extern ActionProfile {
    ActionProfile(bit<32> size); // constructor
}
table tbl {
    actions = { /* body omitted */ }
    implementation = ActionProfile(1024); // constructor invocation
}
```

### 10.2.1. Constructor parameters

In order to support libraries of useful P4 components, `externs`, `parsers`, `controls`, and `packages` can additionally be parameterized through the use of constructor parameters.

Consider the parser declaration syntax:

```
parserDeclaration
: annotationList PARSE name typeParameterListOpt `( parameterList )
  constructorParameterListOpt
  `{ parserLocalDeclarationList parserStateList }
;

constructorParameterListOpt
: /* empty */
| `( parameterList )
;
```

From this grammar fragment we infer that a `parser` declaration may have two sets of parameters:

- The runtime parser parameters (`parameterList`)
- Optional parser constructor parameters (`constructorParameterListOpt`)

Because constructors are evaluated entirely at compilation time, all constructor arguments must be expressions that can be evaluated at compilation time. In consequence, constructor parameters must be directionless (i.e., they cannot be `in`, `out`, or `inout`).

Consider the following example:

```
parser GenericParser(packet_in b, out Packet_header p)
    (bool udpSupport) { // constructor parameters
```

```

state start {
  b.extract(p.ethernet);
  transition select(p.ethernet.etherType) {
    16w0x0800: ipv4;
  }
}
state ipv4 {
  b.extract(p.ipv4);
  transition select(p.ipv4.protocol) {
    6: tcp;
    17: tryudp;
  }
}
state tryudp {
  transition select(udpSupport) {
    false: accept;
    true : udp;
  }
}
state udp {
  // body omitted
}
}

```

When instantiating the `GenericParser` it is necessary to supply a value for the `udpSupport` parameter, as in the following example:

```

// topParser is a GenericParser where udpSupport = false
GenericParser(false) topParser;

```

Internally, constructor parameters are represented as:

```

constructorParameterIR = parameterIR

parameterIR
: annotationList direction typeIR id parameterInitializerOptIR
;

```

### 10.2.1.1. Well-formedness

**ConstructorParameterType\_wf:**

- `constructorParameterIR` is a well-formed constructor parameter type, with bound type variables `B`

`constructorParameterIR` is a well-formed constructor parameter type, with bound type variables `B` when:

1. Let `direction` be the direction of `constructorParameterIR`.
2. Check that `direction` is ``EMPTY`.
3. Check that `constructorParameterIR` is a well-formed parameter type, with bound type variables `B`.
4. The relation holds.

## 10.2.2. Constructor definitions

Similar to how type declarations introduce type definitions and callable declarations introduce callable definitions (see [Section 9.2](#)), constructor declarations introduce constructor definitions. These are parameterized by type parameters, and produces a constructor type when specialized with specific type arguments.

The runtime representation of constructors is defined as follows:

```
constructorDef
: externObjectConstructorDef
| parserObjectConstructorDef
| controlObjectConstructorDef
| packageObjectConstructorDef
;
```

When type arguments and constructor arguments are supplied to a constructor definition, an object of the constructed type is created.

Similar to how callable types are internally used during type checking to represent callables, constructor types internally represent the types of constructors.

```
constructorTypeIR
: CONSTRUCTOR `( constructorParameterIR* ) : typeIR
;

constructorTypeDefIR
: CONSTRUCTOR `< typeParameterIR* , typeParameterIR* >
  `( constructorParameterIR* ) : typeIR
;
```

### 10.2.2.1. Well-formedness

[ConstructorTypeDef\\_wf](#):

- $\text{CONSTRUCTOR} < \text{typeParameterIR}_{\text{expl}}^* , \text{typeParameterIR}_{\text{impl}}^* > ( \text{parameterIR}^* ) : \text{typeIR}_{\text{object}}$  is a well-formed constructor type definition, with bound type variables  $B$

$\text{CONSTRUCTOR} < \text{typeParameterIR}_{\text{expl}}^* , \text{typeParameterIR}_{\text{impl}}^* > ( \text{parameterIR}^* ) : \text{typeIR}_{\text{object}}$  is a well-formed constructor type definition, with bound type variables  $B$  when:

1. Check that  $\text{typeIR}_{\text{object}}$  can be constructed.
2. Let  $\text{typeParameterIR}^*$  be  $\text{typeParameterIR}_{\text{expl}}^*$  concatenated with  $\text{typeParameterIR}_{\text{impl}}^*$ .
3. Check that the elements of  $\text{typeParameterIR}^*$  are distinct.
4. Let  $B_{\text{inner}}$  be the union of the sets  $B$  and  $\{ \text{typeParameterIR}^* \}$ .
5. Check that  $\text{CONSTRUCTOR} ( \text{parameterIR}^* ) : \text{typeIR}_{\text{object}}$  is a well-formed constructor type, with bound type variables  $B_{\text{inner}}$ .
6. The relation holds.

## 10.3. Extern objects

An **extern** object declaration introduces an extern object type and its associated methods. Extern object declarations can also optionally declare constructor methods; these must have the same name as the enclosing **extern** type, no type parameters, and no return type.

```
externConstructorPrototype
  : annotationList typeIdIdentifier `( parameterList ) ;
  ;

externMethodPrototype
  : annotationList functionPrototype ;
  | annotationList ABSTRACT functionPrototype ;
  ;

externObjectDeclaration
  : annotationList EXTERN nonTypeName typeParameterListOpt
    `{ externConstructorOrMethodPrototypeList }
  ;
```

Internally, an extern object constructor is represented as:

```
externObjectConstructorDef
  : EXTERN nameIR `< typeParameterListIR > `( constructorParameterListIR )
    `{ externMethodPrototypeListIR }
  ;

externMethodPrototypeIR
  : annotationList functionPrototypeIR ;
  | annotationList ABSTRACT functionPrototypeIR ;
  ;
```

Extern objects are then instantiated by constructor invocations to yield:

```
externObject
  : EXTERN typeId `< theta > `{ objectState frame externMethodDefEnv }
  ;
```

The only operation on **extern** objects is invoking a method of an extern object instance using a method call expression.

Controls, parsers, packages, and extern constructors can have parameters of type **extern** only if they are directionless parameters. Extern object instances can thus be used as arguments in the construction of such objects.

No other operations are available on extern objects, e.g., equality comparison is not defined.

### 10.3.1. Well-formedness

**CONSTRUCTOR ( parameterIR<sup>\*</sup> ) : typeIR<sub>object</sub>** is a well-formed constructor type, with bound type variables **B** when:

1. Check that **parameterIR** is a well-formed constructor parameter type, with bound type variables **B**, for all **parameterIR** in **parameterIR<sup>\*</sup>**.
2. Check that **typeIR<sub>object</sub>** is a well-formed type, with bound type variables **B**.
3. Let **typeIR** be **typeIR<sub>object</sub>** with typedefs unrolled.
4. Check that **typeIR** has type **externObjectTypeIR**.

5. Let  $\text{externObjectTypeIR}$  be  $\text{typeIR}$ .
6. Let  $\text{typeIR}^*$  be the list of  $\text{typeIR}'$ , obtained by repeating:
  - Let  $\text{typeIR}'$  be the type of  $\text{parameterIR}$ .
 for each  $\text{parameterIR}$  in  $\text{parameterIR}^*$
7. Check that  $\text{typeIR}'$  can be used in an extern constructor type, for all  $\text{typeIR}'$  in  $\text{typeIR}^*$ .
8. The relation holds.

### 10.3.2. Instantiation

Loading  $\text{externObjectConstructorDef} < \text{typeArgumentIR}^* > ( \text{argumentIR}^* )$  with defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$ , under cursor  $p$ , context  $IC$ , and store  $STO_0$ :

1. Let  $\text{EXTERN nameIR} < \text{typeParameterIR}^* > ( \text{constructorParameterIR}^* ) \{ \text{externMethodPrototypeIR}^* \}$  be  $\text{externObjectConstructorDef}$ .
2. Let  $p_{\text{callee}}$  be BLOCK.
3. Let  $IC_{\text{callee}_0}$  be an instantiation context same as  $IC$  up to the GLOBAL layer.
4. Let  $\theta$  be  $\{ ( \text{typeParameterIR} : \text{typeArgumentIR} )^* \}$ .
5. Let  $IC_{\text{callee}_1}$  be  $IC_{\text{callee}_0}$  with BLOCK.TYPE set to  $\theta$ .
6. Let GIVEN  $\text{constructorParameterIR}_{\text{aligned}}^*$  DEFAULT  $\text{constructorParameterIR}_{\text{default}}^*$  be aligning  $\text{constructorParameterIR}^*$  with  $\text{argumentIR}^*$  where defaults are  $\text{id}_{\text{default}}^*$  and optionals are  $\text{id}_{\text{optional}}^*$ .
7. Let  $\text{id}_{\text{aligned}}^*$  be the list of  $\text{id}_{\text{aligned}}$ , obtained by repeating:
  - Let  $\text{id}_{\text{aligned}}$  be the name of  $\text{constructorParameterIR}_{\text{aligned}}$ .
 for each  $\text{constructorParameterIR}_{\text{aligned}}$  in  $\text{constructorParameterIR}_{\text{aligned}}^*$
8. Let store  $STO_1$  and context  $IC_{\text{callee}_2}$  be
  - the result of copy-in from  $p$  layer of  $IC$  with  $\text{argumentIR}^*$  to  $p_{\text{callee}}$  layer of  $IC_{\text{callee}_1}$  with  $\text{id}_{\text{aligned}}^*$ , under store  $STO_0$ .
9. Let store  $STO_2$  and context  $IC_{\text{callee}_3}$  be
  - the result of copy-in defaults  $\text{constructorParameterIR}_{\text{default}}^*$  from  $p$  layer of  $IC$  to  $p_{\text{callee}}$  layer of  $IC_{\text{callee}_2}$ , under store  $STO_0$ .
10. Let context  $IC_{\text{callee}_4}$  be
  - the result of compile-time evaluation of  $\text{externMethodPrototypeIR}^*$ , under context  $IC_{\text{callee}_3}$ .
11. Let  $\{ ( \text{callableId} : \text{callableDef} )^* \}$  be  $IC_{\text{callee}_4}.\text{BLOCK.CALLABLE}$ .
12. Check that  $\text{callableDef}$  has type  $\text{externMethodDef}$ , for all  $\text{callableDef}$  in  $\text{callableDef}^*$ .
13. Let  $\text{externMethodDef}^*$  be the list of  $\text{externMethodDef}$ , obtained by repeating:
  - Let  $\text{externMethodDef}$  be  $\text{callableDef}$ .
 for each  $\text{callableDef}$  in  $\text{callableDef}^*$
14. Let  $\text{id}_{\text{cparam}}^*$  be the list of  $\text{id}_{\text{cparam}}$ , obtained by repeating:

- Let  $id_{cparam}$  be the name of `constructorParameterIR`.
- for each `constructorParameterIR` in `constructorParameterIR`\*
15. Let  $value^{?*$  be the list of  $value^?$ , obtained by repeating:
    - Let  $value^?$  be  $id_{cparam}$  in map `ICcallee_4.BLOCK.FRAME`.

for each  $id_{cparam}$  in  $id_{cparam}$ \*
  16. Check that  $value^?$  is defined, for all  $value^?$  in  $value^{?*$ .
  17. Let  $value_{cparam}^*$  be the list of  $value_{cparam}$ , obtained by repeating:
    - Let  $value_{cparam}$  be  $value^?$ .

for each  $value^?$  in  $value^{?*$
  18. Let `objectState` be `$init_objectState(nameIR, typeArgumentIR*, valuecparam*)`.
  19. Let `objectextern` be `EXTERN nameIR < ICcallee_4.BLOCK.TYPE > { objectState ICcallee_4.BLOCK.FRAME { ( callableId : externMethodDef ) } }`.
  20. Result in store `STO2` and constructed `objectextern`.

## 10.4. Parser objects

A parser declaration comprises a name, a list of parameters, an optional list of constructor parameters, local elements, and parser states (as well as optional annotations).

```

parserDeclaration
  : annotationList PARSE name typeParameterListOpt `( parameterList )
    constructorParameterListOpt
    `{ parserLocalDeclarationList parserStateList }
  ;

parserLocalDeclaration
  : constantDeclaration
  | instantiation
  | variableDeclaration
  | valueSetDeclaration
  ;

parserState
  : annotationList STATE name `{ parserStatementList transitionStatement }
  ;

```

At least one state, named `start`, must be present in any `parser`. A parser may not define two states with the same name. It is also illegal for a parser to give explicit definitions for the `accept` and `reject` states—those states are logically distinct from the states defined by the programmer.

Preceding the parser states, a `parser` may also contain a list of local elements. These can be constants, variables, or instantiations of objects that may be used within the parser. Such objects may be instantiations of `extern` objects, or other `parsers` that may be invoked as subroutines. However, it is illegal to instantiate a `control` block within a `parser`.

The states and local elements are all in the same namespace, thus the following example will produce an error:

```
// erroneous example
parser p() {
  bit<4> t;
  state start {
    t = 1;
    transition t;
  }
  state t { // error: name t is duplicated
    transition accept;
  }
}
```

For an example containing a complete declaration of a parser see [Section 5.3](#).

A **parser** declaration introduces a parser object constructor, represented as:

```
parserObjectConstructorDef
: PARSE < typeParameterListIR > `( parameterListIR )
  `( constructorParameterListIR )
  `{ parserLocalDeclarationListIR parserStateListIR }
;
```

Parser objects are then instantiated by constructor invocations to yield:

```
parserObject
: PARSE < theta > `( parameterListIR )
  `{ frame parserLocalDeclarationListIR stateEnv }
;
```

### 10.4.1. Well-formedness

**CONSTRUCTOR ( parameterIR\* ) : typeIR<sub>object</sub>** is a well-formed constructor type, with bound type variables **B** when:

1. Check that **parameterIR** is a well-formed constructor parameter type, with bound type variables **B**, for all **parameterIR** in **parameterIR\***.
2. Check that **parameterIR** is not an optional parameter, for all **parameterIR** in **parameterIR\***.
3. Check that **typeIR<sub>object</sub>** is a well-formed type, with bound type variables **B**.
4. Let **typeIR** be **typeIR<sub>object</sub>** with typedefs unrolled.
5. Check that **typeIR** has type **parserObjectTypeIR**.
6. Let **parserObjectTypeIR** be **typeIR**.
7. Let **typeIR\*** be the list of **typeIR'**, obtained by repeating:
  - Let **typeIR'** be the type of **parameterIR**.
 for each **parameterIR** in **parameterIR\***
8. Check that **typeIR'** can be used in a parser constructor type, for all **typeIR'** in **typeIR\***.
9. The relation holds.

### 10.4.2. Instantiation

Loading  $\text{parserObjectConstructorDef} < \text{typeArgumentIR}^* > ( \text{argumentIR}^* )$  with defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$ , under cursor  $p$ , context  $IC$ , and store  $STO_0$ :

1. Let  $\text{PARSER} < \text{typeParameterIR}^* > ( \text{parameterIR}^* ) ( \text{constructorParameterIR}^* ) \{ \text{parserLocalDeclarationIR}^* \text{ parserStateIR}^* \}$  be  $\text{parserObjectConstructorDef}$ .
2. Let  $p_{\text{callee}}$  be BLOCK.
3. Let  $IC_{\text{callee}_0}$  be an instantiation context same as  $IC$  up to the GLOBAL layer.
4. Let  $\theta$  be  $\{ ( \text{typeParameterIR} : \text{typeArgumentIR} )^* \}$ .
5. Let  $IC_{\text{callee}_1}$  be  $IC_{\text{callee}_0}$  with BLOCK.TYPE set to  $\theta$ .
6. Let  $\text{GIVEN} \text{ constructorParameterIR}_{\text{aligned}}^* \text{ DEFAULT } \text{constructorParameterIR}_{\text{default}}^* \text{ be aligning constructorParameterIR}^* \text{ with argumentIR}^* \text{ where defaults are } \text{id}_{\text{default}}^* \text{ and optionals are } \text{id}_{\text{optional}}^*.$
7. Let  $\text{id}_{\text{aligned}}^*$  be the list of  $\text{id}_{\text{aligned}}$ , obtained by repeating:
  - Let  $\text{id}_{\text{aligned}}$  be the name of  $\text{constructorParameterIR}_{\text{aligned}}$ .
 for each  $\text{constructorParameterIR}_{\text{aligned}}$  in  $\text{constructorParameterIR}_{\text{aligned}}^*$
8. Let store  $STO_1$  and context  $IC_{\text{callee}_2}$  be
  - the result of copy-in from  $p$  layer of  $IC$  with  $\text{argumentIR}^*$  to  $p_{\text{callee}}$  layer of  $IC_{\text{callee}_1}$  with  $\text{id}_{\text{aligned}}^*$ , under store  $STO_0$ .
9. Let store  $STO_2$  and context  $IC_{\text{callee}_3}$  be
  - the result of copy-in defaults  $\text{constructorParameterIR}_{\text{default}}^*$  from  $p$  layer of  $IC$  to  $p_{\text{callee}}$  layer of  $IC_{\text{callee}_2}$ , under store  $STO_0$ .
10. Let context  $IC_{\text{local}}$ , store  $STO_3$ , and  $\text{parserLocalDeclarationIR}_{\text{inst}}^*$  be
  - the result of compile-time evaluation of  $\text{parserLocalDeclarationIR}^*$ , under context  $IC_{\text{callee}_3}$  and store  $STO_2$ .
11. Let context  $IC_{\text{state}}$  and store  $STO_4$  be
  - the result of compile-time evaluation of  $\text{parserStateIR}^*$ , under context  $IC_{\text{local}}$  and store  $STO_3$ .
12. Let  $\text{object}_{\text{parser}}$  be  $\text{PARSER} < \theta > ( \text{parameterIR}^* ) \{ IC_{\text{callee}_3} \cdot \text{BLOCK} \cdot \text{FRAME } \text{parserLocalDeclarationIR}_{\text{inst}}^* \text{ } IC_{\text{state}} \cdot \text{BLOCK} \cdot \text{STATE} \}.$
13. Result in store  $STO_4$  and constructed  $\text{object}_{\text{parser}}$ .

## 10.5. Control objects

P4 parsers are responsible for extracting bits from a packet into headers. These headers (and other metadata) can be manipulated and transformed within control blocks. The body of a control block resembles a traditional imperative program. Within the body of a control block, match-action units can be invoked to perform data transformations. Match-action units are represented in P4 by constructs called tables.

Syntactically, a control block is declared with a name, parameters, optional type parameters, and a sequence of declarations of constants, variables, actions, tables, and other instantiations:

```
controlDeclaration
: annotationList CONTROL name typeParameterListOpt `( parameterList )
  constructorParameterListOpt
  `{ controlLocalDeclarationList APPLY controlBody }
```



```

;
controlLocalDeclaration
: constantDeclaration
| instantiation
| variableDeclaration
| actionDeclaration
| tableDeclaration
;

controlBody = blockStatement

```

It is illegal to instantiate a **parser** within a **control** block.

P4 does not support exceptional control-flow within a **control** block. The only statement which has a non-local effect on control flow is **exit**, which causes execution of the enclosing control block to immediately terminate. That is, there is no equivalent of the **verify** statement or the **reject** state from parsers. Hence, all error handling must be performed explicitly by the programmer.

A **control** declaration introduces a control object constructor, represented as:

```

controlObjectConstructorDef
: CONTROL `< typeParameterListIR > `( parameterListIR )
  `( constructorParameterListIR )
  `{ controlLocalDeclarationListIR APPLY controlBodyIR }
;

```

Control objects are then instantiated by constructor invocations to yield:

```

controlObject
: CONTROL `< theta > `( parameterListIR )
  `{ frame controlLocalDeclarationListIR actionDefEnv controlBodyIR }
;

```

### 10.5.1. Well-formedness

**CONSTRUCTOR ( parameterIR\* ) : typeIR<sub>object</sub>** is a well-formed constructor type, with bound type variables **B** when:

1. Check that **parameterIR** is a well-formed constructor parameter type, with bound type variables **B**, for all **parameterIR** in **parameterIR\***.
2. Check that **parameterIR** is not an optional parameter, for all **parameterIR** in **parameterIR\***.
3. Check that **typeIR<sub>object</sub>** is a well-formed type, with bound type variables **B**.
4. Let **typeIR** be **typeIR<sub>object</sub>** with **typedefs** unrolled.
5. Check that **typeIR** has type **controlObjectTypeIR**.
6. Let **controlObjectTypeIR** be **typeIR**.
7. Let **typeIR\*** be the list of **typeIR'**, obtained by repeating:
  - Let **typeIR'** be the type of **parameterIR**.
 for each **parameterIR** in **parameterIR\***
8. Check that **typeIR'** can be used in a control constructor type, for all **typeIR'** in **typeIR\***.

9. The relation holds.

## 10.5.2. Instantiation

Loading  $\text{controlObjectConstructorDef} < \text{typeArgumentIR}^* > ( \text{argumentIR}^* )$  with defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$ , under cursor  $p$ , context  $IC$ , and store  $\text{STO}_0$ :

1. Let  $\text{CONTROL} < \text{typeParameterIR}^* > ( \text{parameterIR}^* ) ( \text{constructorParameterIR}^* ) \{ \text{controlLocalDeclarationIR}^* \text{ APPLY } \text{controlBodyIR} \}$  be  $\text{controlObjectConstructorDef}$ .
2. Let  $p_{\text{callee}}$  be  $\text{BLOCK}$ .
3. Let  $IC_{\text{callee}_0}$  be an instantiation context same as  $IC$  up to the GLOBAL layer.
4. Let  $\theta$  be  $\{ ( \text{typeParameterIR} : \text{typeArgumentIR} )^* \}$ .
5. Let  $IC_{\text{callee}_1}$  be  $IC_{\text{callee}_0}$  with  $\text{BLOCK.TYPE}$  set to  $\theta$ .
6. Let  $\text{GIVEN } \text{constructorParameterIR}_{\text{aligned}}^* \text{ DEFAULT } \text{constructorParameterIR}_{\text{default}}^* \text{ be aligning } \text{constructorParameterIR}^* \text{ with } \text{argumentIR}^* \text{ where defaults are } \text{id}_{\text{default}}^* \text{ and optionals are } \text{id}_{\text{optional}}^* .$
7. Let  $\text{id}_{\text{aligned}}^*$  be the list of  $\text{id}_{\text{aligned}}$ , obtained by repeating:
  - Let  $\text{id}_{\text{aligned}}$  be the name of  $\text{constructorParameterIR}_{\text{aligned}}$ .for each  $\text{constructorParameterIR}_{\text{aligned}}$  in  $\text{constructorParameterIR}_{\text{aligned}}^*$
8. Let store  $\text{STO}_1$  and context  $IC_{\text{callee}_2}$  be
  - the result of copy-in from  $p$  layer of  $IC$  with  $\text{argumentIR}^*$  to  $p_{\text{callee}}$  layer of  $IC_{\text{callee}_1}$  with  $\text{id}_{\text{aligned}}^*$ , under store  $\text{STO}_0$ .
9. Let store  $\text{STO}_2$  and context  $IC_{\text{callee}_3}$  be
  - the result of copy-in defaults  $\text{constructorParameterIR}_{\text{default}}^*$  from  $p$  layer of  $IC$  to  $p_{\text{callee}}$  layer of  $IC_{\text{callee}_2}$ , under store  $\text{STO}_0$ .
10. Let context  $IC_{\text{local}_0}$ , store  $\text{STO}_3$ , and  $\text{controlLocalDeclarationIR}^*$  be
  - the result of compile-time evaluation of  $\text{controlLocalDeclarationIR}^*$ , under context  $IC_{\text{callee}_3}$  and store  $\text{STO}_2$ .
11. Let context  $IC_{\text{local}_1}$ , store  $\text{STO}_4$ , and  $\text{controlBodyIR}'$  be
  - the result of compile-time evaluation of  $\text{controlBodyIR}$ , under context  $IC_{\text{local}_0}$ , and store  $\text{STO}_3$ .
12. Let  $\{ ( \text{callableId} : \text{callableDef} )^* \}$  be  $IC_{\text{local}_1}.\text{BLOCK.CALLABLE}$ .
13. Check that  $\text{callableDef}$  has type  $\text{actionDef}$ , for all  $\text{callableDef}$  in  $\text{callableDef}^*$ .
14. Let  $\text{actionDef}^*$  be the list of  $\text{actionDef}$ , obtained by repeating:
  - Let  $\text{actionDef}$  be  $\text{callableDef}$ .for each  $\text{callableDef}$  in  $\text{callableDef}^*$
15. Let  $\text{object}_{\text{control}}$  be  $\text{CONTROL} < \theta > ( \text{parameterIR}^* ) \{ IC_{\text{callee}_3}.\text{BLOCK.FRAME } \text{controlLocalDeclarationIR}^* \{ ( \text{callableId} : \text{actionDef} )^* \} \text{controlBodyIR}' \}$ .
16. Result in store  $\text{STO}_4$  and constructed  $\text{object}_{\text{control}}$ .

## 10.6. Table objects




Figure 11. Match-Action Unit Dataflow.

A **table** describes a match-action unit. The structure of a match-action unit is shown in Figure 11. Processing a packet using a match-action table executes the following steps:

- Key construction.
- Key lookup in a lookup table (the "match" step). The result of key lookup is an "action".
- Action execution (the "action step") over the input data, resulting in mutations of the data.

A **table** declaration introduces a table instance. To obtain multiple instances of a table, it must be declared within a control block that is itself instantiated multiple times.

The look-up table is a finite map whose contents are manipulated asynchronously (read/write) by the target control plane, through a separate control-plane API (see Figure 11). Note that the term "table" is overloaded: it can refer to the P4 **table** objects that appear in P4 programs, as well as the internal look-up tables used in targets. We will use the term "match-action unit" when necessary to disambiguate.

Syntactically, a table is defined in terms of a set of key-value properties. Some of these properties are "standard" properties, but the set of properties can be extended by target-specific compilers as needed. Note that duplicated properties are invalid and the compiler should reject them.

```
tableDeclaration
: annotationList TABLE name `{ tablePropertyList }
;

tablePropertyList
: /* empty */
| tablePropertyList tableProperty
;

tableProperty
: KEY = `{ tableKeyList }
| ACTIONS = `{ tableActionList }
| annotationList constOpt ENTRIES = `{ tableEntryList }
| annotationList constOpt tableCustomName initializer ;
;
```

See [Section 16.3](#) for details on the table properties.

A **table** declaration creates a table object, thus table constructors are not defined in  $P4_{IR}$ . Table objects are defined as:

```
tableObject
: TABLE typeId `{ frame tableObjectProperty }
;

tablePropertyIR
: tableKeysPropertyIR
| tableActionsPropertyIR
| tableDefaultActionPropertyIR
| tableEntriesPropertyIR
| tableCustomPropertyIR
;

tableObjectProperty = {
  KEYS tableKeysPropertyIR,
  ACTIONS tableActionsPropertyIR,
  DEFAULT_ACTION tableDefaultActionPropertyIR,
  ENTRIES tableEntriesPropertyIR,
  CUSTOMS tableCustomPropertyIR*
}
```

### 10.6.1. Well-formedness

**CONSTRUCTOR ( · ) : typeIR<sub>object</sub>** is a well-formed constructor type, with bound type variables **B** when:

1. Check that **typeIR<sub>object</sub>** is a well-formed type, with bound type variables **B**.
2. Let **typeIR** be **typeIR<sub>object</sub>** with typedefs unrolled.
3. Check that **typeIR** has type **tableObjectTypeIR**.
4. Let **tableObjectTypeIR** be **typeIR**.
5. The relation holds.

## 10.7. Parser value set objects

In some cases, the values that determine the transition from one parser state to another need to be determined at runtime. MPLS is one example where the value of the MPLS label field is used to determine what headers follow the MPLS tag and this mapping may change dynamically at runtime. To support this functionality, P4 supports the notion of a Parser Value Set. This is a named set of values with a runtime API to add and remove values from the set.

Value sets are declared locally within a parser. They should be declared before being referenced in parser **keysetExpression** and can be used as a label in a select expression.

The syntax for declaring value sets is:

```
valueSetDeclaration
: annotationList VALUE_SET `< valueSetType > `( expression ) name ;
;

valueSetType
: baseType
| tupleType
```

```
| prefixedTypeName  
;
```

Parser Value Sets support a **size** argument to provide hints to the compiler to reserve hardware resources to implement the value set. Thus, the **size** argument must be a compile-time known value. For example, this parser value set:

```
value_set<bit<16>>(4) pvs;
```

creates a `value_set` of size 4 with entries of type `bit<16>`.

The semantics of the **size** argument is similar to the **size** property of a table. If a value set has a **size** argument with value **N**, it is recommended that a compiler should choose a data plane implementation that is capable of storing **N** value set entries. See "Size property of P4 tables and parser value sets" <sup>[1]</sup> for further discussion on the implementation of parser value set size.

The value set is populated by the control plane by methods specified in the P4Runtime specification. <sup>[2]</sup>

Similar to **tables**, a **value\_set** declaration creates a new parser value set object. Thus, no constructor is defined for them. The object is represented as:

```
valueSetObject  
: VALUE_SET `{ value* `( nat ) }  
;
```

## 10.8. Package objects

A package type declaration introduces a package object constructor.

```
packageTypeDeclaration  
: annotationList PACKAGE name typeParameterListOpt `( parameterList ) ;  
;
```

All parameters of a package are evaluated at compilation time, and in consequence they must all be directionless (they cannot be **in**, **out**, or **inout**). Otherwise package types are very similar to parser type declarations. Packages can only be instantiated; there are no runtime behaviors associated with them.

Package object constructors are defined as follows:

```
packageObjectConstructorDef  
: PACKAGE `< typeParameterListIR > `( constructorParameterListIR )  
;
```

Package objects are then instantiated to yield:

```
packageObject  
: PACKAGE `< theta > `{ frame }  
;
```

### 10.8.1. Well-formedness

$\text{CONSTRUCTOR} ( \text{parameterIR}^* ) : \text{typeIR}_{\text{object}}$  is a well-formed constructor type, with bound type variables  $B$  when:

1. Check that  $\text{parameterIR}$  is a well-formed constructor parameter type, with bound type variables  $B$ , for all  $\text{parameterIR}$  in  $\text{parameterIR}^*$ .
2. Check that  $\text{typeIR}_{\text{object}}$  is a well-formed type, with bound type variables  $B$ .
3. Let  $\text{typeIR}$  be  $\text{typeIR}_{\text{object}}$  with typedefs unrolled.
4. Check that  $\text{typeIR}$  has type  $\text{packageObjectTypeIR}$ .
5. Let  $\text{packageObjectTypeIR}$  be  $\text{typeIR}$ .
6. Let  $\text{typeIR}^*$  be the list of  $\text{typeIR}'$ , obtained by repeating:
  - Let  $\text{typeIR}'$  be the type of  $\text{parameterIR}$ .
for each  $\text{parameterIR}$  in  $\text{parameterIR}^*$
7. Check that  $\text{typeIR}'$  can be used in a package constructor type, for all  $\text{typeIR}'$  in  $\text{typeIR}^*$ .
8. The relation holds.

### 10.8.2. Instantiation

Loading  $\text{packageObjectConstructorDef} < \text{typeArgumentIR}^* > ( \text{argumentIR}^* )$  with defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$ , under cursor  $p$ , context  $IC$ , and store  $\text{STO}_0$ :

1. Let  $\text{PACKAGE} < \text{typeParameterIR}^* > ( \text{constructorParameterIR}^* )$  be  $\text{packageObjectConstructorDef}$ .
2. Let  $p_{\text{callee}}$  be  $\text{BLOCK}$ .
3. Let  $IC_{\text{callee}_0}$  be an instantiation context same as  $IC$  up to the GLOBAL layer.
4. Let  $IC_{\text{callee}_1}$  be  $IC_{\text{callee}_0}$  with  $\text{BLOCK.TYPE}$  set to  $\{ ( \text{typeParameterIR} : \text{typeArgumentIR} )^* \}$ .
5. Let  $\text{GIVEN}$   $\text{constructorParameterIR}_{\text{aligned}}^*$   $\text{DEFAULT}$   $\text{constructorParameterIR}_{\text{default}}^*$  be aligning  $\text{constructorParameterIR}^*$  with  $\text{argumentIR}^*$  where defaults are  $\text{id}_{\text{default}}^*$  and optionals are  $\text{id}_{\text{optional}}^*$ .
6. Let  $\text{id}_{\text{aligned}}^*$  be the list of  $\text{id}_{\text{aligned}}$ , obtained by repeating:
  - Let  $\text{id}_{\text{aligned}}$  be the name of  $\text{constructorParameterIR}_{\text{aligned}}$ .
for each  $\text{constructorParameterIR}_{\text{aligned}}$  in  $\text{constructorParameterIR}_{\text{aligned}}^*$
7. Let store  $\text{STO}_1$  and context  $IC_{\text{callee}_2}$  be
  - the result of copy-in from  $p$  layer of  $IC$  with  $\text{argumentIR}^*$  to  $p_{\text{callee}}$  layer of  $IC_{\text{callee}_1}$  with  $\text{id}_{\text{aligned}}^*$ , under store  $\text{STO}_0$ .
8. Let store  $\text{STO}_2$  and context  $IC_{\text{callee}_3}$  be
  - the result of copy-in defaults  $\text{constructorParameterIR}_{\text{default}}^*$  from  $p$  layer of  $IC$  to  $p_{\text{callee}}$  layer of  $IC_{\text{callee}_2}$ , under store  $\text{STO}_1$ .
9. Let  $\text{object}_{\text{package}}$  be  $\text{PACKAGE} < IC_{\text{callee}_3}.\text{BLOCK.TYPE} > \{ IC_{\text{callee}_3}.\text{BLOCK.FRAME} \}$ .
10. Result in store  $\text{STO}_2$  and constructed  $\text{object}_{\text{package}}$ .

[1] <https://github.com/p4lang/p4-spec/blob/master/p4-16/spec/docs/p4-table-and-parser-value-set-sizes.md>

[2] The P4Runtime API is defined as a Google Protocol Buffer `.proto` file and an accompanying English specification document here: <https://github.com/p4lang/p4runtime>

# 11. Declarations

The syntax of top-level declarations is defined as follows:

```
declaration
: constantDeclaration
| instantiation
| functionDeclaration
| actionDeclaration
| errorDeclaration
| matchKindDeclaration
| externDeclaration
| parserDeclaration
| controlDeclaration
| typeDeclaration
;

externDeclaration
: externFunctionDeclaration
| externObjectDeclaration
;

typeDeclaration
: derivedTypeDeclaration
| typedefDeclaration
| parserTypeDeclaration
| controlTypeDeclaration
| packageTypeDeclaration
;
```

As described in [Chapter 7](#), declarations are type checked, instantiated at compile time, and evaluated at runtime.

## 11.1. Semantics of declarations

### 11.1.1. Type checking

**Decl\_ok:**

- Typing **declaration** under context **typingContext**:
- Result in context **typingContext** and **declarationIR**.

After type checking, declarations are represented in  $P4_{IR}$  as follows:

```
declarationIR
: constantDeclarationIR
| instantiationIR
| functionDeclarationIR
| actionDeclarationIR
| errorDeclarationIR
| matchKindDeclarationIR
| externDeclarationIR
| parserDeclarationIR
| controlDeclarationIR
| typeDeclarationIR
;
```



```

externDeclarationIR
: externFunctionDeclarationIR
| externObjectDeclarationIR
;

typeDeclarationIR
: derivedTypeDeclarationIR
| typedefDeclarationIR
| parserTypeDeclarationIR
| controlTypeDeclarationIR
| packageTypeDeclarationIR
;

```

A list of declarations is type checked as follows:

**Decls\_ok:**

- Typing **declaration\*** under context **typingContext**:
- Result in context **typingContext** and **declarationIR\***.

**Typing declaration\* under context typingContext:**

1. If **declaration\*** is equal to **:**
  - a. Result in context **typingContext** and **.**
2. If let **declaration<sub>h</sub> :: declaration<sub>t</sub>\* be declaration\***:
  - a. Let context **TC<sub>1</sub>** and **declarationIR<sub>h</sub>** be
    - the result of **typing declaration<sub>h</sub> under context typingContext**.
  - b. Let context **TC<sub>2</sub>** and **declarationIR<sub>t</sub>\* be**
    - the result of **typing declaration<sub>t</sub>\* under context TC<sub>1</sub>**.
  - c. Result in context **TC<sub>2</sub>** and **declarationIR<sub>h</sub> :: declarationIR<sub>t</sub>\***.

### 11.1.2. Compile-time evaluation

**Decl\_inst:**

- Loading **declarationIR**, under context **instContext**, and store **store**:
- Result in context **instContext** and store **store**.

Instantiation statically allocates instantiated objects in the global **store**. [Section 11.4](#) describes how objects are instantiated from a declaration.

A list of declarations is instantiated as follows:

**Decls\_inst:**

- Loading **declarationIR\***, under context **instContext**, and store **store**:
- Result in context **instContext** and store **store**.

Loading  $\text{declarationIR}^*$ , under context  $\text{instContext}$ , and store  $\text{store}$ :

1. If  $\text{declarationIR}^*$  is equal to  $\cdot$ :
  - a. Result in context  $\text{instContext}$  and store  $\text{store}$ .
2. If let  $\text{declarationIR}_h :: \text{declarationIR}_t^*$  be  $\text{declarationIR}^*$ :
  - a. Let context  $\text{IC}_1$  and store  $\text{STO}_1$  be
    - the result of loading  $\text{declarationIR}_h$ , under context  $\text{instContext}$ , and store  $\text{store}$ .
  - b. Let context  $\text{IC}_2$  and store  $\text{STO}_2$  be
    - the result of loading  $\text{declarationIR}_t^*$ , under context  $\text{IC}_1$ , and store  $\text{STO}_1$ .
  - c. Result in context  $\text{IC}_2$  and store  $\text{STO}_2$ .

### 11.1.3. Runtime evaluation

All declarations except constant and variable declarations are evaluated at compile-time. See [Section 11.2](#) for the runtime evaluation of variable declarations and [Section 11.3](#) for the runtime evaluation of constant declarations.

The subsequent sections describe each kind of declaration in detail.

## 11.2. Variable declarations

Local variables are declared with a type, a name, and an optional initializer (as well as an optional annotation):

```
variableDeclaration
  : annotationList type name initializerOpt ;
  ;

initializerOpt
  : /* empty */
  | initializer
  ;

initializer
  : = expression
  ;
```

Variable declarations without an initializer are uninitialized (except for headers and other header-related types, which are initialized to invalid in the same way as described for direction `out` parameters in [Section 18.4](#)). The language places few restrictions on the types of variables: most P4 types that can be written explicitly can be used (e.g., base types, `struct`, `header`, header stack, `tuple`). However, it is impossible to declare variables with type `int`, or with types that are only synthesized by the compiler (e.g., `set`). In addition, variables of type `parser`, `control`, `package`, or `extern` types must be declared using instantiations (see [Section 11.4](#)).

Reading the value of a variable that has not been initialized yields an undefined result. The compiler should attempt to detect and emit a warning in such situations.

Variable declarations can appear in the following locations within a P4 program:

- In a block statement,

- In a **parser** state,
- In a **control** block's **apply** sub-block,
- In the list of local declarations in a **parser**, and
- In the list of local declarations in a **control**.

Note that variable declarations *cannot* appear at the top level of a P4 program.

Variables have local scope, and behave like stack-allocated variables in languages such as C. The value of a variable is never preserved from one invocation of its enclosing block to the next. In particular, variables cannot be used to maintain state between different network packets.

### 11.2.1. Type checking

Variable declarations are type checked using the following relation:

**VarDecl\_ok:**

- Typing **variableDeclaration**, under cursor **cursor** and context **typingContext**:
- Result in context **typingContext** and **variableDeclarationIR**.

After typing, variable declarations are represented in P4<sub>IR</sub> as:

```
variableDeclarationIR
  : annotationList typeIR nameIR initializerOptIR ;
  ;

initializerIR
  : = typedExpressionIR
  ;
```

These are produced by the following rules:

**Typing** **annotationList type name initializerOpt ;**, under cursor **p** and context **TC<sub>0</sub>**:

1. If **initializerOpt** is **EMPTY**:
  - a. Let **typeIR** and a set of fresh type variables **typeId\*** be
    - the result of **typing type**, under cursor **p** and context **TC<sub>0</sub>**.
  - b. Check that **typeId\*** is an empty list.
  - c. Let **bound** be **bound type variables from the p layer of TC<sub>0</sub>**.
  - d. Check that **typeIR** is a well-formed type, with bound type variables **bound**.
  - e. Check that **typeIR** supports assignment.
  - f. Let **nameIR** be **the name of name**.
  - g. Let **TC<sub>1</sub>** be **TC<sub>0</sub> where nameIR to INOUT typeIR DYN · is added to the p layer**.
  - h. Let **variableDeclarationIR** be **annotationList typeIR nameIR · ;**.
  - i. Result in context **TC<sub>1</sub>** and **variableDeclarationIR**.
2. Else:

- a. Let  $\text{expression}_{\text{init}}$  be  $\text{initializerOpt}$ .
- b. Let  $\text{typeIR}$  and a set of fresh type variables  $\text{typeId}^*$  be
  - the result of typing  $\text{type}$ , under cursor  $p$  and context  $\text{TC}_0$ .
- c. Check that  $\text{typeId}^*$  is an empty list.
- d. Let  $\text{bound}$  be bound type variables from the  $p$  layer of  $\text{TC}_0$ .
- e. Check that  $\text{typeIR}$  is a well-formed type, with bound type variables  $\text{bound}$ .
- f. Check that  $\text{typeIR}$  supports assignment.
- g. Let  $\text{typedExpressionIR}_{\text{init}}$  be
  - the result of typing  $\text{expression}_{\text{init}}$ , under cursor  $p$  and context  $\text{TC}_0$ .
- h. Let  $\text{typedExpressionIR}_{\text{init\_cast}}$  be  $!$   $\text{typedExpressionIR}_{\text{init}}$  implicitly cast to  $\text{typeIR}$ .
- i. Let  $\text{nameIR}$  be the name of  $\text{name}$ .
- j. Let  $\text{TC}_1$  be  $\text{TC}_0$  where  $\text{nameIR}$  to  $\text{INOUT typeIR DYN}$  is added to the  $p$  layer.
- k. Let  $\text{variableDeclarationIR}$  be  $\text{annotationList typeIR nameIR} = \text{typedExpressionIR}_{\text{init\_cast}} ;$ .
- l. Result in context  $\text{TC}_1$  and  $\text{variableDeclarationIR}$ .

## 11.2.2. Runtime evaluation

Variable declarations are evaluated at runtime using the following relation:

**VarDecl<sub>eval</sub>:**

- Evaluating  $\text{variableDeclarationIR}$ , under cursor  $\text{cursor}$ , context  $\text{evalContext}$ , and state  $\text{arch}$ :
- Result in context  $\text{evalContext}$ , state  $\text{arch}$ ,
  - and result  $\text{declarationResult}$ .

The result of evaluating a variable declaration is:

```

continueEmptyResult
: /* empty */
;

exitResult
: EXIT
;

abortResult
: exitResult
| rejectTransitionResult
;

declarationResult
: continueEmptyResult
| abortResult
;

```

See [Section 13.7](#) for how  $\text{exitResult}$  may occur. The relation is defined by the following rule:

Evaluating `annotationList typeIR nameIR initializerIR?`; under cursor `p`, context `EC0`, and state `arch`:

1. If `initializerIR?` is none:
  - a. Let `typeIRsubst` be `typeIR` substituted by bound type variables in `EC0` from the BLOCK layer.
  - b. Let `valueinit` be the default value for type `typeIRsubst`.
  - c. Let `EC1` be `EC0` where `nameIR` to `valueinit` is added to the `p` layer.
  - d. Result in context `EC1`, state `arch`,
    - and result ``EMPTY`.
2. Else:
  - a. Let `typedExpressionIRinit` be `initializerIR?`.
  - b. Let context `EC1`, state `ARCH1`, and `expressionResult` be
    - the result of evaluating `typedExpressionIRinit`, under cursor `p`, context `EC0`, and state `arch`.
  - c. If let `abortResult` be `expressionResult`:
    - i. Result in context `EC1`, state `ARCH1`,
      - and result `abortResult`.
  - d. Else:
    - i. Let `valueinit` be `expressionResult`.
    - ii. Let `EC2` be `EC1` where `nameIR` to `valueinit` is added to the `p` layer.
    - iii. Result in context `EC2`, state `ARCH1`,
      - and result ``EMPTY`.

## 11.3. Constant declarations

Constant values are defined with the syntax:

```
constantDeclaration
: annotationList CONST type name initializer ;
;

initializer
: = expression
;
```

The `initializer` expression must be a local compile-time known value. A constant declaration introduces a constant whose value has the specified type. The following are all legal constant declarations:

```
const bit<32> COUNTER = 32w0x0;
struct Version {
    bit<32> major;
    bit<32> minor;
}
const Version version = { 32w0, 32w0 };
```

### 11.3.1. Type checking

Constant declarations are type checked with the relation:

**ConstDecl\_ok:**

- Typing `constantDeclaration`, under cursor `cursor` and context `typingContext`:
- Result in context `typingContext` and `constantDeclarationIR`.

After typing, in  $P4_{IR}$ , constant declarations have the syntax:

```
constantDeclarationIR
: annotationList CONST typeIR nameIR constantInitializerIR ;
;

constantInitializerIR
: = `VALUE value
;
```

Notice that `constantInitializerIR` is reduced to a `value` in  $P4_{IR}$ , where `value` is computed from `initializer` via local compile-time evaluation. It is defined by the following rule:

**Typing** `annotationList CONST type name = expressionvalue ;`, under cursor `p` and context  $TC_0$ :

1. Let `typeIR` and a set of fresh type variables `typed*` be
  - the result of **typing** `type`, under cursor `p` and context  $TC_0$ .
2. Check that `typed*` is an empty list.
3. Let `bound` be **bound type variables from the `p` layer of  $TC_0$** .
4. Check that `typeIR` is a well-formed type, with bound type variables `bound`.
5. Let `typedExpressionIRvalue` be
  - the result of **typing** `expressionvalue`, under cursor `p` and context  $TC_0$ .
6. Check that **the compile-time known-ness of `typedExpressionIRvalue` is LCTK**.
7. Let `typedExpressionIRvalue_cast` be **! typedExpressionIR<sub>value</sub> implicitly cast to `typeIR`**.
8. Let `value` be
  - the result of **local compile-time evaluation of `typedExpressionIRvalue_cast`, under cursor `p` and context  $TC_0$** .
9. Let `nameIR` be **the name of `name`**.
10. Let  $TC_1$  be  $TC_0$  **where `nameIR` to ``EMPTY typeIR LCTK value` is added to the `p` layer**.
11. Let `constantDeclarationIR` be `annotationList CONST typeIR nameIR = `VALUE value ;`.
12. Result in context  $TC_1$  and `constantDeclarationIR`.

When used as a top-level declaration, constant declarations are typed with:

**Typing** `constantDeclaration` under context  $TC_0$ :

1. Let context  $TC_1$  and  $constantDeclarationIR$  be
  - the result of **typing**  $constantDeclaration$ , **under cursor**  $GLOBAL$  **and context**  $TC_0$ .
2. Result in context  $TC_1$  and  $constantDeclarationIR$ .

### 11.3.2. Compile-time evaluation

Constant declarations are evaluated during instantiation phase with:

**ConstDecl\_inst:**

- Loading  $constantDeclarationIR$ , **under cursor**  $cursor$ , **and context**  $instContext$ :
- Result in context  $instContext$ .

It is defined by the following rule:

**Loading**  $annotationList$   $CONST$   $typeIR$   $nameIR = \text{`VALUE value ;, under cursor } p, \text{ and context } IC_0$ :

1. Let  $IC_1$  be  $IC_0$  **where**  $nameIR$  **to value is added to the**  $p$  **layer**.
2. Result in context  $IC_1$ .

When used as a top-level declaration, constant declarations are compile-time evaluated with:

**Loading**  $constantDeclarationIR$ , **under context**  $IC_0$ , **and store**  $STO$ :

1. Let context  $IC_1$  be
  - the result of **loading**  $constantDeclarationIR$ , **under cursor**  $GLOBAL$ , **and context**  $IC_0$ .
2. Result in context  $IC_1$  and store  $STO$ .

### 11.3.3. Runtime evaluation

Constant declarations are evaluated at runtime using the following relation:

**ConstDecl\_eval:**

- Evaluating  $constantDeclarationIR$ , **under cursor**  $cursor$ , **and context**  $evalContext$ :
- Result in context  $evalContext$ .

**Evaluating**  $annotationList$   $CONST$   $typeIR$   $nameIR = \text{`VALUE value ;, under cursor } p, \text{ and context } EC_0$ :

1. Let  $EC_1$  be  $EC_0$  **where**  $nameIR$  **to value is added to the**  $p$  **layer**.
2. Result in context  $EC_1$ .

## 11.4. Instantiations

Instantiations are similar to variable declarations, but are reserved for the types with constructors (**extern** objects, **control** blocks, **parsers**, and **packages**):

```
instantiation
: annotationList type `( argumentList ) name ;
| annotationList type `( argumentList ) name objectInitializer ;
;
```

An instantiation is written as a constructor invocation followed by a name. Instantiations are always executed at compilation time (Section [Section 7.3](#)). The effect is to allocate an object with the specified name, and to bind it to the result of the constructor invocation. Note that instantiation arguments can be specified by name.

For example, a hypothetical bank of counter objects can be instantiated as follows:

```
// from target library
enum CounterType {
    Packets,
    Bytes,
    Both
}
extern Counter {
    Counter(bit<32> size, CounterType type);
    void increment(in bit<32> index);
}
// user program
control c(/* parameters omitted */) {
    Counter(32w1024, CounterType.Both) ctr; // instantiation
    apply { /* body omitted */ }
}
```

A P4 program may not instantiate controls and parsers at the top-level. This restriction is designed to ensure that most state resides in the architecture itself, or is local to a **parser** or **control**. For example, the following program is not valid:

```
// Program
control c(/* parameters omitted */) { /* body omitted */ }
c() c1; // illegal top-level instantiation
```

because **control** **c1** is instantiated at the top-level. Note that top-level declarations of constants and instantiations of **extern** objects are permitted.

### 11.4.1. Objects with abstract methods

When instantiating an **extern** type that has **abstract** methods users have to supply implementations for all such methods. This is done using object initializers:

```
objectInitializer
: = `{ objectDeclarationList }
;

objectDeclarationList
: /* empty */
| objectDeclarationList objectDeclaration
;
```



```

objectDeclaration
: functionDeclaration
| instantiation
;

```

In  $P4_{IR}$ , object initializers have the syntax:

```

objectInitializerIR
: = `{ objectDeclarationListIR }
;

objectDeclarationListIR = objectDeclarationIR*

objectDeclarationIR
: functionDeclarationIR
| instantiationIR
;

```

Abstract method implementations must use the same number of parameters, and the same parameter directions as those declared in the extern object declaration. Note that overloading of abstract methods is not allowed, thus an implementation could be matched to a declaration only with the method name.

Abstract method implementations can only use the supplied arguments or refer to values that are in the same initializer block or the top-level scope. When calling another method of the same instance the `this` keyword is used to indicate the current object instance:

```

// Instantiate a balancer
Balancer() b = { // provide an implementation for the abstract methods
    bit<4> on_new_flow(in bit<32> address) {
        // uses the address and the number of flows to balance the load
        bit<32> count = this.getFlowCount(); // call method of the same instance
        return (address + count)[3:0];
    }
}

```

Abstract methods may be invoked by users explicitly, or they may be invoked by the target architecture. The architectural description has to specify when the abstract methods are invoked and what the meaning of their arguments and return values is; target architectures may impose additional constraints on abstract methods.

#### 11.4.1.1. Type checking

An object declaration is type checked with the relation:

**ObjectDecl\_ok:**

- Typing `objectDeclaration` under cursor `cursor` and typing context `typingContext` with `typeFrame` and `externMethodTypeDefEnv`:
- Result in `typeFrame` and `externMethodTypeDefEnv` of the object declaration and `objectDeclarationIR`.

It is defined by the following rules:

**Typing** `objectDeclaration` **under** `cursor` `p` **and** **typing context** `TC0` **with** `typeFrame` **and** `externMethodTypeDefEnv`:

1. If let instantiation be objectDeclaration:
  - a. Let context  $TC_1$  and instantiationIR be
    - the result of typing instantiation, under cursor p and context  $TC_0$ .
  - b. Let nameIR be the name of instantiationIR.
  - c. Let varTypeIR' be ! the type of variable nameIR from the p layer of  $TC_1$ .
  - d. Let typeFrame<sub>init</sub> be the map typeFrame with the value for nameIR is updated to varTypeIR'.
  - e. Result in typeFrame<sub>init</sub> and externMethodTypeDefEnv of the object declaration and instantiationIR.
2. Else:
  - a. Let annotationList typeOrVoid name typeParameterListOpt ( parameterList ) blockStatement be objectDeclaration.
  - b. Let  $TC_1$  be  $TC_0$  with BLOCK.KIND set to EXTERN.
  - c. Let  $TC_2$  be  $TC_1$  with BLOCK.FRAME set to typeFrame.
  - d. Let context  $TC_3$  and type parameters typeId<sub>expl</sub><sup>\*</sup> be
    - the result of typing typeParameterListOpt, under cursor LOCAL and context  $TC_2$ .
  - e. Let context  $TC_4$ , parameterIR<sup>\*</sup>, and a set of fresh type variables typeId<sub>impl</sub><sup>\*</sup> be
    - the result of typing parameterList, under cursor LOCAL and context  $TC_3$ .
  - f. Let typeIR<sub>ret</sub> and a set of fresh type variables typeId<sup>\*</sup> be
    - the result of typing typeOrVoid, under cursor LOCAL and context  $TC_3$ .
  - g. Check that typeId<sup>\*</sup> is an empty list.
  - h. Let  $TC_5$  be  $TC_4$  with LOCAL.KIND set to EXTERN\_METHOD : typeIR<sub>ret</sub>.
  - i. Let context  $\_$ , abstract control flow f, and blockStatementIR be
    - the result of typing blockStatement, under context  $TC_5$ , abstract control flow CONT, and loop context NOLOOP.
  - j. Check that f is equal to RET or typeIR<sub>ret</sub> is equal to VOID.
  - k. Let callableId be the callable identifier for name ( parameterList ).
  - l. Let nameIR be the name of name.
  - m. Let externMethodTypeDefIR be EXTERN\_METHOD nameIR < typeId<sub>expl</sub><sup>\*</sup>, typeId<sub>impl</sub><sup>\*</sup> > ( parameterIR<sup>\*</sup> ) : typeIR<sub>ret</sub><sup>\*</sup>.
  - n. Let bound be bound type variables from the p layer of  $TC_0$ .
  - o. Check that externMethodTypeDefIR is a well-formed callable type definition, with bound type variables bound.
  - p. Let externMethodTypeDefEnv<sub>init</sub> be the map externMethodTypeDefEnv with the value for callableId is updated to externMethodTypeDefIR.
  - q. Let functionDeclarationIR be annotationList typeIR<sub>ret</sub> nameIR < typeId<sub>expl</sub><sup>\*</sup>, typeId<sub>impl</sub><sup>\*</sup> > ( parameterIR<sup>\*</sup> ) blockStatementIR.
  - r. Result in typeFrame and externMethodTypeDefEnv<sub>init</sub> of the object declaration and functionDeclarationIR.

A list of object declarations is type checked with the relation:

ObjectDeclList\_ok:

- Typing `objectDeclarationList` under cursor `cursor` and typing context `typingContext`:
- Result in `typeFrame` and `externMethodTypeDefEnv` of the object declaration block and `objectDeclarationListIR`.

#### 11.4.1.2. Compile-time evaluation

At compile-time, an object declaration is loaded with the relation:

**ObjectDecl\_inst:**

- Loading `objectDeclarationIR` under instantiation context `instContext` and store `store`:
- Result in the updated instantiation context `instContext` and store `store`.

It is defined by the following rules:

**Loading `objectDeclarationIR` under instantiation context  $IC_0$  and store `store`:**

1. If let `functionDeclarationIR` be `objectDeclarationIR`:
  - a. Let context  $IC_1$  be
    - the result of **loading** `functionDeclarationIR`, under cursor `BLOCK`, and context  $IC_0$ .
  - b. Result in the updated instantiation context  $IC_1$  and store `store`.
2. Else:
  - a. Let `instantiationIR` be `objectDeclarationIR`.
  - b. Let context  $IC_1$ , store  $STO_1$ , and reference to object `_` be
    - the result of **loading** `instantiationIR`, under cursor `GLOBAL`, context  $IC_0$ , and store `store`.
  - c. Result in the updated instantiation context  $IC_1$  and store  $STO_1$ .

A list of object declarations is loaded with the relation:

**ObjectDecls\_inst:**

- Loading `objectDeclarationListIR` under instantiation context `instContext` and store `store`:
- Result in the updated instantiation context `instContext` and store `store`.

#### 11.4.2. Type checking

Instantiations are type checked with the relation:

**InstDecl\_ok:**

- Typing `instantiation`, under cursor `cursor` and context `typingContext`:
- Result in context `typingContext` and `instantiationIR`.

After type checking, in  $P4_{IR}$ , instantiations have the syntax:

```
instantiationIR
: annotationList typeIR constructorTargetIR `( argumentListIR ) nameIR
  objectInitializerOptIR ;
;
```

Typing instantiation, under cursor  $p$  and context  $TC_0$ :

1. If let  $\text{annotationList type ( argumentList ) name ;}$  be instantiation:
  - a. If let  $\text{prefixedTypeName}$  be type:
    - i. Let the updated typing context  $TC_1$  and instantiationIR be
      - the result of typing  $\text{annotationList prefixedTypeName < `EMPTY > ( argumentList ) name ;}$  under cursor  $p$  and typing context  $TC_0$ .
    - ii. Result in context  $TC_1$  and instantiationIR.
  - b. Else if let  $\text{prefixedTypeName < typeArgumentList >}$  be type:
    - i. Let the updated typing context  $TC_1$  and instantiationIR be
      - the result of typing  $\text{annotationList prefixedTypeName < typeArgumentList > ( argumentList ) name ;}$  under cursor  $p$  and typing context  $TC_0$ .
    - ii. Result in context  $TC_1$  and instantiationIR.
2. Else:
  - a. Let  $\text{annotationList type ( argumentList ) name = \{ objectDeclarationList \} ;}$  be instantiation.
  - b. If let  $\text{prefixedTypeName}$  be type:
    - i. Let the updated typing context  $TC_1$  and instantiationIR be
      - the result of typing  $\text{annotationList prefixedTypeName < `EMPTY > ( argumentList ) name = \{ objectDeclarationList \} ;}$  under cursor  $p$  and typing context  $TC_0$ .
    - ii. Result in context  $TC_1$  and instantiationIR.
  - c. Else if let  $\text{prefixedTypeName < typeArgumentList >}$  be type:
    - i. Let the updated typing context  $TC_1$  and instantiationIR be
      - the result of typing  $\text{annotationList prefixedTypeName < typeArgumentList > ( argumentList ) name = \{ objectDeclarationList \} ;}$  under cursor  $p$  and typing context  $TC_0$ .
    - ii. Result in context  $TC_1$  and instantiationIR.

When used as a top-level declaration, instantiations are typed with:

Typing instantiation under context  $TC_0$ :

1. Let context  $TC_1$  and instantiationIR be
  - the result of typing instantiation, under cursor GLOBAL and context  $TC_0$ .
2. Result in context  $TC_1$  and instantiationIR.

There are two sub-relations, depending on whether object initializers were provided or not.

## When object initializers are absent

InstDecl\_non\_objectInitializer\_ok:

- Typing `annotationList prefixedTypeName < typeArgumentList > ( argumentList ) name ; under cursor cursor` and typing context `typingContext`:
- Result in the updated typing context `typingContext` and `instantiationIR`.

Typing `annotationList prefixedTypeName < typeArgumentList > ( argumentList ) name ; under cursor p` and typing context `TC0`:

1. Let `typeArgumentIR*` and a set of fresh type variables `typeIdimpl*` be
  - the result of typing `typeArgumentList`, under cursor `p` and context `TC0`.
2. Let `argumentIR*` be
  - the result of typing `argumentList`, under cursor `p` and context `TC0`.
3. Let `prefixedNameIR` be the prefixed name of `prefixedTypeName`.
4. Let `constructorTargetIR` be `prefixedNameIR < typeArgumentIR* >`.
5. Let `constructorTypeIR` with fresh type variables `typeIdinserted*`, defaults `iddefault*` and optionals `idoptional*` be
  - the result of finding type of constructor call `constructorTargetIR ( argumentIR* )`, under cursor `p` and context `TC0`.
6. Let `typeIdinfer*` be `typeIdimpl*` concatenated with `typeIdinserted*`.
7. Let constructed type `typeIRobject` with inferred `typeArgumentIRinferred*` and cast-inserted `argumentIRcast*` be
  - the result of typing instantiation `constructorTypeIR < typeArgumentIR* > ( argumentIR* )` with omitted type arguments `typeIdinfer*`, defaults `iddefault*` and optionals `idoptional*`, under cursor `p`, context `TC0`, and NAMED instantiation site context.
8. Let `nameIR` be the name of `name`.
9. Let `TC1` be `TC0` where `nameIR to `EMPTY typeIRobject CTK`` is added to the `p` layer.
10. Let `constructorTargetIRinferred` be `prefixedNameIR < typeArgumentIRinferred* >`.
11. Let `instantiationIR` be `annotationList typeIRobject constructorTargetIRinferred ( argumentIRcast* ) nameIR ;`.
12. Result in the updated typing context `TC1` and `instantiationIR`.

## When object initializers are present

InstDecl\_objectInitializer\_ok:

- Typing `annotationList prefixedTypeName < typeArgumentList > ( argumentList ) name = { objectDeclarationList } ; under cursor cursor` and typing context `typingContext`:
- Result in the updated typing context `typingContext` and `instantiationIR`.

Typing `annotationList prefixedTypeName < typeArgumentList > ( argumentList ) name = { objectDeclarationList } ; under cursor p` and typing context `TC0`:

1. Let  $\text{typeArgumentIR}^*$  and a set of fresh type variables  $\text{typed}_{\text{impl}}^*$  be
  - the result of **typing**  $\text{typeArgumentList}$ , **under cursor**  $p$  **and context**  $\text{TC}_0$ .
2. Let  $\text{argumentIR}^*$  be
  - the result of **typing**  $\text{argumentList}$ , **under cursor**  $p$  **and context**  $\text{TC}_0$ .
3. Let  $\text{prefixedNameIR}$  be **the prefixed name of**  $\text{prefixedTypeName}$ .
4. Let  $\text{constructorTargetIR}$  be  $\text{prefixedNameIR} < \text{typeArgumentIR}^* >$ .
5. Let  $\text{constructorTypeIR}$  with fresh type variables  $\text{typed}_{\text{inserted}}^*$ , defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$  be
  - the result of **finding type of constructor call**  $\text{constructorTargetIR} ( \text{argumentIR}^* )$ , **under cursor**  $p$  **and context**  $\text{TC}_0$ .
6. Let  $\text{typed}_{\text{infer}}^*$  be  $\text{typed}_{\text{impl}}^*$  concatenated with  $\text{typed}_{\text{inserted}}^*$ .
7. Let constructed type  $\text{typeIR}_{\text{object}}$  with inferred  $\text{typeArgumentIR}_{\text{inferred}}^*$  and cast-inserted  $\text{argumentIR}_{\text{cast}}^*$  be
  - the result of **typing instantiation**  $\text{constructorTypeIR} < \text{typeArgumentIR}^* > ( \text{argumentIR}^* )$  **with omitted type arguments**  $\text{typed}_{\text{infer}}^*$ , **defaults**  $\text{id}_{\text{default}}^*$  **and optionals**  $\text{id}_{\text{optional}}^*$ , **under cursor**  $p$ , **context**  $\text{TC}_0$ , **and NAMED instantiation site context**.
8. Let  $\text{typeIR}$  be  $\text{typeIR}_{\text{object}}$  **with typedefs unrolled**.
9. Check that  $\text{typeIR}$  has type  $\text{externObjectTypeIR}$ .
10. Let  $\text{EXTERN } \text{typed}_{\text{extern}} < \text{typeIR}_{\text{arg}}^* > \text{externMethodTypeDefEnv}_{\text{extern}}$  be  $\text{typeIR}$ .
11. Let  $\text{TC}_1$  be  $\text{TC}_0$  **where "this" to**  $\text{EMPTY } \text{typeIR}_{\text{object}} \text{ CTK}$  **is added to the LOCAL layer**.
12. Let  $\text{typeFrame}_{\text{init}}$  and  $\text{externMethodTypeDefEnv}_{\text{init}}$  of the object declaration block and  $\text{objectDeclarationIR}^*$  be
  - the result of **typing**  $\text{objectDeclarationList}$  **under cursor**  $p$  **and typing context**  $\text{TC}_1$ .
13. Let  $\text{externMethodTypeDefEnv}_{\text{init\_subst}}$  be **substitution of abstract methods in**  $\text{externMethodTypeDefEnv}_{\text{extern}}$  **by implementations in**  $\text{externMethodTypeDefEnv}_{\text{init}}$ .
14. Let  $\text{typeIR}_{\text{object\_init}}$  be  $\text{EXTERN } \text{typed}_{\text{extern}} < \text{typeIR}_{\text{arg}}^* > \text{externMethodTypeDefEnv}_{\text{init\_subst}}$ .
15. Check that  $\text{typeIR}_{\text{object\_init}}$  **is an extern object type without abstract methods**.
16. Let  $\text{nameIR}$  be **the name of**  $\text{name}$ .
17. Let  $\text{TC}_2$  be  $\text{TC}_0$  **where**  $\text{nameIR}$  **to**  $\text{EMPTY } \text{typeIR}_{\text{object\_init}} \text{ CTK}$  **is added to the**  $p$  **layer**.
18. Let  $\text{constructorTargetIR}_{\text{inferred}}$  be  $\text{prefixedNameIR} < \text{typeArgumentIR}_{\text{inferred}}^* >$ .
19. Let  $\text{instantiationIR}$  be  $\text{annotationList } \text{typeIR}_{\text{object\_init}} \text{ constructorTargetIR}_{\text{inferred}} ( \text{argumentIR}_{\text{cast}}^* ) \text{ nameIR} = \{ \text{objectDeclarationIR}^* \};$ .
20. Result in the updated typing context  $\text{TC}_2$  and  $\text{instantiationIR}$ .

### 11.4.3. Compile-time evaluation

Instantiations are evaluated at compile-time with the relation:

**InstDecl\_inst:**

- Loading  $\text{instantiationIR}$ , **under cursor**  $\text{cursor}$ , **context**  $\text{instContext}$ , and **store**  $\text{store}$ :
- Result in context  $\text{instContext}$ , **store**  $\text{store}$ ,
  - and reference to object  $\text{constantDeclarationIR}$ .

Loading annotationList typeIR constructorTargetIR ( argumentListIR ) nameIR objectInitializerOptIR ;, under cursor p, context IC<sub>0</sub>, and store STO<sub>0</sub>:

1. Let prefixedNameIR < typeArgumentListIR > be constructorTargetIR.
2. Let constructor constructorDef < typeArgumentListIR<sub>inst</sub> > with defaults id<sub>default</sub><sup>\*</sup> and optionals id<sub>optional</sub><sup>\*</sup> be
  - the result of finding constructor for prefixedNameIR < typeArgumentListIR > ( argumentListIR ) under cursor p, and context IC<sub>0</sub>.
3. Let IC<sub>inner</sub> be IC<sub>0</sub> with nameIR added to the path.
4. Let store STO<sub>1</sub> and constructed object be
  - the result of loading constructorDef < typeArgumentListIR<sub>inst</sub> > ( argumentListIR ) with defaults id<sub>default</sub><sup>\*</sup> and optionals id<sub>optional</sub><sup>\*</sup>, under cursor p, context IC<sub>inner</sub>, and store STO<sub>0</sub>.
5. If let EXTERN typeId < theta > { objectState frame externMethodDefEnv } be object:
  - a. Let IC<sub>decl</sub> be an instantiation context same as IC<sub>0</sub> up to the GLOBAL layer.
  - b. Let objectDeclarationListIR be the list of object declarations in objectInitializerOptIR.
  - c. Let the updated instantiation context IC<sub>decl\_post</sub> and store STO<sub>2</sub> be
    - the result of loading objectDeclarationListIR under instantiation context IC<sub>decl</sub> and store STO<sub>1</sub>.
  - d. Let frame<sub>merged</sub> be the merged frame of frame and IC<sub>decl\_post</sub>.BLOCK.FRAME.
  - e. Let externMethodDefEnv<sub>merged</sub> be the merged extern method definition environment of externMethodDefEnv and IC<sub>decl\_post</sub>.BLOCK.CALLABLE.
  - f. Let object<sub>merged</sub> be EXTERN typeId < theta > { objectState frame<sub>merged</sub> externMethodDefEnv<sub>merged</sub> }.
  - g. Let objectId be IC<sub>0</sub>.PATH concatenated with nameIR.
  - h. Let STO<sub>3</sub> be STO<sub>2</sub> where objectId to object<sub>merged</sub> is added.
  - i. Let IC<sub>1</sub> be IC<sub>0</sub> where nameIR to REF objectId is added to the p layer.
  - j. Let constantDeclarationIR be `EMPTY CONST typeIR nameIR = `VALUE REF objectId ;.
  - k. Result in context IC<sub>1</sub>, store STO<sub>3</sub>,
    - and reference to object constantDeclarationIR.
6. Else:
  - a. Let objectId be IC<sub>0</sub>.PATH concatenated with nameIR.
  - b. Let STO<sub>2</sub> be STO<sub>1</sub> where objectId to object is added.
  - c. Let IC<sub>1</sub> be IC<sub>0</sub> where nameIR to REF objectId is added to the p layer.
  - d. Let constantDeclarationIR be `EMPTY CONST typeIR nameIR = `VALUE REF objectId ;.
  - e. Result in context IC<sub>1</sub>, store STO<sub>2</sub>,
    - and reference to object constantDeclarationIR.

When used as a top-level declaration, instantiations are evaluated with:

Loading instantiationIR, under context IC<sub>0</sub>, and store STO:

1. Let context IC<sub>1</sub>, store STO<sub>1</sub>, and reference to object \_ be
  - the result of loading instantiationIR, under cursor GLOBAL, context IC<sub>0</sub>, and store STO.

2. Result in context  $IC_1$  and store  $STO_1$ .

## 11.5. Function declarations

Function declarations introduce user-defined functions into a P4 program. [Section 9.4.1](#) describes the semantics of user-defined functions in P4.

```
functionPrototype
: typeOrVoid name typeParameterListOpt `( parameterList )
;

functionDeclaration
: annotationList functionPrototype blockStatement
;
```

### 11.5.1. Type checking

Function declarations are type checked with the relation:

**FuncDecl\_ok:**

- Typing `functionDeclaration`, under cursor `cursor` and context `typingContext`:
- Result in context `typingContext` and `functionDeclarationIR`.

After type checking, function declarations are represented in  $P4_{IR}$  as:

```
functionPrototypeIR
: typeIR nameIR `< typeParameterListIR , typeParameterListIR >
  `( parameterListIR )
;

functionDeclarationIR
: annotationList functionPrototypeIR blockStatementIR
;
```

They are produced by the following rule:

**Typing** `annotationList typeOrVoid name typeParameterListOpt ( parameterList ) blockStatement`, under cursor `p` and context  $TC_0$ :

1. Let context  $TC_1$  and type parameters  $typed_{expl}^*$  be
  - the result of **typing** `typeParameterListOpt`, under cursor `LOCAL` and context  $TC_0$ .
2. Let  $typed_{ret}$  and a set of fresh type variables  $typed^*$  be
  - the result of **typing** `typeOrVoid`, under cursor `LOCAL` and context  $TC_1$ .
3. Check that  $typed^*$  is an empty list.
4. Let context  $TC_2$ ,  $parameterIR^*$ , and a set of fresh type variables  $typed_{impl}^*$  be
  - the result of **typing** `parameterList`, under cursor `LOCAL` and context  $TC_1$ .
5. Let  $TC_3$  be  $TC_2$  with `LOCAL.KIND` set to `FUNCTION : typeIRret`.



6. Let context  $\_$ , abstract control flow  $f$ , and `blockStatementIR` be
  - the result of `typing blockStatement`, under context  $TC_3$ , abstract control flow  $CONT$ , and loop context  $NOLOOP$ .
7. Check that  $f$  is equal to  $RET$  or  $typeIR_{ret}$  is equal to  $VOID$ .
8. Let `callableId` be the callable identifier for `name ( parameterList )`.
9. Let `nameIR` be the name of `name`.
10. Let `definedFunctionTypeDefIR` be `FUNCTION nameIR < typeIdexpl*, typeIdimpl* > ( parameterIR* ) : typeIRret*`.
11. Let `bound` be bound type variables from the  $p$  layer of  $TC_0$ .
12. Check that `definedFunctionTypeDefIR` is a well-formed callable type definition, with bound type variables `bound`.
13. Let  $TC_4$  be  $TC_0$  where `callableId` to `definedFunctionTypeDefIR` is added as an overloaded callable to the  $p$  layer.
14. Let `functionDeclarationIR` be `annotationList typeIRret nameIR < typeIdexpl*, typeIdimpl* > ( parameterIR* ) blockStatementIR`.
15. Result in context  $TC_4$  and `functionDeclarationIR`.

When used as a top-level declaration, function declarations are typed with:

`Typing functionDeclaration` under context  $TC_0$ :

1. Let context  $TC_1$  and `functionDeclarationIR` be
  - the result of `typing functionDeclaration`, under cursor  $GLOBAL$  and context  $TC_0$ .
2. Result in context  $TC_1$  and `functionDeclarationIR`.

## 11.5.2. Compile-time evaluation

At compile-time, function declarations are loaded into the context with the relation:

`FuncDecl_inst`:

- Loading `functionDeclarationIR`, under cursor `cursor`, and context `instContext`:
- Result in context `instContext`.

It is defined by the following rule:

`Loading annotationList typeIR nameIR < typeParameterListIRexpl, typeParameterListIRimpl > ( parameterListIR ) blockStatementIR`, under cursor  $p$ , and context  $IC_0$ :

1. Let `callableId` be the callable identifier for `nameIR ( parameterListIR )`.
2. Let `typeParameterListIR` be `typeParameterListIRexpl` concatenated with `typeParameterListIRimpl`.
3. Let `definedFunctionDef` be `FUNCTION nameIR < typeParameterListIR > ( parameterListIR ) blockStatementIR`.
4. Let  $IC_1$  be  $IC_0$  where `callableId` to `definedFunctionDef` is added as an overloaded callable to the  $p$  layer.
5. Result in context  $IC_1$ .

When used as a top-level declaration, function declarations are loaded with:

Loading `functionDeclarationIR`, under context  $IC_0$ , and store  $STO$ :

1. Let context  $IC_1$  be
  - the result of loading `functionDeclarationIR`, under cursor `GLOBAL`, and context  $IC_0$ .
2. Result in context  $IC_1$  and store  $STO$ .

## 11.6. Action declarations

action declarations introduce actions:

```
actionDeclaration
: annotationList ACTION name `( parameterList ) blockStatement
;
```

Section 9.3 describes the semantics of actions.

### 11.6.1. Type checking

Action declarations are type checked with the relation:

ActionDecl\_ok:

- Typing `actionDeclaration`, under cursor `cursor` and context `typingContext`:
- Result in context `typingContext` and `actionDeclarationIR`.

After type checking, action declarations are represented in  $P4_{IR}$  as:

```
actionDeclarationIR
: annotationList ACTION nameIR `( parameterListIR ) blockStatementIR
;
```

These are produced by the following rule:

Typing `annotationList ACTION name ( parameterList ) blockStatement`, under cursor `p` and context  $TC_0$ :

1. Let  $TC_1$  be  $TC_0$  with `LOCAL.KIND` set to `ACTION`.
2. Let context  $TC_2$ , `parameterIR*`, and a set of fresh type variables `typeld*` be
  - the result of typing `parameterList`, under cursor `LOCAL` and context  $TC_1$ .
3. Check that `typeld*` is an empty list.
4. Let context  $\_$ , abstract control flow  $\_$ , and `blockStatementIR` be
  - the result of typing `blockStatement`, under context  $TC_2$ , abstract control flow `CONT`, and loop context `NOLOOP`.
5. Let `callableId` be the callable identifier for `name ( parameterList )`.

6. Let `nameIR` be the name of `name`.
7. Let `actionTypeDefIR` be `annotationList ACTION nameIR ( parameterIR* )`.
8. Let `bound` be bound type variables from the `p` layer of `TC0`.
9. Check that `actionTypeDefIR` is a well-formed callable type definition, with bound type variables `bound`.
10. Let `TC3` be `TC0` where `callableId` to `actionTypeDefIR` is added as a non-overloaded callable to the `p` layer.
11. Let `actionDeclarationIR` be `annotationList ACTION nameIR ( parameterIR* ) blockStatementIR`.
12. Result in context `TC3` and `actionDeclarationIR`.

When used as a top-level declaration, action declarations are typed with:

Typing `actionDeclaration` under context `TC0`:

1. Let context `TC1` and `actionDeclarationIR` be
  - the result of typing `actionDeclaration`, under cursor `GLOBAL` and context `TC0`.
2. Result in context `TC1` and `actionDeclarationIR`.

## 11.6.2. Compile-time evaluation

At compile-time, action declarations are loaded into the context with the relation:

ActionDecl\_inst:

- Loading `actionDeclarationIR`, under cursor `cursor`, and context `instContext`:
- Result in context `instContext`.

It is defined by the following rule:

Loading `annotationList ACTION nameIR ( parameterListIR ) blockStatementIR`, under cursor `p`, and context `IC0`:

1. Let `callableId` be the callable identifier for `nameIR ( parameterListIR )`.
2. Let `actionDef` be `ACTION nameIR ( parameterListIR ) blockStatementIR`.
3. Let `IC1` be `IC0` where `callableId` to `actionDef` is added as a non-overloaded callable to the `p` layer.
4. Result in context `IC1`.

When used as a top-level declaration, action declarations are loaded with:

Loading `actionDeclarationIR`, under context `IC0`, and store `STO`:

1. Let context `IC1` be
  - the result of loading `actionDeclarationIR`, under cursor `GLOBAL`, and context `IC0`.
2. Result in context `IC1` and store `STO`.

## 11.7. Error declarations

```
errorDeclaration
: ERROR `{ nameList }
;
```

**error** declarations introduce error elements. See [Section 8.2.4](#) for more details on error elements.

### 11.7.1. Type checking

After type checking, an **error** declaration is represented as:

```
errorDeclarationIR
: ERROR `{ nameListIR }
;
```

Typing **ERROR { nameList }** under context  $TC_0$ :

1. Let  $name^*$  be the list of names in **nameList**.
2. Let  $nameIR^*$  be the list of **nameIR**, obtained by repeating:
  - Let **nameIR** be the name of **name**.for each **name** in  $name^*$
3. Check that the elements of  $nameIR^*$  are distinct.
4. Let  $nameIR_{error}^*$  be the list of **nameIR<sub>error</sub>**, obtained by repeating:
  - Let **nameIR<sub>error</sub>** be "error." concatenated with **nameIR**.for each **nameIR** in  $nameIR^*$
5. Let  $value_{error}^*$  be the list of **value<sub>error</sub>**, obtained by repeating:
  - Let **value<sub>error</sub>** be **ERROR . nameIR**.for each **nameIR** in  $nameIR^*$
6. Let  $varTypeIR^*$  be the list of **varTypeIR**, obtained by repeating:
  - Let **varTypeIR** be **EMPTY ERROR LCTK value<sub>error</sub>**.for each **value<sub>error</sub>** in  $value_{error}^*$
7. Let  $TC_1$  be  $TC_0$  where each of  $nameIR_{error}^*$  to each of  $varTypeIR^*$  are added to the GLOBAL layer.
8. Result in context  $TC_1$  and **ERROR { nameIR<sup>\*</sup> }**.

### 11.7.2. Compile-time evaluation

At compile-time, error declarations are loaded into the context by:

Loading `ERROR { nameIR* }`, under context  $IC_0$ , and store  $STO$ :

1. Let  $nameIR_{error}^*$  be the list of  $nameIR_{error}$ , obtained by repeating:
  - Let  $nameIR_{error}$  be the concatenation of `[ "error.", nameIR ]`.for each  $nameIR$  in  $nameIR^*$
2. Let  $value_{error}^*$  be the list of  $value_{error}$ , obtained by repeating:
  - Let  $value_{error}$  be `ERROR . nameIR`.for each  $nameIR$  in  $nameIR^*$
3. Let  $IC_1$  be  $IC_0$  where each of  $nameIR_{error}^*$  to each of  $value_{error}^*$  are added to the GLOBAL layer.
4. Result in context  $IC_1$  and store  $STO$ .

## 11.8. Match kind declarations

```
matchKindDeclaration
: MATCH_KIND `{ nameList trailingCommaOpt }
;
```

Similar to `error` declarations, `match_kind` declarations introduce match kinds. See [Section 8.2.5](#) for more details on match kinds.

### 11.8.1. Type checking

After type checking, an `match_kind` declaration is represented as:

```
matchKindDeclarationIR
: MATCH_KIND `{ nameListIR }
;
```

Typing `MATCH_KIND { nameList trailingCommaOpt }` under context  $TC_0$ :

1. Let  $name^*$  be the list of names in `nameList`.
2. Let  $nameIR^*$  be the list of  $nameIR$ , obtained by repeating:
  - Let  $nameIR$  be the name of `name`.for each  $name$  in  $name^*$
3. Check that the elements of  $nameIR^*$  are distinct.
4. Let  $value_{match\_kind}^*$  be the list of  $value_{match\_kind}$ , obtained by repeating:
  - Let  $value_{match\_kind}$  be `MATCH_KIND . nameIR`.for each  $nameIR$  in  $nameIR^*$

5. Let  $\text{varTypeIR}^*$  be the list of  $\text{varTypeIR}$ , obtained by repeating:
  - Let  $\text{varTypeIR}$  be `EMPTY MATCH_KIND LCTK valuematch_kind`.
 for each  $\text{value}_{\text{match\_kind}}$  in  $\text{value}_{\text{match\_kind}}^*$
6. Let  $\text{TC}_1$  be  $\text{TC}_0$  where each of  $\text{nameIR}^*$  to each of  $\text{varTypeIR}^*$  are added to the GLOBAL layer.
7. Result in context  $\text{TC}_1$  and `MATCH_KIND { nameIR* }`.

## 11.8.2. Compile-time evaluation

At compile-time, match kind declarations are loaded into the context by:

Loading `MATCH_KIND { nameIR* }`, under context  $\text{IC}_0$ , and store  $\text{STO}$ :

1. Let  $\text{value}_{\text{match\_kind}}^*$  be the list of  $\text{value}_{\text{match\_kind}}$ , obtained by repeating:
  - Let  $\text{value}_{\text{match\_kind}}$  be `MATCH_KIND . nameIR`.
 for each  $\text{nameIR}$  in  $\text{nameIR}^*$
2. Let  $\text{IC}_1$  be  $\text{IC}_0$  where each of  $\text{nameIR}^*$  to each of  $\text{value}_{\text{match\_kind}}^*$  are added to the GLOBAL layer.
3. Result in context  $\text{IC}_1$  and store  $\text{STO}$ .

## 11.9. Extern function declarations

```
externFunctionDeclaration
: annotationList EXTERN functionPrototype ;
;
```

An extern function declaration introduces an extern function. See [Section 9.4.2](#) for how extern functions are internally represented.

### 11.9.1. Type checking

After type checking, an extern function declaration is represented in  $\text{P4}_{\text{IR}}$  as:

```
externFunctionDeclarationIR
: annotationList EXTERN functionPrototypeIR ;
;
```

Typing `annotationList EXTERN typeOrVoid name typeParameterListOpt ( parameterList )`; under context  $\text{TC}_0$ :

1. Let context  $\text{TC}_1$  and type parameters  $\text{typeId}_{\text{expl}}^*$  be
  - the result of typing `typeParameterListOpt`, under cursor `LOCAL` and context  $\text{TC}_0$ .
2. Let context  $\text{TC}_2$ ,  $\text{parameterIR}^*$ , and a set of fresh type variables  $\text{typeId}_{\text{impl}}^*$  be
  - the result of typing `parameterList`, under cursor `LOCAL` and context  $\text{TC}_1$ .

3. Let  $\text{typeIR}_{\text{ret}}$  and a set of fresh type variables  $\text{typeID}^*$  be
  - the result of **typing typeOrVoid**, under cursor **LOCAL** and context  $\text{TC}_1$ .
4. Check that  $\text{typeID}^*$  is an empty list.
5. Let  $\text{callableID}$  be **the callable identifier for name ( parameterList )**.
6. Let  $\text{nameIR}$  be **the name of name**.
7. Let  $\text{externFunctionTypeDefIR}$  be **EXTERN\_FUNCTION**  $\text{nameIR} < \text{typeID}_{\text{expl}}^*, \text{typeID}_{\text{impl}}^* > ( \text{parameterIR}^* ) : \text{typeIR}_{\text{ret}}$ .
8. Let  $\text{bound}$  be **bound type variables from the GLOBAL layer of  $\text{TC}_0$** .
9. Check that  $\text{externFunctionTypeDefIR}$  is a well-formed callable type definition, with bound type variables  $\text{bound}$ .
10. Let  $\text{TC}_4$  be  $\text{TC}_0$  **where**  $\text{callableID}$  **to**  $\text{externFunctionTypeDefIR}$  **is added as an overloaded callable to the GLOBAL layer**.
11. Let  $\text{externFunctionDeclarationIR}$  be **annotationList** **EXTERN**  $\text{typeIR}_{\text{ret}}$   $\text{nameIR} < \text{typeID}_{\text{expl}}^*, \text{typeID}_{\text{impl}}^* > ( \text{parameterIR}^* ) ;$ .
12. Result in context  $\text{TC}_4$  and  $\text{externFunctionDeclarationIR}$ .

## 11.9.2. Compile-time evaluation

At compile-time, extern function declarations are loaded into the context by:

**Loading** **annotationList** **EXTERN**  $\text{typeIR}$   $\text{nameIR} < \text{typeParameterListIR}_{\text{expl}}, \text{typeParameterListIR}_{\text{impl}} > ( \text{parameterListIR} )$  **;**, under context  $\text{IC}_0$ , and store  $\text{STO}$ :

1. Let  $\text{callableID}$  be **the callable identifier for**  $\text{nameIR} ( \text{parameterListIR} )$ .
2. Let  $\text{typeParameterListIR}$  be  $\text{typeParameterListIR}_{\text{expl}}$  concatenated with  $\text{typeParameterListIR}_{\text{impl}}$ .
3. Let  $\text{externFunctionDef}$  be **EXTERN\_FUNCTION**  $\text{nameIR} < \text{typeParameterListIR} > ( \text{parameterListIR} )$ .
4. Let  $\text{IC}_1$  be  $\text{IC}_0$  **where**  $\text{callableID}$  **to**  $\text{externFunctionDef}$  **is added as an overloaded callable to the GLOBAL layer**.
5. Result in context  $\text{IC}_1$  and store  $\text{STO}$ .

## 11.10. Extern object declarations

An extern object declaration introduces an extern object.

```
externObjectDeclaration
: annotationList EXTERN nonTypeName typeParameterListOpt
  { externConstructorOrMethodPrototypeList }
;

externConstructorOrMethodPrototype
: externConstructorPrototype
| externMethodPrototype
;

externConstructorOrMethodPrototypeList
: /* empty */
| externConstructorOrMethodPrototypeList externConstructorOrMethodPrototype
;
```

See [Section 10.3](#) for how extern objects are internally represented. An extern object declaration includes its constructors and methods, to be explained in the following sections.

### 11.10.1. Extern methods

Extern objects can have methods, which are declared using the following syntax:

```
externMethodPrototype
: annotationList functionPrototype ;
| annotationList ABSTRACT functionPrototype ;
;
```

See [Section 9.5.1](#) for details on how extern methods are represented internally.

#### 11.10.1.1. Type checking

Extern methods are type checked using the following relation:

[ExternMethod\\_ok](#):

- Typing `externMethodPrototype`, under context `typingContext` for an extern object `typed`:
- Result in `externMethodPrototypeIR`.

After type checking, in  $P4_{IR}$ , an extern method declaration is represented as:

```
externMethodPrototypeIR
: annotationList functionPrototypeIR ;
| annotationList ABSTRACT functionPrototypeIR ;
;
```

These are produced by:

[Typing](#) `externMethodPrototype`, under context  $TC_0$  for an extern object `typedextern`:

1. If let `annotationList functionPrototype ;` be `externMethodPrototype`:
  - a. Let `typeOrVoid name typeParameterListOpt ( parameterList )` be `functionPrototype`.
  - b. Let `nameIR` be [the name of](#) `name`.
  - c. Check that `nameIR` is not equal to `typedextern`.
  - d. Let context  $TC_1$  and type parameters `typedexpl*` be
    - the result of [typing](#) `typeParameterListOpt`, under cursor `LOCAL` and context  $TC_0$ .
  - e. Let `typedretIR` and a set of fresh type variables `typed*` be
    - the result of [typing](#) `typeOrVoid`, under cursor `LOCAL` and context  $TC_1$ .
  - f. Check that `typed*` is an empty list.
  - g. Let  $TC_2$  be  $TC_1$  with `LOCAL.KIND` set to `EXTERN_METHOD : typedretIR`.
  - h. Let context  $TC_3$ , `parameterIR*`, and a set of fresh type variables `typedimpl*` be
    - the result of [typing](#) `parameterList`, under cursor `LOCAL` and context  $TC_2$ .



- i. Let `externMethodTypeDefIR` be `EXTERN_METHOD nameIR < typeIdexpl*, typeIdimpl* > ( parameterIR* ) : typeIRret*`.
  - j. Let `bound` be `bound type variables from the BLOCK layer of TC0`.
  - k. Check that `externMethodTypeDefIR` is a well-formed callable type definition, with bound type variables `bound`.
  - l. Let `externMethodPrototypeIR` be `annotationList typeIRret nameIR < typeIdexpl*, typeIdimpl* > ( parameterIR* ) ;`.
  - m. Result in `externMethodPrototypeIR`.
2. Else:
- a. Let `annotationList ABSTRACT functionPrototype ;` be `externMethodPrototype`.
  - b. Let `typeOrVoid name typeParameterListOpt ( parameterList )` be `functionPrototype`.
  - c. Let `nameIR` be `the name of name`.
  - d. Check that `nameIR` is not equal to `typeIdextern*`.
  - e. Let context `TC1` and type parameters `typeIdexpl*` be
    - the result of `typing typeParameterListOpt, under cursor LOCAL and context TC0`.
  - f. Let `typeIRret` and a set of fresh type variables `typeId*` be
    - the result of `typing typeOrVoid, under cursor LOCAL and context TC1`.
  - g. Check that `typeId*` is an empty list.
  - h. Let `TC2` be `TC1` with `LOCAL.KIND` set to `EXTERN_METHOD ABSTRACT : typeIRret*`.
  - i. Let context `TC3`, `parameterIR*`, and a set of fresh type variables `typeIdimpl*` be
    - the result of `typing parameterList, under cursor LOCAL and context TC2`.
  - j. Let `externMethodTypeDefIR` be `EXTERN_METHOD ABSTRACT nameIR < typeIdexpl*, typeIdimpl* > ( parameterIR* ) : typeIRret*`.
  - k. Let `bound` be `bound type variables from the BLOCK layer of TC0`.
  - l. Check that `externMethodTypeDefIR` is a well-formed callable type definition, with bound type variables `bound`.
  - m. Let `externMethodPrototypeIR` be `annotationList ABSTRACT typeIRret nameIR < typeIdexpl*, typeIdimpl* > ( parameterIR* ) ;`.
  - n. Result in `externMethodPrototypeIR`.

## 11.10.2. Extern constructors

Extern objects may have constructors, which are declared using the following syntax:

```
externConstructorPrototype
: annotationList typeIdIdentifier `( parameterList ) ;
;
```

### 11.10.2.1. Type checking

Extern constructors are type checked using the following relation:

`ExternConstructor_ok`:

- Typing `externConstructorPrototype`, under context `typingContext` for an extern object `typed`:
- Result in `externConstructorPrototypeIR`.

After type checking, in  $P4_{IR}$ , an extern constructor declaration is represented as:

```
externConstructorPrototypeIR
: annotationList nameIR `< , typeParameterListIR > `( parameterListIR ) ;
;
```

These are produced by:

Typing `annotationList typeIdIdentifier ( parameterList ) ;`, under context  $TC_0$  for an extern object `typedextern`:

1. Let `nameIR` be the name of `typeIdentifier`.
2. Check that `nameIR` is equal to `typedextern`.
3. Let context  $TC_1$ , `constructorParameterIR*`, and a set of fresh type variables `typedimpl*` be
  - the result of typing `( parameterList )` under context  $TC_0$ .
4. Let `typeDefIR'` be ! the type definition of `typedextern` from the GLOBAL layer of  $TC_0$ .
5. Check that `typeDefIR'` has type `externObjectTypeDefIR`.
6. Let `externObjectTypeDefIR` be `typeDefIR'`.
7. Let `( typedexpl*, typeParameterIR* )` be the type parameters of `externObjectTypeDefIR`.
8. Check that `typeParameterIR*` is an empty list.
9. Let `typeIRextern` be the underlying type of `externObjectTypeDefIR`.
10. Let `constructorTypeDefIR` be `CONSTRUCTOR < typedexpl*, typedimpl* > ( constructorParameterIR* ) : typeIRextern`.
11. Let `bound` be bound type variables from the BLOCK layer of  $TC_0$ .
12. Check that `constructorTypeDefIR` is a well-formed constructor type definition, with bound type variables `bound`.
13. Let `externConstructorPrototypeIR` be `annotationList nameIR < , typedimpl* > ( constructorParameterIR* ) ;`.
14. Result in `externConstructorPrototypeIR`.

### 11.10.3. Type checking

After type checking, an extern object declaration is represented in  $P4_{IR}$  as:

```
externObjectDeclarationIR
: annotationList EXTERN nameIR `< typeParameterListIR , >
  `{ externConstructorPrototypeListIR externMethodPrototypeListIR }
;

externConstructorPrototypeIR
: annotationList nameIR `< , typeParameterListIR > `( parameterListIR ) ;
;

externMethodPrototypeIR
: annotationList functionPrototypeIR ;
| annotationList ABSTRACT functionPrototypeIR ;
;
```

**Typing** annotationList EXTERN nonTypeName typeParameterListOpt { externConstructorOrMethodPrototypeList }  
under context  $TC_0$ :

1. Let ( externConstructorPrototype<sup>\*</sup>, externMethodPrototype<sup>\*</sup> ) be externConstructorOrMethodPrototypeList split into constructors and methods.
2. Let  $TC_1$  be  $TC_0$  with BLOCK.KIND set to EXTERN.
3. Let context  $TC_2$  and type parameters  $typeId_{expl}$ <sup>\*</sup> be
  - the result of **typing** typeParameterListOpt, under cursor BLOCK and context  $TC_1$ .
4. Let nameIR be the name of nonTypeName.
5. Let externMethodPrototypeIR<sup>\*</sup> be the list of externMethodPrototypeIR, obtained by repeating:
  - Let externMethodPrototypeIR be
    - the result of **typing** externMethodPrototype, under context  $TC_2$  for an extern object nameIR.
 for each externMethodPrototype in externMethodPrototype<sup>\*</sup>
6. Let callableId<sub>method</sub><sup>\*</sup> be the list of callableId<sub>method</sub>, obtained by repeating:
  - Let callableId<sub>method</sub> be callable id of externMethodPrototype.
 for each externMethodPrototype in externMethodPrototype<sup>\*</sup>
7. Check that the elements of callableId<sub>method</sub><sup>\*</sup> are distinct.
8. Let externMethodTypeDefIR<sup>\*</sup> be the list of externMethodTypeDefIR, obtained by repeating:
  - Let externMethodTypeDefIR be callable type definition of externMethodPrototypeIR.
 for each externMethodPrototypeIR in externMethodPrototypeIR<sup>\*</sup>
9. Let externMethodTypeDefEnv be { ( callableId<sub>method</sub> : externMethodTypeDefIR )<sup>\*</sup> }.
10. Let typeDefIR<sub>extern</sub> be EXTERN nameIR < typeId<sub>expl</sub><sup>\*</sup>, · > externMethodTypeDefEnv.
11. Let  $TC_3$  be  $TC_0$  where nameIR to typeDefIR<sub>extern</sub> is added to the GLOBAL layer.
12. Let  $TC_4$  be  $TC_3$  with BLOCK.KIND set to EXTERN.
13. Let  $TC_5$  be type parameters typeId<sub>expl</sub><sup>\*</sup> added to the BLOCK layer of  $TC_4$ .
14. Let externConstructorPrototypeIR<sup>\*</sup> be the list of externConstructorPrototypeIR, obtained by repeating:
  - Let externConstructorPrototypeIR be
    - the result of **typing** externConstructorPrototype, under context  $TC_5$  for an extern object nameIR.
 for each externConstructorPrototype in externConstructorPrototype<sup>\*</sup>
15. Let constructorId<sup>\*</sup> be the list of constructorId, obtained by repeating:
  - Let constructorId be constructor id of externConstructorPrototype.
 for each externConstructorPrototype in externConstructorPrototype<sup>\*</sup>
16. Let typeIR<sub>extern</sub> be the underlying type of typeDefIR<sub>extern</sub>.

17. Let `constructorTypeDefIR*` be the list of `constructorTypeDefIR`, obtained by repeating:
  - Let `constructorTypeDefIR` be the constructor type definition of `externConstructorPrototypeIR` with type parameters `typedexpl*` and type `typeIRextern*`.
 for each `externConstructorPrototypeIR` in `externConstructorPrototypeIR*`
18. Let `TC6` be where each of `constructorId*` to each of `constructorTypeDefIR*` are added to `TC3`.
19. Let `externObjectDeclarationIR` be `annotationList EXTERN nameIR < typedexpl*, > { externConstructorPrototypeIR* externMethodPrototypeIR* }`.
20. Result in context `TC6` and `externObjectDeclarationIR`.

#### 11.10.4. Compile-time evaluation

At compile-time, extern object declarations are loaded into the context by:

**Loading** `annotationList EXTERN nameIR < typeParameterListIR , > { externConstructorPrototypeIR* externMethodPrototypeIR* }`, under context `IC0`, and store `STO`:

1. If `externConstructorPrototypeIR*` is equal to `:`:
  - a. Let `callableIdmethod*` be the list of `callableIdmethod`, obtained by repeating:
    - Let `callableIdmethod` be the callable id of `externMethodPrototypeIR`.
 for each `externMethodPrototypeIR` in `externMethodPrototypeIR*`
  - b. Let `externMethodTypeDefIR*` be the list of `externMethodTypeDefIR`, obtained by repeating:
    - Let `externMethodTypeDefIR` be callable type definition of `externMethodPrototypeIR`.
 for each `externMethodPrototypeIR` in `externMethodPrototypeIR*`
  - c. Let `externMethodTypeDefEnv` be `{ ( callableIdmethod : externMethodTypeDefIR )*`.
  - d. Let `externObjectTypeDefIR` be `EXTERN nameIR < typeParameterListIR , > externMethodTypeDefEnv`.
  - e. Let `IC1` be `IC0` where `nameIR` to `externObjectTypeDefIR` is added to the `GLOBAL` layer.
  - f. Let `callableIdconstructor` be the callable identifier for `nameIR ( · )`.
  - g. Let `constructorDef` be `EXTERN nameIR < typeParameterListIR > ( · ) { externMethodPrototypeIR* }`.
  - h. Let `IC2` be where `callableIdconstructor` to `constructorDef` is added to `IC1`.
  - i. Result in context `IC2` and store `STO`.
2. Else:
  - a. Let `callableIdmethod*` be the list of `callableIdmethod`, obtained by repeating:
    - Let `callableIdmethod` be the callable id of `externMethodPrototypeIR`.
 for each `externMethodPrototypeIR` in `externMethodPrototypeIR*`
  - b. Let `externMethodTypeDefIR*` be the list of `externMethodTypeDefIR`, obtained by repeating:
    - Let `externMethodTypeDefIR` be callable type definition of `externMethodPrototypeIR`.

- for each `externMethodPrototypeIR` in `externMethodPrototypeIR*`
- c. Let `externMethodTypeDefEnv` be `{ ( callableIdmethod : externMethodTypeDefIR )* }`.
  - d. Let `externObjectTypeDefIR` be `EXTERN nameIR < typeParameterListIR , · > externMethodTypeDefEnv`.
  - e. Let `IC1` be `IC0` where `nameIR` to `externObjectTypeDefIR` is added to the GLOBAL layer.
  - f. Let `callableIdconstructor*` be the list of `callableIdconstructor`, obtained by repeating:
    - Let `callableIdconstructor` be the constructor id of `externConstructorPrototypeIR`.
- for each `externConstructorPrototypeIR` in `externConstructorPrototypeIR*`
- g. Let `constructorDef*` be the list of `constructorDef`, obtained by repeating:
    - Let `constructorDef` be the constructor definition of `externConstructorPrototypeIR` with type parameters `typeParameterListIR` and methods `externMethodPrototypeIR*`.
- for each `externConstructorPrototypeIR` in `externConstructorPrototypeIR*`
- h. Let `IC2` be where each of `callableIdconstructor*` to each of `constructorDef*` are added to `IC1`.
  - i. Result in context `IC2` and store `STO`.

## 11.11. Parser declarations

A `parser` declaration introduces a programmable parser:

```

parserDeclaration
  : annotationList PARSE name typeParameterListOpt `( parameterList )
    constructorParameterListOpt
    `{ parserLocalDeclarationList parserStateList }
  ;

parserLocalDeclaration
  : constantDeclaration
  | instantiation
  | variableDeclaration
  | valueSetDeclaration
  ;

parserState
  : annotationList STATE name `{ parserStatementList transitionStatement }
  ;

```

### 11.11.1. Type checking

After type checking, a parser declaration is represented in `P4IR` as:

```

parserDeclarationIR
  : annotationList PARSE nameIR `< typeParameterListIR , typeParameterListIR >
    `( parameterListIR ) `( constructorParameterListIR )
    `{ parserLocalDeclarationListIR parserStateListIR }
  ;

parserLocalDeclarationIR
  : constantDeclarationIR
  | instantiationIR
  | variableDeclarationIR

```

```

    | valueSetDeclarationIR
    ;

parserStateIR
: annotationList STATE nameIR
  `{ parserStatementListIR transitionStatementIR }
;

```

**Typing** annotationList **PARSER** name typeParameterListOpt ( parameterList ) constructorParameterListOpt { parserLocalDeclarationList parserStateList } **under context**  $TC_0$ :

1. Let  $TC_1$  be  $TC_0$  with **BLOCK.KIND** set to **PARSER**.
2. Let context  $TC_2$  and type parameters  $typeId_{expl}^*$  be
  - the result of **typing** typeParameterListOpt, **under cursor** **BLOCK** and **context**  $TC_1$ .
3. Let context  $TC_3$ ,  $constructorParameterIR^*$ , and a set of fresh type variables  $typeId_{impl}^*$  be
  - the result of **typing** constructorParameterListOpt **under context**  $TC_2$ .
4. Let context  $TC_4$ ,  $parameterIR^*$ , and a set of fresh type variables  $typeId^*$  be
  - the result of **typing** parameterList, **under cursor** **BLOCK** and **context**  $TC_3$ .
5. Check that  $typeId^*$  is an empty list.
6. Let context  $TC_5$  and  $parserLocalDeclarationIR^*$  be
  - the result of **typing** parserLocalDeclarationList, **under context**  $TC_4$ .
7. Let  $TC_6$  be  $TC_5$  with **LOCAL.KIND** set to **PARSER\_STATE**.
8. Let  $parserStateIR^*$  be
  - the result of **typing** parserStateList, **under context**  $TC_6$ .
9. Let  $callableTypeDefIR$  be **PARSER\_APPLY** (  $parameterIR^*$  ).
10. Let **bound** be **bound type variables from the BLOCK layer of**  $TC_2$ .
11. Check that  $callableTypeDefIR$  is a well-formed callable type definition, with bound type variables **bound**.
12. Let  $nameIR$  be **the name of** name.
13. Let  $constructorId$  be **the constructor identifier for** name constructorParameterListOpt.
14. Let  $typeDefIR_{parser}$  be **PARSER**  $nameIR < typeId_{expl}^*, typeId_{impl}^* > (parameterIR^*)$ .
15. Let  $typeIR_{parser}$  be **the underlying type of**  $typeDefIR_{parser}$ .
16. Let  $constructorTypeDefIR$  be **CONSTRUCTOR**  $< typeId_{expl}^*, typeId_{impl}^* > (constructorParameterIR^*) : typeIR_{parser}$ .
17. Let **bound** be **bound type variables from the GLOBAL layer of**  $TC_0$ .
18. Check that  $constructorTypeDefIR$  is a well-formed constructor type definition, with bound type variables **bound**.
19. Let  $TC_7$  be **where**  $constructorId$  **to**  $constructorTypeDefIR$  **is added to**  $TC_0$ .
20. Let  $parserDeclarationIR$  be annotationList **PARSER**  $nameIR < typeId_{expl}^*, typeId_{impl}^* > (parameterIR^*) (constructorParameterIR^*) \{ parserLocalDeclarationIR^* parserStateIR^* \}$ .
21. Result in context  $TC_7$  and  $parserDeclarationIR$ .

## 11.11.2. Compile-time evaluation

At compile-time, parser declarations are loaded into the context as parser object constructors.

**Loading** `annotationList` `PARSER` `nameIR` `< typeParameterListIRexpl , typeParameterListIRimpl > ( parameterListIR ) ( constructorParameterListIR ) { parserLocalDeclarationListIR parserStateListIR }, under context IC0, and store STO:`

1. Let `callableId` be **the callable identifier for** `nameIR` ( `constructorParameterListIR` ).
2. Let `typeParameterListIR` be `typeParameterListIRexpl` concatenated with `typeParameterListIRimpl`.
3. Let `constructorDef` be `PARSER < typeParameterListIR > ( parameterListIR ) ( constructorParameterListIR ) { parserLocalDeclarationListIR parserStateListIR }`.
4. Let `IC1` be **where** `callableId` **to** `constructorDef` **is added to** `IC0`.
5. Result in context `IC1` and store `STO`.

When instantiated, an instance of a parser declaration is created:

```
parserObject
: PARSER `< theta > `( parameterListIR )
  `{ frame parserLocalDeclarationListIR stateEnv }
;
```

See [Section 10.4](#) for details about parser objects.

## 11.12. Control declarations

A **control** declaration introduces a control block:

```
controlDeclaration
: annotationList CONTROL name typeParameterListOpt `( parameterList )
  constructorParameterListOpt
  `{ controlLocalDeclarationList APPLY controlBody }
;

controlLocalDeclaration
: constantDeclaration
| instantiation
| variableDeclaration
| actionDeclaration
| tableDeclaration
;

controlBody = blockStatement
```

### 11.12.1. Type checking

After type checking, a control declaration is represented in `P4IR` as:

```
controlDeclarationIR
: annotationList CONTROL nameIR
  `< typeParameterListIR , typeParameterListIR > `( parameterListIR )
  `( constructorParameterListIR )
  `{ controlLocalDeclarationListIR APPLY controlBodyIR }
;
```

```

controlLocalDeclarationIR
: constantDeclarationIR
| instantiationIR
| variableDeclarationIR
| actionDeclarationIR
| tableDeclarationIR
;

controlBodyIR = blockStatementIR

```

**Typing** annotationList CONTROL name typeParameterListOpt ( parameterList ) constructorParameterListOpt { controlLocalDeclarationList APPLY controlBody } **under context**  $TC_0$ :

1. Let  $TC_1$  be  $TC_0$  with BLOCK.KIND set to CONTROL.
2. Let context  $TC_2$  and type parameters  $typeId_{expl}^*$  be
  - the result of **typing** typeParameterListOpt, **under cursor** BLOCK **and context**  $TC_1$ .
3. Let context  $TC_3$ , constructorParameterIR<sup>\*</sup>, and a set of fresh type variables  $typeId_{impl}^*$  be
  - the result of **typing** constructorParameterListOpt **under context**  $TC_2$ .
4. Let context  $TC_4$ , parameterIR<sup>\*</sup>, and a set of fresh type variables  $typeId^*$  be
  - the result of **typing** parameterList, **under cursor** BLOCK **and context**  $TC_3$ .
5. Check that  $typeId^*$  is an empty list.
6. Let context  $TC_5$  and controlLocalDeclarationIR<sup>\*</sup> be
  - the result of **typing** controlLocalDeclarationList, **under context**  $TC_4$ .
7. Let  $TC_6$  be  $TC_5$  with LOCAL.KIND set to CONTROL\_APPLY\_METHOD.
8. Let context  $\_$ , abstract control flow  $\_$ , and controlBodyIR be
  - the result of **typing** controlBody, **under context**  $TC_6$ , **abstract control flow** CONT, **and loop context** NOLOOP.
9. Let callableTypeDefIR be CONTROL\_APPLY ( parameterIR<sup>\*</sup> ).
10. Let bound be bound type variables from the BLOCK layer of  $TC_2$ .
11. Check that callableTypeDefIR is a well-formed callable type definition, with bound type variables bound.
12. Let nameIR be the name of name.
13. Let constructorId be the constructor identifier for name constructorParameterListOpt.
14. Let typeDefIR<sub>control</sub> be CONTROL nameIR <  $typeId_{expl}^*$ ,  $typeId_{impl}^*$  > ( parameterIR<sup>\*</sup> ).
15. Let typeIR<sub>control</sub> be the underlying type of typeDefIR<sub>control</sub>.
16. Let constructorTypeDefIR be CONSTRUCTOR <  $typeId_{expl}^*$ ,  $typeId_{impl}^*$  > ( constructorParameterIR<sup>\*</sup> ) : typeIR<sub>control</sub>.
17. Let bound be bound type variables from the GLOBAL layer of  $TC_0$ .
18. Check that constructorTypeDefIR is a well-formed constructor type definition, with bound type variables bound.
19. Let  $TC_7$  be where constructorId to constructorTypeDefIR is added to  $TC_0$ .
20. Let controlDeclarationIR be annotationList CONTROL nameIR <  $typeId_{expl}^*$ ,  $typeId_{impl}^*$  > ( parameterIR<sup>\*</sup> ) ( constructorParameterIR<sup>\*</sup> ) { controlLocalDeclarationIR<sup>\*</sup> APPLY controlBodyIR }.
21. Result in context  $TC_7$  and controlDeclarationIR.



## 11.12.2. Compile-time evaluation

At compile-time, control declarations are loaded into the context as control object constructors.

**Loading** annotationList CONTROL nameIR < typeParameterListIR<sub>expl</sub> , typeParameterListIR<sub>impl</sub> > ( parameterListIR ) ( constructorParameterListIR ) { controlLocalDeclarationListIR APPLY controlBodyIR }, under context IC<sub>0</sub>, and store STO:

1. Let callableId be the callable identifier for nameIR ( constructorParameterListIR ).
2. Let typeParameterListIR be typeParameterListIR<sub>expl</sub> concatenated with typeParameterListIR<sub>impl</sub>.
3. Let constructorDef be CONTROL < typeParameterListIR > ( parameterListIR ) ( constructorParameterListIR ) { controlLocalDeclarationListIR APPLY controlBodyIR }.
4. Let IC<sub>1</sub> be where callableId to constructorDef is added to IC<sub>0</sub>.
5. Result in context IC<sub>1</sub> and store STO.

When instantiated, an instance of a control declaration is created:

```
controlObject
: CONTROL `< theta > `( parameterListIR )
  `{ frame controlLocalDeclarationListIR actionDefEnv controlBodyIR }
;
```

See [Section 10.5](#) for details about control objects.

## 11.13. Enum type declaration

An enumeration type is defined using the following syntax:

```
enumTypeDeclaration
: annotationList ENUM name `{ nameList trailingCommaOpt }
| annotationList ENUM type name `{ namedExpressionList trailingCommaOpt }
;

namedExpressionList
: namedExpression
| namedExpressionList , namedExpression
;

namedExpression
: name = expression
;
```

After type checking, enum type declarations are represented as follows:

```
enumTypeDeclarationIR
: annotationList ENUM nameIR `{ nameListIR }
| annotationList ENUM typeIR nameIR `{ namedValueListIR }
;

namedValueListIR = namedValueIR*

namedValueIR
: nameIR = value
```

;

See [Section 8.4.8](#) for more details on enums.

## 11.13.1. Enum type declarations without an underlying type

### 11.13.1.1. Type checking

**Typing** annotationList ENUM name { nameList<sub>field</sub> \_ } under context  $TC_0$ :

1. Let nameIR be the name of name.
2. Let name<sub>field</sub><sup>\*</sup> be the list of names in nameList<sub>field</sub>.
3. Let nameIR<sub>field</sub><sup>\*</sup> be the list of nameIR<sub>field</sub>, obtained by repeating:
  - Let nameIR<sub>field</sub> be the name of name<sub>field</sub>.
 for each name<sub>field</sub> in name<sub>field</sub><sup>\*</sup>
4. Let enumTypeDefIR be ENUM nameIR { nameIR<sub>field</sub><sup>\*</sup> }.
5. Let bound be bound type variables from the GLOBAL layer of  $TC_0$ .
6. Check that enumTypeDefIR is a well-formed type definition, with bound type variables bound.
7. Let  $TC_1$  be  $TC_0$  where nameIR to enumTypeDefIR is added to the GLOBAL layer.
8. Let id<sub>field</sub><sup>\*</sup> be the list of id<sub>field</sub>, obtained by repeating:
  - Let id<sub>field</sub> be nameIR concatenated with "." concatenated with nameIR<sub>field</sub>.
 for each nameIR<sub>field</sub> in nameIR<sub>field</sub><sup>\*</sup>
9. Let value<sub>field</sub><sup>\*</sup> be the list of value<sub>field</sub>, obtained by repeating:
  - Let value<sub>field</sub> be nameIR . nameIR<sub>field</sub>.
 for each nameIR<sub>field</sub> in nameIR<sub>field</sub><sup>\*</sup>
10. Let varTypeIR<sup>\*</sup> be the list of varTypeIR, obtained by repeating:
  - Let varTypeIR be `EMPTY enumTypeDefIR LCTK value<sub>field</sub>.
 for each value<sub>field</sub> in value<sub>field</sub><sup>\*</sup>
11. Let  $TC_2$  be  $TC_1$  where each of id<sub>field</sub><sup>\*</sup> to each of varTypeIR<sup>\*</sup> are added to the GLOBAL layer.
12. Let enumTypeDeclarationIR be annotationList ENUM nameIR { nameIR<sub>field</sub><sup>\*</sup> }.
13. Result in context  $TC_2$  and enumTypeDeclarationIR.

### 11.13.1.2. Compile-time evaluation

At compile-time, enum type declarations are loaded into the context by:

**Loading** annotationList ENUM nameIR { nameIR<sub>field</sub><sup>\*</sup> }, under context  $IC_0$ , and store  $STO$ :

1. Let  $\text{nameIR}_{\text{enum\_field}}^*$  be the list of  $\text{nameIR}_{\text{enum\_field}}$ , obtained by repeating:
  - Let  $\text{nameIR}_{\text{enum\_field}}$  be  $\text{nameIR}$  concatenated with "." concatenated with  $\text{nameIR}_{\text{field}}$ .
 for each  $\text{nameIR}_{\text{field}}$  in  $\text{nameIR}_{\text{field}}^*$
2. Let  $\text{value}_{\text{enum\_field}}^*$  be the list of  $\text{value}_{\text{enum\_field}}$ , obtained by repeating:
  - Let  $\text{value}_{\text{enum\_field}}$  be  $\text{nameIR} . \text{nameIR}_{\text{field}}$ .
 for each  $\text{nameIR}_{\text{field}}$  in  $\text{nameIR}_{\text{field}}^*$
3. Let  $\text{IC}_1$  be  $\text{IC}_0$  where each of  $\text{nameIR}_{\text{enum\_field}}^*$  to each of  $\text{value}_{\text{enum\_field}}^*$  are added to the GLOBAL layer.
4. Let  $\text{enumTypeDefIR}$  be  $\text{ENUM nameIR } \{ \text{nameIR}_{\text{field}}^* \}$ .
5. Let  $\text{IC}_2$  be  $\text{IC}_1$  where  $\text{nameIR}$  to  $\text{enumTypeDefIR}$  is added to the GLOBAL layer.
6. Result in context  $\text{IC}_2$  and store  $\text{STO}$ .

## 11.13.2. Enum type declarations with an underlying type

### 11.13.2.1. Type checking

Typing annotationList ENUM type name { namedExpressionList<sub>field \_</sub> } under context  $\text{TC}_0$ :

1. Let  $\text{B}$  be bound type variables from the GLOBAL layer of  $\text{TC}_0$ .
2. Let  $\text{typeIR}$  and a set of fresh type variables  $\text{typeId}^*$  be
  - the result of typing type, under cursor GLOBAL and context  $\text{TC}_0$ .
3. Check that  $\text{typeId}^*$  is an empty list.
4. Check that  $\text{typeIR}$  is a well-formed type, with bound type variables  $\text{B}$ .
5. Let  $\text{nameIR}$  be the name of name.
6. Let the updated typing context  $\text{TC}_1$  and field values  $\text{namedValueIR}_{\text{field}}^*$  be
  - the result of typing namedExpressionList<sub>field</sub> under typing context  $\text{TC}_0$  with enum name  $\text{nameIR}$  and underlying  $\text{typeIR}$ .
7. Let  $\text{nameIR}_{\text{field}}^*$  be the list of  $\text{nameIR}_{\text{field}}$  and  $\text{value}_{\text{field}}^*$  be the list of  $\text{value}_{\text{field}}$ , obtained by repeating:
  - Let  $\text{nameIR}_{\text{field}} = \text{value}_{\text{field}}$  be  $\text{namedValueIR}_{\text{field}}$ .
 for each  $\text{namedValueIR}_{\text{field}}$  in  $\text{namedValueIR}_{\text{field}}^*$
8. Let  $\text{id}_{\text{field}}^*$  be the list of  $\text{id}_{\text{field}}$ , obtained by repeating:
  - Let  $\text{id}_{\text{field}}$  be  $\text{nameIR}$  concatenated with "." concatenated with  $\text{nameIR}_{\text{field}}$ .
 for each  $\text{nameIR}_{\text{field}}$  in  $\text{nameIR}_{\text{field}}^*$
9. Let  $\text{enumTypeDefIR}$  be  $\text{ENUM nameIR } < \text{typeIR} > \{ ( \text{nameIR}_{\text{field}} = \text{value}_{\text{field}} ; )^* \}$ .
10. Let  $\text{varTypeIR}^*$  be the list of  $\text{varTypeIR}$ , obtained by repeating:
  - Let  $\text{varTypeIR}$  be 'EMPTY enumTypeDefIR LCTK  $\text{value}_{\text{field}}$ '.

for each  $value_{field}$  in  $value_{field}^*$

11. Let  $TC_2$  be  $TC_0$  where each of  $id_{field}^*$  to each of  $varTypeIR^*$  are added to the GLOBAL layer.
12. Check that  $enumTypeDefIR$  is a well-formed type definition, with bound type variables  $B$ .
13. Let  $TC_3$  be  $TC_2$  where  $nameIR$  to  $enumTypeDefIR$  is added to the GLOBAL layer.
14. Let  $enumTypeDeclarationIR$  be  $annotationList\ ENUM\ typeIR\ nameIR\ \{ namedValueIR_{field}^* \}$ .
15. Result in context  $TC_3$  and  $enumTypeDeclarationIR$ .

An enum field is type-checked as follows:

**Enum\_serializable\_field\_ok:**

- Typing  $namedExpression$  under typing context  $typingContext$  with enum name  $nameIR$  and underlying  $typeIR$ :
- Result in the updated typing context  $typingContext$ , and field value  $namedValueIR$ .

**Typing**  $name = expression$  under typing context  $TC_0$  with enum name  $nameIR_{enum}$  and underlying  $typeIR$ :

1. Let  $typedExpressionIR$  be
  - the result of typing  $expression$ , under cursor **BLOCK** and context  $TC_0$ .
2. Let  $typedExpressionIR_{cast}$  be  $!$   $typedExpressionIR$  implicitly cast to  $typeIR$ .
3. Check that the compile-time known-ness of  $typedExpressionIR_{cast}$  is LCTK.
4. Let  $value$  be
  - the result of local compile-time evaluation of  $typedExpressionIR_{cast}$  under cursor **BLOCK** and context  $TC_0$ .
5. Let  $nameIR$  be the name of  $name$ .
6. Let  $varTypeIR$  be  $\text{EMPTY typeIR LCTK value}$ .
7. Let  $TC_1$  be  $TC_0$  where  $nameIR$  to  $varTypeIR$  is added to the **BLOCK** layer.
8. Result in the updated typing context  $TC_1$ , and field value  $nameIR = value$ .

A list of enum fields is type-checked with the following relation:

**Enum\_serializable\_fieldList\_ok:**

- Typing  $namedExpressionList$  under typing context  $typingContext$  with enum name  $nameIR$  and underlying  $typeIR$ :
- Result in the updated typing context  $typingContext$  and field values  $namedValueIR^*$ .

### 11.13.2.2. Compile-time evaluation

At compile-time, enum type declarations are loaded into the context by:

**Loading**  $annotationList\ ENUM\ typeIR\ nameIR\ \{ ( nameIR_{field} = value_{field} )^* \}$ , under context  $IC_0$ , and store  $STO$ :

1. Let  $\text{nameIR}_{\text{serenum\_field}}^*$  be the list of  $\text{nameIR}_{\text{serenum\_field}}$ , obtained by repeating:
  - Let  $\text{nameIR}_{\text{serenum\_field}}$  be  $\text{nameIR}$  concatenated with "." concatenated with  $\text{nameIR}_{\text{field}}$ .
 for each  $\text{nameIR}_{\text{field}}$  in  $\text{nameIR}_{\text{field}}^*$
2. Let  $\text{value}_{\text{serenum\_field}}^*$  be the list of  $\text{value}_{\text{serenum\_field}}$ , obtained by repeating:
  - Let  $\text{value}_{\text{serenum\_field}}$  be  $\text{nameIR} . \text{nameIR}_{\text{field}} . \text{value}_{\text{field}}$ .
 for each  $\text{nameIR}_{\text{field}}$  in  $\text{nameIR}_{\text{field}}^*$  and  $\text{value}_{\text{field}}$  in  $\text{value}_{\text{field}}^*$
3. Let  $\text{IC}_1$  be  $\text{IC}_0$  where each of  $\text{nameIR}_{\text{serenum\_field}}^*$  to each of  $\text{value}_{\text{serenum\_field}}^*$  are added to the GLOBAL layer.
4. Let  $\text{enumTypeDefIR}$  be  $\text{ENUM nameIR} < \text{typeIR} > \{ ( \text{nameIR}_{\text{field}} = \text{value}_{\text{field}} ; )^* \}$ .
5. Let  $\text{IC}_2$  be  $\text{IC}_1$  where  $\text{nameIR}$  to  $\text{enumTypeDefIR}$  is added to the GLOBAL layer.
6. Result in context  $\text{IC}_2$  and store  $\text{STO}$ .

## 11.14. Struct type declaration

A struct type is defined with the following syntax:

```
structTypeDeclaration
: annotationList STRUCT name typeParameterListOpt `{ typeFieldList }
;

typeFieldList
: /* empty */
| typeFieldList typeField
;

typeField
: annotationList type name ;
;
```

See [Section 8.4.5](#) for more information about struct types.

### 11.14.1. Type checking

After type checking, a struct type declaration is represented in  $\text{P4}_{\text{IR}}$  as:

```
structTypeDeclarationIR
: annotationList STRUCT nameIR `< typeParameterListIR > `{ typeFieldListIR }
;

typeFieldListIR = typeFieldIR*

typeFieldIR
: annotationList typeIR nameIR ;
;
```

**Typing** annotationList STRUCT name typeParameterListOpt { typeFieldList } under context  $\text{TC}_0$ :

1. Let context  $\text{TC}_1$  and type parameters  $\text{typeId}^*$  be

- the result of **typing**  $\text{typeParameterListOpt}$ , **under cursor** **BLOCK** and **context**  $\text{TC}_0$ .
2. Let  $(\text{annotationList}_{\text{field}} \text{ type}_{\text{field}} \text{ name}_{\text{field}} ;)^*$  be the list of type fields in  $\text{typeFieldList}$ .
  3. Let  $\text{typeIR}_{\text{field}}^*$  be the list of  $\text{typeIR}_{\text{field}}$  and  $\text{typeId}^{**}$  be the list of  $\text{typeId}^*$ , obtained by repeating:
    - Let  $\text{typeIR}_{\text{field}}$  and a set of fresh type variables  $\text{typeId}^*$  be
      - the result of **typing**  $\text{type}_{\text{field}}$ , **under cursor** **BLOCK** and **context**  $\text{TC}_1$ .
 for each  $\text{type}_{\text{field}}$  in  $\text{typeField}^*$
  4. Check that  $\text{typeId}^*$  is an empty list, for all  $\text{typeId}^*$  in  $\text{typeId}^{**}$ .
  5. Let  $\text{nameIR}$  be the name of  $\text{name}$ .
  6. Let  $\text{nameIR}_{\text{field}}^*$  be the list of  $\text{nameIR}_{\text{field}}$ , obtained by repeating:
    - Let  $\text{nameIR}_{\text{field}}$  be the name of  $\text{name}_{\text{field}}$ .
 for each  $\text{name}_{\text{field}}$  in  $\text{nameField}^*$
  7. Let  $\text{structTypeDefIR}$  be **STRUCT**  $\text{nameIR} < \text{typeId}^* > \{ (\text{annotationList}_{\text{field}} \text{ typeIR}_{\text{field}} \text{ nameIR}_{\text{field}} ;)^* \}$ .
  8. Let **bound** be **bound type variables from the GLOBAL layer of**  $\text{TC}_0$ .
  9. Check that  $\text{structTypeDefIR}$  is a well-formed type definition, with bound type variables **bound**.
  10. Let  $\text{TC}_2$  be  $\text{TC}_0$  **where**  $\text{nameIR}$  **to**  $\text{structTypeDefIR}$  **is added to the GLOBAL layer**.
  11. Let  $\text{structTypeDeclarationIR}$  be **annotationList** **STRUCT**  $\text{nameIR} < \text{typeId}^* > \{ (\text{annotationList}_{\text{field}} \text{ typeIR}_{\text{field}} \text{ nameIR}_{\text{field}} ;)^* \}$ .
  12. Result in context  $\text{TC}_2$  and  $\text{structTypeDeclarationIR}$ .

### 11.14.2. Compile-time evaluation

At compile-time, struct type declarations are loaded into the context by:

**Loading**  $\text{annotationList}$  **STRUCT**  $\text{nameIR} < \text{typeParameterListIR} > \{ \text{typeFieldIR}^* \}$ , **under context**  $\text{IC}_0$ , and **store**  $\text{STO}$ :

1. Let  $\text{annotationList}_{\text{field}}^*$  be the list of  $\text{annotationList}_{\text{field}}$ ,  $\text{nameIR}_{\text{field}}^*$  be the list of  $\text{nameIR}_{\text{field}}$ , and  $\text{typeIR}_{\text{field}}^*$  be the list of  $\text{typeIR}_{\text{field}}$ , obtained by repeating:
  - Let  $\text{annotationList}_{\text{field}} \text{ typeIR}_{\text{field}} \text{ nameIR}_{\text{field}} ;$  be  $\text{typeFieldIR}$ .
 for each  $\text{typeFieldIR}$  in  $\text{typeFieldIR}^*$
2. Let  $\text{structTypeDefIR}$  be **STRUCT**  $\text{nameIR} < \text{typeParameterListIR} > \{ (\text{annotationList}_{\text{field}} \text{ typeIR}_{\text{field}} \text{ nameIR}_{\text{field}} ;)^* \}$ .
3. Let  $\text{IC}_1$  be  $\text{IC}_0$  **where**  $\text{nameIR}$  **to**  $\text{structTypeDefIR}$  **is added to the GLOBAL layer**.
4. Result in context  $\text{IC}_1$  and store  $\text{STO}$ .

### 11.15. Header type declaration

A header type is defined with the following syntax:

```

headerTypeDeclaration
  : annotationList HEADER name typeParameterListOpt `{ typeFieldList }
  ;

typeFieldList
  : /* empty */
  | typeFieldList typeField
  ;

typeField
  : annotationList type name ;
  ;

```

See [Section 8.4.6](#) for more information about header types.

### 11.15.1. Type checking

After type checking, a header type declaration is represented in  $P4_{IR}$  as:

```

headerTypeDeclarationIR
  : annotationList HEADER nameIR `< typeParameterListIR > `{ typeFieldListIR }
  ;

typeFieldListIR = typeFieldIR*

typeFieldIR
  : annotationList typeIR nameIR ;
  ;

```

**Typing** annotationList HEADER name typeParameterListOpt { typeFieldList } **under context**  $TC_0$ :

1. Let context  $TC_1$  and type parameters  $typed^*$  be
  - the result of **typing** typeParameterListOpt, **under cursor** BLOCK **and context**  $TC_0$ .
2. Let ( annotationList<sub>*f*</sub> type<sub>*f*</sub> name<sub>*f*</sub> ; )<sup>\*</sup> be the list of type fields in typeFieldList.
3. Let  $typedR_f^*$  be the list of  $typedR_f$  and  $typed^{**}$  be the list of  $typed^*$ , obtained by repeating:
  - Let  $typedR_f$  and a set of fresh type variables  $typed^*$  be
    - the result of **typing** type<sub>*f*</sub>, **under cursor** BLOCK **and context**  $TC_1$ .

for each type<sub>*f*</sub> in type<sub>*f*</sub><sup>\*</sup>
4. Check that  $typed^*$  is an empty list, for all  $typed^*$  in  $typed^{**}$ .
5. Let nameIR be the name of name.
6. Let  $nameIR_f^*$  be the list of  $nameIR_f$ , obtained by repeating:
  - Let  $nameIR_f$  be the name of name<sub>*f*</sub>.

for each name<sub>*f*</sub> in name<sub>*f*</sub><sup>\*</sup>
7. Let headerTypeDefIR be HEADER nameIR < typed<sup>\*</sup> > { ( annotationList<sub>*f*</sub> typedR<sub>*f*</sub> nameIR<sub>*f*</sub> ; )<sup>\*</sup> }.
8. Let bound be bound type variables from the GLOBAL layer of  $TC_0$ .
9. Check that headerTypeDefIR is a well-formed type definition, with bound type variables bound.

10. Let  $TC_2$  be  $TC_0$  where  $nameIR$  to  $headerTypeDefIR$  is added to the GLOBAL layer.
11. Let  $headerTypeDeclarationIR$  be  $annotationList\ HEADER\ nameIR\ <\ typeId^* >\{ (\ annotationList_f\ typeIR_f\ nameIR_f ; )^*\}$ .
12. Result in context  $TC_2$  and  $headerTypeDeclarationIR$ .

## 11.15.2. Compile-time evaluation

At compile-time, header type declarations are loaded into the context by:

Loading  $annotationList\ HEADER\ nameIR\ <\ typeParameterListIR >\{ typeFieldIR^*\}$ , under context  $IC_0$ , and store  $STO$ :

1. Let  $annotationList_{field}^*$  be the list of  $annotationList_{field}$ ,  $nameIR_{field}^*$  be the list of  $nameIR_{field}$ , and  $typeIR_{field}^*$  be the list of  $typeIR_{field}$ , obtained by repeating:
  - Let  $annotationList_{field}\ typeIR_{field}\ nameIR_{field} ;$  be  $typeFieldIR$ .
 for each  $typeFieldIR$  in  $typeFieldIR^*$
2. Let  $headerTypeDefIR$  be  $HEADER\ nameIR\ <\ typeParameterListIR >\{ (\ annotationList_{field}\ typeIR_{field}\ nameIR_{field} ; )^*\}$ .
3. Let  $IC_1$  be  $IC_0$  where  $nameIR$  to  $headerTypeDefIR$  is added to the GLOBAL layer.
4. Result in context  $IC_1$  and store  $STO$ .

## 11.16. Header union type declaration

A header union type is defined with the following syntax:

```
headerUnionTypeDeclaration
: annotationList HEADER_UNION name typeParameterListOpt `{ typeFieldList }
;

typeFieldList
: /* empty */
| typeFieldList typeField
;

typeField
: annotationList type name ;
;
```

See [Section 8.4.7](#) for more information about header union types.

### 11.16.1. Type checking

After type checking, a header union type declaration is represented in  $P4_{IR}$  as:

```
headerUnionTypeDeclarationIR
: annotationList HEADER_UNION nameIR `< typeParameterListIR >
  `{ typeFieldListIR }
;

typeFieldListIR = typeFieldIR*
```



```

typeFieldIR
: annotationList typeIR nameIR ;
;

```

**Typing** annotationList HEADER\_UNION name typeParameterListOpt { typeFieldList } **under context**  $TC_0$ :

1. Let context  $TC_1$  and type parameters  $typed^*$  be
  - the result of **typing** typeParameterListOpt, **under cursor** BLOCK **and context**  $TC_0$ .
2. Let ( annotationList <sub>$f$</sub>  type <sub>$f$</sub>  name <sub>$f$</sub>  ; )<sup>\*</sup> be the list of type fields in typeFieldList.
3. Let  $typeIR_f^*$  be the list of  $typeIR_f$  and  $typed^{**}$  be the list of  $typed^*$ , obtained by repeating:
  - Let  $typeIR_f$  and a set of fresh type variables  $typed^*$  be
    - the result of **typing** type <sub>$f$</sub> , **under cursor** BLOCK **and context**  $TC_1$ .

for each type <sub>$f$</sub>  in type <sub>$f$</sub> <sup>\*</sup>
4. Check that  $typed^*$  is an empty list, for all  $typed^*$  in  $typed^{**}$ .
5. Let nameIR be the name of name.
6. Let  $nameIR_f^*$  be the list of  $nameIR_f$ , obtained by repeating:
  - Let  $nameIR_f$  be the name of name <sub>$f$</sub> .

for each name <sub>$f$</sub>  in name <sub>$f$</sub> <sup>\*</sup>
7. Let headerUnionTypeDefIR be HEADER\_UNION nameIR <  $typed^*$  > { ( annotationList <sub>$f$</sub>   $typeIR_f$   $nameIR_f$  ; )<sup>\*</sup> }.
8. Let bound be bound type variables from the GLOBAL layer of  $TC_0$ .
9. Check that headerUnionTypeDefIR is a well-formed type definition, with bound type variables bound.
10. Let  $TC_2$  be  $TC_0$  where nameIR to headerUnionTypeDefIR is added to the GLOBAL layer.
11. Let headerUnionTypeDeclarationIR be annotationList HEADER\_UNION nameIR <  $typed^*$  > { ( annotationList <sub>$f$</sub>   $typeIR_f$   $nameIR_f$  ; )<sup>\*</sup> }.
12. Result in context  $TC_2$  and headerUnionTypeDeclarationIR.

## 11.16.2. Compile-time evaluation

At compile-time, header union type declarations are loaded into the context by:

**Loading** annotationList HEADER\_UNION nameIR < typeParameterListIR > { typeFieldIR<sup>\*</sup> }, **under context**  $IC_0$ , **and store** STO:

1. Let  $annotationList_{field}^*$  be the list of  $annotationList_{field}$ ,  $nameIR_{field}^*$  be the list of  $nameIR_{field}$ , and  $typeIR_{field}^*$  be the list of  $typeIR_{field}$ , obtained by repeating:
  - Let  $annotationList_{field}$   $typeIR_{field}$   $nameIR_{field}$  ; be typeFieldIR.

for each typeFieldIR in typeFieldIR<sup>\*</sup>
2. Let headerUnionTypeDefIR be HEADER\_UNION nameIR < typeParameterListIR > { (  $annotationList_{field}$   $typeIR_{field}$

$\text{nameIR}_{\text{field}} ; )^* \}$ .

3. Let  $\text{IC}_1$  be  $\text{IC}_0$  where  $\text{nameIR}$  to  $\text{headerUnionTypeDefIR}$  is added to the GLOBAL layer.
4. Result in context  $\text{IC}_1$  and store  $\text{STO}$ .

## 11.17. Typedef declaration

A **typedef** or **type** declaration introduces an alias for an existing type.

```
typedef
  : type
  | derivedTypeDeclaration
  ;

typedefDeclaration
  : annotationList TYPEDEF typedef name ;
  | annotationList TYPE type name ;
  ;
```

In  $\text{P4}_{\text{IR}}$ , **typedef** and **type** declarations are represented as:

```
typedefIR
  : typeIR
  | derivedTypeDeclarationIR
  ;

typedefDeclarationIR
  : annotationList TYPEDEF typedefIR nameIR ;
  | annotationList TYPE typeIR nameIR ;
  ;
```

### 11.17.1. typedef declaration

See [Section 8.5.7](#) for more details about **typedef** aliases.

#### 11.17.1.1. Type checking

**Typing**  $\text{annotationList TYPEDEF typedef name ;}$  under context  $\text{TC}_0$ :

1. If let **type** be **typedef**:
  - a. Let **B** be **bound type variables from the GLOBAL layer of  $\text{TC}_0$** .
  - b. Let  $\text{typeIR}$  and a set of fresh type variables  $\text{typeId}^*$  be
    - the result of **typing type, under cursor GLOBAL and context  $\text{TC}_0$** .
  - c. Check that  $\text{typeId}^*$  is an empty list.
  - d. Check that  $\text{typeIR}$  is a well-formed type, with bound type variables **B**.
  - e. Let  $\text{nameIR}$  be **the name of name**.
  - f. Let  $\text{typeDefIR}_{\text{typedef}}$  be **TYPEDEF  $\text{nameIR}$   $\text{typeIR}$** .
  - g. Check that  $\text{typeDefIR}_{\text{typedef}}$  is a well-formed type definition, with bound type variables **B**.
  - h. Let  $\text{TC}_1$  be  $\text{TC}_0$  where  $\text{nameIR}$  to  $\text{typeDefIR}_{\text{typedef}}$  is added to the GLOBAL layer.

- i. Let `typedefDeclarationIR` be `annotationList TYPEDEF typeIR nameIR ;`.
  - j. Result in context  $TC_1$  and `typedefDeclarationIR`.
2. Else:
- a. Let `derivedTypeDeclaration` be `typedef`.
  - b. Let context  $TC_1$  and `declarationIR` be
    - the result of `typing` `derivedTypeDeclaration` under context  $TC_0$ .
  - c. Check that `declarationIR` has type `derivedTypeDeclarationIR`.
  - d. Let `derivedTypeDeclarationIR` be `declarationIR`.
  - e. Let `set<typeId>` be the domain of the map  $TC_1.GLOBAL.TYPE$ .
  - f. Let `set<typeId>'` be the domain of the map  $TC_0.GLOBAL.TYPE$ .
  - g. Let `{ typeId* }` be the difference of the sets `set<typeId>` and `set<typeId>'`.
  - h. Check that `typeId*` is a list of length 1.
    - i. Let `typeId'` be `typeId*`.
    - j. Let `typeDefIR'` be ! the type definition of `typeId'` from the GLOBAL layer of  $TC_1$ .
  - k. If `typeDefIR'` is monomorphic:
    - i. Let `typeIR` be the underlying type of `typeDefIR'`.
    - ii. Let `nameIR` be the name of `name`.
    - iii. Let `typedefTypeIR` be `TYPEDEF nameIR typeIR`.
    - iv. Let `bound` be bound type variables from the GLOBAL layer of  $TC_0$ .
    - v. Check that `typedefTypeIR` is a well-formed type definition, with bound type variables `bound`.
    - vi. Let  $TC_2$  be  $TC_0$  where `nameIR` to `typedefTypeIR` is added to the GLOBAL layer.
    - vii. Let `typedefDeclarationIR` be `annotationList TYPEDEF derivedTypeDeclarationIR nameIR ;`.
    - viii. Result in context  $TC_1$  and `typedefDeclarationIR`.
  - l. Else:
    - i. Check that `( · , · )` is equal to the type parameters of `typeDefIR'`.
    - ii. Let `nameIR` be the name of `name`.
    - iii. Let `typeIR` be `typeDefIR'` specialized by `·`.
    - iv. Let `typedefTypeIR` be `TYPEDEF nameIR typeIR`.
    - v. Let `bound` be bound type variables from the GLOBAL layer of  $TC_0$ .
    - vi. Check that `typedefTypeIR` is a well-formed type definition, with bound type variables `bound`.
    - vii. Let  $TC_2$  be  $TC_0$  where `nameIR` to `typedefTypeIR` is added to the GLOBAL layer.
    - viii. Let `typedefDeclarationIR` be `annotationList TYPEDEF derivedTypeDeclarationIR nameIR ;`.
    - ix. Result in context  $TC_1$  and `typedefDeclarationIR`.

### 11.17.1.2. Compile-time evaluation

At compile-time, `typedefs` are loaded into the context with:

**Loading** annotationList TYPEDEF typedefIR nameIR ; under context  $IC_0$ , and store  $STO$ :

1. If let typeIR be typedefIR:
  - a. Let aliasTypeDefIR be TYPEDEF nameIR typeIR.
  - b. Let  $IC_1$  be  $IC_0$  where nameIR to aliasTypeDefIR is added to the GLOBAL layer.
  - c. Result in context  $IC_1$  and store  $STO$ .
2. Else:
  - a. Let derivedTypeDeclarationIR be typedefIR.
  - b. Let context  $IC_{local}$  and store  $_$  be
    - the result of loading derivedTypeDeclarationIR, under context  $IC_0$ , and store an empty store.
  - c. Let set<typed> be the domain of the map  $IC_{local}.GLOBAL.TYPE$ .
  - d. Let set<typed>' be the domain of the map  $IC_0.GLOBAL.TYPE$ .
  - e. Let { typed\* } be the difference of the sets set<typed> and set<typed>'.
  - f. Check that typed\* is a list of length 1.
  - g. Let typed<sub>newtype</sub> be typed\*.
  - h. Let typeDefIR' be ! the type definition of . typed<sub>newtype</sub> from the GLOBAL layer of  $IC_{local}$ .
  - i. If typeDefIR' is monomorphic:
    - i. Let typeIR be the underlying type of typeDefIR'.
    - ii. Let aliasTypeDefIR be TYPEDEF nameIR typeIR.
    - iii. Let  $IC_1$  be  $IC_0$  where nameIR to aliasTypeDefIR is added to the GLOBAL layer.
    - iv. Result in context  $IC_1$  and store  $STO$ .
  - j. Else:
    - i. Check that ( ·, · ) is equal to the type parameters of typeDefIR'.
    - ii. Let typeIR be typeDefIR' specialized by ·.
    - iii. Let typedefTypeIR be TYPEDEF nameIR typeIR.
    - iv. Let  $IC_1$  be  $IC_0$  where nameIR to typedefTypeIR is added to the GLOBAL layer.
    - v. Result in context  $IC_1$  and store  $STO$ .

## 11.17.2. New type declaration

See Section 8.5.8 for more details about new type aliases.

### 11.17.2.1. Type checking

**Typing** annotationList TYPE type name ; under context  $TC_0$ :

1. Let B be bound type variables from the GLOBAL layer of  $TC_0$ .
2. Let typeIR and a set of fresh type variables typed\* be
  - the result of typing type, under cursor GLOBAL and context  $TC_0$ .
3. Check that typed\* is an empty list.

4. Check that `typeIR` is a well-formed type, with bound type variables `B`.
5. Let `nameIR` be the name of `name`.
6. Let `newTypeIR` be `TYPE nameIR typeIR`.
7. Check that `newTypeIR` is a well-formed type definition, with bound type variables `B`.
8. Let `TC1` be `TC0` where `nameIR` to `newTypeIR` is added to the GLOBAL layer.
9. Let `typedefDeclarationIR` be `annotationList TYPE typeIR nameIR ;`.
10. Result in context `TC1` and `typedefDeclarationIR`.

### 11.17.2.2. Compile-time evaluation

At compile-time, types are loaded into the context with:

Loading `annotationList TYPE typeIR nameIR ;`, under context `IC0`, and store `STO`:

1. Let `aliasTypeDefIR` be `TYPE nameIR typeIR`.
2. Let `IC1` be `IC0` where `nameIR` to `aliasTypeDefIR` is added to the GLOBAL layer.
3. Result in context `IC1` and store `STO`.

## 11.18. Parser type declaration

A parser type declaration introduces a new parser type.

```
parserTypeDeclaration
: annotationList PARSE name typeParameterListOpt `( parameterList ) ;
;
```

See [Section 8.5.2](#) for more details on parser object types.

### 11.18.1. Type checking

After type checking, a parser type declaration has the following form:

```
parserTypeDeclarationIR
: annotationList PARSE nameIR `< typeParameterListIR , typeParameterListIR >
  `( parameterListIR ) ;
;
```

Typing `annotationList PARSE name typeParameterListOpt ( parameterList ) ;` under context `TC0`:

1. Let `TC1` be `TC0` with `BLOCK.KIND` set to `PARSER`.
2. Let context `TC2` and type parameters `typeIdexpl*` be
  - the result of typing `typeParameterListOpt`, under cursor `BLOCK` and context `TC1`.
3. Let context `TC3`, `parameterIR*`, and a set of fresh type variables `typeIdimpl*` be
  - the result of typing `parameterList`, under cursor `BLOCK` and context `TC2`.

4. Let `nameIR` be the name of `name`.
5. Let `parserObjectTypeDefIR` be `PARSER nameIR < typeIdexpl*, typeIdimpl* > ( parameterIR* )`.
6. Let `bound` be bound type variables from the GLOBAL layer of `TC0`.
7. Check that `parserObjectTypeDefIR` is a well-formed type definition, with bound type variables `bound`.
8. Let `TC4` be `TC0` where `nameIR` to `parserObjectTypeDefIR` is added to the GLOBAL layer.
9. Let `parserTypeDeclarationIR` be `annotationList PARSER nameIR < typeIdexpl*, typeIdimpl* > ( parameterIR* ) ;`.
10. Result in context `TC4` and `parserTypeDeclarationIR`.

## 11.18.2. Compile-time evaluation

At compile-time, a parser type declaration is loaded into the context with:

Loading `annotationList PARSER nameIR < typeParameterListIR , typeParameterListIRinferred > ( parameterIR* ) ;`, under context `IC0`, and store `STO`:

1. Let `parserObjectTypeDefIR` be `PARSER nameIR < typeParameterListIR , typeParameterListIRinferred > ( parameterIR* )`.
2. Let `IC1` be `IC0` where `nameIR` to `parserObjectTypeDefIR` is added to the GLOBAL layer.
3. Result in context `IC1` and store `STO`.

## 11.19. Control type declaration

A control type declaration introduces a new control type.

```
controlTypeDeclaration
: annotationList CONTROL name typeParameterListOpt `( parameterList ) ;
;
```

See [Section 8.5.3](#) for more details on control object types.

### 11.19.1. Type checking

After type checking, a control type declaration has the following form:

```
controlTypeDeclarationIR
: annotationList CONTROL nameIR
  < typeParameterListIR , typeParameterListIR > `( parameterListIR ) ;
;
```

Typing `annotationList CONTROL name typeParameterListOpt ( parameterList ) ;` under context `TC0`:

1. Let `TC1` be `TC0` with `BLOCK.KIND` set to `CONTROL`.
2. Let context `TC2` and type parameters `typeIdexpl*` be
  - the result of typing `typeParameterListOpt`, under cursor `BLOCK` and context `TC1`.

3. Let context  $TC_3$ ,  $parameterIR^*$ , and a set of fresh type variables  $typed_{impl}^*$  be
  - the result of typing  $parameterList$ , under cursor BLOCK and context  $TC_2$ .
4. Let  $nameIR$  be the name of  $name$ .
5. Let  $controlObjectTypeDefIR$  be  $CONTROL\ nameIR < typed_{expl}^*, typed_{impl}^* > (parameterIR^*)$ .
6. Let  $bound$  be bound type variables from the GLOBAL layer of  $TC_0$ .
7. Check that  $controlObjectTypeDefIR$  is a well-formed type definition, with bound type variables  $bound$ .
8. Let  $TC_4$  be  $TC_0$  where  $nameIR$  to  $controlObjectTypeDefIR$  is added to the GLOBAL layer.
9. Let  $controlTypeDeclarationIR$  be  $annotationList\ CONTROL\ nameIR < typed_{expl}^*, typed_{impl}^* > (parameterIR^*) ;$ .
10. Result in context  $TC_4$  and  $controlTypeDeclarationIR$ .

### 11.19.2. Compile-time evaluation

At compile-time, a control type declaration is loaded into the context with:

Loading  $annotationList\ CONTROL\ nameIR < typeParameterListIR, typeParameterListIR_{inferred} > (parameterIR^*) ;$ , under context  $IC_0$ , and store  $STO$ :

1. Let  $controlObjectTypeDefIR$  be  $CONTROL\ nameIR < typeParameterListIR, typeParameterListIR_{inferred} > (parameterIR^*)$ .
2. Let  $IC_1$  be  $IC_0$  where  $nameIR$  to  $controlObjectTypeDefIR$  is added to the GLOBAL layer.
3. Result in context  $IC_1$  and store  $STO$ .

## 11.20. Package type declaration

A package type declaration introduces a new package type.

```
packageTypeDeclaration
: annotationList PACKAGE name typeParameterListOpt `( parameterList ) ;
;
```

See [Section 8.5.4](#) for more details on package object types.

### 11.20.1. Type checking

After type checking, a package type declaration has the following form:

```
packageTypeDeclarationIR
: annotationList PACKAGE nameIR
  `< typeParameterListIR, typeParameterListIR > `( parameterListIR ) ;
;
```

Typing  $annotationList\ PACKAGE\ name\ typeParameterListOpt\ (parameterList) ;$  under context  $TC_0$ :

1. Let  $B$  be bound type variables from the GLOBAL layer of  $TC_0$ .

2. Let  $TC_1$  be  $TC_0$  with `BLOCK.KIND` set to `PACKAGE`.
3. Let context  $TC_2$  and type parameters  $typeId_{expl}^*$  be
  - the result of `typing typeParameterListOpt`, under cursor `BLOCK` and context  $TC_1$ .
4. Let context  $TC_3$ , `constructorParameterIR*`, and a set of fresh type variables  $typeId_{impl}^*$  be
  - the result of `typing ( parameterList )` under context  $TC_2$ .
5. Let `nameIR` be the name of `name`.
6. Let  $typeIR_{package\_inner}^*$  be the list of  $typeIR_{package\_inner}$ , obtained by repeating:
  - Let  $typeIR_{package\_inner}$  be the type of `constructorParameterIR`.
 for each `constructorParameterIR` in `constructorParameterIR*`
7. Let `packageObjectTypeDefIR` be `PACKAGE nameIR < typeIdexpl*, typeIdimpl* > { typeIRpackage\_inner* }`.
8. Check that `packageObjectTypeDefIR` is a well-formed type definition, with bound type variables `B`.
9. Let  $TC_4$  be  $TC_0$  where `nameIR` to `packageObjectTypeDefIR` is added to the `GLOBAL` layer.
10. Let `constructorId` be the constructor identifier for `name ( parameterList )`.
11. Let  $typeIR_{package}$  be the underlying type of `packageObjectTypeDefIR`.
12. Let `constructorTypeDefIR` be `CONSTRUCTOR < typeIdexpl*, typeIdimpl* > ( constructorParameterIR* ) : typeIRpackage`.
13. Check that `constructorTypeDefIR` is a well-formed constructor type definition, with bound type variables `B`.
14. Let  $TC_5$  be where `constructorId` to `constructorTypeDefIR` is added to  $TC_4$ .
15. Let `packageTypeDeclarationIR` be `annotationList PACKAGE nameIR < typeIdexpl*, typeIdimpl* > ( constructorParameterIR* ) ;`.
16. Result in context  $TC_5$  and `packageTypeDeclarationIR`.

## 11.20.2. Compile-time evaluation

At compile-time, a package type declaration is loaded into the context with:

**Loading** `annotationList PACKAGE nameIR < typeParameterListIR , typeParameterListIRinferred > ( parameterIR* ) ;`, under context  $IC_0$ , and store `STO`:

1. Let  $typeIR^*$  be the list of  $typeIR$ , obtained by repeating:
  - Let  $typeIR$  be the type of `parameterIR`.
 for each `parameterIR` in `parameterIR*`
2. Let `packageObjectTypeDefIR` be `PACKAGE nameIR < typeParameterListIR , typeParameterListIRinferred > { typeIR* }`.
3. Let  $IC_1$  be  $IC_0$  where `nameIR` to `packageObjectTypeDefIR` is added to the `GLOBAL` layer.
4. Let `callableId` be the callable identifier for `nameIR ( parameterIR* )`.
5. Let `constructorDef` be `PACKAGE < typeParameterListIR ++ typeParameterListIRinferred > ( parameterIR* )`.
6. Let  $IC_2$  be where `callableId` to `constructorDef` is added to  $IC_1$ .
7. Result in context  $IC_2$  and store `STO`.



## 12. L-values

L-values are expressions that may appear on the left side of an assignment operation or as arguments corresponding to `out` and `inout` function parameters. An l-value represents a storage reference. The following expressions are legal l-values:

```
lvalue
: referenceExpression
| lvalue . member
| lvalue `[ expression ]
| lvalue `[ expression : expression ]
| `( lvalue )
;
```

- Identifiers of a base or derived type.
- Structure, header, and header union field member access operations (using the dot notation).
- References to elements within header stacks (see [Section 8.4.3](#)): indexing, and references to `last` and `next`.
- The result of a bit-slice operator `[m:l]`.

The following is a legal l-value: `headers.stack[4].field`. Note that method and function calls cannot return l-values.

### 12.1. Semantics of l-values

#### 12.1.1. Type checking

After type checking, l-values are represented in  $P4_{IR}$  as:

```
typedLvalueIR
: lvalueIR # lvalueNoteIR
;

lvalueIR
: referenceExpressionIR
| typedLvalueIR . nameIR
| typedLvalueIR `[ typedExpressionIR ]
| typedLvalueIR `[ typedExpressionIR : typedExpressionIR ]
| `( typedLvalueIR )
;

lvalueNoteIR
: `( typeIR )
;
```

Notice that l-values in  $P4_{IR}$  carry type information. L-values are type checked according to the relation:

`Lvalue_ok`:

- Typing `lvalue`, under cursor `cursor` and context `typingContext`:
- Result in `typedLvalueIR`.

The following helper functions are used to fetch the type of a typed l-value:

The type of lvalue `typedLvalueIR`

1. Let ( `typeIR` ) be the note of `typedLvalueIR`.
2. Return `typeIR`.

## 12.1.2. Runtime evaluation

At runtime, l-values are represented as storage references:

```
storageReference
: referenceExpressionIR
| storageReference . nameIR
| storageReference `[ value ]
| storageReference `[ value : value ]
;
```

### 12.1.2.1. Creation

The following relation evaluates an l-value to a storage reference:

`Lvalue_eval`:

- Evaluating `typedLvalueIR`, under cursor `cursor`, context `evalContext`, and state `arch`:
- Result in context `evalContext`, state `arch`, and result `storageReferenceResult`.

The result of evaluating an l-value is:

```
storageReferenceResult
: continueResult<storageReference?>
| abortResult
;

continueResult<X>
: ` X
;

abortResult
: exitResult
| rejectTransitionResult
;
```

### 12.1.2.2. Read

The following relation reads a value from a storage reference:

`Lvalue_read`:

- Reading from `storageReference`, under cursor `cursor`, context `evalContext`, and state `arch`:
- Result in value `value`.

### 12.1.2.3. Write

The following relation writes a value to a storage reference:

**Lvalue\_write:**

- Writing *value* to *storageReference*, under cursor *cursor*, context *evalContext*, and state *arch*:
- Result in context *evalContext*.

The subsequent sections describe each kind of l-value in detail.

## 12.2. Identifiers

### 12.2.1. Type checking

**Typing** *prefixedNonTypeName*, under cursor *p* and context *TC*:

1. Let *prefixedNameIR* be the *prefixed name of* *prefixedNonTypeName*.
2. Let *direction typeIR ctk value?* be ! the *type of variable* *prefixedNameIR* from the *p* layer of *TC*.
3. Check that *ctk* is *DYN*.
4. Check that *value?* is none.
5. Check that *direction* is equal to *OUT* or *direction* is equal to *INOUT*.
6. Result in *prefixedNameIR* with *note ( typeIR )*.

### 12.2.2. Creation

**Evaluating** *referenceExpressionIR* with *note lvalueNoteIR*, under cursor *p*, context *EC*, and state *ARCH*:

1. Result in context *EC*, state *ARCH*, and result *referenceExpressionIR*.

### 12.2.3. Read

**Reading from** *prefixedNameIR*, under cursor *p*, context *EC*, and state *ARCH*:

1. Let *value* be the *value of* *prefixedNameIR* from the *p* layer of *EC*.
2. Result in value *value*.

### 12.2.4. Write

**Writing** *value* to *prefixedNameIR*, under cursor *p*, context *EC<sub>0</sub>*, and state *ARCH*:

1. Let *EC<sub>1</sub>* be *EC<sub>0</sub>* where *prefixedNameIR* is updated to *value* from the *p* layer.

## 12.3. Member accesses

### 12.3.1. Type checking

Typing  $lvalue_{base} . member$ , under cursor  $p$  and context  $TC$ :

1. Let  $typedLvalueIR_{base}$  be
  - the result of typing  $lvalue_{base}$ , under cursor  $p$  and context  $TC$ .
2. Let  $(typeIR_{base})$  be the note of  $typedLvalueIR_{base}$ .
3. Let  $typeIR$  be  $typeIR_{base}$  with typedefs unrolled.
4. If let  $typeIR' [\_]$  be  $typeIR$ :
  - a. Let  $nameIR$  be the name of member.
  - b. Check that  $nameIR$  is equal to "next" or  $nameIR$  is equal to "last".
  - c. Check that  $p$  is equal to `BLOCK` and  $TC.BLOCK.KIND$  is equal to `PARSER` or  $p$  is equal to `LOCAL` and  $TC.LOCAL.KIND$  is equal to `PARSER_STATE`.
  - d. Let  $typedLvalueIR$  be  $typedLvalueIR_{base} . nameIR$  with note  $(typeIR')$ .
  - e. Result in  $typedLvalueIR$ .
5. Else if let  $STRUCT\_ < \_ > \{ ( \_ typeIR_{field} nameIR_{field} ; )^* \}$  be  $typeIR$ :
  - a. Let  $nameIR$  be the name of member.
  - b. Let  $typeIR''$  be ! the value associated to  $nameIR$  in  $(nameIR_{field}, typeIR_{field})^*$ .
  - c. Let  $typedLvalueIR$  be  $typedLvalueIR_{base} . nameIR$  with note  $(typeIR'')$ .
  - d. Result in  $typedLvalueIR$ .
6. Else if let  $HEADER\_ < \_ > \{ ( \_ typeIR_{field} nameIR_{field} ; )^* \}$  be  $typeIR$ :
  - a. Let  $nameIR$  be the name of member.
  - b. Let  $typeIR''$  be ! the value associated to  $nameIR$  in  $(nameIR_{field}, typeIR_{field})^*$ .
  - c. Let  $typedLvalueIR$  be  $typedLvalueIR_{base} . nameIR$  with note  $(typeIR'')$ .
  - d. Result in  $typedLvalueIR$ .
7. Else if let  $HEADER\_UNION\_ < \_ > \{ ( \_ typeIR_{field} nameIR_{field} ; )^* \}$  be  $typeIR$ :
  - a. Let  $nameIR$  be the name of member.
  - b. Let  $typeIR''$  be ! the value associated to  $nameIR$  in  $(nameIR_{field}, typeIR_{field})^*$ .
  - c. Let  $typedLvalueIR$  be  $typedLvalueIR_{base} . nameIR$  with note  $(typeIR'')$ .
  - d. Result in  $typedLvalueIR$ .

### 12.3.2. Creation

Evaluating  $typedLvalueIR . nameIR$  with note  $lvalueNoteIR$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ :

1. Let context  $EC_1$ , state  $ARCH_1$ , and result  $storageReferenceResult$  be
  - the result of evaluating  $typedLvalueIR$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ .
2. If let  $abortResult$  be  $storageReferenceResult$ :
  - a. Result in context  $EC_1$ , state  $ARCH_1$ , and result  $abortResult$ .
3. Else:
  - a. Let  $storageReference'$  be  $storageReferenceResult$ .
  - b. Check that  $storageReference'$  is defined.
  - c. Let  $storageReference'$  be  $storageReference'$ .
  - d. Let value  $value$  be
    - the result of reading from  $storageReference'$ , under cursor  $p$ , context  $EC_1$ , and state  $ARCH_1$ .
  - e. If let  $headerStackValue$  be  $value$ :
    - i. Let  $HEADER\_STACK [ value_{element}^* ( n_{idx} ; n_{size} ) ]$  be  $headerStackValue$ .
    - ii. Check that  $nameIR$  is equal to "next".
    - iii. If  $n_{idx}$  is greater than or equal to  $n_{size}$ :
      - A. Let  $rejectTransitionResult$  be  $REJECT\ ERROR . "StackOutOfBounds"$ .
      - B. Result in context  $EC_1$ , state  $ARCH_1$ , and result  $rejectTransitionResult$ .
    - iv. If  $n_{idx}$  is less than  $n_{size}$ :
      - A. Let  $storageReferenceResult'$  be  $storageReference' . nameIR$ .
      - B. Result in context  $EC_1$ , state  $ARCH_1$ , and result  $storageReferenceResult'$ .
  - f. Else:
    - i. Let  $storageReferenceResult'$  be  $storageReference' . nameIR$ .
    - ii. Result in context  $EC_1$ , state  $ARCH_1$ , and result  $storageReferenceResult'$ .

### 12.3.3. Read

Reading from  $storageReference' . nameIR$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ :

1. Let value  $value_{base}$  be
  - the result of reading from  $storageReference'$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ .
2. If let  $REF\ objectId$  be  $value_{base}$ :
  - a. Let  $object'$  be ! the object  $objectId$  in  $ARCH$ .
  - b. Check that  $object'$  has type  $packageObject$ .
  - c. Let  $PACKAGE < _ > \{ frame \}$  be  $object'$ .
  - d. Let  $value'$  be !  $nameIR$  in map  $frame$ .
  - e. Result in value  $value'$ .
3. Else if let  $headerStackValue_{base}$  be  $value_{base}$ :
  - a. Let  $HEADER\_STACK [ value_{element}^* ( n_{idx} ; n_{size} ) ]$  be  $headerStackValue_{base}$ .
  - b. Check that  $nameIR$  is equal to "next".

- c. Check that  $n_{idx}$  is less than  $n_{size}$ .
  - d. Let  $value$  be  $value_{element}^*[n_{idx}]$ .
  - e. Result in value  $value$ .
4. Else if let  $structValue_{base}$  be  $value_{base}$ :
    - a. Let  $STRUCT\_ \{ (value_{field} nameIR_{field} ;)^* \}$  be  $structValue_{base}$ .
    - b. Let  $value'$  be ! the value associated to  $nameIR$  in  $(nameIR_{field}, value_{field})^*$ .
    - c. Result in value  $value'$ .
  5. Else if let  $headerValue_{base}$  be  $value_{base}$ :
    - a. Let  $HEADER\_ \{ \_ ; (value_{field} nameIR_{field} ;)^* \}$  be  $headerValue_{base}$ .
    - b. Let  $value'$  be ! the value associated to  $nameIR$  in  $(nameIR_{field}, value_{field})^*$ .
    - c. Result in value  $value'$ .
  6. Else if let  $headerUnionValue_{base}$  be  $value_{base}$ :
    - a. Let  $HEADER\_UNION\_ \{ (value_{field} nameIR_{field} ;)^* \}$  be  $headerUnionValue_{base}$ .
    - b. Let  $value'$  be ! the value associated to  $nameIR$  in  $(nameIR_{field}, value_{field})^*$ .
    - c. Result in value  $value'$ .

## 12.3.4. Write

Writing  $value$  to  $storageReference'$ .  $nameIR$ , under cursor  $p$ , context  $EC_0$ , and state  $ARCH$ :

1. Let value  $value'$  be
  - the result of reading from  $storageReference'$ , under cursor  $p$ , context  $EC_0$ , and state  $ARCH$ .
2. If let  $headerStackValue_{base}$  be  $value'$ :
  - a. Let  $HEADER\_STACK [value_{element}^* (n_{idx} ; n_{size})]$  be  $headerStackValue_{base}$ .
  - b. Check that  $nameIR$  is equal to "next".
  - c. Let  $value_{element\_update}^*$  be  $value_{element}^*$  with  $[n_{idx}]$  set to  $value$ .
  - d. Let  $headerStackValue_{base\_update}$  be  $HEADER\_STACK [value_{element\_update}^* (n_{idx} ``1`` ; n_{size})]$ .
  - e. Let context  $EC_1$  be
    - the result of writing  $headerStackValue_{base\_update}$  to  $storageReference'$ , under cursor  $p$ , context  $EC_0$ , and state  $ARCH$ .
  - f. Result in context  $EC_1$ .
3. Else if let  $structValue_{base}$  be  $value'$ :
  - a. Let  $STRUCT$  typed  $\{ fieldValue^* \}$  be  $structValue_{base}$ .
  - b. Let  $fieldValue_{update}^*$  be  $\$update\_fieldValue(fieldValue^*, nameIR, value)$ .
  - c. Let  $structValue_{base\_update}$  be  $STRUCT$  typed  $\{ fieldValue_{update}^* \}$ .
  - d. Let context  $EC_1$  be
    - the result of writing  $structValue_{base\_update}$  to  $storageReference'$ , under cursor  $p$ , context  $EC_0$ , and state  $ARCH$ .
  - e. Result in context  $EC_1$ .

4. Else if let  $\text{headerValue}_{\text{base}}$  be  $\text{value}$ :
  - a. Let  $\text{HEADER}$  typed  $\{ \text{b}_{\text{valid}} ; \text{fieldValue}^* \}$  be  $\text{headerValue}_{\text{base}}$ .
  - b. Let  $\text{fieldValue}_{\text{update}}^*$  be  $\$update\_fieldValue(\text{fieldValue}^*, \text{nameIR}, \text{value})$ .
  - c. Let  $\text{headerValue}_{\text{base\_update}}$  be  $\text{HEADER}$  typed  $\{ \text{b}_{\text{valid}} ; \text{fieldValue}_{\text{update}}^* \}$ .
  - d. Let context  $\text{EC}_1$  be
    - the result of **writing**  $\text{headerValue}_{\text{base\_update}}$  to  $\text{storageReference}$ , under cursor  $p$ , context  $\text{EC}_0$ , and state  $\text{ARCH}$ .
  - e. Result in context  $\text{EC}_1$ .
5. Else if let  $\text{headerUnionValue}_{\text{base}}$  be  $\text{value}$ :
  - a. Let  $\text{HEADER\_UNION}$  typed  $\{ \text{fieldValue}^* \}$  be  $\text{headerUnionValue}_{\text{base}}$ .
  - b. Let  $(\text{value}_{\text{field}} \text{ nameIR}_{\text{field}} ; )^*$  be  $\text{fieldValue}^*$ .
  - c. Let  $\text{value}_{\text{old}}$  be ! the value associated to  $\text{nameIR}$  in  $(\text{nameIR}_{\text{field}}, \text{value}_{\text{field}})^*$ .
  - d. Check that  $\text{value}_{\text{old}}$  has type  $\text{headerValue}$ .
  - e. Let  $\text{HEADER\_}\{ \text{b}_{\text{valid\_old}} ; \_ \}^*$  be  $\text{value}_{\text{old}}$ .
  - f. Let  $\text{fieldValue}_{\text{update}}^*$  be  $\$update\_fieldValue(\text{fieldValue}^*, \text{nameIR}, \text{value})$ .
  - g. Check that  $\text{value}$  has type  $\text{headerValue}$ .
  - h. Let  $\text{HEADER\_}\{ \text{b}_{\text{valid\_new}} ; \_ \}^*$  be  $\text{value}$ .
  - i. Let  $\text{b}_{\text{toggled}}$  be  $\text{b}_{\text{valid\_old}}$  and  $\text{b}_{\text{valid\_new}}$  or  $\text{b}_{\text{valid\_old}}$  and  $\text{b}_{\text{valid\_new}}$ .
  - j. If  $\text{b}_{\text{toggled}}$ :
    - i. Let  $\text{headerUnionValue}_{\text{base\_update}}$  be  $\text{HEADER\_UNION}$  typed  $\{ \text{fieldValue}_{\text{update}}^* \}$ .
    - ii. Let context  $\text{EC}_1$  be
      - the result of **writing**  $\text{headerUnionValue}_{\text{base\_update}}$  to  $\text{storageReference}$ , under cursor  $p$ , context  $\text{EC}_0$ , and state  $\text{ARCH}$ .
    - iii. Result in context  $\text{EC}_1$ .
  - k. Else:
    - i. Let  $\text{fieldValue}_{\text{update}}^*$  be  $\$update\_headerUnion(\text{fieldValue}_{\text{update}}^*, \text{nameIR})$ .
    - ii. Let  $\text{headerUnionValue}_{\text{base\_update}}$  be  $\text{HEADER\_UNION}$  typed  $\{ \text{fieldValue}_{\text{update}}^* \}$ .
    - iii. Let context  $\text{EC}_1$  be
      - the result of **writing**  $\text{headerUnionValue}_{\text{base\_update}}$  to  $\text{storageReference}$ , under cursor  $p$ , context  $\text{EC}_0$ , and state  $\text{ARCH}$ .
    - iv. Result in context  $\text{EC}_1$ .

## 12.4. Index accesses

### 12.4.1. Type checking

**Typing**  $\text{lvalue}_{\text{base}} [\text{expression}_{\text{index}}]$ , under cursor  $p$  and context  $\text{TC}$ :

1. Let  $\text{typedLvalueIR}_{\text{base}}$  be

- the result of **typing**  $lvalue_{base}$ , under cursor  $p$  and context  $TC$ .
2. Let  $(typeIR_{base})$  be the note of  $typedLvalueIR_{base}$ .
  3. Let  $typeIR$  be  $typeIR_{base}$  with **typedefs unrolled**.
  4. Check that  $typeIR$  has type  $headerStackTypeIR$ .
  5. Let  $typeIR' [n_{size}]$  be  $typeIR$ .
  6. Let  $typedExpressionIR_{index}$  be
    - the result of **typing**  $expression_{index}$ , under cursor  $p$  and context  $TC$ .
  7. Let a pair of type  $typeIR_{index}$  and compile-time known-ness  $ctk_{index}$  be the note of  $typedExpressionIR_{index}$ .
  8. Let  $typedExpressionIR_{index\_reduced}$  be **! the result of reducing serializable enums in**  $typedExpressionIR_{index}$  **until**  $\$compat\_array\_index$  **is satisfied**.
  9. If  $ctk_{index}$  is LCTK:
    - a. Let  $value$  be
      - the result of **local compile-time evaluation of**  $typedExpressionIR_{index\_reduced}$ , **under cursor**  $p$  **and context**  $TC$ .
    - b. Check that  $value$  has type  $integerValue$ .
    - c. Let  $integerValue_{index}$  be  $value$ .
    - d. Let  $n_{index}$  be **! the natural number representation of**  $integerValue_{index}$ .
    - e. Check that  $n_{index}$  is less than  $n_{size}$ .
    - f. Let  $typedLvalueIR$  be  $typedLvalueIR_{base} [typedExpressionIR_{index\_reduced}]$  **with note**  $(typeIR')$ .
    - g. Result in  $typedLvalueIR$ .
  10. Else:
    - a. Let  $typedLvalueIR$  be  $typedLvalueIR_{base} [typedExpressionIR_{index\_reduced}]$  **with note**  $(typeIR')$ .
    - b. Result in  $typedLvalueIR$ .

## 12.4.2. Creation

**Evaluating**  $typedLvalueIR [typedExpressionIR]$  **with note**  $lvalueNoteIR$ , **under cursor**  $p$ , **context**  $EC$ , and **state**  $ARCH$ :

1. Let context  $EC_1$ , state  $ARCH_1$ , and result  $storageReferenceResult$  be
  - the result of **evaluating**  $typedLvalueIR$ , **under cursor**  $p$ , **context**  $EC$ , and **state**  $ARCH$ .
2. If let  $abortResult$  be  $storageReferenceResult$ :
  - a. Result in context  $EC_1$ , state  $ARCH_1$ , and result  $abortResult$ .
3. Else:
  - a. Let  $storageReference^?$  be  $storageReferenceResult$ .
  - b. Check that  $storageReference^?$  is defined.
  - c. Let  $storageReference'$  be  $storageReference^?$ .
  - d. Let context  $EC_2$ , state  $ARCH_2$  and  $expressionResult$  be
    - the result of **evaluating**  $typedExpressionIR$ , **under cursor**  $p$ , **context**  $EC_1$ , and **state**  $ARCH_1$ .
  - e. If let  $abortResult$  be  $expressionResult$ :



- i. Result in context  $EC_2$ , state  $ARCH_2$ , and result  $abortResult$ .
- f. Else:
  - i. Let  $value$  be  $expressionResult$ .
  - ii. Check that  $value$  has type  $integerValue$ .
  - iii. Let  $integerValue_{index}$  be  $value$ .
  - iv. Let  $storageReferenceResult'$  be  $storageReference'$  [  $integerValue_{index}$  ].
  - v. Result in context  $EC_2$ , state  $ARCH_2$ , and result  $storageReferenceResult'$ .

### 12.4.3. Read

Reading from  $storageReference'$  [  $integerValue_{index}$  ], under cursor  $p$ , context  $EC$ , and state  $ARCH$ :

1. Let value  $value'$  be
  - the result of reading from  $storageReference'$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ .
2. Check that  $value'$  has type  $headerStackValue$ .
3. Let  $headerStackValue_{base}$  be  $value'$ .
4. Let  $HEADER\_STACK$  [  $value_{element}^* ( \_ ; n_{size} )$  ] be  $headerStackValue_{base}$ .
5. Let  $n_{idx}$  be ! the natural number representation of  $integerValue_{index}$ .
6. If  $n_{idx}$  is less than  $n_{size}$ :
  - a. Let  $value''$  be  $value_{element}^*[n_{idx}]$ .
  - b. Result in value  $value''$ .
7. If  $n_{idx}$  is greater than or equal to  $n_{size}$ :
  - a. Let  $value''$  be  $value_{element}^*[0]$ .
  - b. Check that  $value''$  has type  $headerValue$ .
  - c. Let  $HEADER$  typed {  $b_{valid}$  ;  $fieldValue^*$  } be  $value''$ .
  - d. Let  $value'''$  be  $HEADER$  typed {  $false$  ;  $fieldValue^*$  }.
  - e. Result in value  $value'''$ .

### 12.4.4. Write

Writing value to  $storageReference'$  [  $integerValue_{index}$  ], under cursor  $p$ , context  $EC_0$ , and state  $ARCH$ :

1. Let value  $value''$  be
  - the result of reading from  $storageReference'$ , under cursor  $p$ , context  $EC_0$ , and state  $ARCH$ .
2. Check that  $value''$  has type  $headerStackValue$ .
3. Let  $headerStackValue_{base}$  be  $value''$ .
4. Let  $HEADER\_STACK$  [  $value_{element}^* ( n_{base\_idx} ; n_{size} )$  ] be  $headerStackValue_{base}$ .
5. Let  $n_{idx}$  be ! the natural number representation of  $integerValue_{index}$ .
6. If  $n_{idx}$  is less than  $n_{size}$ :

- a. Let  $\text{value}_{\text{element\_update}}$  be  $\text{value}_{\text{element}}$  with  $[n_{\text{idx}}]$  set to  $\text{value}$ .
  - b. Let  $\text{headerStackValue}_{\text{base\_update}}$  be  $\text{HEADER\_STACK} [ \text{value}_{\text{element\_update}} ( n_{\text{base\_idx}} ; n_{\text{size}} ) ]$ .
  - c. Let context  $\text{EC}_1$  be
    - the result of **writing**  $\text{headerStackValue}_{\text{base\_update}}$  **to storageReference', under cursor p, context  $\text{EC}_0$ , and state ARCH.**
  - d. Result in context  $\text{EC}_1$ .
7. If  $n_{\text{idx}}$  is greater than or equal to  $n_{\text{size}}$ :
- a. Result in context  $\text{EC}_0$ .

## 12.5. Bit-slice accesses

### 12.5.1. Type checking

**Typing**  $\text{lvalue}_{\text{base}} [ \text{expression}_{\text{hi}} : \text{expression}_{\text{lo}} ]$ , under cursor p and context TC:

1. Let  $\text{typedLvalueIR}_{\text{base}}$  be
  - the result of **typing**  $\text{lvalue}_{\text{base}}$ , under cursor p and context TC.
2. Let (  $\text{typeIR}_{\text{base}}$  ) be the note of  $\text{typedLvalueIR}_{\text{base}}$ .
3. Check that  $\text{typeIR}_{\text{base}}$  can be used as a bitslice base.
4. Let  $\text{typedExpressionIR}_{\text{hi}}$  be
  - the result of **typing**  $\text{expression}_{\text{hi}}$ , under cursor p and context TC.
5. Let  $\text{typedExpressionIR}_{\text{lo}}$  be
  - the result of **typing**  $\text{expression}_{\text{lo}}$ , under cursor p and context TC.
6. Let  $\text{typedExpressionIR}_{\text{hi\_reduced}}$  be ! the result of reducing serializable enums in  $\text{typedExpressionIR}_{\text{hi}}$  until  $\text{\$compat\_bitslice\_index}$  is satisfied.
7. Let  $\text{typedExpressionIR}_{\text{lo\_reduced}}$  be ! the result of reducing serializable enums in  $\text{typedExpressionIR}_{\text{lo}}$  until  $\text{\$compat\_bitslice\_index}$  is satisfied.
8. Let a pair of type  $\text{typeIR}_{\text{hi\_reduced}}$  and compile-time known-ness  $\text{ctk}_{\text{hi\_reduced}}$  be the note of  $\text{typedExpressionIR}_{\text{hi\_reduced}}$ .
9. Let a pair of type  $\text{typeIR}_{\text{lo\_reduced}}$  and compile-time known-ness  $\text{ctk}_{\text{lo\_reduced}}$  be the note of  $\text{typedExpressionIR}_{\text{lo\_reduced}}$ .
10. Check that  $\text{ctk}_{\text{hi\_reduced}}$  is LCTK.
11. Let  $\text{value}$  be
  - the result of **local compile-time evaluation of**  $\text{typedExpressionIR}_{\text{hi\_reduced}}$ , under cursor p and context TC.
12. Check that  $\text{value}$  has type  $\text{integerValue}$ .
13. Let  $\text{integerValue}_{\text{hi}}$  be  $\text{value}$ .
14. Let  $n_{\text{hi}}$  be ! the natural number representation of  $\text{integerValue}_{\text{hi}}$ .
15. Check that  $\text{ctk}_{\text{lo\_reduced}}$  is LCTK.
16. Let  $\text{value}'$  be

- the result of **local compile-time evaluation** of  $\text{typedExpressionIR}_{\text{lo\_reduced}}$ , under cursor  $p$  and context  $TC$ .

17. Check that  $\text{value}'$  has type  $\text{integerValue}$ .
18. Let  $\text{integerValue}_{\text{lo}}$  be  $\text{value}'$ .
19. Let  $n_{\text{lo}}$  be **! the natural number representation of**  $\text{integerValue}_{\text{lo}}$ .
20. Check that  $\text{typeIR}_{\text{base}} [ n_{\text{lo}} : n_{\text{hi}} ]$  is a **valid bitslice**.
21. Let  $\text{int}$  be  $n_{\text{hi}} - n_{\text{lo}} + 1$ .
22. Check that  $\text{int}$  has type  $\text{nat}$ .
23. Let  $n_{\text{slice}}$  be  $\text{int}$ .
24. Let  $\text{typeIR}$  be  $\text{BIT} < n_{\text{slice}} >$ .
25. Let  $\text{typedLvalueIR}$  be  $\text{typedLvalueIR}_{\text{base}} [ \text{typedExpressionIR}_{\text{hi\_reduced}} : \text{typedExpressionIR}_{\text{lo\_reduced}} ]$  **with note** (  $\text{typeIR}$  ).
26. Result in  $\text{typedLvalueIR}$ .

## 12.5.2. Creation

**Evaluating**  $\text{typedLvalueIR} [ \text{typedExpressionIR}_{\text{hi}} : \text{typedExpressionIR}_{\text{lo}} ]$  **with note**  $\text{lvalueNoteIR}$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ :

1. Let context  $EC_1$ , state  $ARCH_1$ , and result  $\text{storageReferenceResult}$  be
  - the result of **evaluating**  $\text{typedLvalueIR}$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ .
2. If let  $\text{abortResult}$  be  $\text{storageReferenceResult}$ :
  - a. Result in context  $EC_1$ , state  $ARCH_1$ , and result  $\text{abortResult}$ .
3. Else:
  - a. Let  $\text{storageReference}^?$  be  $\text{storageReferenceResult}$ .
  - b. Check that  $\text{storageReference}^?$  is defined.
  - c. Let  $\text{storageReference}'$  be  $\text{storageReference}^?$ .
  - d. Let context  $EC_2$ , state  $ARCH_2$  and  $\text{expressionListResult}$  be
    - the result of **evaluating**  $[ \text{typedExpressionIR}_{\text{hi}}, \text{typedExpressionIR}_{\text{lo}} ]$ , under cursor  $p$ , context  $EC_1$ , and state  $ARCH_1$ .
  - e. If let  $\text{abortResult}$  be  $\text{expressionListResult}$ :
    - i. Result in context  $EC_2$ , state  $ARCH_2$ , and result  $\text{abortResult}$ .
  - f. Else:
    - i. Let  $\text{value}^*$  be  $\text{expressionListResult}$ .
    - ii. Check that  $\text{value}^*$  is a list of length 2.
    - iii. Let  $[ \text{value}_{\text{hi}}, \text{value}_{\text{lo}} ]$  be  $\text{value}^*$ .
    - iv. Let  $\text{storageReferenceResult}'$  be  $\text{storageReference}' [ \text{value}_{\text{hi}} : \text{value}_{\text{lo}} ]$ .
    - v. Result in context  $EC_1$ , state  $ARCH_1$ , and result  $\text{storageReferenceResult}'$ .

## 12.5.3. Read

Reading from storageReference' [ value<sub>hi</sub> : value<sub>lo</sub> ], under cursor p, context EC, and state ARCH:

1. Let value value<sub>base</sub> be
  - the result of reading from storageReference', under cursor p, context EC, and state ARCH.
2. Let value be value<sub>base</sub> [ value<sub>hi</sub> : value<sub>lo</sub> ].
3. Result in value value.

## 12.5.4. Write

Writing value to storageReference' [ value<sub>hi</sub> : value<sub>lo</sub> ], under cursor p, context EC<sub>0</sub>, and state ARCH:

1. Let value value<sub>base</sub> be
  - the result of reading from storageReference', under cursor p, context EC<sub>0</sub>, and state ARCH.
2. Let value<sub>base\_update</sub> be value<sub>base</sub> [ value<sub>hi</sub> : value<sub>lo</sub> ] replaced with value.
3. Let context EC<sub>1</sub> be
  - the result of writing value<sub>base\_update</sub> to storageReference', under cursor p, context EC<sub>0</sub>, and state ARCH.
4. Result in context EC<sub>1</sub>.

## 12.6. Parenthesized l-values

### 12.6.1. Type checking

Typing ( lvalue<sub>base</sub> ), under cursor p and context TC:

1. Let typedLvalueIR<sub>base</sub> be
  - the result of typing lvalue<sub>base</sub>, under cursor p and context TC.
2. Let ( typeIR<sub>base</sub> ) be the note of typedLvalueIR<sub>base</sub>.
3. Let typedLvalueIR be ( typedLvalueIR<sub>base</sub> ) with note ( typeIR<sub>base</sub> ).
4. Result in typedLvalueIR.

### 12.6.2. Creation

Evaluating ( typedLvalueIR ) with note lvalueNoteIR, under cursor p, context EC, and state ARCH:

1. Let context EC<sub>1</sub>, state ARCH<sub>1</sub>, and result storageReferenceResult be
  - the result of evaluating typedLvalueIR, under cursor p, context EC, and state ARCH.
2. Result in context EC<sub>1</sub>, state ARCH<sub>1</sub>, and result storageReferenceResult.

# 13. Statements

The syntax of statements is defined as follows:

```
statement
: emptyStatement
| assignmentStatement
| callStatement
| directApplicationStatement
| returnStatement
| exitStatement
| blockStatement
| conditionalStatement
| forStatement
| breakStatement
| continueStatement
| switchStatement
;
```

## 13.1. Semantics of statements

### 13.1.1. Type checking

`Stmt_ok`:

- Typing `statement`, under cursor `cursor`, context `typingContext`, abstract control flow `flow`, and loop context `loopctx`:
- Result in context `typingContext`, abstract control flow `flow`, and `statementIR`.

After type checking, statements are represented in  $P4_{IR}$  as follows:

```
statementIR
: emptyStatementIR
| assignmentStatementIR
| callStatementIR
| directApplicationStatementIR
| returnStatementIR
| exitStatementIR
| blockStatementIR
| conditionalStatementIR
| forStatementIR
| breakStatementIR
| continueStatementIR
| switchStatementIR
;
```

In order to statically determine the control flow of a P4 program (e.g., whether a function body always returns), the following indicator for abstract control flow is used:

```
flow
: CONT
| RET
;
```

As a marker of whether a statement is nested inside a loop, the following indicator is used:

```
loopctxt
: LOOP
| NOLOOP
;
```

### 13.1.2. Compile-time evaluation

**Stmt\_inst:**

- Compile-time evaluation of **statementIR**, under cursor **cursor**, context **instContext**, and store **store**:
- Result in context **instContext**, store **store**, and **statementIR**.

Instantiations nested within statements are processed according to the above relation.

### 13.1.3. Runtime evaluation

**Stmt\_eval:**

- Runtime evaluation of **statementIR**, under cursor **cursor**, context **evalContext**, and state **arch**:
- Result in context **evalContext**, state **arch**, and **statementResult**.

The result of evaluating a statement is represented as follows:

```
statementResult
: continueEmptyResult
| callResult
| forResult
;

continueEmptyResult
: /* empty */
;
```

The following is the result of evaluating a call statement:

```
callResult
: abortResult
| returnResult
;

abortResult
: exitResult
| rejectTransitionResult
;

returnResult
: RETURN value?
;

exitResult
: EXIT
;
```

```
rejectTransitionResult
: REJECT errorValue
;
```

The following is the result of evaluating a for statement:

```
forResult
: forBreakResult
| forContinueResult
;

forBreakResult
: BREAK
;

forContinueResult
: CONTINUE
;
```

The subsequent sections describe each kind of statement in detail.

## 13.2. Empty statements

The empty statement, written `;` is a no-op.

```
emptyStatement
: ;
;
```

### 13.2.1. Type checking

After type checking, an empty statement is represented as:

```
emptyStatementIR = emptyStatement
```

Typing `;`, under cursor `p`, context `TC`, abstract control flow `f`, and loop context `l`:

1. Result in context `TC`, abstract control flow `f`, and `;`.

### 13.2.2. Compile-time evaluation

Compile-time evaluation of `emptyStatementIR`, under cursor `p`, context `IC`, and store `STO`:

1. Result in context `IC`, store `STO`, and `emptyStatementIR`.

### 13.2.3. Runtime evaluation

Runtime evaluation of `;`, under cursor `p`, context `EC`, and state `ARCH`:

1. Result in context `EC`, state `ARCH`, and `EMPTY`.

## 13.3. Assignment statements

```
assignop
: =
| +=
| -=
| |+|=
| |-|=
| *=
| /=
| %=
| <<=
| >>=
| &=
| ^=
| |=
;

assignmentStatement
: lvalue assignop expression ;
;
```

An assignment, written with the `=` sign, first evaluates its left sub-expression to an l-value, then evaluates its right sub-expression to a value, and finally copies the value into the l-value. Derived types (e.g. `structs`) are copied recursively, and all components of `headers` are copied, including validity bits. Assignment is not defined for `extern` values.

An assignment may also be written with a binary arithmetic or bit manipulation operator immediately before the `=` sign. This performs the binary operator on the old value of the left sub-expression and the right sub-expression and assigns the result to the l-value. Thus an assignment like `A += B` is equivalent to `A = A + B`, except that `A` is only evaluated once. This means that any side-effects within this operand (eg, a function call inside an array index or slice expression) only occur once. This is not valid for comparison operators, logical operators, concat, range, or mask operators.

### 13.3.1. Type checking

After type checking, an assignment statement has the form:

```
assignmentStatementIR
: typedLvalueIR assignop typedExpressionIR ;
;
```

Typing `lvalue assignop expression ;`, under cursor `p`, context `TC`, abstract control flow `f`, and loop context `l`:

1. If `assignop` is `=`:
  - a. Let `typedLvalueIR` be
    - the result of typing `lvalue`, under cursor `p` and context `TC`.
  - b. Let `typedExpressionIR` be
    - the result of typing `expression`, under cursor `p` and context `TC`.
  - c. Let `typeIRl` be the type of `lvalue` `typedLvalueIR`.



- d. Let  $\text{typeIR}_i$  be the type of  $\text{typedExpressionIR}_i$ .
  - e. Let  $\text{typedExpressionIR}_{\text{cast}}$  be !  $\text{typedExpressionIR}_i$  implicitly cast to  $\text{typeIR}_i$ .
  - f. Result in context  $\text{TC}$ , abstract control flow  $f$ , and  $\text{typedLvalueIR} = \text{typedExpressionIR}_{\text{cast}}$  ;.
2. Else:
- a. Let  $\text{binop}'$  be ! the binary operator corresponding to  $\text{assignop}$ .
  - b. Let  $\text{typedLvalueIR}$  be
    - the result of typing  $\text{lvalue}$ , under cursor  $p$  and context  $\text{TC}$ .
  - c. Let  $\text{expression}_{\text{lvalue}}$  be the expression corresponding to  $\text{lvalue}$ .
  - d. Let  $\text{expression}_{\text{binary}}$  be  $\text{expression}_{\text{lvalue}}$   $\text{binop}'$  expression.
  - e. Let  $\text{typedExpressionIR}_{\text{binary}}$  be
    - the result of typing  $\text{expression}_{\text{binary}}$ , under cursor  $p$  and context  $\text{TC}$ .
  - f. Let (  $\text{typeIR}_{\text{lvalue}}$  ) be the note of  $\text{typedLvalueIR}$ .
  - g. Let  $\text{expressionIR} \# \_$  be !  $\text{typedExpressionIR}_{\text{binary}}$  implicitly cast to  $\text{typeIR}_{\text{lvalue}}$ .
  - h. Check that  $\text{expressionIR}$  has type  $\text{binaryExpressionIR}$ .
  - i. Let  $\_ \text{binop}''$   $\text{typedExpressionIR}_{\text{cast}}$  be  $\text{expressionIR}$ .
  - j. Check that  $\text{binop}''$  is equal to  $\text{binop}'$ .
  - k. Result in context  $\text{TC}$ , abstract control flow  $f$ , and  $\text{typedLvalueIR}$   $\text{assignop}$   $\text{typedExpressionIR}_{\text{cast}}$  ;.

### 13.3.2. Compile-time evaluation

Compile-time evaluation of  $\text{assignmentStatementIR}$ , under cursor  $p$ , context  $\text{IC}$ , and store  $\text{STO}$ :

1. Result in context  $\text{IC}$ , store  $\text{STO}$ , and  $\text{assignmentStatementIR}$ .

### 13.3.3. Runtime evaluation

Runtime evaluation of  $\text{typedLvalueIR}$   $\text{assignop}$   $\text{typedExpressionIR}$  ;, under cursor  $p$ , context  $\text{EC}$ , and state  $\text{ARCH}$ :

1. Let context  $\text{EC}_1$ , state  $\text{ARCH}_1$ , and result  $\text{storageReferenceResult}$  be
  - the result of evaluating  $\text{typedLvalueIR}$ , under cursor  $p$ , context  $\text{EC}$ , and state  $\text{ARCH}$ .
2. If let  $\text{abortResult}$  be  $\text{storageReferenceResult}$ :
  - a. Result in context  $\text{EC}_1$ , state  $\text{ARCH}_1$ , and  $\text{abortResult}$ .
3. Else:
  - a. Let  $\text{storageReference}'$  be  $\text{storageReferenceResult}$ .
  - b. Check that  $\text{storageReference}'$  is defined.
  - c. Let  $\text{storageReference}'$  be  $\text{storageReference}'$ .
  - d. If  $\text{assignop}$  is  $=$ :
    - i. Let context  $\text{EC}_2$ , state  $\text{ARCH}_2$  and  $\text{expressionResult}$  be

- the result of **evaluating** `typedExpressionIR`, under cursor `p`, context `EC1`, and state `ARCH1`.
- ii. If let `abortResult` be `expressionResult`:
  - A. Result in context `EC2`, state `ARCH2`, and `abortResult`.
- iii. Else:
  - A. Let `value` be `expressionResult`.
  - B. Let context `EC3` be
    - the result of **writing** `value` to `storageReference'`, under cursor `p`, context `EC2`, and state `ARCH2`.
  - C. Result in context `EC3`, state `ARCH2`, and `'EMPTY`.
- e. Else:
  - i. Let value `valuei` be
    - the result of **reading from** `storageReference'`, under cursor `p`, context `EC1`, and state `ARCH1`.
  - ii. Let context `EC2`, state `ARCH2` and `expressionResult` be
    - the result of **evaluating** `typedExpressionIR`, under cursor `p`, context `EC1`, and state `ARCH1`.
  - iii. If let `abortResult` be `expressionResult`:
    - A. Result in context `EC2`, state `ARCH2`, and `abortResult`.
  - iv. Else:
    - A. Let `valuer` be `expressionResult`.
    - B. Let `binop'` be **! the binary operator corresponding to** `assignop`.
    - C. Let `valueupdate` be `valuei binop' valuer`.
    - D. Let context `EC3` be
      - the result of **writing** `valueupdate` to `storageReference'`, under cursor `p`, context `EC2`, and state `ARCH2`.
    - E. Result in context `EC3`, state `ARCH2`, and `'EMPTY`.

## 13.4. Call statements

Call statements are used to invoke actions, functions, and methods.

```
callStatement
: lvalue `( argumentList ) ;
| lvalue `< typeArgumentList > `( argumentList ) ;
;
```

Details of how calls are resolved and evaluated are described in [Chapter 18](#).

### 13.4.1. Type checking

After type checking, a call statement is represented as:

```
callStatementIR
: callableTargetIR `< typeArgumentListIR > `( argumentListIR ) ;
;
```

```

callableTargetIR
: referenceExpressionIR
| typedExpressionIR . nameIR
| TYPE prefixedNameIR . nameIR
| `( callableTargetIR )
;

```

Typing `callStatement`, under cursor `p`, context `TC`, abstract control flow `f`, and loop context `l`:

1. If let `lvaluecallable ( argumentList )`; be `callStatement`:
  - a. Let typed callable target `callableTargetIR` be
    - the result of typing `lvaluecallable` as a callable target, under cursor `p` and context `TC`.
  - b. Let `argumentIR*` be
    - the result of typing `argumentList`, under cursor `p` and context `TC`.
  - c. Let callable type `callableTypeIR` with fresh type variables `typeIdimpl*`, defaults `iddefault*` and optionals `idoptional*` be
    - the result of finding type of callable call `callableTargetIR < · > ( argumentIR* )`, under cursor `p` and context `TC`.
  - d. Let return type `typeIRret` with inferred type arguments `typeArgumentIRinferred*` and casted argument list `argumentIRcast*` be
    - the result of typing invocation `callableTypeIR < · > ( argumentIR* )` with omitted type arguments `typeIdimpl*`, defaults `iddefault*` and optionals `idoptional*`, under cursor `p` and context `TC`.
  - e. If `callableTypeIR` is a `static_assert` call:
    - i. Let `callExpressionIR` be `callableTargetIR < typeArgumentIRinferred* > ( argumentIRcast* )`.
    - ii. Let `expressionNoteIR` be a pair of type `typeIRret` and compile-time known-ness LCTK.
    - iii. Let `value` be
      - the result of local compile-time evaluation of `callExpressionIR` annotated with `expressionNoteIR`, under cursor `p` and context `TC`.
    - iv. Check that `value` is equal to ``B true`.
    - v. Let `emptyStatementIR` be `;`.
    - vi. Result in context `TC`, abstract control flow `f`, and `emptyStatementIR`.
  - f. Else:
    - i. Let `callStatementIR` be `callableTargetIR < typeArgumentIRinferred* > ( argumentIRcast* )`;
    - ii. Result in context `TC`, abstract control flow `f`, and `callStatementIR`.
2. Else:
  - a. Let `lvaluecallable < typeArgumentList > ( argumentList )`; be `callStatement`.
  - b. Let typed callable target `callableTargetIR` be
    - the result of typing `lvaluecallable` as a callable target, under cursor `p` and context `TC`.
  - c. Let `typeArgumentIR*` and a set of fresh type variables `typeIdimpl*` be
    - the result of typing `typeArgumentList`, under cursor `p` and context `TC`.
  - d. Let `argumentIR*` be
    - the result of typing `argumentList`, under cursor `p` and context `TC`.

- e. Let callable type `callableTypeIR` with fresh type variables `typeIdinserted*`, defaults `iddefault*` and optionals `idoptional*` be
  - the result of **finding type of callable call** `callableTargetIR < typeArgumentIR* > ( argumentIR* )`, under cursor `p` and context `TC`.
- f. Let `typeIdinfer*` be `typeIdimpl*` concatenated with `typeIdinserted*`.
- g. Let return type `typeIRret` with inferred type arguments `typeArgumentIRinferred*` and casted argument list `argumentIRcast*` be
  - the result of **typing invocation** `callableTypeIR < typeArgumentIR* > ( argumentIR* )` with omitted type arguments `typeIdinfer*`, defaults `iddefault*` and optionals `idoptional*`, under cursor `p` and context `TC`.
- h. Let `callStatementIR` be `callableTargetIR < typeArgumentIRinferred* > ( argumentIRcast* ) ;`.
- i. Result in context `TC`, abstract control flow `f`, and `callStatementIR`.

### 13.4.2. Compile-time evaluation

Compile-time evaluation of `callStatementIR`, under cursor `p`, context `IC`, and store `STO`:

1. Result in context `IC`, store `STO`, and `callStatementIR`.

### 13.4.3. Runtime evaluation

Runtime evaluation of `callableTargetIR < typeArgumentIR* > ( argumentIR* ) ;`, under cursor `p`, context `EC`, and state `ARCH`:

1. Let context `EC1`, state `ARCH1`, and callee `calleeResult` be
  - the result of **finding callee** `callableTargetIR ( argumentIR* )`, under cursor `p`, context `EC`, and state `ARCH`.
2. If let `abortResult` be `calleeResult`:
  - a. Result in context `EC1`, state `ARCH1`, and `abortResult`.
3. Else:
  - a. Let `callee` be `calleeResult`.
  - b. Let context `EC2`, state `ARCH2`, and call result `callResult` be
    - the result of **calling** `callee < typeArgumentIR* > ( argumentIR* )`, under cursor `p`, context `EC1`, and state `ARCH1`.
  - c. If let `abortResult` be `callResult`:
    - i. Result in context `EC2`, state `ARCH2`, and `abortResult`.
  - d. Else:
    - i. Result in context `EC2`, state `ARCH2`, and `EMPTY`.

## 13.5. Direct type invocation

Controls and parsers are often instantiated exactly once. As a light syntactic sugar, control and parser

declarations with no constructor parameters may be applied directly, as if they were an instance. This has the effect of creating and applying a local instance of that type.

```
control Callee(/* parameters omitted */) { /* body omitted */ }

control Caller(/* parameters omitted */)(/* parameters omitted */) {
  apply {
    Callee.apply(/* arguments omitted */); // Callee is treated as an instance
  }
}
```

The definition of `Caller` is equivalent to the following.

```
control Caller(/* parameters omitted */)(/* parameters omitted */) {
  @name("Callee") Callee() Callee_inst; // local instance of Callee
  apply {
    Callee_inst.apply(/* arguments omitted */); // Callee_inst is applied
  }
}
```

```
directApplicationStatement
: namedType . APPLY `( argumentList ) ;
;
```

This feature is intended to streamline the common case where a type is instantiated exactly once. The grammar allows direct calls for generic controls or parsers:

```
control Callee<T>(/* parameters omitted */) { /* body omitted */ }

control Caller(/* parameters omitted */)(/* parameters omitted */) {
  apply {
    // Callee<bit<32>> is treated as an instance
    Callee<bit<32>>.apply(/* arguments omitted */);
  }
}
```

For completeness, the behavior of directly invoking the same type more than once is defined as follows.

- Direct type invocation in different scopes will result in different local instances with different fully-qualified control names.
- In the same scope, direct type invocation will result in a different local instance per invocation—however, instances of the same type will share the same global name, via the `@name` annotation. If the type contains controllable entities, then invoking it directly more than once in the same scope is illegal, because it will produce multiple controllable entities with the same fully-qualified control name.

See [\[sec-name-annotations\]](#) for details of `@name` annotations.

No direct invocation is possible for controls or parsers that require constructor arguments. These need to be instantiated before they are invoked.

### 13.5.1. Type checking

After type checking, a direct application statement is represented as:

```

directApplicationStatementIR
: constructorTargetIR . APPLY `( argumentListIR ) ;
;

```

Typing `namedType` . APPLY ( `argumentList` ) ;, under cursor `p`, context `TC`, abstract control flow `f`, and loop context `l`:

1. Let `expressionIR` annotated with a pair of type `typeIRobject` and compile-time known-ness `_` be
  - the result of typing `namedType` ( `'EMPTY` ), under cursor `p` and context `TC`.
2. Check that `expressionIR` has type `callExpressionIR`.
3. Let `callExpressionIR` be `expressionIR`.
4. Check that `callExpressionIR` matches pattern `% ( % )`.
5. Let `constructorTargetIR ( argumentIR* )` be `callExpressionIR`.
6. Check that `argumentIR*` is an empty list.
7. Let `prefixedNameIR < typeArgumentIR* >` be `constructorTargetIR`.
8. Let `typeIRobject_unroll` be `typeIRobject` with `typeddefs` unrolled.
9. Check that `typeIRobject_unroll` has type `parserObjectTypeIR` or `typeIRobject_unroll` has type `controlObjectTypeIR`.
10. Let `nameIRobject` be `"__direct_application"`.
11. Let `TC1` be `TC` where `nameIRobject` to `'EMPTY` `typeIRobject` `CTK` · is added to the `p` layer.
12. Let `lvalue` be `'ID` `nameIRobject` . `ID` `"apply"`.
13. Let context `_`, abstract control flow `_`, and `statementIR` be
  - the result of typing `lvalue` ( `argumentList` ) ;, under cursor `p`, context `TC1`, abstract control flow `f`, and loop context `l`.
14. Check that `statementIR` has type `callStatementIR`.
15. Let `callStatementIR` be `statementIR`.
16. Let `callableTargetIR < typeArgumentIR* > ( argumentIRcast* )` ; be `callStatementIR`.
17. Check that `callableTargetIR` matches pattern `% . %`.
18. Let `typedExpressionIRbase . text` be `callableTargetIR`.
19. Check that `text` is equal to `"apply"`.
20. Check that `typeArgumentIR*` is an empty list.
21. Check that `nameIRobject` annotated with a pair of type `typeIRobject` and compile-time known-ness `CTK` is equal to `typedExpressionIRbase`.
22. Check that `constructorTargetIR` is equal to `prefixedNameIR < typeArgumentIR* >`.
23. Let `directApplicationStatementIR` be `constructorTargetIR` . APPLY ( `argumentIRcast*` ) ;.
24. Result in context `TC`, abstract control flow `f`, and `directApplicationStatementIR`.

### 13.5.2. Compile-time evaluation

At compile-time, a direct application is instantiated, and then desugared into a method call on that instance with the relation:

### DirectApplicationStmt\_inst:

- Compile-time evaluation of `directApplicationStatementIR`, under cursor `cursor`, context `instContext`, and store `store`:
- Result in store `store` and desugared `constantDeclarationIR callStatementIR`.

It is implemented as:

Compile-time evaluation of `constructorTargetIR . APPLY ( argumentListIR ) ;`, under cursor `p`, context `IC`, and store `STO0`:

1. Let `prefixedNameIR < typeArgumentListIR >` be `constructorTargetIR`.
2. Let `constructor constructorDef < typeArgumentListIRinst >` with defaults `iddefault*` and optionals `idoptional*` be
  - the result of finding constructor for `prefixedNameIR < typeArgumentListIR > ( · )` under cursor `p`, and context `IC`.
3. Let `typeId` be the string form of `prefixedNameIR`.
4. Let `ICcallee` be `IC` with `typeId` added to the path.
5. Let store `STO1` and constructed object be
  - the result of loading `constructorDef < typeArgumentListIRinst > ( · )` with defaults `iddefault*` and optionals `idoptional*`, under cursor `p`, context `ICcallee`, and store `STO0`.
6. Let `typeIdfresh` be a fresh type variable.
7. Let `typeIR` be `typeId`.
8. Let `nameIR` be the concatenation of `[ typeId, "_", typeIdfresh ]`.
9. Let `objectId` be `IC.PATH` concatenated with `typeId`.
10. Let `STO2` be `STO1` where `objectId` to object is added.
11. Let `constantDeclarationIR` be ``EMPTY CONST typeIR nameIR = `VALUE REF objectId ;`.
12. Let `typedExpressionIRbase` be `nameIR` annotated with a pair of type `typeIR` and compile-time knownness `CTK`.
13. Let `callableTargetIR` be `typedExpressionIRbase . "apply"`.
14. Let `callStatementIR` be `callableTargetIR < typeArgumentListIRinst > ( argumentListIR ) ;`.
15. Result in store `STO2` and desugared `constantDeclarationIR callStatementIR`.

A direct application statement is instantiated as:

Compile-time evaluation of `directApplicationStatementIR`, under cursor `p`, context `IC`, and store `STO`:

1. Let store `STO1` and desugared `constantDeclarationIR callStatementIR` be
  - the result of compile-time evaluation of `directApplicationStatementIR`, under cursor `p`, context `IC`, and store `STO`.
2. Let `blockStatementIR` be ``EMPTY { [ constantDeclarationIR, callStatementIR ] }`.
3. Result in context `IC`, store `STO1`, and `blockStatementIR`.

## 13.6. Return statements

The **return** statement immediately terminates the execution of the **action**, **function** or **control** containing it. **return** statements are not allowed within parsers. **return** statements followed by an expression are only allowed within functions that return values; in this case the type of the expression must match the return type of the function. Any copy-out behavior due to direction **out** or **inout** parameters of the enclosing **action**, **function**, or **control** are still performed after the execution of the **return** statement. See [Section 18.4](#) for details on copy-out behavior.

```
returnStatement
: RETURN ;
| RETURN expression ;
;
```

### 13.6.1. Type checking

After type checking, a **return** statement has the form:

```
returnStatementIR
: RETURN ;
| RETURN typedExpressionIR ;
;
```

Typing **returnStatement**, under cursor **LOCAL**, context **TC**, abstract control flow **f**, and loop context **l**:

1. If **returnStatement** is **RETURN ;**:
  - a. Check that **VOID** is equal to the expected return type in **TC**.
  - b. Result in context **TC**, abstract control flow **RET**, and **RETURN ;**.
2. Else:
  - a. Let **RETURN expression ;** be **returnStatement**.
  - b. Let **typedExpressionIR** be
    - the result of typing **expression**, under cursor **LOCAL** and context **TC**.
  - c. Let **typeIR** be the type of **typedExpressionIR**.
  - d. Let **typeIR<sub>ret</sub>** be ! the expected return type in **TC**.
  - e. Let **typedExpressionIR<sub>cast</sub>** be ! **typedExpressionIR** implicitly cast to **typeIR<sub>ret</sub>**.
  - f. Result in context **TC**, abstract control flow **RET**, and **RETURN typedExpressionIR<sub>cast</sub> ;**.

### 13.6.2. Compile-time evaluation

Compile-time evaluation of **returnStatementIR**, under cursor **LOCAL**, context **IC**, and store **STO**:

1. Result in context **IC**, store **STO**, and **returnStatementIR**.



### 13.6.3. Runtime evaluation

Runtime evaluation of `returnStatementIR`, under cursor `LOCAL`, context `EC`, and state `ARCH`:

1. If `returnStatementIR` is `RETURN ;`:
  - a. Result in context `EC`, state `ARCH`, and `RETURN`.
2. Else:
  - a. Let `RETURN typedExpressionIR ;` be `returnStatementIR`.
  - b. Let context `EC1`, state `ARCH1` and `expressionResult` be
    - the result of `evaluating typedExpressionIR`, under cursor `LOCAL`, context `EC`, and state `ARCH`.
  - c. If let `abortResult` be `expressionResult`:
    - i. Result in context `EC1`, state `ARCH1`, and `abortResult`.
  - d. Else:
    - i. Let `value` be `expressionResult`.
    - ii. Result in context `EC1`, state `ARCH1`, and `RETURN value`.

## 13.7. Exit statements

The `exit` statement immediately terminates the execution of all the blocks currently executing: the current `action` (if invoked within an `action`), the current `control`, and all its callers. `exit` statements are not allowed within parsers or functions.

Any copy-out behavior due to direction `out` or `inout` parameters of the enclosing `action` or `control`, and all of its callers, are still performed after the execution of the `exit` statement. See [Section 18.4](#) for details on copy-out behavior.

```
exitStatement
: EXIT ;
;
```

There are some expressions whose evaluation might cause an `exit` statement to be executed. Examples include:

- `table.apply().action_run`, which can only appear as the expression of a `switch` statement (see [Section 13.13](#)), and when it appears there, it must be the entire expression.
- Any expression containing `table.apply().hit` or `table.apply().miss` (see [Section 16.3.7](#)), which can be part of arbitrarily complex expressions in many places of a P4 program, such as:
  - the expression in an `if` statement.
  - the expression `e1` in a conditional expression `e1 ? e2 : e3`.
  - in an assignment statement, in the left and/or right hand sides.
  - an argument passed to a function or method call.
  - an expression to calculate a table key (see [\[sec-mau-semantics\]](#)).

This list is not intended to be exhaustive.

If applying the table causes an action to be executed, which in turn causes an `exit` statement to be

executed, then evaluation of the expression ends immediately, and the rest of the current expression or statement does not complete its execution. See [Section 14.1](#) for the order of evaluation of the parts of an expression. For the examples listed above, it also means the following behavior after the expression evaluation is interrupted.

- For a `switch` statement, if `table.apply()` exits, then none of the blocks in the `switch` statement are executed.
- If `table.apply().hit` or `table.apply().miss` cause an exit during the evaluation of an expression:
  - If it is the expression of an `if` statement, then neither the 'then' nor 'else' branches of the `if` statement are executed.
  - If it is the expression `e1` in a conditional expression `e1 ? e2 : e3`, then neither expression `e2` nor `e3` are evaluated.
  - If the expression is the right hand side of an assignment statement, or part of the calculation of the L-value on the left hand side (e.g. the index expression of a header stack reference), then no assignment occurs.
  - If the expression is an argument passed to a function or method call, then the function/method call does not occur.
  - If the expression is a table key, then the table is not applied.

### 13.7.1. Type checking

After type checking, an `exit` statement is represented in  $P4_{IR}$  as:

```
exitStatementIR = exitStatement
```

Typing `EXIT ;`, under cursor `p`, context `TC`, abstract control flow `f`, and loop context `l`:

1. Result in context `TC`, abstract control flow `f`, and `EXIT ;`.

### 13.7.2. Compile-time evaluation

Compile-time evaluation of `exitStatementIR`, under cursor `p`, context `IC`, and store `STO`:

1. Result in context `IC`, store `STO`, and `exitStatementIR`.

### 13.7.3. Runtime evaluation

Runtime evaluation of `EXIT ;`, under cursor `p`, context `EC`, and state `ARCH`:

1. Result in context `EC`, state `ARCH`, and `EXIT`.

## 13.8. Block statements

A block statement is denoted by curly braces. It contains a sequence of statements and declarations, which are executed sequentially. The declarations (e.g., variables and constants) within a block statement are only visible within the block.

```

blockStatement
  : annotationList `{ blockElementStatementList }
  ;

blockElementStatementList
  : /* empty */
  | blockElementStatementList blockElementStatement
  ;

blockElementStatement
  : constantDeclaration
  | variableDeclaration
  | statement
  ;

```

### 13.8.1. Type checking

After type checking, block statements are represented in  $P4_{IR}$  as:

```

blockStatementIR
  : annotationList `{ blockElementStatementListIR }
  ;

blockElementStatementListIR = blockElementStatementIR*

blockElementStatementIR
  : constantDeclarationIR
  | variableDeclarationIR
  | statementIR
  ;

```

Typing  $blockStatement$ , under cursor  $LOCAL$ , context  $TC$ , abstract control flow  $f$ , and loop context  $l$ :

1. Let  $TC_1$  be  $TC$  with a new local frame.
2. Let context  $TC_2$ , abstract control flow  $f_1$ , and  $blockStatementIR$  be
  - the result of typing  $blockStatement$ , under context  $TC_1$ , abstract control flow  $f$ , and loop context  $l$ .
3. Let  $TC_3$  be  $TC_2$  with the innermost frame removed.
4. Result in context  $TC_3$ , abstract control flow  $f_1$ , and  $blockStatementIR$ .

A block is type checked by the relation:

**Block\_ok:**

- Typing  $blockStatement$ , under context  $typingContext$ , abstract control flow  $flow$ , and loop context  $loopctx$ :
- Result in context  $typingContext$ , abstract control flow  $flow$ , and  $blockStatementIR$ .

A statement or declaration within a block statement is type checked by the relation:

**BlockElementStmt\_ok:**

- Typing `blockElementStatement`, under context `typingContext`, abstract control flow `flow`, and loop context `loopctx`:
- Result in context `typingContext`, abstract control flow `flow`, and `blockElementStatementIR`.

It is implemented as:

Typing `blockElementStatement`, under context `TC0`, abstract control flow `f`, and loop context `l`:

1. If let `constantDeclaration` be `blockElementStatement`:
  - a. Let context `TC1` and `constantDeclarationIR` be
    - the result of typing `constantDeclaration`, under cursor `LOCAL` and context `TC0`.
  - b. Result in context `TC1`, abstract control flow `f`, and `constantDeclarationIR`.
2. Else if let `variableDeclaration` be `blockElementStatement`:
  - a. Let context `TC1` and `variableDeclarationIR` be
    - the result of typing `variableDeclaration`, under cursor `LOCAL` and context `TC0`.
  - b. Result in context `TC1`, abstract control flow `f`, and `variableDeclarationIR`.
3. Else:
  - a. Let `statement` be `blockElementStatement`.
  - b. Let context `TC1`, abstract control flow `fpost`, and `statementIR` be
    - the result of typing `statement`, under cursor `LOCAL`, context `TC0`, abstract control flow `f`, and loop context `l`.
  - c. Result in context `TC1`, abstract control flow `fpost`, and `statementIR`.

A list of block elements is type checked by the relation:

`BlockElementStmtList_ok`:

- Typing `blockElementStatementList`, under context `typingContext`, abstract control flow `flow`, and loop context `loopctx`:
- Result in context `typingContext`, abstract control flow `flow`, and `blockElementStatementIR*`.

Typing `blockElementStatementList`, under context `TC0`, abstract control flow `f`, and loop context `l`:

1. Let `blockElementStatement*` be the list of block element statements in `blockElementStatementList`.
2. Let context `TC1`, abstract control flow `fpost`, and `blockElementStatementIR*` be
  - the result of typing `blockElementStatement*` under context `TC0` with abstract control flow `f` and loop context `l`.
3. Result in context `TC1`, abstract control flow `fpost`, and `blockElementStatementIR*`.

`BlockElementStmts_ok`:

- Typing `blockElementStatement*` under context `typingContext` with abstract control flow `flow` and loop

context `loopctx`:

- Result in context `typingContext`, abstract control flow `flow`, and `blockElementStatementIR*`.

Typing `blockElementStatement*` under context `typingContext` with abstract control flow `flow` and loop context `l`:

1. If `blockElementStatement*` is equal to `.`:
  - a. Result in context `typingContext`, abstract control flow `flow`, and `.`.
2. If let `blockElementStatementh :: blockElementStatementt*` be `blockElementStatement*`:
  - a. Let context `TC1`, abstract control flow `f1`, and `blockElementStatementIRh` be
    - the result of typing `blockElementStatementh`, under context `typingContext`, abstract control flow `flow`, and loop context `l`.
  - b. Let context `TC2`, abstract control flow `f2`, and `blockElementStatementIRt*` be
    - the result of typing `blockElementStatementt*` under context `TC1` with abstract control flow `f1` and loop context `l`.
  - c. Result in context `TC2`, abstract control flow `f2`, and `blockElementStatementIRh :: blockElementStatementIRt*`.

### 13.8.2. Compile-time evaluation

Compile-time evaluation of `annotationList { blockElementStatementListIR }`, under cursor `LOCAL`, context `IC`, and store `STO`:

1. Let `IC1` be `IC` with a new local frame.
2. Let context `IC2`, store `STO1`, and `_ { blockElementStatementListIRinst }` be
  - the result of compile-time evaluation of `annotationList { blockElementStatementListIR }`, under context `IC1`, and store `STO`.
3. Let `IC3` be `IC2` with the innermost frame removed.
4. Result in context `IC3`, store `STO1`, and `annotationList { blockElementStatementListIRinst }`.

A block is compile-time evaluated by the relation:

`Block_inst`:

- Compile-time evaluation of `blockStatementIR`, under context `instContext`, and store `store`:
- Result in context `instContext`, store `store`, and `blockStatementIR`.

A block element is compile-time evaluated by the relation:

`BlockElementStmt_inst`:

- Compile-time evaluation of `blockElementStatementIR`, under context `instContext`, and store `store`:
- Result in context `instContext`, store `store`, and `blockElementStatementIR`.

Compile-time evaluation of `blockElementStatementIR`, under context `instContext`, and store `store`:

1. If let `constantDeclarationIR` be `blockElementStatementIR`:
  - a. Let context  $IC_1$  be
    - the result of loading `constantDeclarationIR`, under cursor `LOCAL`, and context `instContext`.
  - b. Result in context  $IC_1$ , store `store`, and `constantDeclarationIR`.
2. Else if let `variableDeclarationIR` be `blockElementStatementIR`:
  - a. Result in context `instContext`, store `store`, and `variableDeclarationIR`.
3. Else:
  - a. Let `statementIR` be `blockElementStatementIR`.
  - b. Let context  $IC_1$ , store  $STO_1$ , and `statementIRinst` be
    - the result of compile-time evaluation of `statementIR`, under cursor `LOCAL`, context `instContext`, and store `store`.
  - c. Result in context  $IC_1$ , store  $STO_1$ , and `statementIRinst`.

A list of block elements is compile-time evaluated by the relation:

`BlockElementStmtList_inst`:

- Compile-time evaluation of `blockElementStatementListIR`, under context `instContext`, and store `store`:
- Result in context `instContext`, store `store`, and `blockElementStatementIR*`.

### 13.8.3. Runtime evaluation

Runtime evaluation of `blockStatementIR`, under cursor `p`, context `EC`, and state `ARCH`:

1. Let  $EC_1$  be `EC` with a new local frame.
2. Let context  $EC_2$ , state  $ARCH_1$ , and `statementResult` be
  - the result of runtime evaluation of `blockStatementIR`, under context  $EC_1$ , and state `ARCH`.
3. Let  $EC_3$  be  $EC_2$  with the innermost frame removed.
4. Result in context  $EC_3$ , state  $ARCH_1$ , and `statementResult`.

A block is runtime evaluated by the relation:

`Block_eval`:

- Runtime evaluation of `blockStatementIR`, under context `evalContext`, and state `arch`:
- Result in context `evalContext`, state `arch`, and `statementResult`.

A block element is runtime evaluated by the relation:

#### BlockElementStmt\_eval:

- Runtime evaluation of `blockElementStatementIR`, under context `evalContext`, and state `arch`:
- Result in context `evalContext`, state `arch`, and `statementResult`.

#### Runtime evaluation of `blockElementStatementIR`, under context `EC0`, and state `arch`:

1. If let `constantDeclarationIR` be `blockElementStatementIR`:
  - a. Let context `EC1` be
    - the result of **evaluating** `constantDeclarationIR`, under cursor `LOCAL`, and context `EC0`.
  - b. Result in context `EC1`, state `arch`, and `EMPTY`.
2. Else if let `variableDeclarationIR` be `blockElementStatementIR`:
  - a. Let context `EC1`, state `ARCH1`, and result `declarationResult` be
    - the result of **evaluating** `variableDeclarationIR`, under cursor `LOCAL`, context `EC0`, and state `arch`.
  - b. Result in context `EC1`, state `ARCH1`, and `declarationResult`.
3. Else:
  - a. Let `statementIR` be `blockElementStatementIR`.
  - b. Let context `EC1`, state `ARCH1`, and `statementResult` be
    - the result of **runtime evaluation of** `statementIR`, under cursor `LOCAL`, context `EC0`, and state `arch`.
  - c. Result in context `EC1`, state `ARCH1`, and `statementResult`.

A list of block elements is runtime evaluated by the relation:

#### BlockElementStmtList\_eval:

- Runtime evaluation of `blockElementStatementListIR`, under context `evalContext`, and state `arch`:
- Result in context `evalContext`, state `arch`, and `statementResult`.

## 13.9. Conditional statements

The conditional statement uses standard syntax and semantics familiar from many programming languages.

However, the condition expression in P4 is required to be a Boolean (and not an integer).

```
conditionalStatement
: IF `( expression ) statement
| IF `( expression ) statement ELSE statement
;
```

When several `if` statements are nested, the `else` applies to the innermost `if` statement that does not have an `else` statement.

### 13.9.1. Type checking

After type checking, a conditional statement has the form:

```
conditionalStatementIR
: IF `( typedExpressionIR ) statementIR
| IF `( typedExpressionIR ) statementIR ELSE statementIR
;
```

Typing `conditionalStatement`, under cursor `p`, context `TC`, abstract control flow `f`, and loop context `l`:

1. If let `IF ( expressioncond ) statementthen` be `conditionalStatement`:
  - a. Let `typedExpressionIRcond` be
    - the result of typing `expressioncond`, under cursor `p` and context `TC`.
  - b. Let `typeIRcond` be the type of `typedExpressionIRcond`.
  - c. Check that `BOOL` is equal to `typeIRcond` with typedefs unrolled.
  - d. Let context `TCthen`, abstract control flow `fthen`, and `statementIRthen` be
    - the result of typing `statementthen`, under cursor `p`, context `TC`, abstract control flow `f`, and loop context `l`.
  - e. Result in context `TC`, abstract control flow `f`, and `IF ( typedExpressionIRcond ) statementIRthen`.
2. Else:
  - a. Let `IF ( expressioncond ) statementthen ELSE statementelse` be `conditionalStatement`.
  - b. Let `typedExpressionIRcond` be
    - the result of typing `expressioncond`, under cursor `p` and context `TC`.
  - c. Let `typeIRcond` be the type of `typedExpressionIRcond`.
  - d. Check that `BOOL` is equal to `typeIRcond` with typedefs unrolled.
  - e. Let context `TCthen`, abstract control flow `fthen`, and `statementIRthen` be
    - the result of typing `statementthen`, under cursor `p`, context `TC`, abstract control flow `f`, and loop context `l`.
  - f. Let context `TCelse`, abstract control flow `felse`, and `statementIRelse` be
    - the result of typing `statementelse`, under cursor `p`, context `TC`, abstract control flow `f`, and loop context `l`.
  - g. Let `fpost` be the merged control flow of `fthen` and `felse`.
  - h. Result in context `TC`, abstract control flow `fpost`, and `IF ( typedExpressionIRcond ) statementIRthen ELSE statementIRelse`.

### 13.9.2. Compile-time evaluation

Compile-time evaluation of `conditionalStatementIR`, under cursor `p`, context `IC`, and store `STO`:

1. If let `IF ( typedExpressionIRcond ) statementIRthen` be `conditionalStatementIR`:
  - a. Let context `ICthen`, store `STOi`, and `statementIRthen_inst` be
    - the result of compile-time evaluation of `statementIRthen`, under cursor `p`, context `IC`, and



store  $STO$ .

b. Result in context  $IC$ , store  $STO_1$ , and  $IF (typedExpressionIR_{cond}) statementIR_{then\_inst}$ .

2. Else:

a. Let  $IF (typedExpressionIR_{cond}) statementIR_{then} ELSE statementIR_{else}$  be  $conditionalStatementIR$ .

b. Let context  $IC_{then}$ , store  $STO_1$ , and  $statementIR_{then\_inst}$  be

- the result of compile-time evaluation of  $statementIR_{then}$ , under cursor  $p$ , context  $IC$ , and store  $STO$ .

c. Let context  $IC_{else}$ , store  $STO_2$ , and  $statementIR_{else\_inst}$  be

- the result of compile-time evaluation of  $statementIR_{else}$ , under cursor  $p$ , context  $IC$ , and store  $STO_1$ .

d. Result in context  $IC$ , store  $STO_2$ , and  $IF (typedExpressionIR_{cond}) statementIR_{then\_inst} ELSE statementIR_{else\_inst}$ .

### 13.9.3. Runtime evaluation

Runtime evaluation of  $conditionalStatementIR$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ :

1. If let  $IF (typedExpressionIR_{cond}) statementIR_{then}$  be  $conditionalStatementIR$ :

a. Let context  $EC_{cond}$ , state  $ARCH_{cond}$  and  $expressionResult$  be

- the result of evaluating  $typedExpressionIR_{cond}$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ .

b. If let  $abortResult$  be  $expressionResult$ :

i. Result in context  $EC_{cond}$ , state  $ARCH_{cond}$ , and  $abortResult$ .

c. If  $expressionResult$  is equal to `B true:

i. Let context  $EC_{then}$ , state  $ARCH_{then}$ , and  $statementResult$  be

- the result of runtime evaluation of  $statementIR_{then}$ , under cursor  $p$ , context  $EC_{cond}$ , and state  $ARCH_{cond}$ .

ii. Result in context  $EC_{then}$ , state  $ARCH_{then}$ , and  $statementResult$ .

d. If  $expressionResult$  is equal to `B false:

i. Result in context  $EC_{cond}$ , state  $ARCH_{cond}$ , and `EMPTY.

2. Else:

a. Let  $IF (typedExpressionIR_{cond}) statementIR_{then} ELSE statementIR_{else}$  be  $conditionalStatementIR$ .

b. Let context  $EC_{cond}$ , state  $ARCH_{cond}$  and  $expressionResult$  be

- the result of evaluating  $typedExpressionIR_{cond}$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ .

c. If let  $abortResult$  be  $expressionResult$ :

i. Result in context  $EC_{cond}$ , state  $ARCH_{cond}$ , and  $abortResult$ .

d. If  $expressionResult$  is equal to `B true:

i. Let context  $EC_{then}$ , state  $ARCH_{then}$ , and  $statementResult$  be

- the result of runtime evaluation of  $statementIR_{then}$ , under cursor  $p$ , context  $EC_{cond}$ , and state  $ARCH_{cond}$ .

ii. Result in context  $EC_{then}$ , state  $ARCH_{then}$ , and  $statementResult$ .

e. If  $expressionResult$  is equal to `B false:

- i. Let context  $EC_{else}$ , state  $ARCH_{else}$ , and  $statementResult$  be
  - the result of runtime evaluation of  $statementIR_{else}$ , under cursor  $p$ , context  $EC_{cond}$ , and state  $ARCH_{cond}$ .
- ii. Result in context  $EC_{else}$ , state  $ARCH_{else}$ , and  $statementResult$ .

## 13.10. For statements

A **for** statement executes a statement zero or more times, based on a condition or a range or collection.

```

forStatement
: annotationList FOR
  `( forInitStatementList ; expression ; forUpdateStatementList ) statement
| annotationList FOR `( type name IN forCollectionExpression ) statement
| annotationList FOR
  `( annotationListNonEmpty type name IN forCollectionExpression )
  statement
;

forInitStatementList
: /* empty */
| forInitStatementListNonEmpty
;

forInitStatementListNonEmpty
: forInitStatement
| forInitStatementListNonEmpty , forInitStatement
;

forInitStatement
: annotationList type name initializerOpt
| forUpdateStatement
;

forUpdateStatementList
: /* empty */
| forUpdateStatementListNonEmpty
;

forUpdateStatementListNonEmpty
: forUpdateStatement
| forUpdateStatementListNonEmpty , forUpdateStatement
;

forUpdateStatement
: lvalue `( argumentList )
| lvalue `< typeArgumentList > `( argumentList )
| lvalue assignop expression
;

forCollectionExpression
: expression
| expression .. expression
;

```

There are two forms of **for** statements:

- Basic 3-clause **for** statements with initialization, condition, and update.
- **for-in** statements that iterate over a range, list, or header stack.

A **break**; statement may be executed in a loop body to immediately exit the loop, without executing the

rest of the body or the update statements. `break`; statements are explained in detail in [Section 13.11](#).

A `continue`; statement may be executed in a loop body to skip the rest of the current loop body, executing the update statements and then evaluating the condition to either execute the loop body again, or terminate the loop. `continue`; statements are explained in detail in [Section 13.12](#).

The scope of any declaration in a `for` statement is limited to the `for` statement and its body.

After type checking, a `for` statement has the form:

```
forStatementIR
: annotationList FOR
  `( forInitStatementListIR ; typedExpressionIR ; forUpdateStatementListIR )
  statementIR
| annotationList FOR `( typeIR nameIR IN forCollectionExpressionIR )
  statementIR
| annotationList FOR
  `( annotationList typeIR nameIR IN forCollectionExpressionIR )
  statementIR
;
```

### 13.10.1. 3-clause `for` statements

The basic 3-clause `for` statement is similar to a C `for` statement. The init statements will be executed prior to executing the loop. The condition will be evaluated before each iteration, to determine if the loop should exit. If the condition is false, the loop will exit without executing any statements from the loop body or update. The update statements will be executed after the loop body and before evaluating the condition again for the next iteration.

#### 13.10.1.1. Type checking

After type checking, a 3-clause `for` statement has the form:

```
forStatementIR
: annotationList FOR
  `( forInitStatementListIR ; typedExpressionIR ; forUpdateStatementListIR )
  statementIR
| annotationList FOR `( typeIR nameIR IN forCollectionExpressionIR )
  statementIR
| annotationList FOR
  `( annotationList typeIR nameIR IN forCollectionExpressionIR )
  statementIR
;

forInitStatementListIR = forInitStatementIR*

forInitStatementIR
: annotationList typeIR nameIR initializerOptIR
| forUpdateStatementIR
;

forUpdateStatementListIR = forUpdateStatementIR*

forUpdateStatementIR
: callableTargetIR `< typeArgumentListIR > `( argumentListIR )
| typedLvalueIR assignop typedExpressionIR
;
```

Typing `annotationList FOR ( forInitStatementList ; expression ; forUpdateStatementList ) statement'`, [under cursor](#)

LOCAL, context TC, abstract control flow f, and loop context l:

1. Let  $TC_1$  be TC with a new local frame.
2. Let context  $TC_2$  and  $forInitStatementIR^*$  be
  - the result of typing  $forInitStatementList$  under context  $TC_1$ .
3. Let  $typedExpressionIR$  be
  - the result of typing expression, under cursor LOCAL and context  $TC_2$ .
4. Let  $typeIR$  be the type of  $typedExpressionIR$ .
5. Check that  $BOOL$  is equal to  $typeIR$  with  $typeddefs$  unrolled.
6. Let  $forUpdateStatementIR^*$  be
  - the result of typing  $forUpdateStatementList$  under context  $TC_2$ .
7. Let context  $TC_3$ , abstract control flow  $f_{post}$ , and  $statementIR$  be
  - the result of typing  $statement'$ , under cursor LOCAL, context  $TC_2$ , abstract control flow f, and loop context LOOP.
8. Let  $TC_4$  be  $TC_3$  with the innermost frame removed.
9. Let  $forStatementIR$  be  $annotationList$  FOR (  $forInitStatementIR^*$  ;  $typedExpressionIR$  ;  $forUpdateStatementIR^*$  )  $statementIR$ .
10. Result in context TC, abstract control flow  $f_{post}$ , and  $forStatementIR$ .

A list of initialization statements are type checked with the relation:

**ForInitStmtList\_ok:**

- Typing  $forInitStatementList$  under context  $typingContext$ :
- Result in context  $typingContext$  and  $forInitStatementIR^*$ .

This relation invokes the following relation for each initialization statement:

**ForInitStmt\_ok:**

- Typing  $forInitStatement$  under context  $typingContext$ :
- Result in context  $typingContext$  and  $forInitStatementIR$ .

**Typing  $forInitStatement$  under context  $typingContext$ :**

1. If let  $annotationList$  type name  $initializerOpt$  be  $forInitStatement$ :
  - a. If  $initializerOpt$  is `EMPTY`:
    - i. Let  $typeIR$  and a set of fresh type variables  $typeId^*$  be
      - the result of typing type, under cursor LOCAL and context  $typingContext$ .
    - ii. Check that  $typeId^*$  is an empty list.
    - iii. Let  $bound$  be bound type variables from the LOCAL layer of  $typingContext$ .

- iv. Check that  $\text{typeIR}$  is a well-formed type, with bound type variables  $\text{bound}$ .
  - v. Check that  $\text{typeIR}$  supports assignment.
  - vi. Let  $\text{nameIR}$  be the name of  $\text{name}$ .
  - vii. Let  $\text{TC}_1$  be typingContext where  $\text{nameIR}$  to INOUT  $\text{typeIR}$  DYN · is added to the LOCAL layer.
  - viii. Result in context  $\text{TC}_1$  and annotationList  $\text{typeIR}$   $\text{nameIR}$  ·.
- b. Else:
- i. Let  $\text{expression}_{\text{init}}$  be initializerOpt.
  - ii. Let  $\text{typeIR}$  and a set of fresh type variables  $\text{typeId}^*$  be
    - the result of typing type, under cursor LOCAL and context typingContext.
  - iii. Check that  $\text{typeId}^*$  is an empty list.
  - iv. Let  $\text{bound}$  be bound type variables from the LOCAL layer of typingContext.
  - v. Check that  $\text{typeIR}$  is a well-formed type, with bound type variables  $\text{bound}$ .
  - vi. Check that  $\text{typeIR}$  supports assignment.
  - vii. Let  $\text{typedExpressionIR}_{\text{init}}$  be
    - the result of typing  $\text{expression}_{\text{init}}$ , under cursor LOCAL and context typingContext.
  - viii. Let  $\text{typedExpressionIR}_{\text{init\_cast}}$  be !  $\text{typedExpressionIR}_{\text{init}}$  implicitly cast to  $\text{typeIR}$ .
  - ix. Let  $\text{nameIR}$  be the name of  $\text{name}$ .
  - x. Let  $\text{TC}_1$  be typingContext where  $\text{nameIR}$  to INOUT  $\text{typeIR}$  DYN · is added to the LOCAL layer.
  - xi. Result in context  $\text{TC}_1$  and annotationList  $\text{typeIR}$   $\text{nameIR} = \text{typedExpressionIR}_{\text{init\_cast}}$
2. Else:
- a. Let  $\text{forUpdateStatement}$  be  $\text{forInitStatement}$ .
  - b. Let  $\text{forUpdateStatementIR}$  be
    - the result of typing  $\text{forUpdateStatement}$  under context typingContext.
  - c. Result in context typingContext and  $\text{forUpdateStatementIR}$ .

A list of update statements are type checked with the relation:

**ForUpdateStmtList\_ok:**

- Typing  $\text{forUpdateStatementList}$  under context typingContext:
- Result in  $\text{forUpdateStatementIR}^*$ .

This relation invokes the following relation for each update statement:

**ForUpdateStmt\_ok:**

- Typing  $\text{forUpdateStatement}$  under context typingContext:
- Result in  $\text{forUpdateStatementIR}$ .

**Typing  $\text{forUpdateStatement}$  under context TC:**

1. If let  $lvalue_{callable} (argumentList)$  be `forUpdateStatement`:
  - a. Let context  $\_$ , abstract control flow  $\_$ , and `statementIR` be
    - the result of `typing`  $lvalue_{callable} (argumentList)$  ;, under cursor `LOCAL`, context `TC`, abstract control flow `CONT`, and loop context `NOLOOP`.
  - b. Check that `statementIR` has type `callStatementIR`.
  - c. Let `callableTargetIR`  $< typeArgumentIR^* > (argumentIR^*)$  ; be `statementIR`.
  - d. Result in `callableTargetIR`  $< typeArgumentIR^* > (argumentIR^*)$ .
2. Else if let  $lvalue_{callable} < typeArgumentList > (argumentList)$  be `forUpdateStatement`:
  - a. Let context  $\_$ , abstract control flow  $\_$ , and `statementIR` be
    - the result of `typing`  $lvalue_{callable} < typeArgumentList > (argumentList)$  ;, under cursor `LOCAL`, context `TC`, abstract control flow `CONT`, and loop context `NOLOOP`.
  - b. Check that `statementIR` has type `callStatementIR`.
  - c. Let `callableTargetIR`  $< typeArgumentIR^* > (argumentIR^*)$  ; be `statementIR`.
  - d. Result in `callableTargetIR`  $< typeArgumentIR^* > (argumentIR^*)$ .
3. Else:
  - a. Let `lvalue assignop expression` be `forUpdateStatement`.
  - b. Let context  $\_$ , abstract control flow  $\_$ , and `statementIR` be
    - the result of `typing` `lvalue assignop expression` ;, under cursor `LOCAL`, context `TC`, abstract control flow `CONT`, and loop context `NOLOOP`.
  - c. Check that `statementIR` has type `assignmentStatementIR`.
  - d. Let `typedLvalueIR assignop' typedExpressionIR` ; be `statementIR`.
  - e. Check that `assignop'` is equal to `assignop`.
  - f. Result in `typedLvalueIR assignop typedExpressionIR`.

### 13.10.1.2. Compile-time evaluation

**Compile-time evaluation of** `annotationList FOR ( forInitStatementListIR ; typedExpressionIR ; forUpdateStatementListIR ) statementIR'`, under cursor `p`, context `IC`, and store `STO`:

1. Let context  $IC_{body}$ , store  $STO_1$ , and `statementIRbody` be
  - the result of **compile-time evaluation of** `statementIR'`, under cursor `p`, context `IC`, and store `STO`.
2. Let `forStatementIR'` be `annotationList FOR ( forInitStatementListIR ; typedExpressionIR ; forUpdateStatementListIR ) statementIRbody`.
3. Result in context `IC`, store  $STO_1$ , and `forStatementIR'`.

### 13.10.1.3. Runtime evaluation

**Runtime evaluation of** `annotationList FOR ( forInitStatementListIR ; typedExpressionIR ; forUpdateStatementListIR ) statementIR'`, under cursor `LOCAL`, context `EC`, and state `ARCH`:

1. Let  $EC_1$  be `EC` with a new local frame.

2. Let the updated evaluation context  $EC_2$ , state  $ARCH_1$ , and  $statementResult$  be
  - the result of runtime evaluation of  $forInitStatementListIR$ , under evaluation context  $EC_1$  and state  $ARCH$ .
3. If let  $abortResult$  be  $statementResult$ :
  - a. Let  $EC_3$  be  $EC_2$  with the innermost frame removed.
  - b. Result in context  $EC_3$ , state  $ARCH_1$ , and  $abortResult$ .
4. Else if let  $continueEmptyResult$  be  $statementResult$ :
  - a. Let the updated evaluation context  $EC_3$ , state  $ARCH_2$ , and  $statementResult'$  be
    - the result of looping  $statementIR'$  with condition  $typedExpressionIR$  and updates  $forUpdateStatementListIR$ , under evaluation context  $EC_2$  and state  $ARCH_1$ .
  - b. Let  $EC_4$  be  $EC_3$  with the innermost frame removed.
  - c. Result in context  $EC_4$ , state  $ARCH_2$ , and  $statementResult'$ .

A list of initialization statements is evaluated with the relation:

**ForInitStmts\_eval:**

- Runtime evaluation of  $forInitStatementListIR$ , under evaluation context  $evalContext$  and state  $arch$ :
- Result in
  - the updated evaluation context  $evalContext$ , state  $arch$ , and  $statementResult$ .

An initialization statement is evaluated with the relation:

**ForInitStmt\_eval:**

- Runtime evaluation of  $forInitStatementIR$ , under evaluation context  $evalContext$  and state  $arch$ :
- Result in
  - the updated evaluation context  $evalContext$ , state  $arch$ , and  $statementResult$ .

**Runtime evaluation of  $forInitStatementIR$ , under evaluation context  $EC_0$  and state  $arch$ :**

1. If let  $annotationList$   $typeIR$   $nameIR$   $initializerIR^2$  be  $forInitStatementIR$ :
  - a. If  $initializerIR^2$  is none:
    - i. Let  $typeIR_{subst}$  be  $typeIR$  substituted by bound type variables in  $EC_0$  from the LOCAL layer.
    - ii. Let  $value_{init}$  be the default value for type  $typeIR_{subst}$ .
    - iii. Let  $EC_1$  be  $EC_0$  where  $nameIR$  to  $value_{init}$  is added to the LOCAL layer.
    - iv. Result in
      - the updated evaluation context  $EC_1$ , state  $arch$ , and  $EMPTY$ .
  - b. Let  $annotationList$   $typeIR$   $nameIR$   $initializerOptIR$  be  $forInitStatementIR$ .
  - c. If let  $= typedExpressionIR_{init}$  be  $initializerOptIR$ :
    - i. Let context  $EC_1$ , state  $ARCH_1$  and  $expressionResult$  be

- the result of **evaluating**  $\text{typedExpressionIR}_{\text{init}}$ , **under cursor** **LOCAL**, **context**  $\text{EC}_0$ , and **state**  $\text{arch}$ .
- ii. If let  $\text{abortResult}$  be  $\text{expressionResult}$ :
  - A. Result in
    - the updated evaluation context  $\text{EC}_1$ , state  $\text{ARCH}_1$ , and  $\text{abortResult}$ .
- iii. Else:
  - A. Let  $\text{value}_{\text{init}}$  be  $\text{expressionResult}$ .
  - B. Let  $\text{EC}_2$  be  $\text{EC}_1$  **where**  $\text{nameIR}$  **to**  $\text{value}_{\text{init}}$  **is added to the** **LOCAL** **layer**.
  - C. Result in
    - the updated evaluation context  $\text{EC}_2$ , state  $\text{ARCH}_1$ , and **EMPTY**.
- 2. Else:
  - a. Let  $\text{forUpdateStatementIR}$  be  $\text{forInitStatementIR}$ .
  - b. Let the updated evaluation context  $\text{EC}_1$ , state  $\text{ARCH}_1$ , and  $\text{statementResult}$  be
    - the result of **runtime evaluation of**  $\text{forUpdateStatementIR}$ , **under evaluation context**  $\text{EC}_0$  and **state**  $\text{arch}$ .
  - c. Result in
    - the updated evaluation context  $\text{EC}_1$ , state  $\text{ARCH}_1$ , and  $\text{statementResult}$ .

A list of update statements is evaluated with the relation:

**ForUpdateStmts\_eval:**

- Runtime evaluation of  $\text{forUpdateStatementListIR}$ , under evaluation context  $\text{evalContext}$  and state  $\text{arch}$ :
- Result in
  - the updated evaluation context  $\text{evalContext}$ , state  $\text{arch}$ , and  $\text{statementResult}$ .

An update statement is evaluated with the relation:

**ForUpdateStmt\_eval:**

- Runtime evaluation of  $\text{forUpdateStatementIR}$ , under evaluation context  $\text{evalContext}$  and state  $\text{arch}$ :
- Result in
  - the updated evaluation context  $\text{evalContext}$ , state  $\text{arch}$ , and  $\text{statementResult}$ .

**Runtime evaluation of**  $\text{forUpdateStatementIR}$ , **under evaluation context**  $\text{EC}_0$  and **state**  $\text{ARCH}_0$ :

1. If let  $\text{callableTargetIR} < \text{typeArgumentListIR} > ( \text{argumentListIR} )$  be  $\text{forUpdateStatementIR}$ :
  - a. Let context  $\text{EC}_1$ , state  $\text{ARCH}_1$ , and  $\text{statementResult}$  be
    - the result of **runtime evaluation of**  $\text{callableTargetIR} < \text{typeArgumentListIR} > ( \text{argumentListIR} )$  ;, **under cursor** **LOCAL**, **context**  $\text{EC}_0$ , and **state**  $\text{ARCH}_0$ .
  - b. Result in



- the updated evaluation context  $EC_1$ , state  $ARCH_1$ , and  $statementResult$ .

2. Else:

- Let  $typedLvalueIR$  assignop  $typedExpressionIR$  be forUpdateStatementIR.
- Let context  $EC_1$ , state  $ARCH_1$ , and  $statementResult$  be
  - the result of runtime evaluation of  $typedLvalueIR$  assignop  $typedExpressionIR$  ;, under cursor  $LOCAL$ , context  $EC_0$ , and state  $ARCH_0$ .
- Result in
  - the updated evaluation context  $EC_1$ , state  $ARCH_1$ , and  $statementResult$ .

With these, the 3-clause for statement is evaluated with the relation:

**ForThreeClauseStmt\_eval:**

- Looping  $statementIR$  with condition  $typedExpressionIR$  and updates  $forUpdateStatementListIR$ , under evaluation context  $evalContext$  and state  $arch$ :
- Result in
  - the updated evaluation context  $evalContext$ , state  $arch$ , and  $statementResult$ .

**Looping  $statementIR$  with condition  $typedExpressionIR$  and updates  $forUpdateStatementListIR$ , under evaluation context  $EC_0$  and state  $ARCH_0$ :**

- Let context  $EC_1$ , state  $ARCH_1$  and  $expressionResult$  be
  - the result of evaluating  $typedExpressionIR$ , under cursor  $LOCAL$ , context  $EC_0$ , and state  $ARCH_0$ .
- If let  $abortResult$  be  $expressionResult$ :
  - Result in
    - the updated evaluation context  $EC_1$ , state  $ARCH_1$ , and  $abortResult$ .
- If  $expressionResult$  is equal to `B false':
  - Result in
    - the updated evaluation context  $EC_1$ , state  $ARCH_1$ , and `EMPTY'.
- If  $expressionResult$  is equal to `B true':
  - Let context  $EC_2$ , state  $ARCH_2$ , and  $statementResult$  be
    - the result of runtime evaluation of  $statementIR$ , under cursor  $LOCAL$ , context  $EC_1$ , and state  $ARCH_1$ .
  - If let  $abortResult$  be  $statementResult$ :
    - Result in
      - the updated evaluation context  $EC_2$ , state  $ARCH_2$ , and  $abortResult$ .
  - Else if let  $returnResult$  be  $statementResult$ :
    - Result in
      - the updated evaluation context  $EC_2$ , state  $ARCH_2$ , and  $returnResult$ .
  - Else if let  $forBreakResult$  be  $statementResult$ :
    - Result in

- the updated evaluation context  $EC_2$ , state  $ARCH_2$ , and `'EMPTY'`.
- e. If `statementResult` is equal to `'EMPTY'` or `statementResult` is equal to `CONTINUE`:
  - i. Let the updated evaluation context  $EC_3$ , state  $ARCH_3$ , and `statementResult` be
    - the result of **runtime evaluation** of `forUpdateStatementListIR`, under evaluation context  $EC_2$  and state  $ARCH_2$ .
  - ii. If let `exitResult` be `statementResult`:
    - A. Result in
      - the updated evaluation context  $EC_3$ , state  $ARCH_3$ , and `EXIT`.
  - iii. Else if let `continueEmptyResult` be `statementResult`:
    - A. Let the updated evaluation context  $EC_4$ , state  $ARCH_4$ , and `statementResult` be
      - the result of **looping** `statementIR` with **condition** `typedExpressionIR` and **updates** `forUpdateStatementListIR`, under evaluation context  $EC_3$  and state  $ARCH_3$ .
    - B. Result in
      - the updated evaluation context  $EC_4$ , state  $ARCH_4$ , and `statementResult`.

## 13.10.2. **for-in** statements

The **for-in** statement executes the body once for each value in a range or each element in a list expression or header stack. The list or range expression itself will only be evaluated once, before the first iteration of the loop. All side effects in the list or range expression will occur before the first iteration of the loop body.

### 13.10.2.1. Type checking

After type checking, a **for-in** statement has the form:

```
forStatementIR
: annotationList FOR
  `( forInitStatementListIR ; typedExpressionIR ; forUpdateStatementListIR )
  statementIR
| annotationList FOR `( typeIR nameIR IN forCollectionExpressionIR )
  statementIR
| annotationList FOR
  `( annotationList typeIR nameIR IN forCollectionExpressionIR )
  statementIR
;

forCollectionExpressionIR
: typedExpressionIR
| typedExpressionIR .. typedExpressionIR
;
```

**Typing** `forStatement`, under cursor `LOCAL`, context `TC`, abstract control flow `f`, and loop context `l`:

1. If let `annotationList FOR ( type name IN forCollectionExpression ) statement` be `forStatement`:
  - a. Let `typeIR` and a set of fresh type variables `typedId*` be
    - the result of **typing** `type`, under cursor `LOCAL` and context `TC`.
  - b. Check that `typedId*` is an empty list.

- c. Let **bound** be **bound type variables** from the **LOCAL** layer of **TC**.
  - d. Check that **typeIR** is a well-formed type, with bound type variables **bound**.
  - e. Check that **typeIR** supports assignment.
  - f. Let **forCollectionExpressionIR** be
    - the result of **typing** **forCollectionExpression** under context **TC** with iterator type **typeIR**.
  - g. Let **TC<sub>1</sub>** be **TC** with a new local frame.
  - h. Let **nameIR** be the name of **name**.
  - i. Let **TC<sub>2</sub>** be **TC<sub>1</sub>** where **nameIR** to **INOUT typeIR DYN** is added to the **LOCAL** layer.
  - j. Let context **TC<sub>3</sub>**, abstract control flow **f<sub>post</sub>**, and **statementIR** be
    - the result of **typing** **statement'**, under cursor **LOCAL**, context **TC<sub>2</sub>**, abstract control flow **f**, and loop context **LOOP**.
  - k. Let **TC<sub>4</sub>** be **TC<sub>3</sub>** with the innermost frame removed.
  - l. Let **forStatementIR** be **annotationList FOR ( typeIR nameIR IN forCollectionExpressionIR ) statementIR**.
  - m. Result in context **TC**, abstract control flow **f<sub>post</sub>**, and **forStatementIR**.
2. Else if let **annotationList FOR ( annotationListNonEmpty type name IN forCollectionExpression ) statement'** be **forStatement**:
    - a. Let context **TC<sub>1</sub>**, abstract control flow **f<sub>post</sub>**, and **statementIR** be
      - the result of **typing** **annotationList FOR ( type name IN forCollectionExpression ) statement'**, under cursor **LOCAL**, context **TC**, abstract control flow **f**, and loop context **l**.
    - b. Check that **statementIR** has type **forStatementIR**.
    - c. Let **forStatementIR** be **statementIR**.
    - d. Result in context **TC**, abstract control flow **f<sub>post</sub>**, and **forStatementIR**.

Collection expressions are type checked with the relation:

**ForCollectionExpr\_ok**:

- Typing **forCollectionExpression** under context **typingContext** with iterator type **typeIR**:
- Result in **forCollectionExpressionIR**.

**Typing forCollectionExpression under context TC with iterator type typeIR<sub>var</sub>**:

1. If let **expression** be **forCollectionExpression**:
  - a. Let **typedExpressionIR** be
    - the result of **typing** **expression**, under cursor **LOCAL** and context **TC**.
  - b. Let **typeIR<sub>expression</sub>** be the type of **typedExpressionIR**.
  - c. Let **typeIR** be **typeIR<sub>expression</sub>** with **typeddefs** unrolled.
  - d. If let **LIST < typeIR<sub>e</sub> >** be **typeIR**:
    - i. Check that **typeIR<sub>e</sub>** can be implicitly cast to **typeIR<sub>var</sub>**.
    - ii. Result in **typedExpressionIR**.

- e. Else if let  $\text{typeIR}_e [ \_ ]$  be  $\text{typeIR}$ :
  - i. Check that  $\text{typeIR}_e$  and  $\text{typeIR}_{\text{var}}$  are the same type.
  - ii. Result in  $\text{typedExpressionIR}$ .
2. Else:
  - a. Let  $\text{expression}_i \dots \text{expression}_r$  be  $\text{forCollectionExpression}$ .
  - b. Let  $\text{typedExpressionIR}_i$  be
    - the result of typing  $\text{expression}_i$ , under cursor LOCAL and context TC.
  - c. Let  $\text{typedExpressionIR}_r$  be
    - the result of typing  $\text{expression}_r$ , under cursor LOCAL and context TC.
  - d. Let  $\text{typedExpressionIR}_{i\_casted}$  be !  $\text{typedExpressionIR}_i$  implicitly cast to  $\text{typeIR}_{\text{var}}$ .
  - e. Let  $\text{typedExpressionIR}_{r\_casted}$  be !  $\text{typedExpressionIR}_r$  implicitly cast to  $\text{typeIR}_{\text{var}}$ .
  - f. Let  $\text{typeIR}_i$  be the type of  $\text{typedExpressionIR}_{i\_casted}$ .
  - g. Let  $\text{typeIR}_r$  be the type of  $\text{typedExpressionIR}_{r\_casted}$ .
  - h. Check that  $\text{typeIR}_i$  and  $\text{typeIR}_r$  can be used as range bounds.
  - i. Result in  $\text{typedExpressionIR}_{i\_casted} \dots \text{typedExpressionIR}_{r\_casted}$ .

### 13.10.2.2. Compile-time evaluation

Compile-time evaluation of  $\text{forStatementIR}$ , under cursor  $p$ , context  $IC$ , and store  $STO$ :

1. If let  $\text{annotationList FOR ( typeIR nameIR IN forCollectionExpressionIR ) statementIR'}$  be  $\text{forStatementIR}$ :
  - a. Let context  $IC_{\text{body}}$ , store  $STO_1$ , and  $\text{statementIR}_{\text{body}}$  be
    - the result of compile-time evaluation of  $\text{statementIR'}$ , under cursor  $p$ , context  $IC$ , and store  $STO$ .
  - b. Let  $\text{forStatementIR'}$  be  $\text{annotationList FOR ( typeIR nameIR IN forCollectionExpressionIR ) statementIR}_{\text{body}}$ .
  - c. Result in context  $IC$ , store  $STO_1$ , and  $\text{forStatementIR'}$ .
2. Else if let  $\text{annotationList FOR ( annotationList' typeIR nameIR IN forCollectionExpressionIR ) statementIR'}$  be  $\text{forStatementIR}$ :
  - a. Check that  $\text{annotationList}$  is equal to  $\text{annotationList'}$ .
  - b. Let context  $IC_{\text{body}}$ , store  $STO_1$ , and  $\text{statementIR}_{\text{body}}$  be
    - the result of compile-time evaluation of  $\text{statementIR'}$ , under cursor  $p$ , context  $IC$ , and store  $STO$ .
  - c. Let  $\text{forStatementIR'}$  be  $\text{annotationList FOR ( annotationList typeIR nameIR IN forCollectionExpressionIR ) statementIR}_{\text{body}}$ .
  - d. Result in context  $IC$ , store  $STO_1$ , and  $\text{forStatementIR'}$ .

### 13.10.2.3. Runtime evaluation

Runtime evaluation of  $\text{forStatementIR}$ , under cursor LOCAL, context  $EC$ , and state  $ARCH$ :

1. If let  $\text{annotationList FOR ( typeIR nameIR IN forCollectionExpressionIR ) statementIR'}$  be  $\text{forStatementIR}$ :

- a. Let  $EC_1$  be  $EC$  with a new local frame.
  - b. Let the updated evaluation context  $EC_2$ , state  $ARCH_1$ , and  $expressionListResult$  be
    - the result of runtime evaluation of  $forCollectionExpressionIR$ , under evaluation context  $EC_1$  and state  $ARCH$ .
  - c. If let  $abortResult$  be  $expressionListResult$ :
    - i. Let  $EC_3$  be  $EC_2$  with the innermost frame removed.
    - ii. Result in context  $EC_3$ , state  $ARCH_1$ , and  $abortResult$ .
  - d. Else:
    - i. Let  $value^*$  be  $expressionListResult$ .
    - ii. Let  $typeIR_{subst}$  be  $typeIR$  substituted by bound type variables in  $EC$  from the LOCAL layer.
    - iii. Let  $value_{init}$  be the default value for type  $typeIR_{subst}$ .
    - iv. Let  $EC_3$  be  $EC_2$  where  $nameIR$  to  $value_{init}$  is added to the LOCAL layer.
    - v. Let the updated evaluation context  $EC_4$ , state  $ARCH_2$ , and  $statementResult$  be
      - the result of looping over  $value^*$  with loop variable  $nameIR$  and body  $statementIR'$ , under evaluation context  $EC_3$  and state  $ARCH_1$ .
    - vi. Let  $EC_5$  be  $EC_4$  with the innermost frame removed.
    - vii. Result in context  $EC_5$ , state  $ARCH_2$ , and  $statementResult$ .
2. Else if let  $annotationList$  FOR (  $annotationList_{in}$   $typeIR$   $nameIR$  IN  $forCollectionExpressionIR$  )  $statementIR'$  be  $forStatementIR$ :
    - a. Let context  $EC_1$ , state  $ARCH_1$ , and  $statementResult$  be
      - the result of runtime evaluation of  $annotationList$  FOR (  $typeIR$   $nameIR$  IN  $forCollectionExpressionIR$  )  $statementIR'$ , under cursor LOCAL, context  $EC$ , and state  $ARCH$ .
    - b. Result in context  $EC_1$ , state  $ARCH_1$ , and  $statementResult$ .

Collection expressions are evaluated with the relation:

#### ForCollectionExpr\_eval:

- Runtime evaluation of  $forCollectionExpressionIR$ , under evaluation context  $evalContext$  and state  $arch$ :
- Result in
  - the updated evaluation context  $evalContext$ , state  $arch$ , and  $expressionListResult$ .

#### Runtime evaluation of $typedExpressionIR$ , under evaluation context $EC_0$ and state $ARCH_0$ :

1. Let context  $EC_1$ , state  $ARCH_1$ , and  $expressionResult$  be
  - the result of evaluating  $typedExpressionIR$ , under cursor LOCAL, context  $EC_0$ , and state  $ARCH_0$ .
2. If let  $abortResult$  be  $expressionResult$ :
  - a. Result in
    - the updated evaluation context  $EC_1$ , state  $ARCH_1$ , and  $abortResult$ .
3. Else:
  - a. Let  $value$  be  $expressionResult$ .

- b. If let `listValue` be `value`:
  - i. Let `LIST [ value* ]` be `listValue`.
  - ii. Result in
    - the updated evaluation context `EC1`, state `ARCH1`, and `value*`.
- c. Else if let `headerStackValue` be `value`:
  - i. Let `HEADER_STACK [ value* ( _ ; _ ) ]` be `headerStackValue`.
  - ii. Result in
    - the updated evaluation context `EC1`, state `ARCH1`, and `value*`.

With these, the `for-in` statement is evaluated with the relation:

#### `ForInStmt_eval`:

- Looping over `value*` with loop variable `nameIR` and body `statementIR`, under evaluation context `evalContext` and state `arch`:
- Result in
  - the updated evaluation context `evalContext`, state `arch`, and `statementResult`.

#### Looping over `value*` with loop variable `nameIR` and body `statementIR`, under evaluation context `evalContext` and state `arch`:

1. If `value*` is equal to `:`:
  - a. Result in
    - the updated evaluation context `evalContext`, state `arch`, and `'EMPTY'`.
2. If let `valuen :: valuet*` be `value*`:
  - a. Let `EC1` be `evalContext` where `nameIR` is updated to `valuen` from the `LOCAL` layer.
  - b. Let context `EC2`, state `ARCH1`, and `statementResult` be
    - the result of runtime evaluation of `statementIR`, under cursor `LOCAL`, context `EC1`, and state `arch`.
  - c. If let `abortResult` be `statementResult`:
    - i. Result in
      - the updated evaluation context `EC2`, state `ARCH1`, and `abortResult`.
  - d. Else if let `returnResult` be `statementResult`:
    - i. Result in
      - the updated evaluation context `EC2`, state `ARCH1`, and `returnResult`.
  - e. Else if let `forBreakResult` be `statementResult`:
    - i. Result in
      - the updated evaluation context `EC2`, state `ARCH1`, and `'EMPTY'`.
  - f. If `statementResult` is equal to `'EMPTY'` or `statementResult` is equal to `CONTINUE`:
    - i. Let the updated evaluation context `EC3`, state `ARCH2`, and `statementResult'` be

- the result of **looping over**  $value_i$ , **with loop variable**  $nameIR$  and **body**  $statementIR$ , **under evaluation context**  $EC_2$  and **state**  $ARCH_1$ .

ii. Result in

- the updated evaluation context  $EC_3$ , state  $ARCH_2$ , and  $statementResult$ '.

## 13.11. Break statements

A **break**; statement exists the enclosing **for** loop.

```
breakStatement
: BREAK ;
;
```

### 13.11.1. Type checking

After type checking, a **break**; statement has the form:

```
breakStatementIR = breakStatement
```

**Typing**  $breakStatement$ , **under cursor**  $LOCAL$ , **context**  $TC$ , **abstract control flow**  $f$ , and **loop context**  $LOOP$ :

1. Result in context  $TC$ , abstract control flow  $f$ , and  $breakStatement$ .

### 13.11.2. Compile-time evaluation

**Compile-time evaluation of**  $breakStatementIR$ , **under cursor**  $p$ , **context**  $IC$ , and **store**  $STO$ :

1. Result in context  $IC$ , store  $STO$ , and  $breakStatementIR$ .

### 13.11.3. Runtime evaluation

A **break**; statement yields the result:

```
forBreakResult
: BREAK
;
```

**Runtime evaluation of**  $BREAK$  ;, **under cursor**  $LOCAL$ , **context**  $EC$ , and **state**  $ARCH$ :

1. Result in context  $EC$ , state  $ARCH$ , and  $BREAK$ .

## 13.12. Continue statements

A **continue**; statement skips the current iteration of the enclosing **for** loop.

```
continueStatement
: CONTINUE ;
;
```

### 13.12.1. Type checking

After type checking, a `continue;` statement has the form:

```
continueStatementIR = continueStatement
```

Typing `continueStatement`, under cursor `LOCAL`, context `TC`, abstract control flow `f`, and loop context `LOOP`:

1. Result in context `TC`, abstract control flow `f`, and `continueStatement`.

### 13.12.2. Compile-time evaluation

Compile-time evaluation of `continueStatementIR`, under cursor `p`, context `IC`, and store `STO`:

1. Result in context `IC`, store `STO`, and `continueStatementIR`.

### 13.12.3. Runtime evaluation

A `continue;` statement yields the result:

```
forContinueResult
: CONTINUE
;
```

Runtime evaluation of `CONTINUE ;`, under cursor `LOCAL`, context `EC`, and state `ARCH`:

1. Result in context `EC`, state `ARCH`, and `CONTINUE`.

## 13.13. Switch statements

The `switch` statement can only be used within `control` blocks, `action` bodies, or function bodies.

```
switchStatement
: SWITCH `( expression ) `{ switchCaseList }
;

switchCaseList
: /* empty */
| switchCaseList switchCase
;

switchCase
: switchLabel : blockStatement
```



```

| switchLabel :
;

switchLabel
: DEFAULT
| expressionNonBrace
;

```

The `expressionNonBrace` is the same as `expression` as defined in [Chapter 14](#), except it does not include any cases that can begin with a left brace `{` character, to avoid syntactic ambiguity with a block statement.

There are two kinds of `switch` expressions allowed, described separately in the following two subsections.

### 13.13.1. Notes common to all switch statements

It is a compile-time error if two labels of a `switch` statement equal each other. The switch label values need not include all possible values of the switch expression. It is optional to have a `switch` case with the `default` label, but if one is present, it must be the last one in the `switch` statement.

If a switch label is not followed by a block statement, it falls through to the next label. However, if a block statement is present, it does not fall through. Note that this is different from C-style `switch` statements, where a `break` is needed to prevent fall-through. If the last switch label is not followed by a block statement, the behavior is the same as if the last switch label were followed by an empty block statement `{ }`.

When a `switch` statement is executed, first the switch expression is evaluated, and any side effects from evaluating this expression are visible to any `switch` case that is executed. Among switch labels that are not `default`, at most one of them can equal the value of the switch expression. If one is equal, that switch case is executed.

If no labels are equal to the `switch` expression, then:

- if there is a `default` label, the case with the `default` label is executed.
- if there is no `default` label, then no switch case is executed, and execution continues after the end of the `switch` statement, with no side effects (except any that were caused by evaluating the `switch` expression).

See "Implementing generalized P4\_16 switch statements" for possible techniques that one might use to implement generalized switch statements.<sup>[1]</sup>

### 13.13.2. Switch statement on match-action table result

This type of `switch` statement can only be used within control `apply` blocks. For this variant of `switch` statement, the expression must be of the form `t.apply().action_run`, where `t` is the name of a table (see [Section 16.3.7](#)). All switch labels must be names of actions of the table `t`, or `default`.

```

switch (t.apply().action_run) {
  action1:                                // fall-through to action2:
  action2: { /* body omitted */ }
  action3: { /* body omitted */ } // no fall-through from action2 to action3 labels
  default: { /* body omitted */ }
}

```

Note that the `default` label of the `switch` statement is used to match on the kind of action executed, no matter whether there was a table hit or miss. The `default` label does not indicate that the table missed and the `default_action` was executed.

### 13.13.2.1. Type checking

Typing SWITCH ( expression<sub>switch</sub> ) { switchCaseList }, under cursor LOCAL, context TC, abstract control flow f, and loop context l:

1. Let typedExpressionIR<sub>switch</sub> be
  - the result of typing expression<sub>switch</sub> under cursor LOCAL and context TC.
2. Let typeIR<sub>switch</sub> be the type of typedExpressionIR<sub>switch</sub>.
3. Let typeIR be typeIR<sub>switch</sub> with typedefs unrolled.
4. Check that typeIR has type tableMetadataEnumTypeIR.
5. Let TABLE\_ENUM typeId<sub>table\_enum</sub> { \_ } be typeIR.
6. Let text be the text typeId<sub>table\_enum</sub> with the suffix ")" removed.
7. Let typeId<sub>table</sub> be the text text with the prefix "action\_list(" removed.
8. Let abstract control flow f<sub>post</sub>, switchCaseIR\*, and labels switchLabel\* be
  - the result of typing switchCaseList for table typeId<sub>table</sub>, under context TC, abstract control flow f and loop context l.
9. Check that default label is only in the last position of switchLabel\*.
10. Check that the elements of switchLabel\* are distinct.
11. Let switchStatementIR be SWITCH ( typedExpressionIR<sub>switch</sub> ) { switchCaseIR\* }.
12. Result in context TC, abstract control flow f<sub>post</sub>, and switchStatementIR.

Switch cases are type checked with the relation:

SwitchCaseList\_table\_ok:

- Typing switchCaseList for table typeId, under context typingContext, abstract control flow flow and loop context loopctxt:
- Result in abstract control flow flow, switchCaseListIR, and labels switchLabel\*.

A switch case is type checked with:

SwitchCase\_table\_ok:

- Typing switchCase for table typeId, under context typingContext with abstract control flow flow and loop context loopctxt:
- Result in abstract control flow flow and label switchCaseIR.

Typing switchCase for table typeId<sub>table</sub>, under context TC with abstract control flow f and loop context l:

1. If let switchLabel : blockStatement be switchCase:
  - a. Let switchLabelIR be
    - the result of typing switchLabel for table typeId<sub>table</sub>, under context TC.

- b. Let context  $TC_{post}$ , abstract control flow  $f_{post}$ , and  $blockStatementIR$  be
    - the result of **typing**  $blockStatement$ , under context  $TC$ , abstract control flow  $f$ , and loop context  $l$ .
  - c. Let  $switchCaseIR$  be  $switchLabelIR : blockStatementIR$ .
  - d. Result in abstract control flow  $f_{post}$  and label  $switchCaseIR$ .
2. Else:
- a. Let  $switchLabel$  be  $switchCase$ .
  - b. Let  $switchLabelIR$  be
    - the result of **typing**  $switchLabel$  for table  $typed_{table}$ , under context  $TC$ .
  - c. Let  $switchCaseIR$  be  $switchLabelIR$  .:
  - d. Result in abstract control flow  $f$  and label  $switchCaseIR$ .

A switch label is type checked with:

**SwitchLabel\_table\_ok:**

- Typing  $switchLabel$  for table  $typed$ , under context  $typingContext$ :
- Result in  $switchLabelIR$ .

**Typing**  $switchLabel$  for table  $typed_{table}$ , under context  $TC$ :

1. If  $switchLabel$  is **DEFAULT**:
  - a. Result in **DEFAULT**.
2. Else if let  $prefixedNonTypeName$  be  $switchLabel$ :
  - a. Let  $prefixedNameIR$  be the **prefixed name of**  $prefixedNonTypeName$ .
  - b. Check that  $prefixedNameIR$  matches pattern ` %`.
  - c. Let  $nameIR_{label}$  be  $prefixedNameIR$ .
  - d. Let  $typed_{table\_enum}$  be the **concatenation of** [ "action\_list(",  $typed_{table}$ , ")" ].
  - e. Let  $id_{label}$  be the **concatenation of** [  $typed_{table\_enum}$ , ".",  $nameIR_{label}$  ].
  - f. Let  $_{type}IR_{label} \text{ ctk}_{label} \text{ value}^?$  be **! the type of variable**  $id_{label}$  **from the LOCAL layer of**  $TC$ .
  - g. Check that  $value^?$  is defined.
  - h. Let  $value_{label}$  be  $value^?$ .
  - i. Check that  $value_{label}$  is equal to  $TABLE\_ENUM \text{ typed}_{table\_enum} . nameIR_{label}$ .
  - j. Let  $typedExpressionIR_{label}$  be  $nameIR_{label}$  **annotated with a pair of type**  $typeIR_{label}$  **and compile-time known-ness**  $ctk_{label}$ .
  - k. Result in  $typedExpressionIR_{label}$ .

### 13.13.2.2. Compile-time evaluation

**Compile-time evaluation of** `SWITCH ( typedExpressionIR ) { switchCaseListIR }, under cursor p, context IC,`

and store  $STO$ :

1. Let the updated store  $STO_1$  and  $switchCaseListIR_{inst}$  be
  - the result of compile-time evaluation of switch cases  $switchCaseListIR$ , under cursor  $p$ , instantiation context  $IC$ , and store  $STO$ .
2. Result in context  $IC$ , store  $STO_1$ , and  $SWITCH (typedExpressionIR) \{ switchCaseListIR_{inst} \}$ .

The compile-time evaluation of switch cases is defined with the relation:

**SwitchCases\_inst:**

- Compile-time evaluation of switch cases  $switchCaseIR^*$ , under cursor  $cursor$ , instantiation context  $instContext$ , and store  $store$ :
- Result in the updated store  $store$  and  $switchCaseIR^*$ .

A switch case is compile-time evaluated with:

**SwitchCase\_inst:**

- Compile-time evaluation of  $switchCaseIR$ , under cursor  $cursor$ , instantiation context  $instContext$ , and store  $store$ :
- Result in the updated store  $store$  and  $switchCaseIR$ .

**Compile-time evaluation of  $switchCaseIR$ , under cursor  $p$ , instantiation context  $IC$ , and store  $store$ :**

1. If let  $switchLabelIR : blockStatementIR$  be  $switchCaseIR$ :
  - a. Let context  $IC_{switch}$ , store  $STO_1$ , and  $statementIR$  be
    - the result of compile-time evaluation of  $blockStatementIR$ , under cursor  $p$ , context  $IC$ , and store  $store$ .
  - b. Check that  $statementIR$  has type  $blockStatementIR$ .
  - c. Let  $blockStatementIR_{inst}$  be  $statementIR$ .
  - d. Result in the updated store  $STO_1$  and  $switchLabelIR : blockStatementIR_{inst}$ .
2. Else:
  - a. Let  $switchLabelIR$  be  $switchCaseIR$ .
  - b. Result in the updated store  $store$  and  $switchLabelIR$  :.

### 13.13.2.3. Runtime evaluation

**Runtime evaluation of  $SWITCH (typedExpressionIR) \{ switchCaseIR^* \}$ , under cursor  $LOCAL$ , context  $EC$ , and state  $ARCH$ :**

1. Let context  $EC_1$ , state  $ARCH_1$ , and  $expressionResult$  be
  - the result of evaluating  $typedExpressionIR$ , under cursor  $LOCAL$ , context  $EC$ , and state  $ARCH$ .

2. If let **abortResult** be **expressionResult**:
  - a. Result in context  $EC_1$ , state  $ARCH_1$ , and **abortResult**.
3. Else:
  - a. Let **value** be **expressionResult**.
  - b. Check that **value** has type **tableMetadataEnumValue**.
  - c. Let  $TABLE\_ENUM\_id_{enum}$  be **value**.
  - d. Let the matched block **blockStatementIR**<sup>2</sup> be
    - the result of **runtime evaluation of switchCaseIR**<sup>\*</sup> for invocation of table  $id_{enum}$ .
  - e. If let **blockStatementIR**<sup>'</sup> be **blockStatementIR**<sup>2</sup>:
    - i. Let context  $EC_2$ , state  $ARCH_2$ , and **statementResult** be
      - the result of **runtime evaluation of blockStatementIR**<sup>'</sup>, under cursor **LOCAL**, context  $EC_1$ , and state  $ARCH_1$ .
    - ii. Result in context  $EC_2$ , state  $ARCH_2$ , and **statementResult**.
  - f. Else:
    - i. Result in context  $EC_1$ , state  $ARCH_1$ , and **EMPTY**.

Switch cases are runtime evaluated with the relation:

#### SwitchCases\_table\_eval:

- Runtime evaluation of **switchCaseListIR** for invocation of table **id**:
- Result in the matched block **blockStatementIR**<sup>2</sup>.

#### Runtime evaluation of **switchCaseIR**<sup>\*</sup> for invocation of table **id**:

1. If **switchCaseIR**<sup>\*</sup> is equal to **.**:
  - a. Result in the matched block **.**
2. If let **switchCaseIR**<sub>n</sub> :: **switchCaseIR**<sub>i</sub><sup>\*</sup> be **switchCaseIR**<sup>\*</sup>:
  - a. If let **switchLabelIR**<sub>n</sub> : **blockStatementIR**<sub>n</sub> be **switchCaseIR**<sub>n</sub>:
    - i. If **id matches switchLabelIR**<sub>n</sub>:
      - A. Result in the matched block **blockStatementIR**<sub>n</sub>.
    - ii. Else:
      - A. Let the matched block **blockStatementIR**<sup>2</sup> be
        - the result of **runtime evaluation of switchCaseIR**<sub>i</sub><sup>\*</sup> for invocation of table **id**.
      - B. Result in the matched block **blockStatementIR**<sup>2</sup>.
  - b. Else:
    - i. Let **switchLabelIR**<sub>n</sub> : be **switchCaseIR**<sub>n</sub>.
    - ii. If **id matches switchLabelIR**<sub>n</sub>:
      - A. Let **bool**<sup>\*</sup> be the list of **bool**, obtained by repeating:

- Let `bool` be `switchCaseIRi` is not a fall-through case.

for each `switchCaseIRi` in `switchCaseIRt*`

- B. Let `switchCaseIR*` be `switchCaseIRt*` filtered by `bool*`.
  - C. Check that `switchCaseIR*` is a non-empty list.
  - D. Let `switchCaseIR" :: _*` be `switchCaseIR*`.
  - E. Check that `switchCaseIR"` matches pattern `% : %`.
  - F. Let `_ : blockStatementIR` be `switchCaseIR"`.
  - G. Result in the matched block `blockStatementIR`.
- iii. Else:
- A. Let the matched block `blockStatementIR?` be
    - the result of runtime evaluation of `switchCaseIRi*` for invocation of table `id`.
  - B. Result in the matched block `blockStatementIR?`.

### 13.13.3. Switch statement on numeric or enumerated type

For this variant of `switch` statement, the expression must evaluate to a result with one of these types:

- `bit<W>`
- `int<W>`
- `enum`, either with or without an underlying representation specified
- `error`

All switch labels must be expressions with compile-time known values, and must have a type that can be implicitly cast to the type of the `switch` expression (see [sec-implicit-casts]). Switch labels must not begin with a left brace character `{`, to avoid ambiguity with a block statement.

```
// Assume the expression hdr.ethernet.etherType has type bit<16>.
switch (hdr.ethernet.etherType) {
  0x86dd: { /* body omitted */ }
  0x0800: // fall-through to the next body
  0x0802: { /* body omitted */ }
  0xcafe: { /* body omitted */ }
  default: { /* body omitted */ }
}
```

#### 13.13.3.1. Type checking

Typing `SWITCH ( expressionswitch ) { switchCaseList }`, under cursor `LOCAL`, context `TC`, abstract control flow `f`, and loop context `l`:

1. Let `typedExpressionIRswitch` be
  - the result of typing `expressionswitch` under cursor `LOCAL` and context `TC`.
2. Let `typeIRswitch` be the type of `typedExpressionIRswitch`.
3. Check that `typeIRswitch` is a valid switch key type.
4. Let abstract control flow `fpost` and labels `switchCaseIR*` be

- the result of **typing** `switchCaseList` under context `TC` with abstract control flow `f`, loop context `I`, and switch key type `typeIRswitch`.
5. Check that **default label** is only in the last position of `switchLabel*`.
  6. Check that **the elements** of `switchLabel*` are distinct.
  7. Let `switchStatementIR` be `SWITCH ( typedExpressionIRswitch ) { switchCaseIR* }`.
  8. Result in context `TC`, abstract control flow `fpost`, and `switchStatementIR`.

Switch cases are type checked with the relation:

**SwitchCaseList\_general\_ok:**

- Typing `switchCaseList` under context `typingContext` with abstract control flow `flow`, loop context `loopctxt`, and switch key type `typeIR`:
- Result in abstract control flow `flow` and labels `switchCaseListIR`.

A switch case is type checked with:

**SwitchCase\_general\_ok:**

- Typing `switchCase` under context `typingContext` with abstract control flow `flow`, loop context `loopctxt`, and switch key type `typeIR`:
- Result in abstract control flow `flow` and label `switchCaseIR`.

**Typing** `switchCase` under context `TC` with abstract control flow `f`, loop context `I`, and switch key type `typeIRswitch`:

1. If let `switchLabel : blockStatement` be `switchCase`:
  - a. Let `switchLabelIR` be
    - the result of **typing** `switchLabel` under context `TC` with switch key type `typeIRswitch`.
  - b. Let context `TCpost`, abstract control flow `fpost`, and `blockStatementIR` be
    - the result of **typing** `blockStatement`, under context `TC`, abstract control flow `f`, and loop context `I`.
  - c. Let `switchCaseIR` be `switchLabelIR : blockStatementIR`.
  - d. Result in abstract control flow `fpost` and label `switchCaseIR`.
2. Else:
  - a. Let `switchLabel :` be `switchCase`.
  - b. Let `switchLabelIR` be
    - the result of **typing** `switchLabel` under context `TC` with switch key type `typeIRswitch`.
  - c. Let `switchCaseIR` be `switchLabelIR :`.
  - d. Result in abstract control flow `f` and label `switchCaseIR`.

A switch label is type checked with:

SwitchLabel\_general\_ok:

- Typing `switchLabel` under context `typingContext` with switch key type `typeIR`:
- Result in `switchLabelIR`.

Typing `switchLabel` under context `TC` with switch key type `typeIR`:

1. If `switchLabel` is `DEFAULT`:
  - a. Result in `DEFAULT`.
2. Else:
  - a. Let `expressionNonBracelabel` be `switchLabel`.
  - b. Let `expressionlabel` be the expression corresponding to `expressionNonBracelabel`.
  - c. Let `typedExpressionIRlabel` be
    - the result of typing `expressionlabel`, under cursor `LOCAL` and context `TC`.
  - d. Let `typedExpressionIRlabel_cast` be ! `typedExpressionIRlabel` implicitly cast to `typeIR`.
  - e. Let a pair of type `_` and compile-time known-ness `ctk` be the note of `typedExpressionIRlabel_cast`.
  - f. Check that `ctk` is `LCTK`.
  - g. Result in `typedExpressionIRlabel_cast`.

### 13.13.3.2. Compile-time evaluation

See Section 13.13.2.2.

### 13.13.3.3. Runtime evaluation

Runtime evaluation of `SWITCH ( typedExpressionIR ) { switchCaseIR* },` under cursor `LOCAL`, context `EC`, and state `ARCH`:

1. Let context `EC1`, state `ARCH1` and `expressionResult` be
  - the result of evaluating `typedExpressionIR`, under cursor `LOCAL`, context `EC`, and state `ARCH`.
2. If let `abortResult` be `expressionResult`:
  - a. Result in context `EC1`, state `ARCH1`, and `abortResult`.
3. Else:
  - a. Let `value` be `expressionResult`.
  - b. Let the updated evaluation context `EC2`, state `ARCH2`, and `blockStatementIR'` be
    - the result of runtime evaluation of `switchCaseIR*`, under evaluation context `LOCAL` and state `EC1` with switch key `value`.
  - c. If let `blockStatementIR'` be `blockStatementIR'`:
    - i. Let context `EC3`, state `ARCH3`, and `statementResult` be
      - the result of runtime evaluation of `blockStatementIR'`, under cursor `LOCAL`, context `EC2`, and state `ARCH2`.



- ii. Result in context  $EC_3$ , state  $ARCH_3$ , and  $statementResult$ .
- d. Else:
  - i. Result in context  $EC_2$ , state  $ARCH_2$ , and  $EMPTY$ .

Switch cases are runtime evaluated with the relation:

#### SwitchCases\_general\_eval:

- Runtime evaluation of  $switchCaseListIR$ , under evaluation context  $cursor$  and state  $evalContext$  with switch key  $value$ :
- Result in
  - the updated evaluation context  $evalContext$ , state  $arch$ , and  $blockStatementIR^?$ .

Runtime evaluation of  $switchCaseIR^*$ , under evaluation context  $LOCAL$  and state  $EC_0$  with switch key  $value$ :

1. If  $switchCaseIR^*$  is equal to  $\cdot$ :
  - a. Result in
    - the updated evaluation context  $EC_0$ , state  $ARCH_0$ , and  $\cdot$ .
2. If let  $switchCaseIR_h :: switchCaseIR_t^*$  be  $switchCaseIR^*$ :
  - a. If let  $switchLabelIR_h : blockStatementIR_h$  be  $switchCaseIR_h$ :
    - i. Let the updated evaluation context  $EC_1$ , state  $ARCH_1$ , and  $expressionResult$  be
      - the result of runtime evaluation of  $ARCH_0$ , under evaluation context  $LOCAL$  and state  $EC_0$ .
    - ii. Check that  $expressionResult$  has type  $continueResult<value>$ .
    - iii. Let  $value_{label}$  be  $expressionResult$ .
    - iv. If  $value$  matches  $value_{label}$ :
      - A. Result in
        - the updated evaluation context  $EC_1$ , state  $ARCH_1$ , and  $blockStatementIR_h$ .
    - v. Else:
      - A. Let the updated evaluation context  $EC_2$ , state  $ARCH_2$ , and  $blockStatementIR^?$  be
        - the result of runtime evaluation of  $switchCaseIR_t^*$ , under evaluation context  $LOCAL$  and state  $EC_1$  with switch key  $value$ .
      - B. Result in
        - the updated evaluation context  $EC_2$ , state  $ARCH_2$ , and  $blockStatementIR^?$ .
  - b. Else:
    - i. Let  $switchLabelIR_h$  : be  $switchCaseIR_h$ .
    - ii. Let the updated evaluation context  $EC_1$ , state  $ARCH_1$ , and  $expressionResult$  be
      - the result of runtime evaluation of  $ARCH_0$ , under evaluation context  $LOCAL$  and state  $EC_0$ .
    - iii. Check that  $expressionResult$  has type  $continueResult<value>$ .

- iv. Let  $value_{label}$  be `expressionResult`.
- v. If  $value$  matches  $value_{label}$ :
  - A. Let  $bool^*$  be the list of `bool`, obtained by repeating:
    - Let `bool` be `switchCaseIRt` is not a fall-through case.
 for each `switchCaseIRt` in `switchCaseIRt*`
  - B. Let `switchCaseIR*` be `switchCaseIRt*` filtered by  $bool^*$ .
  - C. Check that `switchCaseIR*` is a non-empty list.
  - D. Let `switchCaseIR" :: _*` be `switchCaseIR*`.
  - E. Check that `switchCaseIR"` matches pattern `% : %`.
  - F. Let `_ : blockStatementIR` be `switchCaseIR"`.
  - G. Result in
    - the updated evaluation context  $EC_1$ , state  $ARCH_1$ , and `blockStatementIR`.
- vi. Else:
  - A. Let the updated evaluation context  $EC_2$ , state  $ARCH_2$ , and `blockStatementIR2` be
    - the result of runtime evaluation of `switchCaseIRt*`, under evaluation context `LOCAL` and state  $EC_1$  with switch key `value`.
  - B. Result in
    - the updated evaluation context  $EC_2$ , state  $ARCH_2$ , and `blockStatementIR2`.

A switch label is runtime evaluated with:

#### SwitchLabel\_general\_eval:

- Runtime evaluation of `arch`, under evaluation context `cursor` and state `evalContext`:
- Result in
  - the updated evaluation context `evalContext`, state `arch`, and `expressionResult`.

#### Runtime evaluation of $ARCH_0$ , under evaluation context `LOCAL` and state $EC_0$ :

1. If `switchLabelIR` is `DEFAULT`:
  - a. Result in
    - the updated evaluation context  $EC_0$ , state  $ARCH_0$ , and `DEFAULT`.
2. Else:
  - a. Let `typedExpressionIR` be `switchLabelIR`.
  - b. Let context  $EC_1$ , state  $ARCH_1$  and `expressionResult` be
    - the result of evaluating `typedExpressionIR`, under cursor `LOCAL`, context  $EC_0$ , and state  $ARCH_0$ .
  - c. Result in
    - the updated evaluation context  $EC_1$ , state  $ARCH_1$ , and `expressionResult`.

[1] <https://github.com/p4lang/p4-spec/blob/master/p4-16/spec/docs/implementing-generalized-switch-statements.md>

# 14. Expressions

The syntax of expressions is defined as follows:

```
expression
: literalExpression
| referenceExpression
| defaultExpression
| unaryExpression
| binaryExpression
| ternaryExpression
| castExpression
| dataExpression
| accessExpression
| callExpression
| parenthesizedExpression
;
```

## 14.1. Semantics of expressions

Given a compound expression, the order in which sub-expressions are evaluated is important when the sub-expressions have side-effects. P4 expressions are evaluated as follows:

- Boolean operators `&&` and `||` use short-circuit evaluation—i.e., the second operand is only evaluated if necessary.
- The conditional operator `e1 ? e2 : e3` evaluates `e1`, and then either evaluates `e2` or `e3`.
- All other expressions are evaluated left-to-right as they appear in the source program.
- Method and function calls are evaluated as described in [Section 18.4](#).

### 14.1.1. Type checking

`Expr_ok`:

- Typing `expression`, under cursor `cursor` and context `typingContext`:
- Result in `typedExpressionIR`.

After type checking, expressions are represented in `P4IR` as follows:

```
typedExpressionIR
: expressionIR # expressionNoteIR
;

expressionIR
: literalExpressionIR
| referenceExpressionIR
| defaultExpressionIR
| unaryExpressionIR
| binaryExpressionIR
| ternaryExpressionIR
| castExpressionIR
| dataExpressionIR
| accessExpressionIR
| callExpressionIR
| parenthesizedExpressionIR
```

```

;
expressionNoteIR
: `( typeIR ctk )
;

```

Notice that after type checking, expressions in P4 are annotated with their types and their compile-time known-ness. See [Section 7.5](#) for more details of compile-time known and local compile-time known values.

The following helper functions are used to fetch the type and compile-time known-ness of an expression:

The type of `typedExpressionIR`

1. Let a pair of type `typeIR` and compile-time known-ness `_` be the note of `typedExpressionIR`.
2. Return `typeIR`.

The compile-time known-ness of `typedExpressionIR`

1. Let a pair of type `_` and compile-time known-ness `ctk` be the note of `typedExpressionIR`.
2. Return `ctk`.

### 14.1.2. Local compile-time evaluation

`Expr_eval_lctx`:

- Local compile-time evaluation of `typedExpressionIR`, under cursor `cursor` and context `typingContext`:
- Result in `value`.

Local compile-time known expressions are evaluated with the above relation.

### 14.1.3. Compile-time evaluation

`Expr_inst`:

- Compile-time evaluation of `typedExpressionIR`, under cursor `cursor`, context `instContext`, and store `store`:
- Result in store `store` and `value`.

Compile-time known expressions are evaluated with the above relation. A sequence of expressions can be evaluated with the following relation:

`Exprs_inst`:

- Compile-time evaluation of `typedExpressionIR*`, under cursor `cursor`, context `instContext`, and store `store`:

- Result in store `store` and `value`<sup>\*</sup>.

A list of expressions is evaluated with the following relation:

`Exprs_inst`:

- Compile-time evaluation of `typedExpressionIR`<sup>\*</sup>, under cursor `cursor`, context `instContext`, and store `store`:
- Result in store `store` and `value`<sup>\*</sup>.

Compile-time evaluation of `typedExpressionIR`<sup>\*</sup>, under cursor `p`, context `IC`, and store `store`:

1. If `typedExpressionIR`<sup>\*</sup> is equal to `:`:
  - a. Result in store `store` and `.`.
2. If let `typedExpressionIRn :: typedExpressionIRt* be typedExpressionIR`:
  - a. Let store `STO1` and `valueh` be
    - the result of compile-time evaluation of `typedExpressionIRn`, under cursor `p`, context `IC`, and store `store`.
  - b. Let store `STO2` and `valuet*` be
    - the result of compile-time evaluation of `typedExpressionIRt*`, under cursor `p`, context `IC`, and store `STO1`.
  - c. Result in store `STO2` and `valueh :: valuet*`.

#### 14.1.4. Runtime evaluation

`Expr_eval`:

- Evaluating `typedExpressionIR`, under cursor `cursor`, context `evalContext`, and state `arch`:
- Result in context `evalContext`, state `arch` and `expressionResult`.

The result of evaluating an expression is represented as follows:

```
expressionResult
: continueResult<value>
| abortResult
;

continueResult<X>
: ` X
;

abortResult
: exitResult
| rejectTransitionResult
;

exitResult
: EXIT
```

```

;
rejectTransitionResult
: REJECT errorValue
;

```

See [Section 13.7](#) and [\[sec-packet\]](#) for more details on exit and reject results.

A list of expressions can be evaluated with the following relation:

**Exprs\_eval:**

- Evaluating  $\text{typedExpressionIR}^*$ , under cursor  $\text{cursor}$ , context  $\text{evalContext}$ , and state  $\text{arch}$ :
- Result in context  $\text{evalContext}$ , state  $\text{arch}$  and  $\text{expressionListResult}$ .

The result of evaluating a list of expressions is represented as follows:

```

expressionListResult
: continueResult<value*>
| abortResult
;

```

**Evaluating  $\text{typedExpressionIR}^*$ , under cursor  $p$ , context  $\text{evalContext}$ , and state  $\text{arch}$ :**

1. If  $\text{typedExpressionIR}^*$  is equal to  $\cdot$ :
  - a. Result in context  $\text{evalContext}$ , state  $\text{arch}$  and  $\cdot$ .
2. If let  $\text{typedExpressionIR}_h :: \text{typedExpressionIR}_t^*$  be  $\text{typedExpressionIR}^*$ :
  - a. Let context  $\text{EC}_1$ , state  $\text{ARCH}_1$  and  $\text{expressionResult}$  be
    - the result of **evaluating  $\text{typedExpressionIR}_h$ , under cursor  $p$ , context  $\text{evalContext}$ , and state  $\text{arch}$ .**
  - b. If let  $\text{abortResult}$  be  $\text{expressionResult}$ :
    - i. Result in context  $\text{EC}_1$ , state  $\text{ARCH}_1$  and  $\text{abortResult}$ .
  - c. Else:
    - i. Let  $\text{value}_h$  be  $\text{expressionResult}$ .
    - ii. Let context  $\text{EC}_2$ , state  $\text{ARCH}_2$  and  $\text{expressionListResult}$  be
      - the result of **evaluating  $\text{typedExpressionIR}_t^*$ , under cursor  $p$ , context  $\text{EC}_1$ , and state  $\text{ARCH}_1$ .**
    - iii. If let  $\text{abortResult}$  be  $\text{expressionListResult}$ :
      - A. Result in context  $\text{EC}_2$ , state  $\text{ARCH}_2$  and  $\text{abortResult}$ .
    - iv. Else:
      - A. Let  $\text{value}_t^*$  be  $\text{expressionListResult}$ .
      - B. Result in context  $\text{EC}_2$ , state  $\text{ARCH}_2$  and  $\text{value}_h :: \text{value}_t^*$ .

## 14.2. Literal expressions

Literal expressions denote fixed values of boolean, numeric, or string types:

```

literalExpression
: booleanLiteral
| integerLiteral
| stringLiteral
;

booleanLiteral
: TRUE
| FALSE
;

integerLiteral
: D int
| nat W int
| nat S int
;

stringLiteral
: " text "
;

```

### 14.2.1. Type checking

After type checking, literal expressions have the form:

```
literalExpressionIR = literalExpression
```

Typing expression, under cursor  $p$  and context TC:

1. If let `booleanLiteral` be expression:
  - a. Let `expressionNoteIR` be a pair of type `BOOL` and compile-time known-ness `LCTK`.
  - b. Result in `booleanLiteral` annotated with `expressionNoteIR`.
2. Else if let `integerLiteral` be expression:
  - a. If let `D i` be `integerLiteral`:
    - i. Let `expressionNoteIR` be a pair of type `INT` and compile-time known-ness `LCTK`.
    - ii. Result in `D i` annotated with `expressionNoteIR`.
  - b. Else if let `n S i` be `integerLiteral`:
    - i. Let `expressionNoteIR` be a pair of type `INT < n >` and compile-time known-ness `LCTK`.
    - ii. Result in `n S i` annotated with `expressionNoteIR`.
  - c. Else:
    - i. Let `n W i` be `integerLiteral`.
    - ii. Let `expressionNoteIR` be a pair of type `BIT < n >` and compile-time known-ness `LCTK`.
    - iii. Result in `n W i` annotated with `expressionNoteIR`.
3. Else if let `stringLiteral` be expression:
  - a. Let `expressionNoteIR` be a pair of type `STRING` and compile-time known-ness `LCTK`.
  - b. Result in `stringLiteral` annotated with `expressionNoteIR`.



## 14.2.2. Local compile-time evaluation

Local compile-time evaluation of `expressionIR` annotated with `expressionNodeIR`, under cursor `p` and context `TC`:

1. If let `booleanLiteral` be `expressionIR`:
  - a. Let `boolValue` be ``B true if booleanLiteral is equal to TRUE otherwise `B false`.
  - b. Result in `boolValue`.
2. Else if let `integerLiteral` be `expressionIR`:
  - a. Result in `integerLiteral`.
3. Else if let `stringLiteral` be `expressionIR`:
  - a. Result in `stringLiteral`.

## 14.2.3. Compile-time evaluation

Compile-time evaluation of `expressionIR` annotated with `expressionNodeIR`, under cursor `p`, context `IC`, and store `STO`:

1. If let `booleanLiteral` be `expressionIR`:
  - a. Let `boolValue` be ``B true if booleanLiteral is equal to TRUE otherwise `B false`.
  - b. Result in store `STO` and `boolValue`.
2. Else if let `integerLiteral` be `expressionIR`:
  - a. Result in store `STO` and `integerLiteral`.
3. Else if let `stringLiteral` be `expressionIR`:
  - a. Result in store `STO` and `stringLiteral`.

## 14.2.4. Runtime evaluation

Evaluating `expressionIR` annotated with `expressionNodeIR`, under cursor `p`, context `EC`, and state `ARCH`:

1. If let `booleanLiteral` be `expressionIR`:
  - a. Let `boolValue` be ``B true if booleanLiteral is equal to TRUE otherwise `B false`.
  - b. Let `expressionResult` be `boolValue`.
  - c. Result in context `EC`, state `ARCH` and `expressionResult`.
2. Else if let `integerLiteral` be `expressionIR`:
  - a. Let `expressionResult` be `integerLiteral`.
  - b. Result in context `EC`, state `ARCH` and `expressionResult`.
3. Else if let `stringLiteral` be `expressionIR`:
  - a. Let `expressionResult` be `stringLiteral`.
  - b. Result in context `EC`, state `ARCH` and `expressionResult`.

## 14.3. Reference expressions

A reference expression is an expression that refers to a named entity in a P4 program:

```
referenceExpression
: prefixedNonTypeName
| THIS
;

prefixedNonTypeName
: nonTypeName
| `ID . nonTypeName
;
```

References are resolved according to the scoping rules of P4 (see [Section 6.3](#)).

### 14.3.1. Type checking

After type checking, a reference expression is represented in P4<sub>IR</sub> as:

```
referenceExpressionIR = prefixedNameIR
```

Typing expression, under cursor  $p$  and context TC:

1. If let  $\text{prefixedNonTypeName}$  be expression:
  - a. Let  $\text{prefixedNameIR}$  be the prefixed name of  $\text{prefixedNonTypeName}$ .
  - b. Let  $\_typeIR$  ctk  $\_?$  be ! the type of variable  $\text{prefixedNameIR}$  from the  $p$  layer of TC.
  - c. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}$  and compile-time known-ness ctk.
  - d. Result in  $\text{prefixedNameIR}$  annotated with  $\text{expressionNoteIR}$ .
2. If expression is equal to THIS:
  - a. Let  $\text{prefixedNameIR}$  be "this".
  - b. Let  $\_typeIR$  ctk  $\_?$  be ! the type of variable  $\text{prefixedNameIR}$  from the  $p$  layer of TC.
  - c. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}$  and compile-time known-ness ctk.
  - d. Result in  $\text{prefixedNameIR}$  annotated with  $\text{expressionNoteIR}$ .

A variable is looked up in the typing context with:

The type of variable  $\text{prefixedNameIR}$  from the  $p$  layer of TC

1. If let  $\_id$  be  $\text{prefixedNameIR}$ :
  - a. Let  $\text{typeFrame}$  be TC.GLOBAL.FRAME.
  - b. Return  $\_id$  in map  $\text{typeFrame}$ .
2. Else:
  - a. Let  $\_id$  be  $\text{prefixedNameIR}$ .
  - b. If  $p$  is GLOBAL:

- i. Let `typeFrame` be `TC.GLOBAL.FRAME`.
  - ii. Return `id` in `map` `typeFrame`.
- c. Else if `p` is `BLOCK`:
  - i. Let `typeFrame` be `TC.BLOCK.FRAME`.
  - ii. Let `varTypeIR?` be `id` in `map` `typeFrame`.
  - iii. If let `varTypeIR'` be `varTypeIR?`:
    - A. Return `varTypeIR'`.
  - iv. If `·` is equal to `id` in `map` `typeFrame`:
    - A. Return the type of variable `id` from the `GLOBAL` layer of `TC`.
- d. Else:
  - i. Let `typeFrame*` be `TC.LOCAL.FRAMES`.
  - ii. Let `varTypeIR?` be `id` in `maps` `typeFrame*`.
  - iii. If let `varTypeIR'` be `varTypeIR?`:
    - A. Return `varTypeIR'`.
  - iv. If `·` is equal to `id` in `maps` `typeFrame*`:
    - A. Return the type of variable `id` from the `BLOCK` layer of `TC`.

### 14.3.2. Local compile-time evaluation

Local compile-time evaluation of `prefixedNameIR` annotated with `expressionNoteIR`, under cursor `p` and context `TC`:

1. Let `value` be the value of variable `prefixedNameIR` from the `p` layer of `TC`.
2. Result in `value`.

### 14.3.3. Compile-time evaluation

Compile-time evaluation of `prefixedNameIR` annotated with `expressionNoteIR`, under cursor `p`, context `IC`, and store `STO`:

1. Let `value` be the value of `prefixedNameIR` from the `p` layer of `IC`.
2. Result in store `STO` and `value`.

A variable is looked up in the instantiation context with:

The value of `prefixedNameIR` from the `p` layer of `IC`

1. If let `·.id` be `prefixedNameIR`:
  - a. Let `value'` be `!id` in `map` `IC.GLOBAL.FRAME`.
  - b. Return `value'`.
2. Else:

- a. Let `id` be `prefixedNameIR`.
- b. If `p` is `GLOBAL`:
  - i. Let `value'` be `! id in map IC.GLOBAL.FRAME`.
  - ii. Return `value'`.
- c. Else if `p` is `BLOCK`:
  - i. Let `value'` be `id in map IC.BLOCK.FRAME`.
  - ii. If let `value'` be `value'`:
    - A. Return `value'`.
  - iii. If `·` is equal to `id in map IC.BLOCK.FRAME`:
    - A. Return `the value of id from the GLOBAL layer of IC`.
- d. Else:
  - i. Let `value'` be `id in maps IC.LOCAL.FRAMES`.
  - ii. If let `value'` be `value'`:
    - A. Return `value'`.
  - iii. If `·` is equal to `id in maps IC.LOCAL.FRAMES`:
    - A. Return `the value of id from the BLOCK layer of IC`.

### 14.3.4. Runtime evaluation

Evaluating `prefixedNameIR` annotated with `expressionNotelR`, under cursor `p`, context `EC`, and state `ARCH`:

1. Let `value` be `the value of prefixedNameIR from the p layer of EC`.
2. Let `expressionResult` be `value`.
3. Result in context `EC`, state `ARCH` and `expressionResult`.

A variable is looked up in the runtime context with:

The value of `prefixedNameIR` from the `p` layer of `EC`

1. If let `· id` be `prefixedNameIR`:
  - a. Let `value'` be `! id in map EC.GLOBAL.FRAME`.
  - b. Return `value'`.
2. Else:
  - a. Let `id` be `prefixedNameIR`.
  - b. If `p` is `GLOBAL`:
    - i. Let `value'` be `! id in map EC.GLOBAL.FRAME`.
    - ii. Return `value'`.
  - c. Else if `p` is `BLOCK`:
    - i. Let `value'` be `id in map EC.BLOCK.FRAME`.

- ii. If let `value'` be `value?`:
  - A. Return `value'`.
- iii. If `·` is equal to `id in map EC.BLOCK.FRAME`:
  - A. Return the value of `id` from the GLOBAL layer of `EC`.
- d. Else:
  - i. Let `value?` be `id in maps EC.LOCAL.FRAMES`.
  - ii. If let `value'` be `value?`:
    - A. Return `value'`.
  - iii. If `·` is equal to `id in maps EC.LOCAL.FRAMES`:
    - A. Return the value of `id` from the BLOCK layer of `EC`.

## 14.4. Default expressions

Default expressions provide a way to specify a default value for a type:

```
defaultExpression
: ...
;
```

See [Section 8.6.1](#) for more details on default types. When default expressions are cast to a specific type, they evaluate to the default value for that type. See [Section 19.3](#) for more details on default values.

### 14.4.1. Type checking

After type checking, default expressions have the form:

```
defaultExpressionIR = defaultExpression
```

Typing `...`, under cursor `p` and context `TC`:

1. Let `expressionNoteIR` be a pair of type `DEFAULT` and compile-time known-ness `LCTK`.
2. Result in `...` annotated with `expressionNoteIR`.

### 14.4.2. Local compile-time evaluation

Local compile-time evaluation of `...` annotated with `expressionNoteIR`, under cursor `p` and context `TC`:

1. Result in `DEFAULT`.

### 14.4.3. Compile-time evaluation

Compile-time evaluation of `...` annotated with `expressionNoteIR`, under cursor `p`, context `IC`, and store `STO`:

1. Result in store **STO** and **DEFAULT**.

#### 14.4.4. Runtime evaluation

Evaluating ... annotated with **expressionNoteIR**, under cursor **p**, context **EC**, and state **ARCH**:

1. Let **expressionResult** be **DEFAULT**.
2. Result in context **EC**, state **ARCH** and **expressionResult**.

### 14.5. Unary expressions

```
unaryExpression
: unop expression
;

unop
: !
| ~
| -
| +
;
```

See [Section 19.1](#) for details on how each unary operator is evaluated.

#### 14.5.1. Type checking

After type checking, unary expressions have the form:

```
unaryExpressionIR
: unop typedExpressionIR
;
```

##### 14.5.1.1. Negation

Typing **! expression'**, under cursor **p** and context **TC**:

1. Let **typedExpressionIR** be
  - the result of **typing expression'**, under cursor **p** and context **TC**.
2. Let **typedExpressionIR<sub>reduced</sub>** be **! the result of reducing serializable enums in typedExpressionIR until \$compat\_Inot is satisfied**.
3. Let **typeIR<sub>reduced</sub>** be **the type of typedExpressionIR<sub>reduced</sub>**.
4. Let **ctk<sub>reduced</sub>** be **the compile-time known-ness of typedExpressionIR<sub>reduced</sub>**.
5. Let **expressionNoteIR** be **a pair of type typeIR<sub>reduced</sub> and compile-time known-ness ctk<sub>reduced</sub>**.
6. Result in **! typedExpressionIR<sub>reduced</sub> annotated with expressionNoteIR**.

##### 14.5.1.2. Bitwise complement

Typing  $\sim$  expression', under cursor  $p$  and context  $TC$ :

1. Let  $\text{typedExpressionIR}$  be
  - the result of typing expression', under cursor  $p$  and context  $TC$ .
2. Let  $\text{typedExpressionIR}_{\text{reduced}}$  be ! the result of reducing serializable enums in  $\text{typedExpressionIR}$  until  $\$compat\_bnot$  is satisfied.
3. Let  $\text{typeIR}_{\text{reduced}}$  be the type of  $\text{typedExpressionIR}_{\text{reduced}}$ .
4. Let  $\text{ctk}_{\text{reduced}}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{\text{reduced}}$ .
5. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}_{\text{reduced}}$  and compile-time known-ness  $\text{ctk}_{\text{reduced}}$ .
6. Result in  $\sim \text{typedExpressionIR}_{\text{reduced}}$  annotated with  $\text{expressionNoteIR}$ .

### 14.5.1.3. Plus and minus

Typing  $\text{unop}$  expression', under cursor  $p$  and context  $TC$ :

1. Check that  $\text{unop}$  is equal to  $+$  or  $\text{unop}$  is equal to  $-$ .
2. Let  $\text{typedExpressionIR}$  be
  - the result of typing expression', under cursor  $p$  and context  $TC$ .
3. Let  $\text{typedExpressionIR}_{\text{reduced}}$  be ! the result of reducing serializable enums in  $\text{typedExpressionIR}$  until  $\$compat\_uplusminus$  is satisfied.
4. Let  $\text{typeIR}_{\text{reduced}}$  be the type of  $\text{typedExpressionIR}_{\text{reduced}}$ .
5. Let  $\text{ctk}_{\text{reduced}}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{\text{reduced}}$ .
6. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}_{\text{reduced}}$  and compile-time known-ness  $\text{ctk}_{\text{reduced}}$ .
7. Result in  $\text{unop} \text{typedExpressionIR}_{\text{reduced}}$  annotated with  $\text{expressionNoteIR}$ .

## 14.5.2. Local compile-time evaluation

Local compile-time evaluation of  $\text{unop} \text{typedExpressionIR}$  annotated with  $\text{expressionNoteIR}$ , under cursor  $p$  and context  $TC$ :

1. Let  $\text{value}$  be
  - the result of local compile-time evaluation of  $\text{typedExpressionIR}$ , under cursor  $p$  and context  $TC$ .
2. Result in  $\text{unop} \text{value}$ .

## 14.5.3. Compile-time evaluation

Compile-time evaluation of  $\text{unop} \text{typedExpressionIR}$  annotated with  $\text{expressionNoteIR}$ , under cursor  $p$ , context  $IC$ , and store  $STO$ :

1. Let store  $STO_i$  and  $\text{value}$  be

- the result of **compile-time evaluation** of `typedExpressionIR`, under cursor `p`, context `IC`, and store `STO`.

2. Result in store `STO1` and `unop` value.

## 14.5.4. Runtime evaluation

**Evaluating** `unop typedExpressionIR` annotated with `expressionNotelR`, under cursor `p`, context `EC`, and state `ARCH`:

1. Let context `EC1`, state `ARCH1` and `expressionResult` be
  - the result of **evaluating** `typedExpressionIR`, under cursor `p`, context `EC`, and state `ARCH`.
2. If let `abortResult` be `expressionResult`:
  - a. Result in context `EC1`, state `ARCH1` and `abortResult`.
3. Else:
  - a. Let `value` be `expressionResult`.
  - b. Let `value'` be `unop` value.
  - c. Let `expressionResult'` be `value'`.
  - d. Result in context `EC1`, state `ARCH1` and `expressionResult'`.

## 14.6. Binary expressions

```
binaryExpression
: expression binop expression
;

binop
: *
| /
| %
| +
| -
| |+|
| |-|
| <<
| >>
| <=
| >=
| <
| >
| !=
| ==
| &
| ^
| |
| ++
| &&
| ||
;
```

See [Section 19.2](#) for details on how each binary operator is evaluated. Note that logical operators (`&&`, `||`) use short-circuit evaluation.



## 14.6.1. Type checking

### 14.6.1.1. Plus, minus, and multiplication

Typing  $\text{expression}_i$ ,  $\text{binop}$   $\text{expression}_r$ , under cursor  $p$  and context  $TC$ :

1. Check that  $\text{binop}$  is in  $[+, -, *]$ .
2. Let  $\text{typedExpressionIR}_i$  be
  - the result of typing  $\text{expression}_i$ , under cursor  $p$  and context  $TC$ .
3. Let  $\text{typedExpressionIR}_r$  be
  - the result of typing  $\text{expression}_r$ , under cursor  $p$  and context  $TC$ .
4. Let  $(\text{typedExpressionIR}_{i\_cast}, \text{typedExpressionIR}_{r\_cast})$  be !  $\text{typedExpressionIR}_i$  and  $\text{typedExpressionIR}_r$  implicitly cast to equal types.
5. Let  $(\text{typedExpressionIR}_{i\_reduced}, \text{typedExpressionIR}_{r\_reduced})$  be ! the result of reducing serializable enums in  $\text{typedExpressionIR}_{i\_cast}$  and  $\text{typedExpressionIR}_{r\_cast}$  until  $\$compat\_plusminusmult$  is satisfied.
6. Let  $\text{typeIR}_{reduced}$  be the type of  $\text{typedExpressionIR}_{i\_reduced}$ .
7. Let  $\text{ctk}_{i\_reduced}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{i\_reduced}$ .
8. Let  $\text{ctk}_{r\_reduced}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{r\_reduced}$ .
9. Let  $\text{ctk}_{reduced}$  be the join of  $\text{ctk}_{i\_reduced}$  and  $\text{ctk}_{r\_reduced}$ .
10. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}_{reduced}$  and compile-time known-ness  $\text{ctk}_{reduced}$ .
11. Result in  $\text{typedExpressionIR}_{i\_reduced} \text{ binop } \text{typedExpressionIR}_{r\_reduced}$  annotated with  $\text{expressionNoteIR}$ .

### 14.6.1.2. Saturating plus and minus

Typing  $\text{expression}_i$ ,  $\text{binop}$   $\text{expression}_r$ , under cursor  $p$  and context  $TC$ :

1. Check that  $\text{binop}$  is in  $[|, |, \text{``}\text{``}, \text{``}\text{``}, \text{``}\text{``}]$ .
2. Let  $\text{typedExpressionIR}_i$  be
  - the result of typing  $\text{expression}_i$ , under cursor  $p$  and context  $TC$ .
3. Let  $\text{typedExpressionIR}_r$  be
  - the result of typing  $\text{expression}_r$ , under cursor  $p$  and context  $TC$ .
4. Let  $(\text{typedExpressionIR}_{i\_cast}, \text{typedExpressionIR}_{r\_cast})$  be !  $\text{typedExpressionIR}_i$  and  $\text{typedExpressionIR}_r$  implicitly cast to equal types.
5. Let  $(\text{typedExpressionIR}_{i\_reduced}, \text{typedExpressionIR}_{r\_reduced})$  be ! the result of reducing serializable enums in  $\text{typedExpressionIR}_{i\_cast}$  and  $\text{typedExpressionIR}_{r\_cast}$  until  $\$compat\_satplusminus$  is satisfied.
6. Let  $\text{typeIR}_{reduced}$  be the type of  $\text{typedExpressionIR}_{i\_reduced}$ .
7. Let  $\text{ctk}_{i\_reduced}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{i\_reduced}$ .
8. Let  $\text{ctk}_{r\_reduced}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{r\_reduced}$ .
9. Let  $\text{ctk}_{reduced}$  be the join of  $\text{ctk}_{i\_reduced}$  and  $\text{ctk}_{r\_reduced}$ .
10. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}_{reduced}$  and compile-time known-ness  $\text{ctk}_{reduced}$ .
11. Result in  $\text{typedExpressionIR}_{i\_reduced} \text{ binop } \text{typedExpressionIR}_{r\_reduced}$  annotated with  $\text{expressionNoteIR}$ .

### 14.6.1.3. Division and modulo

Typing  $\text{expression}_l$  binop  $\text{expression}_r$ , under cursor  $p$  and context  $TC$ :

1. Check that  $\text{binop}$  is in  $[ /, \% ]$ .
2. Let  $\text{typedExpressionIR}_l$  be
  - the result of typing  $\text{expression}_l$ , under cursor  $p$  and context  $TC$ .
3. Let  $\text{typedExpressionIR}_r$  be
  - the result of typing  $\text{expression}_r$ , under cursor  $p$  and context  $TC$ .
4. Let  $(\text{typedExpressionIR}_{l\_cast}, \text{typedExpressionIR}_{r\_cast})$  be !  $\text{typedExpressionIR}_l$  and  $\text{typedExpressionIR}_r$  implicitly cast to equal types.
5. Let  $(\text{typedExpressionIR}_{l\_reduced}, \text{typedExpressionIR}_{r\_reduced})$  be ! the result of reducing serializable enums in  $\text{typedExpressionIR}_{l\_cast}$  and  $\text{typedExpressionIR}_{r\_cast}$  until  $\$compat\_divmod$  is satisfied.
6. Let  $\text{typeIR}_{reduced}$  be the type of  $\text{typedExpressionIR}_{l\_reduced}$ .
7. Let  $\text{ctk}_{l\_reduced}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{l\_reduced}$ .
8. Let  $\text{ctk}_{r\_reduced}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{r\_reduced}$ .
9. If  $\text{ctk}_{r\_reduced}$  is LCTK:
  - a. Let  $\text{value}$  be
    - the result of local compile-time evaluation of  $\text{typedExpressionIR}_{r\_reduced}$ , under cursor  $p$  and context  $TC$ .
  - b. Check that  $\text{value}$  has type  $\text{integerValue}$ .
  - c. Let  $\text{integerValue}_r$  be  $\text{value}$ .
  - d. Let  $n_r$  be ! the natural number representation of  $\text{integerValue}_r$ .
  - e. Check that  $n_r$  is greater than 0.
  - f. Let  $\text{ctk}_{reduced}$  be the join of  $\text{ctk}_{l\_reduced}$  and  $\text{ctk}_{r\_reduced}$ .
  - g. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}_{reduced}$  and compile-time known-ness  $\text{ctk}_{reduced}$ .
  - h. Result in  $\text{typedExpressionIR}_{l\_reduced}$  binop  $\text{typedExpressionIR}_{r\_reduced}$  annotated with  $\text{expressionNoteIR}$ .
10. Else:
  - a. Let  $\text{ctk}_{reduced}$  be the join of  $\text{ctk}_{l\_reduced}$  and  $\text{ctk}_{r\_reduced}$ .
  - b. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}_{reduced}$  and compile-time known-ness  $\text{ctk}_{reduced}$ .
  - c. Result in  $\text{typedExpressionIR}_{l\_reduced}$  binop  $\text{typedExpressionIR}_{r\_reduced}$  annotated with  $\text{expressionNoteIR}$ .

### 14.6.1.4. Shift left and right

Typing  $\text{expression}_l$  binop  $\text{expression}_r$ , under cursor  $p$  and context  $TC$ :

1. Check that  $\text{binop}$  is in  $[ <<, >> ]$ .
2. Let  $\text{typedExpressionIR}_l$  be
  - the result of typing  $\text{expression}_l$ , under cursor  $p$  and context  $TC$ .
3. Let  $\text{typedExpressionIR}_r$  be

- the result of **typing**  $\text{expression}_r$ , under cursor  $p$  and context  $TC$ .
- Let  $(\text{typedExpressionIR}_{l\_reduced}, \text{typedExpressionIR}_{r\_reduced})$  be ! the result of reducing serializable enums in  $\text{typedExpressionIR}_l$  and  $\text{typedExpressionIR}_r$  until  $\$compat\_shift$  is satisfied.
  - Let  $\text{typeIR}_{l\_reduced}$  be the type of  $\text{typedExpressionIR}_{l\_reduced}$ .
  - Let  $\text{ctk}_{l\_reduced}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{l\_reduced}$ .
  - Let  $\text{typeIR}_{r\_reduced}$  be the type of  $\text{typedExpressionIR}_{r\_reduced}$ .
  - Let  $\text{ctk}_{r\_reduced}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{r\_reduced}$ .
  - If let  $\text{BIT} < \_ >$  be  $\text{typeIR}_{r\_reduced}$ :
    - Check that if  $\text{typeIR}_{l\_reduced}$  is equal to  $\text{INT}$ , then  $\text{ctk}_{r\_reduced}$  is equal to  $\text{LCTK}$ .
    - Let  $\text{ctk}_{reduced}$  be the join of  $\text{ctk}_{l\_reduced}$  and  $\text{ctk}_{r\_reduced}$ .
    - Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}_{l\_reduced}$  and compile-time known-ness  $\text{ctk}_{reduced}$ .
    - Result in  $\text{typedExpressionIR}_{l\_reduced}$  binop  $\text{typedExpressionIR}_{r\_reduced}$  annotated with  $\text{expressionNoteIR}$ .
  - Else:
    - Check that  $\text{ctk}_{r\_reduced}$  is  $\text{LCTK}$ .
    - Let  $\text{ctk}_{reduced}$  be the join of  $\text{ctk}_{l\_reduced}$  and  $\text{ctk}_{r\_reduced}$ .
    - Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}_{l\_reduced}$  and compile-time known-ness  $\text{ctk}_{reduced}$ .
    - Result in  $\text{typedExpressionIR}_{l\_reduced}$  binop  $\text{typedExpressionIR}_{r\_reduced}$  annotated with  $\text{expressionNoteIR}$ .

#### 14.6.1.5. Equality and inequality

**Typing**  $\text{expression}_l$  binop  $\text{expression}_r$ , under cursor  $p$  and context  $TC$ :

- Check that **binop** is in  $[ ==, != ]$ .
- Let  $\text{typedExpressionIR}_l$  be
  - the result of **typing**  $\text{expression}_l$ , under cursor  $p$  and context  $TC$ .
- Let  $\text{typedExpressionIR}_r$  be
  - the result of **typing**  $\text{expression}_r$ , under cursor  $p$  and context  $TC$ .
- Let  $(\text{typedExpressionIR}_{l\_cast}, \text{typedExpressionIR}_{r\_cast})$  be !  $\text{typedExpressionIR}_l$  and  $\text{typedExpressionIR}_r$  implicitly cast to equal types.
- Let  $\text{typeIR}_{cast}$  be the type of  $\text{typedExpressionIR}_{l\_cast}$ .
- Let  $\text{ctk}_{l\_cast}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{l\_cast}$ .
- Let  $\text{ctk}_{r\_cast}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{r\_cast}$ .
- Check that  $\text{typeIR}_{cast}$  supports equality comparison.
- Let  $\text{ctk}_{cast}$  be the join of  $\text{ctk}_{l\_cast}$  and  $\text{ctk}_{r\_cast}$ .
- Let  $\text{expressionNoteIR}$  be a pair of type  $\text{BOOL}$  and compile-time known-ness  $\text{ctk}_{cast}$ .
- Result in  $\text{typedExpressionIR}_{l\_cast}$  binop  $\text{typedExpressionIR}_{r\_cast}$  annotated with  $\text{expressionNoteIR}$ .

#### 14.6.1.6. Comparison

Typing  $\text{expression}_l$  binop  $\text{expression}_r$ , under cursor  $p$  and context  $TC$ :

1. Check that  $\text{binop}$  is in  $[ \leq, \geq, <, > ]$ .
2. Let  $\text{typedExpressionIR}_l$  be
  - the result of typing  $\text{expression}_l$ , under cursor  $p$  and context  $TC$ .
3. Let  $\text{typedExpressionIR}_r$  be
  - the result of typing  $\text{expression}_r$ , under cursor  $p$  and context  $TC$ .
4. Let  $( \text{typedExpressionIR}_{l\_cast}, \text{typedExpressionIR}_{r\_cast} )$  be !  $\text{typedExpressionIR}_l$  and  $\text{typedExpressionIR}_r$  implicitly cast to equal types.
5. Let  $( \text{typedExpressionIR}_{l\_reduced}, \text{typedExpressionIR}_{r\_reduced} )$  be ! the result of reducing serializable enums in  $\text{typedExpressionIR}_{l\_cast}$  and  $\text{typedExpressionIR}_{r\_cast}$  until  $\$compat\_compare$  is satisfied.
6. Let  $\text{typeIR}_{reduced}$  be the type of  $\text{typedExpressionIR}_{l\_reduced}$ .
7. Let  $\text{ctk}_{l\_reduced}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{l\_reduced}$ .
8. Let  $\text{ctk}_{r\_reduced}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{r\_reduced}$ .
9. Let  $\text{ctk}_{reduced}$  be the join of  $\text{ctk}_{l\_reduced}$  and  $\text{ctk}_{r\_reduced}$ .
10. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{BOOL}$  and compile-time known-ness  $\text{ctk}_{reduced}$ .
11. Result in  $\text{typedExpressionIR}_{l\_reduced}$  binop  $\text{typedExpressionIR}_{r\_reduced}$  annotated with  $\text{expressionNoteIR}$ .

#### 14.6.1.7. Bitwise and, xor, and or

Typing  $\text{expression}_l$  binop  $\text{expression}_r$ , under cursor  $p$  and context  $TC$ :

1. Check that  $\text{binop}$  is in  $[ \&, \wedge, | ]$ .
2. Let  $\text{typedExpressionIR}_l$  be
  - the result of typing  $\text{expression}_l$ , under cursor  $p$  and context  $TC$ .
3. Let  $\text{typedExpressionIR}_r$  be
  - the result of typing  $\text{expression}_r$ , under cursor  $p$  and context  $TC$ .
4. Let  $( \text{typedExpressionIR}_{l\_cast}, \text{typedExpressionIR}_{r\_cast} )$  be !  $\text{typedExpressionIR}_l$  and  $\text{typedExpressionIR}_r$  implicitly cast to equal types.
5. Let  $( \text{typedExpressionIR}_{l\_reduced}, \text{typedExpressionIR}_{r\_reduced} )$  be ! the result of reducing serializable enums in  $\text{typedExpressionIR}_{l\_cast}$  and  $\text{typedExpressionIR}_{r\_cast}$  until  $\$compat\_bitwise$  is satisfied.
6. Let  $\text{typeIR}_{reduced}$  be the type of  $\text{typedExpressionIR}_{l\_reduced}$ .
7. Let  $\text{ctk}_{l\_reduced}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{l\_reduced}$ .
8. Let  $\text{ctk}_{r\_reduced}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{r\_reduced}$ .
9. Let  $\text{ctk}_{reduced}$  be the join of  $\text{ctk}_{l\_reduced}$  and  $\text{ctk}_{r\_reduced}$ .
10. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}_{reduced}$  and compile-time known-ness  $\text{ctk}_{reduced}$ .
11. Result in  $\text{typedExpressionIR}_{l\_reduced}$  binop  $\text{typedExpressionIR}_{r\_reduced}$  annotated with  $\text{expressionNoteIR}$ .

#### 14.6.1.8. Concatenation

Typing  $\text{expression}_l$ ,  $\text{expression}_r$ , under cursor  $p$  and context  $TC$ :

1. Let  $\text{typedExpressionIR}_l$  be
  - the result of typing  $\text{expression}_l$ , under cursor  $p$  and context  $TC$ .
2. Let  $\text{typedExpressionIR}_r$  be
  - the result of typing  $\text{expression}_r$ , under cursor  $p$  and context  $TC$ .
3. Let (  $\text{typedExpressionIR}_{l\_reduced}$ ,  $\text{typedExpressionIR}_{r\_reduced}$  ) be ! the result of reducing serializable enums in  $\text{typedExpressionIR}_l$  and  $\text{typedExpressionIR}_r$  until  $\$compat\_concat$  is satisfied.
4. Let  $\text{typeIR}_{l\_reduced}$  be the type of  $\text{typedExpressionIR}_{l\_reduced}$ .
5. Let  $\text{ctk}_{l\_reduced}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{l\_reduced}$ .
6. Let  $\text{typeIR}_{r\_reduced}$  be the type of  $\text{typedExpressionIR}_{r\_reduced}$ .
7. Let  $\text{ctk}_{r\_reduced}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{r\_reduced}$ .
8. Check that if  $\text{typeIR}_{l\_reduced}$  is equal to  $STRING$  and  $\text{typeIR}_{r\_reduced}$  is equal to  $STRING$ , then  $\text{ctk}_{l\_reduced}$  is equal to  $LCTK$  and  $\text{ctk}_{r\_reduced}$  is equal to  $LCTK$ .
9. Let  $\text{typeIR}_{reduced}$  be  $\$result\_concat(\text{typeIR}_{l\_reduced}, \text{typeIR}_{r\_reduced})$ .
10. Let  $\text{ctk}_{reduced}$  be the join of  $\text{ctk}_{l\_reduced}$  and  $\text{ctk}_{r\_reduced}$ .
11. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}_{reduced}$  and compile-time known-ness  $\text{ctk}_{reduced}$ .
12. Result in  $\text{typedExpressionIR}_{l\_reduced}$   $\text{typedExpressionIR}_{r\_reduced}$  annotated with  $\text{expressionNoteIR}$ .

#### 14.6.1.9. Logical and, and or

Typing  $\text{expression}_l$ ,  $\text{binop}$   $\text{expression}_r$ , under cursor  $p$  and context  $TC$ :

1. Check that  $\text{binop}$  is in [  $\&\&$ ,  $||$  ].
2. Let  $\text{typedExpressionIR}_l$  be
  - the result of typing  $\text{expression}_l$ , under cursor  $p$  and context  $TC$ .
3. Let  $\text{typedExpressionIR}_r$  be
  - the result of typing  $\text{expression}_r$ , under cursor  $p$  and context  $TC$ .
4. Let (  $\text{typedExpressionIR}_{l\_cast}$ ,  $\text{typedExpressionIR}_{r\_cast}$  ) be !  $\text{typedExpressionIR}_l$  and  $\text{typedExpressionIR}_r$  implicitly cast to equal types.
5. Let (  $\text{typedExpressionIR}_{l\_reduced}$ ,  $\text{typedExpressionIR}_{r\_reduced}$  ) be ! the result of reducing serializable enums in  $\text{typedExpressionIR}_{l\_cast}$  and  $\text{typedExpressionIR}_{r\_cast}$  until  $\$compat\_logical$  is satisfied.
6. Let  $\text{typeIR}_{reduced}$  be the type of  $\text{typedExpressionIR}_{l\_reduced}$ .
7. Let  $\text{ctk}_{l\_reduced}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{l\_reduced}$ .
8. Let  $\text{ctk}_{r\_reduced}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{r\_reduced}$ .
9. Let  $\text{ctk}_{reduced}$  be the join of  $\text{ctk}_{l\_reduced}$  and  $\text{ctk}_{r\_reduced}$ .
10. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}_{reduced}$  and compile-time known-ness  $\text{ctk}_{reduced}$ .
11. Result in  $\text{typedExpressionIR}_{l\_reduced}$   $\text{binop}$   $\text{typedExpressionIR}_{r\_reduced}$  annotated with  $\text{expressionNoteIR}$ .

#### 14.6.2. Local compile-time evaluation

Local compile-time evaluation of  $\text{typedExpressionIR}_l$  binop  $\text{typedExpressionIR}_r$  annotated with  $\text{expressionNodeIR}$ , under cursor  $p$  and context  $TC$ :

1. If  $\text{binop}$  is not in  $[ \&\&, || ]$ :
  - a. Let  $\text{value}_l$  be
    - the result of local compile-time evaluation of  $\text{typedExpressionIR}_l$ , under cursor  $p$  and context  $TC$ .
  - b. Let  $\text{value}_r$  be
    - the result of local compile-time evaluation of  $\text{typedExpressionIR}_r$ , under cursor  $p$  and context  $TC$ .
  - c. Result in  $\text{value}_l$  binop  $\text{value}_r$ .
2. If  $\text{binop}$  is  $\&\&$ :
  - a. Let  $\text{value}$  be
    - the result of local compile-time evaluation of  $\text{typedExpressionIR}_l$ , under cursor  $p$  and context  $TC$ .
  - b. If  $\text{value}$  is equal to  $\text{'B false'}$ :
    - i. Result in  $\text{'B false'}$ .
  - c. If  $\text{value}$  is equal to  $\text{'B true'}$ :
    - i. Let  $\text{value}_r$  be
      - the result of local compile-time evaluation of  $\text{typedExpressionIR}_r$ , under cursor  $p$  and context  $TC$ .
    - ii. Result in  $\text{value}_r$ .
3. Else if  $\text{binop}$  is  $||$ :
  - a. Let  $\text{value}$  be
    - the result of local compile-time evaluation of  $\text{typedExpressionIR}_l$ , under cursor  $p$  and context  $TC$ .
  - b. If  $\text{value}$  is equal to  $\text{'B true'}$ :
    - i. Result in  $\text{'B true'}$ .
  - c. If  $\text{value}$  is equal to  $\text{'B false'}$ :
    - i. Let  $\text{value}_r$  be
      - the result of local compile-time evaluation of  $\text{typedExpressionIR}_r$ , under cursor  $p$  and context  $TC$ .
    - ii. Result in  $\text{value}_r$ .

### 14.6.3. Compile-time evaluation

Compile-time evaluation of  $\text{typedExpressionIR}_l$  binop  $\text{typedExpressionIR}_r$  annotated with  $\text{expressionNodeIR}$ , under cursor  $p$ , context  $IC$ , and store  $STO$ :

1. If  $\text{binop}$  is not in  $[ \&\&, || ]$ :
  - a. Let store  $STO_l$  and  $\text{value}_l$  be

- the result of **compile-time evaluation** of  $\text{typedExpressionIR}_i$ , under cursor  $p$ , context  $IC$ , and store  $STO$ .
  - b. Let store  $STO_2$  and  $\text{value}_r$  be
    - the result of **compile-time evaluation** of  $\text{typedExpressionIR}_r$ , under cursor  $p$ , context  $IC$ , and store  $STO_1$ .
  - c. Result in store  $STO_2$  and  $\text{value}_r$  binop  $\text{value}_r$ .
2. If  $\text{binop}$  is `&&`:
- a. Let store  $STO_1$  and  $\text{value}$  be
    - the result of **compile-time evaluation** of  $\text{typedExpressionIR}_i$ , under cursor  $p$ , context  $IC$ , and store  $STO$ .
  - b. If  $\text{value}$  is equal to ``B false`:
    - i. Result in store  $STO_1$  and ``B false`.
  - c. If  $\text{value}$  is equal to ``B true`:
    - i. Let store  $STO_2$  and  $\text{value}_r$  be
      - the result of **compile-time evaluation** of  $\text{typedExpressionIR}_r$ , under cursor  $p$ , context  $IC$ , and store  $STO_1$ .
    - ii. Result in store  $STO_2$  and  $\text{value}_r$ .
3. Else if  $\text{binop}$  is `||`:
- a. Let store  $STO_1$  and  $\text{value}$  be
    - the result of **compile-time evaluation** of  $\text{typedExpressionIR}_i$ , under cursor  $p$ , context  $IC$ , and store  $STO$ .
  - b. If  $\text{value}$  is equal to ``B true`:
    - i. Result in store  $STO_1$  and ``B true`.
  - c. If  $\text{value}$  is equal to ``B false`:
    - i. Let store  $STO_2$  and  $\text{value}_r$  be
      - the result of **compile-time evaluation** of  $\text{typedExpressionIR}_r$ , under cursor  $p$ , context  $IC$ , and store  $STO_1$ .
    - ii. Result in store  $STO_2$  and  $\text{value}_r$ .

#### 14.6.4. Runtime evaluation

Evaluating  $\text{typedExpressionIR}_i$  binop  $\text{typedExpressionIR}_r$  annotated with  $\text{expressionNodeIR}$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ :

1. If  $\text{binop}$  is not in `[ &&, || ]`:
  - a. Let context  $EC_1$ , state  $ARCH_1$  and  $\text{expressionListResult}$  be
    - the result of **evaluating** `[ typedExpressionIRi, typedExpressionIRr ]`, under cursor  $p$ , context  $EC$ , and state  $ARCH$ .
  - b. If let  $\text{abortResult}$  be  $\text{expressionListResult}$ :
    - i. Result in context  $EC_1$ , state  $ARCH_1$  and  $\text{abortResult}$ .
  - c. Else:

- i. Let  $value^*$  be  $expressionListResult$ .
  - ii. Check that  $value^*$  is a list of length 2.
  - iii. Let  $[value_i, value_r]$  be  $value^*$ .
  - iv. Let  $value'$  be  $value_i \text{ binop } value_r$ .
  - v. Let  $expressionResult$  be  $value'$ .
  - vi. Result in context  $EC_1$ , state  $ARCH_1$  and  $expressionResult$ .
2. If  $binop$  is  $\&\&$ :
    - a. Let context  $EC_1$ , state  $ARCH_1$  and  $expressionResult$  be
      - the result of **evaluating**  $typedExpressionIR_i$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ .
    - b. If let  $abortResult$  be  $expressionResult$ :
      - i. Result in context  $EC_1$ , state  $ARCH_1$  and  $abortResult$ .
    - c. If  $expressionResult$  is equal to ``B false`:
      - i. Let  $expressionResult'$  be ``B false`.
      - ii. Result in context  $EC_1$ , state  $ARCH_1$  and  $expressionResult'$ .
    - d. If  $expressionResult$  is equal to ``B true`:
      - i. Let context  $EC_2$ , state  $ARCH_2$  and  $expressionResult'$  be
        - the result of **evaluating**  $typedExpressionIR_r$ , under cursor  $p$ , context  $EC_1$ , and state  $ARCH_1$ .
      - ii. If let  $abortResult$  be  $expressionResult'$ :
        - A. Result in context  $EC_2$ , state  $ARCH_2$  and  $abortResult$ .
      - iii. Result in context  $EC_2$ , state  $ARCH_2$  and  $expressionResult'$ .
  3. Else if  $binop$  is  $||$ :
    - a. Let context  $EC_1$ , state  $ARCH_1$  and  $expressionResult$  be
      - the result of **evaluating**  $typedExpressionIR_i$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ .
    - b. If let  $abortResult$  be  $expressionResult$ :
      - i. Result in context  $EC_1$ , state  $ARCH_1$  and  $abortResult$ .
    - c. If  $expressionResult$  is equal to ``B true`:
      - i. Let  $expressionResult'$  be ``B true`.
      - ii. Result in context  $EC_1$ , state  $ARCH_1$  and  $expressionResult'$ .
    - d. If  $expressionResult$  is equal to ``B false`:
      - i. Let context  $EC_2$ , state  $ARCH_2$  and  $expressionResult'$  be
        - the result of **evaluating**  $typedExpressionIR_r$ , under cursor  $p$ , context  $EC_1$ , and state  $ARCH_1$ .
      - ii. If let  $abortResult$  be  $expressionResult'$ :
        - A. Result in context  $EC_2$ , state  $ARCH_2$  and  $abortResult$ .
      - iii. Result in context  $EC_2$ , state  $ARCH_2$  and  $expressionResult'$ .

## 14.7. Ternary expressions

A conditional expression of the form  $e_1 ? e_2 : e_3$  behaves the same as in languages like C. As described



above, the expression  $e_1$  is evaluated first, and second either  $e_2$  or  $e_3$  is evaluated depending on the result.

The first sub-expression  $e_1$  must have Boolean type and the second and third sub-expressions must have the same type, which cannot both be arbitrary-precision integers unless the condition itself can be evaluated at compilation time. This restriction is designed to ensure that the width of the result of the conditional expression can be inferred statically at compile time.

```
ternaryExpression
  : expression ? expression : expression
  ;
```

### 14.7.1. Type checking

After type checking, ternary expressions have the form:

```
ternaryExpressionIR
  : typedExpressionIR ? typedExpressionIR : typedExpressionIR
  ;
```

**Typing**  $expression_{cond} ? expression_{true} : expression_{false}$ , under cursor  $p$  and context  $TC$ :

1. Let  $typedExpressionIR_{cond}$  be
  - the result of **typing**  $expression_{cond}$ , under cursor  $p$  and context  $TC$ .
2. Let  $typeIR_{cond}$  be the type of  $typedExpressionIR_{cond}$ .
3. Let  $ctk_{cond}$  be the compile-time known-ness of  $typedExpressionIR_{cond}$ .
4. Check that **BOOL** is equal to  $typeIR_{cond}$  with **typeddefs** unrolled.
5. Let  $typedExpressionIR_{true}$  be
  - the result of **typing**  $expression_{true}$ , under cursor  $p$  and context  $TC$ .
6. Let  $typedExpressionIR_{false}$  be
  - the result of **typing**  $expression_{false}$ , under cursor  $p$  and context  $TC$ .
7. Let (  $typedExpressionIR_{true\_cast}$ ,  $typedExpressionIR_{false\_cast}$  ) be **!**  $typedExpressionIR_{true}$  and  $typedExpressionIR_{false}$  **implicitly cast to equal types**.
8. Let  $typeIR_{cast}$  be the type of  $typedExpressionIR_{true\_cast}$ .
9. Let  $ctk_{true\_cast}$  be the compile-time known-ness of  $typedExpressionIR_{true\_cast}$ .
10. Let  $ctk_{false\_cast}$  be the compile-time known-ness of  $typedExpressionIR_{false\_cast}$ .
11. Check that if  $typeIR_{cast}$  is equal to **INT**, then  $ctk_{cond}$  is not equal to **DYN**.
12. Let  $ctk$  be the join of [  $ctk_{cond}$ ,  $ctk_{true\_cast}$ ,  $ctk_{false\_cast}$  ].
13. Let  $expressionNoteIR$  be a pair of type  $typeIR_{cast}$  and compile-time known-ness  $ctk$ .
14. Result in  $typedExpressionIR_{cond} ? typedExpressionIR_{true\_cast} : typedExpressionIR_{false\_cast}$  **annotated with**  $expressionNoteIR$ .

### 14.7.2. Local compile-time evaluation

**Local compile-time evaluation** of  $typedExpressionIR_{cond} ? typedExpressionIR_{true} : typedExpressionIR_{false}$

annotated with  $\text{expressionNodeIR}$ , under cursor  $p$  and context  $TC$ :

1. Let  $\text{value}$  be
  - the result of local compile-time evaluation of  $\text{typedExpressionIR}_{\text{cond}}$ , under cursor  $p$  and context  $TC$ .
2. If  $\text{value}$  is equal to  $\text{'B true'}$ :
  - a. Let  $\text{value}_{\text{true}}$  be
    - the result of local compile-time evaluation of  $\text{typedExpressionIR}_{\text{true}}$ , under cursor  $p$  and context  $TC$ .
  - b. Result in  $\text{value}_{\text{true}}$ .
3. If  $\text{value}$  is equal to  $\text{'B false'}$ :
  - a. Let  $\text{value}_{\text{false}}$  be
    - the result of local compile-time evaluation of  $\text{typedExpressionIR}_{\text{false}}$ , under cursor  $p$  and context  $TC$ .
  - b. Result in  $\text{value}_{\text{false}}$ .

### 14.7.3. Compile-time evaluation

Compile-time evaluation of  $\text{typedExpressionIR}_{\text{cond}} ? \text{typedExpressionIR}_{\text{true}} : \text{typedExpressionIR}_{\text{false}}$  annotated with  $\text{expressionNodeIR}$ , under cursor  $p$ , context  $IC$ , and store  $STO$ :

1. Let store  $STO_1$  and  $\text{value}$  be
  - the result of compile-time evaluation of  $\text{typedExpressionIR}_{\text{cond}}$ , under cursor  $p$ , context  $IC$ , and store  $STO$ .
2. If  $\text{value}$  is equal to  $\text{'B true'}$ :
  - a. Let store  $STO_2$  and  $\text{value}_{\text{true}}$  be
    - the result of compile-time evaluation of  $\text{typedExpressionIR}_{\text{true}}$ , under cursor  $p$ , context  $IC$ , and store  $STO_1$ .
  - b. Result in store  $STO_2$  and  $\text{value}_{\text{true}}$ .
3. If  $\text{value}$  is equal to  $\text{'B false'}$ :
  - a. Let store  $STO_2$  and  $\text{value}_{\text{false}}$  be
    - the result of compile-time evaluation of  $\text{typedExpressionIR}_{\text{false}}$ , under cursor  $p$ , context  $IC$ , and store  $STO_1$ .
  - b. Result in store  $STO_2$  and  $\text{value}_{\text{false}}$ .

### 14.7.4. Runtime evaluation

Evaluating  $\text{typedExpressionIR}_{\text{cond}} ? \text{typedExpressionIR}_{\text{true}} : \text{typedExpressionIR}_{\text{false}}$  annotated with  $\text{expressionNodeIR}$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ :

1. Let context  $EC_1$ , state  $ARCH_1$  and  $\text{expressionResult}$  be
  - the result of evaluating  $\text{typedExpressionIR}_{\text{cond}}$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ .

2. If let `abortResult` be `expressionResult`:
  - a. Result in context  $EC_1$ , state  $ARCH_1$  and `abortResult`.
3. If `expressionResult` is equal to ``B true`:
  - a. Let context  $EC_2$ , state  $ARCH_2$  and `expressionResulttrue` be
    - the result of evaluating `typedExpressionIRtrue`, under cursor `p`, context  $EC_1$ , and state  $ARCH_1$ .
  - b. Result in context  $EC_2$ , state  $ARCH_2$  and `expressionResulttrue`.
4. If `expressionResult` is equal to ``B false`:
  - a. Let context  $EC_2$ , state  $ARCH_2$  and `expressionResultfalse` be
    - the result of evaluating `typedExpressionIRfalse`, under cursor `p`, context  $EC_1$ , and state  $ARCH_1$ .
  - b. Result in context  $EC_2$ , state  $ARCH_2$  and `expressionResultfalse`.

## 14.8. Cast expressions

P4 provides a limited set of casts between types. A cast is written `(t) e`, where `t` is a type and `e` is an expression.

```
castExpression
: `( type ) expression
;
```

### 14.8.1. Type checking

Typing ( `typet` ) `expression`', under cursor `p` and context `TC`:

1. Let `typeIRt` and a set of fresh type variables `typeId*` be
  - the result of typing `typet`, under cursor `p` and context `TC`.
2. Check that `typeId*` is an empty list.
3. Let `bound` be bound type variables from the `p` layer of `TC`.
4. Check that `typeIRt` is a well-formed type, with bound type variables `bound`.
5. Let `typedExpressionIR` be
  - the result of typing `expression`', under cursor `p` and context `TC`.
6. Let `typeIR` be the type of `typedExpressionIR`.
7. Let `ctk` be the compile-time known-ness of `typedExpressionIR`.
8. Check that `typeIR` can be explicitly cast to `typeIRt`.
9. Let `expressionNoteIR` be a pair of type `typeIRt` and compile-time known-ness `ctk`.
10. Result in ( `typeIRt` ) `typedExpressionIR` annotated with `expressionNoteIR`.

### 14.8.2. Local compile-time evaluation

Local compile-time evaluation of ( `typeIR` ) `typedExpressionIR` annotated with `expressionNoteIR`, under cursor `p` and context `TC`:

1. Let  $value$  be
  - the result of **local compile-time evaluation of**  $typedExpressionIR$ , **under cursor**  $p$  **and context**  $TC$ .
2. Let  $value_{cast}$  be  $value$  **casted to type**  $typeIR$ .
3. Result in  $value_{cast}$ .

### 14.8.3. Compile-time evaluation

**Compile-time evaluation of**  $(typeIR)$   $typedExpressionIR$  **annotated with**  $expressionNoteIR$ , **under cursor**  $p$ , **context**  $IC$ , **and store**  $STO$ :

1. Let store  $STO_1$  and  $value$  be
  - the result of **compile-time evaluation of**  $typedExpressionIR$ , **under cursor**  $p$ , **context**  $IC$ , **and store**  $STO$ .
2. Let  $value_{cast}$  be  $value$  **casted to type**  $typeIR$ .
3. Result in store  $STO_1$  and  $value_{cast}$ .

### 14.8.4. Runtime evaluation

**Evaluating**  $(typeIR)$   $typedExpressionIR$  **annotated with**  $expressionNoteIR$ , **under cursor**  $p$ , **context**  $EC$ , **and state**  $ARCH$ :

1. Let context  $EC_1$ , state  $ARCH_1$  and  $expressionResult$  be
  - the result of **evaluating**  $typedExpressionIR$ , **under cursor**  $p$ , **context**  $EC$ , **and state**  $ARCH$ .
2. If let  $abortResult$  be  $expressionResult$ :
  - a. Result in context  $EC_1$ , state  $ARCH_1$  and  $abortResult$ .
3. Else:
  - a. Let  $value$  be  $expressionResult$ .
  - b. Let  $value_{cast}$  be  $value$  **casted to type**  $typeIR$ .
  - c. Result in context  $EC_1$ , state  $ARCH_1$  and  $value_{cast}$ .

## 14.9. Invalid header expressions

$\{ \# \}$  represents an invalid header expression. See [Section 8.6.2](#) for more details.

```
invalidHeaderExpression
: {#}
;
```

### 14.9.1. Type checking

After type checking, an invalid header expression is represented as:

```
invalidHeaderExpressionIR = invalidHeaderExpression
```

Typing `{#}`, under cursor `p` and context `TC`:

1. Let `expressionNoteIR` be a pair of type `HEADER_INVALID` and compile-time known-ness `LCTK`.
2. Result in `{#}` annotated with `expressionNoteIR`.

### 14.9.2. Local compile-time evaluation

Local compile-time evaluation of `{#}` annotated with `expressionNoteIR`, under cursor `p` and context `TC`:

1. Result in `{#}`.

### 14.9.3. Compile-time evaluation

Compile-time evaluation of `{#}` annotated with `expressionNoteIR`, under cursor `p`, context `IC`, and store `STO`:

1. Result in store `STO` and `{#}`.

### 14.9.4. Runtime evaluation

Evaluating `{#}` annotated with `expressionNoteIR`, under cursor `p`, context `EC`, and state `ARCH`:

1. Let `expressionResult` be `{#}`.
2. Result in context `EC`, state `ARCH` and `expressionResult`.

## 14.10. Sequence expressions

A sequence expression is a comma-separated list of expressions enclosed in curly braces `{ }`. See [Section 8.6.3](#) for details.

```
sequenceOrRecordExpression
: `{ sequenceOrRecordElementExpression trailingCommaOpt }
;

sequenceElementExpression = expressionList

sequenceOrRecordElementExpression
: sequenceElementExpression
| recordElementExpression
;
```

### 14.10.1. Type checking

After type checking, a sequence expression is represented as:

```
sequenceExpressionIR
: SEQ `{ typedExpressionListIR }
| SEQ `{ typedExpressionListIR , ... }
;
```

Typing { expressionList trailingCommaOpt }, under cursor p and context TC:

1. Let  $\text{expression}_e^*$  be the list of expressions in expressionList.
2. If ... is not in  $\text{expression}_e^*$ :
  - a. Let  $\text{typedExpressionIR}_e^*$  be the list of  $\text{typedExpressionIR}_e$ , obtained by repeating:
    - Let  $\text{typedExpressionIR}_e$  be
      - the result of typing  $\text{expression}_e$ , under cursor p and context TC.for each  $\text{expression}_e$  in  $\text{expression}_e^*$
  - b. Let  $\text{typeIR}_e^*$  be the list of  $\text{typeIR}_e$ , obtained by repeating:
    - Let  $\text{typeIR}_e$  be the type of  $\text{typedExpressionIR}_e$ .for each  $\text{typedExpressionIR}_e$  in  $\text{typedExpressionIR}_e^*$
  - c. Let  $\text{ctk}_e^*$  be the list of  $\text{ctk}_e$ , obtained by repeating:
    - Let  $\text{ctk}_e$  be the compile-time known-ness of  $\text{typedExpressionIR}_e$ .for each  $\text{typedExpressionIR}_e$  in  $\text{typedExpressionIR}_e^*$
  - d. Let  $\text{typeIR}$  be  $\text{SEQ} < \text{typeIR}_e^* >$ .
  - e. Let  $\text{ctk}$  be the join of  $\text{ctk}_e^*$ .
  - f. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}$  and compile-time known-ness  $\text{ctk}$ .
  - g. Result in  $\text{SEQ} \{ \text{typedExpressionIR}_e^* \}$  annotated with  $\text{expressionNoteIR}$ .
3. Else:
  - a. Let  $\text{expression}^*$  be the reversal of  $\text{expression}_e^*$ .
  - b. Check that  $\text{expression}^*$  is a non-empty list.
  - c. Let  $\text{expression}'' :: \text{expression}_{e_h\text{rev}}^*$  be  $\text{expression}^*$ .
  - d. Check that  $\text{expression}''$  has type  $\text{defaultExpression}$ .
  - e. Let  $\text{defaultExpression}$  be  $\text{expression}''$ .
  - f. Let  $\text{expression}_{e_h}^*$  be the reversal of  $\text{expression}_{e_h\text{rev}}^*$ .
  - g. Check that ... is not in  $\text{expression}_{e_h}^*$ .
  - h. Let  $\text{typedExpressionIR}_{e_h}^*$  be the list of  $\text{typedExpressionIR}_{e_h}$ , obtained by repeating:
    - Let  $\text{typedExpressionIR}_{e_h}$  be
      - the result of typing  $\text{expression}_{e_h}$ , under cursor p and context TC.

- for each  $\text{expression}_{e,h}$  in  $\text{expression}_{e,h}^*$
- i. Let  $\text{typeIR}_{e,h}^*$  be the list of  $\text{typeIR}_{e,h}$ , obtained by repeating:
    - Let  $\text{typeIR}_{e,h}$  be the type of  $\text{typedExpressionIR}_{e,h}$ .

for each  $\text{typedExpressionIR}_{e,h}$  in  $\text{typedExpressionIR}_{e,h}^*$
  - j. Let  $\text{ctk}_{e,h}^*$  be the list of  $\text{ctk}_{e,h}$ , obtained by repeating:
    - Let  $\text{ctk}_{e,h}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{e,h}$ .

for each  $\text{typedExpressionIR}_{e,h}$  in  $\text{typedExpressionIR}_{e,h}^*$
  - k. Let  $\text{typeIR}$  be  $\text{SEQ} < \text{typeIR}_{e,h}^*, \dots >$ .
  - l. Let  $\text{ctk}$  be the join of  $\text{ctk}_{e,h}^*$ .
  - m. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}$  and compile-time known-ness  $\text{ctk}$ .
  - n. Result in  $\text{SEQ} \{ \text{typedExpressionIR}_{e,h}^*, \dots \}$  annotated with  $\text{expressionNoteIR}$ .

## 14.10.2. Local compile-time evaluation

Local compile-time evaluation of  $\text{sequenceExpressionIR}$  annotated with  $\text{expressionNoteIR}$ , under cursor  $p$  and context  $TC$ :

1. If let  $\text{SEQ} \{ \text{typedExpressionIR}^* \}$  be  $\text{sequenceExpressionIR}$ :
  - a. Let  $\text{value}^*$  be the list of  $\text{value}$ , obtained by repeating:
    - Let  $\text{value}$  be
      - the result of local compile-time evaluation of  $\text{typedExpressionIR}$ , under cursor  $p$  and context  $TC$ .

for each  $\text{typedExpressionIR}$  in  $\text{typedExpressionIR}^*$
  - b. Result in  $\text{SEQ} ( \text{value}^* )$ .
2. Else:
  - a. Let  $\text{SEQ} \{ \text{typedExpressionIR}^*, \dots \}$  be  $\text{sequenceExpressionIR}$ .
  - b. Let  $\text{value}^*$  be the list of  $\text{value}$ , obtained by repeating:
    - Let  $\text{value}$  be
      - the result of local compile-time evaluation of  $\text{typedExpressionIR}$ , under cursor  $p$  and context  $TC$ .

for each  $\text{typedExpressionIR}$  in  $\text{typedExpressionIR}^*$
  - c. Result in  $\text{SEQ} ( \text{value}^*, \dots )$ .

### 14.10.3. Compile-time evaluation

Compile-time evaluation of `sequenceExpressionIR` annotated with `expressionNodeIR`, under cursor `p`, context `IC`, and store `STO`:

1. If let `SEQ { typedExpressionListIR }` be `sequenceExpressionIR`:
  - a. Let store `STO1` and `value*` be
    - the result of compile-time evaluation of `typedExpressionListIR`, under cursor `p`, context `IC`, and store `STO`.
  - b. Result in store `STO1` and `SEQ ( value* )`.
2. Else:
  - a. Let `SEQ { typedExpressionListIR , ... }` be `sequenceExpressionIR`.
  - b. Let store `STO1` and `value*` be
    - the result of compile-time evaluation of `typedExpressionListIR`, under cursor `p`, context `IC`, and store `STO`.
  - c. Result in store `STO1` and `SEQ ( value* , ... )`.

### 14.10.4. Runtime evaluation

Evaluating `sequenceExpressionIR` annotated with `expressionNodeIR`, under cursor `p`, context `EC`, and state `ARCH`:

1. If let `SEQ { typedExpressionListIR }` be `sequenceExpressionIR`:
  - a. Let context `EC1`, state `ARCH1`, and `expressionListResult` be
    - the result of evaluating `typedExpressionListIR`, under cursor `p`, context `EC`, and state `ARCH`.
  - b. If let `abortResult` be `expressionListResult`:
    - i. Result in context `EC1`, state `ARCH1` and `abortResult`.
  - c. Else:
    - i. Let `value*` be `expressionListResult`.
    - ii. Let `expressionResult` be `SEQ ( value* )`.
    - iii. Result in context `EC1`, state `ARCH1` and `expressionResult`.
2. Else:
  - a. Let `SEQ { typedExpressionListIR , ... }` be `sequenceExpressionIR`.
  - b. Let context `EC1`, state `ARCH1` and `expressionListResult` be
    - the result of evaluating `typedExpressionListIR`, under cursor `p`, context `EC`, and state `ARCH`.
  - c. If let `abortResult` be `expressionListResult`:
    - i. Result in context `EC1`, state `ARCH1` and `abortResult`.
  - d. Else:
    - i. Let `value*` be `expressionListResult`.
    - ii. Let `expressionResult` be `SEQ ( value* , ... )`.
    - iii. Result in context `EC1`, state `ARCH1` and `expressionResult`.



## 14.11. Record expressions

A record expression is a comma-separated list of named expressions enclosed in curly braces `{}`. See [Section 8.6.4](#) for details.

```
sequenceOrRecordExpression
: `{ sequenceOrRecordElementExpression trailingCommaOpt }
;

recordElementExpression
: name = expression
| name = expression , ...
| name = expression , namedExpressionList
| name = expression , namedExpressionList , ...
;

sequenceOrRecordElementExpression
: sequenceElementExpression
| recordElementExpression
;
```

### 14.11.1. Type checking

After type checking, a record expression is represented as:

```
recordExpressionIR
: RECORD `{ namedExpressionListIR }
| RECORD `{ namedExpressionListIR , ... }
;
```

**Typing** { recordElementExpression trailingCommaOpt }, under cursor *p* and context *TC*:

1. If let  $\text{name}_f = \text{expression}_f$  be recordElementExpression:
  - a. Let  $\text{nameIR}_f$  be the name of  $\text{name}_f$ .
  - b. Let  $\text{typedExpressionIR}_f$  be
    - the result of typing  $\text{expression}_f$ , under cursor *p* and context *TC*.
  - c. Let  $\text{typeIR}_f$  be the type of  $\text{typedExpressionIR}_f$ .
  - d. Let  $\text{ctk}_f$  be the compile-time known-ness of  $\text{typedExpressionIR}_f$ .
  - e. Let  $\text{typeIR}$  be `RECORD { `EMPTY typeIRf nameIRf ; }`.
  - f. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}$  and compile-time known-ness  $\text{ctk}_f$ .
  - g. Result in `RECORD { nameIRf = typedExpressionIRf } annotated with expressionNoteIR`.
2. Else if let  $\text{name}_f = \text{expression}_f, \dots$  be recordElementExpression:
  - a. Let  $\text{nameIR}_f$  be the name of  $\text{name}_f$ .
  - b. Let  $\text{typedExpressionIR}_f$  be
    - the result of typing  $\text{expression}_f$ , under cursor *p* and context *TC*.
  - c. Let  $\text{typeIR}_f$  be the type of  $\text{typedExpressionIR}_f$ .
  - d. Let  $\text{ctk}_f$  be the compile-time known-ness of  $\text{typedExpressionIR}_f$ .
  - e. Let  $\text{typeIR}$  be `RECORD { `EMPTY typeIRf nameIRf ; , ... }`.

- f. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}$  and compile-time known-ness  $\text{ctk}_f$ .
- g. Result in  $\text{RECORD } \{ \text{nameIR}_f = \text{typedExpressionIR}_f, \dots \}$  annotated with  $\text{expressionNoteIR}$ .
3. Else if let  $\text{name}_{f,h} = \text{expression}_{f,h}$ ,  $\text{namedExpressionList}_t$  be  $\text{recordElementExpression}$ :
  - a. Let  $(\text{name}_{f,t} = \text{expression}_{f,t})^*$  be the list of named expressions in  $\text{namedExpressionList}_t$ .
  - b. Let  $\text{name}_f^*$  be  $\text{name}_{f,h} :: \text{name}_{f,t}^*$ .
  - c. Let  $\text{nameIR}_f^*$  be the list of  $\text{nameIR}_f$ , obtained by repeating:
    - Let  $\text{nameIR}_f$  be the name of  $\text{name}_f$ .
 for each  $\text{name}_f$  in  $\text{name}_f^*$
  - d. Let  $\text{expression}_f^*$  be  $\text{expression}_{f,h} :: \text{expression}_{f,t}^*$ .
  - e. Let  $\text{typedExpressionIR}_f^*$  be the list of  $\text{typedExpressionIR}_f$ , obtained by repeating:
    - Let  $\text{typedExpressionIR}_f$  be
      - the result of typing  $\text{expression}_f$ , under cursor  $p$  and context  $\text{TC}$ .
 for each  $\text{expression}_f$  in  $\text{expression}_f^*$
  - f. Let  $\text{typeIR}_f^*$  be the list of  $\text{typeIR}_f$ , obtained by repeating:
    - Let  $\text{typeIR}_f$  be the type of  $\text{typedExpressionIR}_f$ .
 for each  $\text{typedExpressionIR}_f$  in  $\text{typedExpressionIR}_f^*$
  - g. Let  $\text{ctk}_f^*$  be the list of  $\text{ctk}_f$ , obtained by repeating:
    - Let  $\text{ctk}_f$  be the compile-time known-ness of  $\text{typedExpressionIR}_f$ .
 for each  $\text{typedExpressionIR}_f$  in  $\text{typedExpressionIR}_f^*$
  - h. Let  $\text{typeIR}$  be  $\text{RECORD } \{ ( \text{`EMPTY typeIR}_f \text{ nameIR}_f ; )^* \}$ .
  - i. Let  $\text{ctk}$  be the join of  $\text{ctk}_f^*$ .
  - j. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}$  and compile-time known-ness  $\text{ctk}$ .
  - k. Result in  $\text{RECORD } \{ ( \text{nameIR}_f = \text{typedExpressionIR}_f )^* \}$  annotated with  $\text{expressionNoteIR}$ .
4. Else:
  - a. Let  $\text{name}_{f,h} = \text{expression}_{f,h}$ ,  $\text{namedExpressionList}_t, \dots$  be  $\text{recordElementExpression}$ .
  - b. Let  $(\text{name}_{f,t} = \text{expression}_{f,t})^*$  be the list of named expressions in  $\text{namedExpressionList}_t$ .
  - c. Let  $\text{name}_f^*$  be  $\text{name}_{f,h} :: \text{name}_{f,t}^*$ .
  - d. Let  $\text{nameIR}_f^*$  be the list of  $\text{nameIR}_f$ , obtained by repeating:
    - Let  $\text{nameIR}_f$  be the name of  $\text{name}_f$ .
 for each  $\text{name}_f$  in  $\text{name}_f^*$
  - e. Let  $\text{expression}_f^*$  be  $\text{expression}_{f,h} :: \text{expression}_{f,t}^*$ .
  - f. Let  $\text{typedExpressionIR}_f^*$  be the list of  $\text{typedExpressionIR}_f$ , obtained by repeating:
    - Let  $\text{typedExpressionIR}_f$  be

- the result of **typing**  $expression_f$ , under cursor  $p$  and context  $TC$ .

for each  $expression_f$  in  $expression_f^*$

g. Let  $typeIR_f^*$  be the list of  $typeIR_f$ , obtained by repeating:

- Let  $typeIR_f$  be **the type of**  $typedExpressionIR_f$ .

for each  $typedExpressionIR_f$  in  $typedExpressionIR_f^*$

h. Let  $ctk_f^*$  be the list of  $ctk_f$ , obtained by repeating:

- Let  $ctk_f$  be **the compile-time known-ness of**  $typedExpressionIR_f$ .

for each  $typedExpressionIR_f$  in  $typedExpressionIR_f^*$

i. Let  $typeIR$  be  $RECORD \{ ( \text{`EMPTY' } typeIR_f \text{ nameIR}_f ; )^* , \dots \}$ .

j. Let  $ctk$  be **the join of**  $ctk_f^*$ .

k. Let  $expressionNoteIR$  be **a pair of type**  $typeIR$  **and compile-time known-ness**  $ctk$ .

l. Result in  $RECORD \{ ( \text{nameIR}_f = typedExpressionIR_f )^* , \dots \}$  **annotated with**  $expressionNoteIR$ .

## 14.11.2. Local compile-time evaluation

**Local compile-time evaluation of**  $recordExpressionIR$  **annotated with**  $expressionNoteIR$ , under cursor  $p$  and context  $TC$ :

1. If let  $RECORD \{ ( \text{nameIR} = typedExpressionIR )^* \}$  be  $recordExpressionIR$ :

a. Let  $value^*$  be the list of  $value$ , obtained by repeating:

- Let  $value$  be
  - the result of **local compile-time evaluation of**  $typedExpressionIR$ , under cursor  $p$  and context  $TC$ .

for each  $typedExpressionIR$  in  $typedExpressionIR^*$

b. Result in  $RECORD \{ ( \text{value nameIR} ; )^* \}$ .

2. Else:

a. Let  $RECORD \{ ( \text{nameIR} = typedExpressionIR )^* , \dots \}$  be  $recordExpressionIR$ .

b. Let  $value^*$  be the list of  $value$ , obtained by repeating:

- Let  $value$  be
  - the result of **local compile-time evaluation of**  $typedExpressionIR$ , under cursor  $p$  and context  $TC$ .

for each  $typedExpressionIR$  in  $typedExpressionIR^*$

c. Result in  $RECORD \{ ( \text{value nameIR} ; )^* , \dots \}$ .

## 14.11.3. Compile-time evaluation

Compile-time evaluation of `recordExpressionIR` annotated with `expressionNodeIR`, under cursor `p`, context `IC`, and store `STO`:

1. If let `RECORD { ( nameIR = typedExpressionIR )* }` be `recordExpressionIR`:
  - a. Let store `STO1` and `value*` be
    - the result of compile-time evaluation of `typedExpressionIR*`, under cursor `p`, context `IC`, and store `STO`.
  - b. Result in store `STO1` and `RECORD { ( value nameIR ; )* }`.
2. Else:
  - a. Let `RECORD { ( nameIR = typedExpressionIR )* , ... }` be `recordExpressionIR`.
  - b. Let store `STO1` and `value*` be
    - the result of compile-time evaluation of `typedExpressionIR*`, under cursor `p`, context `IC`, and store `STO`.
  - c. Result in store `STO1` and `RECORD { ( value nameIR ; )* , ... }`.

#### 14.11.4. Runtime evaluation

Evaluating `recordExpressionIR` annotated with `expressionNodeIR`, under cursor `p`, context `EC`, and state `ARCH`:

1. If let `RECORD { ( nameIR = typedExpressionIR )* }` be `recordExpressionIR`:
  - a. Let context `EC1`, state `ARCH1` and `expressionListResult` be
    - the result of evaluating `typedExpressionIR*`, under cursor `p`, context `EC`, and state `ARCH`.
  - b. If let `abortResult` be `expressionListResult`:
    - i. Result in context `EC1`, state `ARCH1` and `abortResult`.
  - c. Else:
    - i. Let `value*` be `expressionListResult`.
    - ii. Let `expressionResult` be `RECORD { ( value nameIR ; )* }`.
    - iii. Result in context `EC1`, state `ARCH1` and `expressionResult`.
2. Else:
  - a. Let `RECORD { ( nameIR = typedExpressionIR )* , ... }` be `recordExpressionIR`.
  - b. Let context `EC1`, state `ARCH1` and `expressionListResult` be
    - the result of evaluating `typedExpressionIR*`, under cursor `p`, context `EC`, and state `ARCH`.
  - c. If let `abortResult` be `expressionListResult`:
    - i. Result in context `EC1`, state `ARCH1` and `abortResult`.
  - d. Else:
    - i. Let `value*` be `expressionListResult`.
    - ii. Let `expressionResult` be `RECORD { ( value nameIR ; )* , ... }`.
    - iii. Result in context `EC1`, state `ARCH1` and `expressionResult`.

## 14.12. Error access expression

An error access expression accesses a symbolic name in the `error` namespace. See [Section 8.2.4](#) for details about error types and values.

```
errorAccessExpression
: ERROR . member
;
```

### 14.12.1. Type checking

After type checking, an error access expression is represented as:

```
errorAccessExpressionIR
: ERROR . nameIR
;
```

Typing `ERROR . member`, under cursor `p` and context `TC`:

1. Let `nameIR` be the name of `member`.
2. Let `nameIRerror` be "error." concatenated with `nameIR`.
3. Check that `ERROR . nameIR` is equal to the value of variable `nameIRerror` from the `p` layer of `TC`.
4. Let `expressionNoteIR` be a pair of type `ERROR` and compile-time known-ness `LCTK`.
5. Result in `ERROR . nameIR` annotated with `expressionNoteIR`.

### 14.12.2. Local compile-time evaluation

Local compile-time evaluation of `ERROR . nameIR` annotated with a pair of type `typeIR` and compile-time known-ness `ctk`, under cursor `p` and context `TC`:

1. Let `nameIRerror` be "error." concatenated with `nameIR`.
2. Let `valueerror` be the value of variable `nameIRerror` from the `p` layer of `TC`.
3. Result in `valueerror`.

### 14.12.3. Compile-time evaluation

Compile-time evaluation of `ERROR . nameIR` annotated with `expressionNoteIR`, under cursor `p`, context `IC`, and store `STO`:

1. Let `nameIRerror` be "error." concatenated with `nameIR`.
2. Let `valueerror` be the value of `nameIRerror` from the `p` layer of `IC`.
3. Result in store `STO` and `valueerror`.

## 14.12.4. Runtime evaluation

Evaluating `ERROR . nameIR` annotated with `expressionNoteIR`, under cursor `p`, context `EC`, and state `ARCH`:

1. Let `nameIRerror` be "error." concatenated with `nameIR`.
2. Let `valueerror` be the value of `nameIRerror` from the `p` layer of `EC`.
3. Let `expressionResult` be `valueerror`.
4. Result in context `EC`, state `ARCH` and `expressionResult`.

## 14.13. Member access expressions

A member access expression accesses a user-defined or built-in field in an aggregate value. Also, it may access an element defined in an enum declaration.

```
memberAccessExpression
: memberAccessBase . member
;

memberAccessBase
: prefixedTypeName
| expression
;
```

### 14.13.1. Type checking

After type checking, a member access expression is represented in `P4IR` as:

```
memberAccessExpressionIR
: memberAccessBaseIR . nameIR
;

memberAccessBaseIR
: TYPE prefixedNameIR
| typedExpressionIR
;
```

### Accessing an enum member

Typing `prefixedTypeNamebase . member`, under cursor `p` and context `TC`:

1. Let `prefixedNameIRbase` be the prefixed name of `prefixedTypeNamebase`.
2. Let `typeDefIRbase` be ! the type definition of `prefixedNameIRbase` from the `p` layer of `TC`.
3. Check that `typeDefIRbase` is monomorphic.
4. Let `typeIRbase` be the underlying type of `typeDefIRbase`.
5. Let `typeIR` be `typeIRbase` with typedefs unrolled.
6. If let `ENUM _ { nameIRfield * }` be `typeIR`:
  - a. Let `nameIR` be the name of member.
  - b. Check that `nameIR` is in `nameIRfield *`.

- c. Let `expressionNoteIR` be a pair of type `typeIRbase` and compile-time known-ness LCTK.
  - d. Result in `TYPE prefixedNameIRbase . nameIR` annotated with `expressionNoteIR`.
7. Else if let `ENUM _ < _ > { ( nameIRfield = _ ; ) * }` be `typeIR`:
- a. Let `nameIR` be the name of member.
  - b. Check that `nameIR` is in `nameIRfield *`.
  - c. Let `expressionNoteIR` be a pair of type `typeIRbase` and compile-time known-ness LCTK.
  - d. Result in `TYPE prefixedNameIRbase . nameIR` annotated with `expressionNoteIR`.

## Accessing an aggregate member

Typing `expressionbase . member`, under cursor `p` and context `TC`:

1. Let `typedExpressionIRbase` be
  - the result of typing `expressionbase`, under cursor `p` and context `TC`.
2. Let `typeIRbase` be the type of `typedExpressionIRbase`.
3. Let `typeIR` be `typeIRbase` with typedefs unrolled.
4. If let `typeIR' [ nsize ]` be `typeIR`:
  - a. If "size" is equal to the name of member:
    - i. Let `expressionNoteIR` be a pair of type `BIT < 32 >` and compile-time known-ness LCTK.
    - ii. Result in `typedExpressionIRbase . "size"` annotated with `expressionNoteIR`.
  - b. If "lastIndex" is equal to the name of member:
    - i. Check that `p` is equal to `BLOCK` and `TC.BLOCK.KIND` is equal to `PARSER` or `p` is equal to `LOCAL` and `TC.LOCAL.KIND` is equal to `PARSER_STATE`.
    - ii. Let `expressionNoteIR` be a pair of type `BIT < 32 >` and compile-time known-ness DYN.
    - iii. Result in `typedExpressionIRbase . "lastIndex"` annotated with `expressionNoteIR`.
  - c. If "last" is equal to the name of member:
    - i. Check that `p` is equal to `BLOCK` and `TC.BLOCK.KIND` is equal to `PARSER` or `p` is equal to `LOCAL` and `TC.LOCAL.KIND` is equal to `PARSER_STATE`.
    - ii. Let `expressionNoteIR` be a pair of type `typeIR'` and compile-time known-ness DYN.
    - iii. Result in `typedExpressionIRbase . "last"` annotated with `expressionNoteIR`.
  - d. If "next" is equal to the name of member:
    - i. Check that `p` is equal to `BLOCK` and `TC.BLOCK.KIND` is equal to `PARSER` or `p` is equal to `LOCAL` and `TC.LOCAL.KIND` is equal to `PARSER_STATE`.
    - ii. Let `expressionNoteIR` be a pair of type `typeIR'` and compile-time known-ness DYN.
    - iii. Result in `typedExpressionIRbase . "next"` annotated with `expressionNoteIR`.
5. Let `ctkbase` be the compile-time known-ness of `typedExpressionIRbase`.
6. Let `typeIR` be `typeIRbase` with typedefs unrolled.
7. If let `STRUCT _ < _ * > { ( _ typeIRf nameIRf ; ) * }` be `typeIR`:
  - a. Let `nameIR` be the name of member.
  - b. Let `typeIR` be ! the value associated to `nameIR` in `( nameIRf, typeIRf ) *`.

- c. Let `expressionNoteIR` be a pair of type `typeIR` and compile-time known-ness `ctkbase`.
  - d. Result in `typedExpressionIRbase . nameIR` annotated with `expressionNoteIR`.
8. Else if let `HEADER _ < _ * > { ( _ typeIRf nameIRf ; ) * }` be `typeIR`:
- a. Let `nameIR` be the name of member.
  - b. Let `typeIR` be ! the value associated to `nameIR` in `( nameIRf, typeIRf ) *`.
  - c. Let `expressionNoteIR` be a pair of type `typeIR` and compile-time known-ness `ctkbase`.
  - d. Result in `typedExpressionIRbase . nameIR` annotated with `expressionNoteIR`.
9. Else if let `HEADER_UNION _ < _ * > { ( _ typeIRf nameIRf ; ) * }` be `typeIR`:
- a. Let `nameIR` be the name of member.
  - b. Let `typeIR` be ! the value associated to `nameIR` in `( nameIRf, typeIRf ) *`.
  - c. Let `expressionNoteIR` be a pair of type `typeIR` and compile-time known-ness `ctkbase`.
  - d. Result in `typedExpressionIRbase . nameIR` annotated with `expressionNoteIR`.
10. Let `typeIR` be `typeIRbase` with `typedefs` unrolled.
11. If let `TABLE_STRUCT _ { HIT boolTypeIR ; MISS _ ; ACTION_RUN _ ; }` be `typeIR`:
- a. Let `nameIR` be the name of member.
  - b. If `nameIR` is equal to "hit":
    - i. Let `expressionNoteIR` be a pair of type `boolTypeIR` and compile-time known-ness `DYN`.
    - ii. Result in `typedExpressionIRbase . nameIR` annotated with `expressionNoteIR`.
  - c. Else if `nameIR` is equal to "miss":
    - i. Let `expressionNoteIR` be a pair of type `_` and compile-time known-ness `DYN`.
    - ii. Result in `typedExpressionIRbase . nameIR` annotated with `expressionNoteIR`.
  - d. Else if `nameIR` is equal to "action\_run":
    - i. Let `expressionNoteIR` be a pair of type `_` and compile-time known-ness `DYN`.
    - ii. Result in `typedExpressionIRbase . nameIR` annotated with `expressionNoteIR`.

## 14.13.2. Local compile-time evaluation

### Accessing an enum member

Local compile-time evaluation of `TYPE prefixedNameIRbase . nameIR` annotated with `expressionNoteIR`, under cursor `p` and context `TC`:

1. Let `typeDefIRbase` be ! the type definition of `prefixedNameIRbase` from the `p` layer of `TC`.
2. Check that `typeDefIRbase` is monomorphic.
3. Let `typeIRbase` be the underlying type of `typeDefIRbase`.
4. Let `typeIR` be `typeIRbase` with `typedefs` unrolled.
5. If let `ENUM typeID { nameIRfield * }` be `typeIR`:
  - a. Check that `nameIR` is in `nameIRfield *`.
  - b. Result in `typeID . nameIR`.



6. Else if let **ENUM**  $\text{typed} < \text{typeIR}' > \{ ( \text{nameIR}_{\text{field}} = \text{value}_{\text{field}} ; )^* \}$  be  $\text{typeIR}$ :
  - a. Let  $\text{value}'$  be ! the value associated to  $\text{nameIR}$  in  $( \text{nameIR}_{\text{field}}, \text{value}_{\text{field}} )^*$ .
  - b. Result in  $\text{typed} . \text{nameIR} . \text{value}'$ .

## Accessing an aggregate member

Local compile-time evaluation of  $\text{typedExpressionIR}_{\text{base}} . \text{nameIR}$  annotated with  $\text{expressionNoteIR}$ , under cursor  $p$  and context  $TC$ :

1. Let  $\text{typeIR}_{\text{base}}$  be the type of  $\text{typedExpressionIR}_{\text{base}}$ .
2. Let  $\text{typeIR}$  be  $\text{typeIR}_{\text{base}}$  with **typedefs** unrolled.
3. If let  $\_ [ n_{\text{size}} ]$  be  $\text{typeIR}$ :
  - a. Check that  $\text{nameIR}$  is equal to "size".
  - b. Result in  $D \ n_{\text{size}}$ .
4. Let  $\text{value}$  be
  - the result of local compile-time evaluation of  $\text{typedExpressionIR}_{\text{base}}$ , under cursor  $p$  and context  $TC$ .
5. If let  $\text{structValue}$  be  $\text{value}$ :
  - a. Let **STRUCT**  $\_ \{ ( \text{value}_{\text{field}} \text{nameIR}_{\text{field}} ; )^* \}$  be  $\text{structValue}$ .
  - b. Let  $\text{value}''$  be ! the value associated to  $\text{nameIR}$  in  $( \text{nameIR}_{\text{field}}, \text{value}_{\text{field}} )^*$ .
  - c. Result in  $\text{value}''$ .
6. Else if let  $\text{headerValue}$  be  $\text{value}$ :
  - a. Let **HEADER**  $\_ \{ \_ ; ( \text{value}_{\text{field}} \text{nameIR}_{\text{field}} ; )^* \}$  be  $\text{headerValue}$ .
  - b. Let  $\text{value}''$  be ! the value associated to  $\text{nameIR}$  in  $( \text{nameIR}_{\text{field}}, \text{value}_{\text{field}} )^*$ .
  - c. Result in  $\text{value}''$ .
7. Else if let  $\text{headerUnionValue}$  be  $\text{value}$ :
  - a. Let **HEADER\_UNION**  $\_ \{ ( \text{value}_{\text{field}} \text{nameIR}_{\text{field}} ; )^* \}$  be  $\text{headerUnionValue}$ .
  - b. Let  $\text{value}''$  be ! the value associated to  $\text{nameIR}$  in  $( \text{nameIR}_{\text{field}}, \text{value}_{\text{field}} )^*$ .
  - c. Result in  $\text{value}''$ .

## 14.13.3. Compile-time evaluation

### Accessing an enum member

Compile-time evaluation of  $\text{TYPE } \text{prefixedNameIR} . \text{nameIR}$  annotated with  $\text{expressionNoteIR}$ , under cursor  $p$ , context  $IC$ , and store  $STO$ :

1. Let  $\text{typeDefIR}'$  be ! the type definition of  $\text{prefixedNameIR}$  from the  $p$  layer of  $IC$ .
2. If let **ENUM**  $\text{typed} \{ \_ \}$  be  $\text{typeDefIR}'$ :
  - a. Result in store  $STO$  and  $\text{typed} . \text{nameIR}$ .
3. Else if let **ENUM**  $\text{typed} < \_ > \{ ( \text{id}_{\text{member}} = \text{value}_{\text{member}} ; )^* \}$  be  $\text{typeDefIR}'$ :

- a. Let **value'** be ! the value associated to **nameIR** in ( **id<sub>member</sub>**, **value<sub>member</sub>** )<sup>\*</sup>.
- b. Result in store **STO** and **typed . nameIR . value'**.

### Accessing an aggregate member

Compile-time evaluation of **typedExpressionIR<sub>base</sub> . nameIR** annotated with **expressionNotelR**, under cursor **p**, context **IC**, and store **STO**:

1. Let **typeIR<sub>base</sub>** be the type of **typedExpressionIR<sub>base</sub>**.
2. Let **typeIR** be **typeIR<sub>base</sub>** with **typedefs** unrolled.
3. If let **\_ [ n<sub>size</sub> ]** be **typeIR**:
  - a. Check that **nameIR** is equal to "size".
  - b. Result in store **STO** and **D n<sub>size</sub>**.
4. Let store **STO<sub>1</sub>** and **value** be
  - the result of compile-time evaluation of **typedExpressionIR<sub>base</sub>**, under cursor **p**, context **IC**, and store **STO**.
5. If let **structValue** be **value**:
  - a. Let **STRUCT \_ { ( value<sub>field</sub> id<sub>field</sub> ; )<sup>\*</sup> }** be **structValue**.
  - b. Let **value"** be ! the value associated to **nameIR** in ( **id<sub>field</sub>**, **value<sub>field</sub>** )<sup>\*</sup>.
  - c. Result in store **STO<sub>1</sub>** and **value"**.
6. Else if let **headerValue** be **value**:
  - a. Let **HEADER \_ { \_ ; ( value<sub>field</sub> id<sub>field</sub> ; )<sup>\*</sup> }** be **headerValue**.
  - b. Let **value"** be ! the value associated to **nameIR** in ( **id<sub>field</sub>**, **value<sub>field</sub>** )<sup>\*</sup>.
  - c. Result in store **STO<sub>1</sub>** and **value"**.
7. Else if let **headerUnionValue** be **value**:
  - a. Let **HEADER\_UNION \_ { ( value<sub>field</sub> id<sub>field</sub> ; )<sup>\*</sup> }** be **headerUnionValue**.
  - b. Let **value"** be ! the value associated to **nameIR** in ( **id<sub>field</sub>**, **value<sub>field</sub>** )<sup>\*</sup>.
  - c. Result in store **STO<sub>1</sub>** and **value"**.

## 14.13.4. Runtime evaluation

### Accessing an enum member

Evaluating **TYPE prefixedNameIR . nameIR** annotated with **expressionNotelR**, under cursor **p**, context **EC**, and state **ARCH**:

1. Let **typeDefIR'** be ! \$find\_typeDef\_e(p, EC, prefixedNameIR).
2. If let **ENUM typed { \_<sup>\*</sup> }** be **typeDefIR'**:
  - a. Let **expressionResult** be **typed . nameIR**.
  - b. Result in context **EC**, state **ARCH** and **expressionResult**.
3. Else if let **ENUM typed < \_ > { ( nameIR<sub>member</sub> = value<sub>member</sub> ; )<sup>\*</sup> }** be **typeDefIR'**:

- a. Let *value*' be ! the value associated to *nameIR* in ( *nameIR*<sub>member</sub>, *value*<sub>member</sub> )<sup>\*</sup>.
- b. Let *expressionResult* be *typed* . *nameIR* . *value*'.
- c. Result in context *EC*, state *ARCH* and *expressionResult*.

## Accessing an aggregate member

Evaluating *typedExpressionIR*<sub>base</sub> . *nameIR* annotated with *expressionNotIR*, under cursor *p*, context *EC*, and state *ARCH*:

1. Let context *EC*<sub>1</sub>, state *ARCH*<sub>1</sub> and *expressionResult* be
  - the result of evaluating *typedExpressionIR*<sub>base</sub>, under cursor *p*, context *EC*, and state *ARCH*.
2. If let *abortResult* be *expressionResult*:
  - a. Result in context *EC*<sub>1</sub>, state *ARCH*<sub>1</sub> and *abortResult*.
3. Else:
  - a. Let *value* be *expressionResult*.
  - b. If let *headerStackValue*<sub>base</sub> be *value*:
    - i. Let *HEADER\_STACK* [ *\_* \* ( *\_* ; *n*<sub>size</sub> ) ] be *headerStackValue*<sub>base</sub>.
    - ii. If *nameIR* is equal to "size":
      - A. Let *expressionResult*' be *D* *n*<sub>size</sub>.
      - B. Result in context *EC*<sub>1</sub>, state *ARCH*<sub>1</sub> and *expressionResult*'.
    - iii. Else if *nameIR* is equal to "last":
      - A. Let *b*<sub>out\_of\_bounds</sub> be *\_* is less than 1 or *\_* is greater than *n*<sub>size</sub>.
      - B. If *b*<sub>out\_of\_bounds</sub>:
        - I. Let *rejectTransitionResult* be REJECT ERROR . "StackOutOfBounds".
        - II. Result in context *EC*<sub>1</sub>, state *ARCH*<sub>1</sub> and *rejectTransitionResult*.
      - C. Else:
        - I. Let *int* be *\_* - 1.
        - II. Check that *int* has type *nat*.
        - III. Let *n*<sub>idx\_last</sub> be *int*.
        - IV. Let *value*<sub>last</sub> be *\_* \* [*n*<sub>idx\_last</sub>].
        - V. Let *expressionResult*' be *value*<sub>last</sub>.
        - VI. Result in context *EC*<sub>1</sub>, state *ARCH*<sub>1</sub> and *expressionResult*'.
    - iv. Else if *nameIR* is equal to "lastIndex":
      - A. Let *nat* be *max*( [ *\_*, 1 ] ).
      - B. Let *int* be *nat* - 1.
      - C. Check that *int* has type *nat*.
      - D. Let *n*<sub>idx\_last</sub> be *int*.
      - E. Let *value*<sub>idx\_last</sub> be 32 W *n*<sub>idx\_last</sub>.
      - F. Let *expressionResult*' be *value*<sub>idx\_last</sub>.

- G. Result in context  $EC_1$ , state  $ARCH_1$  and  $expressionResult'$ .
- c. Else if let  $structValue_{base}$  be value:
  - i. Let  $STRUCT\_ \{ (value_{field} id_{field} ; )^* \}$  be  $structValue_{base}$ .
  - ii. Let  $value_{member}$  be ! the value associated to  $nameIR$  in  $( id_{field}, value_{field} )^*$ .
  - iii. Let  $expressionResult'$  be  $value_{member}$ .
  - iv. Result in context  $EC_1$ , state  $ARCH_1$  and  $expressionResult'$ .
- d. Else if let  $headerValue_{base}$  be value:
  - i. Let  $HEADER\_ \{ \_ ; (value_{field} id_{field} ; )^* \}$  be  $headerValue_{base}$ .
  - ii. Let  $value_{member}$  be ! the value associated to  $nameIR$  in  $( id_{field}, value_{field} )^*$ .
  - iii. Let  $expressionResult'$  be  $value_{member}$ .
  - iv. Result in context  $EC_1$ , state  $ARCH_1$  and  $expressionResult'$ .
- e. Else if let  $headerUnionValue_{base}$  be value:
  - i. Let  $HEADER\_UNION\_ \{ (value_{field} id_{field} ; )^* \}$  be  $headerUnionValue_{base}$ .
  - ii. Let  $value_{member}$  be ! the value associated to  $nameIR$  in  $( id_{field}, value_{field} )^*$ .
  - iii. Let  $expressionResult'$  be  $value_{member}$ .
  - iv. Result in context  $EC_1$ , state  $ARCH_1$  and  $expressionResult'$ .
- 4. Let context  $EC_1$ , state  $ARCH_1$  and  $expressionResult$  be
  - the result of evaluating  $typedExpressionIR_{base}$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ .
- 5. If let  $value$  be  $expressionResult$ :
  - a. Check that  $value$  has type  $tableMetadataStructValue$ .
  - b. Let  $tableMetadataStructValue_{base}$  be  $value$ .
  - c. Let  $TABLE\_STRUCT\_ \{ HIT boolValue_{hit} ; MISS \_ ; ACTION\_RUN \_ ; \}$  be  $tableMetadataStructValue_{base}$ .
  - d. If  $nameIR$  is equal to "hit":
    - i. Let  $expressionResult'$  be  $boolValue_{hit}$ .
    - ii. Result in context  $EC_1$ , state  $ARCH_1$  and  $expressionResult'$ .
  - e. Else if  $nameIR$  is equal to "miss":
    - i. Let  $expressionResult'$  be  $\_$ .
    - ii. Result in context  $EC_1$ , state  $ARCH_1$  and  $expressionResult'$ .
  - f. Else if  $nameIR$  is equal to "action\_run":
    - i. Let  $expressionResult'$  be  $\_$ .
    - ii. Result in context  $EC_1$ , state  $ARCH_1$  and  $expressionResult'$ .

## 14.14. Index access expressions

An index access expression accesses an element of a tuple or a header stack.

```
indexAccessExpression
: expression `[ expression ]
;
```

### 14.14.1. Type checking

After type checking, an index access expression is represented as:

```
indexAccessExpressionIR
: typedExpressionIR `[ typedExpressionIR ]
;
```

Typing  $\text{expression}_{\text{base}} [\text{expression}_{\text{index}}]$ , under cursor  $p$  and context  $TC$ :

1. Let  $\text{typedExpressionIR}_{\text{base}}$  be
  - the result of typing  $\text{expression}_{\text{base}}$ , under cursor  $p$  and context  $TC$ .
2. Let  $\text{typedExpressionIR}_{\text{index}}$  be
  - the result of typing  $\text{expression}_{\text{index}}$ , under cursor  $p$  and context  $TC$ .
3. Let  $\text{typeIR}_{\text{base}}$  be the type of  $\text{typedExpressionIR}_{\text{base}}$ .
4. Let  $\text{ctk}_{\text{base}}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{\text{base}}$ .
5. Let  $\text{typeIR}_{\text{index}}$  be the type of  $\text{typedExpressionIR}_{\text{index}}$ .
6. Let  $\text{ctk}_{\text{index}}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{\text{index}}$ .
7. Let  $\text{typedExpressionIR}_{\text{index\_reduced}}$  be ! the result of reducing serializable enums in  $\text{typedExpressionIR}_{\text{index}}$  until  $\$compat\_array\_index$  is satisfied.
8. Let  $\text{typeIR}_{\text{base}}$  be  $\text{typeIR}_{\text{base}}$  with typedefs unrolled.
9. If let  $\text{TUPLE} < \text{typeIR}_e^* >$  be  $\text{typeIR}$ :
  - a. Check that  $\text{ctk}_{\text{index}}$  is LCTK.
  - b. Let  $\text{value}$  be
    - the result of local compile-time evaluation of  $\text{typedExpressionIR}_{\text{index\_reduced}}$ , under cursor  $p$  and context  $TC$ .
  - c. Check that  $\text{value}$  has type  $\text{integerValue}$ .
  - d. Let  $\text{integerValue}_{\text{index}}$  be  $\text{value}$ .
  - e. Let  $n_{\text{index}}$  be ! the natural number representation of  $\text{integerValue}_{\text{index}}$ .
  - f. Check that  $n_{\text{index}}$  is less than the length of  $\text{typeIR}_e^*$ .
  - g. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}_e^*[n_{\text{index}}]$  and compile-time known-ness  $\text{ctk}_{\text{base}}$ .
  - h. Result in  $\text{typedExpressionIR}_{\text{base}} [\text{typedExpressionIR}_{\text{index\_reduced}}]$  annotated with  $\text{expressionNoteIR}$ .
10. Else if let  $\text{typeIR}' [n_{\text{size}}]$  be  $\text{typeIR}$ :
  - a. If  $\text{ctk}_{\text{index}}$  is LCTK:
    - i. Let  $\text{value}$  be
      - the result of local compile-time evaluation of  $\text{typedExpressionIR}_{\text{index\_reduced}}$ , under cursor  $p$  and context  $TC$ .
    - ii. Check that  $\text{value}$  has type  $\text{integerValue}$ .
    - iii. Let  $\text{integerValue}_{\text{index}}$  be  $\text{value}$ .
    - iv. Let  $n_{\text{index}}$  be ! the natural number representation of  $\text{integerValue}_{\text{index}}$ .
    - v. Check that  $n_{\text{index}}$  is less than  $n_{\text{size}}$ .

- vi. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}'$  and compile-time known-ness  $\text{ctk}_{\text{base}}$ .
  - vii. Result in  $\text{typedExpressionIR}_{\text{base}} [ \text{typedExpressionIR}_{\text{index\_reduced}} ]$  annotated with  $\text{expressionNoteIR}$ .
- b. Else:
- i. Let  $\text{ctk}$  be the join of  $\text{ctk}_{\text{base}}$  and  $\text{ctk}_{\text{index}}$ .
  - ii. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}'$  and compile-time known-ness  $\text{ctk}$ .
  - iii. Result in  $\text{typedExpressionIR}_{\text{base}} [ \text{typedExpressionIR}_{\text{index\_reduced}} ]$  annotated with  $\text{expressionNoteIR}$ .

### 14.14.2. Local compile-time evaluation

Local compile-time evaluation of  $\text{typedExpressionIR}_{\text{base}} [ \text{typedExpressionIR}_{\text{index}} ]$  annotated with  $\text{expressionNoteIR}$ , under cursor  $p$  and context  $\text{TC}$ :

1. Let  $\text{value}_{\text{base}}$  be
  - the result of local compile-time evaluation of  $\text{typedExpressionIR}_{\text{base}}$ , under cursor  $p$  and context  $\text{TC}$ .
2. Let  $\text{value}$  be
  - the result of local compile-time evaluation of  $\text{typedExpressionIR}_{\text{index}}$ , under cursor  $p$  and context  $\text{TC}$ .
3. Check that  $\text{value}$  has type  $\text{integerValue}$ .
4. Let  $\text{integerValue}_{\text{index}}$  be  $\text{value}$ .
5. If let  $\text{TUPLE} ( \text{value}_e^* )$  be  $\text{value}_{\text{base}}$ :
  - a. Let  $n_{\text{index}}$  be ! the natural number representation of  $\text{integerValue}_{\text{index}}$ .
  - b. Check that  $n_{\text{index}}$  is less than the length of  $\text{value}_e^*$ .
  - c. Let  $\text{value}'$  be  $\text{value}_e^*[n_{\text{index}}]$ .
  - d. Result in  $\text{value}'$ .
6. Else if let  $\text{HEADER\_STACK} [ \text{value}_e^* ( \_ ; \_ ) ]$  be  $\text{value}_{\text{base}}$ :
  - a. Let  $n_{\text{index}}$  be ! the natural number representation of  $\text{integerValue}_{\text{index}}$ .
  - b. Check that  $n_{\text{index}}$  is less than the length of  $\text{value}_e^*$ .
  - c. Let  $\text{value}'$  be  $\text{value}_e^*[n_{\text{index}}]$ .
  - d. Result in  $\text{value}'$ .

### 14.14.3. Compile-time evaluation

Compile-time evaluation of  $\text{typedExpressionIR}_{\text{base}} [ \text{typedExpressionIR}_{\text{index}} ]$  annotated with  $\text{expressionNoteIR}$ , under cursor  $p$ , context  $\text{IC}$ , and store  $\text{STO}$ :

1. Let store  $\text{STO}_1$  and  $\text{value}_{\text{base}}$  be
  - the result of compile-time evaluation of  $\text{typedExpressionIR}_{\text{base}}$ , under cursor  $p$ , context  $\text{IC}$ , and store  $\text{STO}$ .
2. Let store  $\text{STO}_2$  and  $\text{value}$  be
  - the result of compile-time evaluation of  $\text{typedExpressionIR}_{\text{index}}$ , under cursor  $p$ , context  $\text{IC}$ , and

store  $STO_1$ .

3. Check that  $value$  has type  $integerValue$ .
4. Let  $integerValue_{index}$  be  $value$ .
5. If let  $TUPLE ( value_e^* )$  be  $value_{base}$ :
  - a. Let  $n_{index}$  be ! the natural number representation of  $integerValue_{index}$ .
  - b. Check that  $n_{index}$  is less than the length of  $value_e^*$ .
  - c. Let  $value'$  be  $value_e^*[n_{index}]$ .
  - d. Result in store  $STO_2$  and  $value'$ .
6. Else if let  $HEADER\_STACK [ value_e^* ( \_ ; \_ ) ]$  be  $value_{base}$ :
  - a. Let  $n_{index}$  be ! the natural number representation of  $integerValue_{index}$ .
  - b. Check that  $n_{index}$  is less than the length of  $value_e^*$ .
  - c. Let  $value'$  be  $value_e^*[n_{index}]$ .
  - d. Result in store  $STO_2$  and  $value'$ .

#### 14.14.4. Runtime evaluation

Evaluating  $typedExpressionIR_{base} [ typedExpressionIR_{index} ]$  annotated with  $expressionNodeIR$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ :

1. Let context  $EC_1$ , state  $ARCH_1$  and  $expressionListResult$  be
  - the result of evaluating  $[ typedExpressionIR_{base}, typedExpressionIR_{index} ]$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ .
2. If let  $abortResult$  be  $expressionListResult$ :
  - a. Result in context  $EC_1$ , state  $ARCH_1$  and  $abortResult$ .
3. Else:
  - a. Let  $value^*$  be  $expressionListResult$ .
  - b. Check that  $value^*$  is a list of length 2.
  - c. Let  $[ value', value ]$  be  $value^*$ .
  - d. If let  $tupleValue_{base}$  be  $value'$ :
    - i. Check that  $value$  has type  $integerValue$ .
    - ii. Let  $integerValue_{index}$  be  $value$ .
    - iii. Let  $TUPLE ( value_{elem}^* )$  be  $tupleValue_{base}$ .
    - iv. Let  $n_{index}$  be ! the natural number representation of  $integerValue_{index}$ .
    - v. Let  $expressionResult$  be  $value_{elem}^*[n_{index}]$ .
    - vi. Result in context  $EC_1$ , state  $ARCH_1$  and  $expressionResult$ .
  - e. Else if let  $headerStackValue_{base}$  be  $value'$ :
    - i. Check that  $value$  has type  $integerValue$ .
    - ii. Let  $integerValue_{index}$  be  $value$ .
    - iii. Let  $HEADER\_STACK [ value_{elem}^* ( \_ ; n_{size} ) ]$  be  $headerStackValue_{base}$ .

- iv. Let  $n_{\text{index}}$  be ! the natural number representation of  $\text{integerValue}_{\text{index}}$ .
- v. Let  $\text{int}$  be  $n_{\text{index}}$  if  $n_{\text{index}}$  is less than  $n_{\text{size}}$  otherwise  $n_{\text{size}} - 1$ .
- vi. Check that  $\text{int}$  has type  $\text{nat}$ .
- vii. Let  $n_{\text{idx}}$  be  $\text{int}$ .
- viii. Let  $\text{expressionResult}$  be  $\text{value}_{\text{elem}}^*[n_{\text{idx}}]$ .
- ix. Result in context  $\text{EC}_1$ , state  $\text{ARCH}_1$  and  $\text{expressionResult}$ .

## 14.15. Bitslice access expressions

A bitslice access expression is used to access a contiguous range of bits within a numeric value. The syntax for a bitslice access expression is as follows:

```
sliceAccessExpression
: expression `[ expression : expression ]
;
```

### 14.15.1. Type checking

After type checking, a bitslice access expression is represented as:

```
sliceAccessExpressionIR
: typedExpressionIR `[ typedExpressionIR : typedExpressionIR ]
;
```

Typing  $\text{expression}_{\text{base}} [ \text{expression}_{\text{hi}} : \text{expression}_{\text{lo}} ]$ , under cursor  $p$  and context  $\text{TC}$ :

1. Let  $\text{typedExpressionIR}_{\text{base}}$  be
  - the result of typing  $\text{expression}_{\text{base}}$ , under cursor  $p$  and context  $\text{TC}$ .
2. Let  $\text{typedExpressionIR}_{\text{hi}}$  be
  - the result of typing  $\text{expression}_{\text{hi}}$ , under cursor  $p$  and context  $\text{TC}$ .
3. Let  $\text{typedExpressionIR}_{\text{lo}}$  be
  - the result of typing  $\text{expression}_{\text{lo}}$ , under cursor  $p$  and context  $\text{TC}$ .
4. Let  $\text{typedExpressionIR}_{\text{base\_reduced}}$  be ! the result of reducing serializable enums in  $\text{typedExpressionIR}_{\text{base}}$  until  $\$compat\_bitslice\_base$  is satisfied.
5. Let  $\text{typeIR}_{\text{base\_reduced}}$  be the type of  $\text{typedExpressionIR}_{\text{base\_reduced}}$ .
6. Let  $\text{ctk}_{\text{base\_reduced}}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{\text{base\_reduced}}$ .
7. Let  $\text{typedExpressionIR}_{\text{hi\_reduced}}$  be ! the result of reducing serializable enums in  $\text{typedExpressionIR}_{\text{hi}}$  until  $\$compat\_bitslice\_index$  is satisfied.
8. Let  $\text{typedExpressionIR}_{\text{lo\_reduced}}$  be ! the result of reducing serializable enums in  $\text{typedExpressionIR}_{\text{lo}}$  until  $\$compat\_bitslice\_index$  is satisfied.
9. Let  $\text{typeIR}_{\text{hi\_reduced}}$  be the type of  $\text{typedExpressionIR}_{\text{hi\_reduced}}$ .
10. Let  $\text{ctk}_{\text{hi\_reduced}}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{\text{hi\_reduced}}$ .
11. Let  $\text{typeIR}_{\text{lo\_reduced}}$  be the type of  $\text{typedExpressionIR}_{\text{lo\_reduced}}$ .



12. Let  $\text{ctk}_{\text{lo\_reduced}}$  be the compile-time known-ness of  $\text{typedExpressionIR}_{\text{lo\_reduced}}$ .
13. Check that  $\text{ctk}_{\text{hi\_reduced}}$  is LCTK.
14. Let  $\text{value}$  be
  - the result of local compile-time evaluation of  $\text{typedExpressionIR}_{\text{hi\_reduced}}$ , under cursor  $p$  and context  $\text{TC}$ .
15. Check that  $\text{value}$  has type  $\text{integerValue}$ .
16. Let  $\text{integerValue}_{\text{hi}}$  be  $\text{value}$ .
17. Let  $n_{\text{hi}}$  be ! the natural number representation of  $\text{integerValue}_{\text{hi}}$ .
18. Check that  $\text{ctk}_{\text{lo\_reduced}}$  is LCTK.
19. Let  $\text{value}'$  be
  - the result of local compile-time evaluation of  $\text{typedExpressionIR}_{\text{lo\_reduced}}$ , under cursor  $p$  and context  $\text{TC}$ .
20. Check that  $\text{value}'$  has type  $\text{integerValue}$ .
21. Let  $\text{integerValue}_{\text{lo}}$  be  $\text{value}'$ .
22. Let  $n_{\text{lo}}$  be ! the natural number representation of  $\text{integerValue}_{\text{lo}}$ .
23. Check that  $\text{typeIR}_{\text{base\_reduced}} [ n_{\text{lo}} : n_{\text{hi}} ]$  is a valid bitslice.
24. Let  $\text{int}$  be  $n_{\text{hi}} - n_{\text{lo}} + 1$ .
25. Check that  $\text{int}$  has type  $\text{nat}$ .
26. Let  $n_{\text{slice}}$  be  $\text{int}$ .
27. Let  $\text{typeIR}$  be  $\text{BIT} < n_{\text{slice}} >$ .
28. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}$  and compile-time known-ness  $\text{ctk}_{\text{base\_reduced}}$ .
29. Result in  $\text{typedExpressionIR}_{\text{base}} [ \text{typedExpressionIR}_{\text{hi\_reduced}} : \text{typedExpressionIR}_{\text{lo\_reduced}} ]$  annotated with  $\text{expressionNoteIR}$ .

## 14.15.2. Local compile-time evaluation

Local compile-time evaluation of  $\text{typedExpressionIR}_{\text{base}} [ \text{typedExpressionIR}_{\text{hi}} : \text{typedExpressionIR}_{\text{lo}} ]$  annotated with  $\text{expressionNoteIR}$ , under cursor  $p$  and context  $\text{TC}$ :

1. Let  $\text{value}_{\text{base}}$  be
  - the result of local compile-time evaluation of  $\text{typedExpressionIR}_{\text{base}}$ , under cursor  $p$  and context  $\text{TC}$ .
2. Let  $\text{value}_{\text{hi}}$  be
  - the result of local compile-time evaluation of  $\text{typedExpressionIR}_{\text{hi}}$ , under cursor  $p$  and context  $\text{TC}$ .
3. Let  $\text{value}_{\text{lo}}$  be
  - the result of local compile-time evaluation of  $\text{typedExpressionIR}_{\text{lo}}$ , under cursor  $p$  and context  $\text{TC}$ .
4. Result in  $\text{value}_{\text{base}} [ \text{value}_{\text{hi}} : \text{value}_{\text{lo}} ]$ .

## 14.15.3. Compile-time evaluation

Compile-time evaluation of  $\text{typedExpressionIR}_{\text{base}} [ \text{typedExpressionIR}_{\text{hi}} : \text{typedExpressionIR}_{\text{lo}} ]$  annotated with  $\text{expressionNodeIR}$ , under cursor  $p$ , context  $IC$ , and store  $STO$ :

1. Let store  $STO_1$  and  $\text{value}_{\text{base}}$  be
  - the result of compile-time evaluation of  $\text{typedExpressionIR}_{\text{base}}$ , under cursor  $p$ , context  $IC$ , and store  $STO$ .
2. Let store  $STO_2$  and  $\text{value}_{\text{hi}}$  be
  - the result of compile-time evaluation of  $\text{typedExpressionIR}_{\text{hi}}$ , under cursor  $p$ , context  $IC$ , and store  $STO_1$ .
3. Let store  $STO_3$  and  $\text{value}_{\text{lo}}$  be
  - the result of compile-time evaluation of  $\text{typedExpressionIR}_{\text{lo}}$ , under cursor  $p$ , context  $IC$ , and store  $STO_2$ .
4. Result in store  $STO_3$  and  $\text{value}_{\text{base}} [ \text{value}_{\text{hi}} : \text{value}_{\text{lo}} ]$ .

#### 14.15.4. Runtime evaluation

Evaluating  $\text{typedExpressionIR}_{\text{base}} [ \text{typedExpressionIR}_{\text{hi}} : \text{typedExpressionIR}_{\text{lo}} ]$  annotated with  $\text{expressionNodeIR}$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ :

1. Let context  $EC_1$ , state  $ARCH_1$  and  $\text{expressionListResult}$  be
  - the result of evaluating  $[ \text{typedExpressionIR}_{\text{base}}, \text{typedExpressionIR}_{\text{hi}}, \text{typedExpressionIR}_{\text{lo}} ]$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ .
2. If let  $\text{abortResult}$  be  $\text{expressionListResult}$ :
  - a. Result in context  $EC_1$ , state  $ARCH_1$  and  $\text{abortResult}$ .
3. Else:
  - a. Let  $\text{value}^*$  be  $\text{expressionListResult}$ .
  - b. Check that  $\text{value}^*$  is a list of length 3.
  - c. Let  $[ \text{value}_{\text{base}}, \text{value}_{\text{hi}}, \text{value}_{\text{lo}} ]$  be  $\text{value}^*$ .
  - d. Let  $\text{value}'$  be  $\text{value}_{\text{base}} [ \text{value}_{\text{hi}} : \text{value}_{\text{lo}} ]$ .
  - e. Let  $\text{expressionResult}$  be  $\text{value}'$ .
  - f. Result in context  $EC_1$ , state  $ARCH_1$  and  $\text{expressionResult}$ .

### 14.16. Call expressions

Call expressions are used to invoke callables or constructors.

```
callExpression
: callTarget `( argumentList )
| callableTarget `< realTypeArgumentList > `( argumentList )
;

callTarget
: callableTarget
| constructorTarget
;
```

```

callableTarget = expression
constructorTarget = namedType

```

Details of how calls are resolved and evaluated are described in [Chapter 18](#).

### 14.16.1. Type checking

After type checking, call expressions are represented as:

```

callExpressionIR
: constructorTargetIR `( argumentListIR )
| callableTargetIR `< typeArgumentListIR > `( argumentListIR )
;

callableTargetIR
: referenceExpressionIR
| typedExpressionIR . nameIR
| TYPE prefixedNameIR . nameIR
| `( callableTargetIR )
;

constructorTargetIR
: prefixedNameIR `< typeArgumentListIR >
;

```

#### Calling a callable

Typing `callExpression`, under cursor `p` and context `TC`:

1. If let `callTarget ( argumentList )` be `callExpression`:
  - a. Check that `callTarget` has type `callableTarget`.
  - b. Let `callableTarget` be `callTarget`.
  - c. Let typed callable target `callableTargetIR` be
    - the result of [typing](#) `callableTarget` as a callable target, under cursor `p` and context `TC`.
  - d. Let `argumentIR*` be
    - the result of [typing](#) `argumentList`, under cursor `p` and context `TC`.
  - e. Let callable type `callableTypeIR` with fresh type variables `typeIdinfer*`, defaults `iddefault*` and optionals `idoptional*` be
    - the result of [finding type of callable call](#) `callableTargetIR < · > ( argumentIR* )`, under cursor `p` and context `TC`.
  - f. Let return type `typeIRret` with inferred type arguments `typeArgumentIRinferred*` and casted argument list `argumentIRcast*` be
    - the result of [typing invocation](#) `callableTypeIR < · > ( argumentIR* )` with omitted type arguments `typeIdinfer*`, defaults `iddefault*` and optionals `idoptional*`, under cursor `p` and context `TC`.
  - g. Check that `typeIRret` is not equal to `VOID`.
  - h. Let `ctk` be [compile-time known-ness of](#) `callableTypeIR`.
  - i. If `callableTypeIR` is a `static_assert` call:
    - i. Let `callExpressionIR` be `callableTargetIR < typeArgumentIRinferred* > ( argumentIRcast* )`.

- ii. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}_{\text{ret}}$  and compile-time known-ness  $\text{ctk}$ .
  - iii. Let  $\text{value}$  be
    - the result of local compile-time evaluation of  $\text{callExpressionIR}$  annotated with  $\text{expressionNoteIR}$ , under cursor  $p$  and context  $\text{TC}$ .
  - iv. Check that  $\text{value}$  is equal to  $\text{'B true'}$ .
  - v. Let  $\text{literalExpressionIR}$  be  $\text{TRUE}$ .
  - vi. Result in  $\text{literalExpressionIR}$  annotated with  $\text{expressionNoteIR}$ .
  - j. Else:
    - i. Let  $\text{callExpressionIR}$  be  $\text{callableTargetIR} < \text{typeArgumentIR}_{\text{inferred}}^* > ( \text{argumentIR}_{\text{cast}}^* )$ .
    - ii. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}_{\text{ret}}$  and compile-time known-ness  $\text{ctk}$ .
    - iii. Result in  $\text{callExpressionIR}$  annotated with  $\text{expressionNoteIR}$ .
2. Else:
- a. Let  $\text{callableTarget} < \text{realTypeArgumentList} > ( \text{argumentList} )$  be  $\text{callExpression}$ .
  - b. Let typed callable target  $\text{callableTargetIR}$  be
    - the result of typing  $\text{callableTarget}$  as a callable target, under cursor  $p$  and context  $\text{TC}$ .
  - c. Let  $\text{realTypeArgument}^*$  be the list of real type arguments in  $\text{realTypeArgumentList}$ .
  - d. Let  $\text{typeArgumentIR}^*$  and a set of fresh type variables  $\text{typeID}_{\text{impl}}^*$  be
    - the result of typing  $\text{realTypeArgument}^*$ , under cursor  $p$  and context  $\text{TC}$ .
  - e. Let  $\text{argumentIR}^*$  be
    - the result of typing  $\text{argumentList}$ , under cursor  $p$  and context  $\text{TC}$ .
  - f. Let callable type  $\text{callableTypeIR}$  with fresh type variables  $\text{typeID}_{\text{inserted}}^*$ , defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$  be
    - the result of finding type of callable call  $\text{callableTargetIR} < \text{typeArgumentIR}^* > ( \text{argumentIR}^* )$ , under cursor  $p$  and context  $\text{TC}$ .
  - g. Let  $\text{typeID}_{\text{infer}}^*$  be  $\text{typeID}_{\text{impl}}^*$  concatenated with  $\text{typeID}_{\text{inserted}}^*$ .
  - h. Let return type  $\text{typeIR}_{\text{ret}}$  with inferred type arguments  $\text{typeArgumentIR}_{\text{inferred}}^*$  and casted argument list  $\text{argumentIR}_{\text{cast}}^*$  be
    - the result of typing invocation  $\text{callableTypeIR} < \text{typeArgumentIR}^* > ( \text{argumentIR}^* )$  with omitted type arguments  $\text{typeID}_{\text{infer}}^*$ , defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$ , under cursor  $p$  and context  $\text{TC}$ .
  - i. Check that  $\text{typeIR}_{\text{ret}}$  is not equal to  $\text{VOID}$ .
  - j. Let  $\text{ctk}$  be compile-time known-ness of  $\text{callableTypeIR}$ .
  - k. Let  $\text{callExpressionIR}$  be  $\text{callableTargetIR} < \text{typeArgumentIR}_{\text{inferred}}^* > ( \text{argumentIR}_{\text{cast}}^* )$ .
  - l. Let  $\text{expressionNoteIR}$  be a pair of type  $\text{typeIR}_{\text{ret}}$  and compile-time known-ness  $\text{ctk}$ .
  - m. Result in  $\text{callExpressionIR}$  annotated with  $\text{expressionNoteIR}$ .

## Calling a constructor

Typing  $\text{callTarget} ( \text{argumentList} )$ , under cursor  $p$  and context  $\text{TC}$ :

1. If let  $\text{prefixedTypeName}$  be  $\text{callTarget}$ :

- a. Let  $\text{argumentIR}^*$  be
    - the result of **typing**  $\text{argumentList}$ , under cursor  $p$  and context  $TC$ .
  - b. Let  $\text{prefixedNameIR}$  be the **prefixed name of**  $\text{prefixedTypeName}$ .
  - c. Let  $\text{constructorTargetIR}$  be  $\text{prefixedNameIR} < \cdot >$ .
  - d. Let  $\text{constructorTypeIR}$  with fresh type variables  $\text{typeId}_{\text{impl}}^*$ , defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$  be
    - the result of **finding type of constructor call**  $\text{constructorTargetIR} ( \text{argumentIR}^* )$ , under cursor  $p$  and context  $TC$ .
  - e. Let constructed type  $\text{typeIR}_{\text{Object}}^{\text{cast}}$  with inferred  $\text{typeArgumentIR}_{\text{inferred}}^*$  and cast-inserted  $\text{argumentIR}^*$  be
    - the result of **typing instantiation**  $\text{constructorTypeIR} < \cdot > ( \text{argumentIR}^* )$  with omitted type arguments  $\text{typeId}_{\text{impl}}^*$ , defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$ , under cursor  $p$ , context  $TC$ , and ANON instantiation site context.
  - f. Check that  $\text{typeIR}_{\text{Object}}$  is an **extern object type without abstract methods**.
  - g. Let  $\text{callExpressionIR}$  be  $\text{prefixedNameIR} < \text{typeArgumentIR}_{\text{inferred}}^* > ( \text{argumentIR}_{\text{cast}}^* )$ .
  - h. Let  $\text{expressionNoteIR}$  be a **pair of type**  $\text{typeIR}_{\text{Object}}$  **and compile-time known-ness**  $CTK$ .
  - i. Result in  $\text{callExpressionIR}$  **annotated with**  $\text{expressionNoteIR}$ .
2. Else if let  $\text{prefixedTypeName} < \text{typeArgumentList} >$  be  $\text{callTarget}$ :
    - a. Let  $\text{typeArgumentIR}^*$  and a set of fresh type variables  $\text{typeId}_{\text{impl}}^*$  be
      - the result of **typing**  $\text{typeArgumentList}$ , under cursor  $p$  and context  $TC$ .
    - b. Let  $\text{argumentIR}^*$  be
      - the result of **typing**  $\text{argumentList}$ , under cursor  $p$  and context  $TC$ .
    - c. Let  $\text{prefixedNameIR}$  be the **prefixed name of**  $\text{prefixedTypeName}$ .
    - d. Let  $\text{constructorTargetIR}$  be  $\text{prefixedNameIR} < \text{typeArgumentIR}^* >$ .
    - e. Let  $\text{constructorTypeIR}$  with fresh type variables  $\text{typeId}_{\text{inserted}}^*$ , defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$  be
      - the result of **finding type of constructor call**  $\text{constructorTargetIR} ( \text{argumentIR}^* )$ , under cursor  $p$  and context  $TC$ .
    - f. Let  $\text{typeId}_{\text{infer}}^*$  be  $\text{typeId}_{\text{impl}}^*$  concatenated with  $\text{typeId}_{\text{inserted}}^*$ .
    - g. Let constructed type  $\text{typeIR}_{\text{Object}}^{\text{cast}}$  with inferred  $\text{typeArgumentIR}_{\text{inferred}}^*$  and cast-inserted  $\text{argumentIR}^*$  be
      - the result of **typing instantiation**  $\text{constructorTypeIR} < \text{typeArgumentIR}^* > ( \text{argumentIR}^* )$  with omitted type arguments  $\text{typeId}_{\text{infer}}^*$ , defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$ , under cursor  $p$ , context  $TC$ , and ANON instantiation site context.
    - h. Check that  $\text{typeIR}_{\text{Object}}$  is an **extern object type without abstract methods**.
      - i. Let  $\text{callExpressionIR}$  be  $\text{prefixedNameIR} < \text{typeArgumentIR}_{\text{inferred}}^* > ( \text{argumentIR}_{\text{cast}}^* )$ .
      - j. Let  $\text{expressionNoteIR}$  be a **pair of type**  $\text{typeIR}_{\text{Object}}$  **and compile-time known-ness**  $CTK$ .
      - k. Result in  $\text{callExpressionIR}$  **annotated with**  $\text{expressionNoteIR}$ .

## 14.16.2. Local compile-time evaluation

Certain call expressions can be evaluated during type checking:

Local compile-time evaluation of  $\text{callableTargetIR} < \text{typeArgumentIR}^* > ( \text{argumentIR}^* )$  annotated with  $\text{expressionNodeIR}$ , under cursor  $p$  and context  $TC$ :

1. If let  $\text{prefixedNameIR}$  be  $\text{callableTargetIR}$ :
  - a. Let callable type  $\text{callableTypeIR}$  with fresh type variables  $\_*$ , defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$  be
    - the result of finding type of callable call  $\text{prefixedNameIR} < \text{typeArgumentIR}^* > ( \text{argumentIR}^* )$ , under cursor  $p$  and context  $TC$ .
  - b. Check that  $\text{callableTypeIR}$  has type  $\text{externFunctionTypeIR}$ .
  - c. Let  $\text{externFunctionTypeIR}$  be  $\text{callableTypeIR}$ .
  - d. Let  $\text{EXTERN\_FUNCTION text ( parameterIR }^* ) : \text{typeIR}$  be  $\text{externFunctionTypeIR}$ .
  - e. Check that  $\text{text}$  is equal to "static\_assert".
  - f. Check that  $\text{typeIR}$  has type  $\text{boolTypeIR}$ .
  - g. Let  $\text{boolTypeIR}$  be  $\text{typeIR}$ .
  - h. Let  $\text{nameIR}_{\text{param}}^*$  be the list of  $\text{nameIR}_{\text{param}}$ , obtained by repeating:
    - Let  $\text{nameIR}_{\text{param}}$  be the name of  $\text{parameterIR}$ .
 for each  $\text{parameterIR}$  in  $\text{parameterIR}^*$
  - i. Let  $TC_{\text{callee}_0}$  be an empty typing context.
  - j. Let GIVEN  $\text{parameterIR}_{\text{aligned}}^*$  DEFAULT  $\text{parameterIR}^*$  be aligning  $\text{parameterIR}^*$  with  $\text{argumentIR}^*$  where defaults are  $\text{id}_{\text{default}}^*$  and optionals are  $\text{id}_{\text{optional}}^*$ .
  - k. Check that  $\text{parameterIR}^*$  is an empty list.
  - l. Let  $\text{value}_{\text{argument}}^*$  be the list of  $\text{value}_{\text{argument}}$ , obtained by repeating:
    - Let  $\text{value}_{\text{argument}}$  be
      - the result of local compile-time evaluation of  $\text{argumentIR}$ , under cursor  $p$  and context  $TC$ .
 for each  $\text{argumentIR}$  in  $\text{argumentIR}^*$
  - m. Let  $\text{direction}_{\text{param\_aligned}}^*$  be the list of  $\text{direction}_{\text{param\_aligned}}$ ,  $\text{nameIR}_{\text{param\_aligned}}^*$  be the list of  $\text{nameIR}_{\text{param\_aligned}}$ , and  $\text{typeIR}_{\text{param\_aligned}}^*$  be the list of  $\text{typeIR}_{\text{param\_aligned}}$ , obtained by repeating:
    - Let  $\text{direction}_{\text{param\_aligned}}$ ,  $\text{typeIR}_{\text{param\_aligned}}$ , and  $\text{nameIR}_{\text{param\_aligned}}$  be the direction, the type, and the name of  $\text{parameterIR}_{\text{aligned}}$ .
 for each  $\text{parameterIR}_{\text{aligned}}$  in  $\text{parameterIR}_{\text{aligned}}^*$
  - n. Let  $\text{varTypeIR}^*$  be the list of  $\text{varTypeIR}$ , obtained by repeating:
    - Let  $\text{varTypeIR}$  be  $\text{direction}_{\text{param\_aligned}} \text{ typeIR}_{\text{param\_aligned}} \text{ LCTK value}_{\text{argument}}$ .
 for each  $\text{direction}_{\text{param\_aligned}}$  in  $\text{direction}_{\text{param\_aligned}}^*$ ,  $\text{typeIR}_{\text{param\_aligned}}$  in  $\text{typeIR}_{\text{param\_aligned}}^*$ , and  $\text{value}_{\text{argument}}$  in  $\text{value}_{\text{argument}}^*$
  - o. Let  $TC_{\text{callee}_1}$  be  $TC_{\text{callee}_0}$  where each of  $\text{nameIR}_{\text{param\_aligned}}^*$  to each of  $\text{varTypeIR}^*$  are added to the LOCAL layer.
  - p. Let  $\text{value}$  be

- the result of calling an extern function "static\_assert"(nameIR<sub>param</sub><sup>\*</sup>) under context TC<sub>callee\_1</sub>.
- q. Check that value has type boolValue.
  - r. Let boolValue be value.
  - s. Check that 'B true is equal to boolValue.
  - t. Result in boolValue.
2. Else if let typedExpressionIR<sub>base</sub> . nameIR be callableTargetIR:
    - a. Let a pair of type typeIR<sub>base</sub> and compile-time known-ness \_ be the note of typedExpressionIR<sub>base</sub>.
    - b. Check that nameIR is in [ "minSizeInBits", "minSizeInBytes", "maxSizeInBits", "maxSizeInBytes" ].
    - c. Result in \$sizeof(typeIR<sub>base</sub>, nameIR).
  3. Else if let TYPE prefixedNameIR . nameIR be callableTargetIR:
    - a. Let typeDefIR<sub>base</sub> be ! the type definition of prefixedNameIR from the p layer of TC.
    - b. If typeDefIR<sub>base</sub> is monomorphic:
      - i. Let typeIR<sub>base</sub> be the underlying type of typeDefIR<sub>base</sub>.
      - ii. Check that nameIR is in [ "minSizeInBits", "minSizeInBytes", "maxSizeInBits", "maxSizeInBytes" ].
      - iii. Result in \$sizeof(typeIR<sub>base</sub>, nameIR).
    - c. Else:
      - i. Check that ( · , · ) is equal to the type parameters of typeDefIR<sub>base</sub>.
      - ii. Let typeIR<sub>base</sub> be the underlying type of typeDefIR<sub>base</sub>.
      - iii. Check that nameIR is in [ "minSizeInBits", "minSizeInBytes", "maxSizeInBits", "maxSizeInBytes" ].
      - iv. Result in \$sizeof(typeIR<sub>base</sub>, nameIR).
  4. Else:
    - a. Let ( callableTargetIR' ) be callableTargetIR.
    - b. Let typeIR and ctk be the type and the compile-time known-ness of expressionNoteIR.
    - c. Let value be
      - the result of local compile-time evaluation of callableTargetIR' < typeArgumentIR<sup>\*</sup> > ( argumentIR<sup>\*</sup> ) annotated with a pair of type typeIR and compile-time known-ness ctk, under cursor p and context TC.
    - d. Result in value.

### 14.16.3. Compile-time evaluation

Call expressions may also be evaluated at compile time when instantiation phase takes place. A constructor call evaluates to an instance of the constructed type, while a callable call evaluates to the result of the call.

#### Calling a callable

Compile-time evaluation of callableTargetIR < \_ > ( \_ ) annotated with expressionNoteIR, under cursor p, context IC, and store STO:

1. If let typedExpressionIR<sub>base</sub> . nameIR be callableTargetIR:

- a. Let a pair of type  $\text{typeIR}_{\text{base}}$  and compile-time known-ness  $\_$  be the note of  $\text{typedExpressionIR}_{\text{base}}$ .
  - b. Check that  $\text{nameIR}$  is in [ "minSizeInBits", "minSizeInBytes", "maxSizeInBits", "maxSizeInBytes" ].
  - c. Result in store  $\text{STO}$  and  $\$sizeof(\text{typeIR}_{\text{base}}, \text{nameIR})$ .
2. Else if let  $\text{TYPE}$   $\text{prefixedNameIR} . \text{nameIR}$  be  $\text{callableTargetIR}$ :
    - a. Let  $\text{typeDefIR}_{\text{base}}$  be ! the type definition of  $\text{prefixedNameIR}$  from the  $p$  layer of  $\text{IC}$ .
    - b. If  $\text{typeDefIR}_{\text{base}}$  is monomorphic:
      - i. Let  $\text{typeIR}_{\text{base}}$  be the underlying type of  $\text{typeDefIR}_{\text{base}}$ .
      - ii. Check that  $\text{nameIR}$  is in [ "minSizeInBits", "minSizeInBytes", "maxSizeInBits", "maxSizeInBytes" ].
      - iii. Result in store  $\text{STO}$  and  $\$sizeof(\text{typeIR}_{\text{base}}, \text{nameIR})$ .
    - c. Else:
      - i. Check that  $( \cdot , \cdot )$  is equal to the type parameters of  $\text{typeDefIR}_{\text{base}}$ .
      - ii. Let  $\text{typeIR}_{\text{base}}$  be the underlying type of  $\text{typeDefIR}_{\text{base}}$ .
      - iii. Check that  $\text{nameIR}$  is in [ "minSizeInBits", "minSizeInBytes", "maxSizeInBits", "maxSizeInBytes" ].
      - iv. Result in store  $\text{STO}$  and  $\$sizeof(\text{typeIR}_{\text{base}}, \text{nameIR})$ .

## Calling a constructor

Compile-time evaluation of  $\text{prefixedNameIR} < \text{typeArgumentListIR} > ( \text{argumentListIR} )$  annotated with  $\text{expressionNoteIR}$ , under cursor  $p$ , context  $\text{IC}$ , and store  $\text{STO}$ :

1. Let constructor  $\text{constructorDef} < \text{typeArgumentListIR}_{\text{inst}} >$  with defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$  be
  - the result of finding constructor for  $\text{prefixedNameIR} < \text{typeArgumentListIR} > ( \text{argumentListIR} )$  under cursor  $p$ , and context  $\text{IC}$ .
2. Let store  $\text{STO}_1$  and constructed object be
  - the result of loading  $\text{constructorDef} < \text{typeArgumentListIR}_{\text{inst}} > ( \text{argumentListIR} )$  with defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$ , under cursor  $p$ , context  $\text{IC}$ , and store  $\text{STO}$ .
3. Let  $\text{STO}_2$  be  $\text{STO}_1$  where  $\text{IC.PATH}$  to object is added.
4. Let  $\text{value}_{\text{ref}}$  be  $\text{REF IC.PATH}$ .
5. Result in store  $\text{STO}_2$  and  $\text{value}_{\text{ref}}$ .

## Parenthesized call

Compile-time evaluation of  $( \text{callableTargetIR}' < \_ > ( \_ ) )$  annotated with  $\text{expressionNoteIR}$ , under cursor  $p$ , context  $\text{IC}$ , and store  $\text{STO}$ :

1. Let store  $\text{STO}_1$  and  $\text{value}$  be
  - the result of compile-time evaluation of  $\text{callableTargetIR}' < \_ > ( \_ )$  annotated with  $\text{expressionNoteIR}$ , under cursor  $p$ , context  $\text{IC}$ , and store  $\text{STO}$ .
2. Result in store  $\text{STO}_1$  and  $\text{value}$ .

## 14.16.4. Runtime evaluation



Evaluating `callableTargetIR < typeArgumentIR* > ( argumentIR* )` annotated with `expressionNodeIR`, under cursor `p`, context `EC`, and state `ARCH`:

1. Let context `EC1`, state `ARCH1`, and callee `calleeResult` be
  - the result of `finding callee callableTargetIR ( argumentIR* )`, under cursor `p`, context `EC`, and state `ARCH`.
2. If let `abortResult` be `calleeResult`:
  - a. Result in context `EC1`, state `ARCH1` and `abortResult`.
3. Else:
  - a. Let `callee` be `calleeResult`.
  - b. Let context `EC2`, state `ARCH2`, and call result `callResult` be
    - the result of `calling callee < typeArgumentIR* > ( argumentIR* )`, under cursor `p`, context `EC1`, and state `ARCH1`.
  - c. If let `abortResult` be `callResult`:
    - i. Result in context `EC2`, state `ARCH2` and `abortResult`.
  - d. Else:
    - i. Let `RETURN value?` be `callResult`.
    - ii. Check that `value?` is defined.
    - iii. Let `value'` be `value?`.
    - iv. Result in context `EC2`, state `ARCH2` and `value'`.

## 14.17. Parenthesized expressions

Expressions may be enclosed in parentheses to explicitly specify the order of evaluation.

```
parenthesizedExpression
: `( expression )
;
```

### 14.17.1. Type checking

After type checking, parenthesized expressions have the form:

```
parenthesizedExpressionIR
: `( typedExpressionIR )
;
```

Typing `( expression' )`, under cursor `p` and context `TC`:

1. Let `typedExpressionIR` be
  - the result of `typing expression'`, under cursor `p` and context `TC`.
2. Let `typeIR` be `the type of typedExpressionIR`.
3. Let `ctk` be `the compile-time known-ness of typedExpressionIR`.

4. Let `expressionNodeIR` be a pair of type `typeIR` and compile-time known-ness `ctl`.
5. Result in `( typedExpressionIR ) annotated with expressionNodeIR`.

### 14.17.2. Local compile-time evaluation

Local compile-time evaluation of `( typedExpressionIR ) annotated with expressionNodeIR`, under cursor `p` and context `TC`:

1. Let `value` be
  - the result of local compile-time evaluation of `typedExpressionIR`, under cursor `p` and context `TC`.
2. Result in `value`.

### 14.17.3. Compile-time evaluation

Compile-time evaluation of `( typedExpressionIR ) annotated with expressionNodeIR`, under cursor `p`, context `IC`, and store `STO`:

1. Let store `STO1` and `value` be
  - the result of compile-time evaluation of `typedExpressionIR`, under cursor `p`, context `IC`, and store `STO`.
2. Result in store `STO1` and `value`.

### 14.17.4. Runtime evaluation

Evaluating `( typedExpressionIR ) annotated with expressionNodeIR`, under cursor `p`, context `EC`, and state `ARCH`:

1. Let context `EC1`, state `ARCH1`, and `expressionResult` be
  - the result of evaluating `typedExpressionIR`, under cursor `p`, context `EC`, and state `ARCH`.
2. Result in context `EC1`, state `ARCH1`, and `expressionResult`.

## 15. Abstract parser machine

A parser declaration introduces a constructor for a parser object. See [Section 10.4](#) and [Section 11.11](#) for details.

```
parserDeclaration
  : annotationList PARSE name typeParameterListOpt `( parameterList )
    constructorParameterListOpt
    `{ parserLocalDeclarationList parserStateList }
  ;

parserLocalDeclaration
  : constantDeclaration
```

```

| instantiation
| variableDeclaration
| valueSetDeclaration
;

parserState
: annotationList STATE name `{ parserStatementList transitionStatement }
;

```

This section describes the P4 constructs specific to parsing network packets.

## 15.1. Parser state machine




Figure 12. Parser FSM structure.

A P4 parser describes a state machine with one start state and two final states. The start state is always named `start`. The two final states are named `accept` (indicating successful parsing) and `reject` (indicating a parsing failure). The `start` state is part of the parser, while the `accept` and `reject` states are distinct from the states provided by the programmer and are logically outside of the parser. Figure 12 illustrates the general structure of a parser state machine.

The semantics of a P4 parser can be formulated in terms of an abstract machine that manipulates a `ParserModel` data structure. This section describes this abstract machine in pseudo-code.

A parser starts execution in the `start` state and ends execution when one of the `reject` or `accept` states has been reached.

```

ParserModel {
    error      parseError;
    onPacketArrival(packet p) {
        ParserModel.parseError = error.NoError;
        goto start;
    }
}

```

An architecture must specify the behavior when the `accept` and `reject` states are reached. For example, an architecture may specify that all packets reaching the `reject` state are dropped without further processing. Alternatively, it may specify that such packets are passed to the next block after the parser, with intrinsic metadata indicating that the parser reached the `reject` state, along with the error recorded.

### 15.1.1. Sub-parsers

P4 also allows parsers to invoke the services of other parsers, similar to subroutines. To invoke the

services of another parser, the sub-parser must be first instantiated; the services of an instance are invoked by calling it using its `apply` method.

The following example shows a sub-parser invocation:

```
parser callee(packet_in packet, out IPv4 ipv4) { /* body omitted */ }
parser caller(packet_in packet, out Headers h) {
  callee() subparser; // instance of callee
  state subroutine {
    subparser.apply(packet, h.ipv4); // invoke sub-parser
    transition accept; // accept if sub-parser ends in accept state
  }
}
```

The semantics of a sub-parser invocation can be described as follows:

- The state invoking the sub-parser is split into two half-states at the parser invocation statement.
- The top half includes a transition to the sub-parser `start` state.
- The sub-parser's `accept` state is identified with the bottom half of the current state
- The sub-parser's `reject` state is identified with the reject state of the current parser.




Figure 13. Semantics of invoking a sub-parser: top: original program, bottom: equivalent program.

Figure 13 shows a diagram of this process.

Note that since P4 requires definitions to precede uses, it is impossible to create recursive (or mutually recursive) parsers.

When a parser is instantiated, local instantiations of stateful objects are evaluated recursively. That is, each instantiation of a parser has a unique set of local parser value sets, extern objects, inner parser instances, etc. Thus, in general, invoking a parser instance twice is not the same as invoking two copies of the same parser instance. Note however that local variables do not persist across invocations of the parser. This semantics also applies to direct invocation (see [Section 13.5](#)).

Architectures may impose (static or dynamic) constraints on the number of parser states that can be traversed for processing each packet. For example, a compiler for a specific target may reject parsers

containing loops that cannot be unrolled at compilation time or that may contain cycles that do not advance the cursor. If a parser aborts execution dynamically because it exceeded the time budget allocated for parsing, the parser should transition to `reject` and set the standard error `error.ParserTimeout`.

### 15.1.2. Runtime evaluation of a parser

At runtime, a parser is evaluated by invoking its `apply` method. The following algorithm describes the evaluation of a parser `apply` method invocation:

Calling `parserApplyMethodCallee < typeArgumentListIR > ( argumentListIR )`, under cursor `p`, context `EC0`, and state `ARCH0`:

1. Let `PARSER _ . APPLY ( parameterListIR # iddefault* ) { theta ; frame ; parserLocalDeclarationListIR ; stateEnv }` be `parserApplyMethodCallee`.
2. Let `ECcallee_0` be copy of `EC0` from the GLOBAL layer.
3. Let `ECcallee_1` be `ECcallee_0[BLOCK.TYPE = theta][BLOCK.FRAME = frame]` with `BLOCK.STATE` set to `stateEnv`.
4. Let `GIVEN parameterIRaligned* DEFAULT parameterIRdefault*` be aligning `parameterListIR` with `argumentListIR` where defaults are `iddefault*` and optionals are `.`.
5. Let `pshared` be GLOBAL.
6. Let state `ARCH1`, caller's context `EC1`, callee's context `ECcallee_2`, and copy-in result `copyInResult` be
  - the result of copy-in from `argumentListIR` in BLOCK layer of `ECcallee_1` to `parameterIRaligned*` in `p` layer of `EC0`, under cursor `pshared` and state `ARCH0`.
7. If let `rejectTransitionResult` be `copyInResult`:
  - a. Result in context `EC1`, state `ARCH1`, and call result `rejectTransitionResult`.
8. Else if let `storageReference?` be `copyInResult`:
  - a. Let `ECcallee_3` be
    - the result of copying defaults for `parameterIRdefault*`, under context BLOCK and context `ECcallee_2`.
  - b. Let context `ECcallee_4`, state `ARCH2`, and result `parserDeclarationResult` be
    - the result of evaluating parser local declarations `parserLocalDeclarationListIR`, under context `ECcallee_3`, and state `ARCH1`.
  - c. If let `rejectTransitionResult` be `parserDeclarationResult`:
    - i. Let `EC2` be
      - the result of copy-out from `parameterIRaligned*` in `p` layer of `EC1` to `storageReference?` in BLOCK layer of `ECcallee_4`, under cursor `pshared` and state `ARCH2`.
    - ii. Result in context `EC2`, state `ARCH2`, and call result `rejectTransitionResult`.
  - d. Else:
    - i. Let `continueEmptyResult` be `parserDeclarationResult`.
    - ii. Let context `ECcallee_5`, state `ARCH3`, and `transitionResult` be
      - the result of runtime evaluation of parser transition "start", under context `ECcallee_4` and state `ARCH2`.
    - iii. If let `rejectTransitionResult` be `transitionResult`:
      - A. Let `EC2` be
        - the result of copy-out from `parameterIRaligned*` in `p` layer of `EC1` to `storageReference?` in

BLOCK layer of  $EC_{\text{callee}_5}$ , under cursor  $p_{\text{shared}}$  and state  $ARCH_3$ .

- B. Result in context  $EC_2$ , state  $ARCH_3$ , and call result `rejectTransitionResult`.
- iv. Else if let `acceptTransitionResult` be `transitionResult`:
- A. Let  $EC_2$  be
- the result of copy-out from parameter  $IR_{\text{aligned}}^*$  in p layer of  $EC_1$  to `storageReference2*` in BLOCK layer of  $EC_{\text{callee}_5}$ , under cursor  $p_{\text{shared}}$  and state  $ARCH_3$ .
- B. Result in context  $EC_2$ , state  $ARCH_3$ , and call result `RETURN` .

### 15.1.3. Parser state transitions

At runtime, parser state transitions are defined as:

**ParserState\_trans:**

- Runtime evaluation of parser transition `nameIR`, under context `evalContext` and state `arch`:
- Result in context `evalContext`, state `arch`, and `transitionResult`.

The result of a transition is:

```
transitionResult
: acceptTransitionResult
| rejectTransitionResult
| stateTransitionResult
;

acceptTransitionResult
: ACCEPT
;

rejectTransitionResult
: REJECT errorValue
;

stateTransitionResult
: STATE id
;
```

**Runtime evaluation of parser transition `nameIR`, under context  $EC_0$  and state  $ARCH_0$ :**

- Let `parserStateIR'` be ! the parser state of `nameIR` in  $EC_0$ .
- Let context  $EC_1$ , state  $ARCH_1$ , and `transitionResult` be
  - the result of evaluating parser state `parserStateIR'`, under context  $EC_0$ , and state  $ARCH_0$ .
- If let `acceptTransitionResult` be `transitionResult`:
  - Result in context  $EC_1$ , state  $ARCH_1$ , and `ACCEPT`.
- Else if let `rejectTransitionResult` be `transitionResult`:
  - Result in context  $EC_1$ , state  $ARCH_1$ , and `rejectTransitionResult`.
- Else:
  - Let `STATE nameIRnext` be `transitionResult`.

- b. Let context  $EC_2$ , state  $ARCH_2$ , and  $transitionResult'$  be
  - the result of runtime evaluation of parser transition  $nameIR_{next}$ , under context  $EC_1$  and state  $ARCH_1$ .
- c. Result in context  $EC_2$ , state  $ARCH_2$ , and  $transitionResult'$ .

The following sections describe the components of a parser state transition in more detail.

## 15.2. Parser local declarations

Parser local declarations are defined as follows:

```

parserLocalDeclaration
: constantDeclaration
| instantiation
| variableDeclaration
| valueSetDeclaration
;

parserLocalDeclarationList
: /* empty */
| parserLocalDeclarationList parserLocalDeclaration
;

```

### 15.2.1. Semantics of parser local declarations

#### 15.2.1.1. Type checking

**ParserLocalDecl\_ok:**

- Typing  $parserLocalDeclaration$ , under context  $typingContext$ :
- Result in context  $typingContext$  and  $parserLocalDeclarationIR$ .

After type checking, parser local declarations are represented in  $P4_{IR}$  as follows:

```

parserLocalDeclarationIR
: constantDeclarationIR
| instantiationIR
| variableDeclarationIR
| valueSetDeclarationIR
;

```

A list of parser local declarations is type checked by:

**ParserLocalDeclList\_ok:**

- Typing  $parserLocalDeclarationList$ , under context  $typingContext$ :
- Result in context  $typingContext$  and  $parserLocalDeclarationIR^*$ .

**Typing  $parserLocalDeclarationList$ , under context  $TC_0$ :**

1. Let  $\text{parserLocalDeclaration}^*$  be the list of parser local declarations in  $\text{parserLocalDeclarationList}$ .
2. Let the updated context  $\text{TC}_1$  and the typed parser local declarations  $\text{parserLocalDeclarationIR}^*$  be
  - the result of typing  $\text{parserLocalDeclaration}^*$ , under context  $\text{TC}_0$ .
3. Result in context  $\text{TC}_1$  and  $\text{parserLocalDeclarationIR}^*$ .

#### ParserLocalDecls\_ok:

- Typing  $\text{parserLocalDeclaration}^*$ , under context  $\text{typingContext}$ :
- Result in the updated context  $\text{typingContext}$  and the typed parser local declarations  $\text{parserLocalDeclarationIR}^*$ .

#### Typing $\text{parserLocalDeclaration}^*$ , under context $\text{typingContext}$ :

1. If  $\text{parserLocalDeclaration}^*$  is equal to  $\cdot$ :
  - a. Result in the updated context  $\text{typingContext}$  and the typed parser local declarations  $\cdot$ .
2. If let  $\text{parserLocalDeclaration}_h :: \text{parserLocalDeclaration}_t^*$  be  $\text{parserLocalDeclaration}^*$ :
  - a. Let context  $\text{TC}_1$  and  $\text{parserLocalDeclarationIR}_h$  be
    - the result of typing  $\text{parserLocalDeclaration}_h$ , under context  $\text{typingContext}$ .
  - b. Let the updated context  $\text{TC}_2$  and the typed parser local declarations  $\text{parserLocalDeclarationIR}_t^*$  be
    - the result of typing  $\text{parserLocalDeclaration}_t^*$ , under context  $\text{TC}_1$ .
  - c. Result in the updated context  $\text{TC}_2$  and the typed parser local declarations  $\text{parserLocalDeclarationIR}_h :: \text{parserLocalDeclarationIR}_t^*$ .

### 15.2.1.2. Compile-time evaluation

#### ParserLocalDecl\_inst:

- Compile-time evaluation of  $\text{parserLocalDeclarationIR}$ , under context  $\text{instContext}$  and store  $\text{store}$ :
- Result in context  $\text{instContext}$ , store  $\text{store}$ , and  $\text{parserLocalDeclarationIR}$ .

A list of parser local declarations is compile-time evaluated by:

#### ParserLocalDecls\_inst:

- Compile-time evaluation of  $\text{parserLocalDeclarationIR}^*$ , under context  $\text{instContext}$  and store  $\text{store}$ :
- Result in context  $\text{instContext}$ , store  $\text{store}$ , and  $\text{parserLocalDeclarationIR}^*$ .

#### Compile-time evaluation of $\text{parserLocalDeclarationIR}^*$ , under context $\text{instContext}$ and store $\text{store}$ :

1. If  $\text{parserLocalDeclarationIR}^*$  is equal to  $\cdot$ :



- a. Result in context `instContext`, store `store`, and `.`.
2. If let `parserLocalDeclarationIRh :: parserLocalDeclarationIRt*` be `parserLocalDeclarationIR*`:
  - a. Let context `IC1`, store `STO1`, and `parserLocalDeclarationIRh_inst` be
    - the result of **compile-time evaluation of** `parserLocalDeclarationIRh`, **under context** `instContext` **and store** `store`.
  - b. Let context `IC2`, store `STO2`, and `parserLocalDeclarationIRt_inst*` be
    - the result of **compile-time evaluation of** `parserLocalDeclarationIRt*`, **under context** `IC1` **and store** `STO1`.
  - c. Result in context `IC2`, store `STO2`, and `parserLocalDeclarationIRh_inst :: parserLocalDeclarationIRt_inst*`.

### 15.2.1.3. Runtime evaluation

#### ParserLocalDecl\_eval:

- Evaluating parser local declaration `parserLocalDeclarationIR`, under context `evalContext`, and state `arch`:
- Result in context `evalContext`, state `arch`, and result `parserDeclarationResult`.

Evaluation of a parser local declaration yields:

```

parserDeclarationResult = parserStatementResult

parserStatementResult
: continueEmptyResult
| rejectTransitionResult
;

continueEmptyResult
: /* empty */
;

rejectTransitionResult
: REJECT errorValue
;

```

A list of parser local declarations is runtime evaluated by:

#### ParserLocalDecls\_eval:

- Evaluating parser local declarations `parserLocalDeclarationIR*`, under context `evalContext`, and state `arch`:
- Result in context `evalContext`, state `arch`, and result `parserDeclarationResult`.

#### Evaluating parser local declarations `parserLocalDeclarationIR*`, under context `evalContext`, and state `arch`:

1. If `parserLocalDeclarationIR*` is equal to `.`:
  - a. Result in context `evalContext`, state `arch`, and result ``EMPTY`.
2. If let `parserLocalDeclarationIRh :: parserLocalDeclarationListIRt` be `parserLocalDeclarationIR*`:

- a. Let context  $EC_1$ , state  $ARCH_1$ , and result  $parserDeclarationResult$  be
  - the result of **evaluating parser local declaration**  $parserLocalDeclarationIR_i$ , under context  $evalContext$ , and state  $arch$ .
- b. If let  $rejectTransitionResult$  be  $parserDeclarationResult$ :
  - i. Result in context  $EC_1$ , state  $ARCH_1$ , and result  $rejectTransitionResult$ .
- c. Else:
  - i. Let context  $EC_2$ , state  $ARCH_2$ , and result  $parserStatementResult$  be
    - the result of **evaluating parser local declarations**  $parserLocalDeclarationListIR_i$ , under context  $EC_1$ , and state  $ARCH_1$ .
  - ii. Result in context  $EC_2$ , state  $ARCH_2$ , and result  $parserStatementResult$ .

The subsequent sections describe each kind of declaration in detail.

## 15.2.2. Constant declarations

See [Section 11.3](#) for general information about constant declarations.

### 15.2.2.1. Type checking

**Typing**  $constantDeclaration$ , under context  $TC_0$ :

1. Let context  $TC_1$  and  $constantDeclarationIR$  be
  - the result of **typing**  $constantDeclaration$ , under cursor  $BLOCK$  and context  $TC_0$ .
2. Result in context  $TC_1$  and  $constantDeclarationIR$ .

### 15.2.2.2. Compile-time evaluation

**Compile-time evaluation of**  $constantDeclarationIR$ , under context  $IC_0$  and store  $STO$ :

1. Let context  $IC_1$  be
  - the result of **loading**  $constantDeclarationIR$ , under cursor  $BLOCK$ , and context  $IC_0$ .
2. Result in context  $IC_1$ , store  $STO$ , and  $constantDeclarationIR$ .

### 15.2.2.3. Runtime evaluation

**Evaluating parser local declaration**  $constantDeclarationIR$ , under context  $EC_0$ , and state  $ARCH$ :

1. Let context  $EC_1$  be
  - the result of **evaluating**  $constantDeclarationIR$ , under cursor  $BLOCK$ , and context  $EC_0$ .
2. Result in context  $EC_1$ , state  $ARCH$ , and result `EMPTY`.

### 15.2.3. Instantiations

See [Section 11.4](#) for general information about instantiations.

#### 15.2.3.1. Type checking

Typing *instantiation*, under context  $TC_0$ :

1. Let context  $TC_1$  and *instantiationIR* be
  - the result of typing *instantiation*, under cursor *BLOCK* and context  $TC_0$ .
2. Result in context  $TC_1$  and *instantiationIR*.

#### 15.2.3.2. Compile-time evaluation

Compile-time evaluation of *instantiationIR*, under context  $IC_0$  and store *STO*:

1. Let context  $IC_1$ , store  $STO_1$ , and reference to object *constantDeclarationIR<sub>inst</sub>* be
  - the result of loading *instantiationIR*, under cursor *BLOCK*, context  $IC_0$ , and store *STO*.
2. Result in context  $IC_1$ , store  $STO_1$ , and *constantDeclarationIR<sub>inst</sub>*.

### 15.2.4. Variable declarations

See [Section 11.2](#) for general information about variable declarations.

#### 15.2.4.1. Type checking

Typing *variableDeclaration*, under context  $TC_0$ :

1. Let context  $TC_1$  and *variableDeclarationIR* be
  - the result of typing *variableDeclaration*, under cursor *BLOCK* and context  $TC_0$ .
2. Result in context  $TC_1$  and *variableDeclarationIR*.

#### 15.2.4.2. Compile-time evaluation

Compile-time evaluation of *variableDeclarationIR*, under context  $IC_0$  and store *STO*:

1. Result in context  $IC_0$ , store *STO*, and *variableDeclarationIR*.

#### 15.2.4.3. Runtime evaluation

Evaluating parser local declaration *variableDeclarationIR*, under context  $EC_0$ , and state *ARCH*:

1. Let context  $EC_1$ , state  $ARCH_1$ , and result *declarationResult* be
  - the result of evaluating *variableDeclarationIR*, under cursor *BLOCK*, context  $EC_0$ , and state *ARCH*.

2. If let `rejectTransitionResult` be `declarationResult`:
  - a. Result in context  $EC_1$ , state  $ARCH_1$ , and result `rejectTransitionResult`.
3. Else if let `continueEmptyResult` be `declarationResult`:
  - a. Result in context  $EC_1$ , state  $ARCH_1$ , and result ``EMPTY`.

## 15.2.5. Parser value set declarations

Parser value sets are declared with the syntax:

```
valueSetDeclaration
: annotationList VALUE_SET `< valueSetType > `( expression ) name ;
;

valueSetType
: baseType
| tupleType
| prefixedTypeName
;
```

See [Section 10.7](#) for general information about value sets.

### 15.2.5.1. Type checking

**Typing** `annotationList VALUE_SET < valueSetType > ( expression ) name ;`, under context  $TC_0$ :

1. Let `typeIR` and a set of fresh type variables `typed*` be
  - the result of **typing** `valueSetType`, under cursor `BLOCK` and context  $TC_0$ .
2. Check that `typed*` is an empty list.
3. Let `bound` be **bound type variables from the BLOCK layer of**  $TC_0$ .
4. Check that `SET < typeIR >` is a well-formed type, with **bound type variables** `bound`.
5. Let `typedExpressionIR` be
  - the result of **typing** `expression`, under cursor `BLOCK` and context  $TC_0$ .
6. Check that **the compile-time known-ness of** `typedExpressionIR` does not match pattern `DYN`.
7. Let `nameIR` be **the name of** `name`.
8. Let `varTypeIR` be ``EMPTY SET < typeIR > CTK`.
9. Let  $TC_1$  be  $TC_0$  **where** `nameIR` **to** `varTypeIR` **is added to the BLOCK layer**.
10. Let `valueSetDeclarationIR` be `annotationList VALUE_SET < typeIR > ( typedExpressionIR ) nameIR ;`.
11. Result in context  $TC_1$  and `valueSetDeclarationIR`.

### 15.2.5.2. Compile-time evaluation

**Compile-time evaluation of** `annotationList VALUE_SET < typeIR > ( typedExpressionIRsize ) nameIR ;`, under context  $IC_0$  and store  $STO$ :

1. Let store  $STO_1$  and `value` be

- the result of **compile-time evaluation of**  $\text{typedExpressionIR}_{\text{size}}$ , **under cursor** **BLOCK**, **context**  $\text{IC}_0$ , **and store**  $\text{STO}$ .
2. Check that  $\text{value}$  has type  $\text{integerValue}$ .
  3. Let  $\text{integerValue}_{\text{size}}$  be  $\text{value}$ .
  4. Let  $n_{\text{size}}$  be **! the natural number representation of**  $\text{integerValue}_{\text{size}}$ .
  5. Let  $\text{typeIR}_{\text{subst}}$  be  $\text{typeIR}$  **substituted by bound type variables in**  $\text{IC}_0$  **from the** **BLOCK** **layer**.
  6. Let  $\text{value}''$  be **the default value for type**  $\text{typeIR}_{\text{subst}}$ .
  7. Let  $\text{value}^*$  be **a list of**  $n_{\text{size}}$  **copies of**  $\text{value}''$ .
  8. Let  $\text{valueSetObject}$  be  $\text{VALUE\_SET } \{ \text{value}^* ( n_{\text{size}} ) \}$ .
  9. Let  $\text{objectId}$  be  $\text{IC}_0.\text{PATH}$  concatenated with  $\text{nameIR}$ .
  10. Let  $\text{STO}_2$  be  $\text{STO}_1$  **where**  $\text{objectId}$  **to**  $\text{valueSetObject}$  **is added**.
  11. Let  $\text{typeIR}_{\text{set}}$  be  $\text{SET} < \text{typeIR} >$ .
  12. Let  $\text{constantDeclarationIR}$  be  $\text{'EMPTY CONST } \text{typeIR}_{\text{set}} \text{ nameIR} = \text{'VALUE REF objectId ;}$ .
  13. Result in context  $\text{IC}_0$ , store  $\text{STO}_2$ , and  $\text{constantDeclarationIR}$ .

After compile-time evaluation, parser value set declarations are represented in  $\text{P4}_{\text{IR}}$  as follows:

```
valueSetDeclarationIR
: annotationList VALUE_SET `< typeIR > `( typedExpressionIR ) nameIR ;
;
```

## 15.3. Parser states

A parser state is declared with the following syntax:

```
parserState
: annotationList STATE name `{ parserStatementList transitionStatement }
;
```

Each state has a name and a body. The body consists of a sequence of statements that describe the processing performed when the parser transitions to that state, including:

- Local variable declarations,
- Assignment statements,
- Method calls, which serve several purposes:
  - Invoking functions (e.g., using **verify** to check the validity of data already parsed), and
  - Invoking methods (e.g., extracting data out of packets or computing checksums) and other parsers (see [Section 15.1.1](#)), and
- Conditional statements,
- Transitions to other states (discussed in [Section 15.5](#)).

Architectures may place restrictions on the expressions and statements that can be used in a parser—e.g., they may forbid the use of operations such as multiplication or place restrictions on the number of local variables that may be used.

### 15.3.1. Type checking

A list of parser states is type checked with the following relation:

**ParserStateList\_ok:**

- Typing `parserStateList`, under context `typingContext`:
- Result in `parserStateIR*`.

**Typing `parserStateList`, under context `TC`:**

1. Let `parserState*` be the list of parser states in `parserStateList`.
2. Let `namestate*` be the list of `namestate`, obtained by repeating:
  - Let `_ STATE namestate { _ _ }` be `parserState`.for each `parserState` in `parserState*`
3. Let `nameIRstate*` be the list of `nameIRstate`, obtained by repeating:
  - Let `nameIRstate` be the name of `namestate`.for each `namestate` in `namestate*`
4. Check that the elements of `nameIRstate*` are distinct.
5. Check that "start" is in `nameIRstate*`.
6. Check that "accept" is not in `nameIRstate*` and "reject" is not in `nameIRstate*`.
7. Let `nameIRstate_impl*` be "accept" :: "reject" :: `nameIRstate*`.
8. Let `parserStateIR*` be the list of `parserStateIR`, obtained by repeating:
  - Let `parserStateIR` be
    - the result of typing `parserState`, under context `TC` and parser state names `nameIRstate_impl*`.for each `parserState` in `parserState*`
9. Result in `parserStateIR*`.

A parser state is type checked with the following relation:

**ParserState\_ok:**

- Typing `parserState`, under context `typingContext` and parser state names `nameIR*`:
- Result in `parserStateIR`.

**Typing `parserState`, under context `TC0` and parser state names `nameIRstate*`:**

1. Let `annotationList STATE name { parserStatementList transitionStatement }` be `parserState`.

2. Let  $nameIR$  be the name of  $name$ .
3. Let  $TC_1$  be  $TC_0$  with a new local frame.
4. Let  $parserStatement^*$  be the list of parser statements in  $parserStatementList$ .
5. Let the updated context  $TC_2$  and the typed parser statements  $parserStatementIR^*$  be
  - the result of typing  $parserStatement^*$ , under context  $TC_1$ .
6. Let typed transition statement  $transitionStatementIR$  be
  - the result of typing  $transitionStatement$ , under context  $TC_2$  and parser state names  $nameIR_{state}^*$ .
7. Let  $TC_3$  be  $TC_2$  with the innermost frame removed.
8. Let  $parserStateIR$  be  $annotationList\ STATE\ nameIR\ \{ parserStatementIR^*\ transitionStatementIR\}$ .
9. Result in  $parserStateIR$ .

### 15.3.2. Compile-time evaluation

A list parser states is compile-time evaluated with the following relation:

**ParserStates\_inst:**

- Compile-time evaluation of  $parserStateIR^*$ , under context  $instContext$  and store  $store$ :
- Result in context  $instContext$  and store  $store$ .

**Compile-time evaluation of  $parserStateIR^*$ , under context  $instContext$  and store  $store$ :**

1. If  $parserStateIR^*$  is equal to  $\cdot$ :
  - a. Result in context  $instContext$  and store  $store$ .
2. If let  $parserStateIR_n :: parserStateIR_t^*$  be  $parserStateIR^*$ :
  - a. Let context  $IC_1$  and store  $STO_1$  be
    - the result of compile-time evaluation of  $parserStateIR_n$ , under context  $instContext$  and store  $store$ .
  - b. Let context  $IC_2$  and store  $STO_2$  be
    - the result of compile-time evaluation of  $parserStateIR_t^*$ , under context  $IC_1$  and store  $STO_1$ .
  - c. Result in context  $IC_2$  and store  $STO_2$ .

A parser state is compile-time evaluated with the following relation:

**ParserState\_inst:**

- Compile-time evaluation of  $parserStateIR$ , under context  $instContext$  and store  $store$ :
- Result in context  $instContext$  and store  $store$ .

**Compile-time evaluation of  $parserStateIR$ , under context  $IC_0$  and store  $STO_0$ :**

1. Let `annotationList STATE nameIR { parserStatementListIR transitionStatementIR }` be `parserStateIR`.
2. Let context `IC1` and store `STO1` be
  - the result of **compile-time evaluation of** `parserStatementListIR`, **under context** `IC0` **and store** `STO0`.
3. Let `parserStateIRinst` be `annotationList STATE nameIR { parserStatementListIRinst transitionStatementIR }`.
4. Let `IC2` be `IC1` **where** `nameIR` **to** `parserStateIRinst` **is added**.
5. Result in context `IC2` and store `STO1`.

### 15.3.3. Runtime evaluation

A parser state is runtime evaluated with the following relation:

**ParserState\_eval:**

- Evaluating parser state `parserStateIR`, under context `evalContext`, and state `arch`:
- Result in context `evalContext`, state `arch`, and `transitionResult`.

The result of evaluation is a state transition,

```
transitionResult
: acceptTransitionResult
| rejectTransitionResult
| stateTransitionResult
;
```

**Evaluating parser state** `parserStateIR`, **under context** `EC0`, **and state** `ARCH0`:

1. Let `annotationList STATE nameIR { parserStatementListIR transitionStatementIR }` be `parserStateIR`.
2. Let context `EC1`, state `ARCH1`, and `parserStatementResult` be
  - the result of **runtime evaluation of** `parserStatementListIR`, **under context** `EC0` **and state** `ARCH0`.
3. If let `rejectTransitionResult` be `parserStatementResult`:
  - a. Result in context `EC1`, state `ARCH1`, and `rejectTransitionResult`.
4. Else:
  - a. Let `continueEmptyResult` be `parserStatementResult`.
  - b. Let context `EC2`, state `ARCH2`, and `transitionResult` be
    - the result of **runtime evaluation of** `transitionStatementIR`, **under context** `EC1` **and state** `ARCH1`.
  - c. Result in context `EC2`, state `ARCH2`, and `transitionResult`.

## 15.4. Parser statements

The syntax for parser statements is given by the following grammar rules:

```
parserStatement
: constantDeclaration
```



```

| variableDeclaration
| emptyStatement
| assignmentStatement
| callStatement
| directApplicationStatement
| parserBlockStatement
| parserConditionalStatement
;

parserBlockStatement
: annotationList `{ parserStatementList }
;

parserConditionalStatement
: IF `( expression ) parserStatement
| IF `( expression ) parserStatement ELSE parserStatement
;

parserStatementList
: /* empty */
| parserStatementList parserStatement
;

```

## 15.4.1. Semantics of parser statements

### 15.4.1.1. Type checking

[ParserStmt\\_ok](#):

- Typing `parserStatement`, under context `typingContext`:
- Result in context `typingContext` and typed parser statement `parserStatementIR`.

After type checking, parser statements are represented in  $P4_{IR}$  as follows:

```

parserStatementIR
: constantDeclarationIR
| variableDeclarationIR
| emptyStatementIR
| assignmentStatementIR
| callStatementIR
| directApplicationStatementIR
| parserBlockStatementIR
| parserConditionalStatementIR
;

parserBlockStatementIR
: annotationList `{ parserStatementListIR }
;

parserConditionalStatementIR
: IF `( typedExpressionIR ) parserStatementIR
| IF `( typedExpressionIR ) parserStatementIR ELSE parserStatementIR
;

```

A list of parser statements is type checked by:

[ParserStmtList\\_ok](#):

- Typing  $\text{parserStatementList}$ , under context  $\text{typingContext}$ :
- Result in context  $\text{typingContext}$  and typed parser statements  $\text{parserStatementIR}^*$ .

Typing  $\text{parserStatementList}$ , under context  $\text{TC}_0$ :

1. Let  $\text{parserStatement}^*$  be the list of parser statements in  $\text{parserStatementList}$ .
2. Let the updated context  $\text{TC}_1$  and the typed parser statements  $\text{parserStatementIR}^*$  be
  - the result of typing  $\text{parserStatement}^*$ , under context  $\text{TC}_0$ .
3. Result in context  $\text{TC}_1$  and typed parser statements  $\text{parserStatementIR}^*$ .

ParserStmts\_ok:

- Typing  $\text{parserStatement}^*$ , under context  $\text{typingContext}$ :
- Result in the updated context  $\text{typingContext}$  and the typed parser statements  $\text{parserStatementIR}^*$ .

Typing  $\text{parserStatement}^*$ , under context  $\text{typingContext}$ :

1. If  $\text{parserStatement}^*$  is equal to  $\cdot$ :
  - a. Result in the updated context  $\text{typingContext}$  and the typed parser statements  $\cdot$ .
2. If let  $\text{parserStatement}_h :: \text{parserStatement}_t^*$  be  $\text{parserStatement}^*$ :
  - a. Let context  $\text{TC}_1$  and typed parser statement  $\text{parserStatementIR}_h$  be
    - the result of typing  $\text{parserStatement}_h$ , under context  $\text{typingContext}$ .
  - b. Let the updated context  $\text{TC}_2$  and the typed parser statements  $\text{parserStatementIR}_t^*$  be
    - the result of typing  $\text{parserStatement}_t^*$ , under context  $\text{TC}_1$ .
  - c. Result in the updated context  $\text{TC}_2$  and the typed parser statements  $\text{parserStatementIR}_h :: \text{parserStatementIR}_t^*$ .

#### 15.4.1.2. Compile-time evaluation

ParserStmt\_inst:

- Compile-time evaluation of  $\text{parserStatementIR}$ , under context  $\text{instContext}$  and store  $\text{store}$ :
- Result in context  $\text{instContext}$  and store  $\text{store}$ .

A list of parser statements is compile-time evaluated by:

ParserStmts\_inst:

- Compile-time evaluation of  $\text{parserStatementIR}^*$ , under context  $\text{instContext}$  and store  $\text{store}$ :
- Result in context  $\text{instContext}$  and store  $\text{store}$ .

Compile-time evaluation of  $\text{parserStatementIR}^*$ , under context  $\text{instContext}$  and store  $\text{store}$ :

1. If  $\text{parserStatementIR}^*$  is equal to  $\cdot$ :
  - a. Result in context  $\text{instContext}$  and store  $\text{store}$ .
2. If let  $\text{parserStatementIR}_h :: \text{parserStatementIR}_t^*$  be  $\text{parserStatementIR}^*$ :
  - a. Let context  $\text{IC}_1$  and store  $\text{STO}_1$  be
    - the result of compile-time evaluation of  $\text{parserStatementIR}_h$ , under context  $\text{instContext}$  and store  $\text{store}$ .
  - b. Let context  $\text{IC}_2$  and store  $\text{STO}_2$  be
    - the result of compile-time evaluation of  $\text{parserStatementIR}_t^*$ , under context  $\text{IC}_1$  and store  $\text{STO}_1$ .
  - c. Result in context  $\text{IC}_2$  and store  $\text{STO}_2$ .

### 15.4.1.3. Runtime evaluation

**ParserStmt\_eval:**

- Runtime evaluation of  $\text{parserStatementIR}$ , under context  $\text{evalContext}$  and state  $\text{arch}$ :
- Result in context  $\text{evalContext}$ , state  $\text{arch}$ , and  $\text{parserStatementResult}$ .

Evaluation of a parser statement yields:

```
parserStatementResult
: continueEmptyResult
| rejectTransitionResult
;

continueEmptyResult
: /* empty */
;

rejectTransitionResult
: REJECT errorValue
;
```

A list of parser statements is runtime evaluated by:

**ParserStmts\_eval:**

- Runtime evaluation of  $\text{parserStatementListIR}$ , under context  $\text{evalContext}$  and state  $\text{arch}$ :
- Result in context  $\text{evalContext}$ , state  $\text{arch}$ , and  $\text{parserStatementResult}$ .

Runtime evaluation of  $\text{parserStatementIR}^*$ , under context  $\text{evalContext}$  and state  $\text{arch}$ :

1. If  $\text{parserStatementIR}^*$  is equal to  $\cdot$ :
  - a. Result in context  $\text{evalContext}$ , state  $\text{arch}$ , and `EMPTY`.

2. If let  $\text{parserStatementIR}_h :: \text{parserStatementIR}_t^*$  be  $\text{parserStatementIR}^*$ :
  - a. Let context  $EC_1$ , state  $ARCH_1$ , and  $\text{parserStatementResult}$  be
    - the result of runtime evaluation of  $\text{parserStatementIR}_h$ , under context  $evalContext$  and state  $arch$ .
  - b. If let  $\text{rejectTransitionResult}$  be  $\text{parserStatementResult}$ :
    - i. Result in context  $EC_1$ , state  $ARCH_1$ , and  $\text{rejectTransitionResult}$ .
  - c. Else:
    - i. Let  $\text{continueEmptyResult}$  be  $\text{parserStatementResult}$ .
    - ii. Let context  $EC_2$ , state  $ARCH_2$ , and  $\text{parserStatementResult}'$  be
      - the result of runtime evaluation of  $\text{parserStatementIR}_t^*$ , under context  $EC_1$  and state  $ARCH_1$ .
    - iii. Result in context  $EC_2$ , state  $ARCH_2$ , and  $\text{parserStatementResult}'$ .

The subsequent sections describe each kind of statement in detail.

## 15.4.2. Constant declaration

See [Section 11.3](#) for general information about constant declarations.

### 15.4.2.1. Type checking

Typing  $\text{constantDeclaration}$ , under context  $TC_0$ :

1. Let context  $TC_1$  and  $\text{constantDeclarationIR}$  be
  - the result of typing  $\text{constantDeclaration}$ , under cursor  $LOCAL$  and context  $TC_0$ .
2. Result in context  $TC_1$  and typed parser statement  $\text{constantDeclarationIR}$ .

### 15.4.2.2. Compile-time evaluation

Compile-time evaluation of  $\text{constantDeclarationIR}$ , under context  $IC_0$  and store  $STO$ :

1. Let context  $IC_1$  be
  - the result of loading  $\text{constantDeclarationIR}$ , under cursor  $LOCAL$ , and context  $IC_0$ .
2. Result in context  $IC_1$  and store  $STO$ .

### 15.4.2.3. Runtime evaluation

Runtime evaluation of  $\text{constantDeclarationIR}$ , under context  $EC_0$  and state  $ARCH$ :

1. Let context  $EC_1$  be
  - the result of evaluating  $\text{constantDeclarationIR}$ , under cursor  $LOCAL$ , and context  $EC_0$ .
2. Result in context  $EC_1$ , state  $ARCH$ , and  $'EMPTY'$ .

### 15.4.3. Variable declaration

See [Section 11.2](#) for general information about variable declarations.

#### 15.4.3.1. Type checking

Typing `variableDeclaration`, under context  $TC_0$ :

1. Let context  $TC_1$  and `variableDeclarationIR` be
  - the result of typing `variableDeclaration`, under cursor `LOCAL` and context  $TC_0$ .
2. Result in context  $TC_1$  and typed parser statement `variableDeclarationIR`.

#### 15.4.3.2. Compile-time evaluation

Compile-time evaluation of `variableDeclarationIR`, under context  $IC_0$  and store  $STO$ :

1. Result in context  $IC_0$  and store  $STO$ .

#### 15.4.3.3. Runtime evaluation

Runtime evaluation of `variableDeclarationIR`, under context  $EC_0$  and state  $ARCH$ :

1. Let context  $EC_1$ , state  $ARCH_1$ , and result `declarationResult` be
  - the result of evaluating `variableDeclarationIR`, under cursor `LOCAL`, context  $EC_0$ , and state  $ARCH$ .
2. If let `rejectTransitionResult` be `declarationResult`:
  - a. Result in context  $EC_1$ , state  $ARCH_1$ , and `rejectTransitionResult`.
3. Else if let `continueEmptyResult` be `declarationResult`:
  - a. Result in context  $EC_1$ , state  $ARCH_1$ , and `EMPTY`.

### 15.4.4. Empty statement

See [Section 13.2](#) for general information about empty statements.

#### 15.4.4.1. Type checking

Typing `emptyStatement`, under context  $TC_0$ :

1. Let context `typingContext`, abstract control flow `flow`, and `statementIR` be
  - the result of typing `emptyStatement`, under cursor `LOCAL`, context  $TC_0$ , abstract control flow `CONT`, and loop context `NOLOOP`.
2. Check that `typingContext` is equal to  $TC_0$ .
3. Check that `flow` is `CONT`.
4. Check that `statementIR` has type `emptyStatementIR`.

5. Let `emptyStatementIR` be `statementIR`.
6. Result in context `TC0` and typed parser statement `emptyStatementIR`.

#### 15.4.4.2. Compile-time evaluation

Compile-time evaluation of `emptyStatementIR`, under context `IC0` and store `STO`:

1. Let context `IC1`, store `STO1`, and `statementIR` be
  - the result of compile-time evaluation of `emptyStatementIR`, under cursor `LOCAL`, context `IC0`, and store `STO`.
2. Check that `statementIR` has type `emptyStatementIR`.
3. Let `emptyStatementIRinst` be `statementIR`.
4. Result in context `IC1` and store `STO1`.

#### 15.4.4.3. Runtime evaluation

Runtime evaluation of `emptyStatementIR`, under context `EC0` and state `ARCH`:

1. Let context `EC1`, state `ARCH1`, and `statementResult` be
  - the result of runtime evaluation of `emptyStatementIR`, under cursor `LOCAL`, context `EC0`, and state `ARCH`.
2. Check that `statementResult` has type `continueEmptyResult`.
3. Let `continueEmptyResult` be `statementResult`.
4. Result in context `EC1`, state `ARCH1`, and `EMPTY`.

### 15.4.5. Assignment statement

See [Section 13.3](#) for general information about assignment statements.

#### 15.4.5.1. Type checking

Typing `assignmentStatement`, under context `TC0`:

1. Let context `TC1`, abstract control flow `flow`, and `statementIR` be
  - the result of typing `assignmentStatement`, under cursor `LOCAL`, context `TC0`, abstract control flow `CONT`, and loop context `NOLOOP`.
2. Check that `flow` is `CONT`.
3. Check that `statementIR` has type `assignmentStatementIR`.
4. Let `assignmentStatementIR` be `statementIR`.
5. Result in context `TC1` and typed parser statement `assignmentStatementIR`.

#### 15.4.5.2. Compile-time evaluation

Compile-time evaluation of `assignmentStatementIR`, under context  $IC_0$  and store  $STO$ :

1. Let context  $IC_1$ , store  $STO_1$ , and `statementIR` be
  - the result of compile-time evaluation of `assignmentStatementIR`, under cursor `LOCAL`, context  $IC_0$ , and store  $STO$ .
2. Check that `statementIR` has type `assignmentStatementIR`.
3. Let `assignmentStatementIRinst` be `statementIR`.
4. Result in context  $IC_1$  and store  $STO_1$ .

### 15.4.5.3. Runtime evaluation

Runtime evaluation of `assignmentStatementIR`, under context  $EC_0$  and state  $ARCH$ :

1. Let context  $EC_1$ , state  $ARCH_1$ , and `statementResult` be
  - the result of runtime evaluation of `assignmentStatementIR`, under cursor `LOCAL`, context  $EC_0$ , and state  $ARCH$ .
2. If let `rejectTransitionResult` be `statementResult`:
  - a. Result in context  $EC_1$ , state  $ARCH_1$ , and `rejectTransitionResult`.
3. Else if let `continueEmptyResult` be `statementResult`:
  - a. Result in context  $EC_1$ , state  $ARCH_1$ , and `EMPTY`.

## 15.4.6. Call statement

See [Section 13.4](#) for general information about call statements.

### 15.4.6.1. Type checking

Typing `callStatement`, under context  $TC_0$ :

1. Let context  $TC_1$ , abstract control flow `flow`, and `statementIR` be
  - the result of typing `callStatement`, under cursor `LOCAL`, context  $TC_0$ , abstract control flow `CONT`, and loop context `NOLOOP`.
2. Check that `flow` is `CONT`.
3. Check that `statementIR` has type `callStatementIR`.
4. Let `callStatementIR` be `statementIR`.
5. Result in context  $TC_1$  and typed parser statement `callStatementIR`.

### 15.4.6.2. Compile-time evaluation

Compile-time evaluation of `callStatementIR`, under context  $IC_0$  and store  $STO$ :

1. Let context  $IC_1$ , store  $STO_1$ , and `statementIR` be

- the result of **compile-time evaluation of** `callStatementIR`, under cursor `LOCAL`, context `IC0`, and store `STO`.
2. Check that `statementIR` has type `callStatementIR`.
  3. Let `callStatementIRinst` be `statementIR`.
  4. Result in context `IC1` and store `STO1`.

### 15.4.6.3. Runtime evaluation

**Runtime evaluation of** `callStatementIR`, under context `EC0` and state `ARCH`:

1. Let context `EC1`, state `ARCH1`, and `statementResult` be
  - the result of **runtime evaluation of** `callStatementIR`, under cursor `LOCAL`, context `EC0`, and state `ARCH`.
2. If let `rejectTransitionResult` be `statementResult`:
  - a. Result in context `EC1`, state `ARCH1`, and `rejectTransitionResult`.
3. Else if let `continueEmptyResult` be `statementResult`:
  - a. Result in context `EC1`, state `ARCH1`, and `EMPTY`.

## 15.4.7. Direct type invocation

See [Section 13.5](#) for general information about direct type invocations.

### 15.4.7.1. Type checking

**Typing** `directApplicationStatement`, under context `TC0`:

1. Let context `TC1`, abstract control flow `flow`, and `statementIR` be
  - the result of **typing** `directApplicationStatement`, under cursor `LOCAL`, context `TC0`, abstract control flow `CONT`, and loop context `NOLOOP`.
2. Check that `flow` is `CONT`.
3. Check that `statementIR` has type `directApplicationStatementIR`.
4. Let `directApplicationStatementIR` be `statementIR`.
5. Result in context `TC1` and typed parser statement `directApplicationStatementIR`.

### 15.4.7.2. Compile-time evaluation

**Compile-time evaluation of** `directApplicationStatementIR`, under context `IC0` and store `STO`:

1. Let store `STO1` and desugared `constantDeclarationIR` `callStatementIR` be
  - the result of **compile-time evaluation of** `directApplicationStatementIR`, under cursor `LOCAL`, context `IC0`, and store `STO`.
2. Let `parserBlockStatementIR` be `EMPTY { [ constantDeclarationIR, callStatementIR ] }`.



3. Result in context  $IC_0$  and store  $STO_1$ .

## 15.4.8. Block statement

A parser block statement is a sequence of parser statements enclosed in braces. It is similar to a block statement explained in [Section 13.8](#), but it can only contain parser statements.

```
parserBlockStatement
: annotationList `{ parserStatementList }
;
```

### 15.4.8.1. Type checking

After type checking, a parser block statement is represented in  $P4_{IR}$  as:

```
parserBlockStatementIR
: annotationList `{ parserStatementListIR }
;
```

**Typing**  $annotationList \{ parserStatementList \}$ , under context  $TC_0$ :

1. Let  $TC_1$  be  $TC_0$  with a new local frame.
2. Let context  $TC_2$  and typed parser statements  $parserStatementList^*$  be
  - the result of **typing**  $parserStatementList$ , under context  $TC_1$ .
3. Let  $TC_3$  be  $TC_2$  with the innermost frame removed.
4. Let  $parserBlockStatementIR$  be  $annotationList \{ parserStatementList^* \}$ .
5. Result in context  $TC_1$  and typed parser statement  $parserBlockStatementIR$ .

### 15.4.8.2. Compile-time evaluation

**Compile-time evaluation of**  $annotationList \{ parserStatementListIR \}$ , under context  $IC_0$  and store  $STO$ :

1. Let context  $IC_1$  and store  $STO_1$  be
  - the result of **compile-time evaluation of**  $parserStatementListIR$ , under context  $IC_0$  and store  $STO$ .
2. Let  $parserBlockStatementIR_{inst}$  be  $annotationList \{ parserStatementListIR_{inst} \}$ .
3. Result in context  $IC_1$  and store  $STO_1$ .

### 15.4.8.3. Runtime evaluation

**Runtime evaluation of**  $annotationList \{ parserStatementListIR \}$ , under context  $EC_0$  and state  $ARCH$ :

1. Let  $EC_1$  be  $EC_0$  with a new local frame.
2. Let context  $EC_2$ , state  $ARCH_1$ , and  $parserStatementResult$  be
  - the result of **runtime evaluation of**  $parserStatementListIR$ , under context  $EC_1$  and state  $ARCH$ .

3. Let  $EC_3$  be  $EC_2$  with the innermost frame removed.
4. Result in context  $EC_3$ , state  $ARCH_1$ , and  $parserStatementResult$ .

## 15.4.9. Conditional statement

A parser conditional statement is defined as:

```
parserConditionalStatement
: IF ` ( expression ) parserStatement
| IF ` ( expression ) parserStatement ELSE parserStatement
;
```

It is similar to a conditional statement explained in [Section 13.9](#), but it can only contain parser statements in its branches.

### 15.4.9.1. Type checking

After type checking, a parser conditional statement is represented in  $P4_{IR}$  as:

```
parserConditionalStatementIR
: IF ` ( typedExpressionIR ) parserStatementIR
| IF ` ( typedExpressionIR ) parserStatementIR ELSE parserStatementIR
;
```

Typing  $parserConditionalStatement$ , under context  $TC_0$ :

1. If let  $IF ( expression_{cond} ) parserStatement_{then}$  be  $parserConditionalStatement$ :
  - a. Let  $typedExpressionIR_{cond}$  be
    - the result of typing  $expression_{cond}$ , under cursor LOCAL and context  $TC_0$ .
  - b. Let  $typeIR_{cond}$  be the type of  $typedExpressionIR_{cond}$ .
  - c. Check that **BOOL** is equal to  $typeIR_{cond}$  with typedefs unrolled.
  - d. Let context  $TC_{then}$  and typed parser statement  $parserStatementIR_{then}$  be
    - the result of typing  $parserStatement_{then}$ , under context  $TC_0$ .
  - e. Result in context  $TC_0$  and typed parser statement  $IF ( typedExpressionIR_{cond} ) parserStatementIR_{then}$ .
2. Else:
  - a. Let  $IF ( expression_{cond} ) parserStatement_{then} ELSE parserStatement_{else}$  be  $parserConditionalStatement$ .
  - b. Let  $typedExpressionIR_{cond}$  be
    - the result of typing  $expression_{cond}$ , under cursor LOCAL and context  $TC_0$ .
  - c. Let  $typeIR_{cond}$  be the type of  $typedExpressionIR_{cond}$ .
  - d. Check that **BOOL** is equal to  $typeIR_{cond}$  with typedefs unrolled.
  - e. Let context  $TC_{then}$  and typed parser statement  $parserStatementIR_{then}$  be
    - the result of typing  $parserStatement_{then}$ , under context  $TC_0$ .
  - f. Let context  $TC_{else}$  and typed parser statement  $parserStatementIR_{else}$  be
    - the result of typing  $parserStatement_{else}$ , under context  $TC_0$ .

g. Result in context  $TC_0$  and typed parser statement IF ( typedExpressionIR<sub>cond</sub> ) parserStatementIR<sub>then</sub>  
ELSE parserStatementIR<sub>else</sub>.

### 15.4.9.2. Compile-time evaluation

Compile-time evaluation of parserConditionalStatementIR, under context  $IC_0$  and store STO:

1. If let IF ( typedExpressionIR<sub>cond</sub> ) parserStatementIR<sub>then</sub> be parserConditionalStatementIR:
  - a. Let context  $IC_{then}$  and store  $STO_1$  be
    - the result of compile-time evaluation of parserStatementIR<sub>then</sub>, under context  $IC_0$  and store  $STO$ .
  - b. Result in context  $IC_0$  and store  $STO_1$ .
2. Else:
  - a. Let IF ( typedExpressionIR<sub>cond</sub> ) parserStatementIR<sub>then</sub> ELSE parserStatementIR<sub>else</sub> be parserConditionalStatementIR.
  - b. Let context  $IC_{then}$  and store  $STO_1$  be
    - the result of compile-time evaluation of parserStatementIR<sub>then</sub>, under context  $IC_0$  and store  $STO$ .
  - c. Let context  $IC_{else}$  and store  $STO_2$  be
    - the result of compile-time evaluation of parserStatementIR<sub>else</sub>, under context  $IC_0$  and store  $STO_1$ .
  - d. Result in context  $IC_0$  and store  $STO_2$ .

### 15.4.9.3. Runtime evaluation

Runtime evaluation of parserConditionalStatementIR, under context  $EC_0$  and state ARCH:

1. If let IF ( typedExpressionIR<sub>cond</sub> ) parserStatementIR<sub>then</sub> be parserConditionalStatementIR:
  - a. Let context  $EC_{cond}$ , state  $ARCH_{cond}$  and expressionResult be
    - the result of evaluating typedExpressionIR<sub>cond</sub>, under cursor LOCAL, context  $EC_0$ , and state  $ARCH$ .
  - b. If let rejectTransitionResult be expressionResult:
    - i. Result in context  $EC_{cond}$ , state  $ARCH_{cond}$  and rejectTransitionResult.
  - c. If expressionResult is equal to `B true:
    - i. Let context  $EC_{then}$ , state  $ARCH_{then}$ , and parserStatementResult be
      - the result of runtime evaluation of parserStatementIR<sub>then</sub>, under context  $EC_{cond}$  and state  $ARCH_{cond}$ .
    - ii. Result in context  $EC_{then}$ , state  $ARCH_{then}$ , and parserStatementResult.
  - d. If expressionResult is equal to `B false:
    - i. Result in context  $EC_{cond}$ , state  $ARCH_{cond}$  and `EMPTY.
2. Else:
  - a. Let IF ( typedExpressionIR<sub>cond</sub> ) parserStatementIR<sub>then</sub> ELSE parserStatementIR<sub>else</sub> be

parserConditionalStatementIR.

- b. Let context  $EC_{cond}$ , state  $ARCH_{cond}$  and expressionResult be
  - the result of evaluating typedExpressionIR<sub>cond</sub>, under cursor LOCAL, context  $EC_0$ , and state  $ARCH$ .
- c. If expressionResult is equal to `B true`:
  - i. Let context  $EC_{then}$ , state  $ARCH_{then}$ , and parserStatementResult be
    - the result of runtime evaluation of parserStatementIR<sub>then</sub>, under context  $EC_{cond}$  and state  $ARCH_{cond}$ .
  - ii. Result in context  $EC_{then}$ , state  $ARCH_{then}$ , and parserStatementResult.
- d. If expressionResult is equal to `B false`:
  - i. Let context  $EC_{else}$ , state  $ARCH_{else}$ , and parserStatementResult be
    - the result of runtime evaluation of parserStatementIR<sub>else</sub>, under context  $EC_{cond}$  and state  $ARCH_{cond}$ .
  - ii. Result in context  $EC_{else}$ , state  $ARCH_{else}$ , and parserStatementResult.

## 15.5. Parser transition statements

The last statement in a parser state is an optional **transition** statement, which transfers control to another state, possibly **accept** or **reject**. A **transition** statements is written using the following syntax:

```
transitionStatement
: /* empty */
| TRANSITION stateExpression
;

stateExpression
: name ;
| selectExpression
;
```

The execution of the transition statement causes **stateExpression** to be evaluated, and transfers control to the resulting state.

In terms of the **ParserModel**, the semantics of a **transition** statement can be formalized as follows:

```
goto eval(stateExpression)
```

For example, this statement:

```
transition accept;
```

terminates execution of the current parser and transitions immediately to the **accept** state.

If the body of a state block does not end with a **transition** statement, the implied statement is:

```
transition reject;
```

See [Section 15.6](#) for description of the `select` expression that can be used as the `stateExpression` in a `transition` statement.

### 15.5.1. Type checking

Parser transition statements are type-checked as follows:

`ParserTransition_ok`:

- Typing `transitionStatement`, under context `typingContext` and parser state names `nameIR*`:
- Result in typed transition statement `transitionStatementIR`.

Typing `transitionStatement`, under context `TC0` and parser state names `nameIRstate*`:

1. If `transitionStatement` is `EMPTY`:
  - a. Result in typed transition statement `TRANSITION "reject" ;`.
2. Else:
  - a. Let `TRANSITION stateExpression` be `transitionStatement`.
  - b. If let `name ;` be `stateExpression`:
    - i. Let `nameIR` be the name of `name`.
    - ii. Check that `nameIR` is in `nameIRstate*`.
    - iii. Let `transitionStatementIR` be `TRANSITION nameIR ;`.
    - iv. Result in typed transition statement `transitionStatementIR`.
  - c. Else:
    - i. Let `selectExpression` be `stateExpression`.
    - ii. Let typed transition statement `selectExpressionIR` be
      - the result of typing `selectExpression`, under context `TC0` and parser state names `nameIRstate*`.
    - iii. Result in typed transition statement `TRANSITION selectExpressionIR`.

After type checking, transition statements are represented in `P4IR` as:

```
transitionStatementIR
: TRANSITION stateExpressionIR
;

stateExpressionIR
: nameIR ;
| selectExpressionIR
;
```

### 15.5.2. Runtime evaluation

`ParserTransition_eval`:

- Runtime evaluation of `transitionStatementIR`, under context `evalContext` and state `arch`:
- Result in context `evalContext`, state `arch`, and `transitionResult`.

Runtime evaluation of `TRANSITION stateExpressionIR`, under context `evalContext` and state `arch`:

1. If let `nameIR` ; be `stateExpressionIR`:
  - a. If `nameIR` is equal to "accept":
    - i. Result in context `evalContext`, state `arch`, and `ACCEPT`.
  - b. Else if `nameIR` is equal to "reject":
    - i. Let `errorValue` be `ERROR` . "NoError".
    - ii. Result in context `evalContext`, state `arch`, and `REJECT errorValue`.
  - c. If `nameIR` is not equal to "accept" and `nameIR` is not equal to "reject":
    - i. Result in context `evalContext`, state `arch`, and `STATE nameIR`.
2. Else:
  - a. Let `selectExpressionIR` be `stateExpressionIR`.
  - b. Let context `EC1`, state `ARCH1`, and `transitionResult` be
    - the result of runtime evaluation of `selectExpressionIR`, under context `evalContext` and state `arch`.
  - c. Result in context `EC1`, state `ARCH1`, and `transitionResult`.

## 15.6. Parser select expression

A `select` expression evaluates to a state. The syntax for a `select` expression is as follows:

```
selectExpression
: SELECT `( expressionList ) `{ selectCaseList }
;

selectCaseList
: /* empty */
| selectCaseList selectCase
;

selectCase
: keysetExpression : name ;
;
```

Each expression in the `expressionList` must have a set type, or a type that can be nested in a set type.

In terms of the `ParserModel`, the meaning of a select expression:

```
select(e) {
  ks[0]: s[0];
  ks[1]: s[1];
  /* more labels omitted */
  ks[n-2]: s[n-1];
  _ : sd; // ks[n-1] is default
}
```

is defined in pseudo-code as:

```
key = eval(e);
for (int i=0; i < n; i++) {
    keyset = eval(ks[i]);
    if (keyset.contains(key)) return s[i];
}
verify(false, error.NoMatch);
```

Some targets may require that all keyset expressions in a select expression be compile-time known values. Keysets are evaluated in order, from top to bottom as implied by the pseudo-code above; the first keyset that includes the value in the `select` argument provides the result state. If no label matches, the execution triggers a runtime error with the standard error code `error.NoMatch`.

Note that this implies that all cases after a `default` or `_` label are unreachable; the compiler should emit a warning if it detects unreachable cases. This constitutes an important difference between `select` expressions and the `switch` statements found in many programming languages since the keysets of a `select` expression may "overlap".

The typical way to use a `select` expression is to compare the value of a recently-extracted header field against a set of values, as in the following example:

```
header IPv4_h { bit<8> protocol; /* more fields omitted */ }
struct P { IPv4_h ipv4; /* more fields omitted */ }
P headers;
select (headers.ipv4.protocol) {
    8w6 : parse_tcp;
    8w17 : parse_udp;
    _ : accept;
}
```

For example, to detect TCP reserved ports (< 1024) one could write:

```
select (p.tcp.port) {
    16w0 &&& 16w0xFC00: well_known_port;
    _: other_port;
}
```

The expression `16w0 &&& 16w0xFC00` describes the set of 16-bit values whose most significant six bits are zero.

Some targets may support parser value sets; see [Section 10.7](#). Given a type `T` for the type parameter of the value set, the type of the value set is `set<T>`. The type of the value set must match to the type of all other `keysetExpressions` in the same `select` expression. If there is a mismatch, the compiler must raise an error. The type of the values in the set must be either `bit<>`, `int<>`, `tuple`, `struct`, or serializable `enum`.

For example, to allow the control plane API to specify TCP reserved ports at runtime, one could write:

```
struct vsk_t {
    @match(ternary)
    bit<16> port;
}
value_set<vsk_t>(4) pvs;
select (p.tcp.port) {
    pvs: runtime_defined_port;
    _: other_port;
}
```

The above example allows the runtime API to populate up to 4 different `keysetExpressions` in the `value_set`. If the `value_set` takes a struct as type parameter, the runtime API can use the struct field names to name the objects in the value set. The match type of the struct field is specified with the `@match` annotation. If the `@match` annotation is not specified on a struct field, by default it is assumed to be `@match(exact)`. A single non-exact field must be placed into a struct by itself, with the desired `@match` annotation.

### 15.6.1. Type checking

A select expression is type checked as follows:

**ParserSelect\_ok:**

- Typing `selectExpression`, under context `typingContext` and parser state names `nameIR*`:
- Result in typed transition statement `selectExpressionIR`.

**Typing** `SELECT ( expressionListkey ) { selectCaseList }`, under context `TC0` and parser state names `nameIRstate*`:

1. Let `expressionkey*` be the list of expressions in `expressionListkey`.
2. Let `typedExpressionIRkey*` be the list of `typedExpressionIRkey`, obtained by repeating:
  - Let `typedExpressionIRkey` be
    - the result of typing `expressionkey`, under cursor `LOCAL` and context `TC0`.
 for each `expressionkey` in `expressionkey*`
3. Let `typedExpressionIRkey_reduced*` be the list of `typedExpressionIRkey_reduced`, obtained by repeating:
  - Let `typedExpressionIRkey_reduced` be `typedExpressionIRkey` with surrounding serializable enums reduced.
 for each `typedExpressionIRkey` in `typedExpressionIRkey*`
4. Let `typeIRkey_reduced*` be the list of `typeIRkey_reduced`, obtained by repeating:
  - Let `typeIRkey_reduced` be the type of `typedExpressionIRkey_reduced`.
 for each `typedExpressionIRkey_reduced` in `typedExpressionIRkey_reduced*`
5. Let `bound` be bound type variables from the `LOCAL` layer of `TC0`.
6. Check that `SET < typeIRkey_reduced >` is a well-formed type, with bound type variables `bound`, for all `typeIRkey_reduced` in `typeIRkey_reduced*`.
7. Let `selectCase*` be the list of select cases in `selectCaseList`.
8. Let `selectCaseIR*` be the list of `selectCaseIR`, obtained by repeating:
  - Let `selectCaseIR` be
    - the result of typing `selectCase` under context `TC0` with states `nameIRstate*` and key types `typeIRkey_reduced*`.
 for each `selectCase` in `selectCase*`
9. Let `selectExpressionIR` be `SELECT ( typedExpressionIRkey_reduced* ) { selectCaseIR* }`.



## 10. Result in typed transition statement `selectExpressionIR`.

The type checking of a select case visits its keyset expressions, and each simple keyset expression is visited in turn.

### SelectCase\_ok:

- Typing `selectCase` under context `typingContext` with states `nameIR*` and key types `typeIR*`:
- Result in `selectCaseIR`.

### Typing `keysetExpression : name ;` under context `TC` with states `nameIRstate*` and key types `typeIRkey*`:

1. Let `keysetExpressionIR` be
  - the result of typing `keysetExpression` under context `TC` with key types `typeIRkey*`.
2. Let `nameIR` be the name of `name`.
3. Check that `nameIR` is in `nameIRstate*`.
4. Result in `keysetExpressionIR : nameIR ;`.

A keyset expression is type checked with the relation:

```
keysetExpression
: simpleKeysetExpression
| tupleKeysetExpression
;
```

### SelectCase\_keyset\_ok:

- Typing `keysetExpression` under context `typingContext` with key types `typeIR*`:
- Result in `keysetExpressionIR`.

A simple keyset expression is type checked as follows:

```
simpleKeysetExpression
: expression
| expression &&& expression
| expression .. expression
| DEFAULT
| _
;
```

### SelectCase\_keyset\_simple\_ok:

- Typing `simpleKeysetExpression` under context `typingContext` with key type `typeIR`:
- Result in `simpleKeysetExpressionIR`.

## Expression keys

Typing expression under context TC with key type  $\text{typeIR}_{\text{key}}$ :

1. Let  $\text{typedExpressionIR}$  be
  - the result of typing expression, under cursor LOCAL and context TC.
2. Let  $\text{typeIR}$  be the type of  $\text{typedExpressionIR}$ .
3. Let  $\text{typeIR}'$  be  $\text{typeIR}$  with typedefs unrolled.
4. If let  $\text{SET} < \text{typeIR}_{\text{base}} >$  be  $\text{typeIR}'$ :
  - a. If  $\text{typeIR}_{\text{base}}$  and  $\text{typeIR}_{\text{key}}$  are the same type:
    - i. Result in  $\text{typedExpressionIR}$ .
  - b. Else:
    - i. Check that  $\text{typeIR}_{\text{base}}$  can be implicitly cast to  $\text{typeIR}_{\text{key}}$ .
    - ii. Let  $\text{typeIR}_{\text{cast}}$  be  $\text{SET} < \text{typeIR}_{\text{key}} >$ .
    - iii. Let  $\text{typedExpressionIR}_{\text{cast}}$  be (  $\text{typeIR}_{\text{cast}}$  )  $\text{typedExpressionIR}$  annotated with a pair of type  $\text{typeIR}_{\text{cast}}$  and compile-time known-ness DYN.
    - iv. Result in  $\text{typedExpressionIR}_{\text{cast}}$ .
5. Else:
  - a. Check that  $\text{typeIR}$  can be implicitly cast to  $\text{typeIR}_{\text{key}}$ .
  - b. Let  $\text{typeIR}_{\text{cast}}$  be  $\text{SET} < \text{typeIR}_{\text{key}} >$ .
  - c. Let  $\text{typedExpressionIR}_{\text{cast}}$  be (  $\text{typeIR}_{\text{cast}}$  )  $\text{typedExpressionIR}$  annotated with a pair of type  $\text{typeIR}_{\text{cast}}$  and compile-time known-ness DYN.
  - d. Result in  $\text{typedExpressionIR}_{\text{cast}}$ .

## Mask keys

Typing  $\text{expression}_l \&\&\& \text{expression}_r$  under context TC with key type  $\text{typeIR}_{\text{key}}$ :

1. Let  $\text{typedExpressionIR}_l$  be
  - the result of typing  $\text{expression}_l$ , under cursor LOCAL and context TC.
2. Let  $\text{typedExpressionIR}_r$  be
  - the result of typing  $\text{expression}_r$ , under cursor LOCAL and context TC.
3. Let (  $\text{typedExpressionIR}_{l_{\text{cast}}}$ ,  $\text{typedExpressionIR}_{r_{\text{cast}}}$  ) be !  $\text{typedExpressionIR}_l$  and  $\text{typedExpressionIR}_r$  implicitly cast to equal types.
4. Let (  $\text{typedExpressionIR}_{l_{\text{reduced}}}$ ,  $\text{typedExpressionIR}_{r_{\text{reduced}}}$  ) be ! the result of reducing serializable enums in  $\text{typedExpressionIR}_{l_{\text{cast}}}$  and  $\text{typedExpressionIR}_{r_{\text{cast}}}$  until  $\$ \text{compat\_mask}$  is satisfied.
5. Let  $\text{typeIR}_{\text{reduced}}$  be the type of  $\text{typedExpressionIR}_{l_{\text{reduced}}}$ .
6. Let  $\text{typedExpressionIR}_{l_{\text{casted}}}$  be !  $\text{typedExpressionIR}_{l_{\text{reduced}}}$  implicitly cast to  $\text{typeIR}_{\text{key}}$ .
7. Let  $\text{typedExpressionIR}_{r_{\text{casted}}}$  be !  $\text{typedExpressionIR}_{r_{\text{reduced}}}$  implicitly cast to  $\text{typeIR}_{\text{key}}$ .
8. Result in  $\text{typedExpressionIR}_{l_{\text{casted}}} \&\&\& \text{typedExpressionIR}_{r_{\text{casted}}}$ .

## Range keys

Typing  $\text{expression}_l \dots \text{expression}_r$  under context  $TC$  with key type  $\text{typeIR}_{\text{key}}$ :

1. Let  $\text{typedExpressionIR}_l$  be
  - the result of typing  $\text{expression}_l$ , under cursor  $LOCAL$  and context  $TC$ .
2. Let  $\text{typedExpressionIR}_r$  be
  - the result of typing  $\text{expression}_r$ , under cursor  $LOCAL$  and context  $TC$ .
3. Let  $(\text{typedExpressionIR}_{l\_cast}, \text{typedExpressionIR}_{r\_cast})$  be !  $\text{typedExpressionIR}_l$  and  $\text{typedExpressionIR}_r$  implicitly cast to equal types.
4. Let  $(\text{typedExpressionIR}_{l\_reduced}, \text{typedExpressionIR}_{r\_reduced})$  be ! the result of reducing serializable enums in  $\text{typedExpressionIR}_{l\_cast}$  and  $\text{typedExpressionIR}_{r\_cast}$  until  $\$compat\_range$  is satisfied.
5. Let  $\text{typeIR}_{reduced}$  be the type of  $\text{typedExpressionIR}_{l\_reduced}$ .
6. Check that  $\text{typeIR}_{reduced}$  is equal to the type of  $\text{typedExpressionIR}_{r\_reduced}$ .
7. Let  $\text{typedExpressionIR}_{l\_casted}$  be !  $\text{typedExpressionIR}_{l\_reduced}$  implicitly cast to  $\text{typeIR}_{\text{key}}$ .
8. Let  $\text{typedExpressionIR}_{r\_casted}$  be !  $\text{typedExpressionIR}_{r\_reduced}$  implicitly cast to  $\text{typeIR}_{\text{key}}$ .
9. Result in  $\text{typedExpressionIR}_{l\_casted} \dots \text{typedExpressionIR}_{r\_casted}$ .

## Default and don't care keys

Typing  $DEFAULT$  under context  $TC$  with key type  $\text{typeIR}_{\text{key}}$ :

1. Result in  $DEFAULT$ .

Typing  $\_$  under context  $TC$  with key type  $\text{typeIR}_{\text{key}}$ :

1. Result in  $\_$ .

## 15.6.2. Runtime evaluation

The runtime evaluation of a select expression is defined as follows:

$\text{ParserSelect\_eval}$ :

- Runtime evaluation of  $\text{selectExpressionIR}$ , under context  $\text{evalContext}$  and state  $\text{arch}$ :
- Result in context  $\text{evalContext}$ , state  $\text{arch}$ , and  $\text{transitionResult}$ .

Runtime evaluation of  $\text{selectExpressionIR}$ , under context  $EC_0$  and state  $ARCH_0$ :

1. Let  $SELECT(\text{typedExpressionIR}_{\text{key}}^*) \{ \text{selectCaseListIR} \}$  be  $\text{selectExpressionIR}$ .
2. Let context  $EC_1$ , state  $ARCH_1$ , and  $\text{expressionListResult}$  be
  - the result of evaluating  $\text{typedExpressionIR}_{\text{key}}^*$ , under cursor  $LOCAL$ , context  $EC_0$ , and state  $ARCH_0$ .

3. If let `rejectTransitionResult` be `expressionListResult`:
  - a. Result in context `EC1`, state `ARCH1`, and `rejectTransitionResult`.
4. Else if let `valuekey*` be `expressionListResult`:
  - a. Let the updated context `EC2`, state `ARCH2`, and `selectCaseMatchResult` be
    - the result of `matching valuekey*` against `selectCaseListIR` under context `EC1` and state `ARCH1`.
  - b. If let `rejectTransitionResult` be `selectCaseMatchResult`:
    - i. Result in context `EC2`, state `ARCH2`, and `rejectTransitionResult`.
  - c. Else:
    - i. Let `nameIRstate'` be `selectCaseMatchResult`.
    - ii. If `·` is equal to `nameIRstate'`:
      - A. Let `rejectTransitionResult` be `REJECT ERROR . "NoMatch"`.
      - B. Result in context `EC2`, state `ARCH2`, and `rejectTransitionResult`.
    - iii. If let `nameIRstate'` be `nameIRstate'`:
      - A. Let context `EC3`, state `ARCH3`, and `transitionResult` be
        - the result of `runtime evaluation of TRANSITION nameIRstate' ;` under context `EC2` and state `ARCH2`.
      - B. Result in context `EC3`, state `ARCH3`, and `transitionResult`.

Matching against select cases is defined as follows:

`SelectCases_match`:

- Matching `value*` against `selectCaseListIR` under context `evalContext` and state `arch`:
- Result in the updated context `evalContext`, state `arch`, and `selectCaseMatchResult`.

The result of matching a select case is defined as follows:

```
selectCaseMatchResult
: continueResult<nameIR?>
| rejectTransitionResult
;
```

`Matching valuekey*` against `selectCaseIR*` under context `evalContext` and state `arch`:

1. If `selectCaseIR*` is equal to `·`:
  - a. Result in the updated context `evalContext`, state `arch`, and `·`.
2. If let `selectCaseIRn :: selectCaseIRt*` be `selectCaseIR*`:
  - a. Let the updated context `EC1`, state `ARCH1`, and `selectCaseMatchResult` be
    - the result of `matching valuekey*` against `selectCaseIRn` under context `evalContext` and state `arch`.
  - b. If let `rejectTransitionResult` be `selectCaseMatchResult`:
    - i. Result in the updated context `EC1`, state `ARCH1`, and `rejectTransitionResult`.

- c. Else:
  - i. Let  $\text{nameIR}^?$  be  $\text{selectCaseMatchResult}$ .
  - ii. Check that  $\text{nameIR}^?$  is defined.
  - iii. Let  $\text{nameIR}_{\text{state}}$  be  $\text{nameIR}^?$ .
  - iv. Result in the updated context  $\text{EC}_1$ , state  $\text{ARCH}_1$ , and  $\text{nameIR}_{\text{state}}$ .
- d. If  $\text{selectCaseMatchResult}$  is equal to  $\cdot$ :
  - i. Let the updated context  $\text{EC}_2$ , state  $\text{ARCH}_2$ , and  $\text{selectCaseMatchResult}'$  be
    - the result of **matching**  $\text{value}_{\text{key}}$  **against**  $\text{selectCaseIR}_t$  **under context**  $\text{EC}_1$  **and state**  $\text{ARCH}_1$ .
  - ii. Result in the updated context  $\text{EC}_2$ , state  $\text{ARCH}_2$ , and  $\text{selectCaseMatchResult}'$ .

The matching of a select case is defined as follows:

#### SelectCase\_match:

- Matching  $\text{value}^*$  against  $\text{selectCaseIR}$  under context  $\text{evalContext}$  and state  $\text{arch}$ :
- Result in the updated context  $\text{evalContext}$ , state  $\text{arch}$ , and  $\text{selectCaseMatchResult}$ .

#### Matching $\text{value}_{\text{key}}$ **against** $\text{keysetExpressionIR} : \text{nameIR}$ ; **under context** $\text{EC}_0$ **and state** $\text{ARCH}_0$ :

1. Let context  $\text{EC}_1$ , state  $\text{ARCH}_1$ , and result  $\text{keysetExpressionResult}$  be
  - the result of **evaluating**  $\text{keysetExpressionIR}$ , **under context**  $\text{EC}_0$ , **and state**  $\text{ARCH}_0$ .
2. If let  $\text{rejectTransitionResult}$  be  $\text{keysetExpressionResult}$ :
  - a. Result in the updated context  $\text{EC}_1$ , state  $\text{ARCH}_1$ , and  $\text{rejectTransitionResult}$ .
3. Else if let  $\text{setValue}^*$  be  $\text{keysetExpressionResult}$ :
  - a. If  $\text{value}_{\text{key}}$  **does not match**  $\text{setValue}^*$ :
    - i. Result in the updated context  $\text{EC}_1$ , state  $\text{ARCH}_1$ , and  $\cdot$ .
  - b. Else:
    - i. Result in the updated context  $\text{EC}_1$ , state  $\text{ARCH}_1$ , and  $\text{nameIR}$ .

## 15.7. **verify**

The **verify** statement provides a simple form of error handling. **verify** can only be invoked within a parser; it is used syntactically as if it were a function with the following signature:

```
extern void verify(in bool condition, in error err);
```

If the first argument is **true**, then executing the statement has no side-effect. However, if the first argument is **false**, it causes an immediate transition to **reject**, which causes immediate parsing termination; at the same time, the **parserError** associated with the parser is set to the value of the second argument.

In terms of the **ParserModel** the semantics of a **verify** statement is given by:

```

ParserModel.verify(bool condition, error err) {
    if (condition == false) {
        ParserModel.parserError = err;
        goto reject;
    }
}

```

## 15.8. Packet data extraction

The P4 core library contains the following declaration of a built-in `extern` type called `packet_in` that represents incoming network packets. The `packet_in` extern is special: it cannot be instantiated by the user explicitly. Instead, the architecture supplies a separate instance for each `packet_in` argument to a `parser` instantiation.

```

extern packet_in {
    void extract<T>(out T headerLvalue);
    void extract<T>(out T variableSizeHeader, in bit<32> varFieldSizeBits);
    T lookahead<T>();
    bit<32> length(); // This method may be unavailable in some architectures
    void advance(bit<32> bits);
}

```

To extract data from a packet represented by an argument `b` with type `packet_in`, a parser invokes the `extract` methods of `b`. There are two variants of the `extract` method: a one-argument variant for extracting fixed-size headers, and a two-argument variant for extracting variable-sized headers. Because these operations can cause runtime verification failures (see below), these methods can only be executed within parsers.

When extracting data into a bit-string or integer, the first packet bit is extracted to the most significant bit of the integer.

Some targets may perform cut-through packet processing, i.e., they may start processing a packet before its length is known (i.e., before all bytes have been received). On such a target calls to the `packet_in.length()` method cannot be implemented. Attempts to call this method should be flagged as errors (either at compilation time by the compiler back-end, or when attempting to load the compiled P4 program onto a target that does not support this method).

In terms of the `ParserModel`, the semantics of `packet_in` can be captured using the following abstract model of packets:

```

packet_in {
    unsigned nextBitIndex;
    byte[] data;
    unsigned lengthInBits;
    void initialize(byte[] data) {
        this.data = data;
        this.nextBitIndex = 0;
        this.lengthInBits = data.sizeInBytes * 8;
    }
    bit<32> length() { return this.lengthInBits / 8; }
}

```

### 15.8.1. Fixed-width extraction

The single-argument `extract` method handles fixed-width headers, and is declared in P4 as follows:

```
void extract<T>(out T headerLValue);
```

The expression `headerLValue` must evaluate to an l-value (see [Chapter 12](#)) of type `header` with a fixed width. If this method executes successfully, on completion the `headerLValue` is filled with data from the packet and its validity bit is set to `true`. This method may fail in various ways—e.g., if there are not enough bits left in the packet to fill the specified header.

For example, the following program fragment extracts an Ethernet header:

```
struct Result { Ethernet_h ethernet; /* more fields omitted */ }
parser P(packet_in b, out Result r) {
    state start {
        b.extract(r.ethernet);
    }
}
```

In terms of the `ParserModel`, the semantics of the single-argument `extract` is given in terms of the following pseudo-code method, using data from the `packet` class defined above. We use the special `valid$` identifier to indicate the hidden valid bit of a header, `isNext$` to indicate that the l-value was obtained using `next`, and `nextIndex$` to indicate the corresponding header or header union stack properties.

```
void packet_in.extract<T>(out T headerLValue) {
    bitsToExtract = sizeofInBits(headerLValue);
    lastBitNeeded = this.nextBitIndex + bitsToExtract;
    ParserModel.verify(this.lengthInBits >= lastBitNeeded, error.PacketTooShort);
    headerLValue = this.data.extractBits(this.nextBitIndex, bitsToExtract);
    headerLValue.valid$ = true;
    if headerLValue.isNext$ {
        verify(headerLValue.nextIndex$ < headerLValue.size, error.StackOutOfBounds);
        headerLValue.nextIndex$ = headerLValue.nextIndex$ + 1;
    }
    this.nextBitIndex += bitsToExtract;
}
```

## 15.8.2. Variable-width extraction

The two-argument `extract` handles variable-width headers, and is declared in P4 as follows:

```
void extract<T>(out T headerLValue, in bit<32> variableFieldSize);
```

The expression `headerLValue` must be an l-value representing a header that contains **exactly one** `varbit` field. The expression `variableFieldSize` must evaluate to a `bit<32>` value that indicates the number of bits to be extracted into the unique `varbit` field of the header (i.e., this size is not the size of the complete header, just the `varbit` field).

In terms of the `ParserModel`, the semantics of the two-argument `extract` is captured by the following pseudo-code:

```
void packet_in.extract<T>(out T headerLValue,
                          in bit<32> variableFieldSize) {
    // targets are allowed to include the following line, but need not
    // verify(variableFieldSize[2:0] == 0, error.ParserInvalidArgument);
    bitsToExtract = sizeofFixedPart(headerLValue) + variableFieldSize;
    lastBitNeeded = this.nextBitIndex + bitsToExtract;
    ParserModel.verify(this.lengthInBits >= lastBitNeeded, error.PacketTooShort);
    ParserModel.verify(bitsToExtract <= headerLValue.maxSize, error.HeaderTooShort);
}
```

```

headerLvalue = this.data.extractBits(this.nextBitIndex, bitsToExtract);
headerLvalue.varbitField.size = variableFieldSize;
headerLvalue.valid$ = true;
if headerLvalue.isNext$ {
    verify(headerLvalue.nextIndex$ < headerLvalue.size, error.StackOutOfBounds);
    headerLvalue.nextIndex$ = headerLvalue.nextIndex$ + 1;
}
this.nextBitIndex += bitsToExtract;
}

```

The following example shows one way to parse IPv4 options—by splitting the IPv4 header into two separate headers:

```

// IPv4 header without options
header IPv4_no_options_h {
    bit<4>    version;
    bit<4>    ihl;
    bit<8>    diffserv;
    bit<16>   totalLen;
    bit<16>   identification;
    bit<3>    flags;
    bit<13>   fragOffset;
    bit<8>    ttl;
    bit<8>    protocol;
    bit<16>   hdrChecksum;
    bit<32>   srcAddr;
    bit<32>   dstAddr;
}
header IPv4_options_h {
    varbit<320> options;
}

struct Parsed_headers {
    // Some fields omitted
    IPv4_no_options_h ipv4;
    IPv4_options_h    ipv4options;
}

error { InvalidIPv4Header }

parser Top(packet_in b, out Parsed_headers headers) {
    // Some states omitted

    state parse_ipv4 {
        b.extract(headers.ipv4);
        verify(headers.ipv4.ihl >= 5, error.InvalidIPv4Header);
        transition select (headers.ipv4.ihl) {
            5: dispatch_on_protocol;
            _: parse_ipv4_options;
        }
    }

    state parse_ipv4_options {
        // use information in the ipv4 header to compute the number of bits to extract
        b.extract(headers.ipv4options,
            (bit<32>)((bit<16>)headers.ipv4.ihl - 5) * 32));
        transition dispatch_on_protocol;
    }
}

```

### 15.8.3. Lookahead

The `lookahead` method provided by the `packet_in` packet abstraction evaluates to a set of bits from the input packet without advancing the `nextBitIndex` pointer. Similar to `extract`, it will transition to `reject` and set the



error if there are not enough bits in the packet. When `lookahead` returns a value that contains headers (e.g., a header type, or a struct containing headers), the headers values in the returned result are always valid (otherwise `lookahead` must have transitioned to the `reject` state).

The `lookahead` method can be invoked as follows:

```
b.lookahead<T>()
```

where `T` must be a type with fixed width. In case of success the result of the evaluation of `lookahead` returns a value of type `T`.

In terms of the `ParserModel`, the semantics of `lookahead` is given by the following pseudocode:

```
T packet_in.lookahead<T>() {
    bitsToExtract = sizeof(T);
    lastBitNeeded = this.nextBitIndex + bitsToExtract;
    ParserModel.verify(this.lengthInBits >= lastBitNeeded, error.PacketTooShort);
    T tmp = this.data.extractBits(this.nextBitIndex, bitsToExtract);
    return tmp;
}
```

The TCP options example from [Section 8.4.7](#) also illustrates how `lookahead` can be used:

```
state start {
    transition select(b.lookahead<bit<8>>()) {
        0: parse_tcp_option_end;
        1: parse_tcp_option_nop;
        2: parse_tcp_option_ss;
        3: parse_tcp_option_s;
        5: parse_tcp_option_sack;
    }
}

// Some states omitted

state parse_tcp_option_sack {
    bit<8> n = b.lookahead<Tcp_option_sack_top>().length;
    b.extract(vec.next.sack, (bit<32>) (8 * n - 16));
    transition start;
}
```

### 15.8.4. Skipping bits

P4 provides two ways to skip over bits in an input packet without assigning them to a header:

One way is to `extract` to the underscore identifier, explicitly specifying the type of the data:

```
b.extract<T>(_)
```

Another way is to use the `advance` method of the packet when the number of bits to skip is known.

In terms of the `ParserModel`, the meaning of `advance` is given in pseudocode as follows:

```
void packet_in.advance(bit<32> bits) {
    // targets are allowed to include the following line, but need not
    // verify(bits[2:0] == 0, error.ParserInvalidArgument);
}
```

```

lastBitNeeded = this.nextBitIndex + bits;
ParserModel.verify(this.lengthInBits >= lastBitNeeded, error.PacketTooShort);
this.nextBitIndex += bits;
}

```

## 16. Abstract control machine

A control declaration introduces a constructor for a control object. See [Section 10.5](#) and [Section 11.12](#) for details.

```

controlDeclaration
: annotationList CONTROL name typeParameterListOpt `( parameterList )
  constructorParameterListOpt
  `{ controlLocalDeclarationList APPLY controlBody }
;

controlLocalDeclaration
: constantDeclaration
| instantiation
| variableDeclaration
| actionDeclaration
| tableDeclaration
;

controlBody = blockStatement

```

The rest of this section describes the core components of a **control** block.

### 16.1. Match-action pipeline machine

We can describe the computational model of a match-action pipeline, embodied by a control block: the body of the control block is executed, similarly to the execution of a traditional imperative program:

- At runtime, statements within a block are executed in the order they appear in the control block.
- Execution of the **return** statement causes immediate termination of the execution of the current **control** block, and a return to the caller.
- Execution of the **exit** statement causes the immediate termination of the execution of the current **control** block and of all the enclosing caller **control** blocks.
- Applying a **table** executes the corresponding match-action unit.

#### 16.1.1. Sub-controls

P4 allows controls to invoke the services of other controls, similar to subroutines. To invoke the services of another control, it must be first instantiated; the services of an instance are invoked by calling it using its **apply** method.

The following example shows a control invocation:

```

control Callee(inout IPv4 ipv4) { /* body omitted */ }
control Caller(inout Headers h) {
  Callee() instance; // instance of callee
  apply {
    instance.apply(h.ipv4); // invoke control
  }
}

```

}

As with parsers, when a control is instantiated, local instantiations of stateful objects are evaluated recursively. That is, each instantiation of a control has a unique set of local tables, extern objects, inner control instances, etc. Thus, in general, invoking a control instance twice is not the same as invoking two copies of the same control instance. Note however, that local variables do not persist across invocations of the control. This semantics also applies to direct invocation (see [Section 13.5](#)).

When a control is instantiated, all its local declarations of stateful instantiations are evaluated recursively. Each instantiation of a control will have a unique set of local tables, extern objects, and inner control instances. Thus, invoking a control instance twice is different from invoking two control instances each once, where the former accesses the same local stateful constructs while the latter access two different copies.

The exactly-once evaluation only applies to local stateful instantiations. For local variable declarations, whether in the **apply** block or out, and whether with initializers or not, they are always evaluated when a control instance is invoked. That is, local variables in a control never persist across invocations. For variables declared outside the **apply** block, they are evaluated at the beginning of execution.

All the behavior above also applies to direct invocation (see [Section 13.5](#)).

### 16.1.2. Runtime evaluation of a control

At runtime, a control is evaluated by invoking its **apply** method. The following algorithm describes the evaluation of a control apply method invocation:

Calling `controlApplyMethodCallee < typeArgumentListIR > ( argumentListIR )`, under cursor `p`, context `EC0`, and state `ARCH0`:

1. Let `CONTROL _ . APPLY ( parameterListIR # iddefault ) { theta ; frame ; controlLocalDeclarationListIR ; actionDefEnv ; controlBodyIR }` be `controlApplyMethodCallee`.
2. Let `ECcallee_0` be copy of `EC0` from the GLOBAL layer.
3. Let `{ ( callableId : actionDef ) }` be `actionDefEnv`.
4. Let `ECcallee_1` be `ECcallee_0[BLOCK.TYPE = theta][BLOCK.FRAME = frame]` with `BLOCK.CALLABLE` set to `{ ( callableId : actionDef ) }`.
5. Let `GIVEN parameterIRaligned * DEFAULT parameterIRdefault *` be aligning `parameterListIR` with `argumentListIR` where defaults are `iddefault *` and optionals are `.`.
6. Let `pshared` be GLOBAL.
7. Let state `ARCH1`, caller's context `EC1`, callee's context `ECcallee_2`, and copy-in result `copyInResult` be
  - the result of copy-in from `argumentListIR` in BLOCK layer of `ECcallee_1` to `parameterIRaligned *` in `p` layer of `EC0`, under cursor `pshared` and state `ARCH0`.
8. If let `exitResult` be `copyInResult`:
  - a. Result in context `EC1`, state `ARCH1`, and call result `EXIT`.
9. Else if let `storageReference??` be `copyInResult`:
  - a. Let `ECcallee_3` be
    - the result of copying defaults for `parameterIRdefault *`, under context BLOCK and context `ECcallee_2`.
  - b. Let context `ECcallee_4`, state `ARCH2`, and result `controlLocalDeclarationResult` be
    - the result of evaluating `controlLocalDeclarationListIR`, under context `ECcallee_3`, and state `ARCH1`.

- c. If let `exitResult` be `controlLocalDeclarationResult`:
- i. Let `EC2` be
    - the result of `copy-out from parameterIRaligned* in p layer of EC1 to storageReference?* in BLOCK layer of ECcallee_4, under cursor pshared and state ARCH2.`
  - ii. Result in context `EC2`, state `ARCH2`, and call result `EXIT`.
- d. Else:
- i. Let `continueEmptyResult` be `controlLocalDeclarationResult`.
  - ii. Let context `ECcallee_5`, state `ARCH3`, and result `controlBodyResult` be
    - the result of `evaluating controlBodyIR, under context ECcallee_4 and state ARCH2.`
  - iii. If let `exitResult` be `controlBodyResult`:
    - A. Let `EC2` be
      - the result of `copy-out from parameterIRaligned* in p layer of EC1 to storageReference?* in BLOCK layer of ECcallee_5, under cursor pshared and state ARCH3.`
    - B. Result in context `EC2`, state `ARCH3`, and call result `EXIT`.
  - iv. If `controlBodyResult` is equal to `RETURN` .:
    - A. Let `EC2` be
      - the result of `copy-out from parameterIRaligned* in p layer of EC1 to storageReference?* in BLOCK layer of ECcallee_5, under cursor pshared and state ARCH3.`
    - B. Result in context `EC2`, state `ARCH3`, and call result `RETURN` .

## 16.2. Control local declarations

Control local declarations are defined as follows:

```
controlLocalDeclaration
: constantDeclaration
| instantiation
| variableDeclaration
| actionDeclaration
| tableDeclaration
;

controlLocalDeclarationList
: /* empty */
| controlLocalDeclarationList controlLocalDeclaration
;
```

### 16.2.1. Semantics of parser local declarations

#### 16.2.1.1. Type checking

`ControlLocalDecl_ok`:

- Typing `controlLocalDeclaration`, under context `typingContext`:
- Result in context `typingContext` and `controlLocalDeclarationIR`.

After type checking, control local declarations are represented in  $P4_{IR}$  as follows:

```
controlLocalDeclarationIR
: constantDeclarationIR
| instantiationIR
| variableDeclarationIR
| actionDeclarationIR
| tableDeclarationIR
;
```

A list of control local declarations is type checked by:

**ControlLocalDeclList\_ok:**

- Typing `controlLocalDeclarationList`, under context `typingContext`:
- Result in context `typingContext` and `controlLocalDeclarationIR*`.

**Typing `controlLocalDeclarationList`, under context  $TC_0$ :**

1. Let `controlLocalDeclaration*` be the list of control local declarations in `controlLocalDeclarationList`.
2. Let the updated context  $TC_1$  and the typed control local declarations `controlLocalDeclarationIR*` be
  - the result of typing `controlLocalDeclaration*`, under context  $TC_0$ .
3. Result in context  $TC_1$  and `controlLocalDeclarationIR*`.

**ControlLocalDecls\_ok:**

- Typing `controlLocalDeclaration*`, under context `typingContext`:
- Result in the updated context `typingContext` and the typed control local declarations `controlLocalDeclarationIR*`.

**Typing `controlLocalDeclaration*`, under context `typingContext`:**

1. If `controlLocalDeclaration*` is equal to `.`:
  - a. Result in the updated context `typingContext` and the typed control local declarations `.`
2. If let `controlLocalDeclarationn :: controlLocalDeclarationt*` be `controlLocalDeclaration*`:
  - a. Let context  $TC_1$  and `controlLocalDeclarationIRn` be
    - the result of typing `controlLocalDeclarationn`, under context `typingContext`.
  - b. Let the updated context  $TC_2$  and the typed control local declarations `controlLocalDeclarationIRt*` be
    - the result of typing `controlLocalDeclarationt*`, under context  $TC_1$ .
  - c. Result in the updated context  $TC_2$  and the typed control local declarations `controlLocalDeclarationIRn :: controlLocalDeclarationIRt*`.

#### 16.2.1.2. Compile-time evaluation

#### ControlLocalDecl\_inst:

- Compile-time evaluation of `controlLocalDeclarationIR`, under context `instContext` and store `store`:
- Result in context `instContext`, store `store`, and `controlLocalDeclarationIR`?

A list of control local declarations is compile-time evaluated by:

#### ControlLocalDecls\_inst:

- Compile-time evaluation of `controlLocalDeclarationIR*`, under context `instContext` and store `store`:
- Result in context `instContext`, store `store`, and `controlLocalDeclarationIR*`.

#### Compile-time evaluation of `controlLocalDeclarationIR*`, under context `instContext` and store `store`:

1. If `controlLocalDeclarationIR*` is equal to `.`:
  - a. Result in context `instContext`, store `store`, and `.`
2. If let `controlLocalDeclarationIRh :: controlLocalDeclarationIRt*` be `controlLocalDeclarationIR*`:
  - a. Let context `IC1`, store `STO1`, and `controlLocalDeclarationIR?` be
    - the result of compile-time evaluation of `controlLocalDeclarationIRh`, under context `instContext` and store `store`.
  - b. If `controlLocalDeclarationIR?` is none:
    - i. Let context `IC2`, store `STO2`, and `controlLocalDeclarationIRt_inst*` be
      - the result of compile-time evaluation of `controlLocalDeclarationIRt*`, under context `IC1` and store `STO1`.
    - ii. Result in context `IC2`, store `STO2`, and `controlLocalDeclarationIRt_inst*`.
  - c. Else:
    - i. Let `controlLocalDeclarationIRh_inst` be `controlLocalDeclarationIR?`.
    - ii. Let context `IC2`, store `STO2`, and `controlLocalDeclarationIRt_inst*` be
      - the result of compile-time evaluation of `controlLocalDeclarationIRt*`, under context `IC1` and store `STO1`.
    - iii. Result in context `IC2`, store `STO2`, and `controlLocalDeclarationIRh_inst :: controlLocalDeclarationIRt_inst*`.

### 16.2.1.3. Runtime evaluation

#### ControlLocalDecl\_eval:

- Evaluating `controlLocalDeclarationIR`, under context `evalContext`, and state `arch`:
- Result in context `evalContext`, state `arch`, and result `controlLocalDeclarationResult`.

Evaluation of a control local declaration yields:

`controlLocalDeclarationResult`

```

: continueEmptyResult
| exitResult
;

continueEmptyResult
: /* empty */
;

exitResult
: EXIT
;

```

A list of control local declarations is runtime evaluated by:

#### ControlLocalDecls\_eval:

- Evaluating `controlLocalDeclarationIR*`, under context `evalContext`, and state `arch`:
- Result in context `evalContext`, state `arch`, and result `controlLocalDeclarationResult`.

#### Evaluating `controlLocalDeclarationIR*`, under context `evalContext`, and state `arch`:

1. If `controlLocalDeclarationIR*` is equal to `:`:
  - a. Result in context `evalContext`, state `arch`, and result `'EMPTY'`.
2. If let `controlLocalDeclarationIRn :: controlLocalDeclarationListIRt be controlLocalDeclarationIR*`:
  - a. Let context `EC1`, state `ARCH1`, and result `controlLocalDeclarationResult` be
    - the result of `evaluating controlLocalDeclarationIRn, under context evalContext, and state arch`.
  - b. If let `exitResult` be `controlLocalDeclarationResult`:
    - i. Result in context `EC1`, state `ARCH1`, and result `EXIT`.
  - c. Else:
    - i. Let `continueEmptyResult` be `controlLocalDeclarationResult`.
    - ii. Let context `EC2`, state `ARCH2`, and result `controlLocalDeclarationResult'` be
      - the result of `evaluating controlLocalDeclarationListIRt, under context EC1, and state ARCH1`.
    - iii. Result in context `EC2`, state `ARCH2`, and result `controlLocalDeclarationResult'`.

The subsequent sections describe each kind of declaration in detail. `table` declarations are special and are separately described in [Section 16.3](#).

## 16.2.2. Constant declarations

See [Section 11.3](#) for general information about constant declarations.

### 16.2.2.1. Type checking

#### Typing `constantDeclaration`, under context `TC0`:

1. Let context `TC1` and `constantDeclarationIR` be
  - the result of `typing constantDeclaration, under cursor BLOCK and context TC0`.

2. Result in context  $TC_1$  and `constantDeclarationIR`.

#### 16.2.2.2. Compile-time evaluation

Compile-time evaluation of `constantDeclarationIR`, under context  $IC_0$  and store  $STO$ :

1. Let context  $IC_1$  be
  - the result of `loading` `constantDeclarationIR`, under cursor `BLOCK`, and context  $IC_0$ .
2. Result in context  $IC_1$ , store  $STO$ , and `constantDeclarationIR`.

#### 16.2.2.3. Runtime evaluation

Evaluating `constantDeclarationIR`, under context  $EC_0$ , and state `ARCH`:

1. Let context  $EC_1$  be
  - the result of `evaluating` `constantDeclarationIR`, under cursor `BLOCK`, and context  $EC_0$ .
2. Result in context  $EC_1$ , state `ARCH`, and result `EMPTY`.

### 16.2.3. Instantiations

See [Section 11.4](#) for general information about instantiations.

#### 16.2.3.1. Type checking

Typing `instantiation`, under context  $TC_0$ :

1. Let context  $TC_1$  and `instantiationIR` be
  - the result of `typing` `instantiation`, under cursor `BLOCK` and context  $TC_0$ .
2. Result in context  $TC_1$  and `instantiationIR`.

#### 16.2.3.2. Compile-time evaluation

Compile-time evaluation of `instantiationIR`, under context  $IC_0$  and store  $STO$ :

1. Let context  $IC_1$ , store  $STO_1$ , and reference to object `constantDeclarationIR` be
  - the result of `loading` `instantiationIR`, under cursor `BLOCK`, context  $IC_0$ , and store  $STO$ .
2. Result in context  $IC_1$ , store  $STO_1$ , and `constantDeclarationIR`.

### 16.2.4. Variable declarations

See [Section 11.2](#) for general information about variable declarations.

#### 16.2.4.1. Type checking



Typing `variableDeclaration`, under context  $TC_0$ :

1. Let context  $TC_1$  and `variableDeclarationIR` be
  - the result of typing `variableDeclaration`, under cursor `BLOCK` and context  $TC_0$ .
2. Result in context  $TC_1$  and `variableDeclarationIR`.

#### 16.2.4.2. Compile-time evaluation

Compile-time evaluation of `variableDeclarationIR`, under context  $IC_0$  and store  $STO$ :

1. Result in context  $IC_0$ , store  $STO$ , and `variableDeclarationIR`.

#### 16.2.4.3. Runtime evaluation

Evaluating `variableDeclarationIR`, under context  $EC_0$ , and state  $ARCH$ :

1. Let context  $EC_1$ , state  $ARCH_1$ , and result `declarationResult` be
  - the result of evaluating `variableDeclarationIR`, under cursor `BLOCK`, context  $EC_0$ , and state  $ARCH$ .
2. If let `exitResult` be `declarationResult`:
  - a. Result in context  $EC_1$ , state  $ARCH_1$ , and result `EXIT`.
3. Else if let `continueEmptyResult` be `declarationResult`:
  - a. Result in context  $EC_1$ , state  $ARCH_1$ , and result `EMPTY`.

### 16.2.5. Action declarations

See [Section 11.6](#) for general information about action declarations.

#### 16.2.5.1. Type checking

Typing `actionDeclaration`, under context  $TC_0$ :

1. Let context  $TC_1$  and `actionDeclarationIR` be
  - the result of typing `actionDeclaration`, under cursor `BLOCK` and context  $TC_0$ .
2. Result in context  $TC_1$  and `actionDeclarationIR`.

#### 16.2.5.2. Compile-time evaluation

Compile-time evaluation of `actionDeclarationIR`, under context  $IC_0$  and store  $STO$ :

1. Let context  $IC_1$  be
  - the result of loading `actionDeclarationIR`, under cursor `BLOCK`, and context  $IC_0$ .
2. Result in context  $IC_1$ , store  $STO$ , and `.`

## 16.3. Match-action tables

**tables** are the primary mechanism for implementing match-action behavior in P4 programs. A table performs a lookup based on a key computed from the packet header fields and other metadata, and applies an action associated with the matching entry in the table.

A table is declared with standard properties and target-specific custom properties.

```
tableDeclaration
: annotationList TABLE name `{ tablePropertyList }
;

tablePropertyList
: /* empty */
| tablePropertyList tableProperty
;

tableProperty
: KEY = `{ tableKeyList }
| ACTIONS = `{ tableActionList }
| annotationList constOpt ENTRIES = `{ tableEntryList }
| annotationList constOpt tableCustomName initializer ;
;
```

The standard table properties include:

- **key**: An expression that describes how the key used for look-up is computed.
- **actions**: A list of all actions that may be found in the table.

In addition, the tables may optionally define the following properties,

- **default\_action**: an action to execute when the lookup in the lookup table fails to find a match for the key used.
- **size**: an integer specifying the desired size of the table.
- **entries**: entries that are initially added to a table when the P4 program is loaded, some or all of which may be unchangeable by the control plane software.
- **largest\_priority\_wins**: Only useful for some tables with the **entries** property. See [Section 16.3.5](#) for details.
- **priority\_delta**: Only useful for some tables with the **entries** property. See [Section 16.3.5](#) for details.

The compiler must set the **default\_action** to **NoAction** (and also insert it into the list of **actions**) for tables that do not define the **default\_action** property. Hence, all tables can be thought of as having a **default\_action** property, either implicitly or explicitly.

In addition, tables may contain architecture-specific properties (see [\[sec-additional-table-properties\]](#)).

A property marked as **const** cannot be changed dynamically by the control plane. The **key**, **actions**, and **size** properties cannot be modified so the **const** keyword is not needed for these.

### 16.3.1. Semantics of match-action table properties

#### 16.3.1.1. Type checking

Table properties are type checked with the relation:

#### TableProperty\_ok:

- Typing `tableProperty`, under context `typingContext` and table context `tableContext`:
- Result in table context `tableContext` and `tablePropertyIR`.

A list of table properties are type checked as:

#### TableProperties\_ok:

- Typing `tableProperty*`, under context `typingContext` and table context `tableContext`:
- Result in table context `tableContext` and `tablePropertyListIR`.

#### Typing `tableProperty*`, under context `TC` and table context `tableContext`:

1. If `tableProperty*` is equal to `.`:
  - a. Result in table context `tableContext` and `.`
2. If let `tablePropertyh :: tablePropertyt*` be `tableProperty*`:
  - a. Let table context `TBLC1` and `tablePropertyIRh` be
    - the result of `typing tablePropertyh, under context TC and table context tableContext`.
  - b. Let table context `TBLC2` and `tablePropertyIRt*` be
    - the result of `typing tablePropertyt*, under context TC and table context TBLC1`.
  - c. Result in table context `TBLC2` and `tablePropertyIRh :: tablePropertyIRt*`.

### 16.3.1.2. Compile-time evaluation

Table properties are compile-time evaluated with the relation:

#### TableProperty\_inst:

- Compile-time evaluation of `tablePropertyIR`, under context `instContext` and store `store`:
- Result in store `store` and `tablePropertyIR`.

After type checking, table properties are represented in `P4IR` as:

```
tablePropertyListIR = tablePropertyIR*  
  
tablePropertyIR  
  : tableKeysPropertyIR  
  | tableActionsPropertyIR  
  | tableDefaultActionPropertyIR  
  | tableEntriesPropertyIR  
  | tableCustomPropertyIR  
  ;
```

A list of table properties are compile-time evaluated as:

#### TableProperties\_inst:

- Compile-time evaluation of  $\text{tablePropertyIR}^*$ , under context  $\text{instContext}$  and store  $\text{store}$ :
- Result in store  $\text{store}$  and  $\text{tablePropertyIR}^*$ .

#### Compile-time evaluation of $\text{tablePropertyIR}^*$ , under context $\text{IC}$ and store $\text{store}$ :

1. If  $\text{tablePropertyIR}^*$  is equal to  $\cdot$ :
  - a. Result in store  $\text{store}$  and  $\cdot$ .
2. If let  $\text{tablePropertyIR}_h :: \text{tablePropertyIR}_t^*$  be  $\text{tablePropertyIR}^*$ :
  - a. Let store  $\text{STO}_1$  and  $\text{tablePropertyIR}_{h_{\text{inst}}}$  be
    - the result of compile-time evaluation of  $\text{tablePropertyIR}_h$ , under context  $\text{IC}$  and store  $\text{store}$ .
  - b. Let store  $\text{STO}_2$  and  $\text{tablePropertyIR}_{t_{\text{inst}}}^*$  be
    - the result of compile-time evaluation of  $\text{tablePropertyIR}_t^*$ , under context  $\text{IC}$  and store  $\text{STO}_1$ .
  - c. Result in store  $\text{STO}_2$  and  $\text{tablePropertyIR}_{h_{\text{inst}}} :: \text{tablePropertyIR}_{t_{\text{inst}}}^*$ .

During compile-time evaluation, local instances within table properties are instantiated.

The following subsections describe the standard properties of tables in more detail.

### 16.3.2. Table keys

The **key** is a table property which specifies the data-plane values that should be used to look up an entry. A key is a list of pairs of the form  $(e : m)$ , where  $e$  is an expression that describes the data to be matched in the table, and  $m$  is a **match\_kind** that describes the algorithm used to perform the lookup (see Section 8.2.5).

```
tableKeyList
: /* empty */
| tableKeyList tableKey
;

tableKey
: expression : name annotationList ;
;
```

For example, consider the following program fragment:

```
table Fwd {
  key = {
    ipv4header.dstAddress : ternary;
    ipv4header.version    : exact;
  }
  // more fields omitted
}
```

Here the key comprises two fields from the `ipv4header` header: `dstAddress` and `version`. The **match\_kind** elements serve three purposes:

- They specify the algorithm used to match data-plane values against the entries in the table at runtime.
- They are used to synthesize the control-plane API that is used to populate the table.
- They are used by the compiler back-end to allocate resources for the implementation of the table.

The P4 core library contains three predefined `match_kind` identifiers:

```
match_kind {
    exact,
    ternary,
    lpm
}
```

These identifiers correspond to the P4<sub>14</sub> match kinds with the same names. The semantics of these match kinds is actually not needed to describe the behavior of the P4 abstract machine; how they are used influences only the control-plane API and the implementation of the look-up table. From the point of view of the P4 program, a look-up table is an abstract finite map that is given a key and produces as a result either an action or a "miss" indication, as described in [Section 16.3.7](#).

The expected meaning of these values is as follows:

- an `exact` match kind on a key field means that the value of the field in the table specifies exactly the value the lookup key field must have in order to match. This is applicable for all legal key fields whose types support equality comparisons.
- a `ternary` match kind on a key field means that the field in the table specifies a set of values for the key field using a value and a mask. The meaning of the `(value, mask)` pair is similar to the P4 mask expressions, as described in [Section 8.6.5.1.3](#): a key field `k` matches the table entry when `k & mask == value & mask`.
- a `lpm` (longest prefix match) match kind on a key field is a specific type of `ternary` match where the mask is required to have a form in binary that is a contiguous set of 1 bits followed by a contiguous set of 0 bits. Masks with more 1 bits have automatically higher priorities. A mask with all bits 0 is legal.

Some table entries, in particular the ones with at least one `ternary` field, also require a priority value. A priority is a numeric value which is used to break ties when a particular key belongs to multiple sets. When table entries are specified in the P4 program the priorities are generated by the compiler; when entries are specified by the control-plane, the priority may need to be explicitly specified. Entries with higher priority are matched first. This specification does not mandate whether "higher" priorities are represented by higher or lower numeric values; this choice is left to the target implementation.

An example specifying entries for a table is given in [Section 16.3.5](#).

If a table has no `key` property, or if the value of its `key` property is the empty tuple, i.e. `key = {}`, then it contains no look-up table, just a default action—i.e., the associated lookup table is always the empty map.

Each key element can have an optional `@name` annotation which is used to synthesize the control-plane-visible name for the key field.

Note some implementations might only support a limited number of keys or a limited combinations of `match_kind` for the keys. The implementation should reject those cases with an error message in this case.

### 16.3.2.1. Type checking

A table key property is type checked as follows:

Typing  $KEY = \{ tableKeyList \}$ , under context TC and table context  $TBLC_0$ :

1. Let  $tableKey^*$  be the list of table keys in  $tableKeyList$ .
2. Let table context  $TBLC_1$  and  $tableKeyIR^*$  be
  - the result of typing  $tableKey^*$ , under context TC and table context  $TBLC_0$ .
3. Result in table context  $TBLC_1$  and  $KEY = \{ tableKeyIR^* \}$ .

After type checking, a table key property is represented in  $P4_{IR}$  as:

```
tableKeysPropertyIR
: KEY = `{ tableKeyListIR }
;

tableKeyListIR = tableKeyIR*

tableKeyIR
: typedExpressionIR : nameIR annotationList ;
;
```

Table keys are type checked with the following relation:

TableKeys\_ok:

- Typing  $tableKey^*$ , under context  $typingContext$  and table context  $tableContext$ :
- Result in table context  $tableContext$  and  $tableKeyListIR$ .

Typing  $tableKey^*$ , under context TC and table context  $tableContext$ :

1. If  $tableKey^*$  is equal to  $\cdot$ :
  - a. Result in table context  $tableContext$  and  $\cdot$ .
2. If let  $tableKey_h :: tableKey_t^*$  be  $tableKey^*$ :
  - a. Let table context  $TBLC_1$  and  $tableKeyIR_h$  be
    - the result of typing  $tableKey_h$ , under context TC and table context  $tableContext$ .
  - b. Let table context  $TBLC_2$  and  $tableKeyIR_t^*$  be
    - the result of typing  $tableKey_t^*$ , under context TC and table context  $TBLC_1$ .
  - c. Result in table context  $TBLC_2$  and  $tableKeyIR_h :: tableKeyIR_t^*$ .

The relation invokes the following relation for each key:

TableKey\_ok:

- Typing  $tableKey$ , under context  $typingContext$  and table context  $tableContext$ :
- Result in table context  $tableContext$  and  $tableKeyIR$ .

Typing expression : name<sub>matchkind</sub> annotationList ;, under context TC and table context TBLC<sub>0</sub>:

1. Let typedExpressionIR be
  - the result of typing expression, under cursor LOCAL and context TC.
2. Let typedExpressionIR<sub>reduced</sub> be typedExpressionIR with surrounding serializable enums reduced.
3. Let typeIR<sub>reduced</sub> be the type of typedExpressionIR<sub>reduced</sub>.
4. Let bound be bound type variables from the LOCAL layer of TC.
5. Check that SET < typeIR<sub>reduced</sub> > is a well-formed type, with bound type variables bound.
6. Let nameIR<sub>matchkind</sub> be the name of name<sub>matchkind</sub>.
7. Check that MATCH\_KIND . nameIR<sub>matchkind</sub> is equal to the value of variable nameIR<sub>matchkind</sub> from the LOCAL layer of TC.
8. Check that typeIR<sub>reduced</sub> can be used with match kind nameIR<sub>matchkind</sub>.
9. Let TBLC<sub>1</sub> be TBLC<sub>0</sub> with match mode updated based on key nameIR<sub>matchkind</sub> of type typeIR<sub>reduced</sub>.
10. Let TBLC<sub>2</sub> be TBLC<sub>1</sub> with match key nameIR<sub>matchkind</sub> of type typeIR<sub>reduced</sub> added.
11. Let tableKeyIR be typedExpressionIR<sub>reduced</sub> : nameIR<sub>matchkind</sub> annotationList ;.
12. Result in table context TBLC<sub>2</sub> and tableKeyIR.

### 16.3.2.2. Compile-time evaluation

Compile-time evaluation of tableKeysPropertyIR, under context IC and store STO:

1. Result in store STO and tableKeysPropertyIR.

### 16.3.2.3. Runtime evaluation

A table key is evaluated at runtime as follows:

TableKey\_eval:

- Evaluating tableKeyIR under context evalContext and state arch:
- Result in the updated context evalContext, state arch , and result tableKeyResult.

The result of evaluating a table key is:

```
tableKeyResult
: continueResult<tableKeyValue>
| exitResult
;

tableKeyValue
: value : nameIR
;

exitResult
: EXIT
;
```

Evaluating  $\text{typedExpressionIR} : \text{nameIR annotationList}$  ; under context  $EC_0$  and state  $ARCH_0$ :

1. Let context  $EC_1$ , state  $ARCH_1$  and  $\text{expressionResult}$  be
  - the result of evaluating  $\text{typedExpressionIR}$ , under cursor  $LOCAL$ , context  $EC_0$ , and state  $ARCH_0$ .
2. If let  $\text{exitResult}$  be  $\text{expressionResult}$ :
  - a. Result in the updated context  $EC_1$ , state  $ARCH_1$  , and result  $EXIT$ .
3. Else if let  $\text{value}$  be  $\text{expressionResult}$ :
  - a. Let  $\text{tableKeyValue}$  be  $\text{value} : \text{nameIR}$ .
  - b. Result in the updated context  $EC_1$ , state  $ARCH_1$  , and result  $\text{tableKeyValue}$ .

A list of table keys is evaluated at runtime as follows:

$\text{TableKeys\_eval}$ :

- Evaluating  $\text{tableKeyListIR}$  under context  $\text{evalContext}$  and state  $\text{arch}$ :
- Result in the updated context  $\text{evalContext}$ , state  $\text{arch}$  , and result  $\text{tableKeysResult}$ .

The result of evaluating table keys is:

```
tableKeysResult
: continueResult<tableKeyValue*>
| exitResult
;
```

Evaluating  $\text{tableKeyIR}^*$  under context  $\text{evalContext}$  and state  $\text{arch}$ :

1. If  $\text{tableKeyIR}^*$  is equal to  $\cdot$  :
  - a. Result in the updated context  $\text{evalContext}$ , state  $\text{arch}$  , and result  $\cdot$ .
2. If let  $\text{tableKeyIR}_h :: \text{tableKeyIR}_t^*$  be  $\text{tableKeyIR}^*$ :
  - a. Let the updated context  $EC_1$ , state  $ARCH_1$  , and result  $\text{tableKeyResult}$  be
    - the result of evaluating  $\text{tableKeyIR}_h$  under context  $\text{evalContext}$  and state  $\text{arch}$ .
  - b. If let  $\text{exitResult}$  be  $\text{tableKeyResult}$ :
    - i. Result in the updated context  $EC_1$ , state  $ARCH_1$  , and result  $EXIT$ .
  - c. Else:
    - i. Let  $\text{tableKeyValue}_h$  be  $\text{tableKeyResult}$ .
    - ii. Let the updated context  $EC_2$ , state  $ARCH_2$  , and result  $\text{tableKeysResult}$  be
      - the result of evaluating  $\text{tableKeyIR}_t^*$  under context  $EC_1$  and state  $ARCH_1$ .
    - iii. If let  $\text{exitResult}$  be  $\text{tableKeysResult}$ :
      - A. Result in the updated context  $EC_2$ , state  $ARCH_2$  , and result  $EXIT$ .
    - iv. Else:
      - A. Let  $\text{tableKeyValue}_t^*$  be  $\text{tableKeysResult}$ .



- B. Let `tableKeyValue*` be `tableKeyValuen :: tableKeyValue*`.
- C. Result in the updated context `EC2`, state `ARCH2`, and result `tableKeyValue*`.

### 16.3.3. Table actions

A table must declare all possible actions that may appear within the associated lookup table or in the default action. This is done with the `actions` property; the value of this property is always an `actionList`:

```
tableActionList
: /* empty */
| tableActionList tableAction
;

tableAction
: annotationList tableActionReference ;
;

tableActionReference
: prefixedNonTypeName
| prefixedNonTypeName `( argumentList )
;
```

To illustrate, recall the example Very Simple Switch program in [Section 5.3](#):

```
action Drop_action() {
    outCtrl.outputPort = DROP_PORT;
}

action Rewrite_smac(EthernetAddress sourceMac) {
    headers.ethernet.srcAddr = sourceMac;
}

table smac {
    key = { outCtrl.outputPort : exact; }
    actions = {
        Drop_action;
        Rewrite_smac;
    }
}
```

- The entries in the `smac` table may contain two different actions: `Drop_action` and `Rewrite_mac`.
- The `Rewrite_smac` action has one parameter, `sourceMac`, which in this case will be provided by the control plane.

Each action in the list of actions for a table must have a distinct name—e.g., the following program fragment is illegal:

```
action a() {}
control c() {
    action a() {}
    // Illegal table: two actions with the same name
    table t { actions = { a; .a; } }
}
```

Each action parameter that has a direction (`in`, `inout`, or `out`) must be bound in the `actions` list specification; conversely, no directionless parameters may be bound in the list. The expressions supplied as arguments to an `action` are not evaluated until the action is invoked. Applying tables, whether directly via an

expression like `table1.apply().hit`, or indirectly, are forbidden in the expressions supplied as action arguments.

```

action a(in bit<32> x) { /* body omitted */ }
bit<32> z;
action b(inout bit<32> x, bit<8> data) { /* body omitted */ }
table t {
  actions = {
    // a; -- illegal, x parameter must be bound
    a(5); // binding a's parameter x to 5
    b(z); // binding b's parameter x to z
    // b(z, 3); -- illegal, cannot bind directionless data parameter
    // b(); -- illegal, x parameter must be bound
    // a(table2.apply().hit ? 5 : 3); -- illegal, cannot apply a table here
  }
}

```

### 16.3.3.1. Type checking

A table action property is type checked as follows:

**Typing** `ACTIONS = { tableActionList }`, under context `TC` and table context `TBLC0`:

1. Let `tableAction*` be the list of table actions in `tableActionList`.
2. Let table context `TBLC1` and `tableActionIR*` be
  - the result of **typing** `tableAction*`, under context `TC` and table context `TBLC0`.
3. Result in table context `TBLC1` and `ACTIONS = { tableActionIR* }`.

After type checking, a table action property is represented in  $P4_{IR}$  as:

```

tableActionsPropertyIR
: ACTIONS = `{ tableActionListIR }
;

tableActionListIR = tableActionIR*

tableActionIR
: annotationList tableActionReferenceIR #
  `( parameterListIR , parameterListIR ) ;
;

tableActionReferenceIR
: prefixedNameIR `( argumentListIR )
;

```

Table actions are type checked with the following relation:

**TableActions\_ok**:

- **Typing** `tableAction*`, under context `typingContext` and table context `tableContext`:
- Result in table context `tableContext` and `tableActionListIR`.

**Typing** `tableAction*`, under context `TC` and table context `tableContext`:

1. If  $\text{tableAction}^*$  is equal to  $\cdot$ :
  - a. Result in table context  $\text{tableContext}$  and  $\cdot$ .
2. If let  $\text{tableAction}_h :: \text{tableAction}_t^*$  be  $\text{tableAction}^*$ :
  - a. Let table context  $\text{TBLC}_1$  and  $\text{tableActionIR}_h$  be
    - the result of **typing**  $\text{tableAction}_h$ , under context TC and table context  $\text{tableContext}$ .
  - b. Let table context  $\text{TBLC}_2$  and  $\text{tableActionIR}_t^*$  be
    - the result of **typing**  $\text{tableAction}_t^*$ , under context TC and table context  $\text{TBLC}_1$ .
  - c. Result in table context  $\text{TBLC}_2$  and  $\text{tableActionIR}_h :: \text{tableActionIR}_t^*$ .

The relation invokes the following relation for each action:

#### TableAction\_ok:

- **Typing**  $\text{tableAction}$ , under context  $\text{typingContext}$  and table context  $\text{tableContext}$ :
- Result in table context  $\text{tableContext}$  and  $\text{tableActionIR}$ .

#### **Typing** $\text{annotationList tableActionReference ;}$ , under context TC and table context $\text{TBLC}_0$ :

1. If let  $\text{prefixedNonTypeName}$  be  $\text{tableActionReference}$ :
  - a. Let  $\text{prefixedNameIR}$  be **the prefixed name of**  $\text{prefixedNonTypeName}$ .
  - b. Let  $( \_ \text{ callableTypeDefIR } )$  be **! the non-overloaded callable definition of**  $\text{prefixedNameIR}$  **from the LOCAL layer of** TC.
  - c. Check that  $\text{callableTypeDefIR}$  has type  $\text{actionTypeIR}$ .
  - d. Let  $\text{annotationList}_{\text{action}} \text{ ACTION } \_ ( \text{parameterIR}^* )$  be  $\text{callableTypeDefIR}$ .
  - e. Let  $\text{annotation}_{\text{name}}^?$  be  $\$find\_name\_annotation\_opt(\text{annotationList}_{\text{action}})$ .
  - f. Let  $\text{annotationList}_{\text{update}}$  be  $\$add\_annotationList(\text{annotationList}, \text{annotation}_{\text{name}}^?)$ .
  - g. Let parameters  $\text{parameterIR}_{\text{data}}^*$  for data-plane,  $\text{parameterIR}_{\text{control}}^*$  for control-plane, and casted  $\text{argumentIR}^*$  be
    - the result of **typing partial action call on**  $\text{parameterIR}^*$  **with**  $\cdot$ , under context TC.
  - h. Check that  $\text{argumentIR}^*$  is an empty list.
    - i. Let  $\text{TBLC}_1$  be  $\text{TBLC}_0$  **with match action**  $\text{prefixedNameIR} ( \text{parameterIR}^* )$  **applied using**  $\cdot$  **added**.
    - j. Let  $\text{tableActionIR}$  be  $\text{annotationList}_{\text{update}} \text{ prefixedNameIR } ( \cdot ) \# ( \text{parameterIR}_{\text{data}}^*, \text{parameterIR}_{\text{control}}^* ) ;$ .
  - k. Result in table context  $\text{TBLC}_1$  and  $\text{tableActionIR}$ .
2. Else:
  - a. Let  $\text{prefixedNonTypeName} ( \text{argumentList} )$  be  $\text{tableActionReference}$ .
  - b. Let  $\text{prefixedNameIR}$  be **the prefixed name of**  $\text{prefixedNonTypeName}$ .
  - c. Let  $( \_ \text{ callableTypeDefIR } )$  be **! the non-overloaded callable definition of**  $\text{prefixedNameIR}$  **from the LOCAL layer of** TC.
  - d. Check that  $\text{callableTypeDefIR}$  has type  $\text{actionTypeIR}$ .
  - e. Let  $\text{annotationList}_{\text{action}} \text{ ACTION } \_ ( \text{parameterIR}^* )$  be  $\text{callableTypeDefIR}$ .

- f. Let  $\text{annotation}_{\text{name}}^?$  be  $\$find\_name\_annotation\_opt(\text{annotationList}_{\text{action}})$ .
- g. Let  $\text{annotationList}_{\text{update}}$  be  $\$add\_annotationList(\text{annotationList}, \text{annotation}_{\text{name}}^?)$ .
- h. Let  $\text{argument}^*$  be the list of arguments in  $\text{argumentList}$ .
- i. Let  $\text{argumentIR}^*$  be the list of  $\text{argumentIR}$ , obtained by repeating:
  - Let  $\text{argumentIR}$  be
    - the result of typing argument, under cursor LOCAL and context TC.
- for each  $\text{argument}$  in  $\text{argument}^*$
- j. Let parameters  $\text{parameterIR}_{\text{data}}^*$  for data-plane,  $\text{parameterIR}_{\text{control}}^*$  for control-plane, and casted  $\text{argumentIR}_{\text{cast}}^*$  be
  - the result of typing partial action call on  $\text{parameterIR}^*$  with  $\text{argumentIR}^*$ , under context TC.
- k. Let  $\text{TBLC}_1$  be  $\text{TBLC}_0$  with match action  $\text{prefixedNameIR}(\text{parameterIR}^*)$  applied using  $\text{argumentIR}_{\text{cast}}^*$  added.
- l. Let  $\text{tableActionIR}$  be  $\text{annotationList}_{\text{update}} \text{ prefixedNameIR}(\text{argumentIR}_{\text{cast}}^*) \# (\text{parameterIR}_{\text{data}}^*, \text{parameterIR}_{\text{control}}^*)$ .
- m. Result in table context  $\text{TBLC}_1$  and  $\text{tableActionIR}$ .

To check that each action conforms to the calling convention, the following relation is used:

#### Call\_action\_partial\_ok:

- Typing partial action call on  $\text{parameterIR}^*$  with  $\text{argumentListIR}$ , under context  $\text{typingContext}$ :
- Result in parameters  $\text{parameterIR}^*$  for data-plane,  $\text{parameterIR}^*$  for control-plane, and casted  $\text{argumentListIR}$ .

#### Typing partial action call on $\text{parameterIR}^*$ with $\text{argumentIR}^*$ , under context TC:

1. Let  $(\text{parameterIR}_{\text{data}}^*, \text{parameterIR}_{\text{control}}^*)$  be  $\text{parameterIR}^*$  split into data-plane and control-plane parameters.
2. Check that the length of  $\text{parameterIR}_{\text{data}}^*$  is equal to the length of  $\text{argumentIR}^*$ .
3. Let  $\text{typedExpressionIR}_{\text{sub}}^*$  be the sub-expressions of  $\text{argumentIR}^*$ .
4. Check that all  $\$is\_table\_application(\text{typedExpressionIR}_{\text{sub}}^*)$  are true.
5. Let casted  $\text{argumentIR}_{\text{cast}}^*$  be
  - the result of checking calling convention of  $\text{argumentIR}^*$  applied on  $\text{parameterIR}_{\text{data}}^*$ , under cursor LOCAL, context TC, and action context ACTION.
6. Result in parameters  $\text{parameterIR}_{\text{data}}^*$  for data-plane,  $\text{parameterIR}_{\text{control}}^*$  for control-plane, and casted  $\text{argumentIR}_{\text{cast}}^*$ .

### 16.3.3.2. Compile-time evaluation

#### Compile-time evaluation of $\text{tableActionsPropertyIR}$ , under context IC and store STO:

1. Result in store `STO` and `tableActionsPropertyIR`.

### 16.3.4. Table default actions

The default action for a table is an action that is invoked automatically by the match-action unit whenever the lookup table does not find a match for the supplied key.

If present, the `default_action` property *must* appear after the `action` property. It may be declared as `const`, indicating that it cannot be changed dynamically by the control-plane. The `default action` *must* be one of the actions that appear in the actions list. In particular, the expressions passed as `in`, `out`, or `inout` parameters must be syntactically identical to the expressions used in one of the elements of the `actions` list.

For example, in the above `table` we could set the default action as follows (marking it also as constant):

```
const default_action = Rewrite_smac(48w0xAA_BB_CC_DD_EE_FF);
```

Note that the specified default action must supply arguments for the control-plane-bound parameters (i.e., the directionless parameters), since the action is synthesized at compilation time. The expressions supplied as arguments for parameters with a direction (`in`, `inout`, or `out`) are evaluated when the action is invoked while the expressions supplied as arguments for directionless parameters are evaluated at compile time.

Continuing the example from the previous section, the following are several legal and illegal specifications of default actions for the `table t`:

```
default_action = a(5); // OK - no control-plane parameters
// default_action = a(z); -- illegal, a's x parameter is already bound to 5
default_action = b(z, 8w8); // OK - bind b's data parameter to 8w8
// default_action = b(z); -- illegal, b's data parameter is not bound
// default_action = b(x, 3); -- illegal: x parameter of b bound to x instead of z
```

#### 16.3.4.1. Type checking

A table default action property is type checked as follows:

**Typing** `annotationList constOpt tableCustomName initializer ;`, under context `TC` and table context `TBLC0`:

1. Check that "default\_action" is equal to the name of `tableCustomName`.
2. Let `tableActionReferenceIR` be
  - the result of **typing** `initializer`, under context `TC` and table context `TBLC0`.
3. Let `constOptIR` be the optional `const` qualifier in `constOpt`.
4. Let `tablePropertyIR` be `annotationList constOptIR DEFAULT_ACTION = tableActionReferenceIR ;`.
5. Result in table context `TBLC0` and `tablePropertyIR`.

After type checking, a table default action property is represented in  $P4_{IR}$  as:

```
tableDefaultActionPropertyIR
: annotationList constOptIR DEFAULT_ACTION = tableActionReferenceIR ;
;
```

```

tableActionReferenceIR
: prefixedNameIR `( argumentListIR )
;

```

Table default actions are type checked with the following relation:

#### TableDefaultAction\_ok:

- Typing `initializer`, under context `typingContext` and table context `tableContext`:
- Result in `tableActionReferenceIR`.

#### Typing = expression, under context TC and table context TBLC:

1. If let `prefixedNonTypeName` be `expression`:
  - a. Let `prefixedNameIR` be the prefixed name of `prefixedNonTypeName`.
  - b. Check that `( · , · )` is equal to `$find_action(TBLC, prefixedNameIR)`.
  - c. Result in `prefixedNameIR ( · )`.
2. Else if let `callExpression` be `expression`:
  - a. Check that `callExpression` matches pattern `% ( % )`.
  - b. Let `callTarget ( argumentList )` be `callExpression`.
  - c. Check that `callTarget` has type `prefixedNonTypeName`.
  - d. Let `prefixedNonTypeName` be `callTarget`.
  - e. Let `prefixedNameIR` be the prefixed name of `prefixedNonTypeName`.
  - f. Let `( parameterIRaction*, argumentIRaction* )` be `!$find_action(TBLC, prefixedNameIR)`.
  - g. Let `argument*` be the list of arguments in `argumentList`.
  - h. Let `argumentIR*` be the list of `argumentIR`, obtained by repeating:
    - Let `argumentIR` be
      - the result of typing `argument`, under cursor `LOCAL` and context `TC`.
  - i. Let parameters `parameterIRaction_data*` for data-plane, `parameterIRaction_control*` for control-plane, and casted `argumentIRcast*` be
    - the result of typing action call on `parameterIRaction*` with `argumentIR*`, under context `TC`.
  - j. Let `argumentIRaction_data*` be `argumentIRaction*[0 : the length of parameterIRaction_data*]`.
  - k. Let `argumentIRcast_data*` be `argumentIRcast*[0 : the length of parameterIRaction_data*]`.
  - l. Check that `argumentIRaction_data` is equal to `argumentIRcast_data`, for all `argumentIRaction_data` in `argumentIRaction_data*` and `argumentIRcast_data` in `argumentIRcast_data*`.
  - m. Result in `prefixedNameIR ( argumentIRcast* )`.

To check that a default action conforms to the calling convention, the following relation is used:

#### Call\_action\_default\_ok:

- Typing action call on  $\text{parameterIR}^*$  with  $\text{argumentListIR}$ , under context  $\text{typingContext}$ :
- Result in parameters  $\text{parameterIR}^*$  for data-plane,  $\text{parameterIR}^*$  for control-plane, and casted  $\text{argumentListIR}$ .

#### Typing partial action call on $\text{parameterIR}^*$ with $\text{argumentIR}^*$ , under context TC:

1. Let (  $\text{parameterIR}_{\text{data}}^*$ ,  $\text{parameterIR}_{\text{control}}^*$  ) be  $\text{parameterIR}^*$  split into data-plane and control-plane parameters.
2. Check that the length of  $\text{parameterIR}_{\text{data}}^*$  is equal to the length of  $\text{argumentIR}^*$ .
3. Let  $\text{typedExpressionIR}_{\text{sub}}^*$  be the sub-expressions of  $\text{argumentIR}^*$ .
4. Check that all  $\text{is\_table\_application}(\text{typedExpressionIR}_{\text{sub}}^*)$  are true.
5. Let casted  $\text{argumentIR}_{\text{cast}}^*$  be
  - the result of checking calling convention of  $\text{argumentIR}^*$  applied on  $\text{parameterIR}_{\text{data}}^*$ , under cursor LOCAL, context TC, and action context ACTION.
6. Result in parameters  $\text{parameterIR}_{\text{data}}^*$  for data-plane,  $\text{parameterIR}_{\text{control}}^*$  for control-plane, and casted  $\text{argumentIR}_{\text{cast}}^*$ .

### 16.3.4.2. Compile-time evaluation

#### Compile-time evaluation of $\text{tableDefaultActionPropertyIR}$ , under context IC and store STO:

1. Result in store STO and  $\text{tableDefaultActionPropertyIR}$ .

### 16.3.5. Table entries

```
keysetExpression
: simpleKeysetExpression
| tupleKeysetExpression
;

tableEntryPriority
: PRIORITY = integerLiteral :
| PRIORITY = `( expression ) :
;

tableEntry
: constOpt tableEntryPriority keysetExpression : tableActionReference
  annotationList ;
| constOpt keysetExpression : tableActionReference annotationList ;
;

keysetExpressionIR
: simpleKeysetExpressionIR
| tupleKeysetExpressionIR
;

tableEntryPriorityIR
: PRIORITY = integerLiteral :
| PRIORITY = `( typedExpressionIR ) :
```

```

;
tableEntryIR
: constOptIR tableEntryPriorityOptIR keysetExpressionIR :
  tableActionReferenceIR annotationList ;
;

```

### 16.3.6. Table custom properties

### 16.3.7. Match-action table invocation

## 17. Casting

P4 provides a limited set of casts between types. While this design is arguably more onerous for programmers, it has several benefits:

- It makes user intent unambiguous.
- It makes the costs associated with converting numeric values explicit. Implementing certain casts involves sign extensions, and thus can require significant computational resources on some targets.
- It reduces the number of cases that have to be considered in the P4 specification. Some targets may not support all casts.

### 17.1. Explicit casts

The below relation checks whether a type can be explicitly cast to another type.

**Cast\_expl:**

- $\text{typeIR}_a$  can be explicitly cast to  $\text{typeIR}_b$

First, the two types are unrolled and checked to see if they are the same type. If so, no cast is needed.

$\text{typeIR}_a$  can be explicitly cast to  $\text{typeIR}_b$  when:

1. Let  $\text{typeIR}_{a\_unroll}$  be  $\text{typeIR}_a$  with typedefs unrolled.
2. Let  $\text{typeIR}_{b\_unroll}$  be  $\text{typeIR}_b$  with typedefs unrolled.
3. If  $\text{typeIR}_{a\_unroll}$  and  $\text{typeIR}_{b\_unroll}$  are the same type:
  - a. The relation holds.
4. Else:
  - a. Check that  $\text{typeIR}_{a\_unroll}$  can be explicitly cast to  $\text{typeIR}_{b\_unroll}$  (when unequal).
  - b. The relation holds.

If the two types are not equal, the below relation is applied.

**Cast\_expl\_neq:**



- `typeIR` can be explicitly cast to `typeIR'` (when unequal)

#### Cast from `bool` to `bit<1>`

`BOOL` can be explicitly cast to `BIT < 1 >` (when unequal) when:

1. The relation holds.

#### Cast from `int` to `bool`, `int<S>`, or `bit<W>`

`INT` can be explicitly cast to `typeIR'` (when unequal) when:

1. If `typeIR'` is equal to `BOOL`:
  - a. The relation holds.
2. If `typeIR'` has type `fixedIntTypeIR`:
  - a. The relation holds.
3. Else if `typeIR'` has type `fixedBitTypeIR`:
  - a. The relation holds.

#### Cast from `int<S>` to `int`, `int<T>`, or `bit<W>`

`INT < nat >` can be explicitly cast to `typeIR'` (when unequal) when:

1. If `typeIR'` is equal to `INT`:
  - a. The relation holds.
2. If `typeIR'` has type `fixedIntTypeIR`:
  - a. The relation holds.
3. If `typeIR'` is equal to `BIT < nat >`:
  - a. The relation holds.

#### Cast from `bit<W>` to `bool`, `int`, `int<S>`, or `bit<X>`

`BIT < nat >` can be explicitly cast to `typeIR'` (when unequal) when:

1. If `nat` is equal to 1:
  - a. Check that `typeIR'` is equal to `BOOL`.
  - b. The relation holds.
2. If `typeIR'` is equal to `INT`:
  - a. The relation holds.
3. If `typeIR'` is equal to `INT < nat >`:
  - a. The relation holds.

4. If `typeIR'` has type `fixedBitTypeIR`:
  - a. The relation holds.

#### Cast from a new type to its underlying type, and vice versa

`typeIR` can be explicitly cast to `typeIR'` (when unequal) when:

1. If let `TYPE _ typeIRa` be `typeIR`:
  - a. Check that `typeIRa` can be implicitly cast to `typeIR'`.
  - b. The relation holds.
2. If let `TYPE _ typeIRb` be `typeIR'`:
  - a. Check that `typeIR` can be implicitly cast to `typeIRb`.
  - b. The relation holds.

#### Cast from an enum with an underlying type to the underlying type, and vice versa

`typeIR` can be explicitly cast to `typeIR'` (when unequal) when:

1. If let `ENUM _ < typeIRa > { _ * }` be `typeIR`:
  - a. Check that `typeIRa` can be implicitly cast to `typeIR'`.
  - b. The relation holds.
2. If let `ENUM _ < typeIRb > { _ * }` be `typeIR'`:
  - a. Check that `typeIR` can be implicitly cast to `typeIRb`.
  - b. The relation holds.

#### Cast from a default type to the target type

`DEFAULT` can be explicitly cast to `typeIR'` (when unequal) when:

1. Check that `typeIR'` can be default-initialized.
2. The relation holds.

#### Cast from an invalid header type to a header or header union type

`HEADER_INVALID` can be explicitly cast to `typeIR'` (when unequal) when:

1. If `typeIR'` has type `headerTypeIR`:
  - a. The relation holds.
2. Else if `typeIR'` has type `headerUnionTypeIR`:
  - a. The relation holds.

## Cast from a sequence type to a list, tuple, header stack, struct, header, or another sequence type

$SEQ < typeIR_a^* >$  can be explicitly cast to  $typeIR'$  (when unequal) when:

1. If let  $LIST < typeIR_b >$  be  $typeIR'$ :
  - a. Check that  $typeIR_a$  can be explicitly cast to  $typeIR_b$ , for all  $typeIR_a$  in  $typeIR_a^*$ .
  - b. The relation holds.
2. Else if let  $TUPLE < typeIR_b^* >$  be  $typeIR'$ :
  - a. Check that  $typeIR_a$  can be explicitly cast to  $typeIR_b$ , for all  $typeIR_a$  in  $typeIR_a^*$  and  $typeIR_b$  in  $typeIR_b^*$ .
  - b. The relation holds.
3. Else if let  $typeIR_b [ n_{size} ]$  be  $typeIR'$ :
  - a. Check that the length of  $typeIR_a^*$  is less than or equal to  $n_{size}$ .
  - b. Check that  $typeIR_a$  can be explicitly cast to  $typeIR_b$ , for all  $typeIR_a$  in  $typeIR_a^*$ .
  - c. The relation holds.
4. Else if let  $STRUCT \_ < \_ > \{ ( \_ typeIR_{field\_b} \_ ; )^* \}$  be  $typeIR'$ :
  - a. Check that  $typeIR_a$  can be explicitly cast to  $typeIR_{field\_b}$ , for all  $typeIR_a$  in  $typeIR_a^*$  and  $typeIR_{field\_b}$  in  $typeIR_{field\_b}^*$ .
  - b. The relation holds.
5. Else if let  $HEADER \_ < \_ > \{ ( \_ typeIR_{field\_b} \_ ; )^* \}$  be  $typeIR'$ :
  - a. Check that  $typeIR_a$  can be explicitly cast to  $typeIR_{field\_b}$ , for all  $typeIR_a$  in  $typeIR_a^*$  and  $typeIR_{field\_b}$  in  $typeIR_{field\_b}^*$ .
  - b. The relation holds.

## Cast from a sequence type with default initializer to a tuple, header stack, struct, or header type

$SEQ < typeIR_a^*, \dots >$  can be explicitly cast to  $typeIR'$  (when unequal) when:

1. If let  $TUPLE < typeIR_b^* >$  be  $typeIR'$ :
  - a. Check that the length of  $typeIR_a^*$  is less than the length of  $typeIR_b^*$ .
  - b. Let  $( typeIR_{b\_non\_default}^*, typeIR_{b\_default}^* )$  be  $\$partition\_<typeIR>(typeIR_b^*, \text{the length of } typeIR_a^*)$ .
  - c. Check that  $typeIR_a$  can be explicitly cast to  $typeIR_{b\_non\_default}$ , for all  $typeIR_a$  in  $typeIR_a^*$  and  $typeIR_{b\_non\_default}$  in  $typeIR_{b\_non\_default}^*$ .
  - d. Check that  $typeIR_{b\_default}$  can be default-initialized, for all  $typeIR_{b\_default}$  in  $typeIR_{b\_default}^*$ .
  - e. The relation holds.
2. Else if let  $typeIR_b [ n_{size} ]$  be  $typeIR'$ :
  - a. Check that the length of  $typeIR_a^*$  is less than  $n_{size}$ .
  - b. Check that  $typeIR_a$  can be explicitly cast to  $typeIR_b$ , for all  $typeIR_a$  in  $typeIR_a^*$ .
  - c. Check that  $typeIR_b$  can be default-initialized.
  - d. The relation holds.
3. Else if let  $STRUCT \_ < \_ > \{ ( \_ typeIR_{field\_b} \_ ; )^* \}$  be  $typeIR'$ :
  - a. Check that the length of  $typeIR_a^*$  is less than the length of  $typeIR_{field\_b}^*$ .

- b. Let  $(\text{typeIR}_{\text{field\_b\_non\_default}}^*, \text{typeIR}_{\text{field\_b\_default}}^*)$  be  $\$partition\_<\text{typeIR}>(\text{typeIR}_{\text{field\_b}}^*, \text{the length of } \text{typeIR}_a^*)$ .
  - c. Check that  $\text{typeIR}_a$  can be explicitly cast to  $\text{typeIR}_{\text{field\_b\_non\_default}}$ , for all  $\text{typeIR}_a$  in  $\text{typeIR}_a^*$  and  $\text{typeIR}_{\text{field\_b\_non\_default}}$  in  $\text{typeIR}_{\text{field\_b\_non\_default}}^*$ .
  - d. Check that  $\text{typeIR}_{\text{field\_b\_default}}$  can be default-initialized, for all  $\text{typeIR}_{\text{field\_b\_default}}$  in  $\text{typeIR}_{\text{field\_b\_default}}^*$ .
  - e. The relation holds.
4. Else if let  $\text{HEADER\_} < \_ > \{ ( \_ \text{typeIR}_{\text{field\_b}} ; )^* \}$  be  $\text{typeIR}'$ :
- a. Check that the length of  $\text{typeIR}_a^*$  is less than the length of  $\text{typeIR}_{\text{field\_b}}^*$ .
  - b. Let  $(\text{typeIR}_{\text{field\_b\_non\_default}}^*, \text{typeIR}_{\text{field\_b\_default}}^*)$  be  $\$partition\_<\text{typeIR}>(\text{typeIR}_{\text{field\_b}}^*, \text{the length of } \text{typeIR}_a^*)$ .
  - c. Check that  $\text{typeIR}_a$  can be explicitly cast to  $\text{typeIR}_{\text{field\_b\_non\_default}}$ , for all  $\text{typeIR}_a$  in  $\text{typeIR}_a^*$  and  $\text{typeIR}_{\text{field\_b\_non\_default}}$  in  $\text{typeIR}_{\text{field\_b\_non\_default}}^*$ .
  - d. Check that  $\text{typeIR}_{\text{field\_b\_default}}$  can be default-initialized, for all  $\text{typeIR}_{\text{field\_b\_default}}$  in  $\text{typeIR}_{\text{field\_b\_default}}^*$ .
  - e. The relation holds.

### Cast from a record type to a struct or header type

$\text{RECORD } \{ ( \_ \text{typeIR}_{\text{field\_a}} \text{ id}_{\text{field\_a}} ; )^* \}$  can be explicitly cast to  $\text{typeIR}'$  (when unequal) when:

1. If let  $\text{STRUCT\_} < \_ > \{ ( \_ \text{typeIR}_{\text{field\_b}} \text{ id}_{\text{field\_b}} ; )^* \}$  be  $\text{typeIR}'$ :
  - a. Check that  $\{ \text{id}_{\text{field\_a}}^* \}$  is equal to  $\{ \text{id}_{\text{field\_b}}^* \}$ .
  - b. Let  $\text{typeIR}''^{?^*}$  be the list of  $\text{typeIR}''^{?}$ , obtained by repeating:
    - Let  $\text{typeIR}''^{?}$  be  $\text{id}_{\text{field\_a}}$  in map  $\{ ( \text{id}_{\text{field\_a}} : \text{typeIR}_{\text{field\_a}} )^* \}$ .
 for each  $\text{id}_{\text{field\_a}}$  in  $\text{id}_{\text{field\_a}}^*$
  - c. Check that  $\text{typeIR}''^{?}$  is defined, for all  $\text{typeIR}''^{?}$  in  $\text{typeIR}''^{?^*}$ .
  - d. Let  $\text{typeIR}_{\text{field\_a\_aligned}}^*$  be the list of  $\text{typeIR}_{\text{field\_a\_aligned}}$ , obtained by repeating:
    - Let  $\text{typeIR}_{\text{field\_a\_aligned}}$  be  $\text{typeIR}''^{?}$ .
 for each  $\text{typeIR}''^{?}$  in  $\text{typeIR}''^{?^*}$
  - e. Let  $\text{typeIR}'''^{?^*}$  be the list of  $\text{typeIR}'''^{?}$ , obtained by repeating:
    - Let  $\text{typeIR}'''^{?}$  be  $\text{id}_{\text{field\_a}}$  in map  $\{ ( \text{id}_{\text{field\_b}} : \text{typeIR}_{\text{field\_b}} )^* \}$ .
 for each  $\text{id}_{\text{field\_a}}$  in  $\text{id}_{\text{field\_a}}^*$
  - f. Check that  $\text{typeIR}'''^{?}$  is defined, for all  $\text{typeIR}'''^{?}$  in  $\text{typeIR}'''^{?^*}$ .
  - g. Let  $\text{typeIR}_{\text{field\_b\_aligned}}^*$  be the list of  $\text{typeIR}_{\text{field\_b\_aligned}}$ , obtained by repeating:
    - Let  $\text{typeIR}_{\text{field\_b\_aligned}}$  be  $\text{typeIR}'''^{?}$ .
 for each  $\text{typeIR}'''^{?}$  in  $\text{typeIR}'''^{?^*}$
  - h. Check that  $\text{typeIR}_{\text{field\_a\_aligned}}$  can be explicitly cast to  $\text{typeIR}_{\text{field\_b\_aligned}}$ , for all  $\text{typeIR}_{\text{field\_a\_aligned}}$  in  $\text{typeIR}_{\text{field\_a\_aligned}}^*$  and  $\text{typeIR}_{\text{field\_b\_aligned}}$  in  $\text{typeIR}_{\text{field\_b\_aligned}}^*$ .
  - i. The relation holds.

2. Else if let  $\text{HEADER } \_ < \_ ^* > \{ ( \_ \text{typeIR}_{\text{field\_b}} \text{id}_{\text{field\_b}} ; ) ^* \}$  be  $\text{typeIR}'$ :
  - a. Check that  $\{ \text{id}_{\text{field\_a}} ^* \}$  is equal to  $\{ \text{id}_{\text{field\_b}} ^* \}$ .
  - b. Let  $\text{typeIR}''^{?*}$  be the list of  $\text{typeIR}''^?$ , obtained by repeating:
    - Let  $\text{typeIR}''^?$  be  $\text{id}_{\text{field\_a}}$  in map  $\{ ( \text{id}_{\text{field\_a}} : \text{typeIR}_{\text{field\_a}} ) ^* \}$ .
 for each  $\text{id}_{\text{field\_a}}$  in  $\text{id}_{\text{field\_a}} ^*$
  - c. Check that  $\text{typeIR}''^?$  is defined, for all  $\text{typeIR}''^?$  in  $\text{typeIR}''^{?*}$ .
  - d. Let  $\text{typeIR}_{\text{field\_a\_aligned}} ^*$  be the list of  $\text{typeIR}_{\text{field\_a\_aligned}}$ , obtained by repeating:
    - Let  $\text{typeIR}_{\text{field\_a\_aligned}}$  be  $\text{typeIR}''^?$ .
 for each  $\text{typeIR}''^?$  in  $\text{typeIR}''^{?*}$
  - e. Let  $\text{typeIR}'''^{?*}$  be the list of  $\text{typeIR}'''^?$ , obtained by repeating:
    - Let  $\text{typeIR}'''^?$  be  $\text{id}_{\text{field\_a}}$  in map  $\{ ( \text{id}_{\text{field\_b}} : \text{typeIR}_{\text{field\_b}} ) ^* \}$ .
 for each  $\text{id}_{\text{field\_a}}$  in  $\text{id}_{\text{field\_a}} ^*$
  - f. Check that  $\text{typeIR}'''^?$  is defined, for all  $\text{typeIR}'''^?$  in  $\text{typeIR}'''^{?*}$ .
  - g. Let  $\text{typeIR}_{\text{field\_b\_aligned}} ^*$  be the list of  $\text{typeIR}_{\text{field\_b\_aligned}}$ , obtained by repeating:
    - Let  $\text{typeIR}_{\text{field\_b\_aligned}}$  be  $\text{typeIR}'''^?$ .
 for each  $\text{typeIR}'''^?$  in  $\text{typeIR}'''^{?*}$
  - h. Check that  $\text{typeIR}_{\text{field\_a\_aligned}}$  can be explicitly cast to  $\text{typeIR}_{\text{field\_b\_aligned}}$ , for all  $\text{typeIR}_{\text{field\_a\_aligned}}$  in  $\text{typeIR}_{\text{field\_a\_aligned}} ^*$  and  $\text{typeIR}_{\text{field\_b\_aligned}}$  in  $\text{typeIR}_{\text{field\_b\_aligned}} ^*$ .
  - i. The relation holds.

### Cast from a record type with default initializer to a struct or header type

$\text{RECORD } \{ ( \_ \text{typeIR}_{\text{field\_a}} \text{id}_{\text{field\_a}} ; ) ^* , \dots \}$  can be explicitly cast to  $\text{typeIR}'$  (when unequal) when:

1. If let  $\text{STRUCT } \_ < \_ ^* > \{ ( \_ \text{typeIR}_{\text{field\_b}} \text{id}_{\text{field\_b}} ; ) ^* \}$  be  $\text{typeIR}'$ :
  - a. Check that  $\{ \text{id}_{\text{field\_a}} ^* \}$  is a subset of  $\{ \text{id}_{\text{field\_b}} ^* \}$ .
  - b. Let  $\text{typeIR}''^{?*}$  be the list of  $\text{typeIR}''^?$ , obtained by repeating:
    - Let  $\text{typeIR}''^?$  be  $\text{id}_{\text{field\_a}}$  in map  $\{ ( \text{id}_{\text{field\_a}} : \text{typeIR}_{\text{field\_a}} ) ^* \}$ .
 for each  $\text{id}_{\text{field\_a}}$  in  $\text{id}_{\text{field\_a}} ^*$
  - c. Check that  $\text{typeIR}''^?$  is defined, for all  $\text{typeIR}''^?$  in  $\text{typeIR}''^{?*}$ .
  - d. Let  $\text{typeIR}_{\text{field\_a\_aligned}} ^*$  be the list of  $\text{typeIR}_{\text{field\_a\_aligned}}$ , obtained by repeating:
    - Let  $\text{typeIR}_{\text{field\_a\_aligned}}$  be  $\text{typeIR}''^?$ .
 for each  $\text{typeIR}''^?$  in  $\text{typeIR}''^{?*}$
  - e. Let  $\text{typeIR}'''^{?*}$  be the list of  $\text{typeIR}'''^?$ , obtained by repeating:

- Let  $\text{typeIR}^{\text{m}^?}$  be  $\text{id}_{\text{field}_a}$  in map  $\{ ( \text{id}_{\text{field}_b} : \text{typeIR}_{\text{field}_b} )^* \}$ .
  - for each  $\text{id}_{\text{field}_a}$  in  $\text{id}_{\text{field}_a}^*$
  - f. Check that  $\text{typeIR}^{\text{m}^?}$  is defined, for all  $\text{typeIR}^{\text{m}^?}$  in  $\text{typeIR}^{\text{m}^?}$ .
  - g. Let  $\text{typeIR}_{\text{field}_b_{\text{non\_default\_aligned}}}^*$  be the list of  $\text{typeIR}_{\text{field}_b_{\text{non\_default\_aligned}}}$ , obtained by repeating:
    - Let  $\text{typeIR}_{\text{field}_b_{\text{non\_default\_aligned}}}$  be  $\text{typeIR}^{\text{m}^?}$ .
    - for each  $\text{typeIR}^{\text{m}^?}$  in  $\text{typeIR}^{\text{m}^?}$
  - h. Check that  $\text{typeIR}_{\text{field}_a_{\text{aligned}}}$  can be explicitly cast to  $\text{typeIR}_{\text{field}_b_{\text{non\_default\_aligned}}}$ , for all  $\text{typeIR}_{\text{field}_a_{\text{aligned}}}$  in  $\text{typeIR}_{\text{field}_a_{\text{aligned}}}^*$  and  $\text{typeIR}_{\text{field}_b_{\text{non\_default\_aligned}}}$  in  $\text{typeIR}_{\text{field}_b_{\text{non\_default\_aligned}}}^*$ .
  - i. Let  $\{ \text{id}_{\text{default}}^* \}$  be the difference of the sets  $\{ \text{id}_{\text{field}_b}^* \}$  and  $\{ \text{id}_{\text{field}_a}^* \}$ .
  - j. Let  $\text{typeIR}^{\text{m}^?}$  be the list of  $\text{typeIR}^{\text{m}^?}$ , obtained by repeating:
    - Let  $\text{typeIR}^{\text{m}^?}$  be  $\text{id}_{\text{default}}$  in map  $\{ ( \text{id}_{\text{field}_b} : \text{typeIR}_{\text{field}_b} )^* \}$ .
    - for each  $\text{id}_{\text{default}}$  in  $\text{id}_{\text{default}}^*$
  - k. Check that  $\text{typeIR}^{\text{m}^?}$  is defined, for all  $\text{typeIR}^{\text{m}^?}$  in  $\text{typeIR}^{\text{m}^?}$ .
  - l. Let  $\text{typeIR}_{\text{field}_b_{\text{default}}}^*$  be the list of  $\text{typeIR}_{\text{field}_b_{\text{default}}}$ , obtained by repeating:
    - Let  $\text{typeIR}_{\text{field}_b_{\text{default}}}$  be  $\text{typeIR}^{\text{m}^?}$ .
    - for each  $\text{typeIR}^{\text{m}^?}$  in  $\text{typeIR}^{\text{m}^?}$
  - m. Check that  $\text{typeIR}_{\text{field}_b_{\text{default}}}$  can be default-initialized, for all  $\text{typeIR}_{\text{field}_b_{\text{default}}}$  in  $\text{typeIR}_{\text{field}_b_{\text{default}}}^*$ .
  - n. The relation holds.
2. Else if let  $\text{HEADER\_} < \_ > \{ ( \_ \text{typeIR}_{\text{field}_b} \text{id}_{\text{field}_b} ; )^* \}$  be  $\text{typeIR}'$ :
- a. Check that  $\{ \text{id}_{\text{field}_a}^* \}$  is a subset of  $\{ \text{id}_{\text{field}_b}^* \}$ .
  - b. Let  $\text{typeIR}^{\text{m}^?}$  be the list of  $\text{typeIR}^{\text{m}^?}$ , obtained by repeating:
    - Let  $\text{typeIR}^{\text{m}^?}$  be  $\text{id}_{\text{field}_a}$  in map  $\{ ( \text{id}_{\text{field}_a} : \text{typeIR}_{\text{field}_a} )^* \}$ .
    - for each  $\text{id}_{\text{field}_a}$  in  $\text{id}_{\text{field}_a}^*$
  - c. Check that  $\text{typeIR}^{\text{m}^?}$  is defined, for all  $\text{typeIR}^{\text{m}^?}$  in  $\text{typeIR}^{\text{m}^?}$ .
  - d. Let  $\text{typeIR}_{\text{field}_a_{\text{aligned}}}^*$  be the list of  $\text{typeIR}_{\text{field}_a_{\text{aligned}}}$ , obtained by repeating:
    - Let  $\text{typeIR}_{\text{field}_a_{\text{aligned}}}$  be  $\text{typeIR}^{\text{m}^?}$ .
    - for each  $\text{typeIR}^{\text{m}^?}$  in  $\text{typeIR}^{\text{m}^?}$
  - e. Let  $\text{typeIR}^{\text{m}^?}$  be the list of  $\text{typeIR}^{\text{m}^?}$ , obtained by repeating:
    - Let  $\text{typeIR}^{\text{m}^?}$  be  $\text{id}_{\text{field}_a}$  in map  $\{ ( \text{id}_{\text{field}_b} : \text{typeIR}_{\text{field}_b} )^* \}$ .
    - for each  $\text{id}_{\text{field}_a}$  in  $\text{id}_{\text{field}_a}^*$
  - f. Check that  $\text{typeIR}^{\text{m}^?}$  is defined, for all  $\text{typeIR}^{\text{m}^?}$  in  $\text{typeIR}^{\text{m}^?}$ .
  - g. Let  $\text{typeIR}_{\text{field}_b_{\text{non\_default\_aligned}}}^*$  be the list of  $\text{typeIR}_{\text{field}_b_{\text{non\_default\_aligned}}}$ , obtained by repeating:

- Let  $\text{typeIR}_{\text{field\_b\_non\_default\_aligned}}$  be  $\text{typeIR}^{''''}$ .

for each  $\text{typeIR}^{''''}$  in  $\text{typeIR}^{''''*}$

- h. Check that  $\text{typeIR}_{\text{field\_a\_aligned}}$  can be explicitly cast to  $\text{typeIR}_{\text{field\_b\_non\_default\_aligned}}$ , for all  $\text{typeIR}_{\text{field\_a\_aligned}}$  in  $\text{typeIR}_{\text{field\_a\_aligned}}^*$  and  $\text{typeIR}_{\text{field\_b\_non\_default\_aligned}}$  in  $\text{typeIR}_{\text{field\_b\_non\_default\_aligned}}^*$ .

- i. Let  $\{\text{id}_{\text{default}}^*\}$  be the difference of the sets  $\{\text{id}_{\text{field\_b}}^*\}$  and  $\{\text{id}_{\text{field\_a}}^*\}$ .

- j. Let  $\text{typeIR}^{''''*}$  be the list of  $\text{typeIR}^{''''}$ , obtained by repeating:
  - Let  $\text{typeIR}^{''''}$  be  $\text{id}_{\text{default}}$  in map  $\{(\text{id}_{\text{field\_b}} : \text{typeIR}_{\text{field\_b}})^*\}$ .

for each  $\text{id}_{\text{default}}$  in  $\text{id}_{\text{default}}^*$

- k. Check that  $\text{typeIR}^{''''}$  is defined, for all  $\text{typeIR}^{''''}$  in  $\text{typeIR}^{''''*}$ .

- l. Let  $\text{typeIR}_{\text{field\_b\_default}}^*$  be the list of  $\text{typeIR}_{\text{field\_b\_default}}$ , obtained by repeating:
  - Let  $\text{typeIR}_{\text{field\_b\_default}}$  be  $\text{typeIR}^{''''}$ .

for each  $\text{typeIR}^{''''}$  in  $\text{typeIR}^{''''*}$

- m. Check that  $\text{typeIR}_{\text{field\_b\_default}}$  can be default-initialized, for all  $\text{typeIR}_{\text{field\_b\_default}}$  in  $\text{typeIR}_{\text{field\_b\_default}}^*$ .

- n. The relation holds.

## 17.2. Implicit casts

To keep the language simple and avoid introducing hidden costs, the main implicit casts in P4 are casts from `int` to fixed-width types and from enums with an underlying type to the underlying type. In particular, applying a binary operation (except shifts and concatenation) to an expression of type `int` and an expression with a fixed-width type will implicitly cast the `int` expression to the type of the other expression. For enums with an underlying type, it can be implicitly cast to its underlying type whenever appropriate, including but not limited to in shifts, concatenation, bit slicing indexes, header stack indexes as well as other unary and binary operations.

For example, given the following declarations,

```
enum bit<8> E {
    a = 5
}

bit<8> x;
bit<16> y;
int<8> z;
```

the compiler will add implicit casts as follows:

- $x + 1$  becomes  $x + (\text{bit}<8>)1$
- $z < 0$  becomes  $z < (\text{int}<8>)0$
- $x | 0xFFF$  becomes  $x | (\text{bit}<8>)0xFFF$ ; overflow warning
- $x + E.a$  becomes  $x + (\text{bit}<8>)E.a$
- $x \&\&\& 8$  becomes  $x \&\&\& (\text{bit}<8>)8$
- $x \ll 256$  remains unchanged; 256 not implicitly cast to `8w0` in a shift; overflow warning

- `16w11 << E.a` becomes `16w11 << (bit<8>)E.a`
- `x[E.a:0]` becomes `x[(bit<8>)E.a:0]`
- `E.a ++ 8w0` becomes `(bit<8>)E.a ++ 8w0`

The compiler also adds implicit casts when types of different expressions need to match; for example, as described in Section [\[sec-select\]](#), since select labels are compared against the selected expression, the compiler will insert implicit casts for the select labels when they have `int` types. Similarly, when assigning a structure-valued expression to a structure or header, the compiler will add implicit casts for `int` fields.

The below relation checks whether a type can be implicitly cast to another type.

**Cast\_impl:**

- `typeIRa` can be implicitly cast to `typeIRb`

First, the two types are unrolled and checked to see if they are the same type. If so, no cast is needed.

`typeIRa` can be implicitly cast to `typeIRb` when:

1. Let `typeIRa_unroll` be `typeIRa` with typedefs unrolled.
2. Let `typeIRb_unroll` be `typeIRb` with typedefs unrolled.
3. If `typeIRa_unroll` and `typeIRb_unroll` are the same type:
  - a. The relation holds.
4. Else:
  - a. Check that `typeIRa_unroll` can be implicitly cast to `typeIRb_unroll` (when unequal).
  - b. The relation holds.

If the two types are not equal, the below relation is applied.

**Cast\_impl\_neq:**

- `typeIR` can be implicitly cast to `typeIR'` (when unequal)

**Cast from `int` to `int<S>` or `bit<W>`**

`INT` can be implicitly cast to `typeIR'` (when unequal) when:

1. If `typeIR'` has type `fixedIntTypeIR`:
  - a. The relation holds.
2. Else if `typeIR'` has type `fixedBitTypeIR`:
  - a. The relation holds.



### Cast from an enum with an underlying type to the underlying type

`ENUM typeId < typeIRa > { valueFieldIR* }` can be implicitly cast to `typeIR'` (when unequal) when:

1. Check that `typeIRa` can be implicitly cast to `typeIR'`.
2. The relation holds.

### Cast from a default type to the target type

`DEFAULT` can be implicitly cast to `typeIR'` (when unequal) when:

1. Check that `typeIR'` can be default-initialized.
2. The relation holds.

### Cast from an invalid header type to a header or header union type

`HEADER_INVALID` can be implicitly cast to `typeIR'` (when unequal) when:

1. If `typeIR'` has type `headerTypeIR`:
  - a. The relation holds.
2. Else if `typeIR'` has type `headerUnionTypeIR`:
  - a. The relation holds.

### Cast from a sequence type to a list, tuple, header stack, struct, header, or another sequence type

`SEQ < typeIRa* >` can be implicitly cast to `typeIR'` (when unequal) when:

1. If let `LIST < typeIRb >` be `typeIR'`:
  - a. Check that `typeIRa` can be implicitly cast to `typeIRb`, for all `typeIRa` in `typeIRa*`.
  - b. The relation holds.
2. Else if let `TUPLE < typeIRb* >` be `typeIR'`:
  - a. Check that `typeIRa` can be implicitly cast to `typeIRb`, for all `typeIRa` in `typeIRa*` and `typeIRb` in `typeIRb*`.
  - b. The relation holds.
3. Else if let `typeIRb [ nsize ]` be `typeIR'`:
  - a. Check that the length of `typeIRa*` is less than or equal to `nsize`.
  - b. Check that `typeIRa` can be implicitly cast to `typeIRb`, for all `typeIRa` in `typeIRa*`.
  - c. The relation holds.
4. Else if let `STRUCT _ < _* > { ( _ typeIRfield_b _ ; )* }` be `typeIR'`:
  - a. Check that `typeIRa` can be implicitly cast to `typeIRfield_b`, for all `typeIRa` in `typeIRa*` and `typeIRfield_b` in `typeIRfield_b*`.
  - b. The relation holds.
5. Else if let `HEADER _ < _* > { ( _ typeIRfield_b _ ; )* }` be `typeIR'`:

- a. Check that  $\text{typeIR}_a$  can be implicitly cast to  $\text{typeIR}_{\text{field}_b}$ , for all  $\text{typeIR}_a$  in  $\text{typeIR}_a^*$  and  $\text{typeIR}_{\text{field}_b}$  in  $\text{typeIR}_{\text{field}_b}^*$ .
  - b. The relation holds.
6. Else if let  $\text{sequenceTypeIR}'$  be  $\text{typeIR}'$ :
- a. Check that  $\text{sequenceTypeIR}'$  matches pattern  $\text{SEQ} < \% >$ .
  - b. Let  $\text{SEQ} < \text{typeIR}_b^* >$  be  $\text{sequenceTypeIR}'$ .
  - c. Check that  $\text{typeIR}_a$  can be implicitly cast to  $\text{typeIR}_b$ , for all  $\text{typeIR}_a$  in  $\text{typeIR}_a^*$  and  $\text{typeIR}_b$  in  $\text{typeIR}_b^*$ .
  - d. The relation holds.

### Cast from a sequence type with default initializer to a tuple, header stack, struct, or header type

$\text{SEQ} < \text{typeIR}_a^*, \dots >$  can be implicitly cast to  $\text{typeIR}'$  (when unequal) when:

1. If let  $\text{TUPLE} < \text{typeIR}_b^* >$  be  $\text{typeIR}'$ :
  - a. Check that the length of  $\text{typeIR}_a^*$  is less than the length of  $\text{typeIR}_b^*$ .
  - b. Let  $(\text{typeIR}_{b_{\text{non\_default}}}^*, \text{typeIR}_{b_{\text{default}}}^*)$  be  $\$partition\_<\text{typeIR}>(\text{typeIR}_b^*, \text{the length of } \text{typeIR}_a^*)$ .
  - c. Check that  $\text{typeIR}_a$  can be implicitly cast to  $\text{typeIR}_{b_{\text{non\_default}}}$ , for all  $\text{typeIR}_a$  in  $\text{typeIR}_a^*$  and  $\text{typeIR}_{b_{\text{non\_default}}}$  in  $\text{typeIR}_{b_{\text{non\_default}}}^*$ .
  - d. Check that  $\text{typeIR}_{b_{\text{default}}}$  can be default-initialized, for all  $\text{typeIR}_{b_{\text{default}}}$  in  $\text{typeIR}_{b_{\text{default}}}^*$ .
  - e. The relation holds.
2. Else if let  $\text{typeIR}_b [ n_{\text{size}} ]$  be  $\text{typeIR}'$ :
  - a. Check that the length of  $\text{typeIR}_a^*$  is less than  $n_{\text{size}}$ .
  - b. Check that  $\text{typeIR}_a$  can be implicitly cast to  $\text{typeIR}_b$ , for all  $\text{typeIR}_a$  in  $\text{typeIR}_a^*$ .
  - c. Check that  $\text{typeIR}_b$  can be default-initialized.
  - d. The relation holds.
3. Else if let  $\text{STRUCT\_} < \_ > \{ ( \_ \text{typeIR}_{\text{field}_b\_} ; )^* \}$  be  $\text{typeIR}'$ :
  - a. Check that the length of  $\text{typeIR}_a^*$  is less than the length of  $\text{typeIR}_{\text{field}_b}^*$ .
  - b. Let  $(\text{typeIR}_{\text{field}_b_{\text{non\_default}}}^*, \text{typeIR}_{\text{field}_b_{\text{default}}}^*)$  be  $\$partition\_<\text{typeIR}>(\text{typeIR}_{\text{field}_b}^*, \text{the length of } \text{typeIR}_a^*)$ .
  - c. Check that  $\text{typeIR}_a$  can be implicitly cast to  $\text{typeIR}_{\text{field}_b_{\text{non\_default}}}$ , for all  $\text{typeIR}_a$  in  $\text{typeIR}_a^*$  and  $\text{typeIR}_{\text{field}_b_{\text{non\_default}}}$  in  $\text{typeIR}_{\text{field}_b_{\text{non\_default}}}^*$ .
  - d. Check that  $\text{typeIR}_{\text{field}_b_{\text{default}}}$  can be default-initialized, for all  $\text{typeIR}_{\text{field}_b_{\text{default}}}$  in  $\text{typeIR}_{\text{field}_b_{\text{default}}}^*$ .
  - e. The relation holds.
4. Else if let  $\text{HEADER\_} < \_ > \{ ( \_ \text{typeIR}_{\text{field}_b\_} ; )^* \}$  be  $\text{typeIR}'$ :
  - a. Check that the length of  $\text{typeIR}_a^*$  is less than the length of  $\text{typeIR}_{\text{field}_b}^*$ .
  - b. Let  $(\text{typeIR}_{\text{field}_b_{\text{non\_default}}}^*, \text{typeIR}_{\text{field}_b_{\text{default}}}^*)$  be  $\$partition\_<\text{typeIR}>(\text{typeIR}_{\text{field}_b}^*, \text{the length of } \text{typeIR}_a^*)$ .
  - c. Check that  $\text{typeIR}_a$  can be implicitly cast to  $\text{typeIR}_{\text{field}_b_{\text{non\_default}}}$ , for all  $\text{typeIR}_a$  in  $\text{typeIR}_a^*$  and  $\text{typeIR}_{\text{field}_b_{\text{non\_default}}}$  in  $\text{typeIR}_{\text{field}_b_{\text{non\_default}}}^*$ .
  - d. Check that  $\text{typeIR}_{\text{field}_b_{\text{default}}}$  can be default-initialized, for all  $\text{typeIR}_{\text{field}_b_{\text{default}}}$  in  $\text{typeIR}_{\text{field}_b_{\text{default}}}^*$ .
  - e. The relation holds.

## Cast from a record type to a struct or header type

$\text{RECORD } \{ ( \_ \text{typeIR}_{\text{field\_a}} \text{ id}_{\text{field\_a}} ; )^* \}$  can be implicitly cast to  $\text{typeIR}'$  (when unequal) when:

1. If let  $\text{STRUCT } \_ < \_ > \{ ( \_ \text{typeIR}_{\text{field\_b}} \text{ id}_{\text{field\_b}} ; )^* \}$  be  $\text{typeIR}'$ :
  - a. Check that  $\{ \text{id}_{\text{field\_a}}^* \}$  is equal to  $\{ \text{id}_{\text{field\_b}}^* \}$ .
  - b. Let  $\text{typeIR}''^{?*$  be the list of  $\text{typeIR}''^?$ , obtained by repeating:
    - Let  $\text{typeIR}''^?$  be  $\text{id}_{\text{field\_a}}$  in map  $\{ ( \text{id}_{\text{field\_a}} : \text{typeIR}_{\text{field\_a}} )^* \}$ .
 for each  $\text{id}_{\text{field\_a}}$  in  $\text{id}_{\text{field\_a}}^*$
  - c. Check that  $\text{typeIR}''^?$  is defined, for all  $\text{typeIR}''^?$  in  $\text{typeIR}''^{?*$ .
  - d. Let  $\text{typeIR}_{\text{field\_a\_aligned}}^*$  be the list of  $\text{typeIR}_{\text{field\_a\_aligned}}$ , obtained by repeating:
    - Let  $\text{typeIR}_{\text{field\_a\_aligned}}$  be  $\text{typeIR}''^?$ .
 for each  $\text{typeIR}''^?$  in  $\text{typeIR}''^{?*$
  - e. Let  $\text{typeIR}'''^{?*$  be the list of  $\text{typeIR}'''^?$ , obtained by repeating:
    - Let  $\text{typeIR}'''^?$  be  $\text{id}_{\text{field\_a}}$  in map  $\{ ( \text{id}_{\text{field\_b}} : \text{typeIR}_{\text{field\_b}} )^* \}$ .
 for each  $\text{id}_{\text{field\_a}}$  in  $\text{id}_{\text{field\_a}}^*$
  - f. Check that  $\text{typeIR}'''^?$  is defined, for all  $\text{typeIR}'''^?$  in  $\text{typeIR}'''^{?*$ .
  - g. Let  $\text{typeIR}_{\text{field\_b\_aligned}}^*$  be the list of  $\text{typeIR}_{\text{field\_b\_aligned}}$ , obtained by repeating:
    - Let  $\text{typeIR}_{\text{field\_b\_aligned}}$  be  $\text{typeIR}'''^?$ .
 for each  $\text{typeIR}'''^?$  in  $\text{typeIR}'''^{?*$
  - h. Check that  $\text{typeIR}_{\text{field\_a\_aligned}}$  can be implicitly cast to  $\text{typeIR}_{\text{field\_b\_aligned}}$ , for all  $\text{typeIR}_{\text{field\_a\_aligned}}$  in  $\text{typeIR}_{\text{field\_a\_aligned}}^*$  and  $\text{typeIR}_{\text{field\_b\_aligned}}$  in  $\text{typeIR}_{\text{field\_b\_aligned}}^*$ .
  - i. The relation holds.
2. Else if let  $\text{HEADER } \_ < \_ > \{ ( \_ \text{typeIR}_{\text{field\_b}} \text{ id}_{\text{field\_b}} ; )^* \}$  be  $\text{typeIR}'$ :
  - a. Check that  $\{ \text{id}_{\text{field\_a}}^* \}$  is equal to  $\{ \text{id}_{\text{field\_b}}^* \}$ .
  - b. Let  $\text{typeIR}''^{?*$  be the list of  $\text{typeIR}''^?$ , obtained by repeating:
    - Let  $\text{typeIR}''^?$  be  $\text{id}_{\text{field\_a}}$  in map  $\{ ( \text{id}_{\text{field\_a}} : \text{typeIR}_{\text{field\_a}} )^* \}$ .
 for each  $\text{id}_{\text{field\_a}}$  in  $\text{id}_{\text{field\_a}}^*$
  - c. Check that  $\text{typeIR}''^?$  is defined, for all  $\text{typeIR}''^?$  in  $\text{typeIR}''^{?*$ .
  - d. Let  $\text{typeIR}_{\text{field\_a\_aligned}}^*$  be the list of  $\text{typeIR}_{\text{field\_a\_aligned}}$ , obtained by repeating:
    - Let  $\text{typeIR}_{\text{field\_a\_aligned}}$  be  $\text{typeIR}''^?$ .
 for each  $\text{typeIR}''^?$  in  $\text{typeIR}''^{?*$
  - e. Let  $\text{typeIR}'''^{?*$  be the list of  $\text{typeIR}'''^?$ , obtained by repeating:

- Let  $\text{typeIR}^{m?}$  be  $\text{id}_{\text{field}_a}$  in map  $\{ ( \text{id}_{\text{field}_b} : \text{typeIR}_{\text{field}_b} )^* \}$ .
- for each  $\text{id}_{\text{field}_a}$  in  $\text{id}_{\text{field}_a}^*$
- f. Check that  $\text{typeIR}^{m?}$  is defined, for all  $\text{typeIR}^{m?}$  in  $\text{typeIR}^{m?*$ .
- g. Let  $\text{typeIR}_{\text{field}_b\_aligned}^*$  be the list of  $\text{typeIR}_{\text{field}_b\_aligned}$ , obtained by repeating:
  - Let  $\text{typeIR}_{\text{field}_b\_aligned}$  be  $\text{typeIR}^{m?}$ .
  - for each  $\text{typeIR}^{m?}$  in  $\text{typeIR}^{m?*$
- h. Check that  $\text{typeIR}_{\text{field}_a\_aligned}$  can be implicitly cast to  $\text{typeIR}_{\text{field}_b\_aligned}$ , for all  $\text{typeIR}_{\text{field}_a\_aligned}$  in  $\text{typeIR}_{\text{field}_a\_aligned}^*$  and  $\text{typeIR}_{\text{field}_b\_aligned}$  in  $\text{typeIR}_{\text{field}_b\_aligned}^*$ .
- i. The relation holds.

### Cast from a record type with default initializer to a struct or header type

$\text{RECORD } \{ ( \_ \text{typeIR}_{\text{field}_a} \text{id}_{\text{field}_a} ; )^* , \dots \}$  can be implicitly cast to  $\text{typeIR}'$  (when unequal) when:

1. If let  $\text{STRUCT } \_ < \_ > \{ ( \_ \text{typeIR}_{\text{field}_b} \text{id}_{\text{field}_b} ; )^* \}$  be  $\text{typeIR}'$ :
  - a. Check that  $\{ \text{id}_{\text{field}_a}^* \}$  is a subset of  $\{ \text{id}_{\text{field}_b}^* \}$ .
  - b. Let  $\text{typeIR}^{n?}$  be the list of  $\text{typeIR}^{n?}$ , obtained by repeating:
    - Let  $\text{typeIR}^{n?}$  be  $\text{id}_{\text{field}_a}$  in map  $\{ ( \text{id}_{\text{field}_a} : \text{typeIR}_{\text{field}_a} )^* \}$ .
    - for each  $\text{id}_{\text{field}_a}$  in  $\text{id}_{\text{field}_a}^*$
  - c. Check that  $\text{typeIR}^{n?}$  is defined, for all  $\text{typeIR}^{n?}$  in  $\text{typeIR}^{n?*$ .
  - d. Let  $\text{typeIR}_{\text{field}_a\_aligned}^*$  be the list of  $\text{typeIR}_{\text{field}_a\_aligned}$ , obtained by repeating:
    - Let  $\text{typeIR}_{\text{field}_a\_aligned}$  be  $\text{typeIR}^{n?}$ .
    - for each  $\text{typeIR}^{n?}$  in  $\text{typeIR}^{n?*$
  - e. Let  $\text{typeIR}^{m?*$  be the list of  $\text{typeIR}^{m?}$ , obtained by repeating:
    - Let  $\text{typeIR}^{m?}$  be  $\text{id}_{\text{field}_a}$  in map  $\{ ( \text{id}_{\text{field}_b} : \text{typeIR}_{\text{field}_b} )^* \}$ .
    - for each  $\text{id}_{\text{field}_a}$  in  $\text{id}_{\text{field}_a}^*$
  - f. Check that  $\text{typeIR}^{m?}$  is defined, for all  $\text{typeIR}^{m?}$  in  $\text{typeIR}^{m?*$ .
  - g. Let  $\text{typeIR}_{\text{field}_b\_non\_default\_aligned}^*$  be the list of  $\text{typeIR}_{\text{field}_b\_non\_default\_aligned}$ , obtained by repeating:
    - Let  $\text{typeIR}_{\text{field}_b\_non\_default\_aligned}$  be  $\text{typeIR}^{m?}$ .
    - for each  $\text{typeIR}^{m?}$  in  $\text{typeIR}^{m?*$
  - h. Check that  $\text{typeIR}_{\text{field}_a\_aligned}$  can be implicitly cast to  $\text{typeIR}_{\text{field}_b\_non\_default\_aligned}$ , for all  $\text{typeIR}_{\text{field}_a\_aligned}$  in  $\text{typeIR}_{\text{field}_a\_aligned}^*$  and  $\text{typeIR}_{\text{field}_b\_non\_default\_aligned}$  in  $\text{typeIR}_{\text{field}_b\_non\_default\_aligned}^*$ .
  - i. Let  $\{ \text{id}_{\text{default}}^* \}$  be the difference of the sets  $\{ \text{id}_{\text{field}_b}^* \}$  and  $\{ \text{id}_{\text{field}_a}^* \}$ .
  - j. Let  $\text{typeIR}^{m?*$  be the list of  $\text{typeIR}^{m?}$ , obtained by repeating:

- Let  $\text{typeIR}^{\text{""?}}$  be  $\text{id}_{\text{default}}$  in map  $\{ ( \text{id}_{\text{field\_b}} : \text{typeIR}_{\text{field\_b}} )^* \}$ .
- for each  $\text{id}_{\text{default}}$  in  $\text{id}_{\text{default}}^*$
- k. Check that  $\text{typeIR}^{\text{""?}}$  is defined, for all  $\text{typeIR}^{\text{""?}}$  in  $\text{typeIR}^{\text{""?}*}$ .
- l. Let  $\text{typeIR}_{\text{field\_b\_default}}^*$  be the list of  $\text{typeIR}_{\text{field\_b\_default}}$ , obtained by repeating:
  - Let  $\text{typeIR}_{\text{field\_b\_default}}$  be  $\text{typeIR}^{\text{""?}}$ .
  - for each  $\text{typeIR}^{\text{""?}}$  in  $\text{typeIR}^{\text{""?}*}$
- m. Check that  $\text{typeIR}_{\text{field\_b\_default}}$  can be default-initialized, for all  $\text{typeIR}_{\text{field\_b\_default}}$  in  $\text{typeIR}_{\text{field\_b\_default}}^*$ .
- n. The relation holds.
- 2. Else if let  $\text{HEADER\_} < \_ > \{ ( \_ \text{typeIR}_{\text{field\_b}} \text{id}_{\text{field\_b}} ; )^* \}$  be  $\text{typeIR}'$ :
  - a. Check that  $\{ \text{id}_{\text{field\_a}}^* \}$  is a subset of  $\{ \text{id}_{\text{field\_b}}^* \}$ .
  - b. Let  $\text{typeIR}^{\text{'?}}$  be the list of  $\text{typeIR}^{\text{'?}}$ , obtained by repeating:
    - Let  $\text{typeIR}^{\text{'?}}$  be  $\text{id}_{\text{field\_a}}$  in map  $\{ ( \text{id}_{\text{field\_a}} : \text{typeIR}_{\text{field\_a}} )^* \}$ .
    - for each  $\text{id}_{\text{field\_a}}$  in  $\text{id}_{\text{field\_a}}^*$
  - c. Check that  $\text{typeIR}^{\text{'?}}$  is defined, for all  $\text{typeIR}^{\text{'?}}$  in  $\text{typeIR}^{\text{'?}*}$ .
  - d. Let  $\text{typeIR}_{\text{field\_a\_aligned}}^*$  be the list of  $\text{typeIR}_{\text{field\_a\_aligned}}$ , obtained by repeating:
    - Let  $\text{typeIR}_{\text{field\_a\_aligned}}$  be  $\text{typeIR}^{\text{'?}}$ .
    - for each  $\text{typeIR}^{\text{'?}}$  in  $\text{typeIR}^{\text{'?}*}$
  - e. Let  $\text{typeIR}^{\text{""?}}$  be the list of  $\text{typeIR}^{\text{'?}}$ , obtained by repeating:
    - Let  $\text{typeIR}^{\text{""?}}$  be  $\text{id}_{\text{field\_a}}$  in map  $\{ ( \text{id}_{\text{field\_b}} : \text{typeIR}_{\text{field\_b}} )^* \}$ .
    - for each  $\text{id}_{\text{field\_a}}$  in  $\text{id}_{\text{field\_a}}^*$
  - f. Check that  $\text{typeIR}^{\text{""?}}$  is defined, for all  $\text{typeIR}^{\text{""?}}$  in  $\text{typeIR}^{\text{""?}*}$ .
  - g. Let  $\text{typeIR}_{\text{field\_b\_non\_default\_aligned}}^*$  be the list of  $\text{typeIR}_{\text{field\_b\_non\_default\_aligned}}$ , obtained by repeating:
    - Let  $\text{typeIR}_{\text{field\_b\_non\_default\_aligned}}$  be  $\text{typeIR}^{\text{""?}}$ .
    - for each  $\text{typeIR}^{\text{""?}}$  in  $\text{typeIR}^{\text{""?}*}$
  - h. Check that  $\text{typeIR}_{\text{field\_a\_aligned}}$  can be implicitly cast to  $\text{typeIR}_{\text{field\_b\_non\_default\_aligned}}$ , for all  $\text{typeIR}_{\text{field\_a\_aligned}}$  in  $\text{typeIR}_{\text{field\_a\_aligned}}^*$  and  $\text{typeIR}_{\text{field\_b\_non\_default\_aligned}}$  in  $\text{typeIR}_{\text{field\_b\_non\_default\_aligned}}^*$ .
  - i. Let  $\{ \text{id}_{\text{default}}^* \}$  be the difference of the sets  $\{ \text{id}_{\text{field\_b}}^* \}$  and  $\{ \text{id}_{\text{field\_a}}^* \}$ .
  - j. Let  $\text{typeIR}^{\text{""?}*}$  be the list of  $\text{typeIR}^{\text{""?}}$ , obtained by repeating:
    - Let  $\text{typeIR}^{\text{""?}}$  be  $\text{id}_{\text{default}}$  in map  $\{ ( \text{id}_{\text{field\_b}} : \text{typeIR}_{\text{field\_b}} )^* \}$ .
    - for each  $\text{id}_{\text{default}}$  in  $\text{id}_{\text{default}}^*$
  - k. Check that  $\text{typeIR}^{\text{""?}}$  is defined, for all  $\text{typeIR}^{\text{""?}}$  in  $\text{typeIR}^{\text{""?}*}$ .
  - l. Let  $\text{typeIR}_{\text{field\_b\_default}}^*$  be the list of  $\text{typeIR}_{\text{field\_b\_default}}$ , obtained by repeating:

- Let  $\text{typeIR}_{\text{field\_b\_default}}$  be  $\text{typeIR}^{\text{""}^?}$ .

for each  $\text{typeIR}^{\text{""}^?}$  in  $\text{typeIR}^{\text{""}^?^*}$

- m. Check that  $\text{typeIR}_{\text{field\_b\_default}}$  can be default-initialized, for all  $\text{typeIR}_{\text{field\_b\_default}}$  in  $\text{typeIR}_{\text{field\_b\_default}}^*$ .
- n. The relation holds.

## 17.3. Cast insertion

When typing a  $P4_{16}$  program to a  $P4_{IR}$  program, all implicit casts are made explicit. This process is called *cast insertion*. A cast may be inserted such that an expression matches the expected type, and it may also be inserted to ensure that two expressions have the same type.

### 17.3.1. Casts to match expected type

The below function inserts casts to match expected types.

$\$cast\_unary$ :

- $\text{typedExpressionIR}$  implicitly cast to  $\text{typeIR}_{to}$

$\text{typedExpressionIR}$  implicitly cast to  $\text{typeIR}_{to}$

1. Let a pair of type  $\text{typeIR}$  and compile-time known-ness  $ctk$  be the note of  $\text{typedExpressionIR}$ .
2. If  $\text{typeIR}$  and  $\text{typeIR}_{to}$  are the same type:
  - a. Return  $\text{typedExpressionIR}$ .
3. Else:
  - a. Check that  $\text{typeIR}$  can be implicitly cast to  $\text{typeIR}_{to}$ .
  - b. Let  $\text{typedExpressionIR}_{cast}$  be (  $\text{typeIR}_{to}$  )  $\text{typedExpressionIR}$  annotated with a pair of type  $\text{typeIR}_{to}$  and compile-time known-ness  $ctk$ .
  - c. Return  $\text{typedExpressionIR}_{cast}$ .

### 17.3.2. Casts to ensure type equality

The below function inserts casts to ensure that two expressions have the same type.

$\$cast\_binary$ :

- $\text{typedExpressionIR}_l$  and  $\text{typedExpressionIR}_r$  implicitly cast to equal types

$\text{typedExpressionIR}_l$  and  $\text{typedExpressionIR}_r$  implicitly cast to equal types

1. Let a pair of type  $\text{typeIR}_l$  and compile-time known-ness  $_$  be the note of  $\text{typedExpressionIR}_l$ .
2. Let a pair of type  $\text{typeIR}_r$  and compile-time known-ness  $_$  be the note of  $\text{typedExpressionIR}_r$ .

3. If  $\text{typeIR}_i$  and  $\text{typeIR}_r$  are the same type:
  - a. Return (  $\text{typedExpressionIR}_i$ ,  $\text{typedExpressionIR}_r$  ).
4. Else:
  - a. If  $\text{typeIR}_i$  can be implicitly cast to  $\text{typeIR}_r$ :
    - i. Let  $\text{typedExpressionIR}_{i\_cast}$  be (  $\text{typeIR}_r$  )  $\text{typedExpressionIR}_i$  annotated with a pair of type  $\text{typeIR}_r$  and compile-time known-ness  $\_$ .
    - ii. Return (  $\text{typedExpressionIR}_{i\_cast}$ ,  $\text{typedExpressionIR}_r$  ).
  - b. Else:
    - i. If  $\text{typeIR}_r$  can be implicitly cast to  $\text{typeIR}_i$ :
      - A. Let  $\text{typedExpressionIR}_{r\_cast}$  be (  $\text{typeIR}_i$  )  $\text{typedExpressionIR}_r$  annotated with a pair of type  $\text{typeIR}_i$  and compile-time known-ness  $\_$ .
      - B. Return (  $\text{typedExpressionIR}_i$ ,  $\text{typedExpressionIR}_{r\_cast}$  ).
    - ii. Else:
      - A. Let  $\text{typedExpressionIR}_{i\_cast}$  be  $\text{typedExpressionIR}_i$  with surrounding serializable enums reduced.
      - B. If  $\text{typedExpressionIR}_i$  is not equal to  $\text{typedExpressionIR}_{i\_cast}$ :
        - I. Return  $\text{typedExpressionIR}_{i\_cast}$  and  $\text{typedExpressionIR}_r$  implicitly cast to equal types.
      - C. If  $\text{typedExpressionIR}_i$  is equal to  $\text{typedExpressionIR}_{i\_cast}$ :
        - I. Let  $\text{typedExpressionIR}_{r\_cast}$  be  $\text{typedExpressionIR}_r$  with surrounding serializable enums reduced.
        - II. Check that  $\text{typedExpressionIR}_r$  is not equal to  $\text{typedExpressionIR}_{r\_cast}$ .
        - III. Return  $\text{typedExpressionIR}_i$  and  $\text{typedExpressionIR}_{r\_cast}$  implicitly cast to equal types.
5. Otherwise:
  - a. Return  $\cdot$ .

## 17.4. Performing casts

Cast operations are evaluated with:

$\$cast\_op$ :

- $value$  casted to type  $\text{typeIR}$

$value$  casted to type  $\text{typeIR}$

1. If let  $boolValue$  be  $value$ :
  - a. Let  $\text{typeIR}_{unroll}$  be  $\text{typeIR}$  with typedefs unrolled.
  - b. Return  $boolValue$  casted to type  $\text{typeIR}_{unroll}$ .
2. Else if let  $integerValue$  be  $value$ :
  - a. Let  $\text{typeIR}_{unroll}$  be  $\text{typeIR}$  with typedefs unrolled.
  - b. Return  $integerValue$  casted to type  $\text{typeIR}_{unroll}$ .

3. Else if let `errorValue` be `value`:
  - a. Let `typeIRunroll` be `typeIR` with `typedefs` unrolled.
  - b. Return `errorValue` casted to type `typeIRunroll`.
4. Else if let `listValue` be `value`:
  - a. Let `typeIRunroll` be `typeIR` with `typedefs` unrolled.
  - b. Return `listValue` casted to type `typeIRunroll`.
5. Else if let `headerStackValue` be `value`:
  - a. Let `typeIRunroll` be `typeIR` with `typedefs` unrolled.
  - b. Return `headerStackValue` casted to type `typeIRunroll`.
6. Else if let `structValue` be `value`:
  - a. Let `typeIRunroll` be `typeIR` with `typedefs` unrolled.
  - b. Return `structValue` casted to type `typeIRunroll`.
7. Else if let `headerValue` be `value`:
  - a. Let `typeIRunroll` be `typeIR` with `typedefs` unrolled.
  - b. Return `headerValue` casted to type `typeIRunroll`.
8. Else if let `enumValue` be `value`:
  - a. Let `typeIRunroll` be `typeIR` with `typedefs` unrolled.
  - b. Return `enumValue` casted to type `typeIRunroll`.
9. Else if let `sequenceValue` be `value`:
  - a. Let `typeIRunroll` be `typeIR` with `typedefs` unrolled.
  - b. Return `sequenceValue` casted to type `typeIRunroll`.
10. Else if let `recordValue` be `value`:
  - a. Let `typeIRunroll` be `typeIR` with `typedefs` unrolled.
  - b. Return `recordValue` casted to type `typeIRunroll`.
11. Else if let `defaultValue` be `value`:
  - a. Let `typeIRunroll` be `typeIR` with `typedefs` unrolled.
  - b. Return `DEFAULT` casted to type `typeIRunroll`.
12. Else if `value` has type `invalidHeaderValue`:
  - a. Let `typeIRunroll` be `typeIR` with `typedefs` unrolled.
  - b. Return `{#}` casted to type `typeIRunroll`.
13. Else if let `setValue` be `value`:
  - a. Let `typeIRunroll` be `typeIR` with `typedefs` unrolled.
  - b. Return `setValue` casted to type `typeIRunroll`.

#### From a **bool** value

`boolValue` casted to type `typeIR`

1. Let ``B b` be `boolValue`.



2. If let `boolTypeIR` be `typeIR`:
  - a. Return ``B b`.
3. If let `BIT < w >` be `typeIR`:
  - a. If `boolValue` is equal to ``B true`:
    - i. Return `w W 1`.
  - b. If `boolValue` is equal to ``B false`:
    - i. Return `w W 0`.
4. Else if let `TYPE _ typeIR'` be `typeIR`:
  - a. Return `boolValue casted to type typeIR'`.
5. Else if let `SET < typeIR' >` be `typeIR`:
  - a. Let `value` be `boolValue casted to type typeIR'`.
  - b. Return `SET { value }`.

### From an integer value

`integerValue casted to type typeIR`

1. If let `boolTypeIR` be `typeIR`:
  - a. Check that `integerValue` has type `integerLiteral`.
  - b. Let `integerLiteral` be `integerValue`.
  - c. If let `D i` be `integerLiteral`:
    - i. Return ``B i != 0`.
  - d. Else if let `w W i` be `integerLiteral`:
    - i. Return ``B i != 0`.
2. Else if let `intTypeIR` be `typeIR`:
  - a. Check that `integerValue` has type `integerLiteral`.
  - b. Let `integerLiteral` be `integerValue`.
  - c. If let `D i` be `integerLiteral`:
    - i. Return `D i`.
  - d. Else if let `_ W i` be `integerLiteral`:
    - i. Return `D i`.
  - e. Else:
    - i. Let `w S i` be `integerLiteral`.
    - ii. Let `int` be `the two's complement representation of bitstring i of width w`.
    - iii. Return `D int`.
3. Else if let `BIT < wto >` be `typeIR`:
  - a. Check that `integerValue` has type `integerLiteral`.
  - b. Let `integerLiteral` be `integerValue`.
  - c. If let `D i` be `integerLiteral`:

- i. Let  $i_{\text{cast}}$  be the bitstring of width  $w_{\text{to}}$  representing the integer  $i$ .
    - ii. Return  $w_{\text{to}} \ W \ i_{\text{cast}}$ .
  - d. Else if let  $\_W \ i$  be integerLiteral:
    - i. Let  $i_{\text{cast}}$  be the bitstring of width  $w_{\text{to}}$  representing the integer  $i$ .
    - ii. Return  $w_{\text{to}} \ W \ i_{\text{cast}}$ .
  - e. Else:
    - i. Let  $w_{\text{from}} \ S \ i$  be integerLiteral.
    - ii. Let  $i_{\text{from}}$  be the two's complement representation of bitstring  $i$  of width  $w_{\text{from}}$ .
    - iii. Let  $i_{\text{cast}}$  be the bitstring of width  $w_{\text{to}}$  representing the integer  $i_{\text{from}}$ .
    - iv. Return  $w_{\text{to}} \ W \ i_{\text{cast}}$ .
4. Else if let  $\text{INT} < w_{\text{to}} >$  be typeIR:
- a. Check that integerValue has type integerLiteral.
  - b. Let integerLiteral be integerValue.
  - c. If let  $D \ i$  be integerLiteral:
    - i. Let  $i_{\text{cast}}$  be the bitstring of width  $w_{\text{to}}$  representing the integer  $i$ .
    - ii. Return  $w_{\text{to}} \ S \ i_{\text{cast}}$ .
  - d. Else if let  $\_W \ i$  be integerLiteral:
    - i. Let  $i_{\text{cast}}$  be the bitstring of width  $w_{\text{to}}$  representing the integer  $i$ .
    - ii. Return  $w_{\text{to}} \ S \ i_{\text{cast}}$ .
  - e. Else:
    - i. Let  $w_{\text{from}} \ S \ i$  be integerLiteral.
    - ii. Let  $i_{\text{from}}$  be the two's complement representation of bitstring  $i$  of width  $w_{\text{from}}$ .
    - iii. Let  $i_{\text{cast}}$  be the bitstring of width  $w_{\text{to}}$  representing the integer  $i_{\text{from}}$ .
    - iv. Return  $w_{\text{to}} \ S \ i_{\text{cast}}$ .
5. Else if let  $\text{VARBIT} < w_{\text{max}} >$  be typeIR:
- a. Check that integerValue matches pattern  $\% . \% V \%$ .
  - b. Let  $w_{\text{max}}' . w \ V \ i$  be integerValue.
  - c. Check that  $w_{\text{max}}$  is equal to  $w_{\text{max}}'$ .
  - d. Return  $w_{\text{max}} . w \ V \ i$ .
6. Else if let  $\text{TYPE} \_ \text{typeIR}'$  be typeIR:
- a. Check that integerValue has type integerLiteral.
  - b. Let integerLiteral be integerValue.
  - c. If let  $D \ i$  be integerLiteral:
    - i. Return  $D \ i$  casted to type  $\text{typeIR}'$ .
  - d. Else if let  $w \ W \ i$  be integerLiteral:
    - i. Return  $w \ W \ i$  casted to type  $\text{typeIR}'$ .
  - e. Else:
    - i. Let  $w \ S \ i$  be integerLiteral.

- ii. Return `w S i` **casted to type** `typeIR'`.
- 7. Else if let `enumTypeIR` be `typeIR`:
  - a. Check that `integerValue` has type `integerLiteral`.
  - b. Let `integerLiteral` be `integerValue`.
  - c. If let `w W i` be `integerLiteral`:
    - i. Return `w W i` **casted to enum type** `enumTypeIR`.
  - d. Else if let `w S i` be `integerLiteral`:
    - i. Return `w S i` **casted to enum type** `enumTypeIR`.
- 8. Else if let `SET < typeIR' >` be `typeIR`:
  - a. Check that `integerValue` has type `integerLiteral`.
  - b. Let `integerLiteral` be `integerValue`.
  - c. If let `D i` be `integerLiteral`:
    - i. Let `value` be `D i` **casted to type** `typeIR'`.
    - ii. Return `SET { value }`.
  - d. Else if let `w W i` be `integerLiteral`:
    - i. Let `value` be `w W i` **casted to type** `typeIR'`.
    - ii. Return `SET { value }`.
  - e. Else:
    - i. Let `w S i` be `integerLiteral`.
    - ii. Let `value` be `w S i` **casted to type** `typeIR'`.
    - iii. Return `SET { value }`.

#### From an error value

`errorValue` **casted to type** `typeIR`

1. Let `ERROR . nameIR` be `errorValue`.
2. If let `errorTypeIR` be `typeIR`:
  - a. Return `ERROR . nameIR`.
3. If let `SET < typeIR' >` be `typeIR`:
  - a. Let `value` be `errorValue` **casted to type** `typeIR'`.
  - b. Return `SET { value }`.

#### From a list value

`LIST [ value* ]` **casted to type** `typeIR`

1. Check that `typeIR` has type `listTypeIR`.
2. Let `LIST < typeIR' >` be `typeIR`.

3. Let  $\text{value}^*$  be the list of  $\text{value}'$ , obtained by repeating:

- Let  $\text{value}'$  be  $\text{value}$  **casted to type**  $\text{typeIR}'$ .

for each  $\text{value}$  in  $\text{value}^*$

4. Return  $\text{LIST} [ \text{value}^* ]$ .

#### From a header stack value

$\text{HEADER\_STACK} [ \text{value}^* ( n_{\text{idx}} ; n_{\text{size}} ) ]$  **casted to type**  $\text{typeIR}$

1. Check that  $\text{typeIR}$  has type  $\text{headerStackTypeIR}$ .
2. Let  $\text{typeIR}' [ n_{\text{size}} ]$  be  $\text{typeIR}$ .
3. Check that  $n_{\text{size}}$  is equal to  $n_{\text{size}}$ .
4. Return  $\text{HEADER\_STACK} [ \text{value}^* ( n_{\text{idx}} ; n_{\text{size}} ) ]$ .

#### From a struct value

$\text{STRUCT typeID} \{ ( \text{value}_{\text{field}} \text{ nameIR}_{\text{field}} ; )^* \}$  **casted to type**  $\text{typeIR}$

1. Check that  $\text{typeIR}$  has type  $\text{structTypeIR}$ .
2. Let  $\text{STRUCT typeID}' < \_ * > \{ \_ * \}$  be  $\text{typeIR}$ .
3. Check that  $\text{typeID}'$  is equal to  $\text{typeID}'$ .
4. Return  $\text{STRUCT typeID}' \{ ( \text{value}_{\text{field}} \text{ nameIR}_{\text{field}} ; )^* \}$ .

#### From a header value

$\text{HEADER typeID} \{ b ; ( \text{value}_{\text{field}} \text{ nameIR}_{\text{field}} ; )^* \}$  **casted to type**  $\text{typeIR}$

1. Check that  $\text{typeIR}$  has type  $\text{headerTypeIR}$ .
2. Let  $\text{HEADER typeID}' < \_ * > \{ \_ * \}$  be  $\text{typeIR}$ .
3. Check that  $\text{typeID}'$  is equal to  $\text{typeID}'$ .
4. Return  $\text{HEADER typeID}' \{ b ; ( \text{value}_{\text{field}} \text{ nameIR}_{\text{field}} ; )^* \}$ .

#### From an enum value

$\text{enumValue}$  **casted to type**  $\text{typeIR}$

1. If let  $\text{ENUM typeID} \{ \_ * \}$  be  $\text{typeIR}$ :
  - a. Check that  $\text{enumValue}$  matches pattern  $\% . \%$ .
  - b. Let  $\text{typeID}' . \text{nameIR}$  be  $\text{enumValue}$ .
  - c. Check that  $\text{typeID}$  is equal to  $\text{typeID}'$ .

- d. Return `typelR . nameIR`.
- 2. If let `_ . _ . value` be `enumValue`:
  - a. Return `value` **casted to type** `typelR`.

#### From a default value

`defaultValue` **casted to type** `typelR`

- 1. Return **the default value for type** `typelR`.

#### From an invalid header value

`{#}` **casted to type** `typelR`

- 1. If let `headerTypeIR` be `typelR`:
  - a. Return **the default value for type** `headerTypeIR`.
- 2. Else if let `headerUnionTypeIR` be `typelR`:
  - a. Return **the default value for type** `headerUnionTypeIR`.

#### From a sequence value

`sequenceValue` **casted to type** `typelR`

- 1. If let `LIST < typelR' >` be `typelR`:
  - a. Check that `sequenceValue` matches pattern `SEQ ( % )`.
  - b. Let `SEQ ( value* )` be `sequenceValue`.
  - c. Let `value*` be the list of `value'`, obtained by repeating:
    - Let `value'` be `value` **casted to type** `typelR'`.
 for each `value` in `value*`
  - d. Return `LIST [ value* ]`.
- 2. Else if let `TUPLE < typelR'* >` be `typelR`:
  - a. Check that `sequenceValue` matches pattern `SEQ ( % )`.
  - b. Let `SEQ ( value* )` be `sequenceValue`.
  - c. Let `value*` be the list of `value'` and `value**` be the list of `value*`, obtained by repeating:
    - Let `value'` be `value` **casted to type** `typelR'`.
 for each `typelR'` in `typelR'*` and `value` in `value*`
  - d. Return `TUPLE ( value* )`.
- 3. Else if let `typelR' [ nsize ]` be `typelR`:

- a. Check that `sequenceValue` matches pattern `SEQ ( % )`.
  - b. Let `SEQ ( value* )` be `sequenceValue`.
  - c. Let `valuecast*` be the list of `valuecast`, obtained by repeating:
    - Let `valuecast` be `value` **casted to type** `typeIR`.
 for each `value` in `value*`
  - d. Let `nidx` be the length of `value*`.
  - e. Return `HEADER_STACK [ valuecast* ( nidx ; nsize ) ]`.
4. Else if let `STRUCT typeId < _* > { ( _ typeIRfield nameIRfield ; )* }` be `typeIR`:
    - a. Check that `sequenceValue` matches pattern `SEQ ( % )`.
    - b. Let `SEQ ( value* )` be `sequenceValue`.
    - c. Let `valuecast*` be the list of `valuecast`, obtained by repeating:
      - Let `valuecast` be `value` **casted to type** `typeIRfield`.
 for each `typeIRfield` in `typeIRfield*` and `value` in `value*`
    - d. Return `STRUCT typeId { ( valuecast nameIRfield ; )* }`.
  5. Else if let `HEADER typeId < _* > { ( _ typeIRfield nameIRfield ; )* }` be `typeIR`:
    - a. Check that `sequenceValue` matches pattern `SEQ ( % )`.
    - b. Let `SEQ ( value* )` be `sequenceValue`.
    - c. Let `valuecast*` be the list of `valuecast`, obtained by repeating:
      - Let `valuecast` be `value` **casted to type** `typeIRfield`.
 for each `typeIRfield` in `typeIRfield*` and `value` in `value*`
    - d. Return `HEADER typeId { true ; ( valuecast nameIRfield ; )* }`.

### From a record value

`recordValue` **casted to type** `typeIR`

1. If let `STRUCT typeId < _* > { ( _ typeIRtfield idtfield ; )* }` be `typeIR`:
  - a. Check that `recordValue` matches pattern `RECORD { % }`.
  - b. Let `RECORD { ( valuefield nameIRfield ; )* }` be `recordValue`.
  - c. Let `value?*` be the list of `value?`, obtained by repeating:
    - Let `value?` be `idtfield` **in map** `{ ( nameIRfield : valuefield )* }`.
 for each `idtfield` in `idtfield*`
  - d. Check that `value?` is defined, for all `value?` in `value?*`.
  - e. Let `valuefield'*` be the list of `valuefield'`, obtained by repeating:
    - Let `valuefield'` be `value?`.

for each  $value^?$  in  $value^{?*$

f. Let  $value_{field\_cast}^*$  be the list of  $value_{field\_cast}$  obtained by repeating:

- Let  $value_{field\_cast}$  be  $value_{field'}$  casted to type  $typeIR_{t\_field}$ .

for each  $typeIR_{t\_field}$  in  $typeIR_{t\_field}^*$  and  $value_{field'}$  in  $value_{field'}^*$

g. Return  $STRUCT\ typeId\ \{ (value_{field\_cast}\ nameIR_{field} ; )^* \}$ .

2. Else if let  $HEADER\ typeId\ < \_ > \{ ( \_ typeIR_{t\_field}\ id_{t\_field} ; )^* \}$  be  $typeIR$ :

a. Check that  $recordValue$  matches pattern  $RECORD\ \{ \% \}$ .

b. Let  $RECORD\ \{ (value_{field}\ nameIR_{field} ; )^* \}$  be  $recordValue$ .

c. Let  $value^{?*$  be the list of  $value^?$ , obtained by repeating:

- Let  $value^?$  be  $id_{t\_field}$  in  $map\ \{ (nameIR_{field} : value_{field} )^* \}$ .

for each  $id_{t\_field}$  in  $id_{t\_field}^*$

d. Check that  $value^?$  is defined, for all  $value^?$  in  $value^{?*$ .

e. Let  $value_{field'}^*$  be the list of  $value_{field'}$ , obtained by repeating:

- Let  $value_{field'}$  be  $value^?$ .

for each  $value^?$  in  $value^{?*$

f. Let  $value_{field\_cast}^*$  be the list of  $value_{field\_cast}$  obtained by repeating:

- Let  $value_{field\_cast}$  be  $value_{field'}$  casted to type  $typeIR_{t\_field}$ .

for each  $typeIR_{t\_field}$  in  $typeIR_{t\_field}^*$  and  $value_{field'}$  in  $value_{field'}^*$

g. Return  $HEADER\ typeId\ \{ true ; (value_{field\_cast}\ nameIR_{field} ; )^* \}$ .

## From a set value

$setValue$  casted to type  $typeIR$

1. Check that  $typeIR$  has type  $setTypeIR$ .

2. Let  $SET\ < typeIR' >$  be  $typeIR$ .

3. If let  $SET\ \{ value \}$  be  $setValue$ :

a. Let  $value'$  be  $value$  casted to type  $typeIR'$ .

b. Return  $SET\ \{ value' \}$ .

4. Else if let  $SET\ \{ value_b\ \&\&\&\ value_m \}$  be  $setValue$ :

a. Let  $value_{b\_cast}$  be  $value_b$  casted to type  $typeIR'$ .

b. Let  $value_{m\_cast}$  be  $value_m$  casted to type  $typeIR'$ .

c. Return  $SET\ \{ value_{b\_cast}\ \&\&\&\ value_{m\_cast} \}$ .

5. Else if let  $SET\ \{ value_l\ ..\ value_u \}$  be  $setValue$ :

a. Let  $value_{l\_cast}$  be  $value_l$  casted to type  $typeIR'$ .

- b. Let `valueu_cast` be `valueu` **casted to type** `typeIR`.
- c. Return `SET { valuel_cast .. valueu_cast }`.

## 18. Calls

Calls can be made in several different contexts:

- From call expressions ([Section 14.16](#)), to invoke a callable or a constructor.
- From call statements ([Section 13.4](#)), to invoke a callable.
- From a direct type invocation ([Section 13.5](#)), which is a syntactic sugar for invoking a constructor and then immediately calling an apply method on the resulting instance.
- From an instantiation declaration ([Section 11.4](#)), to invoke a constructor.

A callable invocation can optionally specify for each argument the corresponding parameter name. It is illegal to use names only for some arguments: either all or no arguments must specify the parameter name. Callable arguments are evaluated in the order they appear, left to right, before the function invocation takes place.

```
extern void f(in bit<32> x, out bit<16> y);
bit<32> xa = 0;
bit<16> ya;
f(xa, ya); // match arguments by position
f(x = xa, y = ya); // match arguments by name
f(y = ya, x = xa); // match arguments by name in any order
//f(x = xa); -- error: enough arguments
//f(x = xa, x = ya); -- error: argument specified twice
//f(x = xa, ya); -- error: some arguments specified by name
//f(z = xa, w = yz); -- error: no parameter named z or w
//f(x = xa, y = 0); -- error: y must be a left-value
```

The calling convention is copy-in/copy-out ([Section 6.5](#)). For generic callables and constructors the type arguments can be explicitly specified in the call. The compiler only inserts implicit casts for direction `in` or directionless arguments to methods, functions, or constructors as described in [\[sec-casts\]](#). The types for all other arguments must match the parameter types exactly.

The result returned by a call is discarded when the function call is used as a statement.

The "don't care" identifier (`_`) can only be used for an `out` function/method argument, when the value of returned in that argument is ignored by subsequent computations. When used in generic callables, the compiler may reject the program if it is unable to infer a type for the don't care argument.

This section describes the semantics of calls in detail. In particular, it explains how the call target is found (also with overload resolution), how the call convention is checked, and how the call is evaluated at runtime.

### 18.1. Call targets

Calls are composed of three components: the call target, type arguments, and arguments. Call target identifies what is being called. It may be a callable (actions, functions, and methods) or a constructor.

When calls are made from an expression, the call target is as follows:

```
callExpression
```



```

: callTarget `( argumentList )
| callableTarget `< realTypeArgumentList > `( argumentList )
;

callTarget
: callableTarget
| constructorTarget
;

callableTarget = expression

constructorTarget = namedType

```

When calls are made from a statement, the call target is as follows:

```

lvalue
: referenceExpression
| lvalue . member
| lvalue `[ expression ]
| lvalue `[ expression : expression ]
| `( lvalue )
;

callStatement
: lvalue `( argumentList ) ;
| lvalue `< typeArgumentList > `( argumentList ) ;
;

directApplicationStatement
: namedType . APPLY `( argumentList ) ;
;

```

And when calls are made from instantiation declarations, the call target is as follows:

```

instantiation
: annotationList type `( argumentList ) name ;
| annotationList type `( argumentList ) name objectInitializer ;
;

```

After type checking, call targets are represented as follows:

```

callableTargetIR
: referenceExpressionIR
| typedExpressionIR . nameIR
| TYPE prefixedNameIR . nameIR
| `( callableTargetIR )
;

constructorTargetIR
: prefixedNameIR `< typeArgumentListIR >
;

```

Thus, calls are represented as:

```

callExpressionIR
: constructorTargetIR `( argumentListIR )
| callableTargetIR `< typeArgumentListIR > `( argumentListIR )
;

callStatementIR
: callableTargetIR `< typeArgumentListIR > `( argumentListIR ) ;

```

```

;
directApplicationStatementIR
: constructorTargetIR . APPLY `( argumentListIR ) ;
;

instantiationIR
: annotationList typeIR constructorTargetIR `( argumentListIR ) nameIR
  objectInitializerOptIR ;
;

```

The following relation is used to check callable targets:

#### CallableTarget\_ok:

- Typing `callableTarget` as a callable target, under cursor `cursor` and context `typingContext`:
- Result in typed callable target `callableTargetIR`.

#### Typing `callableTarget` as a callable target, under cursor `p` and context `TC`:

1. If let `prefixedNonTypeName` be `callableTarget`:
  - a. Let `prefixedNameIR` be the prefixed name of `prefixedNonTypeName`.
  - b. Result in typed callable target `prefixedNameIR`.
2. Else if let `memberAccessBase . member` be `callableTarget`:
  - a. If let `prefixedTypeName` be `memberAccessBase`:
    - i. Let `prefixedNameIR` be the prefixed name of `prefixedTypeName`.
    - ii. Let `nameIR` be the name of `member`.
    - iii. Result in typed callable target `TYPE prefixedNameIR . nameIR`.
  - b. Else:
    - i. Let `expressionbase` be `memberAccessBase`.
    - ii. Let `nameIR` be the name of `member`.
    - iii. Let `typedExpressionIRbase` be
      - the result of typing `expressionbase`, under cursor `p` and context `TC`.
    - iv. Result in typed callable target `typedExpressionIRbase . nameIR`.
3. Else if let `( expression )` be `callableTarget`:
  - a. Let typed callable target `callableTargetIR` be
    - the result of typing `expression` as a callable target, under cursor `p` and context `TC`.
  - b. Result in typed callable target `( callableTargetIR )`.
4. If `callableTarget` is equal to `THIS`:
  - a. Result in typed callable target `"this"`.

When a l-value is used as a callable target, the following relation is used to check it:

#### CallableTarget\_lvalue\_ok:

- Typing `lvalue` as a callable target, under cursor `cursor` and context `typingContext`:
- Result in typed callable target `callableTargetIR`.

Typing `lvalue` as a callable target, under cursor `p` and context `TC`:

1. Let `expression` be the expression corresponding to `lvalue`.
2. Let typed callable target `callableTargetIR` be
  - the result of typing `expression` as a callable target, under cursor `p` and context `TC`.
3. Result in typed callable target `callableTargetIR`.

## 18.2. Overload resolution

As explained in [Section 6.6](#), functions, methods, and constructors can be overloaded. Overload should be resolved at compile time based on the number of arguments or the names of the arguments. Additionally, arguments may be omitted when the corresponding parameters have default values or are declared as optional.

The following algorithm is used to resolve overloads and omitted arguments:

`$find_overloaded`:

- Finding the item in  $\{ ( \text{callableId} : V )^* \}$  matching  $\text{nameIR}_f ( \text{id}_{\text{arg}}^{?*} )$  using parameter getter `$get_parameterListIR`

The result of this algorithm is a matched overload item with the default and optional parameter names, or an empty result if no match is found.

```
callResolution<V>
: callableId : V # nameIR* # nameIR*
;
```

The algorithm takes as input the key for overload resolution, which is the call target name and the argument names (if specified).

```
callTargetKey
: nameIR `( id?* )
;
```

Based on whether the arguments are positional or named, the key is refined to either:

```
namedCallTargetKey
: nameIR `( id* )
;

unnamedCallTargetKey
: nameIR `( nat )
;
```

For each item in the overloaded set, the key is compared to determine if it is a match:

```

callTargetMatch
: MATCH id* id*
| NOMATCH
;

```

The algorithm is as follows:

Finding the item in  $\{ ( \text{calleableId} : V )^* \}$  matching  $\text{nameIR}_f ( \text{id}_{\text{arg}}^{?*} )$  using parameter getter  $\$get\_parameterListIR$

1. If the length of  $\text{id}_{\text{arg}}^{?*}$  is greater than 0:
  - a. Check that  $\text{id}_{\text{arg}}^?$  is defined, for all  $\text{id}_{\text{arg}}^?$  in  $\text{id}_{\text{arg}}^{?*}$ .
  - b. Let  $\text{id}_{\text{arg\_inner}}^*$  be the list of  $\text{id}_{\text{arg\_inner}}$ , obtained by repeating:
    - Let  $\text{id}_{\text{arg\_inner}}$  be  $\text{id}_{\text{arg}}^?$ .
 for each  $\text{id}_{\text{arg}}^?$  in  $\text{id}_{\text{arg}}^{?*}$
  - c. If  $\cdot$  is equal to finding all items in  $\{ ( \text{calleableId} : V )^* \}$  matching named key  $\text{nameIR}_f ( \text{id}_{\text{arg\_inner}}^* )$  using parameter getter  $\$get\_parameterListIR$ :
    - i. Return  $\cdot$ .
  - d. Let  $\text{callResolution}\langle V \rangle^*$  be finding all items in  $\{ ( \text{calleableId} : V )^* \}$  matching named key  $\text{nameIR}_f ( \text{id}_{\text{arg\_inner}}^* )$  using parameter getter  $\$get\_parameterListIR$ .
  - e. If let  $\text{calleableId}_{\text{found}} : V_{\text{found}} \# \text{id}_{\text{default}}^* \# \text{id}_{\text{optional}}^*$  be  $\text{callResolution}\langle V \rangle^*$ :
    - i. Return  $\text{calleableId}_{\text{found}} : V_{\text{found}} \# \text{id}_{\text{default}}^* \# \text{id}_{\text{optional}}^*$ .
2. If  $\text{id}_{\text{arg}}^?$  is none, for all  $\text{id}_{\text{arg}}^?$  in  $\text{id}_{\text{arg}}^{?*}$ :
  - a. If  $\cdot$  is equal to finding all items in  $\{ ( \text{calleableId} : V )^* \}$  matching unnamed key  $\text{nameIR}_f ( \text{the length of } \text{id}_{\text{arg}}^{?*} )$  using parameter getter  $\$get\_parameterListIR$ :
    - i. Return  $\cdot$ .
  - b. Let  $\text{callResolution}\langle V \rangle^*$  be finding all items in  $\{ ( \text{calleableId} : V )^* \}$  matching unnamed key  $\text{nameIR}_f ( \text{the length of } \text{id}_{\text{arg}}^{?*} )$  using parameter getter  $\$get\_parameterListIR$ .
  - c. If let  $\text{calleableId}_{\text{found}} : V_{\text{found}} \# \text{id}_{\text{omitted}}^* \# \text{id}_{\text{optional}}^*$  be  $\text{callResolution}\langle V \rangle^*$ :
    - i. Return  $\text{calleableId}_{\text{found}} : V_{\text{found}} \# \text{id}_{\text{omitted}}^* \# \text{id}_{\text{optional}}^*$ .

### 18.2.1. Positional arguments

The following algorithm is used when arguments are positional:

$\$find\_overloaded\_unnamed$ :

- Finding all items in  $\text{set}\langle \text{pair}\langle \text{calleableId}, V \rangle \rangle$  matching unnamed key  $\text{nameIR}_f ( \text{nat} )$  using parameter getter  $\$get\_parameterListIR$

Finding all items in  $\text{set}\langle \text{pair}\langle \text{calleableId}, V \rangle \rangle$  matching unnamed key  $\text{nameIR}_f ( \text{nat} )$  using parameter getter  $\$get\_parameterListIR$

1. If  $\text{set}\langle\text{pair}\langle\text{callableId}, V\rangle\rangle$  is equal to  $\{\cdot\}$ :
  - a. Return  $\cdot$ .
2. Let  $\{\text{pair}\langle\text{callableId}, V\rangle^*\}$  be  $\text{set}\langle\text{pair}\langle\text{callableId}, V\rangle\rangle$ .
3. If let  $\text{callTargetId}_h : V_h :: (\text{callTargetId}_t : V_t)^*$  be  $\text{pair}\langle\text{callableId}, V\rangle^*$ :
  - a. If **matching**  $\text{callTargetId}_h : V_h$  **against unnamed key**  $\text{nameIR}_f(\text{nat})$  **using parameter getter**  $\text{\$get\_parameterListIR}$  **is NOMATCH**:
    - i. Return **finding all items in**  $\{(\text{callTargetId}_t : V_t)^*\}$  **matching unnamed key**  $\text{nameIR}_f(\text{nat})$  **using parameter getter**  $\text{\$get\_parameterListIR}$ .
  - b. Let  $\text{callTargetMatch}$  be **matching**  $\text{callTargetId}_h : V_h$  **against unnamed key**  $\text{nameIR}_f(\text{nat})$  **using parameter getter**  $\text{\$get\_parameterListIR}$ .
  - c. If let  $\text{MATCH id}_{\text{default}}^* \text{id}_{\text{optional}}^*$  be  $\text{callTargetMatch}$ :
    - i. Let  $\text{callResolution}\langle V\rangle^*$  be **finding all items in**  $\{(\text{callTargetId}_t : V_t)^*\}$  **matching unnamed key**  $\text{nameIR}_f(\text{nat})$  **using parameter getter**  $\text{\$get\_parameterListIR}$ .
    - ii. Return  $\text{callTargetId}_h : V_h \# \text{id}_{\text{default}}^* \# \text{id}_{\text{optional}}^* :: \text{callResolution}\langle V\rangle^*$ .

### 18.2.2. Named arguments

The following algorithm is used when arguments are named:

**$\text{\$find\_overloaded\_named}$ :**

- Finding all items in  $\text{set}\langle\text{pair}\langle\text{callableId}, V\rangle\rangle$  **matching named key**  $\text{nameIR}_f(\text{id}_{\text{arg}}^*)$  **using parameter getter**  $\text{\$get\_parameterListIR}$

**Finding all items in**  $\text{set}\langle\text{pair}\langle\text{callableId}, V\rangle\rangle$  **matching named key**  $\text{nameIR}_f(\text{id}_{\text{arg}}^*)$  **using parameter getter**  $\text{\$get\_parameterListIR}$

1. If  $\text{set}\langle\text{pair}\langle\text{callableId}, V\rangle\rangle$  is equal to  $\{\cdot\}$ :
  - a. Return  $\cdot$ .
2. Let  $\{\text{pair}\langle\text{callableId}, V\rangle^*\}$  be  $\text{set}\langle\text{pair}\langle\text{callableId}, V\rangle\rangle$ .
3. If let  $\text{callTargetId}_h : V_h :: (\text{callTargetId}_t : V_t)^*$  be  $\text{pair}\langle\text{callableId}, V\rangle^*$ :
  - a. If **matching**  $\text{callTargetId}_h : V_h$  **against named key**  $\text{nameIR}_f(\text{id}_{\text{arg}}^*)$  **using parameter getter**  $\text{\$get\_parameterListIR}$  **is NOMATCH**:
    - i. Return **finding all items in**  $\{(\text{callTargetId}_t : V_t)^*\}$  **matching named key**  $\text{nameIR}_f(\text{id}_{\text{arg}}^*)$  **using parameter getter**  $\text{\$get\_parameterListIR}$ .
  - b. Let  $\text{callTargetMatch}$  be **matching**  $\text{callTargetId}_h : V_h$  **against named key**  $\text{nameIR}_f(\text{id}_{\text{arg}}^*)$  **using parameter getter**  $\text{\$get\_parameterListIR}$ .
  - c. If let  $\text{MATCH id}_{\text{default}}^* \text{id}_{\text{optional}}^*$  be  $\text{callTargetMatch}$ :
    - i. Let  $\text{callResolution}\langle V\rangle^*$  be **finding all items in**  $\{(\text{callTargetId}_t : V_t)^*\}$  **matching named key**  $\text{nameIR}_f(\text{id}_{\text{arg}}^*)$  **using parameter getter**  $\text{\$get\_parameterListIR}$ .
    - ii. Return  $\text{callTargetId}_h : V_h \# \text{id}_{\text{default}}^* \# \text{id}_{\text{optional}}^* :: \text{callResolution}\langle V\rangle^*$ .

## 18.3. Callee resolution

Given a call target, type arguments, and arguments, the callee should be resolved. This is done both during type checking and runtime evaluation.

### 18.3.1. Resolving constructors

When type checking, constructors are resolved by:

#### ConstructorType\_ok:

- Finding type of constructor call `constructorTargetIR ( argumentIR* )`, under cursor `cursor` and context `typingContext`:
- Result in `constructorTypeIR` with fresh type variables `typedId*`, defaults `id*` and optionals `id*`.

Finding type of constructor call `prefixedNameIR < typeArgumentIR* > ( argumentIR* )`, under cursor `p` and context `TC`:

1. If `·` is equal to the type definition of `prefixedNameIR` from the `p` layer of `TC`:
  - a. Let `callableId : constructorTypeDefIR # iddefault* # idoptional*` be ! the overloaded constructor definition of `prefixedNameIR ( argumentIR* )` in `TC`.
  - b. Let `( constructorTypeIR, typedIdimpl* )` be `constructorTypeDefIR` specialized by `typeArgumentIR*`.
  - c. Let `bound` be bound type variables from the `p` layer of `TC`.
  - d. Let `B` be the union of the sets `bound` and `{ typedIdimpl* }`.
  - e. Check that `constructorTypeIR` is a well-formed constructor type, with bound type variables `B`.
  - f. Result in `constructorTypeIR` with fresh type variables `typedIdimpl*`, defaults `iddefault*` and optionals `idoptional*`.
2. Let `typeDefIR?` be the type definition of `prefixedNameIR` from the `p` layer of `TC`.
3. If let `typeDefIR'` be `typeDefIR?`:
  - a. Check that `typeDefIR'` does not have type `typedTypeIR`.
  - b. Let `callableId : constructorTypeDefIR # iddefault* # idoptional*` be ! the overloaded constructor definition of `prefixedNameIR ( argumentIR* )` in `TC`.
  - c. Let `( constructorTypeIR, typedIdimpl* )` be `constructorTypeDefIR` specialized by `typeArgumentIR*`.
  - d. Let `bound` be bound type variables from the `p` layer of `TC`.
  - e. Let `B` be the union of the sets `bound` and `{ typedIdimpl* }`.
  - f. Check that `constructorTypeIR` is a well-formed constructor type, with bound type variables `B`.
  - g. Result in `constructorTypeIR` with fresh type variables `typedIdimpl*`, defaults `iddefault*` and optionals `idoptional*`.
4. If `typeArgumentIR*` is equal to `:`:
  - a. Let `typeDefIR'` be ! the type definition of `prefixedNameIR` from the `p` layer of `TC`.
  - b. Check that `typeDefIR'` has type `typedTypeIR`.
  - c. Let `TYPDEF nameIRalias typeIRalias` be `typeDefIR'`.
  - d. Let `( nameIR, typeArgumentIR* )` be type alias in `typeIRalias` resolved to aliased name and type

arguments.

- e. Let  $\text{callableId} : \text{constructorTypeDefIR} \# \text{id}_{\text{default}}^* \# \text{id}_{\text{optional}}^*$  be ! the overloaded constructor definition of  $\text{nameIR} ( \text{argumentIR}^* )$  in TC.
- f. Let  $( \text{constructorTypeIR}, \text{typeId}_{\text{impl}}^* )$  be  $\text{constructorTypeDefIR}$  specialized by  $\text{typeArgumentIR}^*$ .
- g. Let  $\text{bound}$  be bound type variables from the  $p$  layer of TC.
- h. Let  $B$  be the union of the sets  $\text{bound}$  and  $\{ \text{typeId}_{\text{impl}}^* \}$ .
- i. Check that  $\text{constructorTypeIR}$  is a well-formed constructor type, with bound type variables  $B$ .
- j. Result in  $\text{constructorTypeIR}$  with fresh type variables  $\text{typeId}_{\text{impl}}^*$ , defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$ .

During compile-time evaluation, constructors are resolved by:

#### Constructor\_inst:

- Finding constructor for  $\text{prefixedNameIR} < \text{typeArgumentListIR} > ( \text{argumentListIR} )$  under cursor  $\text{cursor}$ , and context  $\text{instContext}$ :
- Result in constructor  $\text{constructorDef} < \text{typeArgumentListIR} >$  with defaults  $\text{id}^*$  and optionals  $\text{id}^*$ .

Finding constructor for  $\text{prefixedNameIR} < \text{typeArgumentIR}^* > ( \text{argumentIR}^* )$  under cursor  $p$ , and context  $IC$ :

1. If  $\cdot$  is equal to the type definition of  $\text{prefixedNameIR}$  from the  $p$  layer of  $IC$ :
  - a. Let  $\_ : \text{constructorDef} \# \text{id}_{\text{default}}^* \# \text{id}_{\text{optional}}^*$  be ! the overloaded constructor definition of  $\text{prefixedNameIR} ( \text{argumentIR}^* )$  in  $IC$ .
  - b. Result in constructor  $\text{constructorDef} < \text{typeArgumentIR}^* >$  with defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$ .
2. Let  $\text{typeDefIR}^?$  be the type definition of  $\text{prefixedNameIR}$  from the  $p$  layer of  $IC$ .
3. If let  $\text{typeDefIR}'$  be  $\text{typeDefIR}^?$ :
  - a. Check that  $\text{typeDefIR}'$  does not have type  $\text{typedefTypeIR}$ .
  - b. Let  $\_ : \text{constructorDef} \# \text{id}_{\text{default}}^* \# \text{id}_{\text{optional}}^*$  be ! the overloaded constructor definition of  $\text{prefixedNameIR} ( \text{argumentIR}^* )$  in  $IC$ .
  - c. Result in constructor  $\text{constructorDef} < \text{typeArgumentIR}^* >$  with defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$ .
4. If  $\text{typeArgumentIR}^*$  is equal to  $\cdot$ :
  - a. Let  $\text{typeDefIR}'$  be ! the type definition of  $\text{prefixedNameIR}$  from the  $p$  layer of  $IC$ .
  - b. Check that  $\text{typeDefIR}'$  has type  $\text{typedefTypeIR}$ .
  - c. Let  $\text{TYPDEF nameIR}_{\text{alias}} \text{typeIR}_{\text{alias}}$  be  $\text{typeDefIR}'$ .
  - d. Let  $( \text{nameIR}, \text{typeArgumentIR}^* )$  be type alias in  $\text{typeIR}_{\text{alias}}$  resolved to aliased name and type arguments.
  - e. Let  $\_ : \text{constructorDef} \# \text{id}_{\text{default}}^* \# \text{id}_{\text{optional}}^*$  be ! the overloaded constructor definition of  $\text{nameIR} ( \text{argumentIR}^* )$  in  $IC$ .
  - f. Result in constructor  $\text{constructorDef} < \text{typeArgumentIR}^* >$  with defaults  $\text{id}_{\text{default}}^*$  and optionals  $\text{id}_{\text{optional}}^*$ .

## 18.3.2. Resolving callables

When type checking, callables are resolved by:

### CallableType\_ok:

- Finding type of callable call `callableTargetIR < typeArgumentListIR > ( argumentIR* )`, under cursor `cursor` and context `typingContext`:
- Result in callable type `callableTypeIR` with fresh type variables `typeId*`, defaults `id*` and optionals `id*`.

At runtime, callables are resolved to callees by:

### Callee\_eval:

- Finding callee `callableTargetIR ( argumentListIR )`, under cursor `cursor`, context `evalContext`, and state `arch`:
- Result in context `evalContext`, state `arch`, and callee `calleeResult`.

While resolving callees, `exit` statements may be encountered. Thus, the result of callee resolution is:

```
calleeResult
: continueResult<callee>
| abortResult
;
```

The following subsections describe the two phases, for each kind of callable.

### 18.3.2.1. Actions

During type checking, actions are resolved by:

```
actionTypeIR
: annotationList ACTION nameIR `( parameterIR* )
;
```

Finding type of callable call `prefixedNameIR < · > ( argumentIR* )`, under cursor `p` and context `TC`:

1. Let `callableId : callableTypeDefIR # iddefault* # idoptional*` be ! the overloaded callable definition of `prefixedNameIR( argumentIR* )` from the `p` layer of `TC`.
2. Check that `callableTypeDefIR` has type `actionTypeIR`.
3. Let `actionTypeIR` be `callableTypeDefIR`.
4. Let `bound` be bound type variables from the `p` layer of `TC`.
5. Check that `actionTypeIR` is a well-formed callable type, with bound type variables `bound`.
6. Result in callable type `actionTypeIR` with fresh type variables `·`, defaults `iddefault*` and optionals `idoptional*`.

During runtime evaluation, actions are resolved by:



```

actionCallee
: ACTION cursor . nameIR `( parameterListIR # id* ) blockStatementIR
;

```

Finding callee referenceExpressionIR ( argumentListIR ), under cursor p, context EC, and state ARCH:

1. Let  $\_ : (cursor, callableDef) \# id_{default}^* \# \_^*$  be ! the overloaded callable definition of referenceExpressionIR( argumentListIR ) in the p layer of EC.
2. Check that (cursor, callableDef) has type (cursor, actionDef).
3. Let (  $p_{ref}$ , actionDef ) be (cursor, callableDef).
4. Let ACTION nameIR ( parameterListIR ) blockStatementIR be actionDef.
5. Let actionCallee be ACTION  $p_{ref}$  . nameIR ( parameterListIR #  $id_{default}^*$  ) blockStatementIR.
6. Result in context EC, state ARCH, and callee actionCallee.

### 18.3.2.2. Functions

During type checking, functions are resolved by:

```

functionTypeIR
: definedFunctionTypeIR
| externFunctionTypeIR
;

```

Finding type of callable call prefixedNameIR < typeArgumentIR\* > ( argumentIR\* ), under cursor p and context TC:

1. Let callableId : callableTypeDefIR #  $id_{default}^*$  #  $id_{optional}^*$  be ! the overloaded callable definition of prefixedNameIR( argumentIR\* ) from the p layer of TC.
2. Check that callableTypeDefIR has type functionTypeDefIR.
3. Let functionTypeDefIR be callableTypeDefIR.
4. Let (callableTypeIR, typeId\*) be functionTypeDefIR specialized by typeArgumentIR\*.
5. Check that (callableTypeIR, typeId\*) has type (functionTypeIR, typeId\*).
6. Let ( functionTypeIR, typeId<sub>impl</sub>\* ) be (callableTypeIR, typeId\*).
7. Let bound' be bound type variables from the p layer of TC.
8. Let bound be the union of the sets bound' and { typeId<sub>impl</sub>\* }.
9. Check that functionTypeIR is a well-formed callable type, with bound type variables bound.
10. Result in callable type functionTypeIR with fresh type variables typeId<sub>impl</sub>\*, defaults  $id_{default}^*$  and optionals  $id_{optional}^*$ .

During runtime evaluation, functions are resolved by:

```

functionCallee
: definedFunctionCallee
| externFunctionCallee

```

;

For extern functions,

**Finding callee** `referenceExpressionIR ( argumentListIR ), under cursor p, context EC, and state ARCH:`

1. Let `_ : ( _ callableDef ) # iddefault * # idoptional *` be ! the overloaded callable definition of `referenceExpressionIR( argumentListIR )` in the `p` layer of `EC`.
2. Check that `callableDef` has type `externFunctionDef`.
3. Let `externFunctionDef` be `callableDef`.
4. Let `EXTERN_FUNCTION nameIR < typeParameterListIR > ( parameterListIR )` be `externFunctionDef`.
5. Let `externFunctionCallee` be `EXTERN_FUNCTION nameIR < typeParameterListIR > ( parameterListIR # iddefault * # idoptional * )`.
6. Result in context `EC`, state `ARCH`, and callee `externFunctionCallee`.

For user-defined functions,

**Finding callee** `referenceExpressionIR ( argumentListIR ), under cursor p, context EC, and state ARCH:`

1. Let `_ : ( _ callableDef ) # iddefault * # _ *` be ! the overloaded callable definition of `referenceExpressionIR( argumentListIR )` in the `p` layer of `EC`.
2. Check that `callableDef` has type `definedFunctionDef`.
3. Let `definedFunctionDef` be `callableDef`.
4. Let `FUNCTION nameIR < typeParameterListIR > ( parameterListIR ) blockStatementIR` be `definedFunctionDef`.
5. Let `definedFunctionCallee` be `FUNCTION nameIR < typeParameterListIR > ( parameterListIR # iddefault * ) blockStatementIR`.
6. Result in context `EC`, state `ARCH`, and callee `definedFunctionCallee`.

### 18.3.2.3. Built-in methods

During type checking, built-in methods are resolved by:

```
builtinMethodTypeIR
: BUILTIN_METHOD nameIR `( parameterIR* ) : typeIR
;
```

**Finding type of callable call** `typedExpressionIRbase . nameIR < · > ( argumentIR* ), under cursor p and context TC:`

1. If `argumentIR*` is equal to `:`:
  - a. If `nameIR` is in [ "minSizeInBits", "minSizeInBytes", "maxSizeInBits", "maxSizeInBytes" ]:
    - i. Let `typeIRbase` be the type of `typedExpressionIRbase`.
    - ii. Let `typeIRbase_unroll` be `typeIRbase` with `typeddefs` unrolled.
    - iii. Check that `typeIRbase_unroll` does not have type `objectTypeIR`.

- iv. Check that `typeIRbase_unroll` does not have type `synthesizedTypeIR`.
  - v. Let `methodTypeIR` be `BUILTIN_METHOD nameIR ( · ) : INT`.
  - vi. Result in callable type `methodTypeIR` with fresh type variables `·`, defaults `·` and optionals `·`.
- b. Else if `nameIR` is in "isValid":
- i. Let `typeIRbase` be the type of `typedExpressionIRbase`.
  - ii. Let `typeIR` be `typeIRbase` with `typedefs` unrolled.
  - iii. If let `HEADER _ < _ * > { _ * }` be `typeIR`:
    - A. Let `methodTypeIR` be `BUILTIN_METHOD nameIR ( · ) : BOOL`.
    - B. Result in callable type `methodTypeIR` with fresh type variables `·`, defaults `·` and optionals `·`.
  - iv. Else if let `HEADER_UNION _ < _ * > { _ * }` be `typeIR`:
    - A. Let `methodTypeIR` be `BUILTIN_METHOD nameIR ( · ) : BOOL`.
    - B. Result in callable type `methodTypeIR` with fresh type variables `·`, defaults `·` and optionals `·`.
- c. Else if `nameIR` is in [ "setValid", "setInvalid" ]:
- i. Let `typeIRbase` be the type of `typedExpressionIRbase`.
  - ii. Let `typeIR` be `typeIRbase` with `typedefs` unrolled.
  - iii. Check that `typeIR` has type `headerTypeIR`.
  - iv. Let `HEADER _ < _ * > { _ * }` be `typeIR`.
  - v. Let `methodTypeIR` be `BUILTIN_METHOD nameIR ( · ) : VOID`.
  - vi. Result in callable type `methodTypeIR` with fresh type variables `·`, defaults `·` and optionals `·`.
2. If `argumentIR*` is a list of length 1:
- a. Check that `nameIR` is in [ "push\_front", "pop\_front" ].
  - b. Let `typeIRbase` be the type of `typedExpressionIRbase`.
  - c. Let `typeIR` be `typeIRbase` with `typedefs` unrolled.
  - d. Check that `typeIR` has type `headerStackTypeIR`.
  - e. Let `typeIR' [ _ ]` be `typeIR`.
  - f. Let `parameterIR` be ``EMPTY `EMPTY INT "count" ·`.
  - g. Let `methodTypeIR` be `BUILTIN_METHOD nameIR ( parameterIR ) : INT`.
  - h. Result in callable type `methodTypeIR` with fresh type variables `·`, defaults `·` and optionals `·`.

During runtime evaluation, built-in methods are resolved by:

```
builtinMethodCallee
: BUILTIN_METHOD storageReference . nameIR `< typeArgumentListIR >
  `( parameterListIR )
;
```

Finding callee `typedExpressionIR . nameIR ( argumentListIR )`, under cursor `p`, context `EC`, and state `ARCH`:

- 1. Let `typedLvalueIR?` be the l-value form of `typedExpressionIR`.

2. If let `typedLvalueIR` be `typedLvalueIR`<sup>?</sup>:
  - a. Let context `EC1`, state `ARCH1`, and result `storageReferenceResult` be
    - the result of evaluating `typedLvalueIR`<sup>'</sup>, under cursor `p`, context `EC`, and state `ARCH`.
  - b. Check that `storageReferenceResult` has type `abortResult`.
  - c. Let `abortResult` be `storageReferenceResult`.
  - d. Result in context `EC1`, state `ARCH1`, and callee `abortResult`.
3. If `nameIR` is equal to `"push_front"`:
  - a. Check that `argumentListIR` is a list of length 1.
  - b. Let `typedLvalueIR` be ! the l-value form of `typedExpressionIR`.
  - c. Let context `EC1`, state `ARCH1`, and result `storageReferenceResult` be
    - the result of evaluating `typedLvalueIR`<sup>'</sup>, under cursor `p`, context `EC`, and state `ARCH`.
  - d. Check that `storageReferenceResult` has type `continueResult<storageReference?>`.
  - e. Let `storageReference`<sup>?</sup> be `storageReferenceResult`.
  - f. Check that `storageReference`<sup>?</sup> is defined.
  - g. Let `storageReference`<sup>'</sup> be `storageReference`<sup>?</sup>.
  - h. Let `parameterIR` be ``EMPTY `EMPTY INT "count" `.`
    - i. Let `builtinMethodCallee` be `BUILTIN_METHOD storageReference`<sup>'</sup>. `"push_front" < · > ( parameterIR )`.
    - j. Result in context `EC1`, state `ARCH1`, and callee `builtinMethodCallee`.
4. Else if `nameIR` is equal to `"pop_front"`:
  - a. Check that `argumentListIR` is a list of length 1.
  - b. Let `typedLvalueIR` be ! the l-value form of `typedExpressionIR`.
  - c. Let context `EC1`, state `ARCH1`, and result `storageReferenceResult` be
    - the result of evaluating `typedLvalueIR`<sup>'</sup>, under cursor `p`, context `EC`, and state `ARCH`.
  - d. Check that `storageReferenceResult` has type `continueResult<storageReference?>`.
  - e. Let `storageReference`<sup>?</sup> be `storageReferenceResult`.
  - f. Check that `storageReference`<sup>?</sup> is defined.
  - g. Let `storageReference`<sup>'</sup> be `storageReference`<sup>?</sup>.
  - h. Let `parameterIR` be ``EMPTY `EMPTY INT "count" `.`
    - i. Let `builtinMethodCallee` be `BUILTIN_METHOD storageReference`<sup>'</sup>. `"pop_front" < · > ( parameterIR )`.
    - j. Result in context `EC1`, state `ARCH1`, and callee `builtinMethodCallee`.
5. Else if `nameIR` is equal to `"isValid"`:
  - a. Check that `argumentListIR` is equal to `·`.
  - b. Let `typedLvalueIR` be ! the l-value form of `typedExpressionIR`.
  - c. Let context `EC1`, state `ARCH1`, and result `storageReferenceResult` be
    - the result of evaluating `typedLvalueIR`<sup>'</sup>, under cursor `p`, context `EC`, and state `ARCH`.
  - d. Check that `storageReferenceResult` has type `continueResult<storageReference?>`.
  - e. Let `storageReference`<sup>?</sup> be `storageReferenceResult`.
  - f. Check that `storageReference`<sup>?</sup> is defined.

- g. Let `storageReference'` be `storageReference?`.
  - h. Let `builtinMethodCallee` be `BUILTIN_METHOD storageReference' . "isValid" < · > ( · )`.
  - i. Result in context `EC1`, state `ARCH1`, and callee `builtinMethodCallee`.
6. Else if `nameIR` is equal to `"setValid"`:
- a. Check that `argumentListIR` is equal to `·`.
  - b. Let `typedLvalueIR` be **! the l-value form of** `typedExpressionIR`.
  - c. Let context `EC1`, state `ARCH1`, and result `storageReferenceResult` be
    - the result of **evaluating** `typedLvalueIR`, **under cursor** `p`, **context** `EC`, and **state** `ARCH`.
  - d. Check that `storageReferenceResult` has type `continueResult<storageReference?>`.
  - e. Let `storageReference?` be `storageReferenceResult`.
  - f. Check that `storageReference?` is defined.
  - g. Let `storageReference'` be `storageReference?`.
  - h. Let `builtinMethodCallee` be `BUILTIN_METHOD storageReference' . "setValid" < · > ( · )`.
  - i. Result in context `EC1`, state `ARCH1`, and callee `builtinMethodCallee`.
7. Else if `nameIR` is equal to `"setInvalid"`:
- a. Check that `argumentListIR` is equal to `·`.
  - b. Let `typedLvalueIR` be **! the l-value form of** `typedExpressionIR`.
  - c. Let context `EC1`, state `ARCH1`, and result `storageReferenceResult` be
    - the result of **evaluating** `typedLvalueIR`, **under cursor** `p`, **context** `EC`, and **state** `ARCH`.
  - d. Check that `storageReferenceResult` has type `continueResult<storageReference?>`.
  - e. Let `storageReference?` be `storageReferenceResult`.
  - f. Check that `storageReference?` is defined.
  - g. Let `storageReference'` be `storageReference?`.
  - h. Let `builtinMethodCallee` be `BUILTIN_METHOD storageReference' . "setInvalid" < · > ( · )`.
  - i. Result in context `EC1`, state `ARCH1`, and callee `builtinMethodCallee`.

#### 18.3.2.4. Extern methods

During type checking, extern methods are resolved by:

```
externMethodTypeIR
: EXTERN_METHOD nameIR `( parameterIR* ) : typeIR
| EXTERN_METHOD ABSTRACT nameIR `( parameterIR* ) : typeIR
;
```

**Finding type of callable call** `typedExpressionIRbase . nameIR < typeArgumentIR* > ( argumentIR* )`, **under cursor** `p` and **context** `TC`:

1. Let `typeIRbase` be **the type of** `typedExpressionIRbase`.
2. Let `typeIR` be `typeIRbase` **with typedefs unrolled**.
3. Check that `typeIR` has type `externObjectTypeIR`.

4. Let `EXTERN typed < _ > { ( callableIdextern : externMethodTypeDefIRextern )* }` be `typeIR`.
5. Let `callTargetKey` be the call target key for `nameIR ( argumentIR* )`.
6. Let `_ : externMethodTypeDefIR # iddefault* # idoptional*` be ! finding the item in `{ ( callableIdextern : externMethodTypeDefIRextern )* }` matching `callTargetKey` using parameter getter `$parameterListIR_of_externMethodTypeDefIR`.
7. Let `( callableTypeIR, typed* )` be `externMethodTypeDefIR` specialized by `typeArgumentIR*`.
8. Check that `( callableTypeIR, typed* )` has type `( externMethodTypeIR, typed* )`.
9. Let `( externMethodTypeIR, typedimpl* )` be `( callableTypeIR, typed* )`.
10. Let `bound'` be bound type variables from the `p` layer of `TC`.
11. Let `bound` be the union of the sets `bound'` and `{ typedimpl* }`.
12. Check that `externMethodTypeIR` is a well-formed callable type, with bound type variables `bound`.
13. Result in callable type `externMethodTypeIR` with fresh type variables `typedimpl*`, defaults `iddefault*` and optionals `idoptional*`.

During runtime evaluation, extern methods are resolved by:

```
externMethodCallee
: EXTERN_METHOD objectId . nameIR `< typeParameterListIR >
  `( parameterListIR # id* # id* ) `{ theta ; frame ; blockStatementIR? }
;
```

**Finding callee** `typedExpressionIR . nameIR ( argumentListIR )`, under cursor `p`, context `EC`, and state `ARCH`:

1. Let `typedLvalueIR'` be ! the l-value form of `typedExpressionIR`.
2. Let context `EC1`, state `ARCH1`, and result `storageReferenceResult` be
  - the result of evaluating `typedLvalueIR'`, under cursor `p`, context `EC`, and state `ARCH`.
3. If let `abortResult` be `storageReferenceResult`:
  - a. Result in context `EC1`, state `ARCH1`, and callee `abortResult`.
4. Else:
  - a. Let `storageReference?` be `storageReferenceResult`.
  - b. Check that `storageReference?` is defined.
  - c. Let `storageReference'` be `storageReference?`.
  - d. Let value `value` be
    - the result of reading from `storageReference'`, under cursor `p`, context `EC1`, and state `ARCH1`.
  - e. Check that `value` has type `objectReferenceValue`.
  - f. Let `REF objectId` be `value`.
  - g. Let `object'` be ! the object `objectId` in `ARCH1`.
  - h. Check that `object'` has type `externObject`.
    - i. Let `EXTERN _ < theta > { _ frame externMethodDefEnv }` be `object'`.
    - j. Let `callTargetKey` be the call target key for `nameIR ( argumentListIR )`.
    - k. Let `_ : externMethodDef # iddefault* # idoptional*` be ! finding the item in `externMethodDefEnv` matching `callTargetKey` using parameter getter `$parameterListIR_of_externMethodDef`.

- l. Check that `externMethodDef` matches pattern `EXTERN_METHOD % < % > ( % ) %`.
- m. Let `EXTERN_METHOD nameIR' < typeParameterListIR > ( parameterListIR ) blockStatementIR'` be `externMethodDef`.
- n. Check that `nameIR'` is equal to `nameIR`.
- o. Let `externMethodCallee` be `EXTERN_METHOD objectId . nameIR' < typeParameterListIR > ( parameterListIR # iddefault* # idoptional* ) { theta ; frame ; blockStatementIR' }`.
- p. Result in context `EC1`, state `ARCH1`, and callee `externMethodCallee`.

### 18.3.2.5. Parser apply methods

During type checking, parser apply methods are resolved by:

```
parserApplyMethodTypeIR
: PARSE_APPLY `( parameterIR* )
;
```

**Finding type of callable call** `typedExpressionIRbase . "apply" < · > ( argumentIR* )`, under cursor `p` and context `TC`:

1. Let `typeIRbase` be the type of `typedExpressionIRbase`.
2. Let `typeIR` be `typeIRbase` with typedefs unrolled.
3. Check that `typeIR` has type `parserObjectTypeIR`.
4. Let `PARSE _ < _ * > ( parameterIR* )` be `typeIR`.
5. Let `parserApplyMethodTypeIR` be `PARSE_APPLY ( parameterIR* )`.
6. Let `idparam*` be the list of `idparam`, obtained by repeating:
  - Let `idparam` be the name of `parameterIR`.
 for each `parameterIR` in `parameterIR*`
7. Let `callableId` be `"apply" ( idparam* )`.
8. Let `callTargetKey` be the call target key for `"apply" ( argumentIR* )`.
9. Let `_ : _ # iddefault* # idoptional*` be **! finding the item in** `{ callableId : parserApplyMethodTypeIR }` **matching** `callTargetKey` **using parameter getter** `$parameterListIR_of_parserApplyMethodTypeIR`.
10. Result in callable type `parserApplyMethodTypeIR` with fresh type variables `·`, defaults `iddefault*` and optionals `idoptional*`.

During runtime evaluation, parser apply methods are resolved by:

```
parserApplyMethodCallee
: PARSE objectId . APPLY `( parameterListIR # id* )
  `{ theta ; frame ; parserLocalDeclarationListIR ; stateEnv }
;
```

**Finding callee** `typedExpressionIR . "apply" ( argumentListIR )`, under cursor `p`, context `EC`, and state `ARCH`:

1. Let `typedLvalueIR` be ! the l-value form of `typedExpressionIR`.
2. Let context `EC1`, state `ARCH1`, and result `storageReferenceResult` be
  - the result of evaluating `typedLvalueIR`, under cursor `p`, context `EC`, and state `ARCH`.
3. If let `abortResult` be `storageReferenceResult`:
  - a. Result in context `EC1`, state `ARCH1`, and callee `abortResult`.
4. Else:
  - a. Let `storageReference`<sup>?</sup> be `storageReferenceResult`.
  - b. Check that `storageReference`<sup>?</sup> is defined.
  - c. Let `storageReference'` be `storageReference`<sup>?</sup>.
  - d. Let value `value` be
    - the result of reading from `storageReference'`, under cursor `p`, context `EC1`, and state `ARCH1`.
  - e. Check that `value` has type `objectReferenceValue`.
  - f. Let `REF objectId` be `value`.
  - g. Let `object'` be ! the object `objectId` in `ARCH1`.
  - h. Check that `object'` has type `parserObject`.
    - i. Let `PARSER < theta > ( parameterListIR ) { frame parserLocalDeclarationListIR stateEnv }` be `object'`.
    - j. Let `callableId` be the callable identifier for "apply" ( `parameterListIR` ).
    - k. Let `parserApplyMethodDef` be `PARSER_APPLY ( parameterListIR ) { parserLocalDeclarationListIR ; stateEnv }`.
    - l. Let `callTargetKey` be the call target key for "apply" ( `argumentListIR` ).
  - m. Let `_ : _ # iddefault* # _*` be ! finding the item in { `callableId` : `parserApplyMethodDef` } matching `callTargetKey` using parameter getter `$parameterListIR_of_parserApplyMethodDef`.
  - n. Let `parserApplyMethodCallee` be `PARSER objectId . APPLY ( parameterListIR # iddefault* ) { theta ; frame ; parserLocalDeclarationListIR ; stateEnv }`.
  - o. Result in context `EC1`, state `ARCH1`, and callee `parserApplyMethodCallee`.

### 18.3.2.6. Control apply methods

During type checking, control apply methods are resolved by:

```
controlApplyMethodTypeIR
: CONTROL_APPLY `( parameterIR* )
;
```

Finding type of callable call `typedExpressionIRbase . "apply" < · > ( argumentIR* )`, under cursor `p` and context `TC`:

1. Let `typeIRbase` be the type of `typedExpressionIRbase`.
2. Let `typeIR` be `typeIRbase` with typedefs unrolled.
3. Check that `typeIR` has type `controlObjectTypeIR`.
4. Let `CONTROL _ < _* > ( parameterIR* )` be `typeIR`.
5. Let `controlApplyMethodTypeIR` be `CONTROL_APPLY ( parameterIR* )`.



6. Let  $id_{param}^*$  be the list of  $id_{param}$ , obtained by repeating:
  - Let  $id_{param}$  be the name of  $parameterIR$ .
 for each  $parameterIR$  in  $parameterIR^*$
7. Let  $callableId$  be "apply" (  $id_{param}^*$  ).
8. Let  $callTargetKey$  be the call target key for "apply" (  $argumentIR^*$  ).
9. Let  $\_ : \_ \# id_{default}^* \# id_{optional}^*$  be ! finding the item in {  $callableId : controlApplyMethodTypeIR$  } matching  $callTargetKey$  using parameter getter  $\$parameterListIR\_of\_controlApplyMethodTypeIR$ .
10. Result in callable type  $controlApplyMethodTypeIR$  with fresh type variables  $\_$ , defaults  $id_{default}^*$  and optionals  $id_{optional}^*$ .

During runtime evaluation, control apply methods are resolved by:

```
controlApplyMethodCallee
: CONTROL objectId . APPLY `( parameterListIR # id* )
  `{ theta ; frame ; controlLocalDeclarationListIR ; actionDefEnv ; controlBodyIR }
;
```

Finding callee  $typedExpressionIR$  . "apply" (  $argumentListIR$  ), under cursor  $p$ , context  $EC$ , and state  $ARCH$ :

1. Let  $typedLvalueIR'$  be ! the l-value form of  $typedExpressionIR$ .
2. Let context  $EC_1$ , state  $ARCH_1$ , and result  $storageReferenceResult$  be
  - the result of evaluating  $typedLvalueIR'$ , under cursor  $p$ , context  $EC$ , and state  $ARCH$ .
3. If let  $abortResult$  be  $storageReferenceResult$ :
  - a. Result in context  $EC_1$ , state  $ARCH_1$ , and callee  $abortResult$ .
4. Else:
  - a. Let  $storageReference^?$  be  $storageReferenceResult$ .
  - b. Check that  $storageReference^?$  is defined.
  - c. Let  $storageReference'$  be  $storageReference^?$ .
  - d. Let value  $value$  be
    - the result of reading from  $storageReference'$ , under cursor  $p$ , context  $EC_1$ , and state  $ARCH_1$ .
  - e. Check that  $value$  has type  $objectReferenceValue$ .
  - f. Let  $REF\ objectId$  be  $value$ .
  - g. Let  $object'$  be ! the object  $objectId$  in  $ARCH_1$ .
  - h. Check that  $object'$  has type  $controlObject$ .
    - i. Let  $CONTROL < theta > ( parameterListIR ) \{ frame\ controlLocalDeclarationListIR\ actionDefEnv\ controlBodyIR \}$  be  $object'$ .
    - j. Let  $callableId$  be the callable identifier for "apply" (  $parameterListIR$  ).
    - k. Let  $controlApplyMethodDef$  be  $CONTROL\_APPLY ( parameterListIR ) \{ controlLocalDeclarationListIR ; actionDefEnv ; controlBodyIR \}$ .
    - l. Let  $callTargetKey$  be the call target key for "apply" (  $argumentListIR$  ).
    - m. Let  $\_ : \_ \# id_{default}^* \# \_$  be ! finding the item in {  $callableId : controlApplyMethodDef$  } matching

callTargetKey using parameter getter \$parameterListIR\_of\_controlApplyMethodDef.

- n. Let controlApplyMethodCallee be CONTROL objectId . APPLY ( parameterListIR # id<sub>default</sub><sup>\*</sup> ) { theta ; frame ; controlLocalDeclarationListIR ; actionDefEnv ; controlBodyIR }.
- o. Result in context EC<sub>1</sub>, state ARCH<sub>1</sub>, and callee controlApplyMethodCallee.

### 18.3.2.7. Table apply methods

During type checking, table apply methods are resolved by:

```
tableApplyMethodTypeIR
: TABLE_APPLY : tableMetadataStructTypeIR
;
```

Finding type of callable call typedExpressionIR<sub>base</sub> . "apply" < · > ( · ), under cursor p and context TC:

1. Let typeIR<sub>base</sub> be the type of typedExpressionIR<sub>base</sub>.
2. Let typeIR be typeIR<sub>base</sub> with typeddefs unrolled.
3. Check that typeIR has type tableObjectTypeIR.
4. Let TABLE \_ { tableMetadataStructTypeIR } be typeIR.
5. Let tableApplyMethodTypeIR be TABLE\_APPLY : tableMetadataStructTypeIR.
6. Result in callable type tableApplyMethodTypeIR with fresh type variables ·, defaults · and optionals ·.

During runtime evaluation, table apply methods are resolved by:

```
tableApplyMethodCallee
: TABLE objectId . APPLY { frame ; tableObjectProperty }
;
```

Finding callee typedExpressionIR . "apply" ( · ), under cursor p, context EC, and state ARCH:

1. Let typedLvalueIR' be ! the l-value form of typedExpressionIR.
2. Let context EC<sub>1</sub>, state ARCH<sub>1</sub>, and result storageReferenceResult be
  - the result of evaluating typedLvalueIR', under cursor p, context EC, and state ARCH.
3. If let abortResult be storageReferenceResult:
  - a. Result in context EC<sub>1</sub>, state ARCH<sub>1</sub>, and callee abortResult.
4. Else:
  - a. Let storageReference<sup>?</sup> be storageReferenceResult.
  - b. Check that storageReference<sup>?</sup> is defined.
  - c. Let storageReference' be storageReference<sup>?</sup>.
  - d. Let value value be
    - the result of reading from storageReference', under cursor p, context EC<sub>1</sub>, and state ARCH<sub>1</sub>.
  - e. Check that value has type objectReferenceValue.

- f. Let `REF objectId` be `value`.
- g. Let `object'` be **! the object** `objectId` **in** `ARCH1`.
- h. Check that `object'` has type `tableObject`.
- i. Let `TABLE typeId { frame TBL }` be `object'`.
- j. Let `tableApplyMethodCallee` be `TABLE objectId . APPLY { frame ; TBL }`.
- k. Result in context `EC1`, state `ARCH1`, and callee `tableApplyMethodCallee`.

## 18.4. Call convention

## 18.5. Runtime evaluation of constructor calls

## 18.6. Runtime evaluation of callable calls

At runtime, callable callees are evaluated as follows:

**Call\_eval:**

- Calling `callee < typeArgumentListIR > ( argumentListIR )`, under cursor `cursor`, context `evalContext`, and state `arch`:
- Result in context `evalContext`, state `arch`, and call result `callResult`.

The following subsections describe the evaluation of callable calls for different types of callees.

### 18.6.1. Actions

An action call is evaluated as follows:

**Calling** `actionCallee < · > ( argumentListIR )`, under cursor `p`, context `EC0`, and state `ARCH0`:

1. Let `ACTION pshared . nameIR ( parameterIR* # iddefault* ) blockStatementIR` be `actionCallee`.
2. Let `ECcallee_0` be **copy of** `EC0` **from the** `pshared` **layer**.
3. Let **GIVEN** `parameterIRaligned* DEFAULT parameterIRdefault*` be **aligning** `parameterIR*` **with** `argumentListIR` **where defaults are** `iddefault*` **and optionals are** `·`.
4. Let state `ARCH1`, caller's context `EC1`, callee's context `ECcallee_1`, and copy-in result `copyInResult` be
  - the result of **copy-in from** `argumentListIR` **in LOCAL layer of** `ECcallee_0` **to** `parameterIRaligned*` **in** `p` **layer of** `EC0`, **under cursor** `pshared` **and state** `ARCH0`.
5. If let `exitResult` be `copyInResult`:
  - a. Result in context `EC1`, state `ARCH1`, and call result `EXIT`.
6. Else if let `storageReference?*` be `copyInResult`:
  - a. Let `ECcallee_2` be
    - the result of **copying defaults for** `parameterIRdefault*`, **under context** `LOCAL` **and context** `ECcallee_1`.
  - b. Let the updated context `ECcallee_3`, state `ARCH2` and result `actionResult` be

- the result of evaluating action body `blockStatementIR`, under context `ECcallee_2` and state `ARCH1`.
- c. If let `exitResult` be `actionResult`:
- i. Let `EC2` be
    - the result of copy-out from `parameterIRaligned*` in `p` layer of `EC1` to `storageReference*` in LOCAL layer of `ECcallee_3`, under cursor `pshared` and state `ARCH2`.
  - ii. Result in context `EC2`, state `ARCH2`, and call result `EXIT`.
- d. If `actionResult` is equal to `RETURN` ∴
- i. Let `EC2` be
    - the result of copy-out from `parameterIRaligned*` in `p` layer of `EC1` to `storageReference*` in LOCAL layer of `ECcallee_3`, under cursor `pshared` and state `ARCH2`.
  - ii. Result in context `EC2`, state `ARCH2`, and call result `RETURN` ∴.

An action body is evaluated as follows:

#### ActionBody\_eval:

- Evaluating action body `blockStatementIR`, under context `evalContext` and state `arch`:
- Result in the updated context `evalContext`, state `arch` and result `actionResult`.

The result of evaluating an action body is either an `exit` or a `return`.

`{syntax: actionResult}`

#### Evaluating action body `blockStatementIR`, under context `EC0` and state `ARCH0`:

1. Let context `EC1`, state `ARCH1`, and `statementResult` be
  - the result of runtime evaluation of `blockStatementIR`, under context `EC0`, and state `ARCH0`.
2. If let `continueEmptyResult` be `statementResult`:
  - a. Result in the updated context `EC1`, state `ARCH1` and result `RETURN` ∴.
3. Else if let `exitResult` be `statementResult`:
  - a. Result in the updated context `EC1`, state `ARCH1` and result `EXIT`.
4. If `statementResult` is equal to `RETURN` ∴:
  - a. Result in the updated context `EC1`, state `ARCH1` and result `RETURN` ∴.

## 18.6.2. Functions

## 18.6.3. Built-in methods

## 18.6.4. Extern methods

## 18.6.5. Parser apply methods

### 18.6.6. Control apply methods

### 18.6.7. Table apply methods

## 19. Operations

### 19.1. Unary operations

Unary operations are evaluated with:

`unop value`

1. If `unop` is `~`:
  - a. Return `~ value`.
2. Else if `unop` is `!`:
  - a. Return `! value`.
3. Else if `unop` is `+`:
  - a. Return `+ value`.
4. Else:
  - a. Return `- value`.

#### Negation

`! value`

1. Check that `value` has type `boolValue`.
2. Let ``B b` be `value`.
3. Return ``B ~b`.

#### Bitwise complement

`~ value`

1. Check that `value` has type `integerLiteral`.
2. Let `integerLiteral` be `value`.
3. Check that `integerLiteral` matches pattern `% W %`.
4. Let `w W i` be `integerLiteral`.
5. Let `i'` be the two's complement negation of `i`.
6. Let `int` be 2 to the power of `w`.
7. Let `i''` be `i'` if `i'` is greater than or equal to 0 otherwise `int + i'`.
8. Return `w W i''`.

## Plus

+ value

1. Check that `value` has type `integerLiteral`.
2. Let `integerLiteral` be `value`.
3. If let `D i` be `integerLiteral`:
  - a. Return `D i`.
4. Else if let `w W i` be `integerLiteral`:
  - a. Return `w W i`.
5. Else:
  - a. Let `w S i` be `integerLiteral`.
  - b. Return `w S i`.

## Minus

- value

1. Check that `value` has type `integerLiteral`.
2. Let `integerLiteral` be `value`.
3. If let `D i` be `integerLiteral`:
  - a. Return `D -i`.
4. Else if let `w W i` be `integerLiteral`:
  - a. Let `int` be 2 to the power of `w`.
  - b. Let `i'` be `int - i`.
  - c. Return `w W i'`.
5. Else:
  - a. Let `w S i` be `integerLiteral`.
  - b. Let `int` be the two's complement representation of bitstring `-i` of width `w`.
  - c. Let `i'` be the bitstring of width `w` representing the integer `int`.
  - d. Return `w S i'`.

## 19.2. Binary operations

Binary operations are evaluated with:

`valuel binop valuer`

1. If `binop` is `+`:
  - a. Return `valuel + valuer`.
2. Else if `binop` is `|+|`:

- a. Return  $value_l \mid \mid + value_r$ .
3. Else if **binop** is **-**:
  - a. Return  $value_l - value_r$ .
4. Else if **binop** is **|-|**:
  - a. Return  $value_l \mid - \mid value_r$ .
5. Else if **binop** is **\***:
  - a. Return  $value_l * value_r$ .
6. Else if **binop** is **/**:
  - a. Return  $value_l / value_r$ .
7. Else if **binop** is **%**:
  - a. Return  $value_l \% value_r$ .
8. Else if **binop** is **<<**:
  - a. Return  $value_l << value_r$ .
9. Else if **binop** is **>>**:
  - a. Return  $value_l >> value_r$ .
10. Else if **binop** is **:**
  - a. Let **bool** be  $value_l \leq value_r$ .
  - b. Return ``B bool`.
11. Else if **binop** is **>=**:
  - a. Let **bool** be  $value_l \geq value_r$ .
  - b. Return ``B bool`.
12. Else if **binop** is **<**:
  - a. Let **bool** be  $value_l < value_r$ .
  - b. Return ``B bool`.
13. Else if **binop** is **>**:
  - a. Let **bool** be  $value_l > value_r$ .
  - b. Return ``B bool`.
14. Else if **binop** is **==**:
  - a. Let **bool** be  $value_l == value_r$ .
  - b. Return ``B bool`.
15. Else if **binop** is **!=**:
  - a. Let **bool** be  $value_l != value_r$ .
  - b. Return ``B bool`.
16. Else if **binop** is **&**:
  - a. Return  $value_l \& value_r$ .
17. Else if **binop** is **^**:
  - a. Return  $value_l \wedge value_r$ .
18. Else if **binop** is **|**:

- a. Return  $value_l \mid value_r$ .
19. Else if `binop` is `++`:
- a. Return  $value_l \mid value_r$ .

## Addition

$value + value'$

1. Check that  $value$  has type `integerLiteral`.
2. Let `integerLiteral` be  $value$ .
3. If let  $D \ i_l$  be `integerLiteral`:
  - a. Check that  $value'$  has type `integerLiteral`.
  - b. Let `integerLiteral'` be  $value'$ .
  - c. Check that `integerLiteral'` matches pattern `D %`.
  - d. Let  $D \ i_r$  be `integerLiteral'`.
  - e. Return  $D \ i_l + i_r$ .
4. Else if let  $w \ W \ i_l$  be `integerLiteral`:
  - a. Check that  $value'$  has type `integerLiteral`.
  - b. Let `integerLiteral'` be  $value'$ .
  - c. Check that `integerLiteral'` matches pattern `% W %`.
  - d. Let  $w' \ W \ i_r$  be `integerLiteral'`.
  - e. Check that  $w$  is equal to  $w'$ .
  - f. Let  $i_l$  be the two's complement representation of bitstring  $i_l$  of width  $w$ .
  - g. Let  $i_r$  be the two's complement representation of bitstring  $i_r$  of width  $w$ .
  - h. Let  $i$  be the bitstring of width  $w$  representing the integer  $i_l + i_r$ .
  - i. Return  $w \ W \ i$ .
5. Else:
  - a. Let  $w \ S \ i_l$  be `integerLiteral`.
  - b. Check that  $value'$  has type `integerLiteral`.
  - c. Let `integerLiteral'` be  $value'$ .
  - d. Check that `integerLiteral'` matches pattern `% S %`.
  - e. Let  $w' \ S \ i_r$  be `integerLiteral'`.
  - f. Check that  $w$  is equal to  $w'$ .
  - g. Let  $i_l$  be the two's complement representation of bitstring  $i_l$  of width  $w$ .
  - h. Let  $i_r$  be the two's complement representation of bitstring  $i_r$  of width  $w$ .
  - i. Let  $i$  be the bitstring of width  $w$  representing the integer  $i_l + i_r$ .
  - j. Return  $w \ S \ i$ .

## Saturated addition



value | |+ value'

1. Check that value has type integerLiteral.
2. Let integerLiteral be value.
3. If let  $w \ W \ i_l$  be integerLiteral:
  - a. Check that value' has type integerLiteral.
  - b. Let integerLiteral' be value'.
  - c. Check that integerLiteral' matches pattern % W %.
  - d. Let  $w' \ W \ i_r$  be integerLiteral'.
  - e. Check that w is equal to w'.
  - f. Let i be  $i_l + i_r$ .
  - g. Let  $i_{\max}$  be 2 to the power of w.
  - h. Let i' be i if i is less than  $i_{\max}$  otherwise  $i_{\max} - 1$ .
  - i. Return  $w \ W \ i'$ .
4. Else if let  $w \ S \ i_l$  be integerLiteral:
  - a. Check that value' has type integerLiteral.
  - b. Let integerLiteral' be value'.
  - c. Check that integerLiteral' matches pattern % S %.
  - d. Let  $w' \ S \ i_r$  be integerLiteral'.
  - e. Check that w is equal to w'.
  - f. Let  $i_r$  be the two's complement representation of bitstring  $i_l$  of width w.
  - g. Let  $i_r$  be the two's complement representation of bitstring  $i_r$  of width w.
  - h. Let i be  $i_l + i_r$ .
  - i. If i is greater than 0:
    - i. Let int be  $w - 1$ .
    - ii. Check that int has type nat.
    - iii. Let  $w''$  be int.
    - iv. Let  $i_{\max}$  be 2 to the power of  $w''$ .
    - v. Let i' be i if i is less than  $i_{\max}$  otherwise  $i_{\max} - 1$ .
    - vi. Let i'' be the bitstring of width w representing the integer i'.
    - vii. Return  $w \ S \ i''$ .
  - j. If i is less than or equal to 0:
    - i. Let int be  $w - 1$ .
    - ii. Check that int has type nat.
    - iii. Let  $w''$  be int.
    - iv. Let int' be 2 to the power of  $w''$ .
    - v. Let  $i_{\min}$  be -int'.
    - vi. Let i' be i if i is greater than or equal to  $i_{\min}$  otherwise  $i_{\min}$ .

- vii. Let  $i''$  be the bitstring of width  $w$  representing the integer  $i'$ .
- viii. Return  $w \ S \ i''$ .

## Subtraction

$value - value'$

1. Check that  $value$  has type `integerLiteral`.
2. Let `integerLiteral` be  $value$ .
3. If let  $D \ i_l$  be `integerLiteral`:
  - a. Check that  $value'$  has type `integerLiteral`.
  - b. Let `integerLiteral'` be  $value'$ .
  - c. Check that `integerLiteral'` matches pattern  $D \ %$ .
  - d. Let  $D \ i_r$  be `integerLiteral'`.
  - e. Return  $D \ i_l - i_r$ .
4. Else if let  $w \ W \ i_l$  be `integerLiteral`:
  - a. Check that  $value'$  has type `integerLiteral`.
  - b. Let `integerLiteral'` be  $value'$ .
  - c. Check that `integerLiteral'` matches pattern  $\% \ W \ %$ .
  - d. Let  $w' \ W \ i_r$  be `integerLiteral'`.
  - e. Check that  $w$  is equal to  $w'$ .
  - f. Let  $i_r$  be the two's complement representation of bitstring  $i_l$  of width  $w$ .
  - g. Let  $i_r'$  be the two's complement representation of bitstring  $i_r$  of width  $w$ .
  - h. Let  $i$  be the bitstring of width  $w$  representing the integer  $i_l - i_r'$ .
  - i. Return  $w \ W \ i$ .
5. Else:
  - a. Let  $w \ S \ i_l$  be `integerLiteral`.
  - b. Check that  $value'$  has type `integerLiteral`.
  - c. Let `integerLiteral'` be  $value'$ .
  - d. Check that `integerLiteral'` matches pattern  $\% \ S \ %$ .
  - e. Let  $w' \ S \ i_r$  be `integerLiteral'`.
  - f. Check that  $w$  is equal to  $w'$ .
  - g. Let  $i_r$  be the two's complement representation of bitstring  $i_l$  of width  $w$ .
  - h. Let  $i_r'$  be the two's complement representation of bitstring  $i_r$  of width  $w$ .
  - i. Let  $i$  be the bitstring of width  $w$  representing the integer  $i_l - i_r'$ .
  - j. Return  $w \ S \ i$ .

value |-| value'

1. Check that value has type integerLiteral.
2. Let integerLiteral be value.
3. If let  $w \ W \ i_l$  be integerLiteral:
  - a. Check that value' has type integerLiteral.
  - b. Let integerLiteral' be value'.
  - c. Check that integerLiteral' matches pattern % W %.
  - d. Let  $w' \ W \ i_r$  be integerLiteral'.
  - e. Check that w is equal to w'.
  - f. Let i be  $i_l - i_r$ .
  - g. Let i' be i if i is greater than or equal to 0 otherwise 0.
  - h. Return  $w \ W \ i'$ .
4. Else if let  $w \ S \ i_l$  be integerLiteral:
  - a. Check that value' has type integerLiteral.
  - b. Let integerLiteral' be value'.
  - c. Check that integerLiteral' matches pattern % S %.
  - d. Let  $w' \ S \ i_r$  be integerLiteral'.
  - e. Check that w is equal to w'.
  - f. Let  $i_l$  be the two's complement representation of bitstring  $i_l$  of width w.
  - g. Let  $i_r$  be the two's complement representation of bitstring  $i_r$  of width w.
  - h. Let i be  $i_l - i_r$ .
  - i. If i is greater than 0:
    - i. Let int be  $w - 1$ .
    - ii. Check that int has type nat.
    - iii. Let  $w''$  be int.
    - iv. Let  $i_{\max}$  be 2 to the power of  $w''$ .
    - v. Let i' be i if i is less than  $i_{\max}$  otherwise  $i_{\max} - 1$ .
    - vi. Let i'' be the bitstring of width w representing the integer i'.
    - vii. Return  $w \ S \ i''$ .
  - j. If i is less than or equal to 0:
    - i. Let int be  $w - 1$ .
    - ii. Check that int has type nat.
    - iii. Let  $w''$  be int.
    - iv. Let int' be 2 to the power of  $w''$ .
    - v. Let  $i_{\min}$  be -int'.
    - vi. Let i' be i if i is greater than or equal to  $i_{\min}$  otherwise  $i_{\min}$ .

- vii. Let  $i'$  be the bitstring of width  $w$  representing the integer  $i'$ .
- viii. Return  $w \ S \ i'$ .

## Multiplication

$value * value'$

1. Check that  $value$  has type `integerLiteral`.
2. Let `integerLiteral` be  $value$ .
3. If let  $D \ i_l$  be `integerLiteral`:
  - a. Check that  $value'$  has type `integerLiteral`.
  - b. Let `integerLiteral'` be  $value'$ .
  - c. Check that `integerLiteral'` matches pattern  $D \ %$ .
  - d. Let  $D \ i_r$  be `integerLiteral'`.
  - e. Return  $D \ i_l * i_r$ .
4. Else if let  $w \ W \ i_l$  be `integerLiteral`:
  - a. Check that  $value'$  has type `integerLiteral`.
  - b. Let `integerLiteral'` be  $value'$ .
  - c. Check that `integerLiteral'` matches pattern  $\% \ W \ %$ .
  - d. Let  $w' \ W \ i_r$  be `integerLiteral'`.
  - e. Check that  $w$  is equal to  $w'$ .
  - f. Let  $i_r$  be the two's complement representation of bitstring  $i_l$  of width  $w$ .
  - g. Let  $i_r$  be the two's complement representation of bitstring  $i_r$  of width  $w$ .
  - h. Let  $i$  be the bitstring of width  $w$  representing the integer  $i_l * i_r$ .
  - i. Return  $w \ W \ i$ .
5. Else:
  - a. Let  $w \ S \ i_l$  be `integerLiteral`.
  - b. Check that  $value'$  has type `integerLiteral`.
  - c. Let `integerLiteral'` be  $value'$ .
  - d. Check that `integerLiteral'` matches pattern  $\% \ S \ %$ .
  - e. Let  $w' \ S \ i_r$  be `integerLiteral'`.
  - f. Check that  $w$  is equal to  $w'$ .
  - g. Let  $i_r$  be the two's complement representation of bitstring  $i_l$  of width  $w$ .
  - h. Let  $i_r$  be the two's complement representation of bitstring  $i_r$  of width  $w$ .
  - i. Let  $i$  be the bitstring of width  $w$  representing the integer  $i_l * i_r$ .
  - j. Return  $w \ S \ i$ .

## Division

`value / value'`

1. Check that `value` has type `integerLiteral`.
2. Let `integerLiteral` be `value`.
3. Check that `integerLiteral` matches pattern `D %`.
4. Let `D il` be `integerLiteral`.
5. Check that `value'` has type `integerLiteral`.
6. Let `integerLiteral'` be `value'`.
7. Check that `integerLiteral'` matches pattern `D %`.
8. Let `D ir` be `integerLiteral'`.
9. Return `D il / ir`.

## Modulus

`value % value'`

1. Check that `value` has type `integerLiteral`.
2. Let `integerLiteral` be `value`.
3. Check that `integerLiteral` matches pattern `D %`.
4. Let `D il` be `integerLiteral`.
5. Check that `value'` has type `integerLiteral`.
6. Let `integerLiteral'` be `value'`.
7. Check that `integerLiteral'` matches pattern `D %`.
8. Let `D ir` be `integerLiteral'`.
9. Return `D il \ ir`.

## Shift left

`value << value'`

1. Check that `value` has type `integerLiteral`.
2. Let `integerLiteral` be `value`.
3. If let `D il` be `integerLiteral`:
  - a. Check that `value'` has type `integerLiteral`.
  - b. Let `integerLiteral'` be `value'`.
  - c. If let `D ir` be `integerLiteral'`:
    - i. Let `int` be the left shift of `il` by `ir`.
    - ii. Return `D int`.

- d. Else if let  $w_r W i_r$  be `integerLiteral`:
    - i. Let `int` be the left shift of  $i_l$  by  $i_r$ .
    - ii. Return `D int`.
  - e. Else:
    - i. Let  $w_r S i_r$  be `integerLiteral`.
    - ii. Let  $i_r$  be the two's complement representation of bitstring  $i_r$  of width  $w_r$ .
    - iii. Let `int` be the left shift of  $i_l$  by  $i_r$ .
    - iv. Return `D int`.
4. Else if let  $w_l W i_l$  be `integerLiteral`:
    - a. Check that `value'` has type `integerLiteral`.
    - b. Let `integerLiteral'` be `value'`.
    - c. If let `D i_r` be `integerLiteral'`:
      - i. Let `int` be the two's complement representation of bitstring  $i_r$  of width  $w_l$ .
      - ii. Return  $w_l W i_l << w_l W \text{int}$ .
    - d. Else if let  $w_r W i_r$  be `integerLiteral`:
      - i. Let `int` be the left shift of  $i_l$  by  $i_r$ .
      - ii. Let  $i$  be the bitstring of width  $w_l$  representing the integer `int`.
      - iii. Return  $w_l W i$ .
    - e. Else:
      - i. Let  $w_r S i_r$  be `integerLiteral`.
      - ii. Let  $i_r$  be the two's complement representation of bitstring  $i_r$  of width  $w_r$ .
      - iii. Let `int` be the left shift of  $i_l$  by  $i_r$ .
      - iv. Let  $i$  be the bitstring of width  $w_l$  representing the integer `int`.
      - v. Return  $w_l W i$ .
  5. Else:
    - a. Let  $w_l S i_l$  be `integerLiteral`.
    - b. Check that `value'` has type `integerLiteral`.
    - c. Let `integerLiteral'` be `value'`.
    - d. If let `D i_r` be `integerLiteral'`:
      - i. Let `int` be the two's complement representation of bitstring  $i_r$  of width  $w_l$ .
      - ii. Return  $w_l S i_l << w_l S \text{int}$ .
    - e. Else if let  $w_r W i_r$  be `integerLiteral`:
      - i. Let  $i_r$  be the two's complement representation of bitstring  $i_l$  of width  $w_l$ .
      - ii. Let `int` be the left shift of  $i_l$  by  $i_r$ .
      - iii. Let  $i$  be the bitstring of width  $w_l$  representing the integer `int`.
      - iv. Return  $w_l S i$ .
    - f. Else:
      - i. Let  $w_r S i_r$  be `integerLiteral`.

- ii. Let  $i_r$  be the two's complement representation of bitstring  $i_l$  of width  $w_l$ .
- iii. Let  $i_r$  be the two's complement representation of bitstring  $i_r$  of width  $w_r$ .
- iv. Let  $int$  be the left shift of  $i_l$  by  $i_r$ .
- v. Let  $i$  be the bitstring of width  $w_l$  representing the integer  $int$ .
- vi. Return  $w_l \ S \ i$ .

## Shift right

`value >> value'`

1. Check that `value` has type `integerLiteral`.
2. Let `integerLiteral` be `value`.
3. If let  $D \ i_l$  be `integerLiteral`:
  - a. Check that `value'` has type `integerLiteral`.
  - b. Let `integerLiteral'` be `value'`.
  - c. If let  $D \ i_r$  be `integerLiteral'`:
    - i. Let `int'` be the logical right shift of  $i_l$  by  $i_r$ .
    - ii. Return  $D \ int'$ .
  - d. Else if let  $w_r \ W \ i_r$  be `integerLiteral'`:
    - i. Let `int'` be the logical right shift of  $i_l$  by  $i_r$ .
    - ii. Return  $D \ int'$ .
  - e. Else:
    - i. Let  $w_r \ S \ i_r$  be `integerLiteral'`.
    - ii. Let  $i_r$  be the two's complement representation of bitstring  $i_r$  of width  $w_r$ .
    - iii. Let `int'` be the logical right shift of  $i_l$  by  $i_r$ .
    - iv. Return  $D \ int'$ .
4. Else if let  $w_l \ W \ i_l$  be `integerLiteral`:
  - a. Check that `value'` has type `integerLiteral`.
  - b. Let `integerLiteral'` be `value'`.
  - c. If let  $D \ i_r$  be `integerLiteral'`:
    - i. Let `int'` be the two's complement representation of bitstring  $i_r$  of width  $w_l$ .
    - ii. Return  $w_l \ W \ i_l \ >> \ w_l \ W \ int'$ .
  - d. Else if let  $w_r \ W \ i_r$  be `integerLiteral'`:
    - i. Let `int'` be the logical right shift of  $i_l$  by  $i_r$ .
    - ii. Let  $i$  be the bitstring of width  $w_l$  representing the integer `int'`.
    - iii. Return  $w_l \ W \ i$ .
  - e. Else:
    - i. Let  $w_r \ S \ i_r$  be `integerLiteral'`.
    - ii. Let  $i_r$  be the two's complement representation of bitstring  $i_r$  of width  $w_r$ .

- iii. Let  $int'$  be the logical right shift of  $i_l$  by  $i_r$ .
- iv. Let  $i$  be the bitstring of width  $w_l$  representing the integer  $int'$ .
- v. Return  $w_l \mathbf{W} i$ .

5. Else:

- a. Let  $w_l \mathbf{S} i_l$  be `integerLiteral`.
- b. Check that `value'` has type `integerLiteral`.
- c. Let `integerLiteral'` be `value'`.
- d. If let  $D i_r$  be `integerLiteral'`:
  - i. Let  $i_r$  be the two's complement representation of bitstring  $i_l$  of width  $w_l$ .
  - ii. If  $i_r$  is less than 0:
    - A. Let  $int$  be  $w_l - 1$ .
    - B. Check that  $int$  has type `nat`.
    - C. Let  $w_r$  be  $int$ .
    - D. Let  $int'$  be 2 to the power of  $w_r$ .
    - E. Let  $i$  be the arithmetic right shift of  $i_l$  by  $i_r$  with sign extension  $int'$ .
    - F. Let  $i'$  be the bitstring of width  $w_l$  representing the integer  $i$ .
    - G. Return  $w_l \mathbf{S} i'$ .
  - iii. If  $i_r$  is greater than or equal to 0:
    - A. Let  $i$  be the logical right shift of  $i_l$  by  $i_r$ .
    - B. Let  $i'$  be the bitstring of width  $w_l$  representing the integer  $i$ .
    - C. Return  $w_l \mathbf{S} i'$ .
- e. Else if let  $w_r \mathbf{W} i_r$  be `integerLiteral'`:
  - i. Let  $i_r$  be the two's complement representation of bitstring  $i_l$  of width  $w_l$ .
  - ii. If  $i_r$  is less than 0:
    - A. Let  $int$  be  $w_l - 1$ .
    - B. Check that  $int$  has type `nat`.
    - C. Let  $w_r$  be  $int$ .
    - D. Let  $int'$  be 2 to the power of  $w_r$ .
    - E. Let  $i$  be the arithmetic right shift of  $i_l$  by  $i_r$  with sign extension  $int'$ .
    - F. Let  $i'$  be the bitstring of width  $w_l$  representing the integer  $i$ .
    - G. Return  $w_l \mathbf{S} i'$ .
  - iii. If  $i_r$  is greater than or equal to 0:
    - A. Let  $i$  be the logical right shift of  $i_l$  by  $i_r$ .
    - B. Let  $i'$  be the bitstring of width  $w_l$  representing the integer  $i$ .
    - C. Return  $w_l \mathbf{S} i'$ .
- f. Else:
  - i. Let  $w_r \mathbf{S} i_r$  be `integerLiteral'`.
  - ii. Let  $i_r$  be the two's complement representation of bitstring  $i_l$  of width  $w_l$ .



- iii. Let  $i_r$  be the two's complement representation of bitstring  $i_r$  of width  $w_r$ .
- iv. If  $i_r$  is less than 0:
  - A. Let  $int$  be  $w_l - 1$ .
  - B. Check that  $int$  has type  $nat$ .
  - C. Let  $w_l$  be  $int$ .
  - D. Let  $int'$  be 2 to the power of  $w_l$ .
  - E. Let  $i$  be the arithmetic right shift of  $i_l$  by  $i_r$  with sign extension  $int'$ .
  - F. Let  $i'$  be the bitstring of width  $w_l$  representing the integer  $i$ .
  - G. Return  $w_l S i'$ .
- v. If  $i_r$  is greater than or equal to 0:
  - A. Let  $i$  be the logical right shift of  $i_l$  by  $i_r$ .
  - B. Let  $i'$  be the bitstring of width  $w_l$  representing the integer  $i$ .
  - C. Return  $w_l S i'$ .

## Equality and inequality

`value == value'`

1. If let ``B ba` be `value`:
  - a. Check that `value'` has type `boolValue`.
  - b. Let ``B bb` be `value'`.
  - c. Return `ba` is equal to `bb`.
2. Else if let `ERROR . ida` be `value`:
  - a. Check that `value'` has type `errorValue`.
  - b. Let `ERROR . idb` be `value'`.
  - c. Return `ida` is equal to `idb`.
3. Else if let `MATCH_KIND . ida` be `value`:
  - a. Check that `value'` has type `matchKindValue`.
  - b. Let `MATCH_KIND . idb` be `value'`.
  - c. Return `ida` is equal to `idb`.
4. Else if let `stringValuea` be `value`:
  - a. Check that `value'` has type `stringValue`.
  - b. Let `stringValueb` be `value'`.
  - c. Return `stringValuea` is equal to `stringValueb`.
5. Else if let `integerLiteral` be `value`:
  - a. If let `D ia` be `integerLiteral`:
    - i. Check that `value'` has type `integerLiteral`.
    - ii. Let `integerLiteral'` be `value'`.
    - iii. Check that `integerLiteral'` matches pattern `D %`.

- iv. Let  $D\ i_b$  be `integerLiteral`.
  - v. Return  $i_a$  is equal to  $i_b$ .
- b. Else if let  $w_a\ W\ i_a$  be `integerLiteral`:
- i. Check that `value'` has type `integerLiteral`.
  - ii. Let `integerLiteral'` be `value'`.
  - iii. Check that `integerLiteral'` matches pattern `% W %`.
  - iv. Let  $w_b\ W\ i_b$  be `integerLiteral`.
  - v. Return  $w_a$  is equal to  $w_b$  and  $i_a$  is equal to  $i_b$ .
- c. Else:
- i. Let  $w_a\ S\ i_a$  be `integerLiteral`.
  - ii. Check that `value'` has type `integerLiteral`.
  - iii. Let `integerLiteral'` be `value'`.
  - iv. Check that `integerLiteral'` matches pattern `% S %`.
  - v. Let  $w_b\ S\ i_b$  be `integerLiteral`.
  - vi. Return  $w_a$  is equal to  $w_b$  and  $i_a$  is equal to  $i_b$ .
6. Else if let `LIST [ valuea* ]` be `value`:
- a. Check that `value'` has type `listValue`.
  - b. Let `LIST [ valueb* ]` be `value'`.
  - c. Let `bool`<sup>\*</sup> be the list of `bool'` and `bool`<sup>\*\*</sup> be the list of `bool'`, obtained by repeating:
    - Let `bool'` be `valuea == valueb`.
 for each `valuea` in `valuea*` and `valueb` in `valueb*`
  - d. Let `bool` be `all bool* are true`.
  - e. Return the length of `valuea*` is equal to the length of `valueb*` and `bool`.
7. Else if let `TUPLE ( valuea* )` be `value`:
- a. Check that `value'` has type `tupleValue`.
  - b. Let `TUPLE ( valueb* )` be `value'`.
  - c. Let `bool`<sup>\*</sup> be the list of `bool'` and `bool`<sup>\*\*</sup> be the list of `bool'`, obtained by repeating:
    - Let `bool'` be `valuea == valueb`.
 for each `valuea` in `valuea*` and `valueb` in `valueb*`
  - d. Let `bool` be `all bool* are true`.
  - e. Return the length of `valuea*` is equal to the length of `valueb*` and `bool`.
8. Else if let `HEADER_STACK [ valuea* ( _ ; nsize_a ) ]` be `value`:
- a. Check that `value'` has type `headerStackValue`.
  - b. Let `HEADER_STACK [ valueb* ( _ ; nsize_b ) ]` be `value'`.
  - c. Let `bool`<sup>\*</sup> be the list of `bool'` and `bool`<sup>\*\*</sup> be the list of `bool'`, obtained by repeating:
    - Let `bool'` be `valuea == valueb`.

- for each  $value_a$  in  $value_a^*$  and  $value_b$  in  $value_b^*$
- d. Let  $bool$  be **all**  $bool^*$  **are true**.
  - e. Return the length of  $value_a^*$  is equal to the length of  $value_b^*$  and  $bool$  and  $n_{size\_a}$  is equal to  $n_{size\_b}$ .
9. Else if let  $STRUCT\ typeld_a \{ fieldValue_a^* \}$  be  $value$ :
- a. Check that  $value'$  has type  $structValue$ .
  - b. Let  $STRUCT\ typeld_b \{ fieldValue_b^* \}$  be  $value'$ .
  - c. Let  $nameIR_{field\_a}^*$  be the list of  $nameIR_{field\_a}$  and  $value_{field\_a}^*$  be the list of  $value_{field\_a}$ , obtained by repeating:
    - Let  $value_{field\_a}\ nameIR_{field\_a}$  ; be  $fieldValue_a$ .
 for each  $fieldValue_a$  in  $fieldValue_a^*$
  - d. Let  $nameIR_{field\_b}^*$  be the list of  $nameIR_{field\_b}$  and  $value_{field\_b}^*$  be the list of  $value_{field\_b}$ , obtained by repeating:
    - Let  $value_{field\_b}\ nameIR_{field\_b}$  ; be  $fieldValue_b$ .
 for each  $fieldValue_b$  in  $fieldValue_b^*$
  - e. Let  $bool^*$  be the list of  $bool'$  and  $bool^{**}$  be the list of  $bool^*$ , obtained by repeating:
    - Let  $bool'$  be  $value_{field\_a} == value_{field\_b}$ .
 for each  $value_{field\_a}$  in  $value_{field\_a}^*$  and  $value_{field\_b}$  in  $value_{field\_b}^*$
  - f. Let  $bool$  be **all**  $bool^*$  **are true**.
  - g. Let  $bool''$  be **all** (  $nameIR_{field\_a} = nameIR_{field\_b}$  ) **are true**.
  - h. Return  $typeld_a$  is equal to  $typeld_b$  and the length of  $fieldValue_a^*$  is equal to the length of  $fieldValue_b^*$  and  $bool$  and  $bool''$ .
10. Else if let  $HEADER\ typeld_a \{ _ ; fieldValue_a^* \}$  be  $value$ :
- a. Check that  $value'$  has type  $headerValue$ .
  - b. Let  $HEADER\ typeld_b \{ _ ; fieldValue_b^* \}$  be  $value'$ .
  - c. Let  $nameIR_{field\_a}^*$  be the list of  $nameIR_{field\_a}$  and  $value_{field\_a}^*$  be the list of  $value_{field\_a}$ , obtained by repeating:
    - Let  $value_{field\_a}\ nameIR_{field\_a}$  ; be  $fieldValue_a$ .
 for each  $fieldValue_a$  in  $fieldValue_a^*$
  - d. Let  $nameIR_{field\_b}^*$  be the list of  $nameIR_{field\_b}$  and  $value_{field\_b}^*$  be the list of  $value_{field\_b}$ , obtained by repeating:
    - Let  $value_{field\_b}\ nameIR_{field\_b}$  ; be  $fieldValue_b$ .
 for each  $fieldValue_b$  in  $fieldValue_b^*$
  - e. Let  $bool^*$  be the list of  $bool'$  and  $bool^{**}$  be the list of  $bool^*$ , obtained by repeating:
    - Let  $bool'$  be  $value_{field\_a} == value_{field\_b}$ .

- for each  $value_{field\_a}$  in  $value_{field\_a}^*$  and  $value_{field\_b}$  in  $value_{field\_b}^*$
- f. Let  $bool$  be **all**  $bool^*$  **are true**.
  - g. Let  $bool''$  be **all** ( $nameIR_{field\_a} = nameIR_{field\_b}$ ) **are true**.
  - h. Return  $typeld_a$  is equal to  $typeld_b$  and the length of  $fieldValue_a^*$  is equal to the length of  $fieldValue_b^*$  and  $bool$  and  $bool''$ .
11. Else if let  $HEADER\_UNION typeld_a \{ fieldValue_a^* \}$  be  $value$ :
- a. Check that  $value'$  has type  $headerUnionValue$ .
  - b. Let  $HEADER\_UNION typeld_b \{ fieldValue_b^* \}$  be  $value'$ .
  - c. Let  $nameIR_{field\_a}^*$  be the list of  $nameIR_{field\_a}$  and  $value_{field\_a}^*$  be the list of  $value_{field\_a}$ , obtained by repeating:
    - Let  $value_{field\_a} nameIR_{field\_a} ;$  be  $fieldValue_a$ .

for each  $fieldValue_a$  in  $fieldValue_a^*$
  - d. Let  $nameIR_{field\_b}^*$  be the list of  $nameIR_{field\_b}$  and  $value_{field\_b}^*$  be the list of  $value_{field\_b}$ , obtained by repeating:
    - Let  $value_{field\_b} nameIR_{field\_b} ;$  be  $fieldValue_b$ .

for each  $fieldValue_b$  in  $fieldValue_b^*$
  - e. Let  $bool^*$  be the list of  $bool'$  and  $bool^{**}$  be the list of  $bool^*$ , obtained by repeating:
    - Let  $bool'$  be  $value_{field\_a} == value_{field\_b}$ .

for each  $value_{field\_a}$  in  $value_{field\_a}^*$  and  $value_{field\_b}$  in  $value_{field\_b}^*$
  - f. Let  $bool$  be **all**  $bool^*$  **are true**.
  - g. Let  $bool''$  be **all** ( $nameIR_{field\_a} = nameIR_{field\_b}$ ) **are true**.
  - h. Return  $typeld_a$  is equal to  $typeld_b$  and the length of  $fieldValue_a^*$  is equal to the length of  $fieldValue_b^*$  and  $bool$  and  $bool''$ .
12. Else if let  $enumValue$  be  $value$ :
- a. If let  $typeld_a . nameIR_{field\_a}$  be  $enumValue$ :
    - i. Check that  $value'$  has type  $enumValue$ .
    - ii. Let  $enumValue'$  be  $value'$ .
    - iii. Check that  $enumValue'$  matches pattern  $\% . \%$ .
    - iv. Let  $typeld_b . nameIR_{field\_b}$  be  $enumValue'$ .
    - v. Return  $typeld_a$  is equal to  $typeld_b$  and  $nameIR_{field\_a}$  is equal to  $nameIR_{field\_b}$ .
  - b. Else:
    - i. Let  $typeld_a . _ . value_{field\_a}$  be  $enumValue$ .
    - ii. Check that  $value'$  has type  $enumValue$ .
    - iii. Let  $enumValue'$  be  $value'$ .
    - iv. Check that  $enumValue'$  matches pattern  $\% . \% . \%$ .
    - v. Let  $typeld_b . _ . value_{field\_b}$  be  $enumValue'$ .

- vi. Let `bool` be `valuefield_a == valuefield_b`.
  - vii. Return `typeida` is equal to `typeidb` and `bool`.
13. Else if let `invalidHeaderValue` be `value`:
- a. Check that `value'` has type `invalidHeaderValue`.
  - b. Let `invalidHeaderValue'` be `value'`.
  - c. Return `true`.
14. If let `integerValue` be `value`:
- a. Check that `integerValue` matches pattern `% . % V %`.
  - b. Let `wmax_a . _ V ia` be `integerValue`.
  - c. Check that `value'` has type `integerValue`.
  - d. Let `integerValue'` be `value'`.
  - e. Check that `integerValue'` matches pattern `% . % V %`.
  - f. Let `wmax_b . _ V ib` be `integerValue'`.
  - g. Return `wmax_a` is equal to `wmax_b` and `ia` is equal to `ib`.

`valuei != valuer`

1. Let `bool` be `valuei == valuer`.
2. Return `~bool`.

## Comparisons

`value < value'`

1. Check that `value` has type `integerLiteral`.
2. Let `integerLiteral` be `value`.
3. If let `D ii` be `integerLiteral`:
  - a. Check that `value'` has type `integerLiteral`.
  - b. Let `integerLiteral'` be `value'`.
  - c. Check that `integerLiteral'` matches pattern `D %`.
  - d. Let `D ir` be `integerLiteral'`.
  - e. Return `ii` is less than `ir`.
4. Else if let `w W ii` be `integerLiteral`:
  - a. Check that `value'` has type `integerLiteral`.
  - b. Let `integerLiteral'` be `value'`.
  - c. Check that `integerLiteral'` matches pattern `% W %`.
  - d. Let `w' W ir` be `integerLiteral'`.
  - e. Check that `w` is equal to `w'`.
  - f. Return `ii` is less than `ir`.

5. Else:

- a. Let  $w \ S \ i_l$  be `integerLiteral`.
- b. Check that `value'` has type `integerLiteral`.
- c. Let `integerLiteral'` be `value'`.
- d. Check that `integerLiteral'` matches pattern `% S %`.
- e. Let  $w' \ S \ i_r$  be `integerLiteral'`.
- f. Check that  $w$  is equal to  $w'$ .
- g. Let  $i_r$  be the two's complement representation of bitstring  $i_l$  of width  $w$ .
- h. Let  $i_r$  be the two's complement representation of bitstring  $i_r$  of width  $w$ .
- i. Return  $i_r$  is less than  $i_r$ .

`value <= value'`

1. Check that `value` has type `integerLiteral`.
2. Let `integerLiteral` be `value`.
3. If let  $D \ i_l$  be `integerLiteral`:
  - a. Check that `value'` has type `integerLiteral`.
  - b. Let `integerLiteral'` be `value'`.
  - c. Check that `integerLiteral'` matches pattern `D %`.
  - d. Let  $D \ i_r$  be `integerLiteral'`.
  - e. Return  $i_l$  is less than or equal to  $i_r$ .
4. Else if let  $w \ W \ i_l$  be `integerLiteral`:
  - a. Check that `value'` has type `integerLiteral`.
  - b. Let `integerLiteral'` be `value'`.
  - c. Check that `integerLiteral'` matches pattern `% W %`.
  - d. Let  $w' \ W \ i_r$  be `integerLiteral'`.
  - e. Check that  $w$  is equal to  $w'$ .
  - f. Return  $i_l$  is less than or equal to  $i_r$ .

5. Else:

- a. Let  $w \ S \ i_l$  be `integerLiteral`.
- b. Check that `value'` has type `integerLiteral`.
- c. Let `integerLiteral'` be `value'`.
- d. Check that `integerLiteral'` matches pattern `% S %`.
- e. Let  $w' \ S \ i_r$  be `integerLiteral'`.
- f. Check that  $w$  is equal to  $w'$ .
- g. Let  $i_r$  be the two's complement representation of bitstring  $i_l$  of width  $w$ .
- h. Let  $i_r$  be the two's complement representation of bitstring  $i_r$  of width  $w$ .
- i. Return  $i_r$  is less than or equal to  $i_r$ .

value > value'

1. Check that value has type integerLiteral.
2. Let integerLiteral be value.
3. If let D i<sub>l</sub> be integerLiteral:
  - a. Check that value' has type integerLiteral.
  - b. Let integerLiteral' be value'.
  - c. Check that integerLiteral' matches pattern D %.
  - d. Let D i<sub>r</sub> be integerLiteral'.
  - e. Return i<sub>l</sub> is greater than i<sub>r</sub>.
4. Else if let w W i<sub>l</sub> be integerLiteral:
  - a. Check that value' has type integerLiteral.
  - b. Let integerLiteral' be value'.
  - c. Check that integerLiteral' matches pattern % W %.
  - d. Let w' W i<sub>r</sub> be integerLiteral'.
  - e. Check that w is equal to w'.
  - f. Return i<sub>l</sub> is greater than i<sub>r</sub>.
5. Else:
  - a. Let w S i<sub>l</sub> be integerLiteral.
  - b. Check that value' has type integerLiteral.
  - c. Let integerLiteral' be value'.
  - d. Check that integerLiteral' matches pattern % S %.
  - e. Let w' S i<sub>r</sub> be integerLiteral'.
  - f. Check that w is equal to w'.
  - g. Let i<sub>r</sub> be the two's complement representation of bitstring i<sub>l</sub> of width w.
  - h. Let i<sub>r</sub> be the two's complement representation of bitstring i<sub>r</sub> of width w.
  - i. Return i<sub>l</sub> is greater than i<sub>r</sub>.

value >= value'

1. Check that value has type integerLiteral.
2. Let integerLiteral be value.
3. If let D i<sub>l</sub> be integerLiteral:
  - a. Check that value' has type integerLiteral.
  - b. Let integerLiteral' be value'.
  - c. Check that integerLiteral' matches pattern D %.
  - d. Let D i<sub>r</sub> be integerLiteral'.
  - e. Return i<sub>l</sub> is greater than or equal to i<sub>r</sub>.

4. Else if let  $w \ W \ i_l$  be `integerLiteral`:
  - a. Check that `value'` has type `integerLiteral`.
  - b. Let `integerLiteral'` be `value'`.
  - c. Check that `integerLiteral'` matches pattern `% W %`.
  - d. Let  $w' \ W \ i_r$  be `integerLiteral'`.
  - e. Check that  $w$  is equal to  $w'$ .
  - f. Return  $i_l$  is greater than or equal to  $i_r$ .
5. Else:
  - a. Let  $w \ S \ i_l$  be `integerLiteral`.
  - b. Check that `value'` has type `integerLiteral`.
  - c. Let `integerLiteral'` be `value'`.
  - d. Check that `integerLiteral'` matches pattern `% S %`.
  - e. Let  $w' \ S \ i_r$  be `integerLiteral'`.
  - f. Check that  $w$  is equal to  $w'$ .
  - g. Let  $i_r$  be the two's complement representation of bitstring  $i_l$  of width  $w$ .
  - h. Let  $i_r$  be the two's complement representation of bitstring  $i_r$  of width  $w$ .
  - i. Return  $i_r$  is greater than or equal to  $i_l$ .

## Bitwise

`value & value'`

1. Check that `value` has type `integerLiteral`.
2. Let `integerLiteral` be `value`.
3. If let  $w \ W \ i_l$  be `integerLiteral`:
  - a. Check that `value'` has type `integerLiteral`.
  - b. Let `integerLiteral'` be `value'`.
  - c. Check that `integerLiteral'` matches pattern `% W %`.
  - d. Let  $w' \ W \ i_r$  be `integerLiteral'`.
  - e. Check that  $w$  is equal to  $w'$ .
  - f. Let `int` be the bitwise and of  $i_l$  and  $i_r$ .
  - g. Let  $i$  be the bitstring of width  $w$  representing the integer `int`.
  - h. Return  $w \ W \ i$ .
4. Else if let  $w \ S \ i_l$  be `integerLiteral`:
  - a. Check that `value'` has type `integerLiteral`.
  - b. Let `integerLiteral'` be `value'`.
  - c. Check that `integerLiteral'` matches pattern `% S %`.
  - d. Let  $w' \ S \ i_r$  be `integerLiteral'`.
  - e. Check that  $w$  is equal to  $w'$ .



- f. Let  $i_r$  be the two's complement representation of bitstring  $i_l$  of width  $w$ .
- g. Let  $i_r$  be the two's complement representation of bitstring  $i_r$  of width  $w$ .
- h. Let  $int$  be the bitwise and of  $i_l$  and  $i_r$ .
- i. Let  $i$  be the bitstring of width  $w$  representing the integer  $int$ .
- j. Return  $w \ S \ i$ .

$value \mid value'$

1. Check that  $value$  has type `integerLiteral`.
2. Let `integerLiteral` be  $value$ .
3. If let  $w \ W \ i_l$  be `integerLiteral`:
  - a. Check that  $value'$  has type `integerLiteral`.
  - b. Let `integerLiteral'` be  $value'$ .
  - c. Check that `integerLiteral'` matches pattern  $\% \ W \ \%$ .
  - d. Let  $w' \ W \ i_r$  be `integerLiteral'`.
  - e. Check that  $w$  is equal to  $w'$ .
  - f. Let  $int$  be the bitwise or of  $i_l$  and  $i_r$ .
  - g. Let  $i$  be the bitstring of width  $w$  representing the integer  $int$ .
  - h. Return  $w \ W \ i$ .
4. Else if let  $w \ S \ i_l$  be `integerLiteral`:
  - a. Check that  $value'$  has type `integerLiteral`.
  - b. Let `integerLiteral'` be  $value'$ .
  - c. Check that `integerLiteral'` matches pattern  $\% \ S \ \%$ .
  - d. Let  $w' \ S \ i_r$  be `integerLiteral'`.
  - e. Check that  $w$  is equal to  $w'$ .
  - f. Let  $i_r$  be the two's complement representation of bitstring  $i_l$  of width  $w$ .
  - g. Let  $i_r$  be the two's complement representation of bitstring  $i_r$  of width  $w$ .
  - h. Let  $int$  be the bitwise or of  $i_l$  and  $i_r$ .
  - i. Let  $i$  be the bitstring of width  $w$  representing the integer  $int$ .
  - j. Return  $w \ S \ i$ .

$value \wedge value'$

1. Check that  $value$  has type `integerLiteral`.
2. Let `integerLiteral` be  $value$ .
3. If let  $w \ W \ i_l$  be `integerLiteral`:
  - a. Check that  $value'$  has type `integerLiteral`.
  - b. Let `integerLiteral'` be  $value'$ .

- c. Check that `integerLiteral` matches pattern `% W %`.
  - d. Let `w' W ir` be `integerLiteral`.
  - e. Check that `w` is equal to `w'`.
  - f. Let `int` be the bitwise xor of `il` and `ir`.
  - g. Let `i` be the bitstring of width `w` representing the integer `int`.
  - h. Return `w W i`.
4. Else if let `w S il` be `integerLiteral`:
    - a. Check that `value` has type `integerLiteral`.
    - b. Let `integerLiteral` be `value`.
    - c. Check that `integerLiteral` matches pattern `% S %`.
    - d. Let `w' S ir` be `integerLiteral`.
    - e. Check that `w` is equal to `w'`.
    - f. Let `ir` be the two's complement representation of bitstring `il` of width `w`.
    - g. Let `ir` be the two's complement representation of bitstring `ir` of width `w`.
    - h. Let `int` be the bitwise xor of `il` and `ir`.
    - i. Let `i` be the bitstring of width `w` representing the integer `int`.
    - j. Return `w S i`.

## 19.3. Default values

Some P4 types define a *default value*, which can be used to automatically initialize values of that type. The high-level description of default values are as follows:

- For `int`, `bit<N>` and `int<N>` types the default value is 0.
- For `bool` the default value is `false`.
- For `error` the default value is `error.NoError` (defined in `core.p4`)
- For `string` the default value is the empty string `""`
- For `varbit<N>` the default value is a string of zero bits (there is currently no P4 literal to represent such a value).
- For `enum` values with an underlying type the default value is 0, even if 0 is actually not one of the named values in the enum.
- For `enum` values without an underlying type the default value is the first value that appears in the `enum` type declaration.
- For `header` types the default value is `invalid`.
- For header stacks the default value is that all elements are invalid and the `nextIndex` is 0.
- For `header_union` values the default value is that all union elements are invalid.
- For `struct` types the default value is a `struct` where each field has the default value of the suitable field type—if all such default values are defined.
- For a `tuple` type the default value is a `tuple` where each field has the default value of the suitable type—if all such default values are defined.

Note that some types do not have default values, e.g., `match_kind`, set types, function types, extern types,

parser types, control types, and package types.

Default values are derived from:

**\$default:**

- The default value for type `typeIR`

**The default value for type `typeIR`**

1. If let `boolTypeIR` be `typeIR`:
  - a. Return ``B false`.
2. Else if let `errorTypeIR` be `typeIR`:
  - a. Return `ERROR . "NoError"`.
3. Else if let `stringTypeIR` be `typeIR`:
  - a. Let `textempty` be `""`.
  - b. Return `" textempty "`.
4. Else if let `intTypeIR` be `typeIR`:
  - a. Return `D 0`.
5. Else if let `BIT < w >` be `typeIR`:
  - a. Return `w W 0`.
6. Else if let `INT < w >` be `typeIR`:
  - a. Return `w S 0`.
7. Else if let `VARBIT < w >` be `typeIR`:
  - a. Return `w . 0 V 0`.
8. Else if let `TYPEDEF _ typeIR'` be `typeIR`:
  - a. Return **the default value for type `typeIR'`**.
9. Else if let `TYPE _ typeIR'` be `typeIR`:
  - a. Return **the default value for type `typeIR'`**.
10. Else if let `TUPLE < typeIR* >` be `typeIR`:
  - a. Let `value*` be the list of `value'`, obtained by repeating:
    - Let `value'` be **the default value for type `typeIR'`**.for each `typeIR'` in `typeIR*`
  - b. Return `TUPLE ( value* )`.
11. Else if let `typeIR' [ ns ]` be `typeIR`:
  - a. Let `value'` be **the default value for type `typeIR'`**.
  - b. Let `value*` be **a list of `ns` copies of `value'`**.
  - c. Return `HEADER_STACK [ value* ( 0 ; ns ) ]`.
12. Else if let `STRUCT typeId < _ > { ( _ typeIRi idi ; )* }` be `typeIR`:

- a. Let  $value^*$  be the list of  $value'$ , obtained by repeating:
  - Let  $value'$  be the default value for type  $typeIR_f$ .
 for each  $typeIR_f$  in  $typeIR_f^*$
- b. Return  $STRUCT\ typeld\ \{ (value'\ id_f ; )^* \}$ .
13. Else if let  $HEADER\ typeld < \_ ^* > \{ ( \_ typeIR_f id_f ; )^* \}$  be  $typeIR$ :
  - a. Let  $value^*$  be the list of  $value'$ , obtained by repeating:
    - Let  $value'$  be the default value for type  $typeIR_f$ .
 for each  $typeIR_f$  in  $typeIR_f^*$
  - b. Return  $HEADER\ typeld\ \{ false ; (value'\ id_f ; )^* \}$ .
14. Else if let  $HEADER\_UNION\ typeld < \_ ^* > \{ ( \_ typeIR_f id_f ; )^* \}$  be  $typeIR$ :
  - a. Let  $value^*$  be the list of  $value'$ , obtained by repeating:
    - Let  $value'$  be the default value for type  $typeIR_f$ .
 for each  $typeIR_f$  in  $typeIR_f^*$
  - b. Return  $HEADER\_UNION\ typeld\ \{ (value'\ id_f ; )^* \}$ .
15. Else if let  $ENUM\ typeld\ \{ id^* \}$  be  $typeIR$ :
  - a. Check that  $id^*$  is a non-empty list.
  - b. Let  $id_{f,h} :: \_ ^*$  be  $id^*$ .
  - c. Return  $typeld . id_{f,h}$ .
16. Else if let  $ENUM\ typeld < typeIR' > \{ ( nameIR_{field} = value_{field} ; )^* \}$  be  $typeIR$ :
  - a. Let  $value_{zero}$  be D 0 casted to type  $typeIR'$ .
  - b. Let  $id^?$  be the value associated to  $value_{zero}$  in  $(value_{field}, nameIR_{field})^*$ .
  - c. If let  $id_{zero}$  be  $id^?$ :
    - i. Return  $typeld . id_{zero} . value_{zero}$ .
  - d. If  $\cdot$  is equal to the value associated to  $value_{zero}$  in  $(value_{field}, nameIR_{field})^*$ :
    - i. Let  $id_{zero}$  be `"__UNSPECIFIED"`.
    - ii. Return  $typeld . id_{zero} . value_{zero}$ .

## 20. Annotations

Annotations are a simple mechanism for extending the P4 language to some limited degree without changing the grammar. Annotations are attached to types, fields, variables, etc. using the `@` syntax (as shown explicitly in the P4 grammar). Unstructured annotations, or just "annotations," have an optional body; structured annotations have a mandatory body, containing at least a pair of square brackets `[]`.

```
annotationBody
: /* empty */
| annotationBody `( annotationBody )
| annotationBody annotationToken
```

```

;

structuredAnnotationBody
: sequenceOrRecordElementExpression trailingCommaOpt
;

annotation
: @ name
| @ name `( annotationBody )
| @ name `[ structuredAnnotationBody ]
| @ PRAGMA name annotationBody
;

```

Structured annotations and unstructured annotations on any one element must not use the same **name**. Thus, a given **name** can only be applied to one type of annotation or the other for any one element. An annotation used on one element does not affect the annotation on another because they have different scope.

This is legal:

```

@my_anno(1) table T { /* body omitted */ }
@my_anno[2] table U { /* body omitted */ } // OK - different scope than previous
                                           // use of my_anno

```

This is illegal:

```

@my_anno(1)
@my_anno[2] table U { /* body omitted */ } // Error - changed type of anno
                                           // on an element

```

Multiple unstructured annotations using the same **name** can appear on a given element; they are cumulative. Each one will be bound to that element. In contrast, only one structured annotation using a given **name** may appear on an element; multiple uses of the same **name** will produce an error.

This is legal:

```

@my_anno(1)
@my_anno(2) table U { /* body omitted */ } // OK - unstructured annos accumulate

```

This is illegal:

```

@my_anno[1]
@my_anno[2] table U { /* body omitted */ } // Error - reused the same structured
                                           // anno on an element

```

## 20.1. Bodies of Unstructured Annotations

The flexibility of P4 unstructured annotations comes from the minimal structure mandated by the P4 grammar: unstructured annotation bodies may contain any sequence of terminals, so long as parentheses are balanced. In the following grammar fragment, the **annotationToken** non-terminal represents any terminal produced by the lexer, including keywords, identifiers, string and integer literals, and symbols, but excluding parentheses.

```

annotationBody
: /* empty */

```

```
| annotationBody `( annotationBody )
| annotationBody annotationToken
;
```

Unstructured annotations may impose additional structure on their bodies, and are not confined to the P4 language. For example, the P4Runtime specification <sup>[2 - Chapter 10]</sup> defines a `@pkginfo` annotation that expects key-value pairs. === Bodies of Structured Annotations

Unlike unstructured annotations, structured annotations use square brackets [...] and have a restricted format. They are commonly used to declare custom metadata, consisting of expression lists or key-value lists but not both. An `expressionList` may be empty or contain a comma-separated list of member expressions. A `namedExpressionList` consists of one or more `namedExpressions`, each consisting of a key and a value `expression`. Note the syntax for `expression` is rich, see [Appendix E](#) for details.

All `expressions` within a `structuredAnnotationBody` must be compile-time known values with a result type that is either: `string`, `int`, or `bool`. In particular, structured `expressions` (e.g. an `expression` containing an `expressionList`, a `namedExpressionList`, etc.) are not allowed. Note that P4Runtime information (P4Info) may stipulate additional restrictions. For example, an integer expression might be limited to 64-bit values.

It is illegal to duplicate a `name` within the `namedExpressionList` of a structured annotation.

```
structuredAnnotationBody
: sequenceOrRecordElementExpression trailingCommaOpt
;

sequenceOrRecordElementExpression
: sequenceElementExpression
| recordElementExpression
;

sequenceElementExpression = expressionList

recordElementExpression
: name = expression
| name = expression , ...
| name = expression , namedExpressionList
| name = expression , namedExpressionList , ...
;

namedExpression
: name = expression
;
```

## 20.1.1. Structured Annotation Examples

### Empty Expression List

The following example produces an empty annotation:

```
@Empty[]
table t {
    /* body omitted */
}
```

### Mixed Expression List

The following example will produce an effective expression list as follows:

```
[1,"hello",true, false, 11]
```

```
#define TEXT_CONST "hello"
#define NUM_CONST 6
@MixedExprList[1,TEXT_CONST,true,1==2,5+NUM_CONST]
table t {
    /* body omitted */
}
```

### namedExprssionList of Strings

```
@Labels[short="Short Label", hover="My Longer Table Label to appear in hover-help"]
table t {
    /* body omitted */
}
```

### namedExpressionList of Mixed Expressions

The following example will produce an effective `namedExpressionList` as follows.

```
[label="text", my_bool=true, int_val=6]
```

```
@MixedKV[label="text", my_bool=true, int_val=2*3]
table t {
    /* body omitted */
}
```

### Illegal Mixing of `namedExpression` and `expressionList`

The following example is invalid because the body contains both a `namedExpression` and an `expression`:

```
@IllegalMixing[key=4, 5] // illegal mixing
table t {
    /* body omitted */
}
```

### Illegal Duplicate Key

The following example is invalid because the same key occurs more than once:

```
@DupKey[k1=4,k1=5] // illegal duplicate key
table t {
    /* body omitted */
}
```

### Illegal Duplicate Structured Annotation

The following example is invalid because the annotation `name` occurs more than once on the same element, e.g. `table t`:

```
@DupAnno[k1=4]
@DupAnno[k2=5] // illegal duplicate name
table t {
```

```

    /* body omitted */
}

```

## Illegal Simultaneous Use of Both Structured and Unstructured Annotation

The following example is invalid because the annotation `name` is used by both an unstructured and structured annotation on the same element `table t`:

```

@MixAnno("Anything")
@MixAnno[k2=5] // illegal use in both annotation types
table t {
    /* body omitted */
}

```

## 20.2. Predefined annotations

Annotation names that start with lowercase letters are reserved for the standard library and architecture. This document pre-defines a set of "standard" annotations in [Appendix C](#). We expect that this list will grow. We encourage custom architectures to define annotations starting with a manufacturer prefix: e.g., an organization named X would use annotations named like `@X_annotation`

### 20.2.1. Optional parameter annotations

A parameter to a package, parser type, control type, extern method, extern function or extern object constructor can be annotated with `@optional` to indicate that the user does not need to provide a corresponding argument for that parameter. The meaning of a parameter with no supplied value is target-dependent.

### 20.2.2. Annotations on the table action list

The following two annotations can be used to give additional information to the compiler and control-plane about actions in a table. These annotations have no bodies.

- `@tableonly`: actions with this annotation can only appear within the table, and never as default action.
- `@defaultonly`: actions with this annotation can only appear in the default action, and never in the table.

```

table t {
    actions = {
        a,           // can appear anywhere
        @tableonly b, // can only appear in the table
        @defaultonly c, // can only appear in the default action
    }
    /* body omitted */
}

```

### 20.2.3. Control-plane API annotations

The `@name` annotation directs the compiler to use a different local name when generating the external APIs used to manipulate a language element from the control plane. This annotation takes a local compile-time known value of type `string` (typically a string literal). In the following example, the fully-qualified name of the table is `c_inst.t1`.

```

control c( /* parameters omitted */ )() {
    @name("t1") table t { /* body omitted */ }
}

```



```

    apply { /* body omitted */ }
}
c() c_inst;

```

The `@hidden` annotation hides a controllable entity, e.g. a table, key, action, or extern, from the control plane. This effectively removes its fully-qualified name ([Section 10.1.1](#)). This annotation does not have a body.

### 20.2.3.1. Restrictions

Each element may be annotated with at most one `@name` or `@hidden` annotation, and each control plane name must refer to at most one controllable entity. This is of special concern when using an absolute `@name` annotation: if a type containing a `@name` annotation with an absolute pathname (i.e., one starting with a dot) is instantiated more than once, it will result in the same name referring to two controllable entities.

```

control noargs();
package top(noargs c1, noargs c2);

control c() {
    @name(".foo.bar") table t { /* body omitted */ }
    apply { /* body omitted */ }
}
top(c(), c()) main;

```

Without the `@name` annotation, this program would produce two controllable entities with fully-qualified names `main.c1.t` and `main.c2.t`. However, the `@name(".foo.bar")` annotation renames table `t` in both instances to `foo.bar`, resulting in one name that refers to two controllable entities, which is illegal.

### 20.2.4. Concurrency control annotations

The `@atomic` annotation, described in [Section 7.4.5](#) can be used to enforce the atomic execution of a code block.

### 20.2.5. Branch prediction annotations

The `@likely` and `@unlikely` annotation can be used on blocks that are used in `if-else` or `switch` statements to hint when a branch is likely or unlikely to be taken.

```

if (error_failure) @unlikely {
    /* code that is unlikely to execute as the condition is probably false */
}

switch(value) {
    1: @likely {
        /* code for the most common case */
    }
    2: { /* ... */ }
    default: @unlikely {
        /* code for rare case */
    }
}

```

These annotations have no effect on the semantics of the program; they are just hints to help an optimizer. A warning may be issued if a `@likely` block is found to never execute or an `@unlikely` block will always execute, but is not required.

## 20.2.6. Value set annotations

The `@match` annotation, described in [Section 15.6](#), is used to specify a `match_kind` value other than the default `match_kind` of `exact` for a field of a `value_set`.

## 20.2.7. Extern function/method annotations

Various annotations may appear on extern function and method declarations to describe limitations on the behavior and interactions of those functions. By default extern functions might have any effect on the environment of the P4 program and might interact in non-trivial ways (subject to a few limitations—see [\[sec-calling-convention\]](#)). Since externs are architecture-specific and their behavior is known to the architecture definition, these annotations are not strictly necessary (an implementation can have knowledge of how externs interact based on their names built into it), but these annotations provide a uniform way of describing certain well-defined interactions (or their absence), allowing architecture-independent analysis of P4 programs.

- `@pure` - Describes a function that depends solely on its `in` parameter values, and has no effect other than returning a value, and copy-out behavior on its `out` and `inout` parameters. No hidden state is recorded between calls, and its value does not depend on any hidden state that may be changed by other calls. An example is a `hash` function that computes a deterministic hash of its arguments, and its return value does not depend upon any control-plane writable seed or initialization vector value. A `@pure` function whose results are unused may be safely eliminated with no adverse effects, and multiple calls with identical arguments may be combined into a single call (subject to the limits imposed by copy-out behavior of `out` and `inout` parameters). `@pure` functions may also be reordered with respect to other computations that are not data dependent.
- `@noSideEffects` - Weaker than `@pure` and describes a function that does not change any hidden state, but may depend on hidden state. One example is a `hash` function that computes a deterministic hash of its arguments, plus some internal state that can be modified via control plane API calls such as a seed or initialization vector. Another example is a read of one element of a register array extern object. Such a function may be dead code eliminated, and may be reordered or combined with other `@noSideEffects` or `@pure` calls (subject to the limits imposed by copy-out behavior of `out` and `inout` parameters), but not with other function calls that may have side effects that affect the function.

## 20.2.8. Deprecated annotation

The `deprecated` annotation has a required string argument that is a message that will be printed by a compiler when a program is using the deprecated construct. This is mostly useful for annotating library constructs, such as externs. The parameter must be a local compile-time known value of type `string`.

```
#define DEPR_V1_2_2 "Deprecated in v1.2.2"
@deprecated("Please use the 'check' function instead." ++ DEPR_V1_2_2)
extern Checker {
    /* body omitted */
}
```

## 20.2.9. No warnings annotation

The `noWarn` annotation has a required string argument that indicates a compiler warning that will be inhibited. For example `@noWarn("unused")` on a declaration will prevent a compiler warning if that declaration is not used. The parameter must be a local compile-time known value of type `string`.  
===  
Target-specific annotations

Each P4 compiler implementation can define additional annotations specific to the target of the compiler. The syntax of the annotations should conform to the above description. The semantics of such annotations is target-specific. They could be used in a similar way to pragmas in other languages.

The P4 compiler should provide:

- Errors when annotations are used incorrectly (e.g., an annotation expecting a parameter but used without arguments, or with arguments of the wrong type)
- Warnings for unknown annotations.

## Appendix A: Revision History

### A.1. Summary of changes made in unreleased version

- Clarified that numeric priorities cannot be assigned to entries of a table that has `const` entries ([[sec-entries](#)]).
- Clarified that `switch` statements are allowed in action and function bodies, and that `switch` statements with `action_run` expressions are only allowed in control `apply` blocks ([[sec-stmts](#)] and [[sec-switch-stmt](#)]).
- Added standard branch prediction annotations ([Section 20.2.5](#))
- Added support for compile-time string concatenation using `++` operator ([[sec-string-type](#)] and [[sec-string-ops](#)]).
- Added compound assignment statements ([[sec-assignment](#)])
- Update the specification grammar for `for` loops to match the grammar used in the `p4c` implementation ([[sec-loop-stmt](#)]).

### A.2. Summary of changes made in version 1.2.5, released October 11, 2024

- Improved type nesting rules ([[sec-type-nesting](#)]).
- Clarified that directionless extern parameters are passed by reference.
- Introduced distinction between local compile-time known and compile-time known values ([Section 7.5](#)).

### A.3. Summary of changes made in version 1.2.4, released May 15, 2023

- Added header stack expressions ([[sec-hs-init](#)]).
- Allow casts from a type to itself ([[sec-casts](#)]).
- Added an invalid header or header union expression `{#}` ([[sec-ops-on-hdrs](#)] and [[sec-expr-hu](#)]).
- Added a concept of numeric values ([[sec-numeric-values](#)]).
- Added a section on operations on extern objects ([[sec-extern-operations](#)]).
- Added note in sections operations on types for types that support compile-time size determination.
- Clarified that header stacks are arrays of headers or header unions.
- Added distinctness of fields for types that have fields including error, match kind, struct, header, and header union.
- Clarified types `bit<W>`, `int<W>`, and `varbit<W>` encompass the case where the width is a compile-time known expression evaluating to an appropriate integer ([[sec-unsigned-integers](#)], [[sec-signed-integers](#)], [[sec-dynamically-sized-integers](#)]).

- Clarified restrictions for parameters with default values ([sec-calling-convention]).
- Added optional trailing commas ([sec-trailing-commas]).
- Clarified the scope of parser namespaces ([sec-parser-decl]).
- Specified that algorithm for generating control-plane names for keys is optional ([sec-cp-keys]).
- Clarified types of expressions that may appear in `select` ([sec-select]).
- Added description of semantics of the core.p4 match kinds ([sec-table-keys]).
- Explicitly disallow overloading of parsers, controls, and packages ([sec-extern-objects]).
- Clarified implicit casts present in select expressions ([sec-select]).
- Clarified that slices can be applied to arbitrary-precision integers ([sec-varint-ops]).
- Clarified that direct invocation is not possible for objects that have constructor arguments ([sec-direct-invocation]).
- Added comparison for tuples as a legal operation ([sec-tuple-exprs]).
- Clarified the behavior of `lookahead` on header-typed values (Section 15.8.3).
- Added `static_assert` function ([sec-static-assert]).
- Clarified semantics of ranges where the start is bigger than the end ([sec-ranges]).
- Allow ranges to be specified by serializable enums ([sec-ranges]).
- Specified type produced by the `*sizeInB*` methods ([sec-minsizeinbits]).
- Added section with operations on `match_kind` values ([sec-match-kind-exprs]).
- Renamed infinite-precision integers to arbitrary-precision integers ([sec-arbitrary-precision-integers]).
- compiler-inserted `default_action` is not `const` ([sec-tables]).
- Clarified the restrictions on run time for tables with `const entries` ([sec-entries]).
- renamed list expressions to tuple expressions
- Added `list` type ([sec-list-types]).
- Defined `entries` table property without `const`, for entries installed when the P4 program is loaded, but the control plane can later change them or add to them ([sec-entries]).
- Clarified behavior of table with no `key` property, or if its list of keys is empty ([sec-table-keys]).

## A.4. Summary of changes made in version 1.2.3, released July 11, 2022.

- Extended `minSizeInBits` and `minSizeInBytes` to apply to more expressions ([sec-minsizeinbits]).
- Added support for `maxSizeInBits` and `maxSizeInBytes` ([sec-minsizeinbits]).
- Added support for empty lists of const entries in tables ([sec-entries]).
- Added support for `switch` statements in actions ([sec-actions]).
- Added support for direct invocation of controls and parsers ([sec-parameterization]).
- Added parser `value_set` to list of control-plane visible names ([sec-cp-names]).
- Added `match_kind` as a base type ([sec-match-kind-type]).
- Removed structure initializers as they are subsumed by structure-valued expressions ([sec-structure-expressions]).
- Specified operations on values typed as type variables ([sec-type-variable-operations]).

- Clarified semantics of compile-time known values ([Section 7.5](#)).
- Clarified semantics of directionless parameters ([\[sec-calling-convention\]](#)).
- Clarified semantics of arbitrary precision integers ([\[sec-arbitrary-precision-integers\]](#)).
- Clarified semantics of bit slices, shifts, and concatenation ([\[sec-bit-ops\]](#)).
- Clarified semantics of optional parameters ([\[sec-optional-parameters\]](#)).
- Clarified restrictions on extern method and function invocation ([\[sec-calling-restrictions\]](#)).
- Clarified semantics of implicit casts ([\[sec-implicit-casts\]](#)).

## A.5. Summary of changes made in version 1.2.2, released May 17, 2021

- Added support for accessing tuple fields ([\[sec-tuple-exprs\]](#)).
- Added support for generic structures ([\[sec-type-spec\]](#)).
- Added support for integers, `enums`, and `errors` in `switch` statements ([\[sec-switch-stmt\]](#)).
- Added support for additional enumeration types ([\[sec-enum-types\]](#)).
- Added support for abstract methods ([\[sec-abstract-methods\]](#)).
- Added support for conditional statements and empty statements in parsers ([\[sec-parser-state-stmt\]](#)).
- Added support for casts from `int` to `bool` ([\[sec-casts\]](#)).
- Added support for 0-width bitstrings and varbits ([\[sec-uninitialized-values-and-writing-invalid-headers\]](#)).
- Clarified that `default_action` is `NoAction` if otherwise unspecified ([\[sec-tables\]](#)).
- Clarified the types of expressions that may be used as indexes for header stacks ([\[sec-expr-hs\]](#)).
- Clarified representation of Booleans in headers ([\[sec-header-types\]](#)).
- Clarified representation of empty types ([\[sec-uninitialized-values-and-writing-invalid-headers\]](#)).
- Clarified that action data can be specified by the control plane, `default_action` table property, or `const entries` table property ([\[sec-actions\]](#)).
- Fixed several typos and inconsistencies in grammar ([Appendix E](#)).
- Eliminated annotations on `const` entries in grammar ([Appendix E](#)).

## A.6. Summary of changes made in version 1.2.1, released June 11, 2020

- Added structure-value expressions ([\[sec-structure-expressions\]](#)).
- Added support for default values ([\[sec-default-values\]](#)).
- Added support for concatenating signed strings ([\[sec-concatenation\]](#)).
- Added key-value and list-structured annotations ([\[sec-annotations\]](#)).
- Added `@pure` and `@noSideEffects` annotations ([Section 20.2.7](#)).
- Added `@noWarn` annotation ([Section 20.2.9](#)).
- Generalized typing for masks to allow serializable `enums` ([\[sec-cubes\]](#)).
- Restricted the right operands of bit shifts involving arbitrary-precision integers to be constant and positive ([\[sec-varint-ops\]](#)).

- Clarified copy-out behavior for `return` ([sec-return-stmt]) and `exit` ([sec-exit-stmt]) statements.
- Clarified semantics of invalid header stacks ([sec-uninitialized-values-and-writing-invalid-headers]).
- Clarified initialization semantics ([sec-lvalues] and [sec-calling-convention]), especially for headers and local variables.
- Clarified evaluation order for table keys ([sec-mau-semantics]).
- Fixed grammar to clarify parsing of right shift operator (`>>`), allow empty statements in parser ([sec-parser-state-stmt]), and eliminate annotations on const entries ([sec-entries]).

## A.7. Summary of changes made in version 1.2.0, released October 14, 2019

- Added `table.apply().miss` ([sec-invoke-mau]).
- Added `string` type ([sec-string-type]).
- Added implicit casts from enum values ([sec-enum-exprs]).
- Allow 1-bit signed values
- Define the type of bit slices from signed and unsigned values to be unsigned.
- Constrain `default` label position for `switch` statements.
- Allow empty tuples.
- Added `@deprecated` annotation.
- Relaxed the structure of annotation bodies.
- Removed the `@pkginfo` annotation, which is now defined by the P4Runtime specification.
- Added `int` type ([sec-arbitrary-precision-integers]).
- Added error `ParserInvalidArgument` ([sec-packet-extract-two], Section 15.8.4).
- Clarified the significance of order of entries in `const` entries ([sec-entries]).
- Added methods to calculate header size ([sec-ops-on-hdrs]).

## A.8. Summary of changes made in version 1.1.0, released November 26, 2017.

- Top-level functions ([sec-functions])
  - Functions may be declared at the top-level of a P4 program.
- Optional and named parameters ([sec-calling-convention])
  - Parameters may be specified by name, with a default value, or designated as optional.
- `enum` representations ([sec-enum-exprs])
  - `enum` values to be specified with a concrete representation.
- Parser values sets ([sec-value-set])
  - `value_set` objects for control-plane programmable `select` labels.
- Type definitions (Section 8.5.8)
  - New types may be introduced in programs.
- Saturating arithmetic ([sec-bit-ops])

- Saturating arithmetic is supported on some targets.
- Structured annotations ([[sec-annotations](#)])
  - Annotations may be specified as lists of key-value pairs
- Globalname ([[sec-name-annotations](#)])
  - The reserved `globalname` annotation has been removed.
- Table `size` property ([[sec-size-table-property](#)])
  - Meaning of optional `size` property for tables has been defined.
- Invalid headers ([[sec-ops-on-hdrs](#)])
  - Clarified semantics of operations on invalid headers.
- Calling restrictions ([[sec-calling-restrictions](#)])
  - Added restrictions on kinds of values that may be passed as arguments to calls.
- Bitwise operator precedence ([Appendix E](#))
  - Modified precedence conventions so that bitwise operators `&` `|` and `^` have higher precedence than relation operators `<` `>` `<=` `>=`.
- Computed bitwidths ([[sec-base-types](#)])
  - Added support for specifying widths using expressions in `bit` and `varbit` types.

## A.9. Initial version 1.0.0, released May 17, 2017

# Appendix B: P4 reserved keywords

The following table shows all P4 reserved keywords. Some identifiers are treated as keywords only in specific contexts (e.g., the keyword `actions`).

|                       |                         |                        |                           |
|-----------------------|-------------------------|------------------------|---------------------------|
| <code>abstract</code> | <code>action</code>     | <code>apply</code>     | <code>bit</code>          |
| <code>bool</code>     | <code>const</code>      | <code>control</code>   | <code>default</code>      |
| <code>else</code>     | <code>enum</code>       | <code>error</code>     | <code>extern</code>       |
| <code>exit</code>     | <code>false</code>      | <code>header</code>    | <code>header_union</code> |
| <code>if</code>       | <code>in</code>         | <code>inout</code>     | <code>int</code>          |
| <code>list</code>     | <code>match_kind</code> | <code>package</code>   | <code>parser</code>       |
| <code>out</code>      | <code>return</code>     | <code>select</code>    | <code>state</code>        |
| <code>string</code>   | <code>struct</code>     | <code>switch</code>    | <code>table</code>        |
| <code>this</code>     | <code>transition</code> | <code>true</code>      | <code>tuple</code>        |
| <code>type</code>     | <code>typedef</code>    | <code>value_set</code> | <code>varbit</code>       |
| <code>verify</code>   | <code>void</code>       |                        |                           |

# Appendix C: P4 reserved annotations

The following table shows all P4 reserved annotations.



| Annotation                 | Purpose                                                                | See Section                               |
|----------------------------|------------------------------------------------------------------------|-------------------------------------------|
| <code>atomic</code>        | specify atomic execution                                               | <a href="#">[sec-concurrency]</a>         |
| <code>defaultonly</code>   | action can only appear in the default action                           | <a href="#">[sec-annotations]</a>         |
| <code>hidden</code>        | hides a controllable entity from the control plane                     | <a href="#">[sec-name-annotations]</a>    |
| <code>match</code>         | specify <code>match_kind</code> of a field in a <code>value_set</code> | <a href="#">[sec-value-set]</a>           |
| <code>name</code>          | assign local control-plane name                                        | <a href="#">[sec-name-annotations]</a>    |
| <code>optional</code>      | parameter is optional                                                  | <a href="#">[sec-optional-parameters]</a> |
| <code>tableonly</code>     | action cannot be a default_action                                      | <a href="#">[sec-annotations]</a>         |
| <code>deprecated</code>    | Construct has been deprecated                                          | <a href="#">Section 20.2.8</a>            |
| <code>pure</code>          | pure function                                                          | <a href="#">Section 20.2.7</a>            |
| <code>noSideEffects</code> | function with no side effects                                          | <a href="#">Section 20.2.7</a>            |
| <code>noWarn</code>        | Has a string argument; inhibits compiler warnings                      | <a href="#">Section 20.2.9</a>            |

## Appendix D: P4 core library

The P4 core library contains declarations that are useful to most programs.

For example, the core library includes the declarations of the predefined `packet_in` and `packet_out` extern objects, used in parsers and deparsers to access packet data.

```

/// Standard error codes. New error codes can be declared by users.
error {
    NoError,           /// No error.
    PacketTooShort,    /// Not enough bits in packet for 'extract'.
    NoMatch,           /// 'select' expression has no matches.
    StackOutOfBounds,  /// Reference to invalid element of a header stack.
    HeaderTooShort,    /// Extracting too many bits into a varbit field.
    ParserTimeout,     /// Parser execution time limit exceeded.
    ParserInvalidArgument /// Parser operation was called with a value
                        /// not supported by the implementation.
}

extern packet_in {
    /// Read a header from the packet into a fixed-sized header @hdr
    /// and advance the cursor.
    /// May trigger error PacketTooShort or StackOutOfBounds.
    /// @T must be a fixed-size header type
    void extract<T>(out T hdr);
    /// Read bits from the packet into a variable-sized header @variableSizeHeader
    /// and advance the cursor.
    /// @T must be a header containing exactly 1 varbit field.
    /// May trigger errors PacketTooShort, StackOutOfBounds, or HeaderTooShort.
    void extract<T>(out T variableSizeHeader,
                    in bit<32> variableFieldSizeInBits);
    /// Read bits from the packet without advancing the cursor.
    /// @returns: the bits read from the packet.
    /// T may be an arbitrary fixed-size type.
    T lookahead<T>();
    /// Advance the packet cursor by the specified number of bits.
    void advance(in bit<32> sizeInBits);
    /// @return packet length in bytes. This method may be unavailable on
    /// some target architectures.
    bit<32> length();

```



```

}
extern packet_out {
    /// Write @data into the output packet, skipping invalid headers
    /// and advancing the cursor
    /// @T can be a header type, a header stack, a header_union, or a struct
    /// containing fields with such types.
    void emit<T>(in T data);
}
action NoAction() {}
/// Standard match kinds for table key fields.
/// Some architectures may not support all these match kinds.
/// Architectures can declare additional match kinds.
match_kind {
    /// Match bits exactly.
    exact,
    /// Ternary match, using a mask.
    ternary,
    /// Longest-prefix match.
    lpm
}

/// Static assert evaluates a boolean expression
/// at compilation time. If the expression evaluates to
/// false, compilation is stopped and the corresponding message is printed.
/// The function returns a boolean, so that it can be used
/// as a global constant value in a program, e.g.:
/// const version = static_assert(V1MODEL_VERSION > 20180000, "Expected a v1 model
version >= 20180000");
extern bool static_assert(bool check, string message);

/// Like the above but using a default message.
extern bool static_assert(bool check);

```

## Appendix E: P4 grammar

This is the grammar of P4<sub>16</sub> written using the YACC/bison language. Absent from this grammar is the precedence of various operations.

The grammar is actually ambiguous, so the lexer and the parser must collaborate for parsing the language. In particular, the lexer must be able to distinguish two kinds of identifiers:

- Type names previously introduced (**TYPE\_IDENTIFIER** tokens)
- Regular identifiers (**IDENTIFIER** token)

The parser has to use a symbol table to indicate to the lexer how to parse subsequent appearances of identifiers. For example, given the following program fragment:

```

typedef bit<4> t;
struct s { /* body omitted */}
t x;
parser p(bit<8> b) { /* body omitted */ }

```

The lexer has to return the following terminal kinds:

```

t - TYPE_IDENTIFIER
s - TYPE_IDENTIFIER
x - IDENTIFIER
p - TYPE_IDENTIFIER
b - IDENTIFIER

```

This grammar has been heavily influenced by limitations of the Bison parser generator tool.

The **STRING\_LITERAL** token corresponds to a string literal enclosed within double quotes, as described in [Section 6.2.2.3](#).

All other terminals are uppercase spellings of the corresponding keywords. For example, **RETURN** is the terminal returned by the lexer when parsing the keyword return.

```
trailingCommaOpt
: /* empty */
| ,
;

booleanLiteral
: TRUE
| FALSE
;

integerLiteral
: D int
| nat W int
| nat S int
;

stringLiteral
: " text "
;

identifier
: `ID text
;

typeIdentifier
: `TID text
;

nonTypeName
: identifier
| APPLY
| KEY
| ACTIONS
| STATE
| ENTRIES
| TYPE
| PRIORITY
;

prefixedNonTypeName
: nonTypeName
| `ID . nonTypeName
;

typeName = typeIdentifier

prefixedTypeName
: typeName
| `TID . typeName
;

tableCustomName
: identifier
| typeIdentifier
| APPLY
| STATE
| TYPE
| PRIORITY
;
```

```

name
: nonTypeName
| typeName
| LIST
;

nameList
: name
| nameList , name
;

member = name

direction
: /* empty */
| IN
| OUT
| INOUT
;

baseType
: BOOL
| ERROR
| MATCH_KIND
| STRING
| INT
| INT `< int >
| INT `< `( expression ) >
| BIT
| BIT `< int >
| BIT `< `( expression ) >
| VARBIT `< int >
| VARBIT `< `( expression ) >
;

specializedType
: prefixedTypeName `< typeArgumentList >
;

namedType
: prefixedTypeName
| specializedType
;

headerStackType
: namedType `[ expression ]
;

listType
: LIST `< typeArgument >
;

tupleType
: TUPLE `< typeArgumentList >
;

type
: baseType
| namedType
| headerStackType
| listType
| tupleType
;

typeOrVoid
: type
| VOID
| identifier

```

```

;

typeParameter = name

typeParameterList
: typeParameter
| typeParameterList , typeParameter
;

typeParameterListOpt
: /* empty */
| `< typeParameterList >
;

parameter
: annotationList direction type name initializerOpt
;

nonEmptyParameterList
: parameter
| nonEmptyParameterList , parameter
;

parameterList
: /* empty */
| nonEmptyParameterList
;

constructorParameter = parameter

constructorParameterList = parameterList

constructorParameterListOpt
: /* empty */
| `( parameterList )
;

namedExpression
: name = expression
;

namedExpressionList
: namedExpression
| namedExpressionList , namedExpression
;

literalExpression
: booleanLiteral
| integerLiteral
| stringLiteral
;

referenceExpression
: prefixedNonTypeName
| THIS
;

defaultExpression
: ...
;

unop
: !
| ~
| -
| +
;

unaryExpression

```

```

: unop expression
;

binop
: *
| /
| %
| +
| -
| ++
| --
| <<
| >>
| <=
| >=
| <
| >
| !=
| ==
| &
| ^
| |
| ++
| &&
| ||
;

binaryExpression
: expression binop expression
;

binaryExpressionNonBrace
: expressionNonBrace binop expression
;

ternaryExpression
: expression ? expression : expression
;

ternaryExpressionNonBrace
: expressionNonBrace ? expression : expression
;

castExpression
: `( type ) expression
;

dataExpression
: invalidHeaderExpression
| sequenceOrRecordExpression
;

errorAccessExpression
: ERROR . member
;

memberAccessExpression
: memberAccessBase . member
;

indexAccessExpression
: expression `[ expression ]
;

sliceAccessExpression
: expression `[ expression : expression ]
;

accessExpression

```

```

: errorAccessExpression
| memberAccessExpression
| indexAccessExpression
| sliceAccessExpression
;

memberAccessExpressionNonBrace
: memberAccessBaseNonBrace . member
;

indexAccessExpressionNonBrace
: expressionNonBrace `[ expression ]
;

sliceAccessExpressionNonBrace
: expressionNonBrace `[ expression : expression ]
;

accessExpressionNonBrace
: errorAccessExpression
| memberAccessExpressionNonBrace
| indexAccessExpressionNonBrace
| sliceAccessExpressionNonBrace
;

callExpression
: callTarget `( argumentList )
| callableTarget `< realTypeArgumentList > `( argumentList )
;

callExpressionNonBrace
: callTargetNonBrace `( argumentList )
| callableTargetNonBrace `< realTypeArgumentList > `( argumentList )
;

parenthesizedExpression
: `( expression )
;

expression
: literalExpression
| referenceExpression
| defaultExpression
| unaryExpression
| binaryExpression
| ternaryExpression
| castExpression
| dataExpression
| accessExpression
| callExpression
| parenthesizedExpression
;

expressionList
: /* empty */
| expression
| expressionList , expression
;

memberAccessBase
: prefixedTypeName
| expression
;

sequenceElementExpression = expressionList

recordElementExpression
: name = expression
| name = expression , ...

```

```

| name = expression , namedExpressionList
| name = expression , namedExpressionList , ...
;

sequenceOrRecordElementExpression
: sequenceElementExpression
| recordElementExpression
;

callableTarget = expression

constructorTarget = namedType

callTarget
: callableTarget
| constructorTarget
;

expressionNonBrace
: literalExpression
| referenceExpression
| unaryExpression
| binaryExpressionNonBrace
| ternaryExpressionNonBrace
| castExpression
| accessExpressionNonBrace
| callExpressionNonBrace
| parenthesizedExpression
;

memberAccessBaseNonBrace
: prefixedTypeName
| expressionNonBrace
;

callableTargetNonBrace = expressionNonBrace

callTargetNonBrace
: callableTargetNonBrace
| constructorTarget
;

simpleKeysetExpression
: expression
| expression &&& expression
| expression .. expression
| DEFAULT
| _
;

simpleKeysetExpressionList
: simpleKeysetExpression
| simpleKeysetExpressionList , simpleKeysetExpression
;

tupleKeysetExpression
: `( expression &&& expression )
| `( expression .. expression )
| `( DEFAULT )
| `( _ )
| `( simpleKeysetExpression , simpleKeysetExpressionList )
;

keysetExpression
: simpleKeysetExpression
| tupleKeysetExpression
;

realTypeArgument

```

```

: type
| VOID
| _
;

realTypeArgumentList
: realTypeArgument
| realTypeArgumentList , realTypeArgument
;

typeArgument
: realTypeArgument
| nonTypeName
;

typeArgumentList
: /* empty */
| typeArgument
| typeArgumentList , typeArgument
;

argument
: expression
| name = expression
| name = _
| _
;

argumentListNonEmpty
: argument
| argumentListNonEmpty , argument
;

argumentList
: /* empty */
| argumentListNonEmpty
;

lvalue
: referenceExpression
| lvalue . member
| lvalue `[ expression ]
| lvalue `[ expression : expression ]
| `( lvalue )
;

emptyStatement
: ;
;

assignmentStatement
: lvalue assignop expression ;
;

callStatement
: lvalue `( argumentList ) ;
| lvalue `< typeArgumentList > `( argumentList ) ;
;

directApplicationStatement
: namedType . APPLY `( argumentList ) ;
;

returnStatement
: RETURN ;
| RETURN expression ;
;

exitStatement

```



```

: EXIT ;
;

blockStatement
: annotationList `{ blockElementStatementList }
;

conditionalStatement
: IF `( expression ) statement
| IF `( expression ) statement ELSE statement
;

forUpdateStatement
: lvalue `( argumentList )
| lvalue `< typeArgumentList > `( argumentList )
| lvalue assignop expression
;

forUpdateStatementListNonEmpty
: forUpdateStatement
| forUpdateStatementListNonEmpty , forUpdateStatement
;

forUpdateStatementList
: /* empty */
| forUpdateStatementListNonEmpty
;

forInitStatement
: annotationList type name initializerOpt
| forUpdateStatement
;

forInitStatementListNonEmpty
: forInitStatement
| forInitStatementListNonEmpty , forInitStatement
;

forInitStatementList
: /* empty */
| forInitStatementListNonEmpty
;

forCollectionExpression
: expression
| expression .. expression
;

forStatement
: annotationList FOR
  `( forInitStatementList ; expression ; forUpdateStatementList ) statement
| annotationList FOR `( type name IN forCollectionExpression ) statement
| annotationList FOR
  `( annotationListNonEmpty type name IN forCollectionExpression )
  statement
;

switchLabel
: DEFAULT
| expressionNonBrace
;

switchCase
: switchLabel : blockStatement
| switchLabel :
;

switchCaseList
: /* empty */

```

```

    | switchCaseList switchCase
    ;

switchStatement
: SWITCH `( expression ) `{ switchCaseList }
;

breakStatement
: BREAK ;
;

continueStatement
: CONTINUE ;
;

statement
: emptyStatement
| assignmentStatement
| callStatement
| directApplicationStatement
| returnStatement
| exitStatement
| blockStatement
| conditionalStatement
| forStatement
| breakStatement
| continueStatement
| switchStatement
;

initializer
: = expression
;

constantDeclaration
: annotationList CONST type name initializer ;
;

initializerOpt
: /* empty */
| initializer
;

variableDeclaration
: annotationList type name initializerOpt ;
;

blockElementStatement
: constantDeclaration
| variableDeclaration
| statement
;

blockElementStatementList
: /* empty */
| blockElementStatementList blockElementStatement
;

functionPrototype
: typeOrVoid name typeParameterListOpt `( parameterList )
;

functionDeclaration
: annotationList functionPrototype blockStatement
;

actionDeclaration
: annotationList ACTION name `( parameterList ) blockStatement
;

```

```

objectInitializer
: = `{ objectDeclarationList }
;

instantiation
: annotationList type `( argumentList ) name ;
| annotationList type `( argumentList ) name objectInitializer ;
;

objectDeclaration
: functionDeclaration
| instantiation
;

objectDeclarationList
: /* empty */
| objectDeclarationList objectDeclaration
;

errorDeclaration
: ERROR `{ nameList }
;

matchKindDeclaration
: MATCH_KIND `{ nameList trailingCommaOpt }
;

enumTypeDeclaration
: annotationList ENUM name `{ nameList trailingCommaOpt }
| annotationList ENUM type name `{ namedExpressionList trailingCommaOpt }
;

typeField
: annotationList type name ;
;

typeFieldList
: /* empty */
| typeFieldList typeField
;

structTypeDeclaration
: annotationList STRUCT name typeParameterListOpt `{ typeFieldList }
;

headerTypeDeclaration
: annotationList HEADER name typeParameterListOpt `{ typeFieldList }
;

headerUnionTypeDeclaration
: annotationList HEADER_UNION name typeParameterListOpt `{ typeFieldList }
;

derivedTypeDeclaration
: enumTypeDeclaration
| structTypeDeclaration
| headerTypeDeclaration
| headerUnionTypeDeclaration
;

typedef
: type
| derivedTypeDeclaration
;

typedefDeclaration
: annotationList TYPEDEF typedef name ;
| annotationList TYPE type name ;

```

```

;

externFunctionDeclaration
: annotationList EXTERN functionPrototype ;
;

externConstructorPrototype
: annotationList typeIdIdentifier `( parameterList ) ;
;

externMethodPrototype
: annotationList functionPrototype ;
| annotationList ABSTRACT functionPrototype ;
;

externConstructorOrMethodPrototype
: externConstructorPrototype
| externMethodPrototype
;

externConstructorOrMethodPrototypeList
: /* empty */
| externConstructorOrMethodPrototypeList externConstructorOrMethodPrototype
;

externObjectDeclaration
: annotationList EXTERN nonTypeName typeParameterListOpt
  `{ externConstructorOrMethodPrototypeList }
;

externDeclaration
: externFunctionDeclaration
| externObjectDeclaration
;

selectCase
: keysetExpression : name ;
;

selectCaseList
: /* empty */
| selectCaseList selectCase
;

selectExpression
: SELECT `( expressionList ) `{ selectCaseList }
;

stateExpression
: name ;
| selectExpression
;

transitionStatement
: /* empty */
| TRANSITION stateExpression
;

valueSetType
: baseType
| tupleType
| prefixedTypeName
;

valueSetDeclaration
: annotationList VALUE_SET `< valueSetType > `( expression ) name ;
;

parserTypeDeclaration

```

```

: annotationList PARSE name typeParameterListOpt `( parameterList ) ;
;

parserBlockStatement
: annotationList `{ parserStatementList }
;

parserConditionalStatement
: IF `( expression ) parserStatement
| IF `( expression ) parserStatement ELSE parserStatement
;

parserStatement
: constantDeclaration
| variableDeclaration
| emptyStatement
| assignmentStatement
| callStatement
| directApplicationStatement
| parserBlockStatement
| parserConditionalStatement
;

parserStatementList
: /* empty */
| parserStatementList parserStatement
;

parserState
: annotationList STATE name `{ parserStatementList transitionStatement }
;

parserStateList
: parserState
| parserStateList parserState
;

parserLocalDeclaration
: constantDeclaration
| instantiation
| variableDeclaration
| valueSetDeclaration
;

parserLocalDeclarationList
: /* empty */
| parserLocalDeclarationList parserLocalDeclaration
;

parserDeclaration
: annotationList PARSE name typeParameterListOpt `( parameterList )
  constructorParameterListOpt
  `{ parserLocalDeclarationList parserStateList }
;

const
: CONST
;

constOpt
: /* empty */
| const
;

tableKey
: expression : name annotationList ;
;

tableKeyList

```

```

: /* empty */
| tableKeyList tableKey
;

tableActionReference
: prefixedNonTypeName
| prefixedNonTypeName `( argumentList )
;

tableAction
: annotationList tableActionReference ;
;

tableActionList
: /* empty */
| tableActionList tableAction
;

tableEntryPriority
: PRIORITY = integerLiteral :
| PRIORITY = `( expression ) :
;

tableEntry
: constOpt tableEntryPriority keysetExpression : tableActionReference
annotationList ;
| constOpt keysetExpression : tableActionReference annotationList ;
;

tableEntryList
: /* empty */
| tableEntryList tableEntry
;

tableProperty
: KEY = `{ tableKeyList }
| ACTIONS = `{ tableActionList }
| annotationList constOpt ENTRIES = `{ tableEntryList }
| annotationList constOpt tableCustomName initializer ;
;

tablePropertyList
: /* empty */
| tablePropertyList tableProperty
;

tableDeclaration
: annotationList TABLE name `{ tablePropertyList }
;

controlTypeDeclaration
: annotationList CONTROL name typeParameterListOpt `( parameterList ) ;
;

controlBody = blockStatement

controlLocalDeclaration
: constantDeclaration
| instantiation
| variableDeclaration
| actionDeclaration
| tableDeclaration
;

controlLocalDeclarationList
: /* empty */
| controlLocalDeclarationList controlLocalDeclaration
;

```

```

controlDeclaration
: annotationList CONTROL name typeParameterListOpt `( parameterList )
  constructorParameterListOpt
  `{ controlLocalDeclarationList APPLY controlBody }
;

packageTypeDeclaration
: annotationList PACKAGE name typeParameterListOpt `( parameterList ) ;
;

typeDeclaration
: derivedTypeDeclaration
| typedefDeclaration
| parserTypeDeclaration
| controlTypeDeclaration
| packageTypeDeclaration
;

declaration
: constantDeclaration
| instantiation
| functionDeclaration
| actionDeclaration
| errorDeclaration
| matchKindDeclaration
| externDeclaration
| parserDeclaration
| controlDeclaration
| typeDeclaration
;

annotationToken
: UNEXPECTED_TOKEN
| ABSTRACT
| ACTION
| ACTIONS
| APPLY
| BOOL
| BIT
| BREAK
| CONST
| CONTINUE
| CONTROL
| DEFAULT
| ELSE
| ENTRIES
| ENUM
| ERROR
| EXIT
| EXTERN
| FALSE
| FOR
| HEADER
| HEADER_UNION
| IF
| IN
| INOUT
| INT
| KEY
| MATCH_KIND
| TYPE
| OUT
| PARSER
| PACKAGE
| PRAGMA
| RETURN
| SELECT
| STATE
| STRING

```

```

| STRUCT
| SWITCH
| TABLE
| THIS
| TRANSITION
| TRUE
| TUPLE
| TYPEDEF
| VARBIT
| VALUE_SET
| LIST
| VOID
| -
| identifier
| typeIdentifier
| stringLiteral
| integerLiteral
| &&&
| ..
| <<
| &&
| ||
| ==
| !=
| >=
| <=
| ++
| +
| |+|
| -
| |-|
| *
| /
| %
| |
| &
| ^
| ~
| [
| ]
| {
| }
| <
| >
| !
| :
| ,
| ?
| .
| =
| ;
| @
;

```

```

annotationBody
: /* empty */
| annotationBody `( annotationBody )
| annotationBody annotationToken
;

```

```

structuredAnnotationBody
: sequenceOrRecordElementExpression trailingCommaOpt
;

```

```

annotation
: @ name
| @ name `( annotationBody )
| @ name `[ structuredAnnotationBody ]
| @ PRAGMA name annotationBody

```



```
;
annotationListNonEmpty
: annotation
| annotationListNonEmpty annotation
;

annotationList
: /* empty */
| annotationListNonEmpty
;

p4program
: /* empty */
| p4program declaration
| p4program ;
;
```