

Code Transformation for Distributed Python ML Code

1 Python Abstract Syntax

<i>module</i>	::=	<i>stmt</i> * <i>type_ignore</i>	(MODULEDEF)
<i>stmt</i>	::=	(@ <i>expr</i>)* def <i>id</i> (<i>args</i>) (-> <i>expr</i>)? : (# type:s)? <i>stmt</i> *	(FUNDEF)
		(@ <i>expr</i>)* async def <i>id</i> (<i>args</i>) (-> <i>expr</i>)? : (# type:s)? <i>stmt</i> *	(ASYNCFUNDEF)
		(@ <i>expr</i>)* class <i>id</i> (<i>expr</i> * <i>keyword</i> *) : <i>stmt</i> *	(CLASSDEF)
		return <i>expr</i> ?	(RETURN)
		delete <i>expr</i> *	(DELETE)
		<i>expr</i> * = <i>expr</i> (# type:s)?	(ASSIGN)
		<i>expr</i> <i>binop</i> = <i>expr</i>	(AUGASSIGN)
		<i>expr</i> : <i>expr</i> (= <i>expr</i>)?	(ANNASSIGN)
		(# type:s)? for <i>expr</i> in <i>expr</i> : <i>stmt</i> * (else : <i>stmt</i>)?	(FORLOOP)
		(# type:s)? async for <i>expr</i> in <i>expr</i> : <i>stmt</i> * (else : <i>stmt</i>)?	(ASYNCFORLOOP)
		while (<i>expr</i>) : <i>stmt</i> * (else : <i>stmt</i>)?	(WHILELOOP)
		if (<i>expr</i>) : <i>stmt</i> * (else : <i>stmt</i>)?	(IF)
		(# type:s)? with <i>with_item</i> * : <i>stmt</i> *	(WITH)
		(# type:s)? async with <i>with_item</i> * : <i>stmt</i> *	(ASYNCWITH)
		match <i>expr</i> : <i>match_case</i> *	(MATCH)
		raise <i>expr</i> ? (from <i>expr</i>)?	(RAISE)
		try : <i>stmt</i> * <i>exc_handler</i> * (else : <i>stmt</i>)? (finally : <i>stmt</i>)?	(TRY)
		assert <i>expr</i> <i>expr</i> ?	(ASSERT)
		import <i>alias</i> *	(IMPORT)
		from <i>i id</i> ? import <i>alias</i> *	(IMPORTFROM)
		global <i>id</i> *	(GLOBAL)
		nonlocal <i>id</i> *	(NONLOCAL)
		<i>expr</i>	(EXPRSTMT)
		pass	(PASS)
		break	(BREAK)
		continue	(CONTINUE)

<i>expr</i>	<code>::=</code>	<code>expr boolop expr</code>	(BOOLOP)
		<code>expr := expr</code>	(NAMEDEXPR)
		<code>expr binop expr</code>	(BINARYOP)
		<code>unop expr</code>	(UNARYOP)
		<code>lambda args : expr</code>	(LAMBDA)
		<code>expr if expr else expr</code>	(IFEXPR)
		<code>{(expr : expr)* (**expr)*}</code>	(DICTIONARY)
		<code>{expr*}</code>	(SET)
		<code>[expr*]</code>	(LIST)
		<code>(expr*)</code>	(TUPLE)
		<code>{expr:expr comprehension*}</code>	(DICTIONARYCOMP)
		<code>{expr comprehension*}</code>	(SETCOMP)
		<code>[expr comprehension*]</code>	(LISTCOMP)
		<code>(expr comprehension*)</code>	(GENERATORCOMP)
		<code>await expr</code>	(AWAIT)
		<code>yield expr?</code>	(YIELD)
		<code>yield from expr</code>	(YIELDFROM)
		<code>expr (compop expr)*</code>	(COMPOP)
		<code>expr (expr* keyword*)</code>	(CALL)
		<code>{expr (!i)? (:expr)?}</code>	(FORMATTEDVALUE)
		<code>expr*</code>	(JOINEDSTR)
		<code>constant</code>	(CONSTANT)
		<code>expr.id</code>	(ATTRIBUTE)
		<code>expr[expr]</code>	(SUBSCRIPT)
		<code>*expr</code>	(STARRED)
		<code>**expr</code>	(DOUBLESTARRED)
		<code>id</code>	(NAME)
		<code>expr? (:expr)? (:expr)?</code>	(SLICE)
<i>boolop</i>	<code>::=</code>	<code>and or</code>	(BOOLOPERATOR)
<i>binop</i>	<code>::=</code>	<code>+ - * @ / ** << >> ^ & // %</code>	(BINOPERATOR)
<i>unop</i>	<code>::=</code>	<code>~ not + -</code>	(UNOPERATOR)
<i>compop</i>	<code>::=</code>	<code>== != < <= > >= is is not in not in</code>	(COMPOP)
<i>comprehension</i>	<code>::=</code>	<code>for expr in expr (if expr)*</code>	(COMPREHENSION)
		<code>async for expr in expr (if expr)*</code>	(ASYNCCOMPREHEN)
<i>exc.handler</i>	<code>::=</code>	<code>except expr? (as id)? : stmt*</code>	(EXCHANDLER)
<i>args</i>	<code>::=</code>	<code>(arg (= expr)?)*, (arg (= expr)?)*, arg?, (arg (= expr)?)*, arg?</code>	(ARGUMENTS)
<i>arg</i>	<code>::=</code>	<code>id expr? s?</code>	(ARGUMENT)
<i>keyword</i>	<code>::=</code>	<code>id? = expr</code>	(KEYWORD)
<i>alias</i>	<code>::=</code>	<code>id (.id)* (as id)?</code>	(ALIAS)
<i>with.item</i>	<code>::=</code>	<code>expr (as expr)?</code>	(WITHITEM)

<i>match_case</i>	<code>::= case pattern (if expr)? : stmt*</code>	(MATCHCASE)
<i>pattern</i>	<code>::= expr</code>	(MATCHVALUE)
	<i>constant</i>	(MATCHSINGLETON)
	[<i>pattern</i> *	(MATCHSEQUENCE)
	<i>*(id)?</i>	(MATCHSTAR)
	{(<i>expr</i> : <i>pattern</i>)* <i>id</i> ?}	(MATCHMAPPING)
	<i>expr</i> (<i>pattern</i> * (<i>id</i> = <i>pattern</i>)*)	(MATCHCLASS)
	(<i>pattern</i> as)? <i>id</i>	(MATCHAS)
	<i>pattern</i> <i>pattern</i>	(MATCHOR)
	-	(MATCHWILDCARD)
<i>constant</i>	<code>::= None</code>	(NONELITERAL)
	<i>i</i>	(INTLITERAL)
	<i>f</i>	(FLOATLITERAL)
	<i>c</i>	(COMPLEXLITERAL)
	<i>s</i>	(STRINGLITERAL)
	<i>b</i>	(BOOLEANLITERAL)
	(<i>constant</i> *)	(TUPLELITERAL)
	...	(ELLIPSIS)
<i>type_ignore</i>	<code>::= i*</code>	(TYPEIGNORE)
<i>id</i>	$\in Id$	
<i>s</i>	$\in Str$	
<i>b</i>	$\in \{\text{True}, \text{False}\}$	
<i>i</i>	$\in \mathbb{Z}$	
<i>f</i>	$\in \mathbb{R}$	
<i>c</i>	$\in \mathbb{C}$	

Note: there may be more constant terms such as an immutable container containing only constant elements. Please update the *constant* rule if you know such terms.

2 Transformation Rule for TensorFlow ML Training Code

2.1 Restrictions

1. All import statements must be placed at the top of a module.
2. The `tensorflow` module must be assigned to a variable only using an import statement.
3. Members of the `tensorflow` module must not be aliased.
4. `print` function call expressions must not introduce side-effects.
5. A dataset and an optimizer object must only be created once via an assignment statement with a function call expression and must not be aliased.
6. Variables storing a dataset or a optimizer object must not be reassigned to store another value that is not a dataset or an optimizer object.
7. A dataset and an optimizer object must not be created conditionally.
8. `optimizer.apply_gradients` function call expressions must be expression statements or a direct RHS of an assignment statement.
9. Global variables storing an `optimizer` object and referred in functions must be defined before the functions' definitions and must not be changed after their initializations.
10. A checkpoint object must only be created once via an assignment statement with a function call expression and must not be aliased.

2.2 Rules

2.2.1 Types and Auxiliary Functions

$\tau ::=$	<i>Module</i>	(MODULES)
	<i>Stmt</i>	(STATEMENTS)
	<i>Expr</i>	(EXPRESSIONS)
	<i>Comprehension</i>	(COMPREHENSIONS)
	<i>ExcHandler</i>	(EXCEPTION HANDLERS)
	<i>Alias</i>	(ALIASES)
	<i>WithItem</i>	(WITHITEMS)
	<i>Pattern</i>	(PATTERNS)
	<i>Id</i>	(IDENTIFIERS)
	<i>Str</i>	(STRINGS)
	τ list	(LIST OF ELEMENTS TYPED τ)

$\sigma \in \Sigma = Str \xrightarrow{\text{fin}} Id$ ENVIRONMENT STORING MAPPINGS FROM STRINGS TO IDENTIFIERS

.1	:	$\tau \times \tau \rightarrow \tau$	GET THE FIRST ELEMENT OF THE GIVEN PAIR
@	:	$\tau \text{ list} \rightarrow \tau \text{ list} \rightarrow \tau \text{ list}$	CONCATENATE TWO LISTS
::	:	$\tau \rightarrow \tau \text{ list} \rightarrow \tau \text{ list}$	APPEND AN ELEMENT TO A LIST (RIGHT-ASSOCIATIVE)
<	:	$Expr \times Expr \rightarrow \mathbb{B}$	WHETHER CLASSES SPECIFIED BY THE EXPRESSIONS ARE SUBCLASSES

2.3 Rule: TensorFlow 2.x Keras API Pattern

2.3.1 Transformation Rules

$trans_M : Module \rightarrow Module$

$$trans_M \llbracket stmt^* \text{ type_ignore} \rrbracket = trans_{\bar{S}} \llbracket stmt^* \rrbracket(\sigma).1 \text{ type_ignore}$$

$trans_{\bar{S}} : Stmt \text{ list} \rightarrow \Sigma \rightarrow (Stmt \text{ list} \times \Sigma)$
--

$$\begin{aligned} trans_{\bar{S}} \llbracket stmt_1 \text{ stmt}_2 \dots stmt_n \rrbracket(\sigma) = & \text{LET } stmt_1', \sigma_1 = trans_S \llbracket stmt_1 \rrbracket(\sigma) \text{ IN} \\ & \text{LET } stmt_2', \sigma_2 = trans_S \llbracket stmt_2 \rrbracket(\sigma_1) \text{ IN} \\ & \dots \\ & \text{LET } stmt_n', \sigma_n = trans_S \llbracket stmt_n \rrbracket(\sigma_{n-1}) \text{ IN} \\ & (stmt_1' @ stmt_2' @ \dots @ stmt_n', \sigma_n) \end{aligned}$$

$trans_S : Stmt \rightarrow \Sigma \rightarrow (Stmt \text{ list} \times \Sigma)$

$$\begin{aligned} trans_S \llbracket (@expr_1)^* \text{ def } id (args) (-> expr_2)? : (\#type:s)? stmt^* \rrbracket(\sigma) = \\ ([(@expr_1)^* \text{ def } id (args) (-> expr_2)? : (\#type:s)? trans_{\bar{S}} \llbracket stmt^* \rrbracket(\sigma).1], \sigma) \\ trans_S \llbracket (@expr_1)^* \text{ async def } id (args) (-> expr_2)? : (\#type:s)? stmt^* \rrbracket(\sigma) = \\ ([(@expr_1)^* \text{ async def } id (args) (-> expr_2)? : (\#type:s)? trans_{\bar{S}} \llbracket stmt^* \rrbracket(\sigma).1], \sigma) \\ trans_S \llbracket (@expr_1)^* \text{ class } id (expr_2^* keyword^*) : stmt^* \rrbracket(\sigma) = \\ ([(@expr_1)^* \text{ class } id (expr_2^* keyword^*) : trans_{\bar{S}} \llbracket stmt^* \rrbracket(\sigma).1], \sigma) \\ trans_S \llbracket \text{return } expr? \rrbracket(\sigma) = ([\text{return } (trans_E \llbracket expr \rrbracket(\sigma))], \sigma) \\ trans_S \llbracket \text{delete } expr^* \rrbracket(\sigma) = ([\text{delete } expr^*], \sigma) \end{aligned}$$

A strict form of assignment statements

$$\begin{aligned} trans_S \llbracket id_r = expr_1 (expr_{11} \dots expr_{1n} (id_1 =)? expr_{21} \dots (id_k =)? expr_{2k}) (\#type:s)? \rrbracket(\sigma) = \\ \text{\textcolor{blue}{\# Learning rate scheduler scaling}} \\ \text{IF } expr_1 <: \text{tensorflow.keras.optimizers.schedules.PiecewiseConstantDecay THEN} \\ ([id_r = expr_1 (expr_{11} \dots expr_{1n} (id_1 =)? expr_{21} \dots (id_k =)? expr_{2k}) (\#type:s)?], \\ \sigma["lr_scheduler" \mapsto id_r]) \\ \text{ELIF } expr_1 <: \text{tensorflow.keras.experimental.PiecewiseConstantDecay THEN} \\ ([id_r = expr_1 (expr_{11} \dots expr_{1n} (id_1 =)? expr_{21} \dots (id_k =)? expr_{2k}) (\#type:s)?], \\ \sigma["lr_scheduler" \mapsto id_r]) \\ \text{ELIF } expr_1 <: \text{tensorflow.keras.optimizers.schedules.LearningRateSchedule THEN} \\ \text{IF } id_i = \text{initial_learning_rate WHEN } 1 \leq i \leq k \text{ THEN} \\ ([id_r = expr_1 (expr_{11} \dots expr_{1n} (id_1 =)? expr_{21} \dots id_i = expr_{2i} * \text{hvd.size}() \\ \dots (id_k =)? expr_{2k}) (\#type:s)?], \sigma["lr_scheduler" \mapsto id_r]) \\ \text{ELSE} \\ ([id_r = expr_1 (expr_{11} * \text{hvd.size}() \dots expr_{1n} (id_1 =)? expr_{21} \dots (id_k =)? expr_{2k}) (\#type:s)?], \\ \sigma["lr_scheduler" \mapsto id_r]) \\ \text{ELIF } expr_1 <: \text{tensorflow.compat.v1.train.exponential.decay THEN} \end{aligned}$$

```

IF  $id_i = \text{learning\_rate}$  WHEN  $1 \leq i \leq k$  THEN
  ( $[id_r = \text{expr}_1 (\text{expr}_{11} \dots \text{expr}_{1n} \ (id_1 = )? \text{expr}_{21} \dots id_i = \text{expr}_{2i} * \text{hvd.size}()$ 
     $\dots (id_k = )? \text{expr}_{2k}) \ (\#type:s)?]$ ,  $\sigma["lr\_scheduler" \mapsto id_r]$ )
ELSE
  ( $[id_r = \text{expr}_1 (\text{expr}_{11} * \text{hvd.size}() \dots \text{expr}_{1n} \ (id_1 = )? \text{expr}_{21} \dots (id_k = )? \text{expr}_{2k}) \ (\#type:s)?]$ ,
     $\sigma["lr\_scheduler" \mapsto id_r]$ )
# Optimizer learning rate scaling and wrapping
ELIF  $\text{expr}_1 <: \text{tensorflow.keras.optimizers.Optimizer}$  THEN
  IF  $id_i = \text{learning\_rate}$  WHEN  $1 \leq i \leq k$  THEN
    ( $[id_r = \text{expr}_1 (\text{expr}_{11} \dots \text{expr}_{1n} \ (id_1 = )? \text{expr}_{21} \dots id_i = \text{expr}_{2i} * \text{hvd.size}()$ 
       $\dots (id_k = )? \text{expr}_{2k}) \ (\#type:s)?]$ ,
       $id_r = \text{hvd.DistributedOptimizer}(id_r)] \ \sigma["optimizer" \mapsto id_r]$ )
  ELSE
    ( $[id_r = \text{expr}_1 (\text{expr}_{11} * \text{hvd.size}() \dots \text{expr}_{1n} \ (id_1 = )? \text{expr}_{21} \dots (id_k = )? \text{expr}_{2k}) \ (\#type:s)?]$ ,
       $id_r = \text{hvd.DistributedOptimizer}(id_r)] \ \sigma["optimizer" \mapsto id_r]$ )
# Model related
ELIF  $\text{expr}_1 <: \text{tensorflow.keras.models.Model}$  THEN
  ( $[id_r = \text{expr}_1 (\text{expr}_{11} \dots \text{expr}_{1n} \ (id_1 = )? \text{expr}_{21} \dots (id_k = )? \text{expr}_{2k}) \ (\#type:s)?]$ ,
     $\sigma["model" \mapsto id_r]$ )
ELIF  $\sigma["model"] = id_t$  AND  $\text{expr}_1 = id_t.evaluate$  THEN
  IF  $id_i = \text{verbose}$  WHEN  $1 \leq i \leq k$  THEN
    ( $[id_r = \text{expr}_1 (\text{expr}_{11} \dots \text{expr}_{1n} \ (id_1 = )? \text{expr}_{21} \dots id_i = 1 \text{ if } \text{hvd.rank}() == 0 \text{ else } 0$ 
       $\dots (id_k = )? \text{expr}_{2k}) \ (\#type:s)?]$ ,  $\sigma$ )
  ELSE
    ( $[id_r = \text{expr}_1 (\text{expr}_{11} \dots \text{expr}_{1n} \ (id_1 = )? \text{expr}_{21} \dots (id_k = )? \text{expr}_{2k}$ 
       $\text{verbose} = 1 \text{ if } \text{hvd.rank}() == 0 \text{ else } 0) \ (\#type:s)?]$ ,  $\sigma$ )
# Checkpoint
ELIF  $\sigma["\text{tensor\_flow}"] = id_t$  AND  $\text{expr}_1 = id_t.train.Checkpoint$  THEN
  ( $[id_r = \text{expr}_1 (\text{expr}_{11} \dots \text{expr}_{1n} \ (id_1 = )? \text{expr}_{21} \dots (id_k = )? \text{expr}_{2k}) \ (\#type:s)?]$ ,
     $\sigma["checkpoint" \mapsto id_r]$ )
# Default
ELSE ( $[id_r = \text{trans}_E \llbracket \text{expr}_1 (\text{expr}_{11} \dots \text{expr}_{1n} \ (id_2 = )? \text{expr}_{21} \dots (id_k = )? \text{expr}_{2k}) \rrbracket (\sigma) \ (\#type:s)?]$ ,
   $\sigma$ )

```

```

 $\text{trans}_S \llbracket \text{expr}_0 = \text{expr}_1 \ (\#type:s)? \rrbracket (\sigma) =$ 
  IF  $\sigma["os"] = id_{os}$  AND  $\text{expr}_0 = id_{os}.environ["CUDA_VISIBLE_DEVICES"]$ 
  THEN ( $\llbracket \ , \sigma \rrbracket$ )

```

A general form of assignment statements except for the strict form

```

 $\text{trans}_S \llbracket \text{expr}_1^* = \text{expr}_2 \ (\#type:s)? \rrbracket (\sigma) = ([\text{expr}_1^* = \text{trans}_E \llbracket \text{expr}_2 \rrbracket (\sigma) \ (\#type:s)?]$ ,  $\sigma$ )

```

```

 $\text{trans}_S \llbracket \text{expr}_1 \text{ binop} = \text{expr}_2 \rrbracket (\sigma) = ([\text{expr}_1 \text{ binop} = \text{trans}_E \llbracket \text{expr}_2 \rrbracket (\sigma)]$ ,  $\sigma$ )

```

$trans_S \llbracket expr_1 : expr_2 (= expr_3)? \rrbracket(\sigma) = ([expr_1 : expr_2 (= trans_E \llbracket expr_3 \rrbracket(\sigma))?), \sigma)$
Dataset in Assign
IF $expr_1 = id_1$ **AND** $\sigma(\text{"tensor_flow"}) = id_2$
AND $expr_3 = id_2.data.Dataset.expr_4 (expr_5^* keyword^*)$ **THEN**
 $([expr_1 : expr_2 = expr_3 (\#type:s)?], \sigma[\text{"dataset"} \mapsto id_1])$
ELSE $([expr_1 : expr_2 (= trans_E \llbracket expr_3 \rrbracket(\sigma))?), \sigma)$

$trans_S \llbracket (\#type:s)? \text{ for } expr_1 \text{ in } expr_2 : stmt_1^* (\text{else} : stmt_2^*)? \rrbracket(\sigma) =$
 $([(\#type:s)? \text{ for } expr_1 \text{ in } trans_E \llbracket expr_2 \rrbracket(\sigma) :$
 $trans_{\overline{S}} \llbracket stmt_1^* \rrbracket(\sigma).1 (\text{else} : trans_{\overline{S}} \llbracket stmt_2^* \rrbracket(\sigma).1)?], \sigma)$

$trans_S \llbracket (\#type:s)? \text{ async for } expr_1 \text{ in } expr_2 : stmt_1^* (\text{else} : stmt_2^*)? \rrbracket(\sigma) =$
 $([(\#type:s)? \text{ async for } expr_1 \text{ in } trans_E \llbracket expr_2 \rrbracket(\sigma) :$
 $trans_{\overline{S}} \llbracket stmt_1^* \rrbracket(\sigma).1 (\text{else} : trans_{\overline{S}} \llbracket stmt_2^* \rrbracket(\sigma).1)?], \sigma)$

$trans_S \llbracket \text{while } (expr) : stmt_1^* (\text{else} : stmt_2^*)? \rrbracket(\sigma) =$
 $([\text{while } (trans_E \llbracket expr \rrbracket(\sigma)) : trans_{\overline{S}} \llbracket stmt_1^* \rrbracket(\sigma).1 (\text{else} : trans_{\overline{S}} \llbracket stmt_2^* \rrbracket(\sigma).1)?], \sigma)$

$trans_S \llbracket \text{if } (expr) : stmt^* (\text{else} : stmt^*)? \rrbracket(\sigma) =$
 $([\text{if } (trans_E \llbracket expr \rrbracket(\sigma)) : trans_{\overline{S}} \llbracket stmt^* \rrbracket(\sigma).1 (\text{else} : trans_{\overline{S}} \llbracket stmt^* \rrbracket(\sigma).1)?], \sigma)$

$trans_S \llbracket (\#type:s)? \text{ with } with_item^* : stmt^* \rrbracket(\sigma) =$
LET $with_item^{*'}, \sigma_1 = trans_{\overline{W}} \llbracket with_item^* \rrbracket(\sigma)$ **IN**
LET $stmt^{*'}, \sigma_2 = trans_{\overline{S}} \llbracket stmt^* \rrbracket(\sigma_1)$ **IN**
IF $\sigma_1 \setminus \sigma = [\text{"gradient_tape"} \mapsto id]$ **THEN**
 $([(\#type:s)? \text{ with } with_item^{*'} : stmt^{*'},$
 $id = hvd.DistributedGradientTape(id)], \sigma_2)$
ELSE $([(\#type:s)? \text{ with } with_item^{*'} : stmt^{*'}], \sigma_2)$

$trans_S \llbracket (\#type:s)? \text{ async with } with_item^* : stmt^* \rrbracket(\sigma) =$
LET $with_item^{*'}, \sigma_1 = trans_{\overline{W}} \llbracket with_item^* \rrbracket(\sigma)$ **IN**
LET $stmt^{*'}, \sigma_2 = trans_{\overline{S}} \llbracket stmt^* \rrbracket(\sigma_1)$ **IN**
IF $\sigma_1 \setminus \sigma = [\text{"gradient_tape"} \mapsto id]$ **THEN**
 $([(\#type:s)? \text{ async with } with_item^{*'} : stmt^{*'},$
 $id = hvd.DistributedGradientTape(id)], \sigma_2)$
ELSE $([(\#type:s)? \text{ async with } with_item^{*'} : stmt^{*'}], \sigma_2)$

$trans_S \llbracket \text{match } expr : match_case^* \rrbracket(\sigma) =$
 $([\text{match } trans_E \llbracket expr \rrbracket(\sigma) : (trans_C \llbracket match_case \rrbracket(\sigma))^*], \sigma)$

$trans_S \llbracket \text{raise } expr_1? (\text{from } expr_2)? \rrbracket(\sigma) = ([\text{raise } expr_1? (\text{from } expr_2)?], \sigma)$

$trans_S \llbracket \text{try} : stmt_1^* exc_handler^* (\text{else} : stmt_2^*)? (\text{finally} : stmt_3^*)? \rrbracket(\sigma) =$
 $([\text{try} : trans_{\overline{S}} \llbracket stmt_1^* \rrbracket(\sigma).1 (trans_H \llbracket exc_handler \rrbracket(\sigma))^*$
 $(\text{else} : trans_{\overline{S}} \llbracket stmt_2^* \rrbracket(\sigma).1)? (\text{finally} : trans_{\overline{S}} \llbracket stmt_3^* \rrbracket(\sigma).1)?], \sigma)$

$trans_S \llbracket \text{assert } expr_1 \text{ } expr_2? \rrbracket(\sigma) = ([\text{assert } trans_E \llbracket expr_1 \rrbracket(\sigma) \text{ } expr_2?, \sigma)$

$trans_S \llbracket \text{import } alias^* \rrbracket(\sigma) =$
LET $\sigma_1 = trans_{\bar{A}} \llbracket alias^* \rrbracket(\sigma)$ **IN**
IF $\sigma_1 \setminus \sigma = [\text{“tensor_flow”} \mapsto id]$ **THEN**
 ([import $alias^*$,
 import horovod.tensorflow as hvd,
 hvd.broadcast_done = False,
 hvd.init(),
 gpus = $id.config.experimental.list_physical_devices('GPU')$,
 for gpu in gpus: $id.config.experimental.set_memory_growth(gpu, True)$,
 if gpus: $id.config.experimental.set_visible_devices(gpus[hvd.local_rank()], 'GPU')$], σ_1)
ELSE ([import $alias^*$], σ_1)

$trans_S \llbracket \text{import } alias^* \rrbracket(\sigma) =$
LET $\sigma_1 = trans_{\bar{A}} \llbracket alias^* \rrbracket(\sigma)$ **IN**
IF $\sigma_1 \setminus \sigma = [\text{“tensor_flow”} \mapsto id]$ **THEN**
 ([import $alias^*$,
 import horovod.tensorflow as hvd,
 hvd.init(),
 gpus = $id.config.experimental.list_physical_devices('GPU')$,
 for gpu in gpus: $id.config.experimental.set_memory_growth(gpu, True)$,
 if gpus: $id.config.experimental.set_visible_devices(gpus[hvd.local_rank()], 'GPU')$], σ_1)
ELSE ([import $alias^*$], σ_1)

$trans_S \llbracket \text{from } i \text{ } id? \text{ import } alias^* \rrbracket(\sigma) =$
LET $\sigma_1 = trans_{\bar{A}} \llbracket alias^* \rrbracket(\sigma)$ **IN**
IF $id = \text{tensorflow}$ **AND** $\sigma_1 \setminus \sigma = [\text{“keras”} \mapsto id]$ **THEN**
 ([from $i \text{ } id?$ import $alias^*$,
 import horovod.tensorflow.keras as hvd,
 hvd.init(),
 gpus = $id.config.experimental.list_physical_devices('GPU')$,
 for gpu in gpus: $id.config.experimental.set_memory_growth(gpu, True)$,
 if gpus: $id.config.experimental.set_visible_devices(gpus[hvd.local_rank()], 'GPU')$], σ_1)
ELSE ([from $i \text{ } id?$ import $alias^*$], σ_1)

$trans_S \llbracket \text{global } id^* \rrbracket(\sigma) = ([\text{global } id^*], \sigma)$

$trans_S \llbracket \text{nonlocal } id^* \rrbracket(\sigma) = ([\text{nonlocal } id^*], \sigma)$

A strict form of expr statements

$trans_S \llbracket expr_1 (expr_{11} \dots expr_{1n} \text{ } (id_1 =)? expr_{21} \dots (id_k =)? expr_{2k}) \rrbracket(\sigma) =$
IF $\sigma(\text{“optimizer”}) = id_t$ **AND** $expr_1 = id_t.apply_gradients$ **THEN**


```

IF  $id_i = \text{grads\_and\_vars}$  WHEN  $1 \leq i \leq k$  THEN
  LET  $id_z = \text{NewID}()$  IN
    ( $id_z = \text{expr}_{2i}$ ,
     $\text{expr}_1 (\text{expr}_{11} \dots \text{expr}_{1n} \ (id_1 = )? \text{expr}_{21} \dots id_i = id_z \dots (id_k = )? \text{expr}_{2k})$ ,
    global hvd_broadcast_done,
    if not hvd_broadcast_done: [hvd.broadcast_variables([x[1] for x in id_z], root_rank=0),
      hvd.broadcast_variables(id_t.variables(), root_rank=0),
      hvd_broadcast_done = True ],  $\sigma$ )
ELSE
  LET  $id_z = \text{NewID}()$  IN
    ( $id_z = \text{expr}_{11}$ ,
     $\text{expr}_1 (id_z \text{ expr}_{12} \dots \text{expr}_{1n} \ (id_1 = )? \text{expr}_{21} \dots (id_k = )? \text{expr}_{2k})$ ,
    global hvd_broadcast_done,
    if not hvd_broadcast_done: [hvd.broadcast_variables([x[1] for x in id_z], root_rank=0),
      hvd.broadcast_variables(id_t.variables(), root_rank=0),
      hvd_broadcast_done = True ],  $\sigma$ )
# MainScript rule
ELIF  $\text{expr}_1 = \text{print}$  OR  $\text{expr}_1 = \text{expr.write}$  OR  $\text{expr}_1 = \text{expr.summary}$  OR
   $\text{expr}_1 = \text{expr.save\_weights}$  OR  $\text{expr}_1 = \text{expr.load\_weights}$  THEN
  (if hvd.rank() == 0:  $\text{expr}_1 (\text{expr}_{11} \dots \text{expr}_{1n} \ (id_1 = )? \text{expr}_{21} \dots (id_k = )? \text{expr}_{2k})$ ],  $\sigma$ )
ELIF  $\sigma(\text{"checkpoint"}) = id_t$  AND  $\text{expr}_1 = id_t.\text{save}$  THEN
  (if hvd.rank() == 0: [ $\text{expr}_1 (\text{expr}_{11} \dots \text{expr}_{1n} \ (id_1 = )? \text{expr}_{21} \dots (id_k = )? \text{expr}_{2k})$ ]],  $\sigma$ )
ELIF  $\sigma(\text{"model"}) = id_t$  AND  $\text{expr}_1 = id_t.\text{fit}$  THEN
  IF  $id_i = \text{verbose}$  WHEN  $1 \leq i \leq k$  THEN
    IF  $id_j = \text{callbacks}$  WHEN  $1 \leq j \leq k$  THEN
      ([callback = [hvd.callbacks.BroadcastGlobalVariablesCallback(root_rank=0)]
      if hvd.rank() == 0: callbacks.append(expr_{2j})
       $\text{expr}_1 (\text{expr}_{11} \dots \text{expr}_{1n} \ (id_1 = )? \text{expr}_{21} \dots id_i = 1 \text{ if } \text{hvd.rank}() == 0 \text{ else } 0$ 
       $\dots id_j = \text{callbacks} \dots (id_k = )? \text{expr}_{2k})$ ],  $\sigma$ )
    ELSE
      ( $\text{expr}_1 (\text{expr}_{11} \dots \text{expr}_{1n} \ (id_1 = )? \text{expr}_{21} \dots$ 
       $id_i = 1 \text{ if } \text{hvd.rank}() == 0 \text{ else } 0 \dots (id_k = )? \text{expr}_{2k}$ 
      callbacks = [hvd.callbacks.BroadcastGlobalVariablesCallback(root_rank=0)]),  $\sigma$ )
    ELSE
      IF  $id_j = \text{callbacks}$  WHEN  $1 \leq j \leq k$  THEN
        ([callback = [hvd.callbacks.BroadcastGlobalVariablesCallback(root_rank=0)]
        if hvd.rank() == 0: callbacks.append(expr_{2j})
         $\text{expr}_1 (\text{expr}_{11} \dots \text{expr}_{1n} \ (id_1 = )? \text{expr}_{21} \dots id_j = \text{callbacks} \dots (id_k = )? \text{expr}_{2k}$ 
        verbose = 1 if hvd.rank() == 0 else 0]],  $\sigma$ )
      ELSE
        ( $\text{expr}_1 (\text{expr}_{11} \dots \text{expr}_{1n} \ (id_1 = )? \text{expr}_{21} \dots (id_k = )? \text{expr}_{2k}$ 
        verbose = 1 if hvd.rank() == 0 else 0
        callbacks = [hvd.callbacks.BroadcastGlobalVariablesCallback(0)]),  $\sigma$ )
      ELIF  $\sigma(\text{"model"}) = id_t$  AND  $\text{expr}_1 = id_t.\text{compile}$  THEN

```

```

IF  $id_i = \text{optimizer}$  AND  $expr_{2i} = \text{"adam"}$  WHEN  $1 \leq i \leq k$  THEN
  ( $id_z = \text{tf.optimizers.Adam(learning\_rate=0.001 * hvd.size())}$ 
    $id_z = \text{hvd.DistributedOptimizer}(id_z)$ 
    $expr_1 (expr_{11} \dots expr_{1n} \ (id_1 = )? expr_{21} \dots id_i = id_z \dots (id_k = )? expr_{2k})], \sigma)$ 
ELIF  $expr_{11} = \text{"adam"}$  THEN
  ( $id_z = \text{tf.optimizers.Adam(learning\_rate=0.001 * hvd.size())}$ 
    $id_z = \text{hvd.DistributedOptimizer}(id_z)$ 
    $expr_1 (id_z \dots expr_{1n} \ (id_1 = )? expr_{21} \dots (id_k = )? expr_{2k})], \sigma)$ 
ELSE
  ( $trans_E \llbracket expr_1 (expr_{11} \dots expr_{1n} \ (id_1 = )? expr_{21} \dots (id_k = )? expr_{2k}) \rrbracket(\sigma), \sigma)$ 
ELIF  $expr_1 = \text{model.summary}$  THEN
  ( $[\text{if hvd.rank()} == 0: expr_1 (expr_{11} \dots expr_{1n} \ (id_1 = )? expr_{21} \dots (id_k = )? expr_{2k})], \sigma)$ 
ELSE
  ( $trans_E \llbracket expr_1 (expr_{11} \dots expr_{1n} \ (id_1 = )? expr_{21} \dots (id_k = )? expr_{2k}) \rrbracket(\sigma), \sigma)$ 

```

A general form of expr statements except for the strict form

$trans_S \llbracket expr \rrbracket(\sigma) = ([trans_E \llbracket expr \rrbracket(\sigma)], \sigma)$

$trans_S \llbracket \text{pass} \rrbracket(\sigma) = ([\text{pass}], \sigma)$

$trans_S \llbracket \text{break} \rrbracket(\sigma) = ([\text{break}], \sigma)$

$trans_S \llbracket \text{continue} \rrbracket(\sigma) = ([\text{continue}], \sigma)$

$trans_E : Expr \rightarrow \Sigma \rightarrow Expr$
--

$trans_E \llbracket expr_1 \ \text{boolop} \ expr_2 \rrbracket(\sigma) = trans_E \llbracket expr_1 \rrbracket(\sigma) \ \text{boolop} \ trans_E \llbracket expr_2 \rrbracket(\sigma)$

$trans_E \llbracket expr_1 \ := \ expr_2 \rrbracket(\sigma) = expr_1 \ := \ trans_E \llbracket expr_2 \rrbracket(\sigma)$

$trans_E \llbracket expr_1 \ \text{binop} \ expr_2 \rrbracket(\sigma) = trans_E \llbracket expr_1 \rrbracket(\sigma) \ \text{binop} \ trans_E \llbracket expr_2 \rrbracket(\sigma)$

$trans_E \llbracket \text{unop} \ expr \rrbracket(\sigma) = \text{unop} \ trans_E \llbracket expr \rrbracket(\sigma)$

$trans_E \llbracket \text{lambda} \ args : expr \rrbracket(\sigma) = \text{lambda} \ args : trans_E \llbracket expr \rrbracket(\sigma)$

$trans_E \llbracket expr_1 \ \text{if} \ expr_2 \ \text{else} \ expr_3 \rrbracket(\sigma) =$
 $trans_E \llbracket expr_1 \rrbracket(\sigma) \ \text{if} \ trans_E \llbracket expr_2 \rrbracket(\sigma) \ \text{else} \ trans_E \llbracket expr_3 \rrbracket(\sigma)$

$trans_E \llbracket expr_1 \ \text{if} \ expr_2 \ \text{else} \ expr_3 \rrbracket(\sigma) =$
 $trans_E \llbracket expr_1 \rrbracket(\sigma) \ \text{if} \ trans_E \llbracket expr_2 \rrbracket(\sigma) \ \text{else} \ trans_E \llbracket expr_3 \rrbracket(\sigma)$

$trans_E \llbracket \{(expr_1 : expr_2)^* \ (**expr_3)^*\} \rrbracket(\sigma) = \{(expr_1 : trans_E \llbracket expr_2 \rrbracket(\sigma))^* \ (**expr_3)^*\}$

$$trans_E \llbracket \{expr^*\} \rrbracket(\sigma) = \{(trans_E \llbracket expr \rrbracket(\sigma))^*\}$$

$$trans_E \llbracket [expr^*] \rrbracket(\sigma) = [(trans_E \llbracket expr \rrbracket(\sigma))^*]$$

$$trans_E \llbracket (expr^*) \rrbracket(\sigma) = ((trans_E \llbracket expr \rrbracket(\sigma))^*)$$

$$trans_E \llbracket \{expr_1 : expr_2 \text{ comprehension}^*\} \rrbracket(\sigma) = \{expr_1 : trans_E \llbracket expr_2 \rrbracket(\sigma) \ (trans_O \llbracket comprehension \rrbracket(\sigma))^*\}$$

$$trans_E \llbracket \{expr \text{ comprehension}^*\} \rrbracket(\sigma) = \{trans_E \llbracket expr \rrbracket(\sigma) \ (trans_O \llbracket comprehension \rrbracket(\sigma))^*\}$$

$$trans_E \llbracket [expr \text{ comprehension}^*] \rrbracket(\sigma) = [(trans_E \llbracket expr \rrbracket(\sigma) \ (trans_O \llbracket comprehension \rrbracket(\sigma))^*)]$$

$$trans_E \llbracket (expr \text{ comprehension}^*) \rrbracket(\sigma) = (trans_E \llbracket expr \rrbracket(\sigma) \ (trans_O \llbracket comprehension \rrbracket(\sigma))^*)$$

$$trans_E \llbracket \text{await } expr \rrbracket(\sigma) = \text{await } trans_E \llbracket expr \rrbracket(\sigma)$$

$$trans_E \llbracket \text{yield } expr? \rrbracket(\sigma) = \text{yield } (trans_E \llbracket expr \rrbracket(\sigma))?$$

$$trans_E \llbracket \text{yield from } expr \rrbracket(\sigma) = \text{yield from } trans_E \llbracket expr \rrbracket(\sigma)$$

$$trans_E \llbracket expr_1 \text{ (compop } expr_2)^* \rrbracket(\sigma) = trans_E \llbracket expr_1 \rrbracket(\sigma) \text{ (compop } trans_E \llbracket expr_2 \rrbracket(\sigma))^*$$

$$trans_E \llbracket expr_1 \text{ (} expr_{11} \dots expr_{1n} \text{ (} id_1 = \text{)? } expr_{21} \dots (id_k = \text{)? } expr_{2k} \text{)} \rrbracket(\sigma) =$$

IF $\sigma(\text{"dataset"}) = id_t$ **AND** $expr_1 = id_t.\text{take}$ **THEN**

IF $id_i = \text{count}$ **WHEN** $1 \leq i \leq k$ **THEN**

$expr_1 \text{ (} expr_{11} \dots expr_{1n} \text{ (} id_1 = \text{)? } expr_{21} \dots id_i = expr_{2i} // \text{ hvd.size() } \dots (id_k = \text{)? } expr_{2k} \text{)}$

ELSE

$expr_1 \text{ (} expr_{11} // \text{ hvd.size() } \dots expr_{1n} \text{ (} id_1 = \text{)? } expr_{21} \dots (id_k = \text{)? } expr_{2k} \text{)}$

ELSE

$trans_E \llbracket expr_1 \rrbracket(\sigma) \ (trans_E \llbracket expr_{11} \rrbracket(\sigma) \dots trans_E \llbracket expr_{1n} \rrbracket(\sigma)$

$(id_1 = \text{)? } trans_E \llbracket expr_{21} \rrbracket(\sigma) \dots (id_k = \text{)? } trans_E \llbracket expr_{2k} \rrbracket(\sigma))$

$$trans_E \llbracket \{expr_1 \text{ (!} i \text{)? } (:expr_2)?\} \rrbracket(\sigma) = \{expr_1 \text{ (!} i \text{)? } (:expr_2)?\}$$

$$trans_E \llbracket expr^* \rrbracket(\sigma) = expr^*$$

$$trans_E \llbracket \text{constant} \rrbracket(\sigma) = \text{constant}$$

$$trans_E \llbracket expr.id \rrbracket(\sigma) = (trans_E \llbracket expr \rrbracket(\sigma)).id$$

$$trans_E \llbracket expr_1[expr_2] \rrbracket(\sigma) = trans_E \llbracket expr_1 \rrbracket(\sigma)[trans_E \llbracket expr_2 \rrbracket(\sigma)]$$

$$trans_E \llbracket *expr \rrbracket(\sigma) = *expr$$

$$trans_E \llbracket **expr \rrbracket(\sigma) = **expr$$

$$trans_E \llbracket id \rrbracket(\sigma) = id$$

$$trans_E \llbracket expr_1? (:expr_2)? (:expr_3)? \rrbracket(\sigma) = trans_E \llbracket expr_1 \rrbracket(\sigma)? (:trans_E \llbracket expr_2 \rrbracket(\sigma))? (:trans_E \llbracket expr_3 \rrbracket(\sigma))?$$

$$\boxed{trans_O : Comprehension \rightarrow \Sigma \rightarrow Comprehension}$$

$$trans_O \llbracket \text{for } expr_1 \text{ in } expr_2 \text{ (if } expr_3)^* \rrbracket(\sigma) = \text{for } expr_1 \text{ in } trans_E \llbracket expr_2 \rrbracket(\sigma) \text{ (if } trans_E \llbracket expr_3 \rrbracket(\sigma))^*$$

$$\boxed{trans_H : ExcHandler \rightarrow \Sigma \rightarrow ExcHandler}$$

$$trans_H \llbracket \text{except } expr? \text{ (as } id)? : stmt^* \rrbracket(\sigma) = \text{except } expr? \text{ (as } id)? : trans_{\overline{S}} \llbracket stmt^* \rrbracket(\sigma).1$$

$$\boxed{trans_{\overline{A}} : Alias \text{ list} \rightarrow \Sigma \rightarrow \Sigma}$$

$$trans_{\overline{A}} \llbracket alias_1 \dots alias_{n-1} alias_n \rrbracket(\sigma) = trans_A \llbracket alias_n \rrbracket(trans_A \llbracket alias_{n-1} \rrbracket(\dots trans_A \llbracket alias_1 \rrbracket(\sigma)))$$

$$\boxed{trans_A : Alias \rightarrow \Sigma \rightarrow \Sigma}$$

$$trans_A \llbracket id \rrbracket(\sigma) =$$

LET $id = \text{tensorflow}$ **THEN** $\sigma["\text{tensorflow}"] \mapsto id$
LET $id = \text{keras}$ **THEN** $\sigma["\text{keras}"] \mapsto id$
LET $id = \text{os}$ **THEN** $\sigma["\text{os}"] \mapsto id$
LET $id = \text{optimizers}$ **THEN** $\sigma["\text{optimizers}"] \mapsto id$
ELSE σ

$$trans_A \llbracket id_1 \text{ as } id_2 \rrbracket(\sigma) =$$

LET $id_1 = \text{tensorflow}$ **THEN** $\sigma["\text{tensorflow}"] \mapsto id_2$
LET $id_1 = \text{tensorflow.keras}$ **THEN** $\sigma["\text{keras}"] \mapsto id_2$
LET $id_1 = \text{os}$ **THEN** $\sigma["\text{os}"] \mapsto id_2$
LET $id = \text{optimizers}$ **THEN** $\sigma["\text{optimizers}"] \mapsto id$
ELSE σ

$$trans_A \llbracket id_1 . id_2 (.id_3)^* \text{ (as } id_2)? \rrbracket(\sigma) = \sigma$$

$$\boxed{trans_{\overline{W}} : WithItem \text{ list} \rightarrow \Sigma \rightarrow (WithItem \text{ list} \times \Sigma)}$$

$trans_{\overline{W}} \llbracket with_item_1 with_item_2 \dots with_item_n \rrbracket(\sigma) =$
LET $with_item_1', \sigma_1 = trans_W \llbracket with_item_1 \rrbracket(\sigma)$ **IN**
LET $with_item_2', \sigma_2 = trans_W \llbracket with_item_2 \rrbracket(\sigma_1)$ **IN**
 \dots
LET $with_item_n', \sigma_n = trans_W \llbracket with_item_n \rrbracket(\sigma_{n-1})$ **IN**
 $(with_item_1' :: with_item_2' :: \dots :: [with_item_n'], \sigma_n)$

$trans_W : WithItem \rightarrow \Sigma \rightarrow (WithItem \times \Sigma)$
--

$trans_W \llbracket expr \rrbracket(\sigma) = (trans_E \llbracket expr \rrbracket(\sigma), \sigma)$

$trans_W \llbracket expr_1 \text{ as } expr_2 \rrbracket(smodenv) =$
IF $\sigma(\text{"tensor_flow"}) = id_1$ **AND** $expr_1 = id_1.\text{GradientTape}()$ **AND** $expr_2 = id_2$ **THEN**
 $(expr_1 \text{ as } expr_2, \sigma[\text{"gradient_tape"} \mapsto id_2])$
ELSE $(trans_E \llbracket expr_1 \rrbracket(\sigma) \text{ as } expr_2, \sigma)$

$trans_C : MatchCase \rightarrow \Sigma \rightarrow MatchCase$
--

$trans_C \llbracket \text{case pattern (if expr)? : stmt*} \rrbracket(\sigma) =$
 $\text{case } trans_P \llbracket pattern \rrbracket(\sigma) \text{ (if } trans_E \llbracket expr \rrbracket(\sigma))? : trans_{\overline{S}} \llbracket stmt* \rrbracket(\sigma).1$

$trans_P : Pattern \rightarrow \Sigma \rightarrow Pattern$
--

$trans_P \llbracket expr \rrbracket(\sigma) = trans_E \llbracket expr \rrbracket(\sigma)$

$trans_P \llbracket constant \rrbracket(\sigma) = constant$

$trans_P \llbracket [pattern*] \rrbracket(\sigma) = [trans_P \llbracket pattern \rrbracket(\sigma)*]$

$trans_P \llbracket *(id)? \rrbracket(\sigma) = *(id)?$

$trans_P \llbracket \{(expr : pattern)* id?\} \rrbracket(\sigma) = \{(expr : trans_P \llbracket pattern \rrbracket(\sigma))* id?\}$

$trans_P \llbracket expr (pattern_1^* (id = pattern_2^*)) \rrbracket(\sigma) = expr (trans_P \llbracket pattern_1 \rrbracket(\sigma)^* (id = trans_P \llbracket pattern_2 \rrbracket(\sigma))^*)$

$trans_P \llbracket (pattern \text{ as})? id \rrbracket(\sigma) = (trans_P \llbracket pattern \rrbracket(\sigma) \text{ as})? id$

$trans_P \llbracket pattern_1 \mid pattern_2 \rrbracket(\sigma) = trans_P \llbracket pattern_1 \rrbracket(\sigma) \mid trans_P \llbracket pattern_2 \rrbracket(\sigma)$

$trans_P \llbracket - \rrbracket(\sigma) = -$

2.4 Rule: TensorFlow 2.x GradientTape API Pattern

2.4.1 Transformation Rules

$trans_M : Module \rightarrow Module$

$$trans_M \llbracket stmt^* \text{ type_ignore} \rrbracket = trans_{\bar{S}} \llbracket stmt^* \rrbracket(\sigma).1 \text{ type_ignore}$$

$trans_{\bar{S}} : Stmt \text{ list} \rightarrow \Sigma \rightarrow (Stmt \text{ list} \times \Sigma)$
--

$$\begin{aligned} trans_{\bar{S}} \llbracket stmt_1 \text{ stmt}_2 \dots stmt_n \rrbracket(\sigma) = & \text{LET } stmt_1', \sigma_1 = trans_S \llbracket stmt_1 \rrbracket(\sigma) \text{ IN} \\ & \text{LET } stmt_2', \sigma_2 = trans_S \llbracket stmt_2 \rrbracket(\sigma_1) \text{ IN} \\ & \dots \\ & \text{LET } stmt_n', \sigma_n = trans_S \llbracket stmt_n \rrbracket(\sigma_{n-1}) \text{ IN} \\ & (stmt_1' @ stmt_2' @ \dots @ stmt_n', \sigma_n) \end{aligned}$$

$trans_S : Stmt \rightarrow \Sigma \rightarrow (Stmt \text{ list} \times \Sigma)$

$$\begin{aligned} trans_S \llbracket (@expr_1)^* \text{ def } id (args) (-> expr_2)? : (\#type:s)? stmt^* \rrbracket(\sigma) = \\ & ([(@expr_1)^* \text{ def } id (args) (-> expr_2)? : (\#type:s)? trans_{\bar{S}} \llbracket stmt^* \rrbracket(\sigma).1], \sigma) \\ trans_S \llbracket (@expr_1)^* \text{ async def } id (args) (-> expr_2)? : (\#type:s)? stmt^* \rrbracket(\sigma) = \\ & ([(@expr_1)^* \text{ async def } id (args) (-> expr_2)? : (\#type:s)? trans_{\bar{S}} \llbracket stmt^* \rrbracket(\sigma).1], \sigma) \\ trans_S \llbracket (@expr_1)^* \text{ class } id (expr_2^* keyword^*) : stmt^* \rrbracket(\sigma) = \\ & ([(@expr_1)^* \text{ class } id (expr_2^* keyword^*) : trans_{\bar{S}} \llbracket stmt^* \rrbracket(\sigma).1], \sigma) \\ trans_S \llbracket \text{return } expr? \rrbracket(\sigma) = ([\text{return } (trans_E \llbracket expr \rrbracket(\sigma))?), \sigma) \\ trans_S \llbracket \text{delete } expr^* \rrbracket(\sigma) = ([\text{delete } expr^*], \sigma) \end{aligned}$$

A strict form of assignment statements

$$\begin{aligned} trans_S \llbracket id_r = expr_1 (expr_{11} \dots expr_{1n} (id_1 =)? expr_{21} \dots (id_k =)? expr_{2k}) (\#type:s)? \rrbracket(\sigma) = \\ \text{\textcolor{blue}{\# Dataset}} \\ \text{IF } \sigma(\text{"tensor_flow"}) = id_t \text{ AND } expr_1 = id_t.data.Dataset.expr_3 \text{ THEN} \\ & ([id_r = expr_1 (expr_{11} \dots expr_{1n} (id_1 =)? expr_{21} \dots (id_k =)? expr_{2k}) (\#type:s)?], \\ & \sigma[\text{"dataset"} \mapsto id_r]) \\ \text{\textcolor{blue}{\# Variable Broadcasting}} \\ \text{ELIF } \sigma(\text{"optimizer"}) = id_t \text{ AND } expr_1 = id_t.apply_gradients \text{ THEN} \\ & \text{IF } id_i = \text{grads_and_vars} \text{ WHEN } 1 \leq i \leq k \text{ THEN} \\ & \text{LET } id_z = \text{NewID}() \text{ IN} \\ & ([id_z = expr_{2i}, \\ & id_r = expr_1 (expr_{11} \dots expr_{1n} (id_1 =)? expr_{21} \dots id_i = id_z \dots (id_k =)? expr_{2k}) (\#type:s)?, \\ & \text{global hvd_broadcast_done,} \\ & \text{if not hvd_broadcast_done: [hvd.broadcast_variables([x[1] for x in id_z], root_rank=0),} \\ & \text{hvd.broadcast_variables(id_t.variables(), root_rank=0),} \\ & \text{hvd_broadcast_done = True }], \sigma) \\ \text{ELSE} \end{aligned}$$

```

LET  $id_z$  = NewID() IN
  ( $id_z$  =  $expr_{11}$ ,
   $id_r$  =  $expr_1$  ( $id_z$   $expr_{12}$  ...  $expr_{1n}$  ( $id_1$  = )?  $expr_{21}$  ... ( $id_k$  = )?  $expr_{2k}$ ) (#type:s)?,
  global hvd_broadcast_done,
  if not hvd_broadcast_done: [ hvd.broadcast_variables([x[1] for x in  $id_z$ ], root_rank=0),
    hvd.broadcast_variables( $id_t$ .variables(), root_rank=0),
    hvd_broadcast_done = True ],  $\sigma$ )
# Learning rate scheduler scaling
IF  $expr_1$  <: "tensorflow.keras.optimizers.schedules.PiecewiseConstantDecay" THEN
  ( $id_r$  =  $expr_1$  ( $expr_{11}$  ...  $expr_{1n}$  ( $id_1$  = )?  $expr_{21}$  ... ( $id_k$  = )?  $expr_{2k}$ ) (#type:s)?],
   $\sigma$ ["lr_scheduler"  $\mapsto id_r$ ])
ELIF  $expr_1$  <: tensorflow.keras.optimizers.schedules.LearningRateSchedule THEN
  IF  $id_i$  = initial_learning_rate WHEN  $1 \leq i \leq k$  THEN
    ( $id_r$  =  $expr_1$  ( $expr_{11}$  ...  $expr_{1n}$  ( $id_1$  = )?  $expr_{21}$  ...  $id_i$  =  $expr_{2i}$  * hvd.size()
    ... ( $id_k$  = )?  $expr_{2k}$ ) (#type:s)?],  $\sigma$ ["lr_scheduler"  $\mapsto id_r$ ])
  ELSE
    ( $id_r$  =  $expr_1$  ( $expr_{11}$  * hvd.size() ...  $expr_{1n}$  ( $id_1$  = )?  $expr_{21}$  ... ( $id_k$  = )?  $expr_{2k}$ ) (#type:s)?],
     $\sigma$ ["lr_scheduler"  $\mapsto id_r$ ])
ELIF  $expr_1$  <: tensorflow.compat.v1.train.exponential_decay THEN
  IF  $id_i$  = learning_rate WHEN  $1 \leq i \leq k$  THEN
    ( $id_r$  =  $expr_1$  ( $expr_{11}$  ...  $expr_{1n}$  ( $id_1$  = )?  $expr_{21}$  ...  $id_i$  =  $expr_{2i}$  * hvd.size()
    ... ( $id_k$  = )?  $expr_{2k}$ ) (#type:s)?],  $\sigma$ ["lr_scheduler"  $\mapsto id_r$ ])
  ELSE
    ( $id_r$  =  $expr_1$  ( $expr_{11}$  * hvd.size() ...  $expr_{1n}$  ( $id_1$  = )?  $expr_{21}$  ... ( $id_k$  = )?  $expr_{2k}$ ) (#type:s)?],
     $\sigma$ ["lr_scheduler"  $\mapsto id_r$ ])
# Optimizer learning rate scaling and wrapping
IF  $expr_1$  <: tensorflow.keras.optimizers.Optimizer THEN
  ( $id_r$  =  $expr_1$  ( $expr_{11}$  ...  $expr_{1n}$  ( $id_1$  = )?  $expr_{21}$  ... ( $id_k$  = )?  $expr_{2k}$ ) (#type:s)?],
   $\sigma$ ["optimizer"  $\mapsto id_r$ ])
# Model related
ELIF  $expr_1$  <: tensorflow.keras.Model THEN
  ( $id_r$  =  $expr_1$  ( $expr_{11}$  ...  $expr_{1n}$  ( $id_2$  = )?  $expr_{21}$  ... ( $id_k$  = )?  $expr_{2k}$ )],  $\sigma$ ["model"  $\mapsto id_r$ ])
ELIF  $id_m$  = "model" AND  $expr_1$  =  $id_t$ .evaluate THEN
  IF  $id_i$  = verbose WHEN  $1 \leq i \leq k$  THEN
    ( $id_r$  =  $expr_1$  ( $expr_{11}$  ...  $expr_{1n}$  ( $id_1$  = )?  $expr_{21}$  ...  $id_i$  = 1 if hvd.rank() == 0 else 0
    ... ( $id_k$  = )?  $expr_{2k}$ ) (#type:s)?],  $\sigma$ )
  ELSE
    ( $id_r$  =  $expr_1$  ( $expr_{11}$   $expr_{12}$  1 if hvd.rank() == 0 else 0 ...  $expr_{1n}$ 
    ( $id_1$  = )?  $expr_{21}$  ... ( $id_k$  = )?  $expr_{2k}$ ) (#type:s)?],  $\sigma$ )
# Checkpoint
ELIF  $\sigma$ ("tensor_flow") =  $id_t$  AND  $expr_1$  =  $id_t$ .train.Checkpoint THEN
  ( $id_r$  =  $expr_1$  ( $expr_{11}$  ...  $expr_{1n}$  ( $id_1$  = )?  $expr_{21}$  ... ( $id_k$  = )?  $expr_{2k}$ ) (#type:s)?],
   $\sigma$ ["checkpoint"  $\mapsto id_r$ ])
# Default

```

ELSE $([id_r = trans_E \llbracket expr_1 (expr_{11} \dots expr_{1n} (id_2 =)? expr_{21} \dots (id_k =)? expr_{2k} \rrbracket (\sigma) (\#type:s)?], \sigma)$

$trans_S \llbracket expr_0 = expr_1 (\#type:s)? \rrbracket (\sigma) =$
IF $\sigma(\text{"os"}) = id_{os}$ **AND** $expr_0 = id_{os}.\text{environ} [\text{'CUDA_VISIBLE_DEVICES'}]$
THEN $([], \sigma)$

A general form of assignment statements except for the strict form

$trans_S \llbracket expr_1^* = expr_2 (\#type:s)? \rrbracket (\sigma) = ([expr_1^* = trans_E \llbracket expr_2 \rrbracket (\sigma) (\#type:s)?], \sigma)$

$trans_S \llbracket expr_1 \text{ binop } = expr_2 \rrbracket (\sigma) = ([expr_1 \text{ binop } = trans_E \llbracket expr_2 \rrbracket (\sigma)], \sigma)$

$trans_S \llbracket expr_1 : expr_2 (= expr_3)? \rrbracket (\sigma) =$
 $\# \text{ Dataset}$
IF $expr_1 = id_1$ **AND** $\sigma(\text{"tensor_flow"}) = id_2$
AND $expr_3 = id_2.\text{data.Dataset.expr}_4 (expr_5^* \text{ keyword}^*)$ **THEN**
 $([expr_1 : expr_2 = expr_3 (\#type:s)?], \sigma[\text{"dataset"} \mapsto id_1])$
ELSE $([expr_1 : expr_2 (= trans_E \llbracket expr_3 \rrbracket (\sigma))?), \sigma)$

$trans_S \llbracket (\#type:s)? \text{ for } expr_1 \text{ in } expr_2 : stmt_1^* (\text{else} : stmt_2^*)? \rrbracket (\sigma) =$
 $([(\#type:s)? \text{ for } expr_1 \text{ in } trans_E \llbracket expr_2 \rrbracket (\sigma) :$
 $trans_{\bar{S}} \llbracket stmt_1^* \rrbracket (\sigma).1 (\text{else} : trans_{\bar{S}} \llbracket stmt_2^* \rrbracket (\sigma).1)?], \sigma)$

$trans_S \llbracket (\#type:s)? \text{ async for } expr_1 \text{ in } expr_2 : stmt_1^* (\text{else} : stmt_2^*)? \rrbracket (\sigma) =$
 $([(\#type:s)? \text{ async for } expr_1 \text{ in } trans_E \llbracket expr_2 \rrbracket (\sigma) :$
 $trans_{\bar{S}} \llbracket stmt_1^* \rrbracket (\sigma).1 (\text{else} : trans_{\bar{S}} \llbracket stmt_2^* \rrbracket (\sigma).1)?], \sigma)$

$trans_S \llbracket \text{while } (expr) : stmt_1^* (\text{else} : stmt_2^*)? \rrbracket (\sigma) =$
 $([\text{while } (trans_E \llbracket expr \rrbracket (\sigma)) : trans_{\bar{S}} \llbracket stmt_1^* \rrbracket (\sigma).1 (\text{else} : trans_{\bar{S}} \llbracket stmt_2^* \rrbracket (\sigma).1)?], \sigma)$

$trans_S \llbracket \text{if } (expr) : stmt^* (\text{else} : stmt^*)? \rrbracket (\sigma) =$
 $([\text{if } (trans_E \llbracket expr \rrbracket (\sigma)) : trans_{\bar{S}} \llbracket stmt^* \rrbracket (\sigma).1 (\text{else} : trans_{\bar{S}} \llbracket stmt^* \rrbracket (\sigma).1)?], \sigma)$

$trans_S \llbracket (\#type:s)? \text{ with } with_item^* : stmt^* \rrbracket (\sigma) =$
LET $with_item^{*'}, \sigma_1 = trans_{\bar{W}} \llbracket with_item^* \rrbracket (\sigma)$ **IN**
LET $stmt^{*'}, \sigma_2 = trans_{\bar{S}} \llbracket stmt^* \rrbracket (\sigma_1)$ **IN**
IF $\sigma_1 \setminus \sigma = [\text{"gradient_tape"} \mapsto id]$ **THEN**
 $([(\#type:s)? \text{ with } with_item^{*'} : stmt^{*'},$
 $id = \text{hvd.DistributedGradientTape}(id)], \sigma_2)$
ELSE $([(\#type:s)? \text{ with } with_item^{*'} : stmt^{*'}], \sigma_2)$


```

transS[(#type:s)? async with with_item* : stmt*](σ) =
  LET with_item*', σ1 = transW[with_item*](σ) IN
  LET stmt*', σ2 = transS[stmt*](σ1) IN
  IF σ1 \ σ = ["gradient_tape" ↦ id] THEN
    (([#type:s)? async with with_item*' : stmt*',
      id = hvd.DistributedGradientTape(id)], σ2)
  ELSE (([#type:s)? async with with_item*' : stmt*'], σ2)

transS[match expr : match_case*](σ) =
  ([match transE[expr](σ) : (transC[match_case](σ))*], σ)

transS[raise expr1? (from expr2)?](σ) = ([raise expr1? (from expr2)?], σ)

transS[try : stmt1* exc_handler* (else : stmt2)*? (finally : stmt3)*?](σ) =
  ([try : transS[stmt1](σ).1 (transH[exc_handler](σ))*
    (else : transS[stmt2](σ).1)? (finally : transS[stmt3](σ).1)?], σ)

transS[assert expr1 expr2?](σ) = ([assert transE[expr1](σ) expr2?], σ)

transS[import alias*](σ) =
  LET σ1 = transA[alias*](σ) IN
  IF σ1 \ σ = ["tensor_flow" ↦ id] THEN
    ([import alias*,
      import horovod.tensorflow as hvd,
      hvd.broadcast_done = False,
      hvd.init(),
      gpus = id.config.experimental.list_physical_devices('GPU'),
      for gpu in gpus: id.config.experimental.set_memory_growth(gpu, True),
      if gpus: id.config.experimental.set_visible_devices(gpus[hvd.local_rank()], 'GPU')], σ1)
  ELSE ([import alias*], σ1)

transS[import alias*](σ) =
  LET σ1 = transA[alias*](σ) IN
  IF σ1 \ σ = ["tensor_flow" ↦ id] THEN
    ([import alias*,
      import horovod.tensorflow as hvd,
      hvd.init(),
      gpus = id.config.experimental.list_physical_devices('GPU'),
      for gpu in gpus: id.config.experimental.set_memory_growth(gpu, True),
      if gpus: id.config.experimental.set_visible_devices(gpus[hvd.local_rank()], 'GPU')], σ1)
  ELSE ([import alias*], σ1)

```

```

transS[[ from i id? import alias* ]](σ) =
  LET σ1 = transA[[ alias* ]](σ) IN
  IF id = tensorflow AND σ1 \ σ = ["keras" ↦ id] THEN
    ([from i id? import alias*,
     import horovod.tensorflow.keras as hvd,
     hvd.init(),
     gpus = id.config.experimental.list_physical_devices('GPU'),
     for gpu in gpus: id.config.experimental.set_memory_growth(gpu, True),
     if gpus: id.config.experimental.set_visible_devices(gpus[hvd.local_rank()], 'GPU')], σ1)
  ELSE ([from i id? import alias*], σ1)

```

```

transS[[ global id* ]](σ) = ([global id*], σ)

```

```

transS[[ nonlocal id* ]](σ) = ([nonlocal id*], σ)

```

A strict form of expr statements

```

transS[[ expr1 (expr11 ... expr1n (id1 = )? expr21 ... (idk = )? expr2k) ]](σ) =
  IF σ("optimizer") = idt AND expr1 = idt.apply_gradients THEN
    IF idi = grads_and_vars WHEN 1 ≤ i ≤ k THEN
      LET idz = NewID() IN
      ([idz = expr2i,
       expr1 (expr11 ... expr1n (id1 = )? expr21 ... idi = idz ... (idk = )? expr2k),
       global hvd_broadcast_done,
       if not hvd_broadcast_done: [ hvd.broadcast_variables([x[1] for x in idz], root_rank=0),
        hvd.broadcast_variables(idt.variables(), root_rank=0),
        hvd_broadcast_done = True ], σ)
      ELSE
        LET idz = NewID() IN
        ([idz = expr11,
         expr1 (idz expr12 ... expr1n (id1 = )? expr21 ... (idk = )? expr2k),
         global hvd_broadcast_done,
         if not hvd_broadcast_done: [ hvd.broadcast_variables([x[1] for x in idz], root_rank=0),
          hvd.broadcast_variables(idt.variables(), root_rank=0),
          hvd_broadcast_done = True ], σ)
    ELIF expr1 = print OR expr1 = expr.write OR expr1 = expr.summary OR
      expr1 = expr.save_weights OR expr1 = expr.load_weights THEN
      ([if hvd.rank() == 0: expr1 (expr11 ... expr1n (id1 = )? expr21 ... (idk = )? expr2k)], σ)
    ELIF σ("checkpoint") = idt AND expr1 = idt.save THEN
      ([if hvd.rank() == 0: [expr1 (expr11 ... expr1n (id1 = )? expr21 ... (idk = )? expr2k)]], σ)
    ELIF σ("model") = idt AND expr1 = idt.fit THEN
      IF idi = verbose WHEN 1 ≤ i ≤ k THEN
        IF idj = callbacks WHEN 1 ≤ j ≤ k THEN
          ([callback = [hvd.callbacks.BroadcastGlobalVariablesCallback(root_rank=0)]

```

```

    if hvd.rank() == 0: callbacks.append(expr2j)
    expr1 (expr11 ... expr1n (id1 = )? expr21 ... idi = 1 if hvd.rank() == 0 else 0
    ... idj = callbacks ... (idk = )? expr2k), σ)
ELSE
    ([expr1 (expr11 ... expr1n (id1 = )? expr21 ...
    idi = 1 if hvd.rank() == 0 else 0 ... (idk = )? expr2k
    callbacks = [hvd.callbacks.BroadcastGlobalVariablesCallback(root_rank=0)]), σ)
ELSE
    IF idj = callbacks WHEN 1 ≤ j ≤ k THEN
        ([callback = [hvd.callbacks.BroadcastGlobalVariablesCallback(root_rank=0)]
        if hvd.rank() == 0: callbacks.append(expr2j)
        expr1 (expr11 ... expr1n (id1 = )? expr21 ... idj = callbacks ... (idk = )? expr2k
        verbose = 1 if hvd.rank() == 0 else 0)], σ)
    ELSE
        ([expr1 (expr11 ... expr1n (id1 = )? expr21 ... (idk = )? expr2k
        verbose = 1 if hvd.rank() == 0 else 0
        callbacks = [hvd.callbacks.BroadcastGlobalVariablesCallback(0)]), σ)
ELIF σ("model") = idt AND expr1 = idt.compile THEN
    IF idi = optimizer AND expr2i = "adam" WHEN 1 ≤ i ≤ k THEN
        ([idz = tf.optimizers.Adam(learning_rate=0.001 * hvd.size())
        idz = hvd.DistributedOptimizer(idz)
        expr1 (expr11 ... expr1n (id1 = )? expr21 ... idi = idz ... (idk = )? expr2k), σ)
    ELIF expr11 = "adam" THEN
        ([idz = tf.optimizers.Adam(learning_rate=0.001 * hvd.size())
        idz = hvd.DistributedOptimizer(idz)
        expr1 (idz ... expr1n (id1 = )? expr21 ... (idk = )? expr2k), σ)
    ELSE
        [transE[[expr1 (expr11 ... expr1n (id1 = )? expr21 ... (idk = )? expr2k) ]](σ), σ)
ELIF expr1 = model.summary THEN
        ([if hvd.rank() == 0: expr1 (expr11 ... expr1n (id1 = )? expr21 ... (idk = )? expr2k), σ)
ELSE
        [transE[[expr1 (expr11 ... expr1n (id1 = )? expr21 ... (idk = )? expr2k) ]](σ), σ)

```

A general form of expr statements except for the strict form

$trans_S[[expr]](\sigma) = ([trans_E[[expr]](\sigma)], \sigma)$

$trans_S[[pass]](\sigma) = ([pass], \sigma)$

$trans_S[[break]](\sigma) = ([break], \sigma)$

$trans_S[[continue]](\sigma) = ([continue], \sigma)$

$trans_E : Expr \rightarrow \Sigma \rightarrow Expr$
--

$$\text{trans}_E \llbracket \text{expr}_1 \text{ boolop } \text{expr}_2 \rrbracket(\sigma) = \text{trans}_E \llbracket \text{expr}_1 \rrbracket(\sigma) \text{ boolop } \text{trans}_E \llbracket \text{expr}_2 \rrbracket(\sigma)$$

$$\text{trans}_E \llbracket \text{expr}_1 \text{ := } \text{expr}_2 \rrbracket(\sigma) = \text{expr}_1 \text{ := } \text{trans}_E \llbracket \text{expr}_2 \rrbracket(\sigma)$$

$$\text{trans}_E \llbracket \text{expr}_1 \text{ binop } \text{expr}_2 \rrbracket(\sigma) = \text{trans}_E \llbracket \text{expr}_1 \rrbracket(\sigma) \text{ binop } \text{trans}_E \llbracket \text{expr}_2 \rrbracket(\sigma)$$

$$\text{trans}_E \llbracket \text{unop } \text{expr} \rrbracket(\sigma) = \text{unop } \text{trans}_E \llbracket \text{expr} \rrbracket(\sigma)$$

$$\text{trans}_E \llbracket \text{lambda } \text{args} : \text{expr} \rrbracket(\sigma) = \text{lambda } \text{args} : \text{trans}_E \llbracket \text{expr} \rrbracket(\sigma)$$

$$\begin{aligned} \text{trans}_E \llbracket \text{expr}_1 \text{ if } \text{expr}_2 \text{ else } \text{expr}_3 \rrbracket(\sigma) = \\ \text{trans}_E \llbracket \text{expr}_1 \rrbracket(\sigma) \text{ if } \text{trans}_E \llbracket \text{expr}_2 \rrbracket(\sigma) \text{ else } \text{trans}_E \llbracket \text{expr}_3 \rrbracket(\sigma) \end{aligned}$$

$$\begin{aligned} \text{trans}_E \llbracket \text{expr}_1 \text{ if } \text{expr}_2 \text{ else } \text{expr}_3 \rrbracket(\sigma) = \\ \text{trans}_E \llbracket \text{expr}_1 \rrbracket(\sigma) \text{ if } \text{trans}_E \llbracket \text{expr}_2 \rrbracket(\sigma) \text{ else } \text{trans}_E \llbracket \text{expr}_3 \rrbracket(\sigma) \end{aligned}$$

$$\text{trans}_E \llbracket \{(\text{expr}_1 : \text{expr}_2)^* (**\text{expr}_3)^*\} \rrbracket(\sigma) = \{(\text{expr}_1 : \text{trans}_E \llbracket \text{expr}_2 \rrbracket(\sigma))^* (**\text{expr}_3)^*\}$$

$$\text{trans}_E \llbracket \{\text{expr}^*\} \rrbracket(\sigma) = \{(\text{trans}_E \llbracket \text{expr} \rrbracket(\sigma))^*\}$$

$$\text{trans}_E \llbracket [\text{expr}^*] \rrbracket(\sigma) = [(\text{trans}_E \llbracket \text{expr} \rrbracket(\sigma))^*]$$

$$\text{trans}_E \llbracket (\text{expr}^*) \rrbracket(\sigma) = ((\text{trans}_E \llbracket \text{expr} \rrbracket(\sigma))^*)$$

$$\text{trans}_E \llbracket \{\text{expr}_1 : \text{expr}_2 \text{ comprehension}^*\} \rrbracket(\sigma) = \{\text{expr}_1 : \text{trans}_E \llbracket \text{expr}_2 \rrbracket(\sigma) (\text{trans}_O \llbracket \text{comprehension} \rrbracket(\sigma))^*\}$$

$$\text{trans}_E \llbracket \{\text{expr} \text{ comprehension}^*\} \rrbracket(\sigma) = \{\text{trans}_E \llbracket \text{expr} \rrbracket(\sigma) (\text{trans}_O \llbracket \text{comprehension} \rrbracket(\sigma))^*\}$$

$$\text{trans}_E \llbracket [\text{expr} \text{ comprehension}^*] \rrbracket(\sigma) = [(\text{trans}_E \llbracket \text{expr} \rrbracket(\sigma) (\text{trans}_O \llbracket \text{comprehension} \rrbracket(\sigma))^*)]$$

$$\text{trans}_E \llbracket (\text{expr} \text{ comprehension}^*) \rrbracket(\sigma) = (\text{trans}_E \llbracket \text{expr} \rrbracket(\sigma) (\text{trans}_O \llbracket \text{comprehension} \rrbracket(\sigma))^*)$$

$$\text{trans}_E \llbracket \text{await } \text{expr} \rrbracket(\sigma) = \text{await } \text{trans}_E \llbracket \text{expr} \rrbracket(\sigma)$$

$$\text{trans}_E \llbracket \text{yield } \text{expr}? \rrbracket(\sigma) = \text{yield } (\text{trans}_E \llbracket \text{expr} \rrbracket(\sigma))?$$

$$\text{trans}_E \llbracket \text{yield from } \text{expr} \rrbracket(\sigma) = \text{yield from } \text{trans}_E \llbracket \text{expr} \rrbracket(\sigma)$$

$$\text{trans}_E \llbracket \text{expr}_1 (\text{compop } \text{expr}_2)^* \rrbracket(\sigma) = \text{trans}_E \llbracket \text{expr}_1 \rrbracket(\sigma) (\text{compop } \text{trans}_E \llbracket \text{expr}_2 \rrbracket(\sigma))^*$$

$$\begin{aligned}
& trans_E \llbracket expr_1 (expr_{11} \dots expr_{1n} \ (id_1 =)? \ expr_{21} \dots (id_k =)? \ expr_{2k}) \rrbracket(\sigma) = \\
& \quad \text{IF } \sigma(\text{“dataset”}) = id_t \text{ AND } expr_1 = id_t.\text{take} \text{ THEN} \\
& \quad \quad \text{IF } id_i = \text{count} \text{ WHEN } 1 \leq i \leq k \text{ THEN} \\
& \quad \quad \quad expr_1 (expr_{11} \dots expr_{1n} \ (id_1 =)? \ expr_{21} \dots id_i = expr_{2i} // \text{hvd.size}() \dots (id_k =)? \ expr_{2k}) \\
& \quad \quad \text{ELSE} \\
& \quad \quad \quad expr_1 (expr_{11} // \text{hvd.size}() \dots expr_{1n} \ (id_1 =)? \ expr_{21} \dots (id_k =)? \ expr_{2k}) \\
& \quad \text{ELSE} \\
& \quad \quad trans_E \llbracket expr_1 \rrbracket(\sigma) (trans_E \llbracket expr_{11} \rrbracket(\sigma) \dots trans_E \llbracket expr_{1n} \rrbracket(\sigma) \\
& \quad \quad \quad (id_1 =)? \ trans_E \llbracket expr_{21} \rrbracket(\sigma) \dots (id_k =)? \ trans_E \llbracket expr_{2k} \rrbracket(\sigma)) \\
\\
& trans_E \llbracket \{expr_1 \quad (!i)? \quad (:expr_2)?\} \rrbracket(\sigma) = \{expr_1 \quad (!i)? \quad (:expr_2)?\} \\
\\
& trans_E \llbracket expr^* \rrbracket(\sigma) = expr^* \\
\\
& trans_E \llbracket constant \rrbracket(\sigma) = constant \\
\\
& trans_E \llbracket expr.id \rrbracket(\sigma) = (trans_E \llbracket expr \rrbracket(\sigma)).id \\
\\
& trans_E \llbracket expr_1[expr_2] \rrbracket(\sigma) = trans_E \llbracket expr_1 \rrbracket(\sigma)[trans_E \llbracket expr_2 \rrbracket(\sigma)] \\
\\
& trans_E \llbracket *expr \rrbracket(\sigma) = *expr \\
\\
& trans_E \llbracket **expr \rrbracket(\sigma) = **expr \\
\\
& trans_E \llbracket id \rrbracket(\sigma) = id \\
\\
& trans_E \llbracket expr_1? \ (:expr_2)? \ (:expr_3)? \rrbracket(\sigma) = trans_E \llbracket expr_1 \rrbracket(\sigma)? \ (:trans_E \llbracket expr_2 \rrbracket(\sigma))? \ (:trans_E \llbracket expr_3 \rrbracket(\sigma))? \\
\\
& \boxed{trans_O : Comprehension \rightarrow \Sigma \rightarrow Comprehension} \\
& trans_O \llbracket \text{for } expr_1 \text{ in } expr_2 \text{ (if } expr_3)^* \rrbracket(\sigma) = \text{for } expr_1 \text{ in } trans_E \llbracket expr_2 \rrbracket(\sigma) \text{ (if } trans_E \llbracket expr_3 \rrbracket(\sigma))^* \\
\\
& \boxed{trans_H : ExcHandler \rightarrow \Sigma \rightarrow ExcHandler} \\
& trans_H \llbracket \text{except } expr? \text{ (as } id)? : stmt^* \rrbracket(\sigma) = \text{except } expr? \text{ (as } id)? : trans_{\bar{S}} \llbracket stmt^* \rrbracket(\sigma).\text{1} \\
\\
& \boxed{trans_{\bar{A}} : Alias \text{ list} \rightarrow \Sigma \rightarrow \Sigma} \\
& trans_{\bar{A}} \llbracket alias_1 \dots alias_{n-1} alias_n \rrbracket(\sigma) = trans_A \llbracket alias_n \rrbracket(trans_A \llbracket alias_{n-1} \rrbracket(\dots trans_A \llbracket alias_1 \rrbracket(\sigma))) \\
\\
& \boxed{trans_A : Alias \rightarrow \Sigma \rightarrow \Sigma}
\end{aligned}$$

$trans_A \llbracket id \rrbracket(\sigma) =$
LET $id = \text{tensorflow}$ **THEN** $\sigma[\text{"tensorflow"} \mapsto id]$
LET $id = \text{keras}$ **THEN** $\sigma[\text{"keras"} \mapsto id]$
LET $id = \text{os}$ **THEN** $\sigma[\text{"os"} \mapsto id]$
LET $id = \text{optimizers}$ **THEN** $\sigma[\text{"optimizers"} \mapsto id]$
ELSE σ

$trans_A \llbracket id_1 \text{ as } id_2 \rrbracket(\sigma) =$
LET $id_1 = \text{tensorflow}$ **THEN** $\sigma[\text{"tensorflow"} \mapsto id_2]$
LET $id_1 = \text{tensorflow.keras}$ **THEN** $\sigma[\text{"keras"} \mapsto id_2]$
LET $id_1 = \text{os}$ **THEN** $\sigma[\text{"os"} \mapsto id_2]$
LET $id = \text{optimizers}$ **THEN** $\sigma[\text{"optimizers"} \mapsto id]$
ELSE σ

$trans_A \llbracket id_1 . id_2 (.id_3)^* (\text{as } id_2)? \rrbracket(\sigma) = \sigma$

$trans_{\overline{W}} : WithItem \text{ list} \rightarrow \Sigma \rightarrow (WithItem \text{ list} \times \Sigma)$

$trans_{\overline{W}} \llbracket with_item_1 with_item_2 \dots with_item_n \rrbracket(\sigma) =$
LET $with_item_1', \sigma_1 = trans_W \llbracket with_item_1 \rrbracket(\sigma)$ **IN**
LET $with_item_2', \sigma_2 = trans_W \llbracket with_item_2 \rrbracket(\sigma_1)$ **IN**
 \dots
LET $with_item_n', \sigma_n = trans_W \llbracket with_item_n \rrbracket(\sigma_{n-1})$ **IN**
 $(with_item_1' :: with_item_2' :: \dots :: [with_item_n'], \sigma_n)$

$trans_W : WithItem \rightarrow \Sigma \rightarrow (WithItem \times \Sigma)$

$trans_W \llbracket expr \rrbracket(\sigma) = (trans_E \llbracket expr \rrbracket(\sigma), \sigma)$

$trans_W \llbracket expr_1 \text{ as } expr_2 \rrbracket(\text{smodenv}) =$
IF $\sigma[\text{"tensorflow"}] = id_1$ **AND** $expr_1 = id_1.\text{GradientTape}()$ **AND** $expr_2 = id_2$ **THEN**
 $(expr_1 \text{ as } expr_2, \sigma[\text{"gradient_tape"} \mapsto id_2])$
ELSE $(trans_E \llbracket expr_1 \rrbracket(\sigma) \text{ as } expr_2, \sigma)$

$trans_C : MatchCase \rightarrow \Sigma \rightarrow MatchCase$

$trans_C \llbracket \text{case pattern (if expr)? : stmt}^* \rrbracket(\sigma) =$
 $\text{case } trans_P \llbracket pattern \rrbracket(\sigma) \text{ (if } trans_E \llbracket expr \rrbracket(\sigma))? : trans_{\overline{S}} \llbracket stmt^* \rrbracket(\sigma).1$

$trans_P : Pattern \rightarrow \Sigma \rightarrow Pattern$

$trans_P \llbracket expr \rrbracket(\sigma) = trans_E \llbracket expr \rrbracket(\sigma)$

$trans_P \llbracket constant \rrbracket(\sigma) = constant$

$trans_P \llbracket [pattern]^* \rrbracket(\sigma) = [trans_P \llbracket pattern \rrbracket(\sigma)]^*$

$$\text{trans}_P \llbracket \star(id)? \rrbracket(\sigma) = \star(id)?$$

$$\text{trans}_P \llbracket \{(expr : pattern)^* id?\} \rrbracket(\sigma) = \{(expr : \text{trans}_P \llbracket pattern \rrbracket(\sigma))^* id?\}$$

$$\text{trans}_P \llbracket expr \ (pattern_1^* (id = pattern_2)^*) \rrbracket(\sigma) = expr \ (\text{trans}_P \llbracket pattern_1 \rrbracket(\sigma)^* (id = \text{trans}_P \llbracket pattern_2 \rrbracket(\sigma))^*)$$

$$\text{trans}_P \llbracket (pattern \ \text{as})? id \rrbracket(\sigma) = (\text{trans}_P \llbracket pattern \rrbracket(\sigma) \ \text{as})? id$$

$$\text{trans}_P \llbracket pattern_1 \mid pattern_2 \rrbracket(\sigma) = \text{trans}_P \llbracket pattern_1 \rrbracket(\sigma) \mid \text{trans}_P \llbracket pattern_2 \rrbracket(\sigma)$$

$$\text{trans}_P \llbracket - \rrbracket(\sigma) = -$$

3 Identifying trainig loop

3.1 Restrictions

1. Training loop must be defined in only one file.
2. Training loop type is either `distributed gradient tape` or `distributed optimizer`.
3. Each model must have only one type of training loop.
4. Function must not be assigned to the variables or passed as an argument.
5. Training loop must not be defined conditionally.

3.2 Rules

3.2.1 Summary

$$\begin{aligned}
\text{Summary} &::= \text{ModuleSummary } id \ \sigma_{\top} \ tl && (\text{MODULESUMMARY}) \\
&\quad \text{FuncSummary } tl && (\text{FUNCSUMMARY}) \\
&\quad \text{ClassSummary } arg && (\text{CLASSSUMMARY}) \\
&\quad \text{ValueSummary } s && (\text{VALUESUMMARY}) \\
arg &::= Model \mid \perp && (\text{ARG}) \\
tl &::= GradTape \mid Optimizer \mid \perp && (\text{TRAININGLOOP}) \\
\sigma_{\top} &::= \sigma \cup \top
\end{aligned}$$

$$\sigma \in \Sigma = Id \xrightarrow{\text{fin}} \text{Summary} \quad \text{ENVIRONMENT STORING MAPPINGS FROM IDS TO SUMMARIES}$$

3.2.2 Training Loop

$summary_M : Module \rightarrow \Sigma \rightarrow ModuleSummary$

$summary_M \llbracket id \text{ stmt}^* \text{ type_ignore} \rrbracket =$
LET $\sigma, tl = summary_{\bar{S}} \llbracket stmt^* \rrbracket(\sigma)$ **IN**
 ModuleSummary $id \ \sigma \ tl$

$summary_{\bar{S}} : Stmt \ list \rightarrow \Sigma \rightarrow (\Sigma \times tl)$

$summary_{\bar{S}} \llbracket stmt_1 \ stmt_2 \dots stmt_n \rrbracket(\sigma) =$ **LET** $\sigma_1, tl_1 = summary_S \llbracket stmt_1 \rrbracket(\sigma)$ **IN**
LET $\sigma_2, tl_2 = summary_{\bar{S}} \llbracket stmt_2 \rrbracket(\sigma_1)$ **IN**
 \dots
LET $\sigma_n, tl_n = summary_{\bar{S}} \llbracket stmt_n \rrbracket(\sigma_{n-1})$ **IN**
 $(\sigma_n, tl_1 \sqcup tl_2 \sqcup \dots tl_n)$

$summary_S : Stmt \rightarrow \Sigma \rightarrow (\Sigma \times tl)$
--

$summary_S \llbracket (@expr_1)^* \text{ def } id \ (args) \ (-> expr_2)^? : (\#type:s)^? \ stmt^* \rrbracket(\sigma) =$
LET $\sigma', tl = summary_{\bar{S}} \llbracket stmt^* \rrbracket$ **IN**
 $(\sigma[id \mapsto \text{FuncSummary } tl], \perp)$

$summary_S \llbracket (@expr_1)^* \text{ async def } id \ (args) \ (-> expr_2)^? : (\#type:s)^? \ stmt^* \rrbracket(\sigma) =$
LET $\sigma', tl = summary_{\bar{S}} \llbracket stmt^* \rrbracket$ **IN**
 $(\sigma[id \mapsto \text{FuncSummary } tl], \perp)$

$summary_S \llbracket (@expr)^* \text{ class } id \ (expr_{11} \dots expr_{1n} \ (id_1 =)^? \ expr_{21} \dots (id_k =)^? \ expr_{2k}) : stmt^* \rrbracket(\sigma) =$
IF $expr_{1i} = id_c.keras.Model$ **WHEN** $1 \leq i \leq n$ **AND**
 $\sigma(id_c) = \text{ModuleSummary Id("tensorflow")}$ **THEN** $(\sigma[id \mapsto \text{ClassSummary Model}], \perp)$
ELIF $expr_{2i} = id_c.keras.Model$ **WHEN** $1 \leq i \leq k$ **AND**
 $\sigma(id_c) = \text{ModuleSummary Id("tensorflow")}$ **THEN** $(\sigma[id \mapsto \text{ClassSummary Model}], \perp)$
ELSE $(\sigma[id \mapsto \text{ClassSummary } \perp], \perp)$

A strict form of assignment statements

$summary_S \llbracket id_r = id_c \ () \ (\#type:s)^? \rrbracket(\sigma) =$
IF $\sigma(id_c) = \text{ClassSummary Model}$ **THEN** $(\sigma[id_r \mapsto \text{ValueSummary "model.instance"}], \perp)$
ELSE (σ, \perp)

$summary_S \llbracket (\#type:s)^? \text{ for } expr_1 \text{ in } expr_2 : stmt_1^* \text{ (else : } stmt_2^*)^? \rrbracket(\sigma) =$
LET $_, tl = summary_{\bar{S}} \llbracket stmt_1^* \rrbracket(\sigma)$ **IN**
 (σ, tl)

$summary_S \llbracket (\#type:s)^? \text{ async for } expr_1 \text{ in } expr_2 : stmt_1^* \text{ (else : } stmt_2^*)^? \rrbracket(\sigma) =$
LET $_, tl = summary_{\bar{S}} \llbracket stmt_1^* \rrbracket(\sigma)$ **IN**
 (σ, tl)

$summary_S \llbracket \text{while } (expr) : stmt_1^* \text{ (else : } stmt_2^*)^? \rrbracket(\sigma) =$
LET $_, tl = summary_{\bar{S}} \llbracket stmt_1^* \rrbracket(\sigma)$ **IN**
 (σ, tl)

$summary_S \llbracket (\#type:s)? \text{ with } with_item^* : stmt^* \rrbracket(\sigma) =$

LET $_, tl = summary_{\bar{S}} \llbracket stmt^* \rrbracket(\sigma)$ **IN**
 $(\sigma, summary_{\bar{W}} \llbracket with_item^* \rrbracket(\sigma) \sqcup tl)$

$summary_S \llbracket (\#type:s)? \text{ async with } with_item^* : stmt^* \rrbracket(\sigma) =$

LET $_, tl = summary_{\bar{S}} \llbracket stmt^* \rrbracket(\sigma)$ **IN**
 $(\sigma, summary_{\bar{W}} \llbracket with_item^* \rrbracket(\sigma) \sqcup tl)$

$summary_S \llbracket \text{ try } : stmt_1^* \text{ exc_handler}^* \text{ (else : } stmt_2^*)? \text{ (finally : } stmt_3^*)? \rrbracket(\sigma) =$
 $(\sigma, summary_{\bar{S}} \llbracket stmt_1^* \rrbracket(\sigma))$

$summary_S \llbracket \text{ import } alias^* \rrbracket(\sigma) = (summary_{\bar{A}} \llbracket alias^* \rrbracket(\sigma), \perp)$

$summary_S \llbracket \text{ from } 0 \text{ id}^* \text{ import } alias^* \rrbracket(\sigma) =$

LET $\sigma' = summary_{\bar{A}} \llbracket alias^* \rrbracket(\sigma)$ **IN**
LET $[id_2 \mapsto \text{ModuleSummary } id_2 \sigma_2 \perp, id_2 \mapsto \text{ModuleSummary } id_2 \sigma_2 \perp,$
 $\dots id_n \mapsto \text{ModuleSummary } id_n \sigma_n \perp] = \sigma' \setminus \sigma$ **IN**
 $\sigma ++ [id_2 \mapsto \text{ModuleSummary } (id^* + id_2) \sigma_2 \perp, id_2 \mapsto \text{ModuleSummary } (id^* + id_2) \sigma_2 \perp,$
 $\dots id_n \mapsto \text{ModuleSummary } (id^* + id_n) \sigma_n \perp]$

$summary_S \llbracket expr \rrbracket(\sigma) = (\sigma, summary_E \llbracket expr \rrbracket(\sigma))$

$summary_S \llbracket stmt \rrbracket(\sigma) = (\sigma, \perp)$

$summary_{\bar{A}} : Alias \text{ list} \rightarrow \Sigma \rightarrow \Sigma$

$summary_{\bar{A}} \llbracket alias_1 \dots alias_{n-1} alias_n \rrbracket(\sigma) =$
 $summary_A \llbracket alias_n \rrbracket(summary_A \llbracket alias_{n-1} \rrbracket(\dots summary_A \llbracket alias_1 \rrbracket(\sigma) \dots))$

$trans_A : Alias \rightarrow \Sigma \rightarrow \Sigma$

$trans_A \llbracket id_1 id_2 \dots id_n \rrbracket(\sigma) =$
LET $\sigma_n = [id_n \mapsto \text{ModuleSummary } id_n \top \perp]$
LET $\sigma_{n-1} = [id_{n-1} \mapsto \text{ModuleSummary } id_{n-1} \sigma_n \perp]$
 \dots
LET $\sigma_2 = [id_2 \mapsto \text{ModuleSummary } id_2 \sigma_3 \perp]$
LET $\sigma_1 = [id_1 \mapsto \text{ModuleSummary } id_1 \sigma_2 \perp]$
 $\sigma ++ \sigma_1$

$summary_{\bar{W}} : WithItem \text{ list} \rightarrow \Sigma \rightarrow tl$

$summary_{\bar{W}} \llbracket with_item_1 with_item_2 \dots with_item_n \rrbracket(\sigma) =$
 $summary_W \llbracket with_item_1 \rrbracket(\sigma) \sqcup summary_W \llbracket with_item_2 \rrbracket(\sigma) \sqcup \dots summary_W \llbracket with_item_n \rrbracket(\sigma)$

$summary_W : WithItem \rightarrow \Sigma \rightarrow tl$

$summary_W \llbracket expr_1 \text{ as } expr_2? \rrbracket(\sigma) = summary_E \llbracket expr_1 \rrbracket(\sigma)$

$summary_E : Expr \rightarrow \Sigma \rightarrow tl$
--

A strict form of call expression

$summary_E \llbracket expr_1 (expr_{11} \dots expr_{1n} (id_1 =)? expr_{21} \dots (id_k =)? expr_{2k}) \rrbracket(\sigma) =$

```

  IF  $\sigma(id_r) = \text{ValueSummary "model\_instance"}$  AND
     $expr_1 = id_r.\text{fit}$  THEN  $Optimizer$ 
  ELIF  $\sigma(id_r) = \text{ModuleSummary Id("tensorflow")}$   $\sigma' tl$  AND
     $expr_1 = id_r.\text{GradientTape}$  THEN  $GradTape$ 
  ELIF  $\sigma(id_r) = \text{FuncSummary } tl$  AND
     $expr_1 = id_r$  THEN  $tl$ 
  ELSE  $\perp$ 

```

$summary_E \llbracket expr \rrbracket(\sigma) = \perp$