


Hey Yocto, build me a custom embedded Linux! Er, no

An introduction to building a custom embedded Linux
with the awesome Yocto Project

whoami

I'm Kaiwan, the author of a few of books on Linux (see next). Am happy that a few are listed in the *Published Books* section of the official kernel docs:

[linux/Documentation/process/kernel-docs.rst](https://github.com/torvalds/linux/blob/master/Documentation/process/kernel-docs.rst) at master



The screenshot shows the GitHub repository for the Linux kernel documentation, specifically the 'kernel-docs.rst' file. The left sidebar shows a list of files, with 'kernel-docs.rst' selected. The main content area displays the 'Preview' of the file, showing three book entries with their metadata.

linux / Documentation / process / kernel-docs.rst

370 Lines (291 loc) · 14 KB

Preview Code Blame

- Title:** Linux Kernel Debugging: Leverage proven tools and advanced techniques to effectively debug Linux kernels and kernel modules
- Author:** Kaiwan N Billimoria
- Publisher:** Packt Publishing Ltd
- Date:** August, 2022
- Pages:** 638
- ISBN:** 978-1801075039
- Notes:** Debugging book

- Title:** Linux Kernel Programming: A Comprehensive Guide to Kernel Internals, Writing Kernel Modules, and Kernel Synchronization
- Author:** Kaiwan N Billimoria
- Publisher:** Packt Publishing Ltd
- Date:** March, 2021 (Second Edition published in 2024)
- Pages:** 754
- ISBN:** 978-1789953435 (Second Edition ISBN is 978-1803232225)
- Title:** Linux Kernel Programming Part 2 - Char Device Drivers and Kernel Synchronization: Create user-kernel interfaces, work with peripheral I/O, and handle hardware interrupts
- Author:** Kaiwan N Billimoria
- Publisher:** Packt Publishing Ltd
- Date:** March, 2021
- Pages:** 452
- ISBN:** 978-1801079518

whoami


- Kaiwan N Billimoria: profile all-in-one :

<https://bit.ly/m/kaiwan>



My Books!

Top Kaiwan N Billimoria titles




Linux Kernel Programming: A comprehensive and
★★★★☆ 20



Linux Kernel Programming Part 2 - Char Device
★★★★☆ 113



Linux Kernel Debugging: Leverage proven
★★★★☆ 16




Linux Kernel Programming - Second Edition: A
★★★★☆ 20



Hands-On System Programming with Linux: Explore
★★★★☆ 20

- ★ [LinkedIn public profile](#)
- ★ [My Amazon Author page](#)
- ★ Corporate Training on Linux
 - [Brief](#)
 - [More detailed](#)
- ★ [My GitHub repos](#)
- ★ [My tech blog](#)



We provide both

- Corporate training, and
- Online Training to Individuals. Please visit <https://kaiwantech.com>

Agenda

- Intro to the Yocto Project
- Yocto releases
- What Yocto actually does...
- The Layer model - an overview
- Workspace setup (old way) and modern recommended ≥ 5.3 way
- Demo embedded Linux system (Qemu AArch64) build and try
- The Layer-Recipe template - an overview
 - 'Hello, world' - A quick layer:recipe demo
- Pro Tips!
 - The actual Yocto philosophy: distro $\times$ image $\times$ machine , and many more!
- Appendix

GitHub repo for this presentation

https://github.com/kaiwan/yocto_intro


(Within it are a demo layer:recipe, plus extra docs that go into (much) more detail - used in the 'Embedded Linux with Yocto' training programme.)

YP (Yocto Project) website: <https://www.yoctoproject.org/>

Why the name 'Yocto'?

- *yocto-* is the smallest SI unit prefix
- Represents 10^{-24}
- Hey, it's (also) meant to build small embedded Linux systems, right!

More correctly: **“It's not an embedded Linux distribution, it creates a custom one for you.”**



Yocto/OE Project

- 100% reproducible builds (no 'magic script' / 'golden image'!)
- Layers:
 - Many (most) known board's - BSP layers are available
 - Many, many layers for well-known apps, utils, frameworks, security, etc
- QA tests builtin
- SBOM generation (EU CRA requirement!)
- Details:
 - [Features](#)
 - [Challenges](#)

DO see / read these (later):

- The Yocto Project – **introductory video** 2m:12s (Oct 2011): <https://youtu.be/utZpKM7i5Z4>
- [YPS 2023.11 - 2023/11/30 - Talel BELHAJSALEM - Back to basics | The ultimate Yocto introduction](#) (1h08m) - *excellent!*
- The complete, very detailed official [Yocto Project Concepts documentation](#) is a MUST Read!



<https://www.yoctoproject.org/development/releases/>

THE **LINUX** FOUNDATION PROJECTS

yocto
PROJECT

ABOUT ▾DOCS ▾DEVELOPMENT ▾COMMUNITY ▾NEWS & EVENTS ▾JOIN

Current Release Series

Codename	Series Version	Originally Released	Latest Release	Status	Downloads	Maintainer	Release Notes
Blacksail	6.1			Active Development		Richard Purdie	
Wrynose	6.0	April 2026	6.0.3 / August 2026	LTS until Apr. 2030	Download	Yoann Congal	Release Notes
Scarthgap	5.0	April 2024	5.0.19 / June 2026	LTS until Apr. 2028	Download	Yoann Congal	Release Notes

<https://www.yoctoproject.org/development/releases/>


Previous Release Series

Codename	Series Version	Originally Released	Latest Release	Status	Downloads	Release Notes
Whinlatter	5.3	November 2025	5.3.4 / April 2026	EOL	Download	Release Notes
Walnascar	5.2	April 2025	5.2.4 / September 2025	EOL	Download	Release Notes
Styhead	5.1	September 2024	5.1.4 / March 2025	EOL	Download	Release Notes
Nanbield	4.3	October 2023	4.3.4 / March 2024	EOL	Download	Release Notes
Mickledore	4.2	April 2023	4.2.4 / October 2023	EOL	Download	Release Notes
Langdale	4.1	October 2022	4.1.4 / March 2023	EOL	Download	Release Notes
Kirkstone	4.0	April 2022	4.0.35 / April 2026	EOL	Download	Release Notes

Why's the Whinlatter v5.3 highlighted? As it's the first ver where Poky isn't the default distro! (We'll see...)

The dark black rectangles represent the current releases (as of Dec 2025); releases are on a 6 month cadence.

Src: https://docs.yoctoproject.org/dev/_images/releases.svg




What Yocto actually does

- Any and every Linux system must *minimally* have:
 - a BootLoader (BL) image
 - a kernel image
 - if ARM*/PPC/RiscV/etc, a Device Tree Blob (DTB) image
 - a root filesystem (rootfs) image
 - C library
 - init manager
 - apps and utils
- The next two slides show that Yocto does generate ‘**images**’ - the ones just mentioned!
- This is - in a nutshell - the job of Yocto: **to generate these finished images**, populating their content as specified (via the config metadata: image & distro recipes, local config and the layers & recipes)
- In order to build them, Yocto also generates the *toolchain* as required!
- They’re flashed onto the target board, and voila, we (hopefully) have a running custom embedded Linux system!

What Yocto actually does

Simpler overall Yocto Project flow diagram (pic credit: [Bootlin](#))




Ultimately, the Yocto Project (YP) builds **packages** (ipk/rpm/deb); the packages are then extracted to make bootable image(s)

What Yocto actually does

- The Yocto Project (YP) builds **packages** (ipk/rpm/deb); the packages are then extracted to make bootable image(s)
- [Yocto : the canonical all-in-one diagram](#):

Q> How will the build system know things?
Which machine (& thus toolchain) to compile for, bootloader, DTS, kernel, package versions, C lib, init manager, etc?

A> The 'configuration metadata' provides it...




The Layer Model

[Source](#)



Hey Yocto, build me a custom embedded Linux! Er, no



[Src](#)

Familiarize yourself with the curated - tested and 'Yocto Project Compatible' certified - layers here:

[YOCTO PROJECT COMPATIBLE LAYER INDEX](#).



There is also the [OpenEmbedded layer index](#) which contains many more layers, recipes, BSPs, etc, but the content is less universally validated. Browse through <https://layers.openembedded.org>

OpenEmbedded Layer Index

Submit layer Log in

Branch: master ▾ Layers Recipes Machines Classes Distros

Search layers + Filter layers ▾

Layer name	Description	Type	Repository
openembedded-core 🇮🇳	Core metadata	Base	https://git.openembedded.org/openembedded-core
meta-oe 🇮🇳	Additional shared OE metadata	Base	https://git.openembedded.org/meta-openembedded
meta-xilinx-core	Enables AMD Xilinx hardware devices	Base	https://git.yoctoproject.org/meta-xilinx
de-ensc-bpi-router	router + telephony bsp	Machine (BSP)	https://gitlab.com/ensc-groups/bpi-router/de.ensc.bpi-router
meta-8dev	8devices board support	Machine (BSP)	https://github.com/8devices/meta-8dev.git
meta-96boards	BSP Layer for 96boards platforms	Machine (BSP)	https://github.com/96boards/meta-96boards
meta-aarch64	AArch64 (64-bit ARM) architecture support	Machine (BSP)	git://git.linaro.org/openembedded/meta-linaro.git

Yocto workspace setup : **Let's employ the modern (>= 5.3 Whinlatter) approach: where 'poky' is NOT the default distro!**

<< If you want the 'old way' < 5.3, see the Appendix >>

- **Recommended** dir tree approach : essentially:
 - Keep a directory to hold all the upstream Yocto layers
 - Keep another directory to hold all your project's layers
- Setup via this simple Bash script:

```
#!/bin/bash
# 'Correct' way to setup the Yocto >=5.3 (Whinlatter) layers directory layout
UPSTREAM_LAYERS_DIR=upstream_layers
[[ ! -d ${UPSTREAM_LAYERS_DIR} ]] && mkdir -p ${UPSTREAM_LAYERS_DIR}

git clone -b yocto-6.0 https://git.openembedded.org/bitbake ./${UPSTREAM_LAYERS_DIR}/bitbake
git clone -b yocto-6.0 https://git.openembedded.org/openembedded-core
./${UPSTREAM_LAYERS_DIR}/openembedded-core
git clone -b yocto-6.0 https://git.yoctoproject.org/meta-yocto ./${UPSTREAM_LAYERS_DIR}/meta-yocto
git clone -b yocto-6.0 https://git.yoctoproject.org/yocto-docs ./${UPSTREAM_LAYERS_DIR}/yocto-docs

# Create and maintain your own layers in another dir (which is version controlled, f.e. via git)
# f.e.
MYPRJ_LAYERS_DIR=myprj_layers
[[ ! -d ${MYPRJ_LAYERS_DIR} ]] && mkdir -p ${MYPRJ_LAYERS_DIR}
```

Hey, this is a simplified ver of the script; find the [actual one here](#).

Let's employ the modern (>= 5.3 Whinlatter) approach: where 'poky' is NOT the default distro!

Recommended dir tree approach : essentially:

- Keep a directory to hold all the upstream Yocto layers
- Keep another directory to hold all the project layers

Only 2
levels
seen:
tree . -L 2

(If you want to
see the 'old'
poky way,
check out the
Appendix..)

```
yocto_6.0_qarm64 $ tree . -L 2
.
├── build_qarm64
│   ├── bitbake-cookerdaemon.log
│   ├── buildhistory
│   ├── cache
│   ├── conf
│   ├── downloads
│   ├── sstate-cache
│   ├── tmp
│   └── workspace
├── myprj_layers
│   └── meta-myprj
└── upstream_layers
    ├── bitbake
    ├── meta-yocto
    ├── openembedded-core
    └── yocto-docs
```

The build dir
\${BUILDDIR}
(we'll come to it!)

Our project layers

YP upstream
layers

3

2

1

Let's employ the modern (≥ 5.3 Whinlatter) approach: where 'poky' is NOT the default distro!

An example of a real-world project that does just this is the well known

[OpenBMC project!](#)

openBMC layers

upstream Yocto layers

The screenshot shows the OpenBMC GitHub repository. The left sidebar displays the file tree with a red box around the 'meta-*' layers and a blue box around the 'upstream-layers' directory. The main content area shows the 'upstream-layers' directory with a table of subdirectories and their commit history.

Name	Last commit message	Last commit da...
..		
bitbake	bitbake: subtree update:797b0a348d...	12 hours ago
meta-arm	meta-arm: subtree update:3c0730338...	12 hours ago
meta-openembedded	meta-openembedded: subtree updat...	2 days ago
meta-raspberrypi	meta-raspberrypi: subtree update:b8...	3 weeks ago
meta-security	meta-security: subtree update:9265f1...	2 days ago
openembedded-core	openembedded-core: subtree update...	2 weeks ago
yocto-docs	yocto-docs: subtree update:6b78593b...	2 weeks ago
.gitignore	bitbake: move in prep for poky depre...	3 months ago
README	upstream-layers: add README	3 months ago

README

Subdirectories here are intended to be pristine imports of repositories owned by other organizations. They are managed with tooling from the openbmc/openbmc-config repository.

Changes should not be made here unless they have been submitted to those

Gentlemen, start your engines!

Here, we use Yocto v6.0 - Wrynose.

Ok, first init the work environment, *the “kitchen” where the chef - BitBake! - will cook!* It's the *build dir*, *\${BUILDDIR}*. How? Simple: just source a shell script (every time!):

```
|yocto_6.0_qarm64 $ source upstream_layers/openembedded-core/oe-init-build-env \  
build_qarm64/
```

An aside - one can use pre-downloaded Yocto artifacts for a demo build without any internet download requirement:

To just fetch all required files – IOW, to just download everything required for the build – do this:

```
$ bitbake core-image-base --runall=fetch  
...
```

core-image-base is the
'image recipe'

(Internally it performs only the *do_fetch()* task for every recipe. With the package(group) defaults for the *core-image-base* target image recipe, it downloaded close to 8 GB!)

The build

core-image-base is the
'image recipe'

(a bare-bones Qemu AArch64 Linux)!

\$ time bitbake
core-image-base

On my laptop (core i7, 12 cores,
32 GB RAM) Ubuntu 24.04.4

LTS:

- the build took ~ 2h 40m !
- ... and ate up ~ 77 GB of disk space!
- ... with defaults, and this image recipe (core-image-base), the target rootfs size is just ~ 160 MB !

Pl use as powerful a build system as you can afford!

```
[build qarm64 $ time bitbake core-image-base
Loading cache: 100% |#####| Time: 0:00:00
#####| Time: 0:00:00
Loaded 1970 entries from dependency cache.
NOTE: Resolving any missing task queue dependencies

Build Configuration:
BB_VERSION      = "2.18.0"
BUILD_SYS       = "x86_64-linux"
NATIVELSBSTRING = "universal"
TARGET_SYS      = "aarch64-oe-linux"
MACHINE         = "qemuarm64"
SDKMACHINE      = "x86_64"
DISTRO          = "nodistro"
DISTRO_VERSION   = "nodistro.0"
TUNE_FEATURES    = "aarch64 crc cortexa57"
meta            = "HEAD:42fa856a00ac16b2a7a83d7ecfa60a5be192b16c"

Sstate summary: Wanted 2802 Local 0 Mirrors 0 Missed 2802 Current 352 (0% match, 11% complete)

Initialising tasks: 100% |#####| Time: 0:00:02
#####| Time: 0:00:02
NOTE: Executing Tasks
Setscene tasks: 3154 of 3154
Setscene tasks: 3154 of 3154
Currently 10 running tasks (1895 of 5838) 32% |#####|
0: xz-native-5.8.2-r0 do_configure - 21s (pid 211489)
1: gmp-native-6.3.0-r0 do_configure - 21s (pid 211510)
2: flex-native-2.6.4-r0 do_configure - 21s (pid 211517)
3: gperf-native-3.3-r0 do_configure - 21s (pid 211564)
4: tcl8-native-8.6.17-r0 do_compile - 12s (pid 224338)
5: libyaml-native-0.2.5-r0 do_configure - 6s (pid 233537)
6: gdbm-native-1.26-r0 do_compile - 4s (pid 237923)
7: cross-localedef-native-2.43+git-r0 do_compile - 4s (pid 237999)
8: libpcr2-native-10.47-r0 do_compile - 4s (pid 237985)
9: patch-native-2.8-r0 do_configure - 0s (pid 242146)
```

Build completed; within the `${TMPDIR}`, you'll find the key *images/* dir:

`tmp/deploy/images/qemuarm64/`

It holds all the built artifacts - includes the bootloader, (possibly the DTB), kernel, root filesystem image files (among others)!

```
|build_qarm64 $ ls -lh tmp/deploy/images/qemuarm64/
total 134M
-rw-r--r-- 2 kaiwan kaiwan 53M Jun 5 18:07 core-image-base-qemuarm64.rootfs-20260605103542.ext4.zst
-rw-r--r-- 2 kaiwan kaiwan 4.9K Jun 5 18:07 core-image-base-qemuarm64.rootfs-20260605103542.manifest
-rw-r--r-- 2 kaiwan kaiwan 1.9K Jun 5 18:07 core-image-base-qemuarm64.rootfs-20260605103542.qemuboot.conf
-rw-r--r-- 2 kaiwan kaiwan 5.3M Jun 5 18:44 core-image-base-qemuarm64.rootfs-20260605103542.spdx.json
-rw-r--r-- 2 kaiwan kaiwan 53M Jun 5 18:07 core-image-base-qemuarm64.rootfs-20260605103542.tar.zst
-rw-r--r-- 2 kaiwan kaiwan 233K Jun 5 18:07 core-image-base-qemuarm64.rootfs-20260605103542.testdata.json
lrwxrwxrwx 2 kaiwan kaiwan 56 Jun 5 18:07 core-image-base-qemuarm64.rootfs.ext4.zst -> core-image-base-qemuarm64.rootfs-20260605103542.ext4.zst
lrwxrwxrwx 2 kaiwan kaiwan 56 Jun 5 18:07 core-image-base-qemuarm64.rootfs.manifest -> core-image-base-qemuarm64.rootfs-20260605103542.manifest
lrwxrwxrwx 2 kaiwan kaiwan 61 Jun 5 18:07 core-image-base-qemuarm64.rootfs.qemuboot.conf -> core-image-base-qemuarm64.rootfs-20260605103542.qemuboot.conf
lrwxrwxrwx 2 kaiwan kaiwan 57 Jun 5 18:44 core-image-base-qemuarm64.rootfs.spdx.json -> core-image-base-qemuarm64.rootfs-20260605103542.spdx.json
lrwxrwxrwx 2 kaiwan kaiwan 55 Jun 5 18:07 core-image-base-qemuarm64.rootfs.tar.zst -> core-image-base-qemuarm64.rootfs-20260605103542.tar.zst
lrwxrwxrwx 2 kaiwan kaiwan 61 Jun 5 18:07 core-image-base-qemuarm64.rootfs.testdata.json -> core-image-base-qemuarm64.rootfs-20260605103542.testdata.json
lrwxrwxrwx 2 kaiwan kaiwan 73 Jun 5 17:52 Image -> Image--6.18.24+git0+f94e250f9b_b1ba542851-r0-qemuarm64-20260605103542.bin
-rw-r--r-- 2 kaiwan kaiwan 23M Jun 5 17:52 Image--6.18.24+git0+f94e250f9b_b1ba542851-r0-qemuarm64-20260605103542.bin
lrwxrwxrwx 2 kaiwan kaiwan 73 Jun 5 17:52 Image-qemuarm64.bin -> Image--6.18.24+git0+f94e250f9b_b1ba542851-r0-qemuarm64-20260605103542.bin
-rw-r--r-- 2 kaiwan kaiwan 2.3M Jun 5 17:52 modules--6.18.24+git0+f94e250f9b_b1ba542851-r0-qemuarm64-20260605103542.tgz
lrwxrwxrwx 2 kaiwan kaiwan 75 Jun 5 17:52 modules-qemuarm64.tgz -> modules--6.18.24+git0+f94e250f9b_b1ba542851-r0-qemuarm64-20260605103542.tgz
|build_qarm64 $
```

// demo run #1: `$ runqemu qemuarm64 snapshot`

```
total 296K
-rw-rw-r-- 1 kaiwan kaiwan 244K Jun  5 19:11 bitbake-cookerdaemon.log
-rwxr-xr-x 5 kaiwan kaiwan 4.0K Jun  5 18:44 buildhistory/
-rwxrwxr-x 2 kaiwan kaiwan 4.0K Jun  5 19:11 cache/
-rwxrwxr-x 2 kaiwan kaiwan 4.0K Jun  5 19:02 conf/
-rwxrwxr-x 4 kaiwan kaiwan 24K Jun  5 16:14 downloads/
-rwxrwxr-x 259 kaiwan kaiwan 4.0K Jun  5 16:12 sstate-cache/
-rwxrwxr-x 14 kaiwan kaiwan 4.0K Jun  5 16:48 tmp/
build_qarm64 $
build_qarm64 $ ls ..
build_qarm64/ myprj_layers/ upstream_layers/
build_qarm64 $ ls ../upstream_layers/
bitbake/ meta-yocto/ openembedded-core/ yocto-core/
build_qarm64 $ ls ../upstream_layers/openembedded-core/
contrib/ LICENSE.GPL-2.0-only MAINTAINERS.md meta/
LICENSE LICENSE.MIT MEMORIAM meta-selftest/
build_qarm64 $
build_qarm64 $
build_qarm64 $ runqemu qemuarm64 snapshot
runqemu - INFO - Running MACHINE=qemuarm64 bitbake -e ...
runqemu - INFO - Decompressing /big/yocto 6.0 qarm64/build_qarm64/
p/deploy/images/qemuarm64/core-image-base-qemuarm64.rootfs-2026
big/yocto 6.0_qarm64/build_qarm64/tmp/deploy/images/qemuarm64/c
runqemu - INFO - Continuing with the following parameters:
KERNEL: [/big/yocto 6.0_qarm64/build_qarm64/tmp/deploy/images/qe
MACHINE: [qemuarm64]
STYPE: [ext4]
ROOTFS: [/big/yocto 6.0_qarm64/build_qarm64/tmp/deploy/images/qe
SNAPSHOT: [Enabled. Changes on rootfs won't be kept after QEMU s
CONFIGFILE: [/big/yocto 6.0_qarm64/build_qarm64/tmp/deploy/images/
runqemu - INFO - Setting up tap interface under sudo
[sudo] password for kaiwan:
runqemu - INFO - Network configuration: ip=192.168.7.2::192.168.
runqemu - INFO - Running /big/yocto 6.0_qarm64/build_qarm64/tmp/
ac=52:54:00:12:34:02 -netdev tap,id=net0,ifname=tap0,script=no,
6.0_qarm64/build_qarm64/tmp/deploy/images/qemuarm64/core-image-
blet -device usb-kbd -machine virt -cpu cortex-a57 -smp 4 -m
d_qarm64/tmp/deploy/images/qemuarm64/Image -append 'root=/dev/v
runqemu - INFO - Host uptime: 94986.16
```

yocto
PROJECT


```
$ runqemu \
  qemuarm64 snapshot nographic
```

```
[ OK ] Created slice Slice /system/psplash-start.
Starting Start psplash boot splash screen...
[ OK ] Finished Enable Persistent Storage in systemd-networkd.
[ OK ] Started Start psplash boot splash screen.
[ OK ] Listening on Load/Save RF Kill Switch Status /dev/rfkill Watch.
[ OK ] Started Start psplash-systemd progress communication helper.
Starting Virtual Console Setup...
[ OK ] Finished Virtual Console Setup.

OpenEmbedded nodistro.0 qemuarm64 ttyAMA0

Type 'root' to login with superuser privileges (no password will be asked).

qemuarm64 login: root
root@qemuarm64:~# cat /etc/issue
OpenEmbedded nodistro.0 \n \l

Type 'root' to login with superuser privileges (no password will be asked).


root@qemuarm64:~# cat /proc/version
Linux version 6.18.24-yocto-standard (oe-user@oe-host) (aarch64-oe-linux-g
(GNU Binutils 2.46) #1 SMP PREEMPT Thu Apr 23 15:17:42 UTC 2026
root@qemuarm64:~# ls -l /
lrwxrwxrwx    1 root    root           7 Apr  5  2011 bin -> usr/bin
drwxr-xr-x    2 root    root        1024 Apr  5  2011 boot
drwxr-xr-x   12 root    root       2860 Jun  6 05:17 dev
drwxr-xr-x   25 root    root       3072 Jun  6 05:17 etc
drwxr-xr-x    2 root    root       1024 Apr  5  2011 home
lrwxrwxrwx    1 root    root           7 Apr  5  2011 lib -> usr/lib
drwx-----   2 root    root       12288 Apr  5  2011 lost+found
drwxr-xr-x    2 root    root       1024 Apr  5  2011 media
drwxr-xr-x    2 root    root       1024 Apr  5  2011 mnt
dr-xr-xr-x   158 root    root         0 Jun  6 05:17 proc
drwx-----   3 root    root       1024 Jun  6 05:18 root
drwxr-xr-x   14 root    root       420 Jun  6 05:17 run
lrwxrwxrwx    1 root    root           8 Apr  5  2011/sbin -> usr/sbin
drwxr-xr-x    2 root    root       1024 Apr  5  2011 srv
dr-xr-xr-x   12 root    root         0 Jun  6 05:17 sys
drwxrwxrwt    7 root    root       140 Jun  6 05:17 tmp
drwxr-xr-x   10 root    root       1024 Apr  5  2011 usr
drwxr-xr-x    8 root    root       1024 Jun  6 05:17 var
root@qemuarm64:~#
```

User configuration

*Pic credit: Yocto
official docs*

- *oe-init-build-env* : the startup script to be sourced
- conf:*
 - *bblayers.conf* : all the layers
 - *local.conf* : the local machine build environment

Source Directory (e.g. poky directory)



The Layer-Recipe template

- A layer contains one or more recipes
- Recipes are key: it's how bitbake knows what to do
- **Most (non-image) recipes generate one or more packages.**

```
meta-<LAYER_NAME>
├─ conf
│   └─ layer.conf
├─ <License>
├─ README[.md]
└─ recipes-<LAYER_NAME>*
    └─ <RECIPE_NAME>*
        ├── files
        │   ├── <place required file(s) here>
        │   └─ <as many as are required>
        └─ <RECIPE_NAME>_<PV>.<PR>.bb
```

An example

```
meta-myprj
├─ conf
│   └─ layer.conf
├─ COPYING.MIT
├─ README
└─ recipes-myprj
    └─ myinit
        ├── files
        │   └─ 0setup.sh
        └─ myinit_0.1.bb
```

* The recipe folder name does Not have to be **recipes-<LAYER_NAME>** ; it can be **recipes-<anything>** (or, another name as well).

PV = Pkg Ver; PR = Pkg Release.

Example: layout of the *openembedded-core/meta-skeleton* layer and the recipes within it... (output truncated)

```
|build_qarm64 $ tree ../upstream_layers/openembedded-core/meta-skeleton/  
../upstream_layers/openembedded-core/meta-skeleton/  
├── conf  
│   ├── layer.conf  
│   ├── multilib-example2.conf  
│   └── multilib-example.conf  
├── README.skeleton  
├── recipes-core  
│   └── busybox  
│       ├── busybox  
│       │   └── no_rfkill.cfg  
│       └── busybox_%.bbappend
```

busybox! - the 'Swiss army knife' of embedded Linux

--snip--

```
├── recipes-skeleton  
│   ├── hello-autotools  
│   │   └── hello_2.10.bb  
│   ├── hello-single  
│   │   ├── files  
│   │   │   └── helloworld.c  
│   └── hello_1.0.bb
```

'Hello, world' !

‘Hello, world’ - a quick layer:recipe demo (1)

1. Setup the layer:recipe as per the template we just saw (screenshot); to do so, can use *recipetool* or *devtool* (or do it manually or use my simple [yct_recipe_gen script](#))
2. Place the source file here: *files/helloworld.c*
3. Write the recipe (here):
./meta-myprj/recipes-myprj/helloworld/helloworld_0.1.bb
(due to lack of space+time, see it [in this presentation's GitHub repo](#))
4. Verify that the recipe's ‘seen’ by bitbake:

```
$ bitbake-layers show-recipes helloworld
```

```
...
```

```
=== Matching recipes: ===
```

```
helloworld:
```

```
    meta-myprj          0.1
```

```
|build_qarm64 $ tree ../myprj_layers/meta-myprj/  
../myprj_layers/meta-myprj/  
├── conf  
│   └── layer.conf  
├── COPYING.MIT  
├── README  
└── recipes-myprj  
    ├── helloworld  
    │   ├── files  
    │   │   └── helloworld.c  
    │   └── helloworld_0.1.bb  
    └── myinit  
        ├── files  
        │   └── 0setup.sh  
        └── myinit_0.1.bb
```

‘Hello, world’ - a quick layer:recipe demo (2)

5. Test: build just this recipe:

```
$ bitbake helloworld
```

6. Once it's working, add it to the build via *conf/local.conf* (for now), thus “*plating*” the recipe:

```
IMAGE_INSTALL:append = " helloworld"
```

7. Rebuild:

```
bitbake core-image-base
```

8. Test:

```
runqemu qemuarm64 snapshot nographic
```

...


```
root@qemuarm64:~# helloworld
```

```
Hello, Yocto world
```

Nice!

In addition: our useful [info_yocto script](#) shows some details; one of them's the rootfs location within tmp/ :

```
$ ls -l tmp/work/qemuarm64-oe-linux/core-image-base/1.0/rootfs/usr/bin/helloworld
-rwxr-xr-x 1 kaiwan kaiwan 67672 Mar  9 2018 tmp/work/<...>/helloworld
```



```
OpenEmbedded nodistro.0 qemuarm64 ttyAMA0

Type 'root' to login with superuser privileges (no password will be asked).

qemuarm64 login: root
root@qemuarm64:~#
root@qemuarm64:~# helloworld
Hello, Yocto world
root@qemuarm64:~#
root@qemuarm64:~# which helloworld
/bin/helloworld
root@qemuarm64:~#
```

Adding a lightweight SSH / SCP implementation - dropbear !

In your `#{BUILDDIR}/conf/local.conf`:

```
IMAGE_INSTALL:append = " \
    helloworld \
    dropbear \
"
```

Q> How do we know the recipe name to use?

A>

1. Use the layer index!

<https://layers.openembedded.org/layerindex/branch/master/recipes>

Search within the 'Recipes' tab...

2. Check the 'Layer' that provides the recipe; it needs to be available.. Here, openembedded-core is always available (within the upstream layers). Else, first download and then 'install' the layer by running `bitbake-layers add-layer <layer-name>`

OpenEmbedded Layer Index

Submit layer Log in

Branch: master ▾ Layers Recipes Machines Classes Distros

dropbear search ? help

Recipe name	Version	Description	Layer
dropbear	2025.89	A lightweight SSH and SCP implementation	openembedded-core
dropbear	2025.89	A lightweight SSH and SCP implementation	meta-voltumna
packagegroup-core-ssh-dropbear	1.0	Dropbear SSH client/server	openembedded-core


How a recipe works

Most (non-image) recipes generate one or more packages.

Every package has its 'own rootfs' under a 'work' directory; finally, the union of all package rootfs's becomes the final actual rootfs!

These are the main tasks (functions) - all optional - to be carried out by a recipe; you can write a recipe that can override or prepend or append to it!

Pic: from [Bootlin's doc](#): "The main tasks"



`${DL_DIR}` : download dir

`${WORKDIR}` : work dir (= `${TMPDIR}/work` = `tmp/work`)

`${S}` : source dir ; (>= 5.3: the 'sources' dir is `${UNPACKDIR}` and `S=${UNPACKDIR}/${BP}`)

`${B}` : Build dir

`${D}` : Destination (install) dir

(FYI: `${BUILDDIR}` is the build directory.)

TIP: Query a BB variable with: `bitbake-getvar [--value] <bb-variable-name>`

F.e.:

```
$ bitbake -e helloworld |grep "^WORKDIR="
```

```
WORKDIR="/<...>/build_qarm64/tmp/work/cortexa57-oe-linux/helloworld/0.1"
```

There's more steps than shown here: the `do_package()`, `do_package_qa()`, `do_package_write_<pkgtype>()`, `do_populate_lic()`, `do_recipe_qa()`, etc also follow!

Try

```
bitbake -c listtasks helloworld
```

Layout of the per-package `${WORKDIR} : ${TMPDIR}/work/...`

The per-package (PN) WORKDIR value is:

`WORKDIR = ${TMPDIR}/work/${PACKAGE_ARCH}-${DISTRO}-${TARGET_OS}/${PN}/${PV}-${PR}` ; where

- `${TMPDIR}` : typically named `tmp/`
- **NOTE:** `${PACKAGE_ARCH}` is the processor family (f.e. Cortex A57), not the processor arch (f.e. if you're building Yocto for the Qemu arm64, then the processor type, `PACKAGE_ARCH`, is `cortexa57` (and not `aarch64` or `qemuarm64`; it's often the same as the `TUNE_PKGARCH` value. So:
`bitbake-getvar --value PACKAGE_ARCH` yields `cortexa57`
- `${DISTRO}` is the **distro name** of course. Later, you'll likely want to customize and specify your very own custom distro! When you do so, replace its name here... (by default, it's often simply set to `'oe'` - `openembedded`)
- `${TARGET_OS}` is the target OS (typically `'linux'`)
- `${PN}` is the **Package Name**; usually matches the recipe name. F.e. for our `'helloworld'` recipe, it's `'helloworld'` of course!
`${PV}` is the Package Version
`${PR}` is the Package Release

So for our `'helloworld'` recipe, the `WORKDIR` value is: `tmp/work/cortexa57-oe-linux/helloworld/0.1/`

```
$ ls -F tmp/work/cortexa57-oe-linux/helloworld/0.1/
```

debugsources.list	deploy-source-date-epoch/	license-destdir/	packages-split/	pkgdata-pdata-input/
pseudo/	recipe-sysroot-native/	sources/	sysroot-destdir/	
deploy-ipks/	image/	package/	pkgdata/	pkgdata-sysroot/
recipe-sysroot/	source-date-epoch/	spdx/	temp/	

Layout of `${TMPDIR}/${WORKDIR}` : tmp/work/...

As well:

- Source dir S (or build dir B):

`S = ${WORKDIR}/${BPN}-${PV}`


- Destination dir D:

`D = ${WORKDIR}/image`

PRO / DEBUG TIP:

Under `${WORKDIR}/tmp` you'll find v useful files: `log.do_*`, `run.do_*` (and more)!

The `run.do_*` files are per BB recipe action; f.e. `run.do_compile` (a soft link) will show precisely how compilation was done!



PRO TIPS

- *Must-read:*
 - The extensive [Yocto Documentation, the manuals](#)
 - [Yocto Project Quick Build](#)
 - The complete, very detailed official [Yocto Project Concepts documentation](#) is a MUST Read!
 - [What I wish I'd known about Yocto Project](#)
- **Never** modify anything in the upstream layers (or poky); write your own **layer:<bbappend>recipe** to make changes as required!
- Don't misunderstand how Yocto works; you CANNOT do anything (besides adding/removing a package) that makes a material difference on the rootfs **without a layer and recipe...** this includes creating, editing or removing even a single file (*want a script, a ~/.ssh/authorized_keys, etc? You need to get it in place via a recipe!*)
 - READ THIS thread: [\[yocto\] recipe to clean up files from rootfs](#)
 - You CANNOT directly change what another recipe does
 - CAN:
 - add to / modify what a recipe does, via an **append-style (.bbappend) recipe**
 - postprocess the rootfs image creation.

PRO TIPS

You can add as many of the following features / packages as you like by adding them to your `${TOPDIR}/conf/local.conf`: **EXTRA_IMAGE_FEATURES** variable (shown alphabetically below; they're described [here](#)):

allow-empty-password	allow-root-login			
bash-completion-pkgs				
dbg-pkgs	debug-tweaks	dev-pkgs	doc	doc-pkgs
eclipse-debug	empty-root-password			
hwcodecs				
lic-pkgs				
nfs-client	nfs-server			
package-management	post-install-logging	ptest-pkgs		
read-only-rootfs	read-only-rootfs-delayed-postinsts			
splash src-pkgs	ssh-server-dropbear	ssh-server-openssh		
stateless-rootfs	staticdev-pkgs			
tools-debug	tools-profile	tools-sdk	tools-testapps	
weston				
x11	x11-base	x11-sato		

F.e.: `EXTRA_IMAGE_FEATURES ?= "allow-root-login allow-empty-password
empty-root-password"`

<< Must be 'Secure by default': careful, the default Yocto config has these extreme permissive values on; turn it **OFF** for production! [\[link\]](#) >>

PRO TIPS

When new, we simply use `conf/local.conf`.

IMP: The actual Yocto philosophy: **distro × image x machine** are three orthogonal axes

- The **DISTRO**


- the top of this hierarchy; defines global policy
- defines the distribution: the init manager, login manager, C library, toolchain settings, and more
- akin to ‘capability bits’; they show what’s possible (it’s the superset)
- set via the **DISTRO_FEATURES** bitbake variable

- The **IMAGE**

- the mid-tier in this hierarchy; defines what actually goes into the rootfs (which packages); f.e. Ubuntu is a single distro but can have many ‘flavours’ or ‘images’: desktop, server, coreOS, real-time, minimal, etc
- ultimately generates an image artifact, the rootfs (ext[34] / wic / tar.bz2 / etc)
- set via the **IMAGE_FEATURES** bitbake variable (expands to IMAGE_INSTALL + config)

- The **MACHINE**

- the lowest level of this hierarchy; defines which **MACHINE** to build for (BSP layers)
- points to:
 - which ‘distribution’ or Linux flavour to favour (**DISTRO**)
 - which packages to install via the IMAGE_INSTALL bitbake variable



There's (much) more, but no time to cover it all! :-)

So, please see the

Appendix

at the end of this presentation (a few more slides).



To conclude:

Building a custom embedded Linux with Yocto is not *that* difficult, nor is it that simple!

So:

“Hey Yocto, build me a custom embedded Linux!”



“Er, no”

Thank you!

Done *

* No, we're never really 'done'. Especially with Yocto, we've just seen the tip of the proverbial iceberg!

Q. What's the biggest room in the world?

A. The room for improvement!

Appendix

The stuff I had no time
to cover :-) follows



Yocto workspace setup : FYI, the ‘OLD’ (Yocto < 5.3) way

1. Setup the host workspace: [link](#)

2. One-time: Clone the ‘poky’ repo: f.e.:

```
git clone -b scarthgap https://git.yoctoproject.org/poky
```

3. Initialize the work environment, the “**kitchen**” where the “**chef**” - BitBake - will cook! Run the init script - *every time*:

```
cd poky
source oe-init-build-env [build_dir]
```


Yocto workspace setup : old way, **Poky** is always the default distro

Example with Yocto 5.0.8 Scarthgap

```
$ alias ls='ls -F --color=auto'
```

```
$ ls yocto_qarm64_demo/
```

poky/

```
$ ls yocto_qarm64_demo/poky/
```

```
bitbake/          documentation/  LICENSE.MIT      meta/             meta-security/
meta-yocto-bsp/  README.md@      README.qemu.md  build_qarm64/     LICENSE
MAINTAINERS.md  meta-openembedded/ meta-selftest/  oe-init-build-env  README.OE-Core.md  scripts/
contrib/         LICENSE.GPL-2.0-only  MEMORIAM        meta-poky/        meta-skeleton/
README.hardware.md@ README.poky.md@      SECURITY.md
```

In the ‘old’ way, everything’s under the ‘poky’ umbrella!

Really, let's not!

PRO TIPS

The actual Yocto philosophy: **distro × image × machine** are three orthogonal axes (1)


How a package X makes it into the target root filesystem: there are a few ‘gates’ to get through:

```
if DISTRO_FEATURES (or REQUIRED_DISTRO_FEATURES) includes it AND
    IMAGE_FEATURES includes it OR it's explicitly added into the build via
        IMAGE_INSTALL (via the image recipe or local.conf)
then
    it's packaged in
fi
```

F.e. if Wayland's required (and not the old X11):

```
DISTRO_FEATURES:append = " wayland"
DISTRO_FEATURES:remove = " x11"
IMAGE_INSTALL:append = " weston weston-init" # weston is the reference
                                     # implementation of a Wayland compositor
```

Defaults: if Yocto ver ≥ 5.3 : use ‘nodistro’ else (older < 5.3) poky is the default distro;
‘image’ is typically core-image-{base|minimal}




PRO TIPS

The actual Yocto philosophy: **distro × image × machine** are three orthogonal axes (2)

Conclusion: **What actually determines the installed package set:**


1. **Distro config**: is the superset: **DISTRO_FEATURES** gates whether features like **systemd**, **wayland**, **pam** are even available to be pulled in, and **PREFERRED_*** picks providers/versions. With newer Yocto ver ≥ 5.3 's **nodistro** you just get OE-core's 'un-opinionated' default **DISTRO_FEATURES** (unlike poky's 'opinionated' selections :-)).
2. **The image recipe**: **IMAGE_INSTALL**, the **core-image** class, **IMAGE_FEATURES**. This is the "package manifest." F.e., **core-image-minimal** pulls in **packagegroup-core-boot** + **\${CORE_IMAGE_EXTRA_INSTALL}**. The concept of **package groups** - literally, groups of packages - is key here ([link](#)).
3. **IMAGE_FEATURES** / **EXTRA_IMAGE_FEATURES** : toggles like **debug-tweaks**, **ssh-server-dropbear**, **tools-debug** that expand into package groups (which expand into packages).
4. **Dependencies**: runtime deps (**RDEPENDS**), recommends (**RRECOMMENDS**), and **PACKAGE_INSTALL** resolution can drag in additional packages as required.
5. The **local** config: **\${BUILDDIR}/conf/local.conf** 's **IMAGE_INSTALL** 's.



PRO TIPS

The actual Yocto philosophy: **distro × image × machine** are three orthogonal axes (3)

- **Custom distro config:** `meta-mydistro/conf/distro/mydistro.conf`
 - Meant for project's - all distro-policy variables / settings
 - `DISTRO_NAME`, `DISTRO_VERSION`
F.e.: `DISTRO_FEATURES:append = " ... "`, specifies init manager (`systemd` / `sysvinit`),
`DISTRO_FEATURES:remove = "wayland x11", ...`
 - Details - Yocto official docs: [Creating Your Own Distribution](#)
- **Custom Image recipe (image-specific, determines rootfs content):**
`meta-mydistro/recipes-core/images/myimage.bb`
 - Meant for project's - determines the final rootfs content
 - Build: `bitbake myimage`
 - Contains image-specific settings
 - F.e.: `IMAGE_FEATURES += " ... "`;
`EXTRA_IMAGE_FEATURES ?= "debug-tweaks"`
`IMAGE_INSTALL:append = " ... "`
`BAD_RECOMMENDATIONS += "..."`
`IMAGE_FSTYPES += "wic ext4 ..."`
 - Learn about Yocto *packagegroups* - [Customizing Images Using Custom Package Groups](#)
- **Local config:** `${BUILDDIR}/conf/local.conf`
 - the lowest tier on the reproducibility and shareability ladder
 - holds the immediate '**machine**' build environment
F.e.: `MACHINE`, `buildhistory`, `BB_DISKMON_DIRS` (limits on disk, memory, etc), identifies the `DISTRO` to build against
 - meant for dev / immediate stuff / local hacking only.



PRO TIPS

- Leverage the BitBake toolset
 - [bitbake-layers](#)
 - [recipetool](#) and [devtool](#)
 - [bitbake-getvar, debugging](#)
 - `bitbake -c <cmd>` (f.e. `bitbake -c devshell busybox`)
 - [bitbake-setup](#) (new, Yocto ≥ 5.3)
- Security
 - Yocto docs: [Making Images More Secure](#)
 - `conf/local.conf`: `require conf/distro/include/security_flags.inc`
- Release Notes
 - Very useful...
 - F.e. here's the Release Notes for yocto-6.0 (wrynose):
<https://downloads.yoctoproject.org/releases/yocto/yocto-6.0/RELEASENOTES>

PRO TIPS

- When writing a recipe, do NOT assume that any pathname (file or directory), even a 'system' one, is present; always generate it via the install(1) utility:

```
install -d -m <mode> <dir>
```

- **Migration guides** are Very important! Must-read; f.e.:

<https://docs.yoctoproject.org/dev/migration-guides/migration-5.3.html>

F.e.

WORKDIR changes

`S = ${WORKDIR}/something` **no longer supported**


If a recipe has `S` set to be `${WORKDIR}/something`, this is no longer supported, and an error will be issued. The recipe should be changed to:

`S = "${UNPACKDIR}/something"`

- My [yocto_tools GitHub repo](#) ; YMMV

PRO TIPS

- The complete, very detailed official [Yocto Project Concepts documentation](#) is a MUST Read! It includes the **Bitbake Tasks Map**: [doc](#); [image](#):



- Reminder: pl see this excellent presentation: [YPS 2023.11 - 2023/11/30 - Talel BELHAJSALEM - Back to basics | The ultimate Yocto introduction](#) (1h08m)

<End document>