Algorithms

Robert Sedgewick | Kevin Wayne

Algorithms
FOURTH EDITION
Robert Sedgewick | Kevin Wayne

http://algs4.cs.princeton.edu

2.1 H-sorting Demo

h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.


j
i
not yet processed

h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.


j
i
3
7
5
6
4
10
2
9
8
not yet processed

h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



3-sorted

not yet processed

h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.


j
i
not yet processed

h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



not yet processed

h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



3-sorted

not yet processed

h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.


j
i
not yet processed

h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.


i
3-sorted
not yet processed

h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.


j
i
not yet processed

h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.


j
i
not yet processed

h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.


j
i
not yet processed

h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.


i
3-sorted
not yet processed

h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.


j
i
not yet processed

h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.


i
2
4
5
3
7
10
6
9
8

3-sorted

not yet processed

h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

An array is `h`-sorted if `a[i-h] <= a[i]` for each `i`.


2
4
5
3
7
8
6
9
10

3-sorted

h-sorting demo

An array is `h`-sorted if `a[i-h] <= a[i]` for each `i`.


2
4
5
3
7
8
6
9
10

3-sorted

h-sorting demo

An array is `h`-sorted if `a[i-h] <= a[i]` for each `i`.



h-sorting demo

An array is `h`-sorted if `a[i-h] <= a[i]` for each `i`.



3-sorted