

CS1100 – Introduction to Programming

Lecture 4

Instructor: Shweta Agrawal (shweta.a@cse.iitm.ac.in)

Goals for the day

- Edit, compile and execute the first C program.
- Get **simple yet useful** tasks done via C programs.
 - Add a set of numbers.
 - Find roots of a quadratic equation.
 - Multiply 2 polynomials.

Goals for the day

- Edit, compile and execute the first C program.
- Get **simple yet useful** tasks done via C programs.
 - Add a set of numbers.
 - Find roots of a quadratic equation.
 - Multiply 2 polynomials.
- Learn the **syntax** of C language.
 - Basics – structure of a C program, using standard library.
 - How to store data – variables, data types.
 - How to get inputs, how to print outputs?

Goals for the day

- Edit, compile and execute the first C program.
- Get **simple yet useful** tasks done via C programs.
 - Add a set of numbers.
 - Find roots of a quadratic equation.
 - Multiply 2 polynomials.
- Learn the **syntax** of C language.
 - Basics – structure of a C program, using standard library.
 - How to store data – variables, data types.
 - How to get inputs, how to print outputs?
- Learn about the working environment (Linux based OS).
 - editors – gedit and others.
 - compiler – gcc.
 - executing a compiled program.

First C program

```
#include <stdio.h>

/* My first C program */

main() {
    printf("Hello World!\n");
}
```

First C program

```
#include <stdio.h>

/* My first C program */

main() {
    printf("Hello World!\n");
}
```

- [stdio.h](#) : standard library of input and output.
- [main](#) : a function that every C program must have.
- [printf](#) : a useful library function to print several things in C.

First C program

```
#include <stdio.h>

/* My first C program */

main() {
    printf("Hello World!\n");
}
```

- `stdio.h` : standard library of input and output.
- `main` : a function that every C program must have.
- `printf` : a useful library function to print several things in C.

To do anything more useful than merely printing we need to have more operations / commands and storage to store temporary computations.

Variables in C

Add 2 numbers x and y and store the value in z .

- Define two *variables* x and y .
 - What type of values can x and y take?

Variables in C

Add 2 numbers x and y and store the value in z .

- Define two *variables* x and y .
 - What type of values can x and y take?

integer, positive integers, fractions?

Variables in C

Add 2 numbers x and y and store the value in z .

- Define two *variables* x and y .
 - What type of values can x and y take?
integer, positive integers, fractions?
 - What do x and y represent?

Variables in C

Add 2 numbers x and y and store the value in z .

- Define two *variables* x and y .
 - What type of values can x and y take?
- What do x and y represent?

integer, positive integers, fractions?

Say marks in Maths and marks in Physics respectively.

Variables in C

Add 2 numbers x and y and store the value in z .

- Define two *variables* x and y .
 - What type of values can x and y take?
integer, positive integers, fractions?
 - What do x and y represent?
Say marks in Maths and marks in Physics respectively.
- Use the $+$ operator defined to sum up the values of x and y .

Variables in C

Add 2 numbers x and y and store the value in z .

- Define two *variables* x and y .
 - What type of values can x and y take?
integer, positive integers, fractions?
 - What do x and y represent?
Say marks in Maths and marks in Physics respectively.
- Use the $+$ operator defined to sum up the values of x and y .
- Use an *assignment* operator to store the value in z .

Sum of 2 numbers

```
#include <stdio.h>

/* sum 2 integers */

main() {
    int x;
    int y;
    int z;

    z = x+y;
    printf("%d\n", z);
}
```

Sum of 2 numbers

```
#include <stdio.h>

/* sum 2 integers */

main() {
    int x;
    int y;
    int z;

    z = x+y;
    printf("%d\n", z);
}
```

- **int** : defines that x, y, z are of type integers.
- **$z = x+y$** : evaluates $x+y$ and stores it in z .

Sum of 2 numbers

```
#include <stdio.h>

/* sum 2 integers */

main() {
    int x;
    int y;
    int z;

    z = x+y;
    printf("%d\n", z);
}
```

- **int** : defines that x, y, z are of type integers.
- **$z = x+y$** : evaluates $x+y$ and stores it in z .
- What will be output if we print z ?

Sum of 2 numbers

```
#include <stdio.h>

/* sum 2 integers */

main() {
    int x;
    int y;
    int z;

    z = x+y;
    printf("%d\n", z);
}
```

- **int** : defines that x, y, z are of type integers.
- **$z = x+y$** : evaluates $x+y$ and stores it in z .
- What will be output if we print z ?
- **Initialization** or **reading** of x and y missing.

Sum of 2 numbers

```
#include <stdio.h>

/* sum 2 integers */

main() {
    int x;
    int y;
    int z;

    z = x+y;
    printf("%d\n", z);
}
```

- **int** : defines that x, y, z are of type integers.
- **$z = x+y$** : evaluates $x+y$ and stores it in z .
- What will be output if we print z ?
- **Initialization** or **reading** of x and y missing.

Sum of 2 numbers – with initialization

```
#include <stdio.h>

/* sum 2 integers */

main() {
    int x = 98;
    int y = 99;
    int z;

    z = x+y;
    printf("%d\n", z);
}
```

- **int** : defines that x, y, z are of type integers.
- **$z = x+y$** : evaluates $x+y$ and stores it in z .
- What will be output if we print z ?

Sum of 2 numbers – with initialization

```
#include <stdio.h>

/* sum 2 integers */

main() {
    int x = 98;
    int y = 99;
    int z;

    z = x+y;
    printf("%d\n", z);
}
```

- **int** : defines that x, y, z are of type integers.
- **$z = x+y$** : evaluates $x+y$ and stores it in z .
- What will be output if we print z ?

Basic operators in C

- Arithmetic operators: $+$, $-$, $*$, $/$

Basic operators in C

- Arithmetic operators: `+`, `-`, `*`, `/`
- Modulus operator: `%`
`x % y` : remainder when `x` is divided by `y`.

Basic operators in C

- Arithmetic operators: $+$, $-$, $*$, $/$
- Modulus operator: $\%$
 $x \% y$: remainder when x is divided by y .
- Assignment operator: $=$

Basic operators in C

- Arithmetic operators: $+$, $-$, $*$, $/$
 - Modulus operator: $\%$
 $x \% y$: remainder when x is divided by y .
 - Assignment operator: $=$
-

Input statement: scanf

```
scanf(format-string, &var1, &var2, ... , &var3);
```

- scanf is a function which allows us to accept inputs.
- Usually functions take **fixed** number of parameters/arguments.
- scanf takes variable number of arguments.
- Notice the **&** preceeding the variables.

Weighted sum of 2 numbers

- Recall x denotes marks in Maths, y denotes marks in Physics.
- We wish to calculate weighted total such that Maths marks are given 30% weightage and Physics marks are given 70% weightage.
- $z = \frac{30}{100}x + \frac{70}{100}y$.

Weighted sum of 2 numbers

```
#include <stdio.h>
```

```
/* weighted sum 2 integers */
```

```
main() {
```

```
    int mathMarks = 98;
```

```
    int phyMarks = 99;
```

```
    int total;
```

```
    total = (30/100)*mathMarks + (70/100)*phyMarks;
```

```
    printf("%d\n", total);
```

```
}
```

Weighted sum of 2 numbers

```
#include <stdio.h>

/* weighted sum 2 integers */

main() {
    int mathMarks = 98;
    int phyMarks = 99;
    int total;

    total = (30/100)*mathMarks + (70/100)*phyMarks;
    printf("%d\n", total);
}
```

-
- What is the output of the program?

Weighted sum of 2 numbers

```
#include <stdio.h>

/* weighted sum 2 integers */

main() {
    int mathMarks = 98;
    int phyMarks = 99;
    int total;

    total = (30/100)*mathMarks + (70/100)*phyMarks;
    printf("%d\n", total);
}
```

-
- What is the output of the program?
 - Is the variable `total` still guaranteed to be an integer?

Weighted sum of 2 numbers

```
#include <stdio.h>
```

```
/* weighted sum 2 integers */
```

```
main() {
```

```
    int mathMarks = 98;
```

```
    int phyMarks = 99;
```

```
    float total;          /* float variable */
```

```
    total = (30/100)*mathMarks + (70/100)*phyMarks;
```

```
    printf("%f\n", total); /* change here */
```

```
}
```

Weighted sum of 2 numbers

```
#include <stdio.h>

/* weighted sum 2 integers */

main() {
    int mathMarks = 98;
    int phyMarks = 99;
    float total;          /* float variable */

    total = (30/100)*mathMarks + (70/100)*phyMarks;
    printf("%f\n", total); /* change here */
}
```

-
- What is the output of the program?

Weighted sum of 2 numbers

```
#include <stdio.h>

/* weighted sum 2 integers */

main() {
    int mathMarks = 98;
    int phyMarks = 99;
    float total;          /* float variable */

    total = (30/100)*mathMarks + (70/100)*phyMarks;
    printf("%f\n", total); /* change here */
}
```

-
- What is the output of the program?
 - $\frac{30}{100}$ and $\frac{70}{100}$ evaluate to 0 and therefore total is zero.

Weighted sum of 2 numbers – a correct program

```
#include <stdio.h>

/* weighted sum 2 integers */

main() {
    int mathMarks = 98;
    int phyMarks = 99;
    float total;

    total = (30.0/100)*mathMarks + (70.0/100)*phyMarks;
    printf("%f\n", total);
}
```

Weighted sum of 2 numbers – a correct program

```
#include <stdio.h>

/* weighted sum 2 integers */

main() {
    int mathMarks = 98;
    int phyMarks = 99;
    float total;

    total = (30.0/100)*mathMarks + (70.0/100)*phyMarks;
    printf("%f\n", total);
}
```

-
- What is the output of the program?

Weighted sum of 2 numbers – a correct program

```
#include <stdio.h>

/* weighted sum 2 integers */

main() {
    int mathMarks = 98;
    int phyMarks = 99;
    float total;

    total = (30.0/100)*mathMarks + (70.0/100)*phyMarks;
    printf("%f\n", total);
}
```

-
- What is the output of the program?

Learnings so far..

- C allows different kinds of variables to be declared.
- C defines arithmetic operators, like $+$, $-$, $*$, $/$,...
- Have meaningful names for variables
`mathMarks`, `phyMarks`, `total`

choose variable names to be indicative – good programming practice

avoid reserved words like `int`, `float`, .. as variable names.

Learnings so far..

- C allows different kinds of variables to be declared.
- C defines arithmetic operators, like $+$, $-$, $*$, $/$,...

- Have meaningful names for variables

`mathMarks`, `phyMarks`, `total`

choose variable names to be indicative – good programming practice

avoid reserved words like `int`, `float`, .. as variable names.

- C defines arithmetic operators, like $+$, $-$, $*$, $/$,...
- **Assignment operator** `"="`: used to change contents of a variable.

Exercise: Swap two integers

- Two integers x and y contain 10 and 20 respec.
- Need to exchange values in x and y .
`swap two integers`.
- Write a C program to do the same.

Swap – fill in correct code

```
#include<stdio.h>

main() {
    int x, y;

    printf("Enter x:");
    scanf("%d", &x);
    printf("Enter y:");
    scanf("%d", &y);

    /* Fill in code here */

    printf("x = %d\n", x);
    printf("y = %d\n", y);
}
```

Variable modification

- A C program is a sequence of commands that modify different variables using different operators.
- Basic operators in C.
 - Operator precedence and associativity.
- Basic data types in C.
 - How much space does a particular data type take?
 - How to input and output variables of a particular type?

Basic operators in C

- Arithmetic operators: $+$, $-$, $*$, $/$

Basic operators in C

- Arithmetic operators: `+`, `-`, `*`, `/`
- Modulus operator: `%`
`x % y` : remainder when `x` is divided by `y`.

Basic operators in C

- Arithmetic operators: $+$, $-$, $*$, $/$
- Modulus operator: $\%$
 $x \% y$: remainder when x is divided by y .
- Assignment operator: $=$

Basic operators in C

- Arithmetic operators: `+`, `-`, `*`, `/`
 - Modulus operator: `%`
`x % y` : remainder when `x` is divided by `y`.
 - Assignment operator: `=`
-

Operator precedence:

- **first:** parenthesized sub-expression; inner-most to outer-most.
- **second:** `*`, `/`, `%` ; left to right.
- **third:** `+`, `-` ; left to right.

Basic operators in C

- Arithmetic operators: `+`, `-`, `*`, `/`
 - Modulus operator: `%`
`x % y` : remainder when `x` is divided by `y`.
 - Assignment operator: `=`
-

Operator precedence:

- **first:** parenthesized sub-expression; inner-most to outer-most.
- **second:** `*`, `/`, `%` ; left to right.
- **third:** `+`, `-` ; left to right.
- `total = 30 / 100 * mathMarks + 70 / 100 * phyMarks;`

Basic operators in C

- Arithmetic operators: `+`, `-`, `*`, `/`
 - Modulus operator: `%`
`x % y` : remainder when `x` is divided by `y`.
 - Assignment operator: `=`
-

Operator precedence:

- **first:** parenthesized sub-expression; inner-most to outer-most.
- **second:** `*`, `/`, `%` ; left to right.
- **third:** `+`, `-` ; left to right.
- `total = 30 / 100 * mathMarks + 70 / 100 * phyMarks;`

`total = ((30 / 100) * mathMarks) + ((70 / 100) * phyMarks);`

Basic operators in C

- Arithmetic operators: $+$, $-$, $*$, $/$
 - Modulus operator: $\%$
 $x \% y$: remainder when x is divided by y .
 - Assignment operator: $=$
-

Operator precedence:

- **first:** parenthesized sub-expression; inner-most to outer-most.
- **second:** $*$, $/$, $\%$; left to right.
- **third:** $+$, $-$; left to right.
- $\text{total} = 30 / 100 * \text{mathMarks} + 70 / 100 * \text{phyMarks};$
 $\text{total} = ((30 / 100) * \text{mathMarks}) + ((70 / 100) * \text{phyMarks});$
- $z = a + b * c * d \% e - f / g$

Basic operators in C

- Arithmetic operators: $+$, $-$, $*$, $/$
 - Modulus operator: $\%$
 $x \% y$: remainder when x is divided by y .
 - Assignment operator: $=$
-

Operator precedence:

- **first:** parenthesized sub-expression; inner-most to outer-most.
- **second:** $*$, $/$, $\%$; left to right.
- **third:** $+$, $-$; left to right.
- $\text{total} = 30 / 100 * \text{mathMarks} + 70 / 100 * \text{phyMarks};$
 $\text{total} = ((30 / 100) * \text{mathMarks}) + ((70 / 100) * \text{phyMarks});$
- $z = a + b * c * d \% e - f / g$
 $z = a + (((b * c) * d) \% e) - (f / g)$

Increment / decrement operators

- `++`, `--`
- prefix and post-fix only to a variable.

Increment / decrement operators

- ++, --
- prefix and post-fix only to a variable.

```
#include<stdio.h>
```

```
main() {
```

```
    int x, y;
```

```
    int n = 10;
```

```
    x = n++;
```

```
    y = ++n;
```

```
    printf(" x = %d, y = %d\n", x, y);
```

```
}
```

Assignment operator =

Form: variable-name = expression

- $z = x + y$
- $x + y = z$ Incorrect form

Assignment operator =

Form: variable-name = expression

- $z = x + y$
- $x + y = z$ **Incorrect form**
- Assignment between different data types.
 - What happens if you assign float to int and vice versa?

Assignment operator =

Form: variable-name = expression

- $z = x + y$
- $x + y = z$ **Incorrect form**
- Assignment between different data types.
 - What happens if you assign float to int and vice versa?
- Multiple assignments.
 - $x = y = z = (a + b);$
 - evaluations happen right to left.

Assignment operator =

Form: variable-name = expression

- $z = x + y$
- $x + y = z$ **Incorrect form**
- Assignment between different data types.
 - What happens if you assign float to int and vice versa?
- Multiple assignments.
 - $x = y = z = (a + b);$
 - evaluations happen right to left.
- $x = x + 10$ can be written as $x += 10;$
- instead of $+$, we can also have $-$, $*$, $/$, $\%$

Exercises

Write a program that reads an integer from the input and prints 0 if the integer is even and 1 if the integer is odd.

Write a program that takes as input a 3 digit integer, separates the digits of the integer and prints the individual digits separated by spaces.

For example if the input is 194, then your program must print
1 9 4

Integers in C and Storage

- We have used **int** and **float** data types till now.

Integers in C and Storage

- We have used **int** and **float** data types till now.
- An integer variable is assigned 2 bytes (16 bits) to be stored. (Sometimes 4 bytes).

Integers in C and Storage

- We have used **int** and **float** data types till now.
- An integer variable is assigned 2 bytes (16 bits) to be stored. (Sometimes 4 bytes).
- In the 2s complement form this allows storage of values from

$$-2^{15} \text{ to } 2^{15} - 1$$

Integers in C and Storage

- We have used **int** and **float** data types till now.
- An integer variable is assigned 2 bytes (16 bits) to be stored. (Sometimes 4 bytes).
- In the 2s complement form this allows storage of values from

$$-2^{15} \text{ to } 2^{15} - 1$$

$$-32,768 \text{ to } 32,767$$

- There are limits to representation - we better choose the right type.

Integers in C and Storage

- We have used **int** and **float** data types till now.
- An integer variable is assigned 2 bytes (16 bits) to be stored. (Sometimes 4 bytes).
- In the 2s complement form this allows storage of values from

$$-2^{15} \text{ to } 2^{15} - 1$$

$$-32,768 \text{ to } 32,767$$

- There are limits to representation - we better choose the right type.
- What other data type can we use to store integers?

Integers in C and Storage

- We have used **int** and **float** data types till now.
- An integer variable is assigned 2 bytes (16 bits) to be stored. (Sometimes 4 bytes).
- In the 2s complement form this allows storage of values from

$$-2^{15} \text{ to } 2^{15} - 1$$

$$-32,768 \text{ to } 32,767$$

- There are limits to representation - we better choose the right type.
- What other data type can we use to store integers?
- **unsigned int, long, unsigned long.**

unsigned int

- Typically 4 bytes storage.
- Output an unsigned int: `printf("%u", x);`
- Input an unsigned int: `scanf("%u", &x);`
- Storage: binary format.

The Integers - The detailed Chart

int	2 or 4 bytes	-32,768 to 32,767 or -2,147,483,648 to 2,147,483,647
unsigned int	2 or 4 bytes	0 to 65,535 or 0 to 4,294,967,295
short	2 bytes	-32,768 to 32,767
unsigned short	2 bytes	0 to 65,535
long	4 bytes	-2,147,483,648 to 2,147,483,647
unsigned long	4 bytes	0 to 4,294,967,295

char

- Typically 1 byte storage.
- Every character has a unique code assigned to it (ASCII code).
A = 65, B = 66

char

- Typically 1 byte storage.
- Every character has a unique code assigned to it (ASCII code).
A = 65, B = 66
- Output a character: `printf("%c", x);`
- Input a character: `scanf("%c", &x);`

float

- Typically 4 bytes storage.
- Output a float: `printf("%f ", x);`
- Input a float: `scanf("%f ", &x);`
- How are fractions stored?

Binary vs decimal fractions

- $(10.11)_2 = (1 \times 2) + (0 \times 1) + (1 \times \frac{1}{2}) + (1 \times \frac{1}{2^2}) = (2.75)_{10}$

Binary vs decimal fractions

- $(10.11)_2 = (1 \times 2) + (0 \times 1) + (1 \times \frac{1}{2}) + (1 \times \frac{1}{2^2}) = (2.75)_{10}$
- $(0.90625)_{10} = (\quad)_2$
- $(0.9)_{10} = (\quad)_2$

Decimal Fraction $\rightarrow$ Binary Fraction (1)

Convert $(0.90625)_{10}$ to binary fraction

0.90625			
$\times 2$			
1	0.8125	+ integer part	
$\times 2$			
1	0.625	+ integer part	
$\times 2$			
1	0.25	+ integer part	
$\times 2$			
1	0.5	+ integer part	
$\times 2$			
0			
	0	+ integer part 1	

$$\begin{aligned} 0.90625 &= \frac{1}{2}(1+0.8125) \\ &= \frac{1}{2}(1+\frac{1}{2}(1+0.625)) \\ &= \frac{1}{2}(1+\frac{1}{2}(1+\frac{1}{2}(1+0.25))) \\ &= \frac{1}{2}(1+\frac{1}{2}(1+\frac{1}{2}(1+\frac{1}{2}(0+0.5)))) \\ &= \frac{1}{2}(1+\frac{1}{2}(1+\frac{1}{2}(1+\frac{1}{2}(0+\frac{1}{2}(1+0.0))))) \\ &= \frac{1}{2}+1/2^2+1/2^3+0/2^4+1/2^5 \\ &= (0.11101)_2 \end{aligned}$$

Thus, $(0.90625)_{10} = (0.11101)_2$

Decimal Fraction $\rightarrow$ Binary Fraction (2)

Convert $(0.9)_{10}$ to binary fraction

$$\begin{array}{rcl} 0.9 & & \\ \times 2 & & \\ \hline 0.8 & + \text{integer part } 1 & \\ \times 2 & & \\ \hline 0.6 & + \text{integer part } 1 & \\ \times 2 & & \\ \hline 0.2 & + \text{integer part } 1 & \\ \times 2 & & \\ \hline 0.4 & + \text{integer part } 0 & \\ \times 2 & & \\ \hline 0.8 & + \text{integer part } 0 & \end{array}$$

For some fractions, we do not get 0.0 at any stage!

These fractions require an infinite number of bits!

Cannot be represented exactly!

Repetition

$$(0.9)_{10} = 0.1\textcolor{red}{1}1001100\textcolor{red}{1}1001100 \dots = 0.\overline{11100}$$

Binary vs decimal fractions

- $(10.11)_2 = (1 \times 2^1) + (0 \times 2^0) + (1 \times \frac{1}{2}) + (1 \times \frac{1}{2^2}) = (2.75)_{10}$
- $(0.90625)_{10} = (0.11101)_2$
- $(0.9)_{10} = (0.111001110011100\dots)_2$

Fixed point vs floating point representation

Fixed point

- Position of radix point is fixed and is same for all numbers.
- Lets say we have 3 digits after radix point.

Fixed point vs floating point representation

Fixed point

- Position of radix point is fixed and is same for all numbers.
- Lets say we have 3 digits after radix point.
- $(0.120 \times 0.120)_{10} = (0.014)_{10}$
- A digit is lost.

Floating point

Fixed point vs floating point representation

Fixed point

- Position of radix point is fixed and is same for all numbers.
 - Lets say we have 3 digits after radix point.
 - $(0.120 \times 0.120)_{10} = (0.014)_{10}$
 - A digit is lost.
-

Floating point

- $1.20 \times (10)^{-1} \times 1.20 \times (10)^{-1} = 1.44 \times (10)^{-2}$
- Wider range of numbers can be represented.
- IEEE standard: 32 bits are split as follows:
 - First bit for sign.
 - Next 8 bits for exponent.
 - Next 23 bits for mantissa.

Fixed point vs floating point representation

Fixed point

- Position of radix point is fixed and is same for all numbers.
 - Lets say we have 3 digits after radix point.
 - $(0.120 \times 0.120)_{10} = (0.014)_{10}$
 - A digit is lost.
-

Floating point

- $1.20 \times (10)^{-1} \times 1.20 \times (10)^{-1} = 1.44 \times (10)^{-2}$
- Wider range of numbers can be represented.
- IEEE standard: 32 bits are split as follows:
 - First bit for sign.
 - Next 8 bits for exponent.
 - Next 23 bits for mantissa.
 - $(-39.9)_{10} = (-100111.11100)_2 = (-1.0011111100)_2 \times 2^5$.

Floats - different types

Type	Storage size	Value range
float	4 byte	1.2E-38 to 3.4E+38
double	8 byte	2.3E-308 to 1.7E+308
long double	10 byte	3.4E-4932 to 1.1E+4932

Output floats in C

```
printf( " %w.p f ", x);
```

- w.p is optional.
- w : total width of the field.
- p : precision (digits after decimal).

Output floats in C

```
printf(" %w.p f ", x);
```

- w.p is optional.
- w : total width of the field.
- p : precision (digits after decimal).

```
#include<stdio.h>
```

```
main() {
```

```
    float x = 2.00123;
```

```
    printf ("x = %5.4f\n", x);
```

```
    printf ("x = %8.7f\n", x);
```

```
}
```

Circumference of circle

```
#include<stdio.h>

main() {
    float radius;
    float circum;

    printf("Enter radius : ");
    scanf("%f", &radius);
    circum = 2* (22.0/7) * radius;

    printf ("radius = %f, circum = %f\n", radius, circum);
}
```

Circumference of circle

```
#include<stdio.h>

main() {
    float radius;
    float circum;

    printf("Enter radius : ");
    scanf("%f", &radius);
    circum = 2* (22.0/7) * radius;

    printf ("radius = %f, circum = %f\n", radius, circum);
}
```

- How to print output only upto 2 decimals?

Circumference of circle – formatted output

```
#include<stdio.h>
```

```
main() {
```

```
    float radius;
```

```
    float circum;
```

```
    printf("Enter radius : ");
```

```
    scanf("%f", &radius);
```

```
    circum = 2* (22.0/7) * radius;
```

```
    printf ("radius = %5.2f, circum = %5.2f\n", radius, circum);
```

```
}
```

Output statement

```
printf (format-string,  $var_1$ ,  $var_2$ , ...,  $var_n$ )
```

Output statement

```
printf (format-string, var1, var2, ..., varn)
```

Format string specifies

- How many variables to expect?
- Type of each variable.
- How many columns to use for printing? (width)
- What is the precision? (if applicable)

Output statement

```
printf (format-string, var1, var2, ..., varn)
```

Format string specifies

- How many variables to expect?
- Type of each variable.
- How many columns to use for printing? (width)
- What is the precision? (if applicable)
- **Common mistakes:**
 - comma missing after the double quotes.
 - mismatch in the actual number of variables given and those expected in the format string.

Formatted output

```
printf ("%w.pC", x);
```

Formatted output

```
printf ( "%w.pC", x );
```

-
- **w**, **p** and **C** are place holders, can take different values.
 - **w**: width of the output. (optional)
 - **p**: precision of the output. (optional)
 - **C**: Conversion character.

Formatted output

```
printf ( "%w.pC", x );
```

-
- **w**, **p** and **C** are place holders, can take different values.
 - **w**: width of the output. (optional)
 - **p**: precision of the output. (optional)
 - **C**: Conversion character.
 - d : integer
 - f : float
 - c : character
 - x : hexadecimal
 - o : octal
 - u : unsigned int
 - e : real decimal in exponent form

Input Statement

```
scanf (format-string, &var1, &var2, ..., &varn)
```


Input Statement

```
scanf (format-string, &var1, &var2, ..., &varn)
```

Format string specifies

- How many variables to expect?
- Type of each variable.

Input Statement

```
scanf (format-string, &var1, &var2, ..., &varn)
```

Format string specifies

- How many variables to expect?
- Type of each variable.
- **Common mistakes:**
 - comma missing after the double quotes.
 - mismatch in the actual number of variables given and those expected in the format string.
 - **& missing before the variable.**

Learnings so far..

- Variables in C.

Learnings so far..

- Variables in C.
- Data types in C - how they are stored. Why a programmer should be worried.

Learnings so far..

- Variables in C.
- Data types in C - how they are stored. Why a programmer should be worried.
- Arithmetic operators. Precedence of operators.

Learnings so far..

- Variables in C.
- Data types in C - how they are stored. Why a programmer should be worried.
- Arithmetic operators. Precedence of operators.
- Assignment operator “=”

Learnings so far..

- Variables in C.
- Data types in C - how they are stored. Why a programmer should be worried.
- Arithmetic operators. Precedence of operators.
- Assignment operator “=”
- Formatting the input and output - the `printf` and `scanf`

Learnings so far..

- Variables in C.
- Data types in C - how they are stored. Why a programmer should be worried.
- Arithmetic operators. Precedence of operators.
- Assignment operator “=”
- Formatting the input and output - the `printf` and `scanf`
- What is coming up?
 - Compilation and Execution of C-programs.
 - More Programming.